



(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 54

(51) Int Cl.:
D04B 1/12 (2006.01) D04B 1/22 (2006.01)

(48) Corrigendum issued on:
08.12.2021 Bulletin 2021/49

(43) Date of publication:
09.12.2020 Bulletin 2020/50

(21) Application number: **20169478.3**

(22) Date of filing: **25.09.2015**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(30) Priority: **30.09.2014 US 201462057650 P**
30.09.2014 US 201462057264 P
07.11.2014 US 201414535413
07.11.2014 US 201414535648

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
15778156.8 / 3 200 641

(71) Applicant: **NIKE Innovate C.V.**
Beaverton, OR 97005-6453 (US)

(72) Inventors:
• **LILES, Timothy K.**
Beaverton, OR 97005 (US)

- **HENRICHOT, Oliver**
Beaverton, OR 97005 (US)
- **KLUG, Bryant Russel**
Beaverton, OR 97005 (US)
- **SCHULTZE, Nathan G.**
Beaverton, OR 97005 (US)
- **MEIR, Adrian**
Beaverton, OR 97005 (US)
- **LANGVIN, Elizabeth**
Beaverton, OR 97005 (US)

(74) Representative: **Prinz & Partner mbB**
Patent- und Rechtsanwälte
Rundfunkplatz 2
80335 München (DE)

Remarks:

This application was filed on 14.04.2020 as a divisional application to the application mentioned under INID code 62.

(54) **UPPER COMPRISING KNITTED COMPONENT WITH INLAID TENSILE ELEMENTS**

(57) An article of footwear includes a textile component. The textile component of the upper includes a textile element and a tensile element. The tensile element defines a first segment disposed on a first side of the upper. The first segment of the tensile element is configured to attach the securement device to the textile element on the first side of the upper. The tensile element further includes a second segment that is disposed proximate the lower portion of the upper on the second side. The second segment is fixed relative to the lower portion of the upper on the second side. The tensile element further includes an intermediate segment that extends continuously from the first segment, across the heel region, to the second segment.

