## 

## (11) **EP 3 763 601 A8**

## (12) CORRECTED EUROPEAN PATENT APPLICATION

published in accordance with Art. 153(4) EPC

(15) Correction information:

Corrected version no 2 (W2 A1) Corrections, see Abstract

(48) Corrigendum issued on: 13.10.2021 Bulletin 2021/41

(43) Date of publication: 13.01.2021 Bulletin 2021/02

(21) Application number: 18908569.9

(22) Date of filing: 27.09.2018

(51) Int Cl.:

 B62D 5/22 (2006.01)
 B62D 61/06 (2006.01)

 B62K 5/10 (2013.01)
 B62D 5/10 (2006.01)

 F16H 55/22 (2006.01)
 F16H 25/22 (2006.01)

 B60G 17/016 (2006.01)
 B60G 17/015 (2006.01)

(86) International application number:

PCT/KR2018/011442

(87) International publication number: WO 2019/172496 (12.09.2019 Gazette 2019/37)

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(30) Priority: 06.03.2018 KR 20180026342 20.08.2018 KR 20180096466

(71) Applicant: Daepoong Ev Motors Co., Ltd Jeollanam-do 59554 (KR)


(72) Inventor: YU, Je Woo Chungcheongnam-do 31009 (KR)

(74) Representative: Clarenbach, Carl-Philipp et al Gleiss Große Schrell und Partner mbB Patentanwälte Rechtsanwälte Leitzstraße 45 70469 Stuttgart (DE)

## (54) TILTING CAR FRAME

(57)The technology disclosed in the present specification may comprise: a lower center frame comprising first and second support members which extend from first and second ends thereof, respectively; first and second horizontal linking members which are hinge-connected to the first and second ends, respectively; first and second vertical linking members which are hinge-connected to the first and second horizontal linking members, respectively; a rotating central shaft support which extends from the lower center frame; a first length-variable lever linking member which is hinge-connected to the first vertical linking member and the first support member, and to the end of which a first length-variable linking member is connected; a second length-variable lever linking member which is hinge-connected to the second vertical linking member and the second support member, and a rotor which is connected to the rotating central shaft support, and in which first and second extending members are hinge-connected to the first and second length-variable linking members, respectively.

FIG. 1



EP 3 763 601 A8