



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**14.04.2021 Bulletin 2021/15**

(51) Int Cl.:  
**H04N 19/196 (2014.01) H04N 19/46 (2014.01)**  
**H04N 19/436 (2014.01) H04N 19/91 (2014.01)**

(21) Application number: **20205787.3**

(22) Date of filing: **05.11.2012**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**

(72) Inventor: **OKAWA, Koji**  
**Ohta-ku, Tokyo 146-8501 (JP)**

(30) Priority: **07.11.2011 JP 2011243940**

(74) Representative: **Canon Europe Limited**  
**European Intellectual Property Group**  
**3 The Square, Stockley Park**  
**Uxbridge UB11 1ET (GB)**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
**19151520.4 / 3 499 893**  
**12801780.3 / 2 777 275**

Remarks:  
This application was filed on 04-11-2020 as a divisional application to the application mentioned under INID code 62.


(71) Applicant: **CANON KABUSHIKI KAISHA**  
**OHTA-KU**  
**Tokyo 146-8501 (JP)**

(54) **IMAGE CODING APPARATUS, IMAGE CODING METHOD, IMAGE DECODING APPARATUS, IMAGE DECODING METHOD, AND PROGRAM**

(57) An image coding apparatus configured to divide an image into one or more slices each including a plurality of blocks and to code each slice on a block-by-block basis includes a first coding unit configured to code blocks included in a first portion of the slice, and a second coding unit configured to code blocks included in a second portion of the slice, wherein, when the second coding unit

codes an initial block in the second portion, the second coding unit codes the initial included in the second portion by referring to a first quantization parameter provided to the slice as an initial value and referred to by the first coding unit when the first coding units codes the initial block in the first portion.

**FIG.1**



## Description

[Technical Field]

**[0001]** The present invention relates to an image coding apparatus, an image coding method, an image decoding apparatus, an image decoding method, and a program, and in particular, to a method for coding/decoding a quantization parameter in an image.

[Background Art]

**[0002]** H.264/ MPEG-4 AVC (hereinafter referred to as "H.264") is known as a coding method for use in compressing and recording a moving image (ITU-T H.264 (03/2010), Advanced video coding for generic audiovisual services). According to H.264, a difference in a quantization parameter from a block coded immediately before the current block is coded as mb\_qp\_delta information, whereby a quantization parameter of each block can be an arbitrary value.

**[0003]** Then, it is coded using a conventional binary arithmetic coding method adopted in H. 264. More specifically, each syntax element such as the above-described mb\_qp\_delta information is binarized, as a result of which a binary signal is generated. An occurrence probability is assigned to each syntax element in advance as a table (hereinafter referred to as an "occurrence probability table"). The above-described binary signal is arithmetically coded based on the occurrence probability table. Then, each time a binary signal is coded, the occurrence probability table is updated based on statistical information indicating whether the coded binary signal is the most probable symbol.

**[0004]** In recent years, an activity to standardize a further highly efficient coding technology as a successor of H.264 has started, and Joint Collaborative Team on Video Coding (JCT-VC) was established between ISO/IEC, and ITU-T. JCT-VC has been standardized a coding technology called High Efficiency Video Coding (hereinafter referred to as "HEVC").

**[0005]** In the standardization of HEVC, various kinds of coding methods have been widely considered in terms of not only improvement of coding efficiency but also other aspects including simplicity of implementation and a reduction in a processing time. To reduce a processing time, methods for improving parallelism have been also considered assuming that the coding method is used on, for example, a multi-core CPU. One of them is a method for realizing parallel processing of entropy coding/decoding called "Wavefront" (JCT-VC contribution, JCTV-F274.doc available on the Internet at <[http://phenix.int-evry.fr/jct/doc\\_end\\_user/documents/6\\_Torino/wg11/](http://phenix.int-evry.fr/jct/doc_end_user/documents/6_Torino/wg11/)>). A next coding target should be coded using an updated occurrence probability table, so the processing cannot be performed in parallel unless the statistical information is reset. However, this leads to such a problem that resetting the statistical information deteriorates the coding

efficiency. In contrast, Wavefront makes it possible to code blocks line by line in parallel, while preventing the coding efficiency deterioration, by applying an occurrence probability table obtained at the time of completion of coding a plural pre-specified number of blocks to the leftmost block in the next line. This is mainly a description of encoding process, but it is also applicable to decoding process.

**[0006]** However, Wavefront makes it possible to improve parallelism of arithmetic coding/decoding of each line, but actually, quantization and inverse quantization cannot be performed until the quantization parameter of the immediately preceding block in raster scan is determined. Therefore, even the current implementation of Wavefront has a problem of inability to perform entire coding/decoding processing in parallel.

[Summary of Invention]

**[0007]** The present invention is directed to enabling parallel coding/decoding as entire processing including quantization/inverse quantization processing when blocks are coded/decoded line by line in parallel with the use of the Wavefront method.

**[0008]** According to an aspect of the present invention, an image coding apparatus configured to divide an image into one or more slices each including a plurality of blocks and to code each slice on a block-by-block basis includes first coding means configured to code blocks included in a first portion of the slice, and second coding means configured to code blocks included in a second portion of the slice, wherein, when the second coding means codes the initial block in the second portion, the second coding means codes the initial block included in the second portion by referring to a first quantization parameter provided to the slice as an initial value and referred to by the first coding means when the first coding means codes the initial block in the first portion.

**[0009]** According to exemplary embodiments of the present invention, it is possible to realize parallel coding/decoding as entire processing including quantization/inverse quantization processing when blocks are coded/decoded line by line in parallel with use of the Wavefront method.

**[0010]** Further features and aspects of the present invention will become apparent from the following detailed description of exemplary embodiments with reference to the attached drawings.

[Brief Description of Drawings]

**[0011]** The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate exemplary embodiments, features, and aspects of the invention and, together with the description, serve to explain the principles of the invention.

[Fig. 1] Fig. 1 is a block diagram illustrating a config-

uration of an image coding apparatus according to a first exemplary embodiment.

[Fig. 2] Fig. 2 illustrates configurations of block lines.

[Fig. 3] Fig. 3 is a flowchart illustrating processing for coding a frame by the image coding apparatus according to the first exemplary embodiment.

[Fig. 4] Fig. 4 is a flowchart illustrating processing for coding a top block line by the image coding apparatus according to the first exemplary embodiment.

[Fig. 5] Fig. 5 is a flowchart illustrating processing for coding a block line other than the top block line by the image coding apparatus according to the first exemplary embodiment.

[Fig. 6] Fig. 6 is a flowchart illustrating processing for coding a block by the image coding apparatus according to the first exemplary embodiment.

[Fig. 7A] Fig. 7A illustrates a transfer of a quantization parameter by the conventional image coding apparatus.

[Fig. 7B] Fig. 7B illustrates a transfer of a quantization parameter by the image coding apparatus according to the first exemplary embodiment.

[Fig. 8] Fig. 8 is a block diagram illustrating a configuration of an image decoding apparatus according to a second exemplary embodiment.

[Fig. 9] Fig. 9 is a flowchart illustrating processing for decoding a frame by the image decoding apparatus according to the second exemplary embodiment.

[Fig. 10] Fig. 10 is a flowchart illustrating processing for decoding a top block line by the image decoding apparatus according to the second exemplary embodiment.

[Fig. 11] Fig. 11 is a flowchart illustrating processing for decoding a block line other than the top block line by the image decoding apparatus according to the second exemplary embodiment.

[Fig. 12] Fig. 12 is a flowchart illustrating processing for decoding a block by the image decoding apparatus according to the second exemplary embodiment.

[Fig. 13] Fig. 13 is a block diagram illustrating an example of a hardware configuration of a computer employable as the image coding apparatuses and image decoding apparatuses according to the exemplary embodiments of the present invention.

[Fig. 14] Fig. 14 is a block diagram illustrating a configuration of an image coding apparatus according to a third exemplary embodiment.

[Fig. 15] Fig. 15 is a flowchart illustrating processing for coding a top block line by the image coding apparatus according to the third exemplary embodiment.

[Fig. 16] Fig. 16 is a flowchart illustrating processing for coding a block line other than the top block line by the image coding apparatus according to the third exemplary embodiment.

[Fig. 17A] Fig. 17A illustrates a transfer of a quantization parameter by the image coding apparatus according to the third exemplary embodiment.

[Fig. 17B] Fig. 17B illustrates a transfer of a quantization parameter by the image coding apparatus according to the third exemplary embodiment.

[Fig. 18] Fig. 18 is a block diagram illustrating a configuration of an image decoding apparatus according to a fourth exemplary embodiment.

[Fig. 19] Fig. 19 is a flowchart illustrating processing for decoding a top block line by the image decoding apparatus according to the fourth exemplary embodiment.

[Fig. 20] Fig. 20 is a flowchart illustrating processing for decoding a block line other than the top block line by the image decoding apparatus according to the fourth exemplary embodiment.

[Fig. 21] Fig. 21 is a block diagram illustrating a configuration of an image coding apparatus according to a fifth exemplary embodiment.

[Fig. 22] Fig. 22 is a flowchart illustrating processing for coding a top block line according to the fifth exemplary embodiment.

[Fig. 23] Fig. 23 is a flowchart illustrating processing for coding a block line other than the top block line according to the fifth exemplary embodiment.

[Fig. 24] Fig. 24 is a block diagram illustrating a configuration of an image decoding apparatus according to a sixth exemplary embodiment.

[Fig. 25] Fig. 25 is a flowchart illustrating processing for decoding a top block line according to the sixth exemplary embodiment.

[Fig. 26] Fig. 26 is a flowchart illustrating processing for decoding a block line other than the top block line according to the sixth exemplary embodiment.

#### [Description of Embodiments]

**[0012]** Various exemplary embodiments, features, and aspects of the invention will be described in detail below with reference to the drawings.

**[0013]** Fig. 1 is a block diagram illustrating an image coding apparatus according to a first exemplary embodiment.

**[0014]** Referring to Fig. 1, a selector 101 determines whether a processing target block belongs to an even-numbered block line. The selector 101 outputs the block to a first coding unit 102 if the block belongs to an even-numbered block line, and otherwise outputs the block to a second coding unit 103.

**[0015]** The first and second coding units 102 and 103 code blocks, into which an input image is divided by  $n \times n$  pixels ("n" is a positive integer of 2 or larger), line by line as illustrated in Fig. 2 (the units corresponding to "first coding means" and "second coding means", and "coding blocks included in a first portion of the slice" and "coding blocks included in a second portion of the slice" in the claims). Hereinafter, a line of blocks will be referred

to as a "block line". The present exemplary embodiment will be described based on an example using two coding units, but the present invention is not limited thereto. Referring to Fig. 2, a section 201 indicated as a square drawn by a thin line represents a block, and a section 202 indicated as a rectangle drawn by a thick line represents a block line. Further, blocks in white areas, which indicate even-numbered block lines including a top block line (the 0-th block line), are coded by the first coding unit 102. Blocks in shaded areas, which indicate odd-numbered block lines, are coded by the second coding unit 103.

**[0016]** Each of the first and second coding units 102 and 103 first generates prediction errors according to the prediction by referring to pixels surrounding the coding target block or another frame, and performs orthogonal transform to generate transform coefficients. Next, each of the first and second coding units 102 and 103 determines a quantization parameter for the orthogonally transformed transform coefficients, and quantizes each transform coefficient to generate quantization coefficients. Next, each of the first and second coding units 102 and 103 binarizes each syntax element including the quantization coefficients to generate binary signals. An occurrence probability is assigned to each syntax element in advance as a table (hereinafter referred to as an "occurrence probability table"). The binary signals are arithmetically coded based on the above-described occurrence probability table. Then, each time a binary signal is coded, the occurrence probability table is updated using statistical information indicating whether the coded binary signal is the most probable symbol.

**[0017]** A first occurrence probability table storage unit 104 stores the occurrence probability table generated by the first coding unit 102. Hereinafter, the occurrence probability table stored in the first occurrence probability table storage unit 104 will be referred to as a "first occurrence probability table".

**[0018]** A first quantization parameter storage unit 105 stores the quantization parameter determined by the first coding unit 102. Hereinafter, the quantization parameter stored in the first quantization parameter storage unit 105 will be referred to as a "first quantization parameter".

**[0019]** A second occurrence probability table storage unit 106 stores the occurrence probability table generated by the second coding unit 103. Hereinafter, the occurrence probability table stored in the second occurrence probability table storage unit 106 will be referred to as a "second occurrence probability table".

**[0020]** A second quantization parameter storage unit 107 stores the quantization parameter determined by the second coding unit 103. Hereinafter, the quantization parameter stored in the second quantization parameter storage unit 107 will be referred to as a "second quantization parameter".

**[0021]** An integration coding unit 108 integrates coded data generated by the first coding unit 102 and coded data generated by the second coding unit 103, and out-

puts the integrated data as a bit stream.

**[0022]** An operation of the image coding apparatus according to the present exemplary embodiment will be described in detail with reference to the flowcharts illustrated in Figs. 3 to 6. In the present exemplary embodiment, moving image data is input frame by frame, is divided into blocks, and is processed in raster order. The present exemplary embodiment is configured to input moving image data frame by frame, but may be configured to input still image data corresponding to one frame or to input image data slice by slice, which a frame is divided into. Further, for simplification of description, the present exemplary embodiment will be described based on only intra prediction coding processing, but is not limited thereto. The present exemplary embodiment can be also employed to inter prediction coding processing.

**[0023]** First, in step S301, the image coding apparatus determines whether a processing target block belongs to a top block line. If the block belongs to the top block line (YES in step S301), the processing proceeds to step S302. If the block does not belong to the top block line (NO in step S301), the processing proceeds to step S303.

**[0024]** The processing of step S302 is processing for coding the top block line, the details of which will be described below. The processing of step S303 is processing for coding a block line other than the top block line, the details of which will be also described below. Further, the selector 101 determines whether the block line to which the processing target block belongs is an even-numbered block line or an odd-numbered block line. If the block line is an even-numbered block line, the processing target block is coded by the first coding unit 102 independently. If the block line is not an even-numbered block line, the processing target block is coded by the second coding unit 103 independently.

**[0025]** Next, in step S304, the integration coding unit 108 integrates coded data output from the first coding unit 102 and coded data output from the second coding unit 103, and generates and outputs a bit stream.

**[0026]** Next, in step S305, the image coding apparatus determines whether all block lines in the processing target frame are coded. If all block lines are coded (YES in step S305), the processing for coding one frame is ended. If not all block lines are coded (NO in step S305), the processing proceeds to step S301 again, and coding of the next block line starts.

**[0027]** The processing of step S302 (the processing for coding the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 4. The top block line is an even-numbered block line, so the processing target block is input into the first coding unit 102 by the selector 101, and is coded by the first coding unit 102.

**[0028]** First, in step S401, a quantization parameter, based on which a block is coded, is initialized so as to match an initial value of a quantization parameter for a slice. Hereinafter, the quantization parameter, based on which a block is coded, will be referred to as a "block

reference quantization parameter". Regarding a quantization parameter used to quantize a coding target block, the value thereof itself is not coded as a syntax element, but a difference value thereof from the block reference quantization parameter is coded. In the present exemplary embodiment, this difference value corresponds to a value of `cu_qp_delta` in the HEVC method. However, the present invention is not limited thereto, and for example, the above-described difference value may correspond to a code of `mb_qp_delta` in the H.264 method. Next, in step S402, an occurrence probability table is initialized by a predetermined method. The initialized occurrence probability table is used to arithmetically code the first binary signal of the leftmost block in the block line, and is updated as necessary in step S403, which will be described below. Hereinafter, the occurrence probability table used to arithmetically code the first binary signal of the leftmost block in a block line will be referred to as a "block line reference occurrence probability table".

**[0029]** Next, in step S403, the first coding unit 102 codes pixel data block by block.

**[0030]** In the present exemplary embodiment, one block is constituted by 64 x 64 pixels, but the present invention is not limited thereto. The size of a block may be a smaller size such as 32 x 32 pixels, or a larger size such as 128 x 128 pixels. The block coding processing in step S403 will be described in detail with reference to the flowchart illustrated in Fig. 6.

**[0031]** First, in step S601, the first coding unit 102 performs intra prediction on an input image block with use of pixels surrounding the block to generate prediction errors.

**[0032]** Next, in step S602, the first coding unit 102 performs orthogonal transform on the prediction errors to generate transform coefficients. Further, the first coding unit 102 quantizes the transform coefficients using a quantization parameter (hereinafter referred to as a "block quantization parameter") determined based on, for example, the characteristics and the coding amount of the image to generate quantization coefficients.

**[0033]** Next, in step S603, the first coding unit 102 calculates a difference value between the above-described block reference quantization parameter and the block quantization parameter to generate a `cu_qp_delta` value.

**[0034]** Next, in step S604, the first coding unit 102 sets the block quantization parameter used to code the processing target block to the block reference quantization parameter, thereby updating the block reference quantization parameter. The block reference quantization parameter will be used to generate a `cu_qp_delta` value of a next block.

**[0035]** Next, in step S605, the first coding unit 102 binarizes each syntax element including the above-described `cu_qp_delta` value and the above-described quantization coefficients to generate binary signals. The first coding unit 102 uses various kinds of binarization methods such as unary binarization and fixed-length bi-

narization while switching the binarization method for each syntax element in a similar manner to the H.264 method. Further, the first coding unit 102 arithmetically codes the binary signals based on the occurrence probability table.

**[0036]** Next, in step S606, the first coding unit 102 updates the occurrence probability table based on whether the arithmetically coded binary signal is the most probable symbol.

**[0037]** Next, in step S607, the first coding unit 102 determines whether all syntax elements in the block are arithmetically coded. If all syntax elements are arithmetically coded (YES in step S607), the block coding processing is ended. If not all syntax elements are coded (NO in step S607), the processing proceeds to step S605 again.

**[0038]** Referring back to Fig. 4, in step S404, the first coding unit 102 determines whether a condition for storing the block reference quantization parameter is satisfied. In the present exemplary embodiment, the condition for storing the block reference quantization parameter is whether the block coded in step S403 is a leftmost block in a block line. If the condition is satisfied (YES in step S404), the processing proceeds to step S405. In step S405, the block reference quantization parameter is stored in the first quantization parameter storage unit 105 as a first quantization parameter. If the condition is not satisfied (NO in step S404), the processing proceeds to step S406. The first quantization parameter will be used as a block reference quantization parameter when the second coding unit 103 codes the leftmost block in the next block line.

**[0039]** Next, in step S406, the first coding unit 102 determines whether a condition for storing the occurrence probability table is satisfied. In the present exemplary embodiment, the condition for storing the occurrence probability table is whether the block coded in step S403 is a predetermined number-th block from the leftmost block in the block line. If this condition is satisfied (YES in step S406), the processing proceeds to step S407. In step S407, the occurrence probability table is stored in the first occurrence probability table storage unit 104 as a first occurrence probability table. If the condition is not satisfied (NO in step S406), the processing proceeds to step S408. The first occurrence probability table will be used as a block line reference occurrence probability table when the second coding unit 103 codes the leftmost block in the next block line.

**[0040]** Next, in step S408, the first coding unit 102 determines whether all blocks in the processing target block line are coded. If all blocks are coded (YES in step S408), coding of the top block line is ended. If not all blocks are coded (NO in step S408), the processing proceeds to step S403 again. In step S403, the next block in raster order is coded.

**[0041]** The processing of step S303 (the processing for coding a block line other than the top block line) will be described in detail with reference to the flowchart il-

illustrated in Fig. 5. The selector 101 determines for each block line whether the block line is an even-numbered block line. If the block line is an even-numbered block line, an image of the processing target block line is input into the first coding unit 102 and is coded by the first coding unit 102. If the block line is an odd-numbered block line, an image of the processing target block line is input into the second coding unit 103, and is coded by the second coding unit 103. First, a flow when the second coding unit 103 codes an odd-numbered block line will be described.

**[0042]** First, in step S501, the first quantization parameter is input from the first quantization parameter storage unit 105 as a block reference quantization parameter. Next, in step S502, the first occurrence probability table is input from the first occurrence probability table storage unit 104 as a block line reference occurrence probability table.

**[0043]** The processing of steps S503, S504, S506, and S508 is similar to the processing of steps S403, S404, S406, and S408, and, therefore, the description thereof is omitted here.

**[0044]** In step S505, the block reference quantization parameter is stored in the second quantization parameter storage unit 107 as a second quantization parameter. The second quantization parameter will be used as a block reference quantization parameter for a leftmost block in a next block line.

**[0045]** In step S507, the occurrence probability table is stored in the second occurrence probability table storage unit 106 as a second occurrence probability table. The second occurrence probability table will be used as a block line reference occurrence probability table when the leftmost block in the next block line is arithmetically coded.

**[0046]** Next, a flow when the first coding unit 102 codes an even-numbered block line will be described.

**[0047]** First, in step S501, the second quantization parameter is input from the second quantization parameter storage unit 107 as a block reference quantization parameter. Next, in step S502, the second occurrence probability table is input from the second occurrence probability table storage unit 106 as a block line reference occurrence probability table.

**[0048]** The processing of steps S503 to S508 is similar to the processing of steps S403 to S408, and, therefore, the description thereof is omitted here.

**[0049]** The above-described configuration and operation enable parallel encoding by allowing reference to the reference quantization parameter in addition to the occurrence probability table during processing of a leftmost block even before the completion of processing of a block line immediately before the block line being coded. Figs. 7A and 7B each illustrate how the block reference quantization parameter is referred to. According to the conventional technique, as illustrated in Fig. 7A, until processing of a preceding block line is completed, processing of a next block line cannot start. However,

according to the present exemplary embodiment, by making the reference to a spatially upper block possible when a leftmost block is processed, which eventually allows a reference pattern as illustrated in Fig. 7B, it becomes unnecessary to wait for the completion of the preceding block line processing.

**[0050]** Further, in the present exemplary embodiment, a quantization parameter used at a leftmost block in an immediately upper block line is used as a block reference quantization parameter when a leftmost block is coded. However, the present invention is not limited thereto, and may be embodied by any configuration capable of improving parallelism of processing block line by block line. For example, an initial value of a quantization parameter provided to a slice may be used as a block reference quantization parameter when leftmost blocks in all block lines are coded. As another possible configuration, a block reference quantization parameter may be the same as the condition for storing the occurrence probability table provided in steps S406 and S506. More specifically, a quantization parameter when a predetermined number-th block from a leftmost block in a block line is coded may be used as a block reference quantization parameter for a leftmost block in a next block line. Further, the image coding apparatus may be configured to switch a block referred to as a block reference quantization parameter based on a coding mode of a leftmost block.

**[0051]** Further, in the present exemplary embodiment, arithmetic coding is used for entropy coding, but the present invention is not limited thereto. Any coding may be employed, as long as, at the time of entropy coding based on statistical information such as the occurrence probability table, the statistical information in the middle of coding of a block line is used to perform entropy coding of a leftmost block of a next block line.

**[0052]** The present exemplary embodiment has been described based on an example using two coding units. However, it is apparent that the addition of, for example, a third coding unit, a third occurrence probability table storage unit, and a third quantization parameter storage unit enables parallel processing by a larger number of coding units.

**[0053]** Fig. 8 is a block diagram illustrating an image decoding apparatus according to a second exemplary embodiment.

**[0054]** Referring to Fig. 8, a selector 801 determines whether a processing target block belongs to an even-numbered block line. The selector 801 outputs the above-described bit stream to a first decoding unit 802 if the processing target block belongs to an even-numbered block line, and otherwise outputs the above-described bit stream to a second decoding unit 803.

**[0055]** The decoding units 802 and 803 decode the input bit stream, block line by block line as illustrated in Fig. 2. The present exemplary embodiment will be described based on an example using two decoding units, but the present invention is not limited thereto. Referring to Fig. 2, the blocks in the white areas, which indicate

even-numbered block lines including the top block line (the 0-th block line), are decoded by the first decoding unit 802. The blocks in the shaded areas, which indicate odd-numbered block lines, are decoded by the second decoding unit 803.

**[0056]** Each of the first and second decoding units 802 and 803 first selects an occurrence probability table for binary signals of a bit stream to be decoded, and arithmetically decodes the binary signals based on the occurrence probability table to generate quantization coefficients. Next, each of the first and second decoding units 802 and 803 inversely quantizes the quantization coefficients based on a quantization parameter to generate transform coefficients. Then, each of the first and second decoding units 802 and 803 performs inverse orthogonal transform on the transform coefficients to generate prediction errors. Next, each of the first and second decoding units 802 and 803 performs the prediction by referring to pixels surrounding the decoding target block or to another frame to generate image data of the decoding target block. A first occurrence probability table storage unit 804 stores the occurrence probability table generated by the first decoding unit 802. A first quantization parameter storage unit 805 stores the quantization parameter determined by the first decoding unit 802.

**[0057]** A second occurrence probability table storage unit 806 stores the occurrence probability table generated by the second decoding unit 803. A second quantization parameter storage unit 807 stores the quantization parameter determined by the second decoding unit 803. An image data integration unit 808 shapes the image data generated by the first decoding unit 802 and the image data generated by the second decoding unit 803, and outputs the shaped image data.

**[0058]** An operation of the image decoding apparatus according to the present exemplary embodiment will be described in detail with reference to the flowcharts illustrated in Figs. 9 to 12. In the present exemplary embodiment, a bit stream is input frame by frame. The bit stream is divided into coded data pieces and then is decoded. The present exemplary embodiment is configured in such a manner that a bit stream is input frame by frame, but may be configured in such a manner that a frame is divided into slices, and a bit stream is input slice by slice. Further, for simplification of the description, the present exemplary embodiment will be described based on intra prediction decoding processing only, but is not limited thereto. The present exemplary embodiment can be also employed to inter prediction decoding processing.

**[0059]** First, in step S901, the image decoding apparatus determines whether a processing target block belongs to a top block line. If the processing target block belongs to the top block line (YES in step S901), the processing proceeds to step S902. If the processing target block does not belong to the top block line (NO in step S901), the processing proceeds to step S903.

**[0060]** The processing of step S902 is processing for decoding the top block line, the details of which will be

described below. The processing of step S903 is processing for decoding a block line other than the top block line, the details of which will be also described below. Further, the selector 801 determines whether the block line to which the processing target block belongs is an even-numbered block line or an odd-numbered block line. If the block line is an even-numbered block line, the processing target block is decoded by the first decoding unit 802 independently. If the block line is not an even-numbered block line, the processing target block is decoded by the second decoding unit 803 independently. In the present exemplary embodiment, the selector 801 determines whether a block line is an even-numbered block line based on the number of decoded blocks. However, the present invention is not limited thereto. For example, an input bit stream may include an identifier, which is provided at a boundary between block lines in advance, and the selector 801 may determine whether a block line is an even-numbered block line based on the identifier. Alternatively, information indicating a size of a bit stream of each block line or a starting position of a next block line may be provided, and the selector 801 may determine whether a block line is an even-numbered block line based on this information.

**[0061]** Next, in step S904, the image data integration unit 808 integrates image data output from the first decoding unit 802 and image data output from the second decoding unit 803, and generates and outputs a decoded image.

**[0062]** Next, in step S905, the image decoding apparatus determines whether all block lines in the processing target frame are decoded. If all block lines are decoded (YES in step S905), the processing for decoding one frame is ended. If not all blocks are decoded (NO in step S905), the processing proceeds to step S901 again, from which the next block line is decoded.

**[0063]** The processing of step S902 (the processing for decoding the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 10. Since the top block line is an even-numbered block line, coded data of the processing target block line is input into the first decoding unit 802 by the selector 801, and is decoded by the first decoding unit 802.

**[0064]** Referring to Fig. 10, first, in step S1001, a quantization parameter, based on which a block is decoded, is initialized so as to match an initial value of a quantization parameter for a slice. Hereinafter, the quantization parameter, based on which a block is decoded, will be referred to as a "block reference quantization parameter" in a similar manner to the image coding apparatus according to the first exemplary embodiment. The block quantization parameter when a decoding target block is inversely quantized is in such a state that the value itself is not coded but a difference value thereof from the block reference quantization parameter is coded as a syntax element. Therefore, at the time of decoding, the block quantization parameter should be generated by adding the block reference quantization parameter and the

above-described difference value, and the decoding apparatus should perform inverse quantization using the generated block quantization parameter. In the present exemplary embodiment, this difference value corresponds to a `cu_qp_delta` value in the HEVC method. However, the present invention is not limited thereto. For example, the difference value may correspond to an `mb_qp_delta` value in the H.264 method. Next, in step S1002, an occurrence probability table is initialized by a predetermined method. The initialized occurrence probability table is used to arithmetically decode the first binary signal of the leftmost block in the block line, and is updated as necessary in step S1003, which will be described below. Hereinafter, the occurrence probability table used to arithmetically decode a first binary signal of an initial block in a block line will be referred to as a "block line reference occurrence probability table", in a similar manner to the image coding apparatus according to the first exemplary embodiment.

**[0065]** Next, in step S1003, the first decoding unit 802 decodes the bit stream block by block to generate image data.

**[0066]** In the present exemplary embodiment, one block is constituted by 64 x 64 pixels, but the present invention is not limited thereto. The size of a block may be a smaller size such as 32 x 32 pixels, or a larger size such 128 x 128 pixels. The block decoding processing in step S1003 will be described in detail with reference to the flowchart illustrated in Fig. 12.

**[0067]** First, in step S1201, the first decoding unit 802 arithmetically decodes the bit stream based on the above-described occurrence probability table to generate a binary signal. Further, the first decoding unit 802 decodes the binary signal binarized according any of various kinds of binarization methods, such as unary binarization and fixed-length binarization, for each syntax element in a similar manner to the H.264 method to generate syntax elements including quantization coefficients.

**[0068]** Next, in step S1202, the occurrence probability table is updated based on whether the arithmetically decoded binary signal is the most probable symbol.

**[0069]** Next, in step S1203, the first decoding unit 802 determines whether all syntax elements in the block are arithmetically decoded. If all syntax elements are arithmetically decoded (YES in step S1203), the processing proceeds to step S1204. If not all syntax elements are arithmetically decoded (NO in step S1203), the processing proceeds to step S1201 again.

**[0070]** Next, in step S1204, the first decoding unit 802 generates a block quantization parameter by adding the above-described block reference quantization parameter and the `cu_qp_delta` value decoded in step S1201.

**[0071]** Next, in step S1205, the first decoding unit 802 inversely quantizes the quantization coefficients based on the block quantization parameter to generate transform coefficients. Then, the first decoding unit 802 performs inverse orthogonal transform on the transform co-

efficients to generate prediction errors.

**[0072]** Next, in step S1206, the first decoding unit 802 sets the block quantization parameter used when inversely quantizing the processing target block to the block reference quantization parameter, thereby updating the block reference quantization parameter. The block reference quantization parameter will be used to generate a block quantization parameter of a next block.

**[0073]** Next, in step S1207, the first decoding unit 802 performs intra prediction from pixels surrounding the processing target block to generate a prediction image. Further, the first decoding unit 802 generates image data corresponding to one block by adding the prediction errors and the prediction image.

**[0074]** Referring back to the flowchart illustrated in Fig. 10, in step S1004, the first decoding unit 802 determines whether a condition for storing the block reference quantization parameter is satisfied. In the present exemplary embodiment, the condition for storing the block reference quantization parameter is whether the block decoded in step S1003 is the leftmost block in the block line. If the condition is satisfied (YES in step S1004), the processing proceeds to step S1005. In step S1005, the block reference quantization parameter is stored in the first quantization parameter storage unit 805 as a first quantization parameter. If the condition is not satisfied (NO in step S1004), the processing proceeds to step S1006. The first quantization parameter will be used as a block reference quantization parameter when the second decoding unit 803 decodes the leftmost block in the next block line.

**[0075]** Next, in step S1006, the first decoding unit 802 determines whether a condition for storing the occurrence probability table is satisfied. In the present exemplary embodiment, the condition for storing the occurrence probability table is whether the block decoded in step S1003 is the predetermined number-th block from the leftmost block in the block line. If this condition is satisfied (YES in step S1006), the processing proceeds to step S1007. In step S1007, the occurrence probability table is stored in the first occurrence probability table storage unit 804 as a first occurrence probability table. If the condition is not satisfied (NO in step S1006), the processing proceeds to step S1008. The first occurrence probability table will be used as a block line reference occurrence probability table when the second decoding unit 803 decodes the leftmost block in the next block line.

**[0076]** Next, in step S1008, the first decoding unit 802 determines whether all blocks in the processing target block line are decoded. If all blocks are decoded (YES in step S1008), decoding the top block line is ended. If not all blocks are decoded (NO in step S1008), the processing proceeds to step S1003 again, from which the first decoding unit 802 decodes the next block in raster order.

**[0077]** The processing of step S903 (the processing for decoding a block line other than the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 11. The selector 801 determines for

each block line whether the block line is an even-numbered block line. If the block line is an even-numbered block line, the bit stream of the processing target block is input into the first decoding unit 802, and is decoded by the first decoding unit 802. If the block line is an odd-numbered block line, the bit stream of the processing target block is input into the second decoding unit 803, and is decoded by the second decoding unit 803. First, a flow when the second decoding unit 803 decodes an odd-numbered block line will be described.

**[0078]** First, in step S1101, the first quantization parameter is input from the first quantization parameter storage unit 805 as a block reference quantization parameter. Next, in step S1102, the first occurrence probability table is input from the first occurrence probability table storage unit 804 as a block line reference occurrence probability table.

**[0079]** The processing of steps S1103, S1104, S1106, and S1108 is similar to the processing of steps S1003, S1004, S1006, and S1008, and, therefore, the description thereof is omitted here.

**[0080]** In step S1105, the block reference quantization parameter is stored in the second quantization parameter storage unit 807 as a second quantization parameter. The second quantization parameter will be used as a block reference quantization parameter for the leftmost block in the next block line.

**[0081]** In step S1107, the occurrence probability table is stored in the second occurrence probability table storage unit 806 as a second occurrence probability table. The second occurrence probability table will be used as a block line reference occurrence probability table when the first decoding unit 802 arithmetically decodes the leftmost block in the next block line.

**[0082]** Subsequently, a flow when the first decoding unit 802 decodes an even-numbered block line will be described.

**[0083]** First, in step S1101, the second quantization parameter is input from the second quantization parameter storage unit 807 as a block reference quantization parameter. Next, in step S1102, the second occurrence probability table is input from the second occurrence probability table storage unit 806 as a block line reference occurrence probability table.

**[0084]** The processing of steps S1103 to S1108 is similar to the processing of steps S1003 to S1008, and, therefore, the description thereof is omitted here.

**[0085]** The above-described configuration and operation enable parallel execution of decoding by allowing reference to a block reference quantization parameter in addition to an occurrence probability table, which is statistical information, during processing of a leftmost block even before completion of processing of a block line immediately before the block line that is currently being decoded. Figs. 7A and 7B each illustrate how a block reference quantization parameter is referred to. According to the conventional technique, as illustrated in Fig. 7A, until processing of a preceding block line is completed,

processing of a next block line cannot start. However, according to the present exemplary embodiment, a spatially upper block can be referred to when a leftmost block is processed, which allows a reference pattern as illustrated in Fig. 7B, thereby eliminating the necessity of waiting for completion of processing of a preceding block line.

**[0086]** Further, in the present exemplary embodiment, a quantization parameter used at a leftmost block in an immediately upper block line is used as a block reference quantization parameter when a leftmost block is decoded. However, the present invention is not limited thereto, and may be embodied by any configuration capable of improving parallelism of processing block line by block line. For example, an initial value of a quantization parameter provided to a slice may be used as a block reference quantization parameter when leftmost blocks in all block lines are decoded. As another possible configuration, the condition for storing a block reference quantization parameter may be the same as the condition for storing the occurrence probability table provided in steps S1006 and S1106. More specifically, a quantization parameter when a predetermined number-th block from a leftmost block in a block line is decoded may be used as a block reference quantization parameter for the leftmost block in the next block line. Further, the image decoding apparatus may be configured to switch a block referred to as a block reference quantization parameter based on a coding mode of a leftmost block.

**[0087]** Further, in the present exemplary embodiment, arithmetic decoding is used for entropy decoding, but the present invention is not limited thereto. Any decoding may be employed, as long as, at the time of entropy decoding based on statistical information such as the occurrence probability table, the statistical information in the middle of decoding of a block line is used to perform entropy decoding of the leftmost block of the next block line.

**[0088]** The present exemplary embodiment has been described based on an example using two decoding units. However, it is apparent that the addition of, for example, a third decoding unit, a third occurrence probability table storage unit, and a third quantization parameter storage unit enables parallel processing by a larger number of decoding units.

**[0089]** Fig. 14 is a block diagram illustrating an image coding apparatus according to a third exemplary embodiment.

**[0090]** Referring to Fig. 14, a selector 1401 determines whether a processing target block belongs to an even-numbered block line. The selector 1401 outputs the block to a first coding unit 1402 if the block belongs to an even-numbered block line, and otherwise outputs the block to a second coding unit 1403.

**[0091]** The first and second coding units 1402 and 1403 code blocks, into which an input image is divided by  $n \times n$  pixels (" $n$ " is a positive integer of 2 or larger), line by line as illustrated in Fig. 2 The present exemplary embodiment will be described based on an example us-

ing two coding units, but the present invention is not limited thereto. Referring to Fig. 2, the section 201 indicated as the square drawn by the thin line represents a block, and the section 202 indicated as the rectangle drawn by the thick line represents a block line. Further, the blocks in the white areas, which indicate even-numbered block lines including the top block line (the 0-th block line), are coded by the first coding unit 1402. The blocks in the shaded areas, which indicate odd-numbered block lines, are coded by the second coding unit 1403.

**[0092]** Each of the first and second coding units 1402 and 1403 first generates prediction errors according to the prediction by referring to pixels surrounding a coding target block or another frame, and performs orthogonal transform to generate transform coefficients. Next, each of the first and second coding units 1402 and 1403 determines a quantization parameter for the orthogonally transformed transform coefficients, and quantizes each transform coefficient to generate quantization coefficients. Next, each of the first and second coding units 1402 and 1403 binarizes each syntax element including the quantization coefficients to generate binary signals. An occurrence probability is assigned to each syntax element in advance as a table (hereinafter referred to as an "occurrence probability table"). The binary signals are arithmetically coded based on the above-described occurrence probability table. Then, each time a binary signal is coded, the occurrence probability table is updated using statistical information indicating whether the coded binary signal is the most probable symbol.

**[0093]** An initial quantization parameter storage unit 1404 stores an initial value of a quantization parameter.

**[0094]** A first occurrence probability table storage unit 1405 stores the occurrence probability table generated by the first coding unit 1402. Hereinafter, the occurrence probability table stored in the first occurrence probability table storage unit 1405 will be referred to as a "first occurrence probability table".

**[0095]** A second occurrence probability table storage unit 1406 stores the occurrence probability table generated by the second coding unit 1403. Hereinafter, the occurrence probability table stored in the second occurrence probability table storage unit 1406 will be referred to as a "second occurrence probability table".

**[0096]** An integration coding unit 1407 integrates coded data generated by the first coding unit 1402 and coded data generated by the second coding unit 1403, and outputs the integrated data as a bit stream.

**[0097]** An operation of the image coding apparatus according to the present exemplary embodiment will be described in detail with reference to the flowcharts illustrated in Figs. 3, 15, and 16. In the present exemplary embodiment, moving image data is input frame by frame, is divided into blocks, and is processed in raster order. The present exemplary embodiment is configured to input moving image data frame by frame, but may be configured to input still image data corresponding to one frame or to input image data slice by slice, which a frame is

divided into. Further, for simplification of description, the present exemplary embodiment will be described based on only intra prediction coding processing, but is not limited thereto. The present exemplary embodiment can be also employed to inter prediction coding processing.

**[0098]** First, the processing of steps S301, S304, and S305 illustrated in Fig. 3 is the same as the first exemplary embodiment, and, therefore, the description thereof is omitted here.

**[0099]** Then, the processing of step S302 (the processing for coding the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 15. Since the top block line is an even-numbered block line, a processing target block is input into the first coding unit 1402 by the selector 1401, and is coded by the first coding unit 1402.

**[0100]** First, in step S1501, a quantization parameter, based on which a block is coded, is initialized so as to match an initial value of a quantization parameter for a slice, and is stored in the initial quantization parameter storage unit 1404. Hereinafter, the quantization parameter, based on which a block is coded, will be referred to as a "block reference quantization parameter" in a similar manner to the first exemplary embodiment. Regarding a quantization parameter used to quantize a coding target block, the value thereof itself is not coded as a syntax element, but a difference value thereof from the block reference quantization parameter is coded.

**[0101]** Next, in step S1502, the first coding unit 1402 reads the initialized quantization parameter from the initial quantization parameter storage unit 1404 as a block reference quantization parameter for coding a leftmost block in a block line. Next, the processing of steps S1503 to S1507 is similar to the processing of steps S402, S403, and S406 to S408 illustrated in Fig. 4, respectively, and, therefore, the description thereof is omitted here.

**[0102]** However, in step S1504, the first coding unit 1402 codes pixel data block by block.

**[0103]** Next, the processing of step S303 (the processing for coding a block line other than the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 16. The selector 1401 determines for each block line whether the block line is an even-numbered block line. If the block line is an even-numbered block line, an image of the processing target block line is input into the first coding unit 1402 and is coded by the first coding unit 1402. If the block line is an odd-numbered block line, an image of the processing target block line is input into the second coding unit 1403, and is coded by the second coding unit 1403. First, a flow when the second coding unit 1403 codes an odd-numbered block line will be described.

**[0104]** First, in step S1601, a block reference quantization parameter for coding a leftmost block in a block line is input from the initial quantization parameter storage unit 1404. Next, in step S1602, the first occurrence probability table is input from the first occurrence probability table storage unit 1405 as a block line reference

occurrence probability table.

**[0105]** In step S1603, the second coding unit 1403 codes pixel data block by block. The processing of step S1604 is similar to the processing of step S1505 illustrated in Fig. 15.

**[0106]** In step S1605, the occurrence probability table is stored in the second occurrence probability table storage unit 1406 as a second occurrence probability table. The second occurrence probability table will be used as a block line reference occurrence probability table when the first coding unit 1402 arithmetically codes the leftmost block in the next block line.

**[0107]** The processing of step S1606 is similar to the processing of step S1507 illustrated in Fig. 15.

**[0108]** Subsequently, a flow when the first coding unit 1402 codes an even-numbered block line will be described.

**[0109]** First, in step S1601, a block reference quantization parameter for coding the leftmost block in the block line is input from the initial quantization parameter storage unit 1404. Next, in step S1602, the second occurrence probability table is input from the second occurrence probability table storage unit 1406 as a block line reference occurrence probability table.

**[0110]** The processing of steps S1603 to S1606 are similar to the processing of steps S1504 to S1507, and, therefore, the description thereof is omitted here.

**[0111]** The above-described configuration and operation enable parallel execution of coding by allowing reference to a block reference quantization parameter in addition to an occurrence probability table, which is statistical information, during processing of a leftmost block even before completion of processing of a block line immediately before the block line that is currently being coded. Figs 17A and 17B each illustrate how a block reference quantization parameter is referred to. In Figs. 17A and 17B, "SLICE QP" indicates an initial value of a quantization parameter provided to a slice. According to the conventional technique, as illustrated in Fig. 17A, until processing of a preceding block line is completed, processing of the next block line cannot start. However, according to the present exemplary embodiment, an initial value of a quantization parameter provided to a slice can be referred as a block reference quantization parameter for coding the leftmost block in the block line, thereby eliminating the necessity of waiting for completion of processing of the preceding block line as illustrated in Fig. 17B.

**[0112]** Further, in the present exemplary embodiment, arithmetic coding is used for entropy coding, but the present invention is not limited thereto. Any coding may be employed, as long as, at the time of entropy coding based on statistical information such as the occurrence probability table, the statistical information in the middle of coding of a block line is used to perform entropy coding of the leftmost block of the next block line.

**[0113]** The present exemplary embodiment has been described based on an example using two coding units.

However, it is apparent that the addition of, for example, a third coding unit and a third occurrence probability table storage unit enables parallel processing by a larger number of coding units.

5 **[0114]** Fig. 18 is a block diagram illustrating an image decoding apparatus according to a fourth exemplary embodiment.

**[0115]** Referring to Fig. 18, a selector 1801 determines whether a processing target block belongs to an even-numbered block line. The selector 1801 outputs the above-described bit stream to a first decoding unit 1802 if the processing target block belongs to an even-numbered block line, and otherwise outputs the above-described bit stream to a second decoding unit 1803.

10 **[0116]** The decoding units 1802 and 1803 decode the input bit stream, block line by block line as illustrated in Fig. 2. The present exemplary embodiment will be described based on an example using two decoding units, but the present invention is not limited thereto. Referring to Fig. 2, the blocks in the white areas, which indicate even-numbered block lines including the top block line (the 0-th block line), are decoded by the first decoding unit 1802. The blocks in the shaded areas, which indicate odd-numbered block lines, are decoded by the second decoding unit 1803.

15 **[0117]** Each of the first and second decoding units 1802 and 1803 first selects an occurrence probability table for binary signals of a bit stream that is a decoding target, and arithmetically decodes the binary signals based on the occurrence probability table to generate quantization coefficients. Next, each of the first and second decoding units 1802 and 1803 inversely quantizes the quantization coefficients based on a quantization parameter to generate transform coefficients. Then, each of the first and second decoding units 1802 and 1803 performs inverse orthogonal transform on the transform coefficients to generate prediction errors. Next, each of the first and second decoding units 1802 and 1803 performs motion compensation by referring to pixels surrounding the decoding target block or another frame to generate image data of the decoding target block. An initial quantization parameter storage unit 1804 stores an initial value of a quantization parameter. A first occurrence probability table storage unit 1805 stores the occurrence probability table generated by the first decoding unit 1802.

20 **[0118]** A second occurrence probability table storage unit 1806 stores the occurrence probability table generated by the second decoding unit 1803. An image data integration unit 1807 shapes image data generated by the first decoding unit 1802 and image data generated by the second decoding unit 1803, and outputs the shaped image data

25 **[0119]** An operation of the image decoding apparatus according to the present exemplary embodiment will be described in detail with reference to the flowcharts illustrated in Figs. 9, 19, and 20. In the present exemplary embodiment, a bit stream is input frame by frame. The

bit stream is divided into coded data pieces, each of which corresponds to one block, and then is decoded. The present exemplary embodiment is configured in such a manner that a bit stream is input frame by frame, but may be configured in such a manner that a frame is divided into slices, and a bit stream is input slice by slice. Further, for simplification of description, the present exemplary embodiment will be described based on only intra prediction decoding processing, but is not limited thereto. The present exemplary embodiment can be also employed to inter prediction decoding processing.

**[0120]** First, the processing of steps S901, S904, and S905 illustrated in Fig. 9 is the same as the second exemplary embodiment, and, therefore, the description thereof is omitted here.

**[0121]** The processing of step S902 (the processing for decoding the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 19. Since the top block line is an even-numbered block line, coded data of a processing target block line is input into the first decoding unit 1802 by the selector 1801, and is decoded by the first decoding unit 1802.

**[0122]** First, in step S1901, a quantization parameter, based on which a block is decoded, is initialized so as to match an initial value of a quantization parameter for a slice, and is stored in the initial quantization parameter storage unit 1804. Hereinafter, the quantization parameter, based on which a block is decoded, will be referred to as a "block reference quantization parameter" in a similar manner to the image decoding apparatus according to the second exemplary embodiment. The block quantization parameter when a decoding target block is inversely quantized is in such a state that the value itself is not coded but a difference value thereof from the block reference quantization parameter is coded as a syntax element. Therefore, at the time of decoding, the block quantization parameter should be generated by adding the block reference quantization parameter and the above-described difference value, and the decoding apparatus should perform inverse quantization using the generated block quantization parameter.

**[0123]** Next, in step S1902, the first decoding unit 1802 reads the value from the initial quantization parameter storage unit 1804 as a block reference quantization parameter for decoding the leftmost block in the block line. Next, the processing of steps S1903 to S1907 is similar to the processing of steps S1002, S1003, S1006 to S1008, respectively, and, therefore, the description thereof is omitted here.

**[0124]** Subsequently, the processing of step S903 (the processing for decoding a block line other than the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 20. The selector 1801 determines for each block line whether the block line is an even-numbered block line. If the block line is an even-numbered block line, a bit stream of a processing target block is input into the first decoding unit 1802, and is decoded by the first decoding unit 1802. If the block line

is an odd-numbered block line, a bit stream of a processing target block is input into the second decoding unit 1803, and is decoded by the second decoding unit 1803. First, a flow when the second decoding unit 1803 decodes an odd-numbered block line will be described.

**[0125]** First, in step S2001, a block reference quantization parameter for decoding the leftmost block in the block line is input from the initial quantization parameter storage unit 1804. Next, in step S2002, the first occurrence probability table is input from the first occurrence probability table storage unit 1805 as a block line reference occurrence probability table.

**[0126]** In step S2003, the second decoding unit 1403 decodes pixel data block by block. The processing of step S2004 is similar to the processing of step S1905, and, therefore, the description thereof is omitted here.

**[0127]** In step S2005, the occurrence probability table is stored in the second occurrence probability table storage unit 1806 as a second occurrence probability table. The second occurrence probability table will be used as a block line reference occurrence probability table when the first decoding unit 1402 arithmetically decodes the leftmost block in the next block line.

**[0128]** The processing of step S2006 is similar to the processing of step S1907, and, therefore, the description thereof is omitted here. Subsequently, a flow when the first decoding unit 1802 decodes an even-numbered block line will be described.

**[0129]** First, in step S2001, a block reference quantization parameter for decoding the leftmost block in the block line is input from the initial quantization parameter storage unit 1804. Next, in step S2002, the second occurrence probability table is input from the second occurrence probability table storage unit 1806 as a block line reference occurrence probability table.

**[0130]** The processing of steps S2003 to S2006 is similar to the processing of steps S1904 to S1907, and, therefore, the description thereof is omitted here.

**[0131]** The above-described configuration and operation enable parallel execution of decoding by allowing reference to a block reference quantization parameter in addition to an occurrence probability table, which is statistical information, during processing of a leftmost block even before completion of processing of a block line immediately before the block line that is currently being decoded.

**[0132]** Further, in the present exemplary embodiment, arithmetic decoding is used for entropy decoding, but the present invention is not limited thereto. Any decoding may be employed, as long as, at the time of entropy decoding based on statistical information such as the occurrence probability table, the statistical information in the middle of decoding of a block line is used to perform entropy decoding of the leftmost block of the next block line.

**[0133]** The present exemplary embodiment has been described based on an example using two decoding units. However, it is apparent that the addition of, for ex-

ample, a third decoding unit and a third occurrence probability table storage unit enables parallel processing by a larger number of decoding units.

**[0134]** Fig. 21 is a block diagram illustrating an image coding apparatus according to a fifth exemplary embodiment.

**[0135]** Referring to Fig. 21, a selector 2101 determines whether a processing target block belongs to an even-numbered block line. The selector 2101 outputs the block to a first coding unit 2102 if the block belongs to an even-numbered block line, and otherwise outputs the block to a second coding unit 2103.

**[0136]** The first and second coding units 2102 and 2103 code blocks, into which an input image is divided by  $n \times n$  pixels ("n" is a positive integer of 2 or larger), line by line as illustrated in Fig. 2. The present exemplary embodiment will be described based on an example using two coding units, but the present invention is not limited thereto. Referring to Fig. 2, the section 201 indicated as the square drawn by the thin line represents a block, and the section 202 indicated as the rectangle drawn by the thick line represents a block line. Further, the blocks in the white areas, which indicate even-numbered block lines including the top block line (the 0-th block line), are coded by the first coding unit 2102. The blocks in the shaded areas, which indicate odd-numbered block lines, are coded by the second coding unit 2103.

**[0137]** Each of the first and second coding units 2102 and 2103 first generates prediction errors according to prediction by referring to pixels surrounding a coding target block or another frame, and performs orthogonal transform to generate transform coefficients. Next, each of the first and second coding units 2102 and 2103 determines a quantization parameter for the orthogonally transformed transform coefficients, and quantizes each transform coefficient to generate quantization coefficients. Next, each of the first and second coding units 2102 and 2103 binarizes each syntax element including the quantization coefficients to generate binary signals. An occurrence probability is assigned to each syntax element in advance as a table (hereinafter referred to as an "occurrence probability table"). The binary signals are arithmetically coded based on the above-described occurrence probability table. Then, each time a binary signal is coded, the occurrence probability table is updated using statistical information indicating whether the coded binary signal is the most probable symbol.

**[0138]** An initial quantization parameter storage unit 2104 stores an initial value of a quantization parameter. An initial occurrence probability table storage unit 2105 stores an initial value of an occurrence probability table. An integration coding unit 2106 integrates coded data generated by the first coding unit 2102 and coded data generated by the second coding unit 2103, and outputs the integrated data as a bit stream.

**[0139]** An operation of the image coding apparatus according to the present exemplary embodiment will be described in detail with reference to the flowcharts illustrat-

ed in Figs. 3, 22, and 23. In the present exemplary embodiment, moving image data is input frame by frame, is divided into blocks, and is processed in raster order. The present exemplary embodiment is configured to input moving image data frame by frame, but may be configured to input still image data corresponding to one frame or to input image data slice by slice, which a frame is divided into. Further, for simplification of description, the present exemplary embodiment will be described based on only intra prediction coding processing, but is not limited thereto. The present exemplary embodiment can be also employed to inter prediction coding processing.

**[0140]** The processing of steps S301, S304, and S305 illustrated in Fig. 3 is the same as the first exemplary embodiment, and, therefore, the description thereof is omitted here.

**[0141]** The processing of step S302 (the processing for coding the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 22. Since the top block line is an even-numbered block line, a processing target block is input into the first coding unit 2102 by the selector 2101, and is coded by the first coding unit 2102.

**[0142]** First, in step S2201, a quantization parameter, based on which a block is coded, is initialized so as to match an initial value of a quantization parameter for a slice, and is stored in the initial quantization parameter storage unit 2104. Hereinafter, the quantization parameter, based on which a block is coded, will be referred to as a "block reference quantization parameter" in a similar manner to the first exemplary embodiment. Regarding a quantization parameter used to quantize a coding target block, the value thereof itself is not coded as a syntax element, but a difference value thereof from the block reference quantization parameter is coded.

**[0143]** Next, in step S2202, the first coding unit 2102 reads the initialized quantization parameter from the initial quantization parameter storage unit 2104 as a block reference quantization parameter for coding a leftmost block in a block line. Next, in step S2203, an occurrence probability table is initialized by a predetermined method, and is stored in the initial occurrence probability table storage unit 2105. The occurrence probability table stored in the initial occurrence probability table storage unit 2105 is used to arithmetically code the first binary signal of the leftmost block in the block line, and is updated as necessary in step S2205, which will be described below. Hereinafter, the occurrence probability table used to arithmetically code a binary signal of a first block in a block line will be referred to as a "block line reference occurrence probability table" in a similar manner to the first exemplary embodiment.

**[0144]** Next, in step S2204, the first coding unit 2102 reads the initialized quantization parameter from the initial occurrence probability table storage unit 2105 as a block line reference occurrence probability table.

**[0145]** Next, the processing of steps S2205 and S2206 is similar to the processing of steps S403 and S408 illus-

trated in Fig. 4, respectively, and, therefore, the description thereof is omitted here. However, in step S2205, the first coding unit 2012 codes pixel data block by block. Subsequently, the processing of step S303 (the processing for coding a block line other than the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 23. The selector 2101 determines for each block line whether the block line is an even-numbered block line. If the block line is an even-numbered block line, an image of the processing target block line is input into the first coding unit 2102 and is coded by the first coding unit 2102. If the block line is an odd-numbered block line, an image of the processing target block line is input into the second coding unit 2103, and is coded by the second coding unit 2103. First, a flow when the second coding unit 2103 codes an odd-numbered block line will be described.

**[0146]** First, in step S2301, a block reference quantization parameter for coding the leftmost block in the block line is input from the initial quantization parameter storage unit 2104.

**[0147]** Next, in step S2302, the value is input from the initial occurrence probability table storage unit 2105 as a block line reference occurrence probability table.

**[0148]** Next, in step S2303, the second coding unit 2103 codes pixel data block by block. The processing of step S2304 is similar to the processing of step S2206 illustrated in Fig. 22. Subsequently, a flow when the first coding unit 2102 codes an even-numbered block line will be described. First, in step S2301, a block reference quantization parameter for coding the leftmost block in the block line is input from the initial quantization parameter storage unit 2104. Next, in step S2302, the value is input from the initial occurrence probability table storage unit 2105 as a block line reference occurrence probability table.

**[0149]** The processing of steps S2303 and S2304 is similar to the processing of steps S2205 and S2206, and, therefore, the description thereof is omitted here.

**[0150]** The above-described configuration and operation enable parallel execution of coding by using an occurrence probability table, which is statistical information, and an initialized value as a block reference quantization parameter during processing of a leftmost block even before completion of processing of a block line immediately before the block line that is currently being coded. Further, in the present exemplary embodiment, arithmetic coding is used for entropy coding, but the present invention is not limited thereto. Any coding method may be employed, as long as statistical information is initialized at the beginning of coding processing, coding processing is performed with use of the statistical information, and the statistical information is updated each time coding processing is performed.

**[0151]** The present exemplary embodiment has been described based on an example using two coding units. However, it is apparent that the addition of, for example, a third coding unit enables parallel processing by a larger

number of coding units.

**[0152]** Fig. 24 is a block diagram illustrating an image decoding apparatus according to a sixth exemplary embodiment.

**[0153]** Referring to Fig. 24, a selector 2401 determines whether a processing target block belongs to an even-numbered block line. The selector 2401 outputs the block to a first decoding unit 2402 if the block belongs to an even-numbered block line, and otherwise outputs the block to a second decoding unit 2403.

**[0154]** The first and second decoding units 2402 and 2403 decode the input bit stream, line by line as illustrated in Fig. 2. Hereinafter, a line of blocks will be referred to as a "block line". The present exemplary embodiment will be described based on an example using two decoding units, but the present invention is not limited thereto. Referring to Fig. 2, the section 201 indicated as the square drawn by the thin line represents a block, and the section 202 indicated as the rectangle drawn by the thick line represents a block line. Further, the blocks in the white areas, which indicate even-numbered block lines including the top block line (the 0-th block line), are decoded by the first decoding unit 2402. The blocks in the shaded areas, which indicate odd-numbered block lines, are decoded by the second decoding unit 2403.

**[0155]** Each of the first and second decoding units 2402 and 2403 first selects an occurrence probability table for a binary signal of a bit stream that is a decoding target, and arithmetically decodes the binary signal based on the occurrence probability table to generate quantization coefficients. Next, each of the first and second decoding units 2402 and 2403 inversely quantizes the quantization coefficients based on a quantization parameter to generate transform coefficients. Then, each of the first and second decoding units 2402 and 2403 performs inverse orthogonal transform on the transform coefficients to generate prediction errors. Next, each of the first and second decoding units 2402 and 2403 performs prediction by referring to pixels surrounding the decoding target block or another frame to generate image data of the decoding target block.

**[0156]** An initial quantization parameter storage unit 2404 stores an initial value of a quantization parameter. An initial occurrence probability table storage unit 2405 stores an initial value of an occurrence probability table. An image data integration unit 2406 shapes image data generated by the first decoding unit 2402 and image data generated by the second decoding unit 2403, and outputs the shaped data.

**[0157]** An operation of the image decoding apparatus according to the present exemplary embodiment will be described in detail with reference to the flowcharts illustrated in Figs. 9, 25, and 26. In the present exemplary embodiment, a bit stream is input frame by frame. The bit stream is divided into coded data pieces, each of which corresponds to one block, and then is decoded. The present exemplary embodiment is configured in such a manner that a bit stream is input frame by frame, but may

be configured in such a manner that a frame is divided into slices, and a bit stream is input slice by slice. Further, for simplification of description, the present exemplary embodiment will be described based on only intra prediction decoding processing, but is not limited thereto. The present exemplary embodiment can be also employed to inter prediction decoding processing.

**[0158]** The processing of steps S901, S904, and S905 illustrated in Fig. 9 are the same as the second exemplary embodiment, and, therefore, the description thereof is omitted here.

**[0159]** The processing of step S902 (the processing for decoding the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 25. Since the top block line is an even-numbered block line, coded data of a processing target block line is input into the first decoding unit 2402 by the selector 2401, and is decoded by the first decoding unit 2402.

**[0160]** First, in step S2501, a quantization parameter, based on which a block is decoded, is initialized so as to match an initial value of a quantization parameter for a slice, and is stored in the initial quantization parameter storage unit 2404. Hereinafter, the quantization parameter, based on which a block is decoded, will be referred to as a "block reference quantization parameter" in a similar manner to the second exemplary embodiment. The block quantization parameter when a decoding target block is inversely quantized is in such a state that the value itself is not coded but a difference value thereof from the block reference quantization parameter is coded as a syntax element. Therefore, at the time of decoding, the block quantization parameter should be generated by adding the block reference quantization parameter and the above-described difference value, and the decoding apparatus should perform inverse quantization.

**[0161]** Next, in step S2502, the first decoding unit 2402 reads the value from the initial quantization parameter storage unit 2404 as a block reference quantization parameter for coding the leftmost block in the block line. Next, in step S2503, the occurrence probability table is initialized by a predetermined method, and is stored in the initial occurrence probability table storage unit 2405. The occurrence probability table stored in the initial occurrence probability table storage unit 2405 is used to arithmetically decode the first binary signal of the leftmost block in the block line, and is updated as necessary in step S2505, which will be described below. Hereinafter, the occurrence probability table used to arithmetically decode a first binary signal of an initial block in a block line will be referred to as a "block line reference occurrence probability table", in a similar manner to the second exemplary embodiment.

**[0162]** Next, in step S2504, the first decoding unit 2402 reads the value from the initial occurrence probability table storage unit 2405 as a block line reference occurrence probability table.

**[0163]** Next, the processing of steps S2505 and S2506 is similar to the processing of steps S1003 and S1008

illustrated in Fig. 10, respectively, and, therefore, the description thereof is omitted here.

**[0164]** However, in step S2505, the first decoding unit 2402 decodes pixel data block by block.

**[0165]** Subsequently, the processing of step S903 (the processing for decoding a block line other than the top block line) will be described in detail with reference to the flowchart illustrated in Fig. 26. The selector 2401 determines for each block line whether the block line is an even-numbered block line. If the block line is an even-numbered block line, a bit stream of the processing target block is input into the first decoding unit 2402, and is decoded by the first decoding unit 2402. If the block line is an odd-numbered block line, a bit stream of the processing target block is input into the second decoding unit 2403, and is decoded by the second decoding unit 2403. First, a flow when the second decoding unit 2403 decodes an odd-numbered block line will be described.

**[0166]** First, in step S2601, a block reference quantization parameter for decoding the leftmost block in the block line is input from the initial quantization parameter storage unit 2404.

**[0167]** Next, in step S2602, the value is input from the initial occurrence probability table storage unit 2405 as a block line reference occurrence probability table.

**[0168]** Next, in step S2603, the second decoding unit 2403 decodes pixel data block by block. The processing of step S2604 is similar to the processing of step S2506 illustrated in Fig. 25. Subsequently, a flow when the first decoding unit 2402 decodes an even-numbered block line will be described. First, in step S2601, a block reference quantization parameter for decoding the leftmost block in the block line is input from the initial quantization parameter storage unit 2404. Next, in step S2602, the value is input from the initial occurrence probability table storage unit 2405 as a block line reference occurrence probability table.

**[0169]** The processing of steps S2603 and S2604 is similar to the processing of steps S2505 and S2506, and, therefore, the description thereof is omitted here.

**[0170]** The above-described configuration and operation enable parallel execution of decoding by using an occurrence probability table, which is statistical information, and an initialized value as a block reference quantization parameter during processing of a leftmost block even before completion of processing of a block line immediately before a block line that is currently being decoded.

**[0171]** Further, in the present exemplary embodiment, arithmetic decoding is used for entropy decoding, but the present invention is not limited thereto. Any decoding method may be employed, as long as statistical information is initialized at the beginning of decoding processing, decoding processing is performed with use of the statistical information, and the statistical information is updated each time decoding processing is performed.

**[0172]** The present exemplary embodiment has been described based on an example using two decoding

units. However, it is apparent that the addition of, for example, a third decoding unit enables parallel processing by a larger number of decoding units.

**[0173]** The above-described exemplary embodiments have been described assuming that the respective processing units illustrated in Figs. 1, 8, 14, 18, 21, and 24 are realized by hardware apparatuses. However, the processing performed by the respective processing units illustrated in Figs. 1, 8, 14, 18, 21, and 24 may be realized by a computer program.

**[0174]** Fig. 13 is a block diagram illustrating an example of a hardware configuration of a computer employable as the image processing apparatuses according to the above-described respective exemplary embodiments.

**[0175]** A central processing unit (CPU) 1301 controls the entire computer with use of a computer program and data stored in a random access memory (RAM) 1302 and a read only memory (ROM) 1303, and performs the respective kinds of processing that have been described to be performed by the image processing apparatuses according to the above-described respective exemplary embodiments. In other words, the CPU 1301 functions as the respective processing units illustrated in Figs. 1, 8, 14, 18, 21 and 24.

**[0176]** The RAM 1302 has an area for temporarily storing, for example, a computer program and data loaded from an external storage device 1306, and data acquired from the outside via an interface (I/F) 1307. Further, the RAM 1302 has a work area used when the CPU 1301 performs various kinds of processing. In other words, for example, the RAM 1302 can be assigned as a frame memory or can provide other various kinds of areas as necessary.

**[0177]** The ROM 1303 stores, for example, setting data of the present computer and a boot program. An operation unit 1304 includes a keyboard and a mouse. A user of the present computer can input various kinds of instructions to the CPU 1301 by operating the operation unit 1304. A display unit 1305 displays a result of processing performed by the CPU 1301. Further, the display unit 1305 includes a display device such as a liquid crystal display.

**[0178]** The external storage device 1306 is a large-capacity information storage device represented by a hard disk drive device. The external storage device 1306 stores an operating system (OS), and the computer program for enabling the CPU 1301 to realize the functions of the respective units illustrated in Figs. 1, 8, 14, 18, 21 and 24. Further, the external storage device 1306 may store image data as a processing target.

**[0179]** The computer program and data stored in the external storage device 1306 are loaded to the RAM 1302 as necessary according to the control by the CPU 1301, and are processed by the CPU 1301. A network such as a local area network (LAN) and the Internet, and another device such as a projection device and a display device can be connected to the I/F 1307. The computer can acquire and transmit various kinds of information via the

I/F 1307. A bus 1308 connects the above-described respective units to one another.

**[0180]** As the operation by the above-described configuration, the CPU 1301 plays a central role in controlling the operations explained with reference to the above-described flowcharts.

**[0181]** The present invention can be also embodied by supplying a storage medium storing codes of the computer program capable of realizing the above-described functions to a system, and causing the system to read out and execute the codes of the computer program. In this case, the codes of the computer program read from the storage medium realize the functions of the above-described exemplary embodiments, and the storage medium storing the codes of the computer program is within the scope of the present invention. Alternatively, an operating system (OS) or the like that works on a computer may perform a part or all of actual processing based on instructions of the codes of the computer program, thereby realizing the above-described functions by this processing. This case is also within the scope of the present invention.

**[0182]** Further alternatively, the present invention may be embodied by the following embodiment; the codes of the computer program read from the storage medium may be written in a function expansion card inserted in a computer or a memory provided to a function expansion unit connected to a computer, and a CPU or the like provided to the function expansion card or the function expansion unit may perform a part or all of actual processing based on instructions of the codes of the computer program, thereby realizing the above-described functions. This case is also within the scope of the present invention.

**[0183]** In a case where the present invention is embodied by the above-described storage medium, the storage medium stores the codes of the computer program corresponding to the above-described flowcharts.

**[0184]** While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all modifications, equivalent structures, and functions.

**[0185]** This application claims priority from Japanese Patent Application No. 2011-243940 filed November 7, 2011, which is hereby incorporated by reference herein in its entirety.

**[0186]** The following numbered statements describing embodiments form part of the description. The claims follow the numbered statements and are labelled as such.

[Statement 1] An image coding apparatus configured to divide an image into one or more slices each including a plurality of blocks and to code each slice on a block-by-block basis, the image coding apparatus comprising:

first coding means configured to code blocks included in a first portion of the slice; and  
 second coding means configured to code blocks included in a second portion of the slice,

wherein, when the second coding means codes the initial block in the second portion, the second coding means codes the initial block included in the second portion by referring to a first quantization parameter provided to the slice as an initial value and referred to by the first coding means when the first coding means codes the initial block in the first portion.

[Statement2] The image coding apparatus according to Statement 1, wherein, when the first coding means codes a block other than the initial block in the first portion of the slice, the first coding means codes the block other than the initial block by referring to a quantization parameter of a block that the first coding means codes immediately before the block, and wherein, when the second coding means codes a block other than the initial block in the second portion of the slice, the second coding means refers to a quantization parameter of a block that the second coding means codes immediately before the block.

[Statement3] The image coding apparatus according to Statement 1 or 2, wherein, when the first coding means codes each block included in the first portion, the first coding means codes each block by referring to statistical information for entropy coding and further updates the statistical information, and wherein, when the second coding means codes the initial block in the second portion, the second coding means codes the initial block by referring to the updated statistical information updated after coding a predetermined block included in the first portion.

[Statement4] An image coding apparatus configured to divide an image into one or more slices each including a plurality of blocks and to code each slice on a block-by-block basis, the image coding apparatus comprising:

first coding means configured to code blocks included in a first portion of the slice; and  
 second coding means configured to code blocks included in a second portion of the slice,

wherein, when the second coding means codes the initial block in the second portion of the slice, the second coding means codes the initial block by referring to a second quantization parameter used for coding the initial block or the block following the initial block in the first portion.

[Statement5] An image coding method for dividing an image into one or more slices each including a plurality of blocks and coding each slice on a block-by-block basis, the image coding method comprising:

5

10

15

20

25

30

35

40

45

50

55

coding blocks included in a first portion of the slice;  
 coding blocks included in a second portion of the slice; and  
 coding the initial block in the second portion by referring to a first quantization parameter provided to the slice as an initial value and referred to when the initial block in the first portion is coded.

[Statement6] An image decoding apparatus configured to decode code data which are coded slice-by-slice basis each including a plurality of blocks on a block-by-block basis, the image decoding apparatus comprising:

first decoding means configured to decode blocks included in a first portion of the slice; and  
 second decoding means configured to decode blocks included in a second portion of the slice,

wherein, when the second decoding means decodes the initial block in the second portion, the second decoding means decodes the initial block in the second portion by referring to a first quantization parameter provided to the slice as an initial value and referred to by the first decoding means when the first decoding means decodes the initial block in the first portion.

[Statement7] The image decoding apparatus according to Statement 6, wherein, when the first decoding means decodes each block included in the first portion, the first decoding means decodes each block by referring to statistical information for entropy coding and further updates the statistical information, and

wherein, when the second decoding means decodes the initial block in the second portion, the second decoding means decodes the initial block by referring to the updated statistical information updated after decoding a predetermined block included in the first portion.

[Statement8] An image decoding method for decoding code data which are coded slice-by-slice basis each including plurality of blocks on a block-by-block basis, the image decoding method comprising:

decoding blocks included in a first portion of the slice;  
 decoding blocks included in a second portion of the slice; and  
 decoding the initial block in the second portion by referring to a first quantization parameter provided to the slice as an initial value and referred to when the initial block in the first portion is decoded.

[Statement9] A program that is readable and exe-

cutable by a computer and that causes the computer to function as the image coding apparatus according to Statement 1.

[Statement10] A program that is readable and executable by a computer and that causes the computer to function as the image decoding apparatus according to Statement 6.

## Claims

1. An image coding apparatus configured to code an image into a bit stream, the image including one or more slices, each slice including a plurality of blocks a size of each of which is  $n \times n$  pixels, where  $n$  is a positive integer of 2 or larger, the image coding apparatus comprising:

first coding means (102) for coding blocks included in a first block line of the slice in an order starting from a first block which is a left-most block of the first block line, said first block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the first coding means is arranged to code the blocks included in the first block line by using arithmetic coding, and wherein the first coding means is arranged to update statistical information for arithmetic coding when coding the blocks included in the first block line; and

second coding means (103) for coding blocks included in a second block line of the slice in an order starting from a first block which is a left-most block of the second block line, said second block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the second coding means is arranged to code the blocks included in the second block line by using arithmetic coding, and wherein when coding the first block of the second block line, the second coding means is arranged to use the statistical information updated when a predetermined block of the first block line is coded,

wherein, the first coding means is arranged to code a quantization parameter of the first block in the order of coding the blocks included in the first block line by using a slice quantization parameter that is provided to the slice as an initial value,

the second coding means is arranged to code a quantization parameter of the first block in the order of coding the blocks included in the second block line by using the slice quantization parameter that is used by the first coding means when coding the quantization parameter of the first block of the first block line, and quantization parameters of subsequent blocks

of the first block of the first block line and quantization parameters of subsequent blocks of the first block of the second block line are coded by using the quantization parameter of a preceding block of the respective block line according to the order of coding.

2. An image decoding apparatus configured to decode an image from a bit stream which is coded in units of slices, each slice including a plurality of blocks a size of each of which is  $n \times n$  pixels, where  $n$  is a positive integer of 2 or larger, the image decoding apparatus comprising:

first decoding means (802) for decoding blocks included in a first block line of the slice in an order starting from a first block which is a left-most block of the first block line, said first block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the first decoding means is arranged to decode the blocks included in the first block line by using arithmetic decoding, and wherein the first decoding means is arranged to update statistical information for arithmetic decoding when decoding the blocks included in the first block line; and second decoding means (803) for decoding blocks included in a second block line of the slice in an order starting from a first block which is a left-most block of the second block line, said second block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the second decoding means is arranged to decode the blocks included in the second block line by using arithmetic decoding, and wherein when decoding the first block of the second block line, the second decoding means is arranged to use the statistical information updated when a predetermined block of the first block line is decoded,

wherein, the first decoding means is arranged to decode a quantization parameter of the first block in the order of decoding the blocks included in the first block line by using a slice quantization parameter that is provided to the slice as an initial value,

the second decoding means is arranged to decode a quantization parameter of the first block in the order of decoding the blocks included in the second block line by using the slice quantization parameter that is used by the first decoding means when decoding the quantization parameter of the first block of the first block line, and

quantization parameters of subsequent blocks of the first block of the first block line and quantization parameters of subsequent blocks of the first block of the second block line are decoded

by using the quantization parameter of a preceding block of the respective block line according to the order of decoding.

3. An image coding method for coding an image into a bit stream, the image including one or more slices, each slice including a plurality of blocks a size of each of which is  $n \times n$  pixels, where  $n$  is a positive integer of 2 or larger, the image coding method comprising:

a first coding step for coding blocks included in a first block line of the slice in an order starting from a first block which is a left-most block of the first block line, said first block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the blocks included in the first block line are coded by using arithmetic coding, and wherein statistical information for arithmetic coding is updated when coding the blocks included in the first block line; and

a second coding step for coding blocks included in a second block line of the slice in an order starting from a first block which is a left-most block of the second block line, said second block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the blocks included in the second block line are coded by using arithmetic coding, and wherein when coding the first block of the second block line, the statistical information updated when a predetermined block of the first block line is coded is used,

wherein, when coding the first block the first coding step includes coding a quantization parameter of the first block in the order of coding the blocks included in the first block line by using a slice quantization parameter that is provided to the slice as an initial value,

when coding the first block the second coding step includes coding a quantization parameter of the first block in the order of coding the blocks included in the second block line by using the slice quantization parameter that is used in the first coding step when coding the quantization parameter of the first block of the first block line, and

quantization parameters of subsequent blocks of the first block of the first block line and quantization parameters of subsequent blocks of the first block of the second block line are coded by using the quantization parameter of a preceding block of the respective block line according to the order of coding.

4. An image decoding method for decoding code data coded slice-by-slice, each slice including a plurality of blocks a size of each of which is  $n \times n$  pixels, where

$n$  is a positive integer of 2 or larger, the image decoding method comprising:


a first decoding step of decoding blocks included in a first block line of the slice in an order starting from a first block which is a left-most block of the first block line, said first block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the blocks included in the first block line are decoded by using arithmetic decoding, and wherein statistical information for arithmetic decoding is updated when decoding the blocks included in the first block line; a second decoding step of decoding blocks included in a second block line of the slice in an order starting from a first block which is a left-most block of the second block line, said second block line comprising a plurality of blocks arranged in a horizontal direction in the image, wherein the blocks included in the second block line are decoded by using arithmetic decoding wherein when decoding the first block of the second block line, the statistical information updated when a predetermined block of the first block line is decoded is used,

wherein, the first decoding step includes decoding a quantization parameter of the first block in the order of decoding the blocks included in the first block line by using a slice quantization parameter that is provided to the slice as an initial value,

the second decoding step includes decoding a quantization parameter of the first block in the order of decoding the blocks included in the second block line by using the slice quantization parameter that is used in the first decoding step when decoding the quantization parameter of the first block of the first block line, and quantization parameters of subsequent blocks of the first block of the first block line and quantization parameters of subsequent blocks of the first block of in the second block line are decoded by using the quantization parameter of a preceding block of the respective block line according to the order of decoding.

5. A computer program comprising instructions which, when the program is executed by a computer, cause the computer to perform the method of claim 3.
6. A computer program comprising instructions which, when the program is executed by a computer, cause the computer to perform the method of claim 4.

FIG.1



**FIG.2**




FIG.3







FIG.4




**FIG.5**



**FIG.6**



**FIG.7A**



**FIG.7B**





FIG.8



**FIG.9**




FIG.10




FIG.11





FIG.12



**FIG.13**




FIG.14




FIG.15






FIG.16



**FIG.17A**



**FIG.17B**






FIG.19




FIG.20




FIG.21





FIG.22



**FIG.23**




FIG.24






FIG.25



**FIG.26**





EUROPEAN SEARCH REPORT

Application Number  
EP 20 20 5787

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	EP 2 290 985 A1 (PANASONIC CORP [JP]) 2 March 2011 (2011-03-02) * paragraph [0088] * * paragraph [0116]; figure 5 *	1-6	INV. H04N19/196 H04N19/46 H04N19/436 H04N19/91
A	KIRAN MISRA ET AL: "Periodic entropy coder initialization for wavefront decoding of video bitstream", IMAGE PROCESSING (ICIP), 2011 18TH IEEE INTERNATIONAL CONFERENCE ON, IEEE, 11 September 2011 (2011-09-11), pages 3517-3520, XP032080456, DOI: 10.1109/ICIP.2011.6116474 ISBN: 978-1-4577-1304-0 * the whole document *	1-6	
A	FULDSETH (CISCO) A ET AL: "Tiles", 97. MPEG MEETING; 18-7-2011 - 22-7-2011; TORINO; (MOTION PICTURE EXPERT GROUP OR ISO/IEC JTC1/SC29/WG11),, no. m20757, 14 July 2011 (2011-07-14), - 22 July 2011 (2011-07-22), XP030049320, * paragraph [2.5.1] *	1-6	
A	MUHAMMED COBAN ET AL: "CU-Level QP Prediction", 5. JCT-VC MEETING; 96. MPEG MEETING; 16-3-2011 - 23-3-2011; GENEVA; (JOINT COLLABORATIVE TEAM ON VIDEO CODING OF ISO/IEC JTC1/SC29/WG11 AND ITU-T SG.16 ); URL: HTTP://WFTP3.ITU.INT/AV-ARCH/JCTVC-SITE/, no. JCTVC-E391, 11 March 2011 (2011-03-11), XP030008897, ISSN: 0000-0005 * paragraph [02.2]; figure 2 *	1-6	TECHNICAL FIELDS SEARCHED (IPC)  H04N
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 13 January 2021	Examiner Schoeyer, Marnix
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document	

EPO FORM 1503 03.02 (P04C01)



EUROPEAN SEARCH REPORT

Application Number  
EP 20 20 5787

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	GORDON C ET AL: "Wavefront Parallel Processing for HEVC Encoding and Decoding", 6. JCT-VC MEETING; 97. MPEG MEETING; 14-7-2011 - 22-7-2011; TORINO; (JOINT COLLABORATIVE TEAM ON VIDEO CODING OF ISO/IEC JTC1/SC29/WG11 AND ITU-T SG.16 ); URL: HTTP://WFTP3.ITU.INT/AV-ARCH/JCTVC-SITE/, , no. JCTVC-F274, 1 January 2011 (2011-01-01), XP030009297, * the whole document * -----	1-6	
			TECHNICAL FIELDS SEARCHED (IPC)
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 13 January 2021	Examiner Schoeyer, Marnix
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons ..... & : member of the same patent family, corresponding document	

1  
EPO FORM 1503 03.02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 20 20 5787

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.  
The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

13-01-2021

10	Patent document cited in search report	Publication date	Patent family member(s)	Publication date
	EP 2290985	A1 02-03-2011	CN 101779466 A	14-07-2010
			EP 2290985 A1	02-03-2011
			JP 5756921 B2	29-07-2015
15			JP WO2009150808 A1	10-11-2011
			TW 201004359 A	16-01-2010
			US 2011200115 A1	18-08-2011
			WO 2009150808 A1	17-12-2009
20	-----			
25				
30				
35				
40				
45				
50				
55				

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- JP 2011243940 A [0185]