



(11)

EP 3 858 663 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
04.08.2021 Bulletin 2021/31

(51) Int Cl.:
B60N 2/28 (2006.01)

(21) Application number: **21157290.4**

(22) Date of filing: **16.07.2013**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
**18187663.2 / 3 437 920
13003568.6 / 2 826 662**

(71) Applicant: **BRITAX RÖMER Kindersicherheit GmbH
89340 Leipheim (DE)**

(72) Inventors:
• **HAAS, Martin
89555 Steinheim (DE)**

- **FRANK, Richard
89275 Elchingen (DE)**
- **HENSELER, Richard
89081 Ulm (DE)**

(74) Representative: **Richardt Patentanwälte PartG mbB
Wilhelmstraße 7
65185 Wiesbaden (DE)**


Remarks:

This application was filed on 16-02-2021 as a divisional application to the application mentioned under INID code 62.

(54) CHILD SAFETY SEAT

(57) The child safety seat (1) for a vehicle in accordance with the invention comprises an outer shell (2) enclosing a seating area (3) for a child (4) and a protective element (5). The protective element (5) comprises a housing component (7) and an impact component (8), wherein the housing component (7) is embedded into the outer shell (2) and the impact component (8) is mounted to the housing component (7), is configured to be enclosed at least partially by the housing component (7), and is configured to protrude laterally from the outer shell (2) in a direction facing away from the seating area (3). Elastic elements (15) are used for coupling the outer shell (2) to fixed bearings (12) allowing impact forces to be

guided into a structurally stable part of the child safety seat (1), wherein the housing component (7) comprises a flange (112) configured to rest on the outer shell (2), for firmly mount the housing component (7) to the outer shell (2) such that impact forces acting on the impact component (8) are transferred from the impact component (8) to the housing component (7) and are then guided via the flange (112) into the outer shell (2) of the child safety seat (1), deforming the outer shell (2) and compressing the elastic elements (15). Preferably, the housing component (7) or the impact component (8) comprises a deformable region (9) adapted to cushion forces impacting on the impact component (8).



Description

[0001] The present invention relates to a child safety seat and, more particularly, to a child safety seat for use in a vehicle, the child safety seat being designed to increase the level of protection provided to a child seated in the child safety seat. The child safety seat is designed to offer improved protection in various crash configurations, in particular in crash configurations involving a side impact.

[0002] Many conventional child safety seats are designed to provide optimized protection in frontal crash configurations. About 25 % of all crashes, however, occur from the side. Injuries received in side impact crashes are generally more severe than those typically received in front crashes. It is estimated that up to 30 % of all fatalities are a result of side impact crashes. As a result, there is a great need for effective and reliable side impact protection in child safety seats.

[0003] Previous attempts at improving the side impact protection of child safety seats suffer from various drawbacks. In one attempt cushion elements have been attached to the interior of the head rest of a child safety seat. This results in improved protection of the head of a child only. The protection of other parts of the child's body, such as the child's torso, is not improved by these cushion elements. In another attempt, large damping components have been attached to the exterior of a child safety seat. While these damping components may significantly improve the side impact protection of the respective child safety seat, they increase the overall dimensions of the child safety seat. In many situations, for example in small vehicles, this might turn out to be a problem. In yet another attempt, adjustable protective elements have been added to a child safety seat whose configuration can be adapted to various factors. To achieve optimal side impact protection it has to be ensured that the adjustable protective elements of these child safety seats are always correctly configured which is not a trivial task.

[0004] As a result, most of the previous attempts at improving the side impact protection of child safety seats are associated with disadvantages such as shortcomings with respect to their ease of use. In addition, in many of these child safety seats the resulting protective effect of the child safety seat in a side crash is unsatisfactory and insufficient.

[0005] Therefore, it is an object of the present invention to provide a child safety seat which offers improved side impact protection to a child sitting in the child safety seat.

[0006] This object is solved by the child safety seat with the features of claim 1. Advantageous embodiments of the present invention are indicated in the dependent claims.

[0007] The child safety seat for a vehicle in accordance with embodiments of the invention comprises an outer shell enclosing a seating area for a child and a protective element. The protective element comprises a housing

component and an impact component, wherein the housing component is embedded into the outer shell and the impact component is mounted to the housing component, is configured to be enclosed at least partially by the housing component, and is configured to protrude laterally from the outer shell in a direction facing away from the seating area.

[0008] In accordance with embodiments of the invention, by embedding the housing component of the protective element into the outer shell of the child safety seat the space required by the protective element can be minimized. Preferably, the housing component does not protrude from the outer shell. When the housing component is embedded into the outer shell and the impact component is mounted to the housing component and is enclosed at least partially by the housing component, the impact component is also at least partially embedded or sunk into the outer shell and therefore does not protrude fully from the outer shell. As a result, an impact component of a given size which would require a certain amount of space if mounted directly to the outer shell, requires less space when mounted to the housing component.

[0009] In the child safety seat in accordance with embodiments of the invention, the housing component or the impact component preferably comprises a deformable region adapted to cushion forces impacting on the impact component.

[0010] Such a deformable region allows the housing component or the impact component to be deformed by a force acting on the impact component. When the deformable region is being deformed, impact energy will be absorbed and therefore, during a side crash of the vehicle carrying the child safety seat of the invention, the impact on the child safety seat will be cushioned. Preferably, the deformable region is configured to be deformed plastically or elastically. If the deformable region is configured to be deformed plastically, impact energy will be converted into heat when the deformable region is being deformed. If the deformable region is configured to be deformed elastically, impact energy will be converted into potential energy which is temporarily stored in the deformed deformable region and will eventually be converted back into kinetic energy as the deformed deformable region returns to its original shape. Advantageously, the housing component comprises a first deformable region and the impact component comprises a second deformable region. By adjusting the properties of the second deformable region to the properties of the first deformable region the cushioning effect of the protective element can be maximized.

[0011] Advantageously, in accordance with embodiments, the deformable region of the impact component of the protective element of the child safety seat of the invention comprises a plurality of zones of varying compressibility. This allows the cushioning effect of the protective element to be adjusted to various factors, such as the distance between the child safety seat and an adjacent door of the vehicle.

[0012] The housing component of the protective element of the child safety seat of the invention preferably comprises a compressible side wall. Impact energy can then be absorbed by compression of the compressible side wall. The compressible side wall has a double function: on the one hand, as a structural component of the housing component to which the impact component is mounted, it allows the impact component to be mounted to the outer shell of the child safety seat. On the other hand, since it is compressible, it allows impact energy to be absorbed by the protective element. Advantageously, the housing component comprises a harmonica type side wall.

[0013] The compressible side wall of the housing component of the protective element of the child safety seat of the invention preferably comprises apertures. Providing the compressible side wall with apertures is a convenient way of making the compressible side wall compressible. Furthermore, by providing the compressible side wall of the housing component with apertures the weight of the housing component can be reduced.

[0014] In the child safety seat of the invention, the housing component is preferably supported by a fixed bearing. This fixed bearing allows impact forces to be guided into a structurally stable part of the child safety seat.

[0015] The impact component of the protective element of the child safety seat of the invention is preferably configured to be transferred between a rest position and a functioning position. Then the impact component can be disposed either in the functioning position or in the rest position.

[0016] Consequently, in accordance with embodiments, the protective element can adopt two distinct configurations: a first configuration with the impact component disposed in the rest position and a second configuration with the impact component disposed in the functioning position. Providing two distinct configurations for the protective element makes it easier to adapt the protective effect of the protective element to specific needs and to reduce the space required by the protective element.

[0017] In the child safety seat in accordance with embodiments of the invention, the impact component of the protective element is preferably configured to protrude further from the outer shell when disposed in the functioning position than when disposed in the rest position. Preferably, the impact component is configured not to protrude from the outer shell when disposed in the rest position. As a result, when the impact component is disposed in the functioning position the protective effect of the protective element will be maximized. In addition, when the impact component is disposed in the rest position the space required by the protective element may be minimized. Therefore, in a child safety seat in accordance with in accordance with embodiments the invention which comprises more than one protective element, it might be advantageous to transfer only some of these

protective elements to the functioning position while keeping the remaining protective elements in the rest position. In particular, it might be advantageous to dispose those protective elements in the functioning position that

5 face a nearby door of the vehicle carrying the child safety seat and to dispose the protective elements facing away from this door in the rest position. In this way, the side of the child safety seat facing the door will be optimally cushioned whereas the amount of space required by the opposite side of the child safety seat can be kept small. If for some reasons it is desirable to cushion both sides of the child safety seat, for example in order to protect a passenger sitting on the seat next to the child safety seat, the impact components of the protective elements on 10 both sides of the child safety seat should be disposed in the functioning position.

[0018] The impact component and the housing component of the protective element of the child safety seat of the invention are preferably configured to achieve 15 cushioning of forces impacting on the impact component by transferring the impact component from the functioning position towards the rest position. This cushioning of forces might be achieved by providing for friction as the impact component is transferred from the functioning position towards the rest position. Then during the transfer of the impact component from the functioning position towards the rest position impact energy will be converted into heat.

[0019] In the child safety seat of the invention, the impact component of the protective element is preferably 20 configured to protrude permanently from the outer shell. By having the impact component protrude permanently from the outer shell, the design of the protective element can be simplified. Furthermore, misuse can be avoided 25 since an impact component protruding permanently from the outer shell will always be ready to cushion impact forces.

[0020] The outer shell of the child safety seat of the invention preferably comprises a side wing and the housing component is preferably embedded into the side wing. The side wing itself provides for improved side impact protection by shielding a child sitting in the child safety seat from lateral impacts. This protective effect is 30 enhanced by the protective element whose housing component is embedded into the side wing. When the housing component of the protective element is embedded into the side wing, forces acting laterally on the side wing can be cushioned by the protective element. As a result, the side impact forces reaching the child will be reduced.

[0021] The outer shell of the child safety seat of the invention preferably comprises a base portion and the housing component is preferably embedded into the base portion. By embedding the housing component into the base portion of the child safety seat, the protective 35 element can be provided in a low position on the child safety seat, near the hip area of a child sitting in the child safety seat. Impact forces transferred from the protective element to the child safety seat and from the child safety

seat to the child can then be easily guided towards the hip area of the child. This is advantageous since the forces will then be guided to a robust part of the child's body.

[0022] The child safety seat of the invention preferably comprises a plurality of protective elements. Advantageously, protective elements are mounted to both sides of the child safety seat. Preferably, at least two protective elements are mounted to each side of the child safety seat with, on each side, at least one protective element positioned in the upper half of the child safety seat and another protective element positioned in the lower half of the child safety seat. Advantageously, a protective element positioned in the upper half of the child safety seat is mounted to a side wing of the child safety seat and a protective element positioned in the lower half of the child safety seat is mounted to a base portion of the child safety seat.

[0023] In the child safety seat of the invention, the housing component of the protective element is preferably integrally formed with the outer shell. In this way, the production process of the child safety seat of the invention can be simplified. Furthermore, the weight of the child safety seat can be reduced and the structural complexity of the child safety seat can be minimized.

[0024] The impact component of the protective element of the child safety seat of the invention preferably comprises a rigid body molded from a thermoplastic material. By molding the rigid body from a thermoplastic material the weight and the production costs of the impact component can be kept low. Furthermore, the rigid body can be conveniently configured to resist high impact forces without being damaged.

[0025] Preferably, the rigid body of the impact component of the protective element of the child safety seat of the invention comprises a screw thread. This screw thread allows a rotational movement of the impact component to be transferred to a linear movement. Advantageously, the screw thread is configured to allow the impact component to be transferred between the rest position and the functioning position by rotating the impact component. The impact component can then be easily transferred between the rest position and the functioning position without application of high forces.

[0026] In the child safety seat in accordance with embodiments of the invention, the housing component of the protective element preferably comprises a flange configured to rest on the outer shell. With this flange the housing component can be firmly mounted to the outer shell of the child safety seat. Impact forces acting on the impact component which are transferred from the impact component to the housing component can then be safely and reliably guided into the outer shell of the child safety seat.

[0027] Specific embodiments of the invention will now be described by way of example only and with reference to the accompanying drawings, in which:

Figure 1a is a perspective view of a child safety seat

in accordance with a first embodiment of the invention with a child seated in the child safety seat;

5 Figure 1 b is a side view of the child safety seat of Figure 1 a;

10 Figure 2 is a side view of a child safety seat in accordance with a second embodiment of the invention;

15 Figure 3 is a detail of a child safety seat in accordance with another embodiment of the invention;

20 Figure 4a is a side view of a protective element of a child safety seat in accordance with another embodiment of the invention;

25 Figure 4b is a side view of a protective element of a child safety seat in accordance with another embodiment of the invention;

30 Figure 4c is a side view of a protective element of a child safety seat in accordance with another embodiment of the invention;

35 Figure 4d is a side view of a protective element of a child safety seat in accordance with another embodiment of the invention;

40 Figure 5 is a detail of a child safety seat in accordance with another embodiment of the invention;

45 Figure 6 is a detail of a child safety seat in accordance with another embodiment of the invention; and

50 Figure 7 is a detail of a child safety seat in accordance with another embodiment of the invention.

[0028] Figure 1a shows a child safety seat 1 for transporting a child 4 in a vehicle in accordance with a first embodiment of the invention. The child safety seat 1 comprises an outer shell 2 which encloses a seating area 3 for a child 4. The outer shell 2 comprises a back rest 103 which comprises side wings 13. The outer shell 2 furthermore comprises a base portion 14. In addition, the child safety seat 1 comprises a head rest 6 which is mounted to the back rest 103. The child 4 sits on the base portion 14 and leans against the back rest 103 with the child's 4 head positioned on the head rest 6. The side wings 13 are configured to enclose the child's 4 torso on both sides. The child safety seat 1 furthermore comprises two protective elements 5 which are mounted to the side wings 13. In Figure 1 a only the protective element 5 mounted

to the left side wing 13 is visible since the protective element 5 mounted to the right side wing 13 is hidden by the right side wing 13. The protective elements 5 are attached to the upper half of the side wings 13 and are positioned in the vicinity of the child's head and shoulders. The protective elements 5 protrude laterally from the side wings 13 and, since the side wings 13 are part of the outer shell 2, from the outer shell 2.

[0029] Conventionally, for transporting a child in a vehicle a child safety seat is mounted to one of the seats of the vehicle. Therefore, when installed in a vehicle, a child safety seat is usually positioned in close proximity to one of the doors of the vehicle. In case of a side crash of a vehicle carrying a child safety seat, the child safety seat will therefore usually impact on one of the doors of the vehicle. If this impact is severe, the child sitting in the child safety seat may get injured.

[0030] Since in the child safety seat 1 of the invention the protective elements 5 protrude laterally from the outer shell 2, in case of a side crash of the vehicle carrying the child safety seat 1 the protective element 5 facing the nearby door of the vehicle will be the first component of the child safety seat 1 that hits the vehicle. Therefore, the protective elements 5 may be used to control the dynamics of the impact of the child safety seat 1 on the vehicle at a very early stage.

[0031] Figure 1b shows a side view of the child safety seat of Figure 1 a. This view shows that the protective element 5 covers a large part of the side wing 13. Therefore, forces impacting on the protective element 5 which are transferred from the protective element 5 to the side wing 13 are distributed over a large area of the side wing 13. As a result, the occurrence of high peak forces acting on the side wing 13 can be avoided. This is advantageous since such high peak forces might damage the side wing 13 and result in severe injuries of the child 4.

[0032] Figure 2 shows a side view of a child safety seat 1 in accordance with a second embodiment of the invention. This child safety seat 1 differs from the child safety seat of Figures 1a and 1b in that it comprises two protective elements on each side of the child safety seat. In particular, as shown in Figure 2, the child safety seat 1 comprises a first protective element 5a which is mounted to the side wing 13 and a second protective element 5b which is mounted to the base portion 14. Figure 2 only shows the left side of the child safety seat 1, therefore only two protective elements are visible. Two additional protective elements, which are not visible in Figure 2, are attached to the right side of the child safety seat 1. By providing two protective elements on each side of the child safety seat 1 the potential area of contact between the child safety seat 1 and the vehicle can be increased. The first protective element 5a and the second protective element 5b constitute two load paths to guide impact forces to the outer shell 2 during a side crash. By providing two load paths the distribution of impact forces across the outer shell 2 can be improved.

[0033] The protective elements 5 of the child safety

seat 1 of Figures 1 a and 1 b and the protective elements 5a and 5b of the child safety seat 1 of Figure 2 are preferably configured to be transferred between a rest position and a functioning position. Advantageously, the protective elements are configured to protrude further from the outer shell of the child safety seat when disposed in the functioning position than when disposed in the rest position. The protective elements 5, 5a, 5b might be configured to protrude permanently from the outer shell 2 of the child safety seat 1.

[0034] Figure 3 is a partial sectional view of a protective element 5 of a child safety seat in accordance with a preferred embodiment of the invention. Figure 3 shows a section of the outer shell 2 of a child safety seat comprising a protective element 5. Protective element 5 comprises a housing component 7 and an impact component 8. The housing component 7 is embedded into the outer shell 2 of the child safety seat. In particular, the outer shell 2 comprises an opening which is configured to receive the housing component 7. The housing component 7 is cup-shaped and comprises a compressible side wall 10 and a bottom area 101. Preferably, the bottom area 101 is circular. The compressible side wall 10 comprises a plurality of apertures 11. In the embodiment of Figure 3, the apertures 11 are oval holes. The apertures 11 are shaped and arranged to allow the housing component 7 to be compressed and to extend in the directions indicated by arrow 16. The compressible side wall 10 of the housing component 7 constitutes a deformable region 9. The bottom area 101 of the housing component 7 is supported by a fixed bearing 12. The housing component furthermore comprises an internal thread 7a.

[0035] The impact component 8 comprises a top portion 8a and a bottom portion 8b. The top portion 8a is mounted on top of the bottom portion 8b. As shown in Figure 3, the top portion 8a is wider in diameter than the bottom portion 8b. Preferably, the top portion 8a is integrally molded with the bottom portion 8b. The bottom portion 8b is essentially cylindrical and comprises an external thread 8c. The external thread 8c of the impact component 8 is configured to work together with the internal thread 7a of the housing component to build a screw thread. With this screw thread the impact component 8 can be extended from the housing component 7 by rotating the impact component 8 in a first direction and can be retracted into the housing component 7 by rotating the impact component 8 in a second direction opposite to the first direction. Preferably, the first direction is counterclockwise, whereas the second direction is clockwise.

[0036] When the impact component 8 is retracted completely into the housing component 7, the outer edge of the top portion 8a rests on the outer shell 2. In this rest position of the impact component 8 a force acting on the impact component 8 in the direction indicated by arrow 20 cannot push the impact component further into the outer shell 2. When, starting from the rest position, the impact component 8 is rotated in the first direction, the impact component 8 will be gradually extracted from the

housing component 7. Preferably, the protective element 5 comprises a stop unit which prevents the impact component 8 from being extracted completely from the housing component 7. Advantageously, the stop unit is provided on the impact component 8. The stop unit defines a position of the impact component 8 in which the impact component 8 protrudes maximally from the housing component 7. This position is also referred to as functioning position. In the embodiment of Figure 3 the impact component 8 can adopt a continuum of intermediate positions between the rest position (fully retracted) and the functioning position (fully extended). Figure 3 shows one of these intermediate positions.

[0037] When the impact component 8 is disposed in the functioning position (or in the intermediate position of Figure 3), a force acting on the impact component 8 in the direction indicated by arrow 20 will be transferred from the top portion 8a of the impact component 8 via the bottom portion 8b and the external thread 8c to the internal thread 7a of the housing component 7. Since the internal thread 7a is positioned near the top edge of the compressible side wall 10 of the housing component 7, the force will then be transferred from the internal thread 7a to the compressible side wall 10. From the compressible side wall 10 the force will finally be transferred into the fixed bearing 12 via the bottom area 101. Since the compressible side wall 10 is compressible, this flow of forces will result in a compression of the compressible side wall 10 of the housing component 7. Consequently, the impact component 8 will be pushed into the outer shell 2 of the child safety seat. As a result, when the impact component 8 is disposed in the functioning position, a force impacting on the impact position 8 can push the impact component 8 into the outer shell 2. During this process, compressing the compressible side wall 10 will absorb impact energy and therefore the impact on the child safety seat will be cushioned.

[0038] Depending on the dimensions and design of the impact component 8 and the housing component 7 the impact component 8 can be pushed into the outer shell 2 until the top portion 8a of the impact component 8 contacts the outer shell 2, or until the bottom portion 8b of the impact component 8 hits the bottom area 101 of the housing component 7, or until the compressible side wall 10 of the housing component 7 is completely compressed. In the first case a force impacting on the impact component 8 will finally be transferred to the child safety seat via the outer shell 2, whereas in the second and third case the force will finally be transferred to the child safety seat via the fixed bearing 12.

[0039] Figures 4a-d show additional variants of protective elements 5 in accordance with further embodiments of the invention. In the embodiment of Figure 4a the housing component 7 of the protective element 5 comprises a plurality of triangular apertures 11. In the embodiment of Figure 4b the housing component 7 of the protective element 5 comprises a plurality of curved apertures 11. In the embodiment of Figure 4c the housing component

7 of the protective element 5 comprises a plurality of oval apertures 11. The oval apertures 11 are arranged in a regular pattern. In the embodiment of Figure 4d the housing component 7 of the protective element 5 comprises one or more apertures 11 which spiral around the side wall of the housing component 7. In all four embodiments of Figures 4a-d the side wall 10 of the housing component 7 of the protective element 5 is made compressible by the provision of apertures 11.

[0040] Figure 5 shows a protective element 5 of a child safety seat in accordance with another embodiment of the invention. In this embodiment the side wall 111 of the housing component 7 of the protective element 5 is not compressible but rigid. Preferably, the side wall 111 of the housing component 7 does not comprise any apertures. The housing component 7 is again embedded into the outer shell 2 of the child safety seat. In this embodiment, however, the upper edge of the housing component 7 comprises a flange 112 which rests on the outer shell 2. Furthermore, in the vicinity of the opening in the outer shell 2 which receives the housing component 7 the outer shell 2 is supported by fixed bearings 12. The bottom area 101 of the housing component 7 is also supported by a fixed bearing 12.

[0041] The impact component 8 of the protective element 5 is mounted to the housing component 7 as described in the context of Figure 3. In the embodiment of Figure 5, however, the impact component 8 comprises a deformable region 9. The deformable region 9 allows the impact component 8 to be compressed and to expand again in the directions indicated by arrow 17. Preferably, the deformable region 9 comprises a foam-like structure comprising thermoplastics or alternative structural elements with damping characteristics. The thermoplastics preferably comprise crosslinked polyethylene (XPE), expanded polystyrene (EPS), expanded polypropylene (EPP), or expanded polyethylene (EPE). The deformable region 9 of the impact component 8 may also be implemented as described in the context of Figures 3 and 4a-d for the deformable region of the housing component, i.e. the impact component 8 may be made compressible by providing the impact component 8 with apertures. Preferably, the apertures are positioned in a side wall of the bottom portion 8b of the impact component 8.

[0042] The impact component 8 is preferably configured to be transferred between a functioning position and a rest position as described for the impact component 8 of Figure 3. When the impact component 8 is disposed in the functioning position (or in the intermediate position of Figure 5), a force acting on the impact component 8 in the direction indicated by arrow 20 will be transferred from the top portion 8a of the impact component 8 via the bottom portion 8b and the external thread 8c to the internal thread 7a of the housing component 7. From the internal thread 7a of the housing component 7 a first part of the force will be transferred to the outer shell 2 via the flange 112 of the housing component 7 and from the outer shell 2 to the fixed bearings 12 that support the outer

shell 2. A second part of the force will be transferred from the internal thread 7a to the bottom area 101 of the housing component 7 via the side wall 111 of the housing component 7 and from the bottom area 101 to the fixed bearing 12 that supports the bottom area 101. This flow of forces will result in a compression of the deformable region 9 of the impact component 8. Compressing the deformable region 9 of the impact component 8 will absorb impact energy and therefore the impact on the child safety seat will be cushioned.

[0043] In a preferred embodiment of the invention, the deformable region 9 of the impact component 8 comprises a plurality of zones of varying compressibility. In particular, the impact component 8 may comprise a plurality of zones of varying compressibility with each zone exhibiting a constant compressibility and with the compressibility of each zone differing from the compressibility of the other zones. Generally, the compressibility of a zone correlates with the hardness or rigidity of this zone. A highly compressible zone will be softer than a zone which is less compressible. Advantageously, in the impact component 8 of the protective element 5 of Figure 5, the zones of varying compressibility are stacked on top of each other. Therefore, the impact component 8 comprises a topmost compressible zone positioned at or near the top of the impact component 8, a bottommost compressible zone positioned at or near the bottom of the impact component 8, and a plurality of other compressible zones placed between the topmost compressible zone and the bottommost compressible zone. Advantageously, the compressibility of the compressible zones increases from top to bottom. Therefore, the topmost compressible zone is preferably more rigid, i.e. less compressible, than the rest of the compressible zones. In addition, the bottommost compressible zone is preferably softer, i.e. more compressible, than the rest of the compressible zones. The compressibility of the impact component 8 might increase from top to bottom stepwise or continually. Preferably, the compressibility of the impact component 8 increases exponentially. With such a compressibility profile of the impact component 8 of the protective element 5 the amount of energy which is absorbed when the impact component 8 is pushed into the outer shell 2 can be kept essentially constant regardless of how far the impact component 8 extends from the outer shell 2.

[0044] In the configuration of the protective element 5 shown in Figure 5, for example, only a small fraction of the impact component 8 protrudes from the outer shell 2. When the impact component 8 is compressed by a force acting in the direction of arrow 20, only this small fraction of the impact component 8 will be compressed. Since the upper part of the impact component 8 is quite rigid (i.e. is hard to compress), however, compressing this part of the impact component 8 will require a high force. Therefore, although the impact component 8 does not have to be pushed far to bring the top portion 8a of the impact component 8 into contact with the outer shell

2, a high force will be required to push the impact component 8.

[0045] When the impact component 8 protrudes further from the outer shell 2 than shown in Figure 5, a larger fraction of the impact component 8 will be compressed. The fraction of the impact component 8 protruding from the outer shell 2 will then comprise deformable zones which are softer (i.e. more compressible) than the compressible zones protruding from the outer shell 2 in the configuration of Figure 5. Therefore, the force required to compress the impact component 8 will be smaller. Consequently, the impact component 8 will have to be pushed further to bring the top portion 8a of the impact component 8 into contact with the outer shell 2 than in Figure 5. Since the force required to push in the impact component 8, however, is smaller than the force required in the configuration of Figure 5, the work required to push in the impact component 8 might be similar in the two configurations.

[0046] Therefore, the amount of energy which is absorbed when the impact component 8 is pushed into the outer shell 2 is preferably independent of how far the impact component 8 originally protrudes from the outer shell 2. This is particularly advantageous, since in this way it can be ensured that the protective element is always configured to absorb impact energy in a side crash.

[0047] Figure 6 shows a protective element 5 of a child safety seat in accordance with another embodiment of the invention. In many aspects, this embodiment is similar to the embodiment of Figure 5. The side wall 111 of the housing component 7 of the protective element 5 is not compressible but rigid and the upper edge of the housing component 7 comprises a flange 112 which rests on the outer shell 2. The protective element 5 of Figure 6 differs from the protective element 5 of Figure 5 mainly in the way the impact component 8 is mounted to the housing component 7. In the embodiment of Figure 6, the impact component 8 is configured to be pushed into the housing component by a force acting on the impact component 8 in the direction of arrow 20. Preferably, the external thread 8c of the impact component 8 and the internal thread 7a of the housing component 7 are designed to allow the ridges of the external thread 8c to be pushed past the ridges of the internal thread 7a. Therefore, when the impact component 8 is pushed into the housing component 7 the bottom portion 8b of the impact component 8 will be compressed laterally and expand again repeatedly. Laterally compressing the bottom portion 8b of the impact component 8 will absorb impact energy and therefore the impact on the child safety seat will be cushioned as the impact component 8 is pushed into the housing component 7. Generally, the impact component 8 will not be pushed into the housing component 7 at a constant speed but will be pushed in in steps instead. This stepwise movement is indicated by arrows 18 in Figure 6.

[0048] Instead of an external thread 8c and an internal thread 7b the protective element 5 may comprise a catch mechanism to connect the impact component 8 to the

housing component 7. This catch mechanism preferably allows the impact component 8 to be pushed into and to be pulled out of the housing component 7. Advantageously, the bottom portion 8b of the impact component 8 comprises a plurality of circular grooves instead of the external thread 8c. The housing component 7 preferably comprises a circular ridge instead of the internal thread 7a. The circular ridge is configured to mesh with the circular grooves of the impact component 8. Rotating the impact component 8 about its central axis will then not result in transfer of the impact component 8 between the rest position and the functioning position. Instead, to transfer the impact component 8 between the rest position and the functioning position the impact component 8 has to be pushed into the housing component 7 or be pulled out of the housing component 7. By providing the impact component 8 and the housing component 7 with a catch mechanism other than a screw thread, impact component 8 and housing component 7 no longer need to be circular in cross-section. The cross-section of the protective element 5 can then be freely designed. In particular, it is possible to adapt the shape of the protective element 5 to the shape of the child safety seat. For a protective element 5 attached to the base portion of a child safety seat, for instance, the shape of the protective element 5 could be adapted to the shape of the base portion and, for a protective element 5 attached to the side wing of a child safety seat, the shape of the protective element 5 could be adapted to the shape of the side wing.

[0049] Figure 7 shows a protective element 5 of a child safety seat in accordance with another embodiment of the invention. In this embodiment the upper edge of the housing component 7 again comprises a flange 112 which rests on the outer shell 2. The outer shell 2 is configured to be resilient or elastic in the vicinity of the protective element 5. As shown in Figure 7, the child safety seat comprises elastic elements 15 which couple the outer shell 2 to fixed bearings 12. When the section of the outer shell 2 shown in Figure 7 is pushed downwards towards the fixed bearings 12, the elastic elements 15 are being compressed. When the force on the outer shell 2 is reduced, the elastic elements 15 will push the outer shell 2 back towards its original position. This is indicated by arrow 19 in Figure 7. As an alternative to the elastic elements 15, the outer shell 2 itself could be configured to exhibit a high degree of resilience. Then the outer shell 2 will by itself return to its original position after it has been pushed downwards.

[0050] In the embodiment of Figure 7 a force acting on the impact component 8 in the direction of arrow 20 will be transferred from the top portion 8a of the impact component 8 to the bottom portion 8b of the impact component 8 and from the bottom portion 8b to the outer shell 2 via the external thread 8c, the internal thread 7a, and the flange 112. As a result, the impact component 8, the housing component 7, and the outer shell 2 will be pushed downwards, deforming the outer shell 2 and compressing the elastic elements 15. Deforming the outer shell 2 and

compressing the elastic elements 15 will absorb impact energy and therefore the impact on the child safety seat will be cushioned. Since in this embodiment of the invention there is no flow of forces along the side wall and the bottom area of the housing component 7, side wall and bottom area might be omitted. The resulting housing component is preferably ring-shaped and is advantageously integrally formed with the outer shell 2.

[0051] Several aspects of the embodiments of the invention described in the context of Figures 3-7 might advantageously be combined in a single embodiment. In particular, in the protective elements of Figures 3, 6, and 7 the impact component 8 might advantageously comprise a deformable region as described for the impact component of Figure 5. In the protective elements of Figures 3, 5, and 7 the screw thread comprising an external thread and an internal thread might be replaced by a catch mechanism as described for the protective element of Figure 6. In the protective elements of Figures 3, 5, and 6 the outer shell might comprise a resilient region as described for the impact component of Figure 7. The resulting protective element will be particularly suitable for cushioning impact forces acting on a child safety seat.

25 List of reference numerals

[0052]

1	child safety seat
2	outer shell
3	seating area
4	child
5	protective element
5a	first protective element
35 5b	second protective element
6	head rest
7	housing component
7a	internal thread
8	impact component
40 8a	top portion of impact component 8
8b	bottom portion of impact component 8
9	deformable region
10	compressible element
11	apertures
45 12	fixed bearing
13	side wing
14	base portion
15	elastic element
16	arrow
50 17	arrow
18	arrow
19	arrow
20	arrow
101	bottom area
55 103	back rest
111	side wall
112	flange

Claims

1. A child safety seat (1) for a vehicle comprising

- an outer shell (2) enclosing a seating area (3) for a child (4),
- a protective element (5), the protective element (5) comprising a housing component (7) and an impact component (8), and
- elastic elements (15) coupling the outer shell (2) to fixed bearings (12),

wherein the housing component (7) comprises a flange (112) configured to rest on the outer shell (2), for firmly mounting the housing component (7) to the outer shell (2) such that impact forces acting on the impact component (8) are transferred from the impact component (8) to the housing component (7) and are then guided via the flange (112) into the outer shell (2) of the child safety seat (1), deforming the outer shell (2) and compressing the elastic elements (15), wherein the housing component (7) is embedded into the outer shell (2),

wherein the impact component (8) is mounted to the housing component (7), is configured to be enclosed at least partially by the housing component (7) and is configured to protrude laterally from the outer shell (2) in a direction facing away from the seating area (3), and

the fixed bearing (12) allowing the impact forces to be guided into a structurally stable part of the child safety seat (1).

2. The child safety seat (1) of claim 1, wherein the impact component (8) is configured to be transferred from a rest position to a functioning position, and is configured to protrude further from the outer shell (2) when disposed in the functioning position than when disposed in the rest position.

3. The child safety seat (1) of claim 1 or claim 2, wherein the impact component (8) comprises a top portion (8a) and a bottom portion (8b), the top portion being mounted on top of the bottom portion and the top portion being wider in diameter than the bottom portion, the outer edge of the top portion resting on the outer shell (2), when the impact component is retracted completely into the housing component (7).

4. The child safety seat (1) of any one of the previous claims, wherein the impact component (8) comprises a deformable region (9) adapted to cushion forces impacting on the impact component (8) and wherein the deformable region (9) comprises a plurality of zones of varying compressibility.

5. The child safety seat (1) of any one of the previous claims, wherein the deformable region (9) comprises

6. The child safety seat (1) of any one of the previous claims, wherein the impact component (8) comprises a rigid body molded from a thermoplastic material.

7. The child safety seat (1) of claim 6, wherein the rigid body comprises a screw thread (8c).

8. The child safety seat (1) of any one of claims 1 to 6, wherein the impact component (8) comprises catch mechanism.

9. The child safety seat (1) of any one of the previous claims, wherein at least two protective elements (5) are mounted to each side of the child safety seat (1) with, on each side, at least one protective element (5) positioned in the upper half of the child safety seat (1) and another protective element (5) positioned in the lower half of the child safety seat (1).

10. A child safety seat (1) for a vehicle comprising

- an outer shell (2) enclosing a seating area (3) for a child (4), the outer shell (2) comprising a resilient region,
- a protective element (5), the protective element (5) comprising a housing component (7) and an impact component (8) and
- fixed bearings (12),

wherein the housing component (7) comprises a flange (112) configured to rest on the outer shell (2), for firmly mounting the housing component (7) to the outer shell (2) such that impact forces acting on the impact component (8) are transferred from the impact component (8) to the housing component (7) and are then guided via the flange (112) into the outer shell (2) of the child safety seat (1), deforming the resilient region of the outer shell (2), and wherein the housing component (7) is embedded into the outer shell (2),

wherein the impact component (8) is mounted to the housing component (7), is configured to be enclosed at least partially by the housing component (7) and is configured to protrude laterally from the outer shell (2) in a direction facing away from the seating area (3), and

the fixed bearing (12) allowing the impact forces to be guided into a structurally stable part of the child safety seat (1).

11. The child safety seat (1) of claim 10, wherein the resilient region of the outer shell (2) is adapted to return to its original position when the impact force acting on the impact component (8) is reduced.




Fig. 1a




Fig. 1b




Fig. 2




Fig. 3




Fig. 4a




Fig. 4b




Fig. 4c




Fig. 4d




Fig. 5




Fig. 6




Fig. 7



EUROPEAN SEARCH REPORT

Application Number

EP 21 15 7290

5

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
10 A	EP 2 570 299 A1 (BRITAX ROEMER KINDERSICHERHEIT [DE]) 20 March 2013 (2013-03-20) * the whole document *	1-11	INV. B60N2/28
15 A	EP 2 275 303 A1 (BRITAX ROEMER KINDERSICHERHEIT [DE]) 19 January 2011 (2011-01-19) * paragraphs [0016], [0045] - [0047]; figure 11 *	1-11	
20 A	US 2010/026064 A1 (MARDEN ANDREW W [US] ET AL) 4 February 2010 (2010-02-04) * paragraphs [0065] - [0073]; figures 13-16 *	1-11	
25			
30			TECHNICAL FIELDS SEARCHED (IPC)
35			B60N
40			
45			
50 2	The present search report has been drawn up for all claims		
55	Place of search Munich	Date of completion of the search 18 June 2021	Examiner Lotz, Klaus-Dieter
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			
T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.

EP 21 15 7290

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

18-06-2021

10	Patent document cited in search report	Publication date	Patent family member(s)		Publication date				
15	EP 2570299	A1 20-03-2013	AU 2012216718	A1 28-03-2013					
			CA 2789617	A1 13-03-2013					
			CN 103072497	A 01-05-2013					
			EP 2570299	A1 20-03-2013					
			ES 2538327	T3 19-06-2015					
			KR 20130029030	A 21-03-2013					
			US 2013062917	A1 14-03-2013					
20	EP 2275303	A1 19-01-2011	CN 101954873	A 26-01-2011					
			EP 2275303	A1 19-01-2011					
			EP 2578444	A1 10-04-2013					
			EP 2578445	A1 10-04-2013					
			ES 2426225	T3 22-10-2013					
			ES 2616070	T3 09-06-2017					
			ES 2616072	T3 09-06-2017					
			US 2011012398	A1 20-01-2011					
			US 2013234479	A1 12-09-2013					

30	US 2010026064	A1 04-02-2010	AU 2008311740	A1 01-04-2010					
			BR PI0805813	A2 30-08-2011					
			CA 2701307	A1 04-02-2010					
			CN 101638065	A 03-02-2010					
			CN 103770675	A 07-05-2014					
			DK 2307241	T3 10-03-2014					
			EA 200900559	A1 29-10-2010					
			EP 2307241	A1 13-04-2011					
			ES 2452467	T3 01-04-2014					
			HK 1152279	A1 24-02-2012					
35			IL 198278	A 31-01-2013					
			JP 2010531274	A 24-09-2010					
			NZ 576263	A 30-11-2012					
			PL 2307241	T3 30-05-2014					
			PT 2307241	E 13-03-2014					
			US 2010026064	A1 04-02-2010					
			US 2010231012	A1 16-09-2010					
			WO 2010014122	A1 04-02-2010					

50									
55	EPO FORM P0459	For more details about this annex : see Official Journal of the European Patent Office, No. 12/82							