



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
06.10.2021 Bulletin 2021/40

(51) Int Cl.:
A63F 13/352 ^(2014.01) **A63F 13/60** ^(2014.01)
A63F 13/77 ^(2014.01)

(21) Application number: **20187377.5**

(22) Date of filing: **23.07.2020**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(72) Inventors:
• **MARES, Peter**
GX1 11AA Tradewinds (GI)
• **TURBATU, Cristina**
11300 Cadiz (ES)

(74) Representative: **Modiano, Gabriella Diana et al**
Modiano & Partners (DE)
Thierschstrasse 11
80538 München (DE)

(30) Priority: **30.03.2020 US 202016833893**

(71) Applicant: **Playtech Software Limited**
British Isles (IM)

(54) **A CONTENT AGGREGATION SYSTEM AND METHOD OF OPERATING THEREOF**

(57) The presently disclosed subject matter includes a computer-based content aggregation system and a computerized method for identifying a logical geographic location of a piece of content stored on a server. More

specifically, the proposed technique generates unique path identifier for each piece of content and enables to communicate data to the particular server, based on the unique path identifier.




Fig 4

Description**TECHNICAL FIELD**

[0001] The presently disclosed subject matter relates to a computerized content aggregation system, and more particularly, to a computerized gaming content aggregation system and methods of operating thereof.

BACKGROUND

[0002] In the industry of computerized games, a content aggregation system or platform, is a software or hardware system that provides a standardised protocol or application programming interface (API) that integrates various entities of the network, and assists them to communicate with each other through the content aggregation platform. Different remote game servers (RGSs) can be integrated into content aggregation system platforms. In turn, the content aggregation platform is usually integrated into multiple player management systems and gaming platforms that connect between client terminals to gaming creators and operators, and wallet management systems that support the gaming.

[0003] Content aggregation of this nature introduces a number of complexities at the aggregation platform level, for example, when multiple instances of the aggregation platform exist, and each has multiple instances of the same RGS connected to it potentially, in more than one geographic area. Moreover, the same content can be available from multiple instances of the same RGS across the multiple aggregation platform instances. Identifying the exact location of a particular content within a particular RGS that is connected to a particular instance of the aggregation platform currently involves many challenges. The problems compound even further when a single gaming operator or a casino is served by multiple different aggregation platforms that deliver the content to it.

[0004] Therefore, a simplified integration of content is desired.

GENERAL DESCRIPTION

[0005] According to one aspect of the presently disclosed subject matter there is provided A computer-based content aggregation system , comprising:

an aggregator aggregation platform (AAP);
 one or more aggregation platforms operatively communicating with the AAP, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform;
 at least one remote game server (RGS) configured for storing at least one piece of content and operatively communicating with a designated aggregation

platform of the one or more aggregation platforms, wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, wherein each of the at least one RGS is configured to:

associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content; and
 communicate the at least one associated content identifier and the RGS identifier to the designated aggregation platform;

wherein each of the at least one aggregation platform is configured to:

communicate to the AAP both the at least one content identifier and the RGS identifier received from each of the at least one RGS, and the aggregation identifier;

wherein the AAP is configured to generate for each of the stored at least one piece of content, a respective unique path identifier, based on the associated content identifier, the RGS identifier and the aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content, and

wherein usage of a generated unique path identifier, by the AAP, facilitates communicating data, that pertains to the piece of content identified by the generated unique path identifier.

[0006] In addition to the above features, the system according to this aspect of the presently disclosed subject matter can optionally comprise one or more of features (i) to (v) below, in any technically possible combination or permutation:

I. the AAP is further configured to:

operatively communicate with at least one external system; and
 communicate data that pertains to a specific piece of content stored on a particular RGS, from/to the at least one external system, based on the unique path identifier associated with the specific piece of content;

II. the AAP is further configured to send/receive data that pertains to a specific piece of content stored on a particular RGS to/from the AAP and the particular RGS, using the unique path identifier;

III. the piece of content is a game, and wherein the characteristics of the content include at least one selected from: operational parameters of the game, configuration characteristics of the game, configuration schema and configuration characteristics of the

game based on a configuration schema;

IV. wherein the at least one RGS is further configured to the receive updated configuration characteristics, based on the configuration schema, and to configure the schema, based on the updated configuration characteristics;

V. wherein the RGS identifier includes the RGS type and/or the RGS instance, and the AAP is further configured to communicate updated configuration characteristics, based on the RGS type and/or the RGS instance.

[0007] According to another aspect of the presently disclosed subject matter there is provided a computerized method for identifying a location of piece of content, comprising:

providing an aggregator aggregation platform (AAP), one or more aggregation platforms operatively communicating with the AAP, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform and at least one remote game server (RGS) configured for storing at least one piece of content and operatively communicating with a designated aggregation platform of the one or more aggregation platforms, wherein each of at least one RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, the method further comprising:

by a processor of each of the at least one RGS:

associating a content identifier for each of the stored at least one piece of content indicative of characteristics of the content; and communicating the at least one associated content identifier and the RGS identifier to a designated aggregation platform of one or more aggregation platforms;

by a processor of each of the at least one aggregation platform:

communicating to the AAP both the at least one associated content identifier and the RGS identifier received from each of the at least one RGS, and the aggregation identifier;

by a processor of the AAP:

generating a respective unique path identifier for each of the stored at least one piece of content, based on the associated unique content identifier, the unique RGS identifier, and the unique aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content, and using the generated unique path identifier, to fa-

cilitate communicating data, that pertains to the piece of content identified by the generated unique path identifier.

5 According to another aspect of the presently disclosed subject matter there is provided a computer-based content aggregation system, comprising:

10 an aggregator aggregation platform (AAP) comprising a processor; wherein the AAP is configured, by the processor, to:

operatively communicate with one or more aggregation platforms, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform, and wherein each of the one or more aggregation platforms is configured to operatively communicate with at least one remote game server (RGS), wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, and is configured for storing at least one piece of content, and to associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content; obtain from each of the one or more aggregation platforms:

(i) the associated aggregation identifier; (ii) the at least one associated RGS identifier of the at least one RGSs operatively communicating with the aggregation platform; and (iii) the at least one associated content identifier for each of the at least one piece of content stored in each of the at least one RGS that is operatively communicating with the respective aggregation platform;

generate a respective unique path identifier for each of the stored at least one piece of content, based on the obtained associated content identifier, the obtained RGS identifier and the obtained aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content; and use the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the generated unique path identifier.

55 **[0008]** In addition to the above features, the system according to this aspect of the presently disclosed subject matter can optionally comprise the feature below, in any technically possible combination or permutation:

wherein the AAP is further configured to obtain from each of the one or more aggregation platforms:

(iv) a configuration schema associated with the obtained content; and

based on the obtained data and the generated unique path identifier, the AAP is further configured to:

(a) provide data on at least one piece of content and its associated configuration schema;

(b) receive updated configuration characteristics, based on the configuration schema; and

(c) apply the updated configuration characteristics.

[0009] According to another aspect of the presently disclosed subject matter there is provided a computerized method for identifying a location of piece of content, comprising:

by a processor of an aggregator aggregation platform (AAP) operatively communicating with one or more aggregation platforms, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform, and wherein each of the one or more aggregation platforms is configured to operatively communicate with at least one remote game server (RGS), wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, and is configured for storing at least one piece of content, and to associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content, the method comprising:

obtaining from each of the one or more aggregation platforms the associated aggregation identifier;

obtaining, through each of the at least one aggregation platform, the at least one RGS identifier;

obtaining, through each of the at least one aggregation platform and the at least one RGS, the at least one associated content identifier for each of the at least one piece of content stored in each of the at least one RGS;

generating a respective unique path identifier for each of the stored at least one piece of content, based on the obtained associated content identifier, the obtained RGS identifier and the obtained aggregation identifier for identifying a logical geographic location of each of the stored at least one piece of content; and

using the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the unique path identifier.

[0010] According to another aspect of the presently disclosed subject matter there is provided a non-transitory computer readable storage medium tangibly embodying a program of instructions that, when executed by a computer, cause the computer to perform a method for

identifying a location of piece of content, comprising:

providing an aggregator aggregation platform (AAP), one or more aggregation platforms operatively communicating with the AAP, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform and at least one remote game server (RGS) configured for storing at least one piece of content and operatively communicating with a designated aggregation platform of the one or more aggregation platforms, wherein each of at least one RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, the method further comprising:

by a processor of each of the at least one RGS:

associating a content identifier for each of the stored at least one piece of content indicative of characteristics of the content; and

communicating the at least one associated content identifier and the RGS identifier to a designated aggregation platform of one or more aggregation platforms;

by a processor of each of the at least one aggregation platform:

communicating to the AAP both the at least one associated content identifier and the RGS identifier received from each of the at least one RGS, and the aggregation identifier;

by a processor of the AAP:

generating a respective unique path identifier for each of the stored at least one piece of content, based on the associated unique content identifier, the unique RGS identifier, and the unique aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content, and

using the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the generated unique path identifier.

According to another aspect of the presently disclosed subject matter there is provided a non-transitory computer readable storage medium tangibly embodying a program of instructions that, when executed by a computer, cause the computer to perform method for identifying a location of piece of content, comprising:

by a processor of an aggregator aggregation platform (AAP) operatively communicating with one or more aggregation platforms, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform, and wherein each of the one or more aggregation platforms is configured

to operatively communicate with at least one remote game server (RGS), wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, and is configured for storing at least one piece of content, and to associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content, the method comprising:

obtaining from each of the one or more aggregation platforms the associated aggregation identifier;
 obtaining, through each of the at least one aggregation platform, the at least one RGS identifier;
 obtaining, through each of the at least one aggregation platform and the at least one RGS, the at least one associated content identifier for each of the at least one piece of content stored in each of the at least one RGS;
 generating a respective unique path identifier for each of the stored at least one piece of content, based on the obtained associated content identifier, the obtained RGS identifier and the obtained aggregation identifier for identifying a logical geographic location of each of the stored at least one piece of content; and
 using the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the unique path identifier.

[0011] The system, method and the non-transitory computer readable storage media disclosed herein according to various aspects, can optionally further comprise one or more of features (i) to (v) listed above, mutatis mutandis, in any technically possible combination or permutation.

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] In order to understand the invention and to see how it can be carried out in practice, embodiments will be described, by way of non-limiting examples, with reference to the accompanying drawings, in which:

Fig. 1 shows a high-level illustration of a gaming environment 100 in accordance with certain embodiments of the presently disclosed subject matter;

Fig. 2 illustrates a high-level functional block diagram of a gaming environment, in accordance with certain embodiments of the presently disclosed subject matter;

Fig. 3 illustrates a high-level functional block diagram of an integrated gaming environment, in accordance with certain embodiments of the presently disclosed subject matter;

Fig. 4 illustrates a generalized block diagram of a

gaming hierarchy in accordance with certain embodiments of the presently disclosed subject matter;

Fig. 5 illustrates a generalized flowchart of operations performed by entities in the gaming hierarchy, in accordance with certain embodiments of the presently disclosed subject matter;

Fig. 6 illustrates a flowchart of operations carried out by an aggregator aggregation platform (AAP) in accordance with certain embodiments of the presently disclosed subject matter; and

Fig. 7 illustrates a process of configuring configuration schema.

DETAILED DESCRIPTION

[0013] As apparent from the following discussions, and unless specifically stated otherwise, it is appreciated that throughout the specification discussions utilizing terms such as "communicating", "storing", "associating", "using", "generating", "providing", "discovering" or the like, refer to the action(s) and/or process(es) of a computer that manipulate and/or transform data into other data, said data represented as physical, such as electronic, quantities and/or said data representing the physical objects. The term "computer" should be expansively construed to cover any kind of hardware-based electronic device with data processing capabilities including, by way of non-limiting example, the gaming system disclosed in the present application.

[0014] The operations in accordance with the teachings herein may be performed by a computer specially constructed for the desired purposes, or by a general-purpose computer specially configured for the desired purpose by a computer program stored in a non-transitory computer-readable storage medium.

[0015] Gaming environments involve a large number of separate entities operating and communicating through a complex network and architecture. Content, such as games, are created by a content creator or content provider and are stored on Remote Gaming Servers (RGSs) around the world. A game can be stored on more than one RGS. A licensee of a casino, also to be referred to herein as an operator, can choose to operate one or more games by adding them to the operator's portfolio, while the games themselves are stored on a single RGS or multiple RGSs. Operation of the games is subject to various dynamic parameters and configurations, some of which are dictated by local legislation and some being determined or structured by the content creator, the licensee operator, or the RGS itself. In addition, the games can communicate with external systems, such as back-end and management systems of the licensee operators, player management systems, various analytic systems, and wallet management systems. As such, there is a constant communication of data to and from the content

stored on a particular RGS, e.g. the game, to other entities operating in the network.

[0016] A content aggregation system or platform provides a standardised protocol or API that integrates various entities of the network, and assists them to communicate with each other through the content aggregation platform. In order to simplify the effort needed to integrate different content providers to operators, an Aggregator Aggregation Platform (AAP) is created. The AAP aggregates numerous content aggregation systems (or platforms) in a hierarchical manner and implements a discovery process, after which the AAP generates a logical geographic coordinate system of content stored in the network. The logical geographic coordinate system assists the AAP to accurately identify a particular content stored on a particular RGS that communicates with the AAP through one of the aggregation platforms.

[0017] Bearing this in mind, attention is drawn to Fig. 1 which shows a high level illustration of a gaming environment 100 in accordance with certain embodiments of the presently disclosed subject matter.

[0018] Fig. 1 illustrates a specific example of a gaming environment with two aggregation platforms 102, each located in a different geographic location. One of the platforms is located in Europe, and the other is located in the East. An aggregation platform 102 is configured to implement a unified point of integration for several entities of the network, and provides an abstraction layer(s) between the various entities. As illustrated, aggregation platform 102 aggregates several different content providers (to be referred to hereinbelow also as Remote Game Servers (RGSs)), operators of the content, gaming system (GPAS) providing gaming functionalities, and wallet systems.

[0019] Each platform 102 illustrated in Fig. 1 implements a unified interface and aggregates several entities in the complex and dynamic network illustrated in Fig. 1 by operatively communicating with the entities. However, the two platforms 102 in Europe and in the East, do not communicate with each other. As such, content provider #3 that communicates with aggregation platform 102 East, and wishes to communicate with aggregation platform 102 and offer the games created by it to the operators of aggregation platform 102 Europe, cannot do so without a specific connection to the aggregation platform 102 Europe. The reverse applies to content provider #2. Hence, it may be advantageous to integrate, in a higher level, at an aggregator aggregation platform (AAP) layer, the services provided by each aggregation platform 102, in order that entities operating in the network may obtain easier access to all available services.

[0020] Before illustrating the aggregation of platforms 102 in the higher level of AAP, in order to better describe the functionality of an aggregation platform 102, attention is drawn to Fig. 2 illustrates a high level functional block diagram of the gaming environment 100, in accordance with certain embodiments of the presently disclosed subject matter.

[0021] Fig. 2 illustrates two aggregation platforms 102, aggregation platform 102 -1, e.g. representing platform 102 Europe of Fig. 1, and aggregation platform 102 -2, e.g. representing platform 102 East of Fig. 1. Aggregation platform 102 operatively communicates with one or more Remote Game Servers (RGSs) 103 (representing the content providers of Fig. 1). In addition, platform 102 operatively communicates with GPAS 105, with one or more wallet systems 106 of wallet operator of Fig. 1, with one or more operators 107, e.g. casino licensees, and with one or more external systems 108.

[0022] Each RGS 103 is a content provider. The RGS 103 is a software platform that can be deployed as single or multiple instances and can host one or more types of content 104. In some examples, content 104 is a game. RGSs 103 provides functioning games and gaming services such as clients, game logic, and random number generation to operators 107, that choose to operate the games. Operators 107 include, for example, casinos licensees. RGSs 103 can provide its gaming services to operators 107 via aggregation platform 102.

[0023] GPAS (Gaming Platform as a Service) 105 is configured to communicate with aggregation platform 102, as an RGS, and operatively communicates with one or more client terminals (referred to hereinafter as "client") and is configured to run one or more game clients. GPAS can be configured to enable all necessary game management functions (e.g. executing and resolving game logic, game flows, error flows, regulation requirements, etc.) and further operatively communicates, directly, or via platform 102, to operator 107 or wallet systems 106. Other functionalities and gaming services of GPAS 105 are available through aggregation platform 102.

[0024] The entities in the network, including aggregation platform 102, RGSs 103 and GPAS 105 can be implemented on one or more server computers, and comprise a processor and memory circuitry (PMC) (not shown). Each PMC of an entity comprises a processor and a memory, and is configured to execute several functional modules in accordance with computer-readable instructions implemented on a non-transitory computer-readable storage medium. Such functional modules are referred to hereinafter as comprised in the PMC.

[0025] Furthermore, a person versed in the art would appreciate that in some examples, one or more of the entities in the network can constitute a complex entity, comprised of several entities having a similar functionality, in a consolidated manner. For example, an aggregation platform 102 can be integrated into another aggregation platform 102, both constituting the functionality of the aggregation platform 102 as described throughout the description. Similarly, each RGS 103 can be integrated into another RGS 103, or operate in a collaborative manner. Also, any content referred to as stored in an RGS, can be stored in a remote storage, or in another entity, such as in the aggregation platform 102 or the AAP 103. In such cases, any reference to an identifier of an entity can

be referred to as a complex identifier, composed of identifiers of all entities integrated in the complex entity, e.g. composed in a concatenated manner or the like.

[0026] As mentioned, it may be advantageous to integrate, in a higher level, the services provided by each aggregation platform **102**. Bearing this in mind, reference is made to Fig. 3, showing a high-level functional block diagram of an integrated gaming environment **300**, in accordance with certain embodiments of the presently disclosed subject matter.

[0027] Fig. 3 illustrates an aggregator aggregation platform (AAP) **301** that is configured to aggregate the two aggregation platforms **102** illustrated in Fig. 2. The AAP **301** operatively communicates with aggregation platform **102-1** and aggregation platform **102-2** and is configured to obtain data from the platforms **102** and to integrate the data that is received from each platform.

[0028] Aggregating the data on each stored content **104** at the AAP **301** level has several technological advantages. Operators **107-1** communicating with the platform **102-1** obtain services from RGS **103-1.1** and/or RGS **103-1.2** only. Aggregating the data on the AAP **301** level enables RGS **103-2.1** and **103-2.2** that communicate with platform **102-2** to provide services and communicate also with operators **107-1**, and not only operators **107-2**. Operators **107-1** can communicate directly with the AAP **301** in a single user interface, and be exposed to services provided by all RGSs **103** from the various platforms **102**, including RGS **103-2.1** and **103-2.2**. Communicating data from external systems **108** that pertains to a particular piece of content **104** through the AAP **301**, is also achieved in a simpler manner.

[0029] However, the integration itself involves several challenges with respect to locating and accurately identifying a particular piece of content **104** stored on a particular RGS **103**, and communicating data that pertains to the particular piece of content **104**, to the correct RGS that stores the piece of content **104**. For example, if the game is operated both by an RGS **103-2.1** and by an RGS **103-1.1**, any game identifier that is used to identify the game on the RGSs **103** is expected to be the same across both instances of the RGSs **103**. This challenge is further enhanced when there are several instances of the platforms **102**, each having multiple instances of the same RGS **103** connected to it, in potentially multiple geographic areas, each of which store the same type of game. Assuming that operator **107** wishes to configure a game by updating the game characteristics, such as updating the maximal betting amount, communicating data from the operator **107** to the correct RGS **103** that stores that game, may encounter difficulties.

[0030] In order to identify the location of each of stored piece of content **104**, AAP **301** aggregates numerous content aggregation systems (or platforms) in a hierarchical manner, and implements a discovery process, after which the AAP **301** generates a logical geographic coordinate system of the network. The logical geographic coordinate system includes generating a unique path

identifier for each stored piece of content **104**. The unique path identifier assists the AAP **301** to accurately identify the logical geographic location of each of the stored at least one piece of content in the network, in order to facilitate communicating data that pertains to a specific piece of content **104**. The meaning of logical geographic location of a piece of content is further described below in relation to Figs. 5 and 6.

[0031] Generating a unique path identifier for each piece of content enables casino licensees (operator **107**) to communicate with AAP **301**, and configure a game that is operated by separate RGSs **103** and platforms **102**, in a single process, through the AAP **301**. Moreover, displaying various games **104** operated by various RGSs **103**, after discovering them by the AAP **301**, enables operators **107** to add them to the casino portfolio operated by them.

[0032] In some examples, using the unique path identifier to identify a logical geographic location of a stored piece of content **104** assists additional systems to communicate data that pertains to the piece of content **104**, through the AAP **301**, in a more simplified manner. Such systems include, for example, external systems **108**, wallet systems **106** and GPAS **105**.

[0033] For example, AAP **301** can run a discovery process and compare the results of content **104** that was returned, to the results of a previous discovery process. Any changes can be conveyed to relevant operators. For example, if a particular game **104** that was available on a particular RGS **103** as discovered in a discovery process, was not returned in the results of a later discovery process, then any operators **107** that added that game **104** to its portfolio, can be notified that the game **104** is no longer available. Another example includes updating operators **107** with respect to any changes to characteristics of game **104**, e.g. whether a game moved from a staging mode to a production mode, or a list of the games that are currently operating in each mode. Other characteristics relating to content **104**, that were updated, such as if a certain game has updated the languages/ currencies or any other information or parameter, then such information can be conveyed back to the operators. The entities of environment **300** marked by a dashed line (block **302** in Fig. 3) are described in Fig. 4, in a hierarchical manner, in a content aggregation network **400**.

[0034] Fig. 4 illustrates a generalized block diagram of a gaming hierarchy configured in accordance with certain embodiments of the presently disclosed subject matter. In some examples, the lowest level includes RGSs **103**. Since there are multiple types of RGSs available, such as RGS configured for casino games, GPAS (Gaming Platform as a Service) and such, an identifier that describes the type of the RGS is associated with each RGS **103**, denoted as rgsType. For example, RGS **103** denoted by rgsType: provider_1 indicates that the RGS **103** is operated by provider_1.

[0035] Since more than one RGS **103** (or instances of a specific RGS type) can be integrated into aggregation

platform **102**, each instance of RGS **103** is identified by an instance identifier. The instance identifier is local to the instance of the aggregation platform **102** and is denoted as rgsID. The rgsID can be a simple or complex identifier. In order for an RGS to be uniquely identified by the platform **102**, each RGS **103** is associated with an RGS identifier. The RGS identifier can include the RGS type and/or the RGS instance. The RGS identifier is indicative of at least a geographic location of the associated RGS. In some examples, the geographic location includes an indication of the territory or area on which the RGS **103** is located. Upon receipt of the RGS identifier by platform **102**, platform **102** can obtain data on the geographic location of the RGS **103**.

[0036] In some examples, each RGS **103** is configured for storing at least one piece of content **104**, e.g. a game. The game is hosted and made available through a specific RGS **103**. RGS **103** is configured to associate a content identifier for each of the stored content **104**. The content identifier is an immutable identifier, denoted in Fig. 4 by gameId. For example, RGS **103** of rgsType: provider_1 stores two games **104** identified by content identifiers gameId: 1 and gameId: 2. In some examples, each content **104** is associated with characteristics. For example, for a content **104** constituting a game, the characteristics of the content can include operational parameters of the game or configuration characteristics of the game. Operational parameters of the game includes for example, versioning information of the game, game payable (RTF (return to player) information, software package version, list of currencies the game is playable in, list of languages the game supports, etc. Configuration characteristics of the game can include configuration parameters that are often unique to the game itself. Examples of configuration parameters of a slot machine may include (but are not limited to): Maximum Bet, Minimum Bet, Available bet sizes/coin sizes, Free bet sizes/coin sizes, and feature enabling flags. Configuration parameters of a table game such as Blackjack may include (but not be limited to): Number of decks, Number of cards per deck, Insurance allowed and Double Down Bet allowed. In some examples, the content identifier is indicative of characteristics of the content. Further details of providing information on the characteristics of the game **104** and configuration of a game are described below with respect to Fig. 7.

[0037] Each RGS **103** is configured to operatively communicate with a designated aggregation platform **102** of the one or more aggregation platforms **102** in the network. RGS **103** is configured to communicate to the designated aggregation platform **102**, at least one of the content identifiers associated with each piece of content being stored on the RGS **103** and the RGS identifier.

[0038] The network **400** can include more than one instance of an aggregation platform **102**. Two instances of aggregation platform **102** are illustrated in Fig. 4, aggregation platform **102-1** and aggregation platform **102-2**. Each instance of an aggregation platform **102**

must itself be identified by an aggregation identifier, denoted in fig. 4 as aggregatorID. In case platform **102** is integrated into another platform **102**, both constituting the functionality of one platform **102**, then the aggregation identifier can be a complex aggregation identifier. Aggregation platform **102-1** is identified by aggregatorID: agg1 and Aggregation platform **102-2** is identified by aggregatorID: agg2. The aggregation identifier is indicative of at least a geographic location of the associated aggregation platform. The geographic location includes an indication of the territory or area in which the aggregation platform **102** is located. Upon receipt of the aggregation identifier later by the AAP **301**, the AAP **301** can obtain data on the geographic location of platform **102**.

[0039] The aggregation platforms **102** are aggregated into the AAP **301**. The aggregation platforms **102** operatively communicating with the AAP **301** and AAP **301** are configured to obtain from each platform **102** the one or more content identifiers and RGS identifiers received at platform **102** from each RGS **103**. In addition, AAP **301** is configured to obtain from platform **102** the aggregation identifier of the platform itself.

[0040] After receiving data from platform **102**, AAP **301** is configured to generate, for each stored piece of content, a respective unique path identifier based on the associated content identifier, the RGS identifier and the aggregation identifier. Using a coordinate system that describes the geographic location of a specific piece of content, **104** the unique path identifier can include a structure of a chain of coordinates of the entities involved in the piece of content. For example, the structure can include coordinates such as (aggregatorID, rgsType, rgsID, gameId). The predefined order assists the AAP **301** to accurately and deterministically locate a specific piece of content **104** in a logical manner, in the complex network of an aggregated content system. For example, in order to identify the game **104**, with content identifier (gameID) "1", provided by the RGS **103** associated with RGS identifier "provider_1", that is aggregated by the aggregation platform **102** identified by aggregation identifier as "agg1", AAP **301** is configured to generate a unique path identifier of: ("agg1", "provider_1", "gs1_1", "1"). Chaining the identifiers of all entities to generate the unique path identifier assures that path identifier is indeed unique. It is to be noted that although there could exist several games with content identifiers "1" and several RGS **103** with an RGS identifier "provider_1", "gs1_1", each respective unique path, which includes also the different aggregation identifiers, will be unique to AAP **301** generating the path identifier.

[0041] In some examples, the structure includes coordinates of entities in the network, in a predefined order. For example, the order can include: "aggregation identifier", "RGS identifier", "content identifier". In some examples, the RGS identifier includes the RGS type and/or the RGS instance. The structure of the unique path identifier, based on coordinates in a specific order, inherently indicates the exact location of a piece of content, in a

logical manner. The logical location of a piece of content indicates the location of the piece of content within the network, i.e. which entities are involved in order to communicate data to that piece of content (as opposed to the physical location of storing the actual content, in terms of GPS coordinates of the RGS **103**).

[0042] Moreover, a predefined order of coordinates can describe the parent-child relationship of aggregator platforms in the network, such that the structure of the unique path identifier indicates the logical path of entities in the network from the AAP **301** to the RGS **103** storing the specific piece of content, that should be followed, in order to communicate data to that piece of content **104**. The logical location of the piece of content **104** and the indication of the path of entities that are involved from the AAP **301** to the particular RGS that stored that piece of content **104**, is to be referred to as a logical geographic location of the piece of content **104**. The discovery process is further described below with relation to Fig. 5.

[0043] After the AAP **301** generates the unique path identifier, it is configured to use the generated unique path identifier to facilitate communicating data, e.g. to send or receive data, that pertains to the piece of content identified by the generated unique path identifier. Since the unique path identifier constitutes a path, it can use the unique path identifier to communicate data to the particular RGS **103** storing the particular piece of content **104** for implementation and/or configuration.

[0044] In examples where the piece of content is a game, the characteristics of the content include at least one of the operational parameters of the game and configuration characteristics of the game. The AAP **301** is configured to send to the particular RGS **103** that stores the particular piece of content **104**, data that pertains to the operational parameters of the game and/or the configuration characteristics of the game, using the unique path identifier. In cases where the RGS identifier obtained by the AAP **301** includes the RGS type and/or the RGS instance, the AAP **301** is further configured to communicate operational parameters of the game and/or configuration characteristics of the game, based on the RGS type and/or the RGS instance. Further details of providing information on the characteristics of the game and communicating data that pertains to the operational parameters of the game and/or configuration characteristics of the game, are described below with respect to Fig. 7.

[0045] In some examples, the AAP **301** operatively communicates with at least one external system **108** and communicates data that pertains to a specific piece of content **104** stored on a particular RGS **103**, from or to the at least one external system **108**, based on the unique path identifier associated with the specific piece of content **104**.

[0046] It is noted that the teachings of the presently disclosed subject matter are not bound by the gaming environment and network described with reference to Figs. 1-4. Equivalent and/or modified functionality can be

consolidated or divided in another manner and can be implemented in any appropriate combination of software with firmware and/or hardware and executed on a suitable device(s) in any suitable cloud-based architectural framework. In certain embodiments, at least some of the described functional modules can be implemented as a standalone entity (or as entities) operatively communicating to the clients and operating in conjunction with AAP **301**, aggregation platforms **102**, RGSs **103**, operators **107**, GPAS **105**, or the like. In certain embodiments, aggregation platform **102** can be integrated into one or more other platforms, or a wallet system can comprise a plurality of separate wallets (per each licensee) implemented on the same or on different servers; optionally, part of the functions of the separate wallets can be integrated in a centralized manner.

[0047] Reference is now made to Fig. 5 illustrating a generalized flowchart of operations performed by entities in the gaming hierarchy, in accordance with certain embodiments of the presently disclosed subject matter.

[0048] The operations are performed by entities in the hierarchal network illustrated with reference to Fig. 4, in which there is provided an AAP **301**, one or more aggregation platforms **102** each of the one or more aggregation platforms **102** being associated with a aggregation identifier indicative of at least a geographic location of the associated aggregation platform. The one or more aggregation platforms **102** operatively communicate with the AAP **301**. In addition, there is provided at least one RGS **103** configured for storing at least one piece of content **104**. Each of the at least one RGS **103** is associated with an RGS identifier indicative of at least a geographic location of the associated RGS **103**. RGS **103** are configured to operatively communicate with a designated aggregation platform **102** of the one or more aggregation platforms **102** (block **510**). Each of the RGS, e.g. by their processors, associate a content identifier for each piece of content **104** that they store. The content identifier for each piece of content **104** is indicative of characteristics of the piece of content **104**. In some examples, the piece of content is a game, and the characteristics of the game include operational parameters of the game, or configuration characteristics of the game.

[0049] In some examples, the discovery process implemented by AAP **301** includes obtaining data from aggregation platforms **102** that pertains to the pieces of contents **104** that are stored on each RGS **103** operatively communicating with each aggregation platform **102**. Each layer sends requests for data to the layer below it, and each layer sends back data to the layer above it. Hence, AAP **301** sends requests for data to platforms **102**, and aggregation platforms **102** sends requests to the RGSs **103**. Each layer sends back data, until it reaches AAP **301**. For example, AAP **301** sends each aggregation platform **102** a request for a list of all RGSs **103** that operatively communicating with the aggregation platform **102**. Then, the AAP **103** sends each aggregation platform **102** another request for a list of operators and

a list of RGSs **103** that operatively connected to each operator. Based on the response from each aggregation platform **102**, AAP **103** can map the rest of the required information, for example, which content is associated with each operator in each RGS **103**.

[0050] In some examples, the discovery process can include a continuous update. Unless specifically stated otherwise, it is appreciated that throughout the specification the term "continuous update" may refer to receiving, (in push or pull mode), data substantially each time new data is available to RGS **103** and/or platform **102** and/or other entities of the network and/or responsive to predefined events (including scheduled events and events occurring in accordance with predefined periodicity).

[0051] During the discovery process, the RGS **103**, e.g. using its processor, associates a unique content identifier and communicates the at least one associated content identifier and the RGS identifier to the designated aggregation platform **102** of one or more aggregation platforms that it are operatively communicating with (block **520**). In some examples, associating a unique content identifier can occur upon first storing the content identifier, irrespective of the discovery process. Once requested, the associated content identifier is sent to the designated aggregation platform **102**. Each aggregation platform **102**, e.g. using its processor, once requested, communicates to the AAP **301** its aggregation identifier, as well as the data obtained from the each of the RGS **103** operatively communicating with it. The data received from each of the RGS **103** includes, among others, the RGS identifier received from each of the RGS **103** and a list of content identifiers of associated pieces of content stored on that RGS **103** (block **530**).

[0052] Once the data is obtained by the AAP **301**, the AAP **301**, e.g. using its processor, generates a unique path identifier for each of the pieces of content **104** stored on each of the RGSs **103** (block **540**). AAP **301** generates a respective unique path identifier for each particular piece of content **104**, stored on each particular RGS **103**, based on at least the following data:

1. the associated particular unique content identifier, generated by the particular RGS **103** for the particular piece of content **104**, as received by the aggregation platform **102**;
2. the unique RGS identifier of the particular RGS **103** storing the particular piece of content, as received by the aggregation platform **102**;
3. the received unique aggregation identifier of the aggregation platform **102** that sent the data relating to the particular piece of content.

[0053] Using a coordinate system that describes the geographic location of a specific piece of content **104**, the unique path identifier can include a structure of a

chain of coordinates of the entities involved in the piece of content. For example, the structure can include coordinates such as (aggregatorId, rgsType, rgsID, gameId). The predefined order assists the AAP **301** to accurately and deterministically locate a specific piece of content **104** in a logical manner, in the complex network of the aggregated content system. For example, in order to identify the game **104**, with content identifier (gameID) **"1"**, provided by the RGS **103** associated with RGS identifier "provider_1", that is aggregated by the aggregation platform **102** identified by aggregation identifier as "agg1", AAP **301** generates a unique path identifier of: ("agg1", "provider_1", "gs1_1", **"1"**). Chaining the identifiers of all entities to generate the unique path identifier assures that the path identifier is indeed unique. It is to be noted that although there could exist several games with content identifiers **"1"** and several RGS **103** with an RGS identifier "provider_1", "gs1_1", each respective unique path will be unique to AAP **301** generating the path identifier.

[0054] In some examples, the structure includes coordinates of entities in the network, in a predefined order. For example, the order can include "aggregation identifier", "RGS identifier", and "content identifier". In some examples, the RGS identifier includes the RGS type and/or the RGS instance. The structure of the unique path identifier, based on coordinates in a specific order, inherently indicates the exact location of a piece of content, in a logical manner. The logical location of a piece of content indicates the location of the piece of content within the network, i.e. which entities are involved in order to communicate data to that piece of content (as opposed to the physical location of storing the actual content, in terms of GPS coordinates of the RGS **103**).

[0055] Moreover, a predefined order of coordinates can describe the parent-child relationship of aggregator platforms in the network, such that the structure of the unique path identifier indicates the logical path of entities in the network from the AAP **301** to the RGS **103** storing the specific piece of content, that should be followed, in order to communicate data to that piece of content **104**. The logical location of the piece of content **104** and the indication of the path of entities to the RGS within it, is referred to as a logical geographic location of the piece of content **104**.

[0056] After the AAP **301** generates the unique path identifier, the AAP **301** uses the generated unique path identifier to facilitate communicating data, e.g. to send or receive data, that pertains to the piece of content identified by the generated unique path identifier (block **550**). Since the unique path identifier constitutes a path, the AAP **301** can use the unique path identifier to communicate data to the particular RGS **103** storing the particular piece of content **104** for implementation and/or configuration, through all the entities on the path, e.g. the platform.

[0057] Reference is now made to Fig. **6** illustrating a flowchart of operations carried out by the AAP **301**, in

accordance with certain embodiments of the presently disclosed subject matter.

[0058] In the hierarchal network illustrated above, the processor of the AAP 301 operatively communicates with one or more aggregation platforms 102, and each of the one or more aggregation platforms 102 is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform. In addition, there is provided at least one RGS 103 configured for storing at least one piece of content 104. Each of the at least one RGS 103 is associated with an RGS identifier indicative of at least a geographic location of the associated RGS 103. RGS 103 is configured to operatively communicate with a designated aggregation platform 102 of the one or more aggregation platforms 102.

[0059] In some examples, in order for the AAP 301 to identify the location of a piece of content, the AAP 301, e.g. using its processor, obtains from each of the one or more aggregation platforms 102 the associated aggregation identifier (block 610). For example, the AAP 301 issues a discovery process querying each operatively communicating platform 102 for its aggregation identifier. Alternatively or additionally, once an aggregation platform 102 is operatively communicating to AAP 301, the aggregation platform 102 sends to the AAP 301 its respective aggregation identifier, and the AAP 301 stores in a database the aggregation identifiers of the aggregation platform 102 that operatively communicated with the AAP 301. Obtaining from each of the one or more aggregation platforms the associated aggregation identifier can include retrieving from the database the aggregation identifiers of the aggregation platform 102 that is operatively communicating to AAP 301 (block 610).

[0060] For each platform that is operatively communicating with AAP 301, AAP 301 further obtains, through the aggregation platform 102, a list of all RGSs 103 that are operatively communicating with that platform 102, and their respective RGS identifiers (block 620). For example, the list includes at least one RGS identifier of at least one RGS 103 that is operatively communicating with aggregation platform 102.

[0061] Each platform obtains from the RGSs 103 that are operatively communicating with the designated platform 102, a list of all pieces of content 104 that are stored on each RGS 103, and their associated content identifiers. Hence, AAP 301 obtains, through each of the aggregation platform 102 and the RGS 103, associated content identifiers for pieces of content 104 stored in each RGS 103 (block 630). For example, AAP 301 obtains at least one content identifier associated with at least one piece of content 104 stored on an RGS 103.

[0062] Based on the obtained associated content identifier, the obtained RGS identifier and the obtained aggregation identifier, AAP 301 generates a respective unique path identifier for each of the stored at least one piece of content. The unique path identifier is for identifying a logical geographic location of each of the stored at least one piece of content (block 640). The AAP 301

can then use the generated unique path identifier, to facilitate communicating data that pertains to the piece of content identified by the unique path identifier (block 650). The data can be issued from the AAP 301 or received from other systems or network entities that communicate with the AAP 301, and be sent to the RGS 103 storing the piece of content. For example, the data pertains to one or more characteristics of the content.

[0063] As described above, in some examples, each content 104 is associated with **characteristics**. For example, for a content 104 being a game, the characteristics of the content can include **operational parameters** of the game or **configuration characteristics** of the game. Operational parameters of the game include for example, versioning information of the game, game payable (RTF (return to player) information, software package version, list of currencies the game is playable in, list of languages the game supports, etc. **Configuration characteristics** of the game can include **configuration parameters and/or other requirements**. In some examples, different instances of content require specific types of **configuration parameters** that are often unique to the content itself. Examples of configuration parameters of a slot machine game content may include (but are not limited to): Maximum Bet, Minimum Bet, Available bet sizes/coin sizes, Free bet sizes/coin sizes, and Feature enabling flags. In contrast, configuration parameters of a table game such as Blackjack may include (but not be limited to): Number of decks, Number of cards per deck, Insurance allowed, and Double Down Bet allowed.

[0064] Due to almost infinite possibilities of combining individual configuration parameters, and the fact that it is impossible to predict the required configuration parameters by a specific game, in some examples an RGS 103 is configured to provide specific configuration capabilities, per game. To address this complexity and enable an RGS 103 to provide configuration capabilities and implement configuration to parameters of a game, the game is configured to generate data describing its configuration parameters. Alternatively, the data describing the configuration parameters can automatically be generated by using known standards in the field, such as the descriptive JSON Schema standard. The data describing the configuration parameters as well as the required structure of the configuration parameters is referred to herein as configuration schema of the content 104. For example, the configuration schema includes the characteristics described above, including Maximum Bet, Minimum Bet, Available bet sizes/coin sizes and such. Configuration schema can also describe other secondary parameters such as labels, comments, data-type identifiers, related values and so forth. Once a **configuration schema** is generated, the RGS 103 is configured to store the **configuration schema** and associate between the relevant content and its **configuration schema**. In some examples, the RGS 103 also configures the game 103 based on its associated **configuration schema**, e.g. by updat-

ing the configuration parameters of the game.

[0065] The **configuration schema** can be retrieved by the RGS 103 at any time during a discovery process, a continuous update, or upon demand, and be sent together with the content identifier to the platform 102 and eventually to the AAP 301. The **configuration schema** can be provided to entities of the network, and can be used e.g. for analytics, for configuring game parameters by operators 107 etc. In some examples, the **configuration schema** can be provided to operators or clients or the game, for setting configuration updates, which are later validated, e.g. by the RGS 103 versus the configuration schema. Once receiving configuration updates, the AAP 301 uses the unique path identifier for applying the configuration updates, for example, by sending the configuration updates to the particular RGS 103 storing the particular game 104, for which updates were received, so the RGS 103 can apply the confirmation updates to the game accordingly. Using the unique path identifier is advantageously such that it enables the AAP 301 to communicate the updates to the particular RGS 103 storing the particular game 104 in the network.

[0066] Bearing this in mind, reference is made to Fig. 7 illustrating the process of configuring **configuration schema**. Some stages of Fig. 7 refer to stages illustrated in relation to Fig. 6. As such, in blocks 610 and 620, AAP 301 obtaining an aggregation identifier from platform 102 and an RGS identifier from RGS 103 through aggregation platform 102 are illustrated. Each RGS 103 is configured to provide a list of pieces of content 104 stored within the RGS 103, and hence, during the discovery process, AAP 301 is configured to obtain at least one content identifier, wherein each content identifier is indicative of characteristics of the content (block 630). In some examples, where a configuration schema was generated e.g. by the content 104 itself and was stored and associated with the content 104, e.g. by the RGS 103, then AAP 301 is configured to obtain also configuration schema associated with the content 104 (block 710). For example, RGS 103 can send the configuration schema associated with a content 104 to AAP 301 through the platform 102. In some examples, AAP 301 obtains the configuration schema during the discovery process. Alternatively or additionally, AAP 301 obtains the configuration schema associated with the particular content 104, based on the respective content identifier, upon request. For example, AAP 301 can send a specific request to a particular RGS 103 storing a particular content 104 with an associated content identifier, to obtain the configuration schema associated with that particular content 104.

[0067] AAP 301 can generate a respective unique path identifier (block 640). AAP 301 then uses the generated unique path identifier (block 650), for example, AAP 301 provides data on a stored content 104 and associated configuration schema (block 720). In some examples, AAP 301 displays a list of one or more games and their associated configuration schema to operators, e.g. operators 107 illustrated in relation to Fig. 1 and 2. The

operators 107 can then insert or update data relating to the configuration, based on the configuration schema, and send such data to AAP 301. For example, update to the configuration, based on the configuration schema, includes revising/editing/adding/disabling/removing and updating values of any configuration parameters and/or requirements. AAP 301 obtains the updated configuration (block 730), e.g. by receiving it from operators 107. AAP 301 can then apply the updated configuration (block 740). For example, AAP 301 sends the updated configuration to the RGS 103 storing the particular piece of content 104 associated with the configuration schema, by sending the updated configuration to the aggregation platform 102, which in turn, sends the updated configuration to the RGS 103 storing the particular piece of content 104. Sending the updated configuration can be done using the unique path identifier associated with the particular piece of content 104.

[0068] The process of updating configuration associated with the content 104 can be done when the operator initially selects the content 104 to be added to his portfolio, or upon request, after the content 104 has already been added, and the operator 107 then chooses to update the configuration, based on the configuration schema that was provided by the RGS 103. Using the unique path identifier is advantageously such that it enables the AAP 301 to communicate the updates to the particular RGS 103 storing the particular game 104 in the network.

[0069] It is noted that the teachings of the presently disclosed subject matter are not bound by the flow charts illustrated in Figs. 5, 6, and 7 the illustrated operations can occur out of the illustrated order. For example, operations 610, 620 and 630 shown in succession can be executed substantially concurrently, or in the reverse order. It is also noted that whilst the flow chart is described with reference to elements of system 400, this is by no means binding, and the operations can be performed by elements other than those described herein.

[0070] It is to be understood that the invention is not limited in its application to the details set forth in the description contained herein or illustrated in the drawings. The invention is capable of other embodiments and of being practised and carried out in various ways. Hence, it is to be understood that the phraseology and terminology employed herein are for the purpose of description and should not be regarded as limiting. As such, those skilled in the art will appreciate that the conception upon which this disclosure is based may readily be utilized as a basis for designing other structures, methods, and systems for carrying out the several purposes of the presently disclosed subject matter.

[0071] It will also be understood that the system according to the invention may be, at least partly, implemented on a suitably programmed computer. Likewise, the invention contemplates a computer program being readable by a computer for executing the method of the invention. The invention further contemplates a non-transitory computer-readable memory tangibly embodying a

program of instructions executable by the computer for executing the method of the invention.

[0072] Those skilled in the art will readily appreciate that various modifications and changes can be applied to the embodiments of the invention as hereinbefore described without departing from its scope, defined in and by the appended claims.

Claims

1. A computer-based content aggregation system , comprising:

an aggregator aggregation platform (AAP);
 one or more aggregation platforms operatively communicating with the AAP, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform;
 at least one remote game server (RGS) configured for storing at least one piece of content and operatively communicating with a designated aggregation platform of the one or more aggregation platforms, wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS,
 wherein each of the at least one RGS is configured to:

associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content; and
 communicate the at least one associated content identifier and the RGS identifier to the designated aggregation platform;

wherein each of the at least one aggregation platform is configured to:
 communicate to the AAP both the at least one content identifier and the RGS identifier received from each of the at least one RGS, and the aggregation identifier;
 wherein the AAP is configured to generate for each of the stored at least one piece of content, a respective unique path identifier, based on the associated content identifier, the RGS identifier and the aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content, and
 wherein usage of a generated unique path identifier, by the AAP, facilitates communicating data, that pertains to the piece of content identified by the generated unique path identifier.

2. The computer-based content aggregation system of

claim 1 wherein the AAP is further configured to:

operatively communicate with at least one external system; and
 communicate data that pertains to a specific piece of content stored on a particular RGS, from/to the at least one external system, based on the unique path identifier associated with the specific piece of content.

3. The computer-based content aggregation system of claim 1 wherein the AAP is further configured to send/receive data that pertains to a specific piece of content stored on a particular RGS to/from the AAP and the particular RGS, using the unique path identifier.

4. The computer-based content aggregation system of claim 1 wherein the piece of content is a game, and wherein the characteristics of the content include at least one selected from: operational parameters of the game, configuration characteristics of the game, configuration schema and configuration characteristics of the game based on a configuration schema.

5. The computer-based content aggregation system of claim 4 wherein the at least one RGS is further configured to the receive updated configuration characteristics, based on the configuration schema, and to configure the schema, based on the updated configuration characteristics.

6. The computer-based content aggregation system of claim 4, wherein the RGS identifier includes the RGS type and/or the RGS instance, and the AAP is further configured to communicate updated configuration characteristics, based on the RGS type and/or the RGS instance.

7. A computerized method for identifying a location of piece of content, comprising:
 providing an aggregator aggregation platform (AAP), one or more aggregation platforms operatively communicating with the AAP, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform and at least one remote game server (RGS) configured for storing at least one piece of content and operatively communicating with a designated aggregation platform of the one or more aggregation platforms, wherein each of at least one RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, the method further comprising:

by a processor of each of the at least one RGS:

- associating a content identifier for each of the stored at least one piece of content indicative of characteristics of the content; and
communicating the at least one associated content identifier and the RGS identifier to a designated aggregation platform of one or more aggregation platforms;
- by a processor of each of the at least one aggregation platform:
communicating to the AAP both the at least one associated content identifier and the RGS identifier received from each of the at least one RGS, and the aggregation identifier;
by a processor of the AAP:
- generating a respective unique path identifier for each of the stored at least one piece of content, based on the associated unique content identifier, the unique RGS identifier, and the unique aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content, and
using the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the generated unique path identifier.
8. A computer-based content aggregation system, comprising:
- an aggregator aggregation platform (AAP) comprising a processor;
wherein the AAP is configured, by the processor, to:
- operatively communicate with one or more aggregation platforms, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform, and wherein each of the one or more aggregation platforms is configured to operatively communicate with at least one remote game server (RGS), wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, and is configured for storing at least one piece of content, and to associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content;
obtain from each of the one or more aggregation platforms:
- (i) the associated aggregation identifier;
(ii) the at least one associated RGS identifier of the at least one RGSs operatively communicating with the aggregation platform; and
(iii) the at least one associated content identifier for each of the at least one piece of content stored in each of the at least one RGS that is operatively communicating with the respective aggregation platform;
- generate a respective unique path identifier for each of the stored at least one piece of content, based on the obtained associated content identifier, the obtained RGS identifier and the obtained aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content; and
use the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the generated unique path identifier.
9. The computer-based content aggregation system of claim 8, wherein the AAP is further configured to obtain from each of the one or more aggregation platforms:
- (iv) a configuration schema associated with the obtained content; and
based on the obtained data and the generated unique path identifier, the AAP is further configured to:
- (a) provide data on at least one piece of content and its associated configuration schema;
(b) receive updated configuration characteristics, based on the configuration schema; and
(c) apply the updated configuration characteristics.
10. A computerized method for identifying a location of piece of content, comprising:
by a processor of an aggregator aggregation platform (AAP) operatively communicating with one or more aggregation platforms, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform, and wherein each of the one or more aggregation platforms is configured to operatively communicate with at least one remote game server (RGS), wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, and is configured for storing at least one piece of content, and

to associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content, the method comprising:

obtaining from each of the one or more aggregation platforms the associated aggregation identifier;
 obtaining, through each of the at least one aggregation platform, the at least one RGS identifier;
 obtaining, through each of the at least one aggregation platform and the at least one RGS, the at least one associated content identifier for each of the at least one piece of content stored in each of the at least one RGS;
 generating a respective unique path identifier for each of the stored at least one piece of content, based on the obtained associated content identifier, the obtained RGS identifier and the obtained aggregation identifier for identifying a logical geographic location of each of the stored at least one piece of content; and
 using the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the unique path identifier.

11. The computerized method of claim 10, wherein the obtaining the at least one associated content identifier further comprises obtaining a configuration schema associated with the obtained content, the method further comprising:

providing data on at least one piece of content and its associated configuration schema, based on the obtained data and the generated unique path identifier;
 receiving updated configuration, based on the configuration schema; and
 applying the updated configuration characteristics.

12. A non-transitory computer readable storage medium tangibly embodying a program of instructions that, when executed by a computer, cause the computer to perform a method for identifying a location of a piece of content, comprising:
 providing an aggregator aggregation platform (AAP), one or more aggregation platforms operatively communicating with the AAP, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform and at least one remote game server (RGS) configured for storing at least one piece of content and operatively communicating with a designated aggregation platform of the one or more aggregation platforms, wherein each of at least one RGS is as-

sociated with an RGS identifier indicative of at least a geographic location of the associated RGS, the method further comprising:

by a processor of each of the at least one RGS:

associating a content identifier for each of the stored at least one piece of content indicative of characteristics of the content; and
 communicating the at least one associated content identifier and the RGS identifier to a designated aggregation platform of one or more aggregation platforms;

by a processor of each of the at least one aggregation platform:

communicating to the AAP both the at least one associated content identifier and the RGS identifier received from each of the at least one RGS, and the aggregation identifier;

by a processor of the AAP:

generating a respective unique path identifier for each of the stored at least one piece of content, based on the associated unique content identifier, the unique RGS identifier, and the unique aggregation identifier, for identifying a logical geographic location of each of the stored at least one piece of content, and
 using the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the generated unique path identifier.

13. A non-transitory computer readable storage medium tangibly embodying a program of instructions that, when executed by a computer, cause the computer to perform a method for identifying a location of piece of content, comprising:

by a processor of an aggregator aggregation platform (AAP) operatively communicating with one or more aggregation platforms, wherein each of the one or more aggregation platforms is associated with an aggregation identifier indicative of at least a geographic location of the associated aggregation platform, and wherein each of the one or more aggregation platforms is configured to operatively communicate with at least one remote game server (RGS), wherein each of the one or more RGS is associated with an RGS identifier indicative of at least a geographic location of the associated RGS, and is configured for storing at least one piece of content, and to associate a content identifier for each of the stored at least one piece of content indicative of characteristics of the content, the method comprising:

obtaining from each of the one or more aggregation platforms the associated aggregation identifier;
obtaining, through each of the at least one aggregation platform, the at least one RGS identifier;
obtaining, through each of the at least one aggregation platform and the at least one RGS, the at least one associated content identifier for each of the at least one piece of content stored in each of the at least one RGS;
generating a respective unique path identifier for each of the stored at least one piece of content, based on the obtained associated content identifier, the obtained RGS identifier and the obtained aggregation identifier for identifying a logical geographic location of each of the stored at least one piece of content; and
using the generated unique path identifier, to facilitate communicating data, that pertains to the piece of content identified by the unique path identifier.

25

30

35

40

45

50

55




Fig 1




Fig 2




Fig 3





Fig 4

500

**Fig 5**





Fig 6

700

**Fig 7**



EUROPEAN SEARCH REPORT

Application Number
EP 20 18 7377

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	WO 2018/183325 A1 (TAPP TECH LLC [US]) 4 October 2018 (2018-10-04) * abstract * * figure 3 * * page 14, line 9 - line 24 * * page 4, line 14 - line 23 * * page 23, line 27 - page 24, line 28 * * page 32, line 33 - page 33, line 7 * -----	1-13	INV. A63F13/352 A63F13/60 A63F13/77
X	WO 2018/142414 A1 (PLAYTECH SOFTWARE LTD [GB]; PLAYTECH SOFTWARE LTD [IL]) 9 August 2018 (2018-08-09) * abstract * * page 1, line 12 - page 3, line 30 * * page 6, line 4 - line 25 * -----	1-13	
A	US 2011/213655 A1 (HENKIN ASSAF [IL] ET AL) 1 September 2011 (2011-09-01) * abstract * * paragraph [0004] - paragraph [0008] * * paragraph [0061] - paragraph [0062] * * paragraph [0297] - paragraph [0309] * * paragraph [0481] - paragraph [0489] * -----	1-13	TECHNICAL FIELDS SEARCHED (IPC)
A	EP 3 220 330 A1 (BOEING CO [US]) 20 September 2017 (2017-09-20) * abstract * * paragraph [0004] - paragraph [0012] * * paragraph [0027] * * paragraph [0034] - paragraph [0041] * -----	1-13	A63F G07F
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 25 November 2020	Examiner Garton, Paul
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 20 18 7377

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-11-2020

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 2018183325 A1	04-10-2018	NONE	
WO 2018142414 A1	09-08-2018	AU 2018215820 A1 CA 3052119 A1 EP 3576858 A1 US 2019351332 A1 WO 2018142414 A1	22-08-2019 09-08-2018 11-12-2019 21-11-2019 09-08-2018
US 2011213655 A1	01-09-2011	US 2011213655 A1 WO 2010085773 A1	01-09-2011 29-07-2010
EP 3220330 A1	20-09-2017	BR 102017001544 A2 CA 2953841 A1 CN 107203581 A EP 3220330 A1 JP 2017208069 A SG 10201701720Y A US 2017270182 A1	21-11-2017 17-09-2017 26-09-2017 20-09-2017 24-11-2017 30-10-2017 21-09-2017