

(19)



(11)

EP 3 888 945 B9

(12)

CORRECTED EUROPEAN PATENT SPECIFICATION

(15) Correction information:

Corrected version no 1 (W1 B1)

Corrections, see

Description Paragraph(s) 42

(48) Corrigendum issued on:

01.01.2025 Bulletin 2025/01

(45) Date of publication and mention
of the grant of the patent:

23.10.2024 Bulletin 2024/43

(21) Application number: **19890149.8**

(22) Date of filing: **10.10.2019**

(51) International Patent Classification (IPC):

B60C 11/03^(2006.01) B60C 11/12^(2006.01)

(52) Cooperative Patent Classification (CPC):

**B60C 11/0304; B60C 11/0306; B60C 11/1218;
B60C 11/1236; B60C 2011/0383; B60C 2011/1209;
B60C 2011/1213; B60C 2011/1227**

(86) International application number:

PCT/JP2019/039963

(87) International publication number:

WO 2020/110474 (04.06.2020 Gazette 2020/23)

(54) **PNEUMATIC TIRE**

LUFTREIFEN

PNEUMATIQUE

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **26.11.2018 JP 2018220261**

(43) Date of publication of application:

06.10.2021 Bulletin 2021/40

(73) Proprietor: **The Yokohama Rubber Co., Ltd.**

Hiratsuka-shi, Kanagawa 254-8601 (JP)

(72) Inventor: **NAGAYASU, Masaaki**

Hiratsuka-shi, Kanagawa 254-8601 (JP)

(74) Representative: **Dilg, Haeusler, Schindelmann**

Patentanwalts-gesellschaft mbH

Leonrodstraße 58

80636 München (DE)

(56) References cited:

EP-A2- 0 864 448	JP-A- 2001 150 446
JP-A- 2002 292 640	JP-A- 2002 316 328
JP-A- 2005 041 339	JP-A- 2005 162 197
JP-A- 2005 205 988	JP-A- 2006 082 632
JP-A- 2009 255 734	JP-A- 2012 041 024
JP-A- 2013 136 366	JP-A- 2013 252 690
JP-A- 2016 168 966	JP-A- H0 524 044
JP-A- H0 631 832	JP-B1- S 494 511
US-A1- 2014 265 033	US-A1- 2015 041 034
US-A1- 2017 129 287	US-A1- 2017 305 201

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

Technical Field

[0001] The present invention relates to a pneumatic tire and particularly relates to a pneumatic tire that allows enhancing braking performance on wet road surfaces and icy and snowy road surfaces and suppressing poor appearance generated during vulcanization molding, without changing the appearance of a tire.

Background Art

[0002] During vulcanization molding of a pneumatic tire including a plurality of sipes in a tread portion, a problem occurs in which rubber forming the tread portion (tread rubber) bonds to a tire mold, generating poor appearance in a vulcanized pneumatic tire. Such a bonding between the tire mold and the tread rubber is significant in winter tires in which a large number of sipes are disposed in a tread portion. With respect to this problem, when using a sectional tire mold that forms a tread portion by sectors divided in a tire circumferential direction, reducing the number of sipes in the vicinity of a sector dividing position and shortening the length of the sipes in a tire width direction has been proposed (for example, see Patent Documents 1, 2).

[0003] However, this method involves a problem of causing a change in the appearance of a tire because the presence of sipes and the length thereof are different between the vicinity of the sector dividing position and other portions. Further, reduction in the number of sipes and the length thereof causes deterioration in wet performance (braking performance on wet road surfaces) and snow performance (braking performance on icy and snowy road surfaces), both of which are based on the sipes, and thus there is a risk that a sufficient tire performance originally intended may not be obtained. Pneumatic tires, each having a tire tread, in which each of a plurality of tread blocks comprises both, two-dimensional sipes and three-dimensional sipes, are known from each of documents JP 2005 041339A, JP 2012 041024 A, JP 2005 205988 A and

[0004] JP 2013 136366 A.

Citation List

Patent Literature

[0005]

Patent Document 1: JP 3494511 B

Patent Document 2: JP 4411975 B

Summary of Invention

Technical Problem

[0006] An object of the present invention is to provide a pneumatic tire that allows enhancing braking performance on wet road surfaces and icy and snowy road surfaces and suppressing the occurrence of poor appearance, without changing the appearance of a tire.

Solution to Problem

[0007] A pneumatic tire according to an embodiment of the present invention for achieving the object described above, is defined in claim 1. Preferred embodiments of the invention are defined in the dependent claims.

Advantageous Effects of Invention

[0008] As described above, in a pneumatic tire according to an embodiment of the present invention including a tread portion formed by a plurality of sectors divided in a tire circumferential direction, a plurality of rows of land portions are defined by a plurality of circumferential grooves, the land portions including a plurality of sipes extending in a tire width direction. The plurality of sipes include a three-dimensional sipe and a two-dimensional sipe, and a ratio R1 of the number of a plurality of the three-dimensional sipes in a first boundary region is smaller than a ratio Rt of the number of a plurality of the three-dimensional sipes in all of the tread portion. Thus, bonding between a tire mold and tread rubber can be prevented, and the occurrence of poor appearance can be suppressed. Specifically, the two-dimensional sipe is formed by a blade having less unevenness in a depth direction, and the blade tends to come out easily after vulcanization. The three-

dimensional sipe is formed by a blade having more unevenness in the depth direction, and the blade tends to come out less easily after vulcanization. Accordingly, a few of the three-dimensional sipes, from which the blades come out less easily, can be disposed (disposing many of the two-dimensional sipes, from which the blades come out more easily) in the vicinity of a sector dividing position (first boundary region) where the tread rubber tends to bond to the tire mold easily, and thus bonding between the tire mold and the tread rubber can be prevented. On the other hand, the two-dimensional sipe, which has a simpler structure than that of the three-dimensional sipe, tends to yield lower running performance based on the sipe (wet performance and snow performance) than that of the three-dimensional sipe. However, since a region where the ratio of the number of the three-dimensional sipes is reduced is limited to the first boundary region where contribution to bonding between the tire mold and the tread rubber is great, still a sufficient number of the three-dimensional sipes can be provided on a tire as a whole, and good running performance based on the plurality of sipes (wet performance and snow performance) can be obtained. By using the two-dimensional sipe or the three-dimensional sipe, that is, by using a difference in the sipe structure along the depth direction, rather than the sipe shape appearing on the tread surface, to adjust the easiness with which a blade comes out (the difficulty with which the rubber and the mold bond), this has no effect on the appearance of the tire (the sipe shape appearing on the tread surface).

[0009] In a preferred embodiment of the present invention, a ratio $R1/Rt$ of a ratio $R1$ and a ratio Rt is preferably not greater than 0.80. The ratio of the three-dimensional sipes in the first boundary region can thus be sufficiently reduced to prevent bonding between the tire mold and the tread rubber, and the occurrence of poor appearance can be advantageously suppressed.

[0010] In an embodiment of the present invention, the plurality of rows of land portions include three or more rows of land portions including a pair of shoulder land portions, and all of the land portions include a plurality of sipes. In an embodiment according to a preferred configuration, the ratio of the number of the three-dimensional sipes disposed in the first boundary region of each of the land portions with respect to the total number of the plurality of sipes disposed in the first boundary region of each of the land portions is $R1'$; and the ratio of the number of the three-dimensional sipes in an entire circumference of each of the land portions with respect to the total number of the plurality of sipes in the entire circumference of each of the land portions is Rt' , a ratio $R1' / Rt'$ in the shoulder land portion is preferably smaller than a ratio $R1' / Rt'$ in any other land portion. A relationship of a ratio $R1' / Rt'$ of each of the land portions can thus be set to reduce the ratio of the three-dimensional sipes included in the first boundary region in the shoulder land portion where bonding between the tire mold and the tread rubber is relatively easily generated, and such a configuration effectively prevents bonding between the tire mold and the tread rubber and advantageously suppresses the occurrence of poor appearance.

[0011] In an embodiment of the present invention, the plurality of rows of land portions include three or more rows of land portions including a pair of shoulder land portions, and in a configuration in which: all of the land portions have a plurality of sipes; the ratio of the number of the three-dimensional sipes disposed in the first boundary region of each of the land portions with respect to the total number of a plurality of sipes disposed in the first boundary region of each of the land portions is $R1'$; and the ratio of the number of the three-dimensional sipes in an entire circumference of each of the land portions with respect to the total number of a plurality of sipes in the entire circumference of each of the land portions is Rt' , an inclination angle, with respect to the tire width direction, of the plurality of sipes provided in the first boundary region of a land portion having a smallest ratio $R1' / Rt'$ is preferably smaller than an inclination angle, with respect to the tire width direction, of the plurality of sipes provided in the first boundary region of any other land portion. Generally, the smaller an inclination angle of a sipe is, the less easily a blade forming the sipe comes out, and thus an inclination angle of a sipe and a ratio $R1' / Rt'$ can be associated to reduce the ratio of the three-dimensional sipes included in the first boundary region where the inclination angle of the plurality of sipes is small and the blades come out less easily, effectively preventing bonding between the tire mold and the tread rubber and advantageously suppressing the occurrence of poor appearance.

[0012] In a preferred embodiment of the present invention, when a range within 5 mm on one side of the sector dividing position in the tire circumferential direction is defined as a second boundary region, a ratio $R1$ of the number of the three-dimensional sipes disposed in the first boundary region with respect to the total number of the plurality of sipes disposed in the first boundary region and a ratio $R2$ of the number of the three-dimensional sipes disposed in the second boundary region with respect to the total number of the plurality of sipes disposed in the second boundary region preferably satisfy the relationship $R1 > R2$. Thus setting a relationship between the ratios $R1$, $R2$ reduces the ratio of the three-dimensional sipes toward the sector dividing position, effectively preventing bonding between the tire mold and the tread rubber and advantageously suppressing the occurrence of poor appearance.

[0013] In a preferred embodiment of the present invention, an average $D1$ of the maximum depths of the plurality of sipes disposed in the first boundary region and an average Dt of the maximum depths of the plurality of sipes in all of the tread portion preferably satisfy the relationship $D1 < Dt$. Generally, the smaller a maximum depth of a sipe is, the more easily a blade forming the sipe comes out, and by reducing the depths of a plurality of sipes in the vicinity of the sector dividing position (first boundary region) where the tread rubber tends to bond to the mold easily, bonding between the tire mold and the tread rubber can be effectively prevented and the occurrence of poor appearance can be advantageously suppressed.

Brief Description of Drawings

[0014]

FIG. 1 is a meridian cross-sectional view of a pneumatic tire according to an embodiment of the present invention.
 FIG. 2 is a plan view illustrating a tread portion of a pneumatic tire according to an embodiment of the present invention.
 FIG. 3 is an explanatory diagram schematically illustrating a form of a sipe by cutting out a portion of a land portion including the sipe.

Description of Embodiments

[0015] Configurations of embodiments of the present invention will be described in detail below with reference to the accompanying drawings. FIG. 1 and FIG. 2 illustrate a pneumatic tire according to an embodiment of the present invention. In FIG. 2, Tc denotes a tire circumferential direction and Tw denotes a tire width direction.

[0016] As illustrated in FIG. 1, a pneumatic tire of an embodiment of the present invention includes a tread portion 1, a pair of sidewall portions 2 disposed on both sides of the tread portion 1, and a pair of bead portions 3 disposed in the sidewall portions 2 in an inner side in a tire radial direction. Note that "CL" in FIG. 1 denotes a tire equator. Additionally, FIG. 1 is a meridian cross-sectional view, and accordingly, although not illustrated, each of the tread portion 1, the sidewall portions 2, and the bead portions 3 extends in the tire circumferential direction to form an annular shape. Thus, the basic structure of the toroidal shape of the pneumatic tire is configured. Although the description using FIG. 1 is basically based on the illustrated meridian cross-sectional shape, all of the tire components each extend in the tire circumferential direction and form the annular shape.

[0017] A carcass layer 4 is mounted between the left-right pair of bead portions 3. The carcass layer 4 includes a plurality of reinforcing cords extending in the tire radial direction, and is folded back around a bead core 5 disposed in each of the bead portions 3 from a vehicle inner side to a vehicle outer side. Additionally, bead fillers 6 are disposed on the outer circumference of the bead cores 5, and each of the bead fillers 6 is enveloped by a main body portion and a folded back portion of the carcass layer 4. On the other hand, in the tread portion 1, a plurality of belt layers 7 (two layers in FIG. 1) are embedded on an outer circumferential side of the carcass layer 4. The belt layers 7 each include a plurality of reinforcing cords that are inclined with respect to the tire circumferential direction, with the reinforcing cords of the different layers arranged in a criss-cross manner. In these belt layers 7, the inclination angle of the reinforcing cords with respect to the tire circumferential direction ranges from, for example, 10° to 40°. In addition, a belt reinforcing layer 8 is provided on the outer circumferential side of the belt layers 7. The belt reinforcing layer 8 includes organic fiber cords oriented in the tire circumferential direction. In the belt reinforcing layer 8, the angle of the organic fiber cords with respect to the tire circumferential direction is set, for example, to from 0° to 5°.

[0018] The present invention may be applied to such a pneumatic tire having a general cross-sectional structure; however, the basic structure is not limited to the aforementioned structure.

[0019] The pneumatic tire is vulcanized and molded using a sectional tire mold. The tire mold includes an annular side mold for molding the tread portion 1, and the side mold includes sectors plurally divided along the tire circumferential direction. The sectors divided into 7 to 11 in the tire circumferential direction are usually used. As illustrated in FIG. 2, the tread portion 1 includes a sector dividing position P as well as a first boundary region S1 and a second boundary region S2, both of which include the sector dividing position P. The boundary regions S1, S2 each have a predetermined length in the tire circumferential direction on both sides of the sector dividing position P as the center. Specifically, the first boundary region S1 is a region within 15 mm in the tire circumferential direction on one side of the sector dividing position P as the center. Additionally, the second boundary region S2 is a region within 5 mm in the tire circumferential direction on one side of the sector dividing position P as the center.

[0020] Four circumferential grooves 9 extending in the tire circumferential direction are formed in the tread portion 1. The circumferential grooves 9 include a pair of inner circumferential grooves 9A located on both sides of a tire center line CL and a pair of outer circumferential grooves 9B located on the outermost side in the tire width direction. Land portions 10 are defined by the four circumferential grooves 9 in the tread portion 1. The land portions 10 include a center land portion 10A located on the tire center line CL, a pair of intermediate land portions 10B located on the outer side of the center land portion 10A in the tire width direction, and a pair of shoulder land portions 10C located on the outer side of the respective intermediate land portions 10B in the tire width direction. A plurality of sipes 20 extending in the tire width direction are formed in at least one row of the land portion 10 of the land portions 10A to 10C. The sipes 20 can be formed in a linear or zigzag-like manner on a road contact surface of the tread portion 1. The sipes 20 are narrow grooves having a groove width of 1.5 mm or less.

[0021] More specifically, a plurality of sipes 20A and a plurality of narrow grooves 31, which are inclined in the same direction with respect to the tire width direction, are disposed at intervals in the tire circumferential direction in the center land portion 10A. One end of the sipe 20A communicates with the inner circumferential groove 9A, and the other end

communicates with the narrow groove 31. On the other hand, the narrow groove 31 is a groove having a larger groove width than that of the sipe 20A. One end of the narrow groove 31 communicates with the inner circumferential groove 9A, and the other end communicates with the sipe 20A. The sipes 20A and the narrow grooves 31 are disposed alternately in the tire circumferential direction such that the narrow grooves 31 are disposed in a staggered manner in the tire circumferential direction in the center land portion 10A as a whole.

[0022] A plurality of lug grooves 32 inclined in the same direction with respect to the tire width direction are disposed at intervals in the tire circumferential direction in the intermediate land portion 10B. While one end of the lug groove 32 opens to the outer circumferential groove 9B, the other end terminates within the intermediate land portion 10B. The lug groove 32 includes a bent portion 32A formed in an acute angle manner at a midway position between the one end and the other end. A plurality of sipes 20B extending in a direction intersecting with the lug grooves 32 are disposed at intervals in the tire circumferential direction. The sipes 20B are divided into a plurality of portions by intersecting with the lug grooves 32, and the divided portions are disposed on the same straight lines. At least one end of the sipe 20B communicates with the outer circumferential groove 9B.

[0023] A plurality of lug grooves 33 inclined in the same direction with respect to the tire width direction are disposed at intervals in the tire circumferential direction in the shoulder land portion 10C. The lug grooves 33 do not communicate with the outer circumferential groove 9B. A plurality of narrow grooves 34 that communicate with the lug grooves 33 and extend in the tire circumferential direction are formed. A plurality of sipes 20C inclined in the same direction with respect to the tire width direction are disposed at intervals in the tire circumferential direction. The sipes 20C do not communicate with the outer circumferential groove 9B. The sipes 20C are divided into a plurality of portions by intersecting with the narrow grooves 34, and the divided portions are disposed on the same straight lines.

[0024] The sipes 20 (sipes 20A to 20C) described above include at least one two-dimensional sipe 21 and a plurality of three-dimensional sipes 22. In other words, all of the sipes 20 excluding the at least one two-dimensional sipe 21 are three-dimensional sipes 22. As illustrated in FIG. 3 (a), "two-dimensional sipe 21" is a sipe, the shape of which appearing on a tread surface (on a road contact surface of the tread portion 1) is constant along a sipe depth direction. For example, as in FIG. 3 (a), a zigzag shape on the tread surface indicates that the zigzag shape is maintained at any position in the sipe depth direction. Additionally, a linear shape on the tread surface indicates that the linear shape is maintained at any position in the sipe depth direction. Preferably, as illustrated, the two-dimensional sipe 21 has a linear shape that extends along the sipe depth direction in a cross-section (for example, a cross-section with hatched lines in the diagram) whose normal line direction is a sipe length direction. As illustrated in FIG. 3 (b), "three-dimensional sipe 22" is a sipe, the shape of which appearing on the tread surface changes along the sipe depth direction. For example, as in FIG. 3 (b), a zigzag shape on the tread surface indicates that the shape of the sipe changes into a linear shape or a different zigzag shape depending on the position in the sipe depth direction. Additionally, a linear shape on the tread surface indicates that the shape of the sipe changes into a different shape from the linear shape such as a zigzag shape, depending on the position in the sipe depth direction. Preferably, as illustrated, the three-dimensional sipe 22 has a shape extending while bending along the sipe depth direction in a cross-section (for example, a cross-section with hatched lines in the diagram) whose normal line direction is the sipe length direction. The three-dimensional sipe 22, which includes, as illustrated, planes having complicated unevenness that mutually contact each other in accordance with a deformation of the land portion 20, yields more excellent wet performance and snow performance than the two-dimensional sipe 21.

[0025] When comparing the two-dimensional sipe 21 and the three-dimensional sipe 22, the two-dimensional sipe 21 with its structure described above is formed by a blade having less unevenness in the depth direction, and the blade tends to come out easily after vulcanization. Conversely, the three-dimensional sipe 22 with its structure described above is formed by a blade having more unevenness in the depth direction, and the blade tends to come out less easily after vulcanization. An embodiment of the present invention takes this difference into consideration such that a few of the three-dimensional sipes 22, from which the blades come out less easily, are disposed (disposing many of the two-dimensional sipes 21, from which the blades come out more easily) in the vicinity of the sector dividing position P (first boundary region S1) where the tread rubber tends to bond to the mold easily, thus preventing bonding between the tire mold and the tread rubber. Specifically, a ratio R1 of the number of the three-dimensional sipes 22 included in the first boundary region S1 with respect to the total number of the sipes 20 included in the first boundary region S1; and a ratio Rt of the number of the three-dimensional sipes 22 in all of the tread portion 1 with respect to the total number of the sipes 20 in all of the tread portion 1 satisfy the relationship $R1 < Rt$.

[0026] Note that when counting the number of the sipes 20 (two-dimensional sipe 21 and three-dimensional sipe 22), the sipe 20 including at least a portion included in the first boundary region S1 is counted as the sipe 20 included in the first boundary region. Additionally, as in the intermediate land portion 10B and the shoulder land portion 10C in FIG. 2, when a pair of the sipes 20 are positioned on both sides of a groove and appear continuous, if the groove width of the groove positioned between the pair of sipes 20 is greater than the groove width of the sipe 20, they are counted as two divided separate sipes. Conversely, when the groove width of the groove positioned between the pair of sipes 20 is less than or equal to the groove width of the sipe 20, the pair of sipes 20 are counted as a single continuous sipe. In the illustrated example, the groove width of the lug groove 32 and that of the narrow groove 34 are larger than that of the sipe 20, and

accordingly, the pair of sipes 20 positioned on both sides thereof are deemed as separate sipes.

[0027] By thus adopting the three-dimensional sipe 22 and the two-dimensional sipe 21 as the plurality of sipes 20, and configuring the ratio R1 of the number of the three-dimensional sipes 22 in the first boundary region S1 to be smaller than the ratio Rt of the number of the three-dimensional sipes 22 in all of the tread portion 1, bonding between the tire mold and the tread rubber can be prevented, and the occurrence of poor appearance can be suppressed. Additionally, although the structure of the two-dimensional sipe 21 is simpler than that of the three-dimensional sipe 22 and running performance (wet performance and snow performance) based on the sipes 20 tends to be lower than that of the three-dimensional sipe 22, since a region having a lower ratio of the number of the three-dimensional sipes 22 is limited to the first boundary region S1 where contribution to bonding between the tire mold and the tread rubber is great, still a sufficient number of the three-dimensional sipes 22 are provided in the tire as a whole, and thus good running performance (wet performance and snow performance) based on the sipes 20 can be obtained. By using the two-dimensional sipe 21 or the three-dimensional sipe 22, that is, by using a difference in structure of the sipes 20 along the depth direction, rather than the shape of the sipe appearing on the tread surface, to adjust the easiness with which the blade comes out (the difficulty with which the rubber and the mold bond), this has no effect on the appearance of the tire (the sipe shape appearing on the tread surface).

[0028] When the size relationship between the ratio R1 and the ratio Rt is $R1 \geq Rt$, a larger number of the three-dimensional sipes 22 are disposed in the first boundary region S1 where the tire mold and the tread rubber tend to bond easily, and bonding between the tire mold and the tread rubber cannot be prevented. When the ratio R1 and the ratio Rt are set to the size relationship described above, a ratio R1/Rt of the ratio R1 to the ratio Rt is preferably set to not greater than 0.80, and more preferably not less than 0.3 and not greater than 0.7. The ratio R1/Rt can thus be set to sufficiently reduce the ratio of the three-dimensional sipes 22 in the first boundary region S1, preventing bonding between the tire mold and the tread rubber, advantageously suppressing the occurrence of poor appearance. When the ratio R1/Rt exceeds 0.80, the difference between the ratio R1 and the ratio Rt decreases, and the ratio of the three-dimensional sipes 22 in the first boundary region S1 is not sufficiently reduced, and this causes a difficulty in sufficiently preventing bonding between the tire mold and tread rubber.

[0029] An embodiment of the present invention prevents bonding between the tire mold and the tread rubber by disposing the two-dimensional sipe 21 and the three-dimensional sipe 22, and the overall structure (tread pattern) of the tread portion 1 is not particularly limited. As in the illustrated example, however, when a plurality of rows of land portions 10 include three or more rows of land portions 10 including a pair of shoulder land portions 10C and when all of the land portions 10 include the plurality of sipes 20, particularly good effect can be obtained. When the ratio of the number of the three-dimensional sipes 22 included in the first boundary region S1 of each of the land portions 10 with respect to the total number of the sipes 20 included in the first boundary region S1 of each of the land portions 10 is R1', and the ratio of the number of the three-dimensional sipes 20 in an entire circumference of each of the land portions 10 with respect to the total number of the plurality of the sipes 20 included in the entire circumference of each of the land portions 10 is Rt', the relationship of a ratio R1' / Rt' between the land portions 10 can be adjusted to effectively prevent bonding between the tire mold and the tread rubber.

[0030] Specifically, the ratio R1' / Rt' in the shoulder land portion 10C is preferably smaller than the ratio R1' / Rt' in any other land portion. That is, due to the shape of the tire as a whole (toroidal shape), bonding between the tire mold and the tread rubber tends to occur relatively more easily in the shoulder land portion 10C than in any other land portion, and by minimizing the ratio R1' / Rt' in the shoulder land portion 10C (minimizing the ratio of the three-dimensional sipes 22 included in the first boundary region S1), bonding between the tire mold and the tread rubber can be effectively prevented, and the occurrence of poor appearance can be advantageously suppressed.

[0031] Alternatively, an inclination angle θ , with respect to a tire width direction, of the sipes 20 provided in the first boundary region S1 of the land portion 10 having the smallest ratio R1' / Rt' is preferably smaller than an inclination angle θ , with respect to the tire width direction, of the sipes 20 provided in the first boundary region S1 of any other land portion 10. Generally, the smaller the inclination angle θ of the sipe 20 is, the less easily a blade forming the sipe 20 comes out, and thus the inclination angle of the sipe 20 and the ratio R1' / Rt' can be associated to reduce the ratio of the three-dimensional sipes 22 included in the first boundary region S1, where the inclination angle θ of the sipe 20 is small and the blades do not easily come out, such that bonding between the tire mold and the tread rubber can be effectively prevented and the occurrence of poor appearance can be advantageously suppressed.

[0032] Note that the sector dividing position P basically divides sectors along the tire width direction, and the inclination angle θ of the sipe 20 with respect to the tire width direction is substantially synonymous with an inclination angle of the sipe 20 with respect to a sector dividing line (see FIG. 2). The inclination angle θ of the sipe 20 is an angle formed between: a straight line connecting the center positions of the groove width at both ends of the sipe 20 in a longitudinal direction; and the tire width direction (sector dividing line). Although the range of the inclination angle of the sipe 20 is not particularly limited, the inclination angle θ , with respect to the tire width direction, of the sipe 20 provided in the first boundary region S1 of the land portion 10 having the smallest ratio R1' / Rt' can be set to, for example, from 0° to 10°, and the inclination angle θ , with respect to the tire width direction, of the sipe 20 provided in the first boundary region S1 of any other land portion 10 can be set to, for example, from 15° to 40°.

[0033] The bonding between the tire mold and the tread rubber tends to occur more easily toward the sector dividing position P, and the ratio of the three-dimensional sipes 22 can be reduced toward the sector dividing position P to effectively prevent bonding between the tire mold and the tread rubber. Accordingly, the ratio R1 of the number of the three-dimensional sipes 22 included in the first boundary region S 1 with respect to the total number of the sipes 10 included in the first boundary region S 1; and a ratio R2 of the number of the three-dimensional sipes 22 included in the second boundary region S2 with respect to the total number of the sipes 10 included in the second boundary region S2 preferably satisfy the relationship $R1 > R2$. Thus setting a relationship between the ratios R1, R2 reduces the ratio of the three-dimensional sipes toward the sector dividing position, effectively preventing bonding between the tire mold and the tread rubber and advantageously suppressing the occurrence of poor appearance. Note that the number of the sipes 20 included in the second boundary region S2 is counted the same way as that included in the first boundary region S1. When the sipe 20 includes at least a portion included in the secondary boundary region S2, the sipe 20 is counted as a sipe included in the second boundary region S2.

[0034] As described above, an embodiment of the present invention prevents bonding of the tire mold and the tread rubber by disposing the two-dimensional sipe 21 and the three-dimensional sipe 22; still generally, the shallower the sipe 20 is, the more easily a blade forming the sipe 20 comes out. Thus, not only a difference in structures of the two-dimensional sipe 21 and the three-dimensional sipe 22, but also sipe depths can be considered to adjust the easiness with which the blade comes out. Specifically, an average D1 of the maximum depths of the sipes 20 included in the first boundary region S1 and an average Dt of the maximum depths of the sipes 20 in all of the tread portion 1 preferably satisfy the relationship $D1 < Dt$. As described above, the smaller the maximum depth of the sipe 20 is, the more easily a blade forming the sipe 20 comes out, and thus by reducing the maximum depths of the sipes 20 in the vicinity of the sector dividing position P (first boundary region S1) where the tread rubber tends to bond to the mold easily, bonding between the tire mold and the tread rubber can be effectively prevented, and the occurrence of poor appearance can be advantageously suppressed. When the relationship between the sipe depths is thus set, a ratio $D1/Dt$ is preferably set to, for example, within a range of from 0.30 to 0.80. Note that "average of the maximum depths of the sipes 20" refers to averaging the maximum depth of each of the sipes 20 included in the region of interest (depths from the road contact surface of the tread portion 1 to the maximum depth portions of the sipes 20).

[0035] A type of tire to which a sipe structure according to an embodiment of the present invention is applied is not particularly limited, but preferably, such a sipe structure is applied to a winter tire including a plurality of sipes. In the winter tire to which an embodiment of the present invention is applied, wet performance and snow performance can be enhanced, bonding of a tire mold and tread rubber can be prevented, and the occurrence of poor appearance during vulcanization molding can be suppressed, without changing the appearance of the tire.

Examples

[0036] Tires of Conventional Example 1, Comparative Examples 1 and 2, and Examples 1 to 13 are manufactured. The tires have: a tire size of 205/55R16, a basic structure illustrated in FIG. 1, and a basic tread pattern of FIG. 2. The tires are set for: presence of sipes in a boundary region, a size relationship of the ratios R1, Rt, the ratio $R1/Rt$, a land portion having the smallest ratio $R1'/Rt'$, a land portion having the smallest inclination angle θ , a size relationship of the ratios R1, R2, and a size relationship of the depths D1 and Dt as indicated in Table 1.

[0037] Note that a tire of Conventional Example 1 has a structure in which the number of sipes in the first boundary region (second boundary region) is so reduced that no sipes are disposed in the first boundary region (second boundary region).

[0038] In each of the columns of "Land portion having smallest ratio $R1'/Rt'$ " and "land portion having smallest inclination angle θ ", a type of land portion (Center, Intermediate, or Shoulder) is indicated. The ratio $R1'/Rt'$ or the inclination angle θ that is common in all of the land portions is indicated as "Uniform".

[0039] The test tires are evaluated, according to the following test methods, for braking performance on wet road surfaces (wet performance), braking performance on icy and snowy road surfaces (snow performance), and a poor appearance occurrence rate. Table 1 shows the results.

Wet Performance

[0040] Each of the test tires is assembled on a wheel having a rim size of 16×7J, inflated to an air pressure of 230 kPa, and mounted on a test vehicle (passenger vehicle) having an engine displacement of 2000 cc. Braking is performed from a traveling condition at a speed of 40 km/h on a wet road surface, and a braking distance until the test vehicle comes to a complete stop is measured. The evaluation results are expressed as index values using reciprocals of measurement values, with Conventional Example 1 being assigned an index value of 100. Larger index values indicate excellent braking performance on wet road surfaces (wet performance).

Snow Performance

[0041] Each of the test tires is assembled on a wheel having a rim size of 16×7J, inflated to an air pressure of 230 kPa, and mounted on a test vehicle having an engine displacement of 2000 cc. Braking is performed from a traveling condition at a speed of 40 km/h on an icy and snowy road surface, and a braking distance until the test vehicle comes to a complete stop is measured. The evaluation results are expressed as index values using reciprocals of measurement values, with Conventional Example 1 being assigned an index value of 100. Larger index values indicate excellent braking performance on icy and snowy road surfaces (snow performance).

Poor Appearance Occurrence Rate

[0042] 1000 of each of the test tires are manufactured, chips and cracks of a land portion in each boundary region (first boundary region) on a tire circumference are visually confirmed, and the number of the boundary regions with the occurrence of the chips and the cracks is counted. The evaluation results show the ratio of the number of boundary regions with the occurrence of chips and cracks in each of the test tires. Smaller ratios indicate a superior suppressing effect on the occurrence of poor appearance.

[Table 1-1]

	Conventional Example 1	Comparative Example 1	Comparative Example 2
Presence of sipe in boundary region	No	Yes	Yes
Size relationship of ratios R1, Rt	-	$R1 > Rt$	$R1 = Rt$
Ratio R1/Rt	-	1.2	1.0
Land portion having smallest ratio R1' / Rt'	-	Uniform	Uniform
Land portion having smallest inclination angle θ	-	Uniform	Uniform
Size relationship of ratios R1, R2	-	$R1 = R2$	$R1 = R2$
Size relationship of depths D1, Dt	-	$D1 = Dt$	$D1 = Dt$
Snow performance Index value	100	95	105
Wet performance Index value	100	95	105
Appearance failure rate %	0.5	0.5	0.5

[Table 1-2]

	Example 1	Example 2	Example 3	Example 4	Example 5
Presence of sipe in boundary region	Yes	Yes	Yes	Yes	Yes
Size relationship of ratios R1, Rt	$R1 < Rt$	$R1 < Rt$	$R1 < Rt$	$R1 < Rt$	$R1 < Rt$
Ratio R1/Rt	0.9	0.8	0.3	0.8	0.8
Land portion having smallest ratio R1' / Rt'	Uniform	Uniform	Uniform	Center	Intermediate
Land portion having smallest inclination angle θ	Uniform	Uniform	Uniform	Uniform	Uniform
Size relationship of ratios R1, R2	$R1 = R2$	$R1 = R2$	$R1 = R2$	$R1 = R2$	$R1 = R2$
Size relationship of depths D1, Dt	$D1 = Dt$	$D1 = Dt$	$D1 = Dt$	$D1 = Dt$	$D1 = Dt$

EP 3 888 945 B9

(continued)

		Example 1	Example 2	Example 3	Example 4	Example 5
5	Snow performance Index value	105	105	101	105	105
	Wet performance Index value	105	105	101	105	105
10	Appearance failure rate %	0.1	0.05	0.05	0.05	0.05

[Table 2-1]

		Example 6	Example 7	Example 8	Example 9
15	Presence of sipe in boundary region	Yes	Yes	Yes	Yes
	Size relationship of ratios R1, Rt	$R1 < Rt$	$R1 < Rt$	$R1 < Rt$	$R1 < Rt$
	Ratio R1/Rt	0.8	0.8	0.8	0.8
20	Land portion having smallest ratio R1' / Rt'	Shoulder	Shoulder	Shoulder	Shoulder
	Land portion having smallest inclination angle θ	Uniform	Center	Intermediate	Shoulder
	Size relationship of ratios R1, R2	$R1 = R2$	$R1 = R2$	$R1 = R2$	$R1 = R2$
25	Size relationship of depths D1, Dt	$D1 = Dt$	$D1 = Dt$	$D1 = Dt$	$D1 = Dt$
	Snow performance Index value	108	108	108	108
	Wet performance Index value	108	108	108	108
30	Appearance failure rate %	0.03	0.03	0.03	0.01

[Table 2-2]

		Example 10	Example 11	Example 12	Example 13
35	Presence of sipe in boundary region	Yes	Yes	Yes	Yes
	Size relationship of ratios R1, Rt	$R1 < Rt$	$R1 < Rt$	$R1 < Rt$	$R1 < Rt$
	Ratio R1/Rt	0.8	0.8	0.8	0.8
40	Land portion having smallest ratio R1' / Rt'	Uniform	Uniform	Uniform	Uniform
	Land portion having smallest inclination angle θ	Uniform	Uniform	Uniform	Uniform
	Size relationship of ratios R1, R2	$R1 < R2$	$R1 > R2$	$R1 = R2$	$R1 = R2$
	Size relationship of depths D1, Dt	$D1 = Dt$	$D1 = Dt$	$D1 > Dt$	$D1 < Dt$
45	Snow performance Index value	104	110	104	110
	Wet performance Index value	104	110	104	110
	Appearance failure rate %	0.15	0.02	0.15	0.01

50 **[0043]** As can be seen from Tables 1 to 2, each of Examples 1 to 10 provides, in a well-balanced manner, better wet performance and snow performance as well as a lower poor appearance occurrence rate than Conventional Example 1. On the other hand, in Comparative Example 1, the ratio R1 is greater than the ratio Rt, the ratio of the three-dimensional sipes included in the first boundary region is greater, and thus the appearance failure rate is worsened. In Comparative Example 2, the ratio R1 and the ratio Rt are equal, there is no difference in the ratios of the three-dimensional sipes between the entire tire and the first boundary region, and thus the appearance failure rate cannot be lowered.

Reference Signs List

[0044]

- 5 1 Tread portion
- 2 Sidewall portion
- 3 Bead portion
- 4 Carcass layer
- 5 Bead core
- 10 6 Bead filler
- 7 Belt layer
- 8 Belt reinforcing layer
- 9 Circumferential groove
- 10 Land portion
- 15 10A Center land portion
- 10B Intermediate land portion
- 10C Shoulder land portion
- 20 Sipe
- 21 Two-dimensional sipe
- 20 22 Three-dimensional sipe
- P Sector dividing position
- S1 First boundary region
- S2 Second boundary region

25

Claims**1.** A pneumatic tire, comprising:

- 30 in a tread portion (1), a plurality of circumferential grooves (9) extending in a tire circumferential direction (Tc);
a plurality of rows of land portions (10) defined by the plurality of circumferential grooves (9);
in at least one of the plurality of rows of land portions (10), a plurality of sipes (20) extending in a tire width direction (Tw); and
- 35 the tread portion (1) being formed by a plurality of sectors divided in the tire circumferential direction (Tc),
the plurality of sipes (20) comprising a three-dimensional sipe (22), whose shape appearing on a tread surface changes along a sipe depth direction, and a two-dimensional sipe (21), whose shape appearing on the tread surface is constant along the sipe depth direction, wherein the plurality of rows of land portions (10) comprise three or more rows of land portions (10) comprising a pair of shoulder land portions (10C), all of the plurality of rows of land portions (10) comprise the plurality of sipes (20),
- 40 **characterised in that**
a range within 15 mm on one side of a sector dividing position (P) in the tire circumferential direction (Tc) is a first boundary region (S 1), and
a ratio R1 of a number of a plurality of the three-dimensional sipes (22) disposed in the first boundary region (S1) with respect to a total number of the plurality of sipes (20) disposed in the first boundary region (S1) and a ratio Rt
- 45 of a number of the plurality of three-dimensional sipes (22) in all of the tread portion (1) with respect to a total number of the plurality of sipes (20) in all of the tread portion (1) is satisfying a relationship $R1 < Rt$,
wherein a sipe (20) comprising at least a portion included in the first boundary region (S1) is counted as a sipe (20) included in the first boundary region (S1),
wherein the sipes (20) are counted as two divided separate sipes (20), when a pair of the sipes (20) are positioned
- 50 on both sides of a groove and appear continuous, if the groove width of the groove positioned between the pair of sipes (20) is greater than the groove width of the sipe (20),

a ratio of a number of the plurality of three-dimensional sipes (22) disposed in the first boundary region (S1) of each of the plurality of rows of land portions (10) with respect to a total number of the plurality of sipes (20) disposed in the first boundary region (S1) of each of the plurality of rows of land portions (10) is $R1'$,
a ratio of a number of the plurality of three-dimensional sipes (22) in an entire circumference of each of the plurality of rows of land portions (10) with respect to a total number of the plurality of sipes (20) in the entire circumference of each of the plurality of rows of land portions (10) is Rt' , and
- 55

an inclination angle (θ), with respect to the tire width direction (T_w), of the plurality of sipes (20) provided in a land portion (10) having a smallest ratio $R1' / R_t'$ is smaller than an inclination angle (θ), with respect to the tire width direction (T_w), of the plurality of sipes (20) provided in any other of the plurality of rows of land portions (10),

wherein the inclination angle (θ) of the sipe (20) is an angle formed between a straight line connecting the center positions of the groove width at both ends of the sipe (20) in a longitudinal direction and the sector dividing line.

2. The pneumatic tire according to claim 1,

wherein a ratio $R1/R_t$ of the ratio $R1$ and the ratio R_t is 0.80 or less.

3. The pneumatic tire according to claim 1 or 2, wherein

the plurality of rows of land portions (10) comprise three or more rows of land portions (10) comprising a pair of shoulder land portions (10C),

all of the plurality of rows of land portions (10) comprise the plurality of sipes (20),

a ratio of a number of the plurality of three-dimensional sipes (22) disposed in the first boundary region (S1) of each of the plurality of rows of land portions (10) with respect to a total number of the plurality of sipes (22) disposed in the first boundary region (S1) of each of the plurality of rows of land portions (10) is $R1'$,

a ratio of a number of the plurality of three-dimensional sipes (22) in an entire circumference of each of the plurality of rows of land portions (10) with respect to a total number of the plurality of sipes (20) in the entire circumference of each of the plurality of rows of land portions (10) is R_t' , and

a ratio $R1' / R_t'$ in each of the pair of shoulder land portions (10C) is smaller than a ratio $R1' / R_t'$ in any other of the plurality of rows of land portions (10).

4. The pneumatic tire according to any one of claims 1 to 3, wherein

a range within 5 mm on one side of the sector dividing position (P) in the tire circumferential direction (T_c) is a second boundary region (S2), and

the ratio $R1$ of the number of the plurality of three-dimensional sipes (22) disposed in the first boundary region (S1) with respect to the total number of the plurality of sipes (20) disposed in the first boundary region (S1) and a ratio $R2$ of a number of the plurality of three-dimensional sipes (22) disposed in the second boundary region (S2) with respect to a total number of the plurality of sipes (20) disposed in the second boundary region (S2) satisfy the relationship $R1 > R2$.

5. The pneumatic tire according to any one of claims 1 to 4,

wherein an average $D1$ of maximum depths of the plurality of sipes (20) disposed in the first boundary region (S1) and an average D_t of maximum depths of the plurality of sipes (20) in all of the tread portion (1) satisfy the relationship $D1 < D_t$.

Patentansprüche

1. Luftreifen, umfassend:

in einem Laufflächenabschnitt (1) eine Mehrzahl von Umfangsrillen (9), die sich in einer Reifenumfangsrichtung (T_c) erstrecken;

eine Mehrzahl von Reihen von Stegabschnitten (10), die durch die Mehrzahl von Umfangsrillen (9) definiert sind; in mindestens einer der Mehrzahl von Reihen von Stegabschnitten (10) eine Mehrzahl von Lamellen (20), die sich

in einer Reifenbreitenrichtung (T_w) erstrecken; und

wobei der Laufflächenabschnitt (1) aus einer Mehrzahl von Sektoren besteht, die in Reifenumfangsrichtung (T_c) unterteilt sind,

wobei die Mehrzahl von Lamellen (20) eine dreidimensionale Lamelle (22), deren auf einer Laufflächenoberfläche erscheinende Form sich entlang einer Lamellentiefenrichtung ändert, und eine zweidimensionale Lamelle (21) umfasst, deren auf der Laufflächenoberfläche erscheinende Form entlang der Lamellentiefenrichtung konstant ist, wobei die Mehrzahl von Reihen von Stegabschnitten (10) drei oder mehr Reihen von Stegabschnitten (10) umfasst, die ein Paar Schulterstegabschnitte (10C) umfassen, wobei alle der Mehrzahl von Reihen von Stegabschnitten (10) die Vielzahl von Lamellen (20) umfassen,

dadurch gekennzeichnet, dass

ein Bereich innerhalb von 15 mm auf einer Seite einer Sektorteilungsposition (P) in Reifenumfangsrichtung (Tc) ein erster Grenzbereich (S1) ist, und

ein Verhältnis $R1$ einer Anzahl einer Mehrzahl der dreidimensionalen Lamellen (22), die in dem ersten Grenzbereich (S1) angeordnet sind, in Bezug auf eine Gesamtzahl der Mehrzahl von Lamellen (20), die in dem ersten Grenzbereich (S1) angeordnet sind, und ein Verhältnis Rt einer Anzahl der Vielzahl von dreidimensionalen Lamellen (22) in dem gesamten Laufflächenabschnitt (1) in Bezug auf eine Gesamtzahl der Vielzahl von Lamellen (20) in dem gesamten Laufflächenabschnitt (1) eine Beziehung $R1 < Rt$ erfüllt, wobei eine Lamelle (20), die mindestens einen in der ersten Grenzregion (S1) enthaltenen Abschnitt umfasst, als eine in dem ersten Grenzbereich (S1) enthaltene Lamelle (20) gezählt wird,

wobei die Lamellen (20) als zwei geteilte, separate Lamellen (20) gezählt werden, wenn ein Paar der Lamellen (20) auf beiden Seiten einer Rille angeordnet ist und durchgehend erscheint, wenn die Rillenbreite der zwischen dem Paar von Lamellen (20) angeordneten Rille größer als die Rillenbreite der Lamelle (20) ist,

ein Verhältnis einer Anzahl der Mehrzahl von dreidimensionalen Lamellen (22), die in dem ersten Grenzbereich (S1) jeder der Mehrzahl von Reihen von Stegabschnitten (10) angeordnet sind, in Bezug auf eine Gesamtzahl der Mehrzahl von Lamellen (20), die in dem ersten Grenzbereich (S1) jeder der Mehrzahl von Reihen von Stegabschnitten (10) angeordnet sind, $R1'$ ist,

ein Verhältnis einer Anzahl der Mehrzahl von dreidimensionalen Lamellen (22) in einem Gesamtumfang jeder der Mehrzahl von Reihen von Stegabschnitten (10) in Bezug auf eine Gesamtzahl der Mehrzahl von Lamellen (20) in dem Gesamtumfang jeder der Mehrzahl von Reihen von Stegabschnitten (10) Rt' ist, und

ein Neigungswinkel (θ), in Bezug auf die Reifenbreitenrichtung (Tw), der Mehrzahl von Lamellen (20), die in einem Stegabschnitt (10) bereitgestellt sind, der ein kleinstes Verhältnis $R1' / Rt'$ aufweist, kleiner ist als ein Neigungswinkel (θ), in Bezug auf die Reifenbreitenrichtung (Tw), der Mehrzahl von Lamellen (20), die in einer beliebigen anderen der Mehrzahl von Reihen von Stegabschnitten (10) bereitgestellt sind, wobei der Neigungswinkel (θ) der Lamelle (20) ein Winkel ist, der zwischen einer geraden Linie, die die Mittelpunkte der Rillenbreite an beiden Enden der Lamelle (20) in Längsrichtung verbindet, und der Sektorteilungslinie gebildet wird.

2. Luftreifen nach Anspruch 1,

wobei ein Verhältnis $R1/Rt$ des Verhältnisses $R1$ und des Verhältnisses Rt 0,80 oder weniger beträgt.

3. Luftreifen nach Anspruch 1 oder 2, wobei

die Mehrzahl von Reihen von Stegabschnitten (10) drei oder mehr Reihen von Stegabschnitten (10), umfassend ein Paar Schulterstegabschnitte (10C), umfassen,

alle der Mehrzahl von Reihen von Stegabschnitten (10) die Mehrzahl von Lamellen (20) umfassen, ein Verhältnis einer Anzahl der Mehrzahl von dreidimensionalen Lamellen (22), die in dem ersten Grenzbereich (S1) jeder der Mehrzahl von Reihen von Landabschnitten (10) angeordnet sind, in Bezug auf eine Gesamtzahl der Mehrzahl von Lamellen (22), die in dem ersten Grenzbereich (S1) jeder der Mehrzahl von Reihen von Stegabschnitten (10) angeordnet sind, $R1'$ ist,

ein Verhältnis einer Anzahl der Mehrzahl von dreidimensionalen Lamellen (22) in einem Gesamtumfang jeder der Mehrzahl von Reihen von Stegabschnitten (10) in Bezug auf eine Gesamtzahl der Mehrzahl von Lamellen (20) in dem Gesamtumfang jeder der Mehrzahl von Reihen von Stegabschnitten (10) Rt' ist, und

ein Verhältnis $R1' / Rt'$ in jedem Paar von Schulterstegabschnitten (10C) kleiner als ein Verhältnis $R1' / Rt'$ in jeder anderen der Mehrzahl von Reihen von Stegabschnitten (10) ist.

4. Luftreifen nach einem der Ansprüche 1 bis 3, wobei

ein Bereich innerhalb von 5 mm auf einer Seite der Sektorteilungsposition (P) in Reifenumfangsrichtung (Tc) ein zweiter Grenzbereich (S2) ist, und

das Verhältnis $R1$ der Anzahl der im ersten Grenzbereich (S1) angeordneten Vielzahl dreidimensionaler Lamellen (22) zu der Gesamtanzahl der im ersten Grenzbereich (S1) angeordneten Mehrzahl von Lamellen (20) und ein Verhältnis $R2$ einer Anzahl der im zweiten Grenzbereich (S2) angeordneten Mehrzahl dreidimensionaler Lamellen (22) zu einer Gesamtanzahl der im zweiten Grenzbereich (S2) angeordneten Mehrzahl von Lamellen (20) die Beziehung $R1 > R2$ erfüllen.

5. Luftreifen nach einem der Ansprüche 1 bis 4,

wobei ein Durchschnitt $D1$ der maximalen Tiefen der Mehrzahl von Lamellen (20), die in dem ersten Grenzbereich (S1) angeordnet sind, und ein Durchschnitt Dt der maximalen Tiefen der Mehrzahl von Lamellen (20) im gesamten

Laufflächenabschnitt (1) die Beziehung $D1 < Dt$ erfüllen.

Revendications

1. Pneumatique, comprenant :

dans une partie de bande de roulement (1), une pluralité de rainures circonférentielles (9) s'étendant dans une direction circonférentielle de pneu (T_c) ;

une pluralité de rangées de parties de méplat (10) définies par la pluralité de rainures circonférentielles (9) ; dans au moins l'une parmi la pluralité de rangées de parties de méplat (10), une pluralité de lamelles (20) s'étendant dans une direction de largeur de pneu (T_w) ; et

la partie de bande de roulement (1) étant formée d'une pluralité de secteurs divisés dans la direction circonférentielle de pneu (T_c),

la pluralité de lamelles (20) comprenant une lamelle tridimensionnelle (22), dont la forme apparaissant sur une surface de bande de roulement change le long d'une direction de profondeur de lamelle, et une lamelle bidimensionnelle (21), dont la forme apparaissant sur la surface de bande de roulement est constante le long de la direction de profondeur de lamelle, dans lequel la pluralité de rangées de parties de méplat (10) comprennent trois rangées ou plus de parties de méplat (10) comprenant une paire de parties de méplat d'épaulement (10C), toutes les rangées de la pluralité de rangées de parties de méplat (10) comprennent la pluralité de lamelles (20),

caractérisé en ce que

une plage située à moins de 15 mm sur un côté d'une position de division de secteur (P) dans la direction circonférentielle de pneu (T_c) est une première région limite (S_1), et

un rapport R_1 d'un nombre d'une pluralité de lamelles tridimensionnelles (22) disposées dans la première région limite (S_1) par rapport à un nombre total de la pluralité de lamelles (20) disposées dans la première région limite (S_1) et un rapport R_t d'un nombre de la pluralité de lamelles tridimensionnelles (22) dans toute la partie de bande de roulement (1) par rapport à un nombre total de la pluralité de lamelles (20) dans toute la partie de bande de roulement (1) satisfait à une relation $R_1 < R_t$, dans lequel une lamelle (20) comprenant au moins une partie incluse dans la première région limite (S_1) est comptée comme une lamelle (20) incluse dans la première région limite (S_1),

dans lequel les lamelles (20) sont comptées comme deux lamelles séparées (20) divisées lorsqu'une paire de lamelles (20) sont positionnées de part et d'autre d'une rainure et semblent continues, si la largeur de rainure de la rainure positionnée entre la paire de lamelles (20) est supérieure à la largeur de rainure de la lamelle (20),

un rapport d'un nombre de la pluralité de lamelles tridimensionnelles (22) disposées dans la première région limite (S_1) de chacune de la pluralité de rangées de parties de méplat (10) par rapport à un nombre total de la pluralité de lamelles (20) disposées dans la première région limite (S_1) de chacune de la pluralité de rangées de parties méplat (10) est R_1' ,

un rapport d'un nombre de la pluralité de lamelles tridimensionnelles (22) sur l'ensemble de la circonférence de chacune de la pluralité de rangées de parties de méplat (10) par rapport à un nombre total de la pluralité de lamelles (20) sur l'ensemble de la circonférence de chacune de la pluralité de rangées de parties de méplat (10) est R_t' , et

un angle d'inclinaison (θ), par rapport à la direction de largeur de pneu (T_w), de la pluralité de lamelles (20) prévues dans une partie de méplat (10) ayant un rapport R_1' / R_t' le plus petit est inférieur à un angle d'inclinaison (θ), par rapport à la direction de largeur de pneu (T_w), de la pluralité de lamelles (20) prévues dans une quelconque autre de la pluralité de rangées de parties de méplat (10), dans lequel l'angle d'inclinaison (θ) de la lamelle (20) est un angle formé entre une ligne droite reliant les positions centrales de la largeur de rainure de part et d'autre de la lamelle (20) dans une direction longitudinale et la ligne de division de secteur.

2. Pneumatique selon la revendication 1, dans lequel le rapport R_1/R_t du rapport R_1 et du rapport R_t est inférieur ou égal à 0,80.

3. Pneumatique selon la revendication 1 ou 2, dans lequel

la pluralité de rangées de parties de méplat (10) comprennent trois rangées ou plus de parties de méplat (10) comprenant une paire de parties de méplat d'épaulement (10C), toutes les rangées de la pluralité de rangées de parties de méplat (10) comprennent la pluralité de lamelles (20), un rapport d'un nombre de la pluralité de lamelles tridimensionnelles (22) disposées dans la première région

limite (S1) de chacune de la pluralité de rangées de parties de méplat (10) par rapport à un nombre total de la pluralité de lamelles (22) disposées dans la première région limite (S1) de chacune de la pluralité de rangées de parties de méplat (10) est $R1'$,
 un rapport d'un nombre de la pluralité de lamelles tridimensionnelles (22) sur l'ensemble de la circonférence de
 chacune de la pluralité de rangées de parties de méplat (10) par rapport à un nombre total de la pluralité de
 lamelles (20) sur l'ensemble de la circonférence de chacune de la pluralité de rangées de parties de méplat (10)
 est Rt' , et
 un rapport $R1' / Rt'$ dans chacune de la paire de parties de méplat d'épaulement (10C) est inférieur à un rapport
 $R1' / Rt'$ dans un quelconque autre de la pluralité de rangées de parties de méplat (10).

4. Pneumatique selon l'une quelconque des revendications 1 à 3, dans lequel

une plage située à moins de 5 mm sur un côté de la position de division de secteur (P) dans la direction
 circonférentielle de pneu (Tc) est une seconde région limite (S2), et
 le rapport $R1$ du nombre de la pluralité de lamelles tridimensionnelles (22) disposées dans la première région
 limite (S1) par rapport au nombre total de la pluralité de lamelles (20) disposées dans la première région limite
 (S1) et un rapport $R2$ d'un nombre de la pluralité de lamelles tridimensionnelles (22) disposées dans la seconde
 région limite (S2) par rapport à un nombre total de la pluralité de lamelles (20) disposées dans la seconde région
 limite (S2) satisfont à la relation $R1 > R2$.

5. Pneumatique selon l'une quelconque des revendications 1 à 4,
 dans lequel une moyenne $D1$ de profondeurs maximales de la pluralité de lamelles (20) disposées dans la première
 région limite (S1) et une moyenne Dt de profondeurs maximales de la pluralité de lamelles (20) dans l'ensemble de la
 partie de bande de roulement (1) satisfont à la relation $D1 < Dt$.




FIG. 1




FIG. 2




FIG. 3

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2005041339 A [0003]
- JP 2012041024 A [0003]
- JP 2005205988 A [0003]
- JP 2013136366 A [0004]
- JP 3494511 B [0005]
- JP 4411975 B [0005]