



EUROPEAN PATENT APPLICATION

(43) Date of publication:
06.10.2021 Bulletin 2021/40

(21) Application number: **21166012.1**

(22) Date of filing: **30.03.2021**

(51) Int Cl.:
D06F 34/10 (2020.01) **D06F 29/00** (2006.01)
D06F 101/00 (2020.01) **D06F 101/20** (2020.01)
D06F 103/02 (2020.01) **D06F 105/56** (2020.01)
D06F 105/58 (2020.01) **D06F 34/04** (2020.01)
D06F 34/28 (2020.01)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(30) Priority: **31.03.2020 KR 20200039326**
21.09.2020 KR 20200121625

(71) Applicant: **LG Electronics Inc.**
Seoul 07336 (KR)

(72) Inventors:
• **KIM, Dowan**
08592 Seoul (KR)
• **CHOE, Woonje**
08592 Seoul (KR)


(74) Representative: **Vossius & Partner**
Patentanwälte Rechtsanwälte mbB
Siebertstraße 3
81675 München (DE)

(54) **LAUNDRY TREATING APPARATUS AND CONTROL METHOD FOR THE SAME**

(57) A control method for a laundry treating apparatus (100) comprises a course setup step (S130) of inputting a washing course through a washing machine interface provided to receive a control command; a first communication step of transmitting the washing course to a dryer by a washing machine (L) if a control command

requesting recommendation of a drying course is input through the washing machine interface (P2); and an interface power supply step (S230) of supplying a power to a dryer interface provided to receive a control command if the dryer (T) receives information on the washing course.

[Fig. 5]



Description

[0001] This application claims the benefit of the Korean Patent Applications Nos. 10-2020-0039326 and 10-2020-0121625, filed on March 31 and September 21, 2020, which is hereby incorporated by reference as if fully set forth herein.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present disclosure relates to a laundry treating apparatus and a control method for the same.

Discussion of the Related Art

[0003] A laundry treating apparatus collectively refers to a laundry washing apparatus, a laundry drying apparatus, and a laundry washing and drying apparatus.

[0004] A laundry treating apparatus of the related art is provided to include a dryer for drying laundry, and a washing machine located on an upper surface of the dryer or provided to support a bottom surface of the dryer and then wash laundry. The laundry treating apparatus in which the dryer and the washing machine are stacked up and down has an advantage in that a user may easily move washed laundry from the washing machine to the dryer.

[0005] However, in the aforementioned laundry treating apparatus of the related art, since a controller provided in the dryer and a controller provided in the washing machine operate by their respective circuits independent from each other, a problem occurs in that one apparatus fails to control another apparatus. Therefore, when the operation of any one of the washing machine and the dryer is completed, a problem occurs in that a user should directly perform a process of supplying a power to the other one and a process of inputting a control command.

SUMMARY OF THE INVENTION

[0006] Accordingly, the present disclosure is directed to a laundry treating apparatus and a control method for the same, which substantially obviate one or more problems due to limitations and disadvantages of the related art.

[0007] An object of the present disclosure is to provide a laundry treating apparatus and a control method for the same, in which one of two treating apparatuses capable of washing and drying laundry may control the other one.

[0008] Another object of the present disclosure is to provide a laundry treating apparatus and a control method for the same, in which a predicted time required for drying of laundry may be notified to a user.

[0009] Other object of the present disclosure is to provide a laundry treating apparatus and a control method for the same, in which consumption of a standby power

may be minimized.

[0010] Additional advantages, objects, and features of the disclosure will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the disclosure. The objectives and other advantages of the disclosure may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

[0011] To achieve these objects and other advantages and in accordance with the purpose of the disclosure, as embodied and broadly described herein, the present disclosure provides a control method for a laundry treating apparatus comprising a washing machine provided with a tub in which water is stored and a washing drum provided inside the tub, storing laundry therein, and a dryer provided with a drying drum in which laundry is stored and a supply unit for removing water from laundry by supplying the air to the drying drum.

[0012] The control method may be provided to include a course setup step of inputting a washing course through a washing machine interface provided to receive a control command; a first communication step of transmitting the washing course to the dryer by the washing machine if a preset control command is input through the washing machine interface; and an interface power supply step of supplying a power to a dryer interface provided to receive a control command if the dryer receives information on the washing course.

[0013] The preset control command may be set to a control command requesting recommendation of a drying course.

[0014] The control method may further comprise a course selection step of selecting one of a plurality of drying courses, which can be executed by the dryer, if the dryer receives the information on the washing course; and a course display step of displaying the recommended course on the dryer interface.

[0015] The control method may further comprise a laundry amount measuring step of measuring the amount of laundry stored in the washing drum by being initiated after the course setup step is completed; a second communication step of transmitting the amount of laundry measured at the laundry amount measuring step to the dryer by the washing machine; and a time display step of displaying a predicted time required to complete the recommended course on the dryer interface.

[0016] The control method may further comprise a drying standby mode step of blocking a power supplied to the dryer interface and a dryer driving unit controlling rotation of the drying drum, wherein the drying standby mode step may be initiated when a preset reference time passes after the time display step is completed.

[0017] The control method may further comprise a washing standby mode step of blocking a power supplied to the washing machine interface and a washing machine driving unit controlling rotation of the washing drum,

wherein the washing standby mode step may be initiated when execution of the washing course ends.

[0018] The course selection step may select a default course set to the dryer as the recommended course.

[0019] The course selection step may select a drying course for setting the same kind of laundry as washing target laundry set to the washing course as a drying target, as the recommended course.

[0020] In another aspect of the present disclosure, a control method for a laundry treating apparatus comprises a washing standby mode step of supplying a power to a washing machine second controller controlling a washing machine interface without supplying the power to a washing machine driving unit controlling rotation of a washing drum, the washing machine interface, and a washing machine first controller controlling the washing machine driving unit; a drying standby mode step of supplying the power to a dryer second controller controlling the dryer interface without supplying the power to a dryer driving unit controlling rotation of a drying drum and a heat exchanger, the dryer interface and a dryer first controller controlling the dryer driving unit; a washing machine power supply step of supplying the power to the washing machine first controller, the washing machine driving unit and the washing machine interface; a course setup step of inputting a washing course through the washing machine interface; a first communication step of transmitting the washing course to the dryer second controller by the washing machine second controller if a control command requesting recommendation of a drying course is input through the washing machine interface; and an interface power supply step of supplying the power to the dryer interface if the dryer second controller receives information on the washing course.

[0021] The control method may further comprise a course selection step of selecting one of a plurality of drying courses, which can be executed by the dryer driving unit, by the dryer second controller if the dryer second controller receives the information on the washing course; and a course display step of displaying the recommended course on the dryer interface.

[0022] The control method may further comprise a laundry amount measuring step of measuring the amount of laundry stored in the washing drum by being initiated after the course setup step is completed; a second communication step of transmitting the amount of laundry measured at the laundry amount measuring step to the dryer second controller by the washing machine second controller; and a time display step of displaying a predicted time required to complete the recommended course on the dryer interface.

[0023] The predicted time may be set to be increased in proportion to the amount of laundry.

[0024] The control method may be provided to resume the drying standby mode step if a preset reference time passes after the time display step is completed.

[0025] The course selection step may be provided to select a default course set to the dryer as the recom-

mended course.

[0026] The course selection step may be provided to select a drying course for setting the same kind of laundry as washing target laundry set to the washing course as a drying target, as the recommended course.

[0027] In other aspect of the present disclosure, a control method for a laundry treating apparatus comprises a standby mode step of supplying a power to a second controller controlling a dryer interface and a washing machine interface without supplying the power to a washing machine driving unit, the washing machine interface, the dryer driving unit, the dryer interface and a first controller controlling the washing machine driving unit and the dryer driving unit; a washing machine power supply step of supplying the power to the first controller, the washing machine driving unit and the washing machine interface; a course setup step of inputting a washing course through the washing machine interface; and an interface power supply step of supplying the power to the dryer interface if a control command requesting recommendation of a drying course is input through the washing machine interface.

[0028] The control method may further comprise a course selection step of selecting one of a plurality of drying courses, which can be executed by the dryer driving unit, by the second controller; and a course display step of displaying the recommended course on the dryer interface.

[0029] The control method may further comprise a laundry amount measuring step of measuring the amount of laundry stored in the washing drum; and a time display step of displaying a predicted time required to complete the recommended course on the dryer interface, and the predicted time may be set to be increased in proportion to the amount of laundry.

[0030] According to the present disclosure, a laundry treating apparatus and a control method for the same may be provided, in which one of two treating apparatuses capable of washing and drying laundry may control the other one.

[0031] Also, according to the present disclosure, a laundry treating apparatus and a control method for the same may be provided, in which a predicted time required for drying of laundry may be notified to a user.

[0032] Also, according to the present disclosure, a laundry treating apparatus and a control method for the same may be provided, in which consumption of a standby power may be minimized.

[0033] It is to be understood that both the foregoing general description and the following detailed description of the present disclosure are exemplary and explanatory and are intended to provide further explanation of the disclosure as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

[0034] The accompanying drawings, which are included to provide a further understanding of the disclosure

and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the disclosure and together with the description serve to explain the principle of the disclosure. In the drawings:

FIG. 1 illustrate an example of a laundry treating apparatus;

FIGS. 2 and 3 illustrates another embodiment of a laundry treating apparatus;

FIG. 4 illustrates an example of a control panel, a washing machine driving unit, a dryer driving unit, a washing machine interface and a dryer interface, which are provided in a laundry treating apparatus; FIG. 5 illustrates an example of a control method for a laundry treating apparatus; and

FIG. 6 illustrates another embodiment of a control method for a laundry treating apparatus.

DETAILED DESCRIPTION OF THE INVENTION

[0035] Reference will now be made in detail to the preferred embodiments of the present disclosure, examples of which are illustrated in the accompanying drawings. Meanwhile, elements or control method of apparatuses which will be described below are only intended to describe the embodiments of the present disclosure and are not intended to restrict the scope of the present disclosure. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0036] As shown in FIG. 1, a laundry treating apparatus 100 may be provided to include a dryer (first treating apparatus T) for drying laundry, and a washing machine (second treating apparatus L) provided to support a bottom surface of the dryer and therefore wash or dry laundry. Unlike the case shown in FIG. 1, the laundry treating apparatus 100 may be provided such that the dryer T may support a bottom surface of the washing machine L.

[0037] The dryer T includes a first cabinet 1, a drying drum 2 rotatably provided in the first cabinet 1, providing a space in which laundry is stored, and a supply unit 4 supplying the heated air into the drying drum 2.

[0038] The first cabinet 1 may be provided to include a front panel 11 (first front panel) forming a front surface of the dryer, a rear panel 12 (first rear panel) forming a rear surface of the dryer, an upper panel forming an upper surface of the dryer, and a base panel mounted on an upper surface of the washing machine L.

[0039] The first front panel 11 is provided with a first inlet 111 provided to be communicated with the drying drum 2, and the first inlet 111 may be provided to be opened or closed by a door 15 (first door) rotatably coupled to the first cabinet.

[0040] The drying drum 2 may be provided as a drum body 21 of a cylindrical shape of which front surface and rear surface are respectively opened. In this case, a front support 22 rotatably supporting the front surface of the drum body 211 and a rear support 24 rotatably supporting

the rear surface of the drum body 211 may be provided inside the first cabinet 1.

[0041] The front support 22 may be provided to include a first fixed body fixed into the first cabinet 1, a drying drum inlet 225 provided to pass through the first fixed body, communicating the first inlet 111 with the inside of the drum body 21, and a first support body 221 provided in the first fixed body and inserted into the front surface of the drum body 21.

[0042] The first fixed body may be provided even in any shape if it may be provided with the drying drum inlet 225 and the first support body 221. The first support body 221 may be provided in a pipe shape protruded from the first fixed body toward the drum body 21.

[0043] The front support 22 may be provided to be connected to the first inlet 111 through a connecting body 223. The connecting body 223 may be provided in a cylindrical shape to surround the first inlet 111. In this case, the drying drum inlet 225 may be provided as a through hole connected to the first inlet 111 by passing through the connecting body 223.

[0044] A discharge outlet communicated with the supply unit 4 may be provided in the connecting body 223. The discharge outlet may be provided as a hole provided to pass through the connecting body 223, and a filter 227 may detachably be inserted into the discharge outlet. The air inside the drum body 21 may move to the supply unit 4 through the discharge outlet and the filter 227, and particles contained in the air in this process may be filtered by the filter 227.

[0045] The rear support 24 may be provided to include a second fixed body fixed into the first cabinet 1, and a second support body 241 provided in the second fixed body and inserted into the rear surface of the drum body 21. The rear support 24 is provided with a supply hole 243 provided to pass through the second fixed body, guiding the air supplied from the supply unit 4 to the drum body 21.

[0046] A lifter 213 for stirring of laundry may be provided on a circumferential surface of the drum body 21. The lifter 213 may be provided as a board protruded from the circumferential surface of the drum body 211 toward a rotation center of the drum body.

[0047] The drum body 21 is rotated by a drying drum driving unit 3, and the drying drum driving unit 3 may be provided to include a drying drum motor 31 fixed into the first cabinet 1, a pulley rotated by the drying drum motor, and a belt 33 connecting a circumferential surface of the pulley with the circumferential surface of the drum body 21.

[0048] The supply unit 4 may be provided to include ducts 41 and 46 and a heat exchanger 47 provided in the ducts to exchange heat with the air. The ducts may be provided to include a discharge duct 41 guiding the air discharged from the drying drum 2 to the outside of the first cabinet 1 through the discharge outlet, and a supply duct 46 supplying the air to the inside of the drying drum 2 through the supply hole 243.

[0049] The discharge duct 41 may be provided with fans 43 and 45, and the supply duct 46 may be provided with the heat exchanger 47. The heat exchanger 47 may be provided as a heater for heating the air entering the supply duct 46. FIG. 1 illustrates that the heater is provided with a first heater 47a and a second heater 47b, which may be controlled independently, as an example. The fans may be provided to include an impeller 43 rotatably provided inside the discharge duct 41, and a fan motor 45 rotating the impeller if a power is supplied thereto. The discharge duct 41 may be provided with a temperature sensor 411 for measuring a temperature of the air discharged from the drying drum 2.

[0050] The supply duct 46 may be provided as a path of which one end is connected to the supply hole 243 and free end is arranged inside or outside the first cabinet 1. If the free end of the supply duct 46 is arranged inside the first cabinet 1, a through hole 121 may be provided in the first rear panel 12.

[0051] The washing machine L may be provided to include a second cabinet 5 provided to support a bottom surface of the first cabinet 1, and a second accommodating unit 6 provided inside the second cabinet, providing a space in which laundry is stored.

[0052] The second cabinet 5 may be provided to include a front panel 51 (second front panel) forming a front surface of the washing machine L, a rear panel 52 (second rear panel) forming a rear surface of the washing machine, and an upper panel 54 (second upper panel) forming an upper surface of the washing machine, providing a space on which the bottom surface of the first cabinet 1 is supported.

[0053] The second front panel 51 is provided with an inlet 511 (second inlet), and the second inlet 511 may be provided to be opened or closed by a door 55 (second door). The second accommodating unit 6 may be provided to include a tub 61 provided inside the second cabinet 5, providing a space in which water is stored, and a washing drum 64 rotatably provided inside the tub, storing laundry therein.

[0054] The tub 61 may be fixed to the second cabinet 5 through a tub support 612. A tub inlet 611 communicated to the second inlet 511 is provided on a front surface of the tub 61, and may be connected to the second inlet 511 through a gasket 613.

[0055] The tub 61 is supplied with water through a water supply unit, and water stored in the tub 61 is discharged to the outside of the second cabinet 5 through a drainage unit.

[0056] The water supply unit may be provided to include a water supply pipe 614 connecting a water supply source with the tub 61, and a water supply valve 616 controlling switching of the water supply pipe. The drainage unit may be provided to include a first drainage pipe 617 guiding water inside the tub 61 to the drainage pump 618, and a second drainage pipe 619 guiding water discharged from the drainage pump 618 to the outside of the second cabinet 5. The tub 61 may be provided with

a heating unit 63 for heating the water supplied through the water supply source.

[0057] The washing drum 64 may be provided in a hollow cylindrical shape. A washing drum inlet 641 communicated with the second inlet 511 through the tub inlet 611 may be provided on the front surface of the washing drum, and a drum through hole 642 communicating the inside of the washing drum with the inside of the tub may be provided on the circumferential surface and the rear surface of the washing drum.

[0058] The washing drum 64 may be rotated by a washing drum driving unit 7 (washing drum motor). The washing drum driving unit 7 may be provided to include a stator 71 fixed to the rear surface of the tub 61, forming a rotating magnetic field, a rotor 72 rotated by the rotating magnetic field, and a rotary shaft 74 connecting the rotor 72 with the rear surface of the washing drum 64 by passing through the rear surface of the tub.

[0059] FIG. 2 illustrates another embodiment of the laundry treating apparatus 100, and the laundry treating apparatus according to this embodiment is also provided to include a dryer T and a washing machine L. The laundry treating apparatus provided in this embodiment may be provided in the same structure as that of the laundry treating apparatus shown in FIG. 1 except the structure of the supply unit 4 provided in the dryer.

[0060] The supply unit 4 according to this embodiment may be provided to include ducts 41, 46 and 48 forming a path for re-supplying the air discharged from the drum body 21 to the drum body 21, and a heat exchanger 47 dehumidifying and heating the air entering the ducts.

[0061] The ducts may be provided to include a discharge duct 41 connected to the discharge outlet, a supply duct 46 connected to the supply hole 243, and a connection duct 48 connecting the discharge duct with the supply duct. In this case, the impeller 43 of the fan may be provided inside the connection duct 48.

[0062] As shown in FIG. 3, the heat exchanger 47 includes a first heat exchanger 471 (heat absorption unit) removing water from the air entering the connection duct 48, and a second heat exchanger 472 (heat emission unit) provided inside the connection duct 48, heating the air passing through the first heat exchanger 471. The heat absorption unit 471 and the heat emission unit 472 are sequentially disposed along a moving direction of the air and connected with each other through a refrigerant pipe 475 that forms a circulating path of a refrigerant.

[0063] The refrigerant moves along the refrigerant pipe 475 by means of a compressor 473 arranged outside the ducts 41, 46 and 48, and the refrigerant pipe 475 is provided with a pressure controller 474 for controlling a pressure of the refrigerant that has passed through the heat emission unit 472.

[0064] The heat absorption unit 471 is a means for cooling the air and evaporating the refrigerant by delivering heat of the air entering the discharge duct 41 to the refrigerant. The heat emission unit 472 is a means for heating the air and condensing the refrigerant by deliv-

ering heat owned by the refrigerant that has passed through the compressor 473 to the air. In this case, water contained in the air will be collected in the bottom surface of the connection duct 48 along the surface of the heat absorption unit 471 when passing through the heat absorption unit 471.

[0065] In order to collect water removed from the air passing through the heat absorption unit 471, the dryer T is provided with a water collecting body 481. The water collecting body 481 may be provided anywhere in the laundry treating apparatus, which can store water discharged from the heat absorption unit, and FIG. 3 illustrates that the water collecting body 481 is provided to be communicated with the bottom surface of the connection duct 48, as an example.

[0066] A heat exchanger support 483 may further be provided in the water collecting body 481 such that the heat absorption unit 471 and the heat emission unit 472 are not in contact with the water (condensed water) stored in the water collecting body 481.

[0067] The aforementioned laundry treating apparatus 100 should be provided with an input unit and a display unit, which are required for control of each of the apparatuses T and L. That is, as shown in FIG. 4, the dryer T is provided with a dryer interface P1, and the washing machine is provided with a washing machine interface P2.

[0068] The dryer interface P1 may be provided to include a dryer display 921 and dryer input units 922 and 923, and the washing machine interface P2 may be provided to include a washing machine display 961 and washing machine input units 962 and 963.

[0069] The dryer display 921 is a means for displaying a control command capable of being input to the dryer T or a control command input to the dryer T, and the dryer input units 922 and 923 are means for inputting the control command to the dryer T. Likewise, the washing machine display 961 is a means for displaying a control command capable of being input to the washing machine L or a control command input to the washing machine L, and the washing machine input units 962 and 963 are means for inputting the control command to the washing machine L.

[0070] In order to form unity in design of the laundry treating apparatus 100 in which two treating apparatuses are arranged up and down, the dryer display 921, the dryer input units 922 and 923, the washing machine display 961 and the washing machine input units 962 and 963 may be provided in one control panel P.

[0071] The control panel P may be provided such that an upper surface is fixed to the front surface (the first front panel) of the dryer and a lower surface is fixed to the front surface (the second front panel) of the washing machine. In this case, the control panel P will serve as a fastening unit for fixing the dryer T to the washing machine L (serve to fasten the first front panel with the second front panel).

[0072] Unlike the aforementioned description, the con-

trol panel P may be provided to be fixed to any one of the first front panel 11 and the second front panel 51. FIGS. 1 and 2 show that the control panel P is fixed to a lower end of the first front panel 11, as an example. That is, a panel accommodating groove formed as the surface of the first front panel is bent to be concave is provided on the lower end of the first front panel 11, and the control panel P may be fixed to the panel accommodating groove. In this case, the control panel P will form the front surface of the dryer together with the first front panel 11.

[0073] The dryer display 921 and the dryer input units 922 and 923 are controlled by a second controller 92 provided in the dryer, and the washing machine display 961 and the washing machine input units 962 and 963 are controlled by a second display controller 96 provided in the washing machine. The case that the second controller controls the display and the input units means that the second controller and each apparatus are provided to transmit and receive a control command (or control signal) to and from each other. The second controller 92 of the dryer and the second controller 96 of the washing machine may be provided to be communicated with each other through a communication circuit 98.

[0074] The dryer input unit may be provided to include a dryer first input unit 922 and a dryer second input unit 923. The dryer first input unit 922 may be provided as a means for selecting any one of control commands (drying courses) that can be executed by the dryer, and the dryer second input unit 923 may be provided as a means for executing the selected control command or inputting a control command requesting a temporary stop of the control command which is being executed.

[0075] The washing machine input unit may be provided to include a washing machine first input unit 962 and a washing machine second input unit 963. The washing machine first input unit 962 may be provided as a means for selecting any one of control commands (washing courses) that can be executed by the washing machine, and the washing machine second input unit 963 may be provided as a means for executing the selected control command or inputting a control command requesting a temporary stop of the control command which is being executed.

[0076] Moreover, the control panel P may further be provided with a recommendation request unit 965. The recommendation request unit 965 is a means for requesting the dryer T to recommend a drying course corresponding to a washing course (or a washing course which is being executed by the washing machine) set to the washing machine L.

[0077] The recommendation request unit 965 may be provided in the dryer interface P1 or the washing machine interface P2, and FIG. 4 illustrates that the recommendation request unit 965 is provided in the washing machine interface P2, as an example.

[0078] Load of the dryer is classified into driving load and interface load, wherein the driving load (dryer driving load) is a dryer driving unit B1 comprised of the drying

drum motor 31, the fan motor 45, the heat exchanger 47, and the temperature sensor 411, and the interface load (dryer interface load) is a dryer interface P1 comprised of the dryer display 921 and the dryer input units 922 and 923.

[0079] A power of the dryer load B1 and P1 may be provided to be controlled by a dryer first controller 91. However, the operation of the dryer driving unit B1 may be controlled by the dryer first controller 91 and the operation of the dryer interface P1 may be controlled by the dryer second controller 92.

[0080] The dryer T is connected to a power source S through a first power line 931, and may be provided such that an alternating current power supplied to the first power line 931 is converted to a direct current power through a first converter 93 (dryer power converter). In this case, the dryer second controller 92 may be provided to be supplied with a power through a dryer first power circuit 932 connected to the first converter 93, the dryer first controller 91 may be provided to be supplied with a power through a dryer second power circuit 935, and the dryer driving unit B1 and the dryer interface P1 may be provided to be supplied with a power through a dryer third power circuit 937.

[0081] The dryer second power circuit 935 may be provided with a dryer first switch 936, and the dryer third power circuit 937 may be provided with a dryer second switch 938. The dryer first switch 936 may be provided to open or close the dryer second power circuit 935 in accordance with a control command of the dryer second controller 92 or a control command of the dryer power controller 924. The dryer power controller 924 may be provided in the control panel P and provided as a means for controlling power supply to the dryer driving unit B1 and the dryer interface P1.

[0082] If the dryer power controller 924 transmits a control command requesting power supply to the dryer second controller 92 (if a user inputs a power supply request signal through the dryer power controller), the dryer second controller 92 controls the dryer first switch 936 to close the dryer second power circuit 935 through the dryer first switch control circuit 92a. If the dryer first switch 936 closes the dryer second power circuit 935, the dryer first controller 936 may be supplied with a power.

[0083] Meanwhile, the dryer second switch 938 may be provided to open or close the dryer third power circuit 937 in accordance with the control command transmitted from the dryer first controller 91 through the second switch control circuit 91a, or may be provided to open or close the dryer third power circuit 937 in accordance with the control command transmitted from the dryer second controller 92. The dryer driving unit B1 and the dryer interface P1 may be supplied with a power when the dryer second switch 938 closes the dryer third power circuit 937.

[0084] The dryer second controller 92 and the dryer power controller 924 are always connected with a power source through the dryer first power circuit 932. However,

the dryer driving unit B1 and the dryer interface P1 will be supplied with a power when a user inputs a control command to the dryer power controller 924 or when the dryer second controller 92 receives a control command from the washing machine second controller 96.

[0085] Since the dryer T of the aforementioned structure supplies a power to only the dryer second controller 92 and the dryer power controller 924 when the dryer driving unit and the interfaces B1 and P1 are not operated, consumption of a standby power may be minimized.

[0086] Load of the washing machine L is classified into driving load and interface load, wherein the driving load of the washing machine is a washing machine driving unit B2 comprised of the washing drum driving unit 7, a water supply valve 616, a drainage pump 618, and a heating unit 63, and the interface load of the washing machine is a washing machine interface P2 comprised of the washing machine display 961, the washing machine input units 962 and 963 and the preheating request unit 965.

[0087] A power of the washing machine load B2 and P2 may be provided to be controlled by a washing machine first controller 94. The operation of the washing machine driving unit B2 may be controlled by the washing machine first controller 94 and the operation of the washing machine interface P2 may be controlled by the washing machine second controller 96.

[0088] The washing machine L is connected to the power source S through a second power line 971, and may be provided such that an alternating current power supplied to the second power line 971 is converted to a direct current power through a second converter 97 (washing machine converter). The power line 931 of the dryer T and the power line 971 of the washing machine L are provided separately (independently) from each other, whereby even though any one of the two power lines is damaged or any one of the two apparatuses is out of order, the other one may be operated.

[0089] The washing machine second controller 96 may be provided to be supplied with a power through a washing machine first power circuit 972 connected to the second converter 97, the washing machine first controller 94 may be provided to be supplied with a power through a washing machine second power circuit 975, and the loads B2 and P2 of the washing machine may be provided to be supplied with a power through a washing machine third power circuit 977.

[0090] The washing machine second power circuit 975 may be provided with a washing machine first switch 976, and the washing machine first switch 976 may be provided to open or close the washing machine second power circuit 975 in accordance with the control command of the washing machine second controller 96 or the control command of the washing machine power controller 964. The washing machine power controller 964 may be provided in the control panel P1 and thus may be provided as a means for controlling power supply to the washing machine driving unit B2 and the washing machine inter-

face P2.

[0091] If the washing machine power controller 964 transmits a control command requesting power supply to the washing machine second controller 96 (if a user inputs a power supply request signal through the washing machine power controller), the washing machine second controller 96 controls the washing machine first switch 976 to close the washing machine second power circuit 975 through the washing machine first switch control circuit 96a. If the washing machine first switch 976 closes the washing machine second power circuit 975, the washing machine first controller 94 will be supplied with a power.

[0092] Meanwhile, the washing machine second switch 978 may be provided to open or close the washing machine third power circuit 977 in accordance with the control signal transmitted from the washing machine first controller 94 through the washing machine second switch control circuit 94a, or may be provided to open or close the washing machine third power circuit 977 in accordance with the control command transmitted from the washing machine second controller 96. The washing machine driving unit B2 and the washing machine interface P2 will be supplied with a power when the washing machine second switch 978 closes the washing machine third power circuit 977.

[0093] The washing machine second controller 96 and the washing machine power controller 964 are always connected with a power source through the washing machine first power circuit 972. However, the washing machine driving unit B2 and the washing machine interface P2 will be supplied with a power when a user inputs a control command to the washing machine power controller 964 or when the washing machine second controller 96 receives a control command from the dryer first controller 92.

[0094] FIG. 5 illustrates an example of a control method for the aforementioned laundry treating apparatus 100.

[0095] As shown, if the first power line 931 and the second power line 971 are respectively connected to the power source S, the laundry treating apparatus 100 proceeds to a washing standby mode step S110 and a drying standby mode step S210.

[0096] The washing standby mode step S110 is the step of supplying a power to the washing machine second controller 96 and the washing machine power controller 964 without supplying the power to the washing machine driving unit B2, the washing machine interface P2 and the washing machine first controller 94. That is, at the washing standby mode step S110, the washing machine first switch 976 maintains the state that the washing machine second power circuit 975 is opened, and the washing machine second switch 978 maintains the state that the washing machine third power circuit 977 is opened.

[0097] The washing machine power controller 964 may be provided as a switch that may operate the washing machine first switch 976 even though a power is not sup-

plied thereto. In this case, the washing standby mode step S110 will be the step of supplying a power to the washing machine second controller without supplying the power to the washing machine driving unit, the washing machine interface and the washing machine first controller.

[0098] The drying standby mode step S210 is the step of supplying a power to the dryer second controller 92 and the dryer power controller 924 without supplying the power to the dryer driving unit B1, the dryer interface P1 and the dryer first controller 91. That is, at the drying standby mode step S210, the dryer first switch 936 maintains the state that the dryer second power circuit 935 is opened, and the dryer second switch 938 maintains the state that the dryer third power circuit 937 is opened.

[0099] The dryer power controller 924 may be provided as a switch that may operate the dryer first switch 936 even though a power is not supplied thereto. In this case, the drying standby mode step S210 will be the step of supplying a power to the dryer second controller without supplying the power to the dryer driving unit, the dryer interface and the dryer first controller.

[0100] If a control signal requesting power supply is input to the washing machine load through the washing machine power controller 964 in the middle of the washing machine standby mode step S110, a washing machine power supply step S120 is executed. The washing machine power supply step S120 is the step of supplying a power to the washing machine first controller 94, the washing machine driving unit B2 and the washing machine interface P2.

[0101] If the washing machine power supply step S120 is completed, the control method proceeds to a course setup step S130 of inputting a washing course to the washing machine interface P2. If a selection command of the washing course is input through the washing machine first input unit 962 (S130) and a start command of the selected washing course is input through the washing machine second input unit 963, the control method proceeds to a course execution step S140 by controlling the washing machine driving unit B2.

[0102] The course execution step S140 may be provided to perform a laundry amount measuring step S141, a water supply step S143, a particle removal step S145, a drainage step S147 and a dehydrating step S149 in due order.

[0103] The laundry amount measuring step S141 is a process of determining the amount of laundry (washing target) inserted into the washing drum 64 by the washing machine first controller 94. The laundry amount measuring step S141 may be provided with a process of determining the amount of laundry through the amount of a current supplied to the stator 71 while the washing drum 64 is being accelerated for the number of preset revolutions or is being rotated to reach a preset angle. In this case, the washing machine L may be provided with a current amount sensor (not shown) for measuring the amount of a current supplied to the stator 71.

[0104] The water supply step S143 may be provided as a process of supplying water to the tub 61 by controlling the water supply valve 616 by the washing machine first controller 94, and the particle removal step S145 may be provided as a process of rotating the washing drum 64 by controlling the washing drum driving unit 7 by the washing machine first controller 94. The particle removal step S145 is the step of separating particles from laundry, and may be an example of a washing stroke or a rinsing stroke.

[0105] The drainage step S147 may be provided as a process of discharging water stored in the tub 61 to the outside of the second cabinet 5 by controlling the drainage pump 618 by washing machine first controller 94, and the dehydrating step S149 may be provided as a process of removing water from laundry by controlling the washing drum driving unit 7 by the washing machine first controller 94. If the dehydrating step ends (S150) (the course execution step ends), the control method resumes the washing standby mode step S110 and switches the washing machine L to a standby mode state.

[0106] If the time (predicted time) predicted when laundry which is being washed is dried by the dryer T may be notified to a user, the user may arrange a schedule in consideration of the time when drying is completed or determine whether to operate the dryer in consideration of the schedule.

[0107] In order to implement the aforementioned effect, the control method includes a first communication step S132 for notifying the dryer second controller 92 of a washing course set at the course setup step S130 by the washing machine second controller 96. At the first communication step S132, the washing machine second controller 96 and the dryer second controller 92 perform communication with each other through the communication circuit 98. The first communication step S132 may be provided to be executed only if a user requests a recommendation of a drying course through the recommendation request unit 965 (S131).

[0108] If the dryer second controller 92 receives information on the washing course through the first communication step S132, the control method executes an interface power supply step S230 of supplying a power the dryer interface P1 and a course selection step S250 of allowing the dryer second controller 92 to select one of a plurality of drying courses that can be executed by the dryer driving unit B1.

[0109] The interface power supply step S230 and the course selection step S250 may be set to be executed at the same time, or any one of the interface power supply step S230 and the course selection step S250 may be set to be earlier executed than the other one.

[0110] The interface power supply step S230 may be provided to supply a power to the entire dryer interface P1, or may be provided to supply a power to only the dryer display 921 of the dryer interface P1.

[0111] The recommended course selected at the course selection step S250 may be set to a drying course

set to dry laundry that is the same kind of laundry as that washed through the washing course. That is, if the washing course is a wool washing course, the recommended course may be set to a wool drying course, if the washing course is a cotton washing course, the recommended course may be set to a cotton drying course, and if the washing course is a functional laundry washing course, the recommended course may be set to a functional laundry drying course. Unlike the aforementioned case, the recommended course may be set to a course having the lowest power consumption among the drying courses (a plurality of courses executed by the dryer driving unit) set to the dryer T.

[0112] Unlike the aforementioned description, the recommended course may be set to a default course. The default course means a drying course to the dryer T when a power is supplied to the dryer interface P1, and may include a standard course as an example.

[0113] If a power is supplied to the dryer display 921 through the interface power supply step S230 and the recommended course is selected through the course selection step S250, the control method executes a course display step S260 of displaying the recommended course on the dryer display 921.

[0114] If the course display step S260 is completed, the control method executes a second communication step S142 of notifying the dryer T of the amount of laundry measured at the laundry amount measuring step S141 by the washing machine L. The second communication step S142 may be executed by transmitting the amount of laundry to the dryer second controller 92 by the washing machine second controller 96.

[0115] If the amount of laundry is received through the second communication step S142, the dryer second controller 92 executes a time display step S290 of displaying a predicted time required to complete the recommended course on the dryer display 921. The predicted time is preferably set to be increased in proportion to the amount of laundry.

[0116] The time display step S290 may be provided to be executed for a preset reference time. That is, if the execution time of the time display step S290 reaches the reference time (S291), the control method may be provided to resume the drying standby mode step S210.

[0117] The aforementioned control method may be applied to the laundry treating apparatus in which the controllers 91 and 92 for controlling the dryer and the controllers 94 and 96 for controlling the washing machine are integrated. That is, as shown in FIG. 6, the aforementioned control method may be applied to a laundry treating apparatus provided with a first controller for controlling the dryer driving unit B1 and the washing machine driving unit B2 and a second controller for controlling the dryer interface P1 and the washing machine interface P2.

[0118] The control method of FIG. 6 includes a standby mode step S10, a washing machine power supply step S120, a course selection step S130, and a course execution step S140.

[0119] The standby mode step S10 may be provided as a step of supplying a power to the second controller 96 without supplying the power to the washing machine driving unit B2, the washing machine interface P2, the dryer driving unit B1, the dryer interface P1 and the first controller.

[0120] The washing machine power supply step S120 may be set to a step of supplying a power to the first controller, the washing machine driving unit B2 and the washing machine interface P2, and the course setup step S130 may be set to a step of inputting a washing course through the washing machine interface P2.

[0121] The course execution step S140 may be provided to include a laundry amount measuring step S141, a water supply step S143, a particle removal step S145, a drainage step S147 and a dehydrating step S149.

[0122] After the course setup step S130 is completed, if a control command is input through the washing machine interface, the control method of FIG. 6 executes the interface power supply step S230 of supplying a power to the dryer interface P1. The control command for initiating the interface power supply step S230 may be set to a control command requesting recommendation of a drying course input through the recommendation request unit 965.

[0123] If the power is supplied to the dryer interface P1, the control method of FIG. 6 executes the course selection step S250 and the course display step S260.

[0124] The course selection step S250 may be provided as a step of selecting one of a plurality of drying courses, which can be executed by the dryer driving unit B1, as a recommended course by the second controller, and the course display step S260 may be provided as a step of displaying the recommended course on the dryer display 921.

[0125] If the amount of laundry stored in the washing drum is determined through the laundry amount measuring step S141 in the middle of the course display step S260, the control method of FIG. 6 executes the time display step S290 of displaying a predicted time required to execute the recommended course on the dryer display 921.

[0126] The aforementioned laundry treating apparatus and the aforementioned control method for the laundry treating apparatus may be carried out by various modifications. That is, the aforementioned control method of the laundry treating apparatus may be applied to a laundry treating apparatus comprising a control system different from the control system shown in FIG. 4.

[0127] Referring to FIG. 5, in the laundry treating apparatus comprising the washing machine provided with the tub and the washing drum and the dryer provided with the drying drum and the supply unit, the control method for the laundry treating apparatus may be provided to include a course setup step S130 of inputting a washing course through the washing machine interface provided to receive a control command, a first communication step S132 of transmitting the washing course to the dryer by

the washing machine if a control command requesting recommendation of the drying course is input through the washing machine interface (S131), and an interface power supply step S230 of supplying a power to the dryer interface provided to receive a control command if the dryer receives information on the washing course.

[0128] If the information on the washing course is received, the dryer T may execute the course selection step S250 of selecting one of a plurality of drying courses, which can be executed, as a recommended course, and a course display step S260 of displaying the recommended course on the dryer interface P1.

[0129] After the course setup step S130 is completed, the washing machine L may execute the laundry amount measuring step S141 of measuring the amount of laundry stored in the washing drum 64 and a second communication step S142 of transmitting the amount of laundry measured at the laundry amount measuring step to the dryer T by the washing machine L. If data on the amount of laundry is transmitted through the second communication step S142, the dryer T may execute the time display step S290 of displaying a predicted time required to complete the recommended course on the dryer interface P1. The predicted time may be set to be increased in proportion to the amount of laundry.

[0130] If a preset reference time passes (S291) after the time display step S290 is completed, the dryer T may execute the drying standby mode step S210. The drying standby mode step S210 may be provided as a step of blocking the power supplied to the dryer interface and the dryer driving unit controlling rotation of the drying drum. If the dryer T executes the recommended course, the drying standby mode step S210 may be initiated even when execution of the recommended course is completed.

[0131] The course selection step S130 may be provided to select a default course (drying course set to be executed when a user does not input a separate drying course selection command) set to the dryer T or a drying course for setting the same kind of laundry as washing target laundry set to the washing course as a drying target, as a recommended course.

[0132] If the course execution step S140 is completed, the washing machine L may execute the washing standby mode step S110. The washing standby mode may be provided as a step of blocking the power supplied to the washing machine interface P2 and the washing machine driving unit B2 controlling rotation of the washing drum 64.

[0133] It will be apparent to those skilled in the art that the present disclosure may be embodied in other specific forms without departing from the spirit and essential characteristics of the disclosure. Thus, the above embodiments are to be considered in all respects as illustrative and not restrictive. The scope of the disclosure should be determined by reasonable interpretation of the appended claims and all change which comes within the equivalent scope of the disclosure are included in the

scope of the disclosure.

Claims

1. A control method for a laundry treating apparatus (100) comprising a washing machine (L) provided with a tub (61) in which water is stored and a washing drum (64) provided inside the tub (61), storing laundry therein, and a dryer (T) provided with a drying drum (2) in which laundry is stored and a supply unit (4) for removing water from laundry by supplying the air to the drying drum (2), the control method comprising:

a course setup step (S130) of inputting a washing course through a washing machine interface (P2) provided to receive a control command; a first communication step (S132) of transmitting the washing course to the dryer (T) by the washing machine (L) if a preset control command is input through the washing machine interface (P2); and an interface power supply step (S230) of supplying a power to a dryer interface provided to receive a control command if the dryer (T) receives information on the washing course.

2. The control method of claim 1, further comprising:

a course selection step (S250) of selecting one of a plurality of drying courses, which can be executed by the dryer (T), if the dryer (T) receives the information on the washing course; and a course display step (S260) of displaying the recommended course on the dryer interface.

3. The control method of claim 1 or 2, further comprising:

a laundry amount measuring step (S141) of measuring the amount of laundry stored in the washing drum (64) by being initiated after the course setup step is completed; a second communication step (S142) of transmitting the amount of laundry measured at the laundry amount measuring step (S141) to the dryer (T) by the washing machine (L); and a time display step (S290) of displaying a predicted time required to complete the recommended course on the dryer interface (P1).

4. The control method of claim 3, further comprising a drying standby mode step (S210) of blocking a power supplied to the dryer interface (P1) and a dryer driving unit (B1) controlling rotation of the drying drum (2), wherein the drying standby mode step (S210) is

initiated when a preset reference time (S291) passes after the time display step (S290) is completed.

5. The control method of claim 3 or 4, further comprising a washing standby mode step (S110) of blocking a power supplied to the washing machine interface (P2) and a washing machine driving unit (B2) controlling rotation of the washing drum (64), wherein the washing standby mode step (S110) is initiated when execution of the washing course ends.

6. The control method of any one of claims 2 to 5, wherein the course selection step (S250) selects a default course set to the dryer (T) as the recommended course.

7. The control method of any one of claims 2 to 5, wherein the course selection step (S250) selects a drying course for setting the same kind of laundry as washing target laundry set to the washing course as a drying target, as the recommended course.

8. A control method for a laundry treating apparatus (100), the control method comprising:

a washing standby mode step (S10) of supplying a power to a washing machine second controller (96) controlling a washing machine interface (P2) without supplying the power to a washing machine driving unit (B2) controlling rotation of a washing drum (64), the washing machine interface (P2), and a washing machine first controller controlling the washing machine driving unit (B2);

a drying standby mode step (S210) of supplying the power to a dryer second controller (92) controlling the dryer interface (P1) without supplying the power to a dryer driving unit (B1) controlling rotation of a drying drum (2) and a heat exchanger, the dryer interface (P1) and a dryer first controller controlling the dryer driving unit (B1);

a washing machine power supply step (S120) of supplying the power to the washing machine first controller, the washing machine driving unit (B2) and the washing machine interface (P2); a course setup step (S130) of inputting a washing course through the washing machine interface (P2);

a first communication step (S132) of transmitting the washing course to the dryer second controller (92) by the washing machine second controller (96) if a control command requesting recommendation of a drying course is input through the washing machine interface (P2); and

an interface power supply step (S230) of supplying the power to the dryer interface (P1) if the dryer second controller (92) receives information on the washing course.

9. The control method of claim 8, further comprising:

a course selection step (S250) of selecting one of a plurality of drying courses, which can be executed by the dryer driving unit (B1), by the dryer second controller (92) if the dryer second controller (92) receives the information on the washing course; and
a course display step (S260) of displaying the recommended course on the dryer interface (P1).

10. The control method of claim 8 or 9, further comprising:

a laundry amount measuring step (S141) of measuring the amount of laundry stored in the washing drum (64) by being initiated after the course setup step (S130) is completed;
a second communication step (S142) of transmitting the amount of laundry measured at the laundry amount measuring step (S141) to the dryer second controller (92) by the washing machine second controller (96); and
a time display step (S290) of displaying a predicted time required to complete the recommended course on the dryer interface (P1).

11. The control method of claim 10, wherein the drying standby mode step (S210) is resumed if a preset reference time (S291) passes after the time display step (S290) is completed.

12. The control method of any one of claims 9 to 11, wherein the course selection step (S250) selects a default course set to the dryer (T) as the recommended course.


13. The control method of any one of claims 9 to 11, wherein the course selection step (S250) selects a drying course for setting the same kind of laundry as washing target laundry set to the washing course as a drying target, as the recommended course.

45


50

55


[Fig. 1]




[Fig. 2]




[Fig. 3]




[Fig. 4]



[Fig. 5]



[Fig. 6]





EUROPEAN SEARCH REPORT

 Application Number
 EP 21 16 6012

5

10

15

20

25

30

35

40

45

50

55

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	EP 1 433 894 A1 (LG ELECTRONICS INC [KR]) 30 June 2004 (2004-06-30) * paragraph [0021] - paragraph [0032]; figures 2-3 *	1	INV. D06F34/10
A	EP 1 548 174 A1 (LG ELECTRONICS INC [KR]) 29 June 2005 (2005-06-29) * paragraph [0067] - paragraph [0072]; figure 4 *	1-13	ADD. D06F29/00 D06F101/00 D06F101/20 D06F103/02 D06F105/56 D06F105/58
A	WO 2020/027578 A1 (LG ELECTRONICS INC [KR]) 6 February 2020 (2020-02-06) * figure 3 *	1-13	D06F34/04 D06F34/28
A	WO 2016/122275 A1 (LG ELECTRONICS INC [KR]) 4 August 2016 (2016-08-04) * figure 4 *	1-13	
			TECHNICAL FIELDS SEARCHED (IPC)
			D06F
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 19 July 2021	Examiner Diaz y Diaz-Caneja
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

 1
 EPO FORM 1503 03.02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 21 16 6012

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-07-2021

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1433894	A1	30-06-2004	AU 2003235067 A1	15-07-2004
			CN 1510206 A	07-07-2004
			EP 1433894 A1	30-06-2004
			JP 2004202214 A	22-07-2004
			KR 20040057888 A	02-07-2004
			US 2004118008 A1	24-06-2004
			US 2006265897 A1	30-11-2006

EP 1548174	A1	29-06-2005	AU 2004242547 A1	14-07-2005
			CN 1648320 A	03-08-2005
			EP 1548174 A1	29-06-2005
			US 2005138835 A1	30-06-2005
			US 2006225301 A1	12-10-2006
			US 2006225302 A1	12-10-2006

WO 2020027578	A1	06-02-2020	CN 112514330 A	16-03-2021
			EP 3831019 A1	09-06-2021
			KR 20200014029 A	10-02-2020
			WO 2020027578 A1	06-02-2020

WO 2016122275	A1	04-08-2016	AU 2016212842 A1	21-09-2017
			EP 3250746 A1	06-12-2017
			KR 20160094098 A	09-08-2016
			US 2018023243 A1	25-01-2018
			WO 2016122275 A1	04-08-2016

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- KR 1020200039326 [0001]
- KR 1020200121625 [0001]