



(11) **EP 3 991 566 A8**

(12) **CORRECTED EUROPEAN PATENT APPLICATION**

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71

(51) International Patent Classification (IPC):
A23G 9/50 ^(2006.01) **B65D 3/06** ^(2006.01)
B65D 85/78 ^(2006.01)

(48) Corrigendum issued on:
29.06.2022 Bulletin 2022/26

(52) Cooperative Patent Classification (CPC):
B65D 85/78; A23G 9/50; B65D 3/06; B65D 2203/00

(43) Date of publication:
04.05.2022 Bulletin 2022/18

(21) Application number: **21382984.9**

(22) Date of filing: **02.11.2021**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(71) Applicant: **D'Hoore, Dick Prosper**
43205 Reus (Tarragona) (ES)

(72) Inventors:
• **RIBERA RUIZ, Jordi**
43205 REUS (Tarragona) (ES)
• **SABATÉ CAMPS, Francesc**
43205 REUS (Tarragona) (ES)

(30) Priority: **03.11.2020 ES 202032365 U**

(74) Representative: **Herrero & Asociados, S.L.**
Cedaceros, 1
28014 Madrid (ES)

(54) **SHEET CONTAINER**

(57) The sheet container (1), which is conical or truncated cone-shaped, comprises an opening (2) defining an edge (4), characterised in that the sheet container (1) also comprises at least one mark (3) formed by at least two lines and/or at least one figure defining at least one line, the at least two lines being inclined with respect to

the edge (4) defined by the opening (2).

It allows to provide a sheet container, in which it is possible to detect dosing defects that may occur in the automatic process of assembling the container with the biscuit cones.

EP 3 991 566 A8