

(19)



(11)

**EP 4 043 359 A1**

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:  
**17.08.2022 Bulletin 2022/33**

(51) International Patent Classification (IPC):  
**B65D 19/34** <sup>(2006.01)</sup> **B65D 19/40** <sup>(2006.01)</sup>

(21) Application number: **22020043.0**

(52) Cooperative Patent Classification (CPC):  
**B65D 19/40; B65D 19/0075**; B65D 2519/00019;  
B65D 2519/00054; B65D 2519/00273;  
B65D 2519/00293; B65D 2519/00303;  
B65D 2519/00323; B65D 2519/00338;  
B65D 2519/00358; B65D 2519/00562

(22) Date of filing: **09.02.2022**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB  
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO  
PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**  
Designated Validation States:  
**KH MA MD TN**

(71) Applicant: **Tonelli S.p.A.**  
**47891 Falciano (SM) (SM)**


(72) Inventor: **Tonelli, Piero**  
**47891 FALCIANO (SM) (SM)**

(74) Representative: **Montebelli, Marco**  
**Brema S.r.l.**  
**Piazza E. Enriquez, 22C**  
**47891 Dogana (SM)**

(30) Priority: **12.02.2021 IT 202100000725 U**  
**29.10.2021 IT 202100005165 U**

(54) **PALLET FOOT**

(57) A foot for a pallet comprises an alveolar central body (1) made of paper and lateral walls (2), made up of at least one layer (2a) of corrugated cardboard, which are suitable for supporting the weight of the goods.



**FIG.1**

**EP 4 043 359 A1**

## Description

**[0001]** The invention relates to a foot for a pallet.

**[0002]** The enormous spread of pallets, since the 1950s to the present day, has profoundly influenced the ways in which goods are handled and stored.

**[0003]** As is known, pallets are made up of a flat surface, on which the goods are placed, below which there are feet which are appropriately spaced to allow the forks of operating equipment, such as fork-lift trucks or pallet trucks, to occupy the spaces between the feet and to favour pallet handling.

**[0004]** Originally, the material used to make pallets was exclusively wood: today, although wood is still the most used material, there are also pallets made of plastic, metal and even cardboard.

**[0005]** Regarding cardboard pallets, considering the loads to be supported, the feet are a critical factor: there are prior art feet obtained from panels with a "cellular" alveolar structure covered by paperboard sheets, on which paperboard the flat surface which supports the goods is placed. In this way, the weight of the goods is supported by the alveolar structure characterised by good resistance to vertical compression.

**[0006]** However, the poor resistance of the alveolar structure to lateral crushing means that repeated impacts against the forks of fork-lift trucks or pallet trucks deform the sides of the feet, compromising their effectiveness in a relatively short time.

**[0007]** Moreover, the feet made with an alveolar structure are not very good at withstanding sliding on roller conveyors and therefore they deform easily.

**[0008]** A further disadvantage arises when the pallet must be "strapped", that is to say, wrapped in a band (strap) made of appropriately tensioned plastic or metal material.

**[0009]** In this case too, the resistance of the alveolar structure is unable to withstand the tension applied to the strap without deforming, therefore the strap will have to interact with the foot at non-deformable portions of the latter.

**[0010]** The aim of this invention is therefore to eliminate the above-mentioned disadvantages.

**[0011]** The invention, characterised as set out in the claims, achieves the aim thanks to the use of corrugated cardboard.

**[0012]** The main advantage obtained by means of this invention is basically the fact that there is a considerable increase in the resistance to impacts caused by the forks of operating equipment, but without a reduction in the capacity for supporting the heavy weights of the goods to be transported.

**[0013]** Moreover, even if the pallets must be strapped, the tension of the strap does not damage the integrity of the packaging.

**[0014]** Finally, the particular shape of the foot which is the subject of the invention allows easy sliding on roller conveyors thanks to the surface formed by the corrugat-

ed cardboard

**[0015]** Further advantages and features of the invention will be more apparent in the detailed description which follows, with reference to the accompanying drawings, which show an example, non-limiting embodiment, in which:

- Figure 1 illustrates the invention according to a perspective view;
- Figure 2 illustrates the invention according a perspective view in a condition of use;
- Figure 3 illustrates the invention according to a view similar to that of Figure 2, with some parts cut away to better illustrate others.
- Figure 4 illustrates an accessory of the invention according to a perspective side view;
- Figure 5 illustrates the same accessory as Figure 4, according to a perspective top view;
- Figure 6 illustrates an alternative embodiment of the accessory of the preceding figures according to a perspective view;
- Figure 7 illustrates an alternative embodiment of the invention according to a perspective view;
- Figure 8 illustrates a further embodiment of the invention according to a perspective view;
- Figures 9 and 10 illustrate another alternative embodiment of the invention according to a perspective side view and top view;
- Figure 11 illustrates the invention according a perspective top assembly view in a condition of use.

**[0016]** As can be seen from the figures, the invention relates to a foot for a pallet, comprising an alveolar central body (1), formed by a "cellular" structure with cells having linear dimensions preferably in the range of from 8 to 30 millimetres, and lateral walls (2), made up of at least one layer (2a) of corrugated cardboard, which are suitable for supporting the weight of the goods.

**[0017]** In this way, in the condition of use shown in Figures 2 and 3, use is made of the high resistance of the corrugated cardboard in the "flute direction", certainly comparable to the resistance of the alveolar structure to compression. Based on the resistance required, with regard to the weight of the goods to be loaded on the pallet (P), the lateral walls (2) have a plurality of layers (2a) of corrugated cardboard, usually not more than three.

**[0018]** In contrast, the resistance to compression of the alveolar structure of which the central body (1) of the foot (10) is composed is exploited to withstand horizontal impacts mainly caused by the forks of fork-lift trucks and pallet trucks. Moreover, thanks to a particular gluing system, the foot (10) has gluing lines (3) which give it good resistance even in a transversal direction.

**[0019]** In a preferred embodiment, shown in Figure 4 the foot (10) comprises a protector (20) which prevents it from deforming even in the case of strapping.

**[0020]** The protector (20) comprises a block (11) composed of a plurality of sheets (11a) of paper which are

glued to each other, the block being suitable for application to at least one end face (10a) of the foot (10) which will have to make contact with a packaging strap. The sheets (11a) of which the block (11) is composed, shown in Figures 4, 5 and 6, may be glued along strips (11b), in such a way as to form a "cellular" alveolar structure, as in Figures 4 and 5, or even completely at the surfaces facing each other, as in Figure 6.

**[0021]** Figures 7 and 8 show the protector (20) applied respectively to one and two end faces of the foot (10).


**[0022]** The protector (20) may also be provided with an angular portion (12) made of pressed paperboard, to an inner face (12a) of which the block (11) described above is constrained. The angular portion (12) may adopt an "L" shape, as shown in Figure 9, or a "U" shape, as shown in Figure 10.

**[0023]** In this way, in the condition of use shown in Figure 11, in addition to the resistance of the corrugated cardboard in the "flute direction", use is made of the resistance of the protector (20) on the wall of the foot (10) where the packaging strap could be applied.

**that** it has gluing lines (3) suitable for providing resistance even in a transversal direction.

## Claims

1. A foot for a pallet, **characterised in that** it comprises an alveolar central body (1) made of paper and lateral walls (2), made up of at least one layer (2a) of corrugated cardboard, which are suitable for supporting the weight of the goods.
2. The foot according to claim 1, **characterised in that** it comprises a protector (20), suitable for being joined to at least one end face (10a) of the foot (10).
3. The foot according to claim 2, **characterised in that** the protector (20) comprises a block (11) composed of a plurality of sheets (11a) of paper which are glued to each other.
4. The foot according to claim 2, **characterised in that** the sheets (11a) are glued along strips (11b), in such a way as to form a "cellular" alveolar structure.
5. The foot according to claim 2, **characterised in that** the sheets (11a) are completely glued on the surfaces facing each other.
6. The foot according to claim 3, **characterised in that** the protector (20) comprises an angular portion (12) made of pressed paperboard, to at least one inner face (12a) of which said block (11) is constrained.
7. The foot according to claim 1 or 2, **characterised in that** the lateral walls (2) have a plurality of layers (2a) of corrugated cardboard.
8. The foot according to claim 1 or 2, **characterised in**






FIG. 2




FIG.3




FIG.4




FIG. 5




FIG. 6



FIG. 7







FIG. 8






FIG.11



## EUROPEAN SEARCH REPORT

Application Number

EP 22 02 0043

5

10

15

20

25

30

35

40

45

50

55

1

EPO FORM 1503 03.82 (P04C01)

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	JP H07 112742 A (NIPPON DIA CLEVITE CO) 2 May 1995 (1995-05-02)	1-3, 5, 7, 8	INV. B65D19/34
Y	* abstract; figures 1-16 *	1-3, 5, 7, 8	B65D19/40
A	-----	4, 6	
X	US 2013/112117 A1 (CASEY CHRISTOPHER [CA] ET AL) 9 May 2013 (2013-05-09)	1-3, 5, 7, 8	
Y	* paragraph [0022] - paragraph [0028] *	1-3, 5, 7, 8	
A	* paragraph [0040] - paragraph [0044] * * figures 8-14 *	4, 6	
X	KR 100 432 562 B1 (CHEON EUN BONG [KR]) 27 May 2004 (2004-05-27)	1-3, 5, 7, 8	
Y	* figures 1, 2 *	1-3, 5, 7, 8	
A	-----	4, 6	
Y	FR 2 795 706 A1 (BESIN BV [NL]) 5 January 2001 (2001-01-05) * page 4, line 22 - page 5, line 9 * * page 6, line 21 - page 7, line 2 * * figures 1, 4A-4D *	1-3, 5, 7, 8	TECHNICAL FIELDS SEARCHED (IPC)  B65D
Y	CN 2 409 174 Y (FU YIRONG [CN]) 6 December 2000 (2000-12-06) * figures 1, 2 *	1-3, 5, 7, 8	
The present search report has been drawn up for all claims			
Place of search <b>Munich</b>		Date of completion of the search <b>15 June 2022</b>	Examiner <b>Fitterer, Johann</b>
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 22 02 0043

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

15-06-2022

10

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
<b>JP H07112742 A</b>	<b>02-05-1995</b>	<b>NONE</b>	
<hr/>			
<b>US 2013112117 A1</b>	<b>09-05-2013</b>	<b>CA 2805211 A1</b>	<b>26-01-2012</b>
		<b>US 2013112117 A1</b>	<b>09-05-2013</b>
		<b>US 2014041557 A1</b>	<b>13-02-2014</b>
		<b>WO 2012010967 A2</b>	<b>26-01-2012</b>
<hr/>			
<b>KR 100432562 B1</b>	<b>27-05-2004</b>	<b>NONE</b>	
<hr/>			
<b>FR 2795706 A1</b>	<b>05-01-2001</b>	<b>NONE</b>	
<hr/>			
<b>CN 2409174 Y</b>	<b>06-12-2000</b>	<b>NONE</b>	
<hr/>			

15

20

25

30

35

40

45

50

55

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82