

(19)



(11)

EP 4 060 261 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention of the grant of the patent:

08.07.2026 Bulletin 2026/28

(21) Application number: **20887092.3**

(22) Date of filing: **10.11.2020**

(51) International Patent Classification (IPC):

F25D 21/08 ^(2006.01) **F25D 21/14** ^(2006.01)

(52) Cooperative Patent Classification (CPC):

F25D 21/08; F25D 21/14; H05B 3/44;

F25D 2321/144; F25D 2321/146; H05B 2203/032

(86) International application number:

PCT/CN2020/127645

(87) International publication number:

WO 2021/093713 (20.05.2021 Gazette 2021/20)

(54) **DEFROSTING DEVICE AND REFRIGERATOR COMPRISING SAME**

AUFTAUVORRICHTUNG UND DAMIT AUSGERÜSTETER KÜHLSCHRANK

DISPOSITIF DE DÉGIVRAGE ET RÉFRIGÉRATEUR COMPRENANT CELUI-CI

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **11.11.2019 JP 2019204064**

(43) Date of publication of application:

21.09.2022 Bulletin 2022/38

(73) Proprietors:

- **Qingdao Haier Refrigerator Co., Ltd.**
Qingdao, Shandong 266101 (CN)
- **Haier Smart Home Co., Ltd.**
Qingdao, Shandong 266101 (CN)
- **Aqua Co., Ltd.**
Tokyo 103-0012 (JP)

(72) Inventors:

- **KURATANI, Toshiharu**
Tokyo 103-0012 (JP)

- **OKUHARA, Naoshi**
Tokyo 103-0012 (JP)

(74) Representative: **Winter, Brandl - Partnerschaft mbB**

Alois-Steinecker-Straße 22
85354 Freising (DE)

(56) References cited:

CN-A- 1 580 676	CN-A- 103 453 718
CN-A- 108 120 211	CN-U- 203 605 587
CN-U- 204 006 894	CN-U- 204 648 801
CN-U- 207 741 416	CN-U- 210 220 362
JP-A- 2000 018 799	JP-A- 2000 314 581
JP-A- 2000 314 581	JP-A- 2004 183 998
JP-A- 2005 055 004	JP-A- 2006 010 151
JP-A- H08 313 146	JP-A- H11 132 637
KR-A- 20090 036 837	

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

TECHNICAL FIELD

[0001] The present invention relates to a defrosting device for defrosting an evaporator of a refrigerator and a refrigerator including the same.

BACKGROUND

[0002] In order to defrost an evaporator, a defrosting device is widely used, and the defrosting device includes a glass tube heater below the evaporator. In such a refrigerator, a temperature of an outer surface of the glass tube heater is required to be sufficiently lower than a flammable temperature of a solvent flowing in the evaporator. However, when input power of the glass tube heater is reduced to lower the temperature of the outer surface of the glass tube heater, an insufficient defrosting performance may be obtained. In particular, even when frost in the evaporator above the glass tube heater is melted by heat transferred by natural convection due to the glass tube heater, water falling from the evaporator after the melting process may be refrozen in a tray disposed below the glass tube heater.

[0003] In order to solve the problem, there is proposed a defrosting device with a defrosting heater in which a heating element is provided in a double-layer glass tube (for example, see patent document 1). In the defrosting device described in patent document 1, by using the double-layer glass tube, sufficient heat may be applied to melt the frost refrozen in the tray even when the outer surface of the glass tube heater has a low temperature.

[0004] Patent document 1: Publication No.JP 2004 198097.

[Problem to be solved by invention]

[0005] However, the glass tube heater including the double-layer glass tube has a high manufacturing cost, and the defrosting device including the glass tube heater or the refrigerator including the defrosting device has an increased manufacturing cost.

[0006] JP 2000 314581 A discloses a drain pan arranged at the lower part of a cooler, and a drain hole 1a. At the inside space part of the drain pan, a defrosting heater is provided. At the upper part of the heater, a protective plate for protecting the defrost heater from dew dropping from the cooler on defrost is arranged, and both ends of the protective plate are mounted to the defrost heater. A thermally good conductor is arranged at the recessed part of the protection plate for engaging, and at the same time both the ends are inserted into the drain hole, so that the heat of the defrost heater is transmitted to the drain hole 1a, thus firmly fixing the thermally good conductor by the engagement with the recessed part of the protection plate, and the elastic holding power between the end part and the drain hole, and hence achieving simple structure,

without decreasing performance in a drain device.

[0007] JP 2006 010151 A discloses a refrigeration cycle using the flammable refrigerant, and the defrosting heater mounted near a lower part of the evaporator. The defrosting heater comprises a heater wire composed of a metallic resistor, the glass tube storing the heater wire, a metallic tube covering an outer part of the glass tube and forming a double tube with a clearance there between, and an upper cover mounted just above the metallic tube for covering an upper part of the metallic tube. Further prior art is disclosed in JP 2000 018799 A.

SUMMARY

[0008] An object of the present invention is to solve the above problems and to provide a defrosting device which may be manufactured at a low cost and has a sufficient defrosting function, and a refrigerator including the same.

[Means for solving problem]

[0009] The invention is set out in the appended set of claims. A defrosting device according to the present invention is defined in claim 1.

[0010] According to the present invention, the single-layer glass tube is used to reduce the manufacturing cost of the device. Even when input power of the defrosting heater is suppressed to reduce a temperature of an outer surface of the glass tube, the radiant heat from the defrosting heater may be reflected towards the tray side by the roof portion, so as to melt frost in the tray. In particular, in the cross section perpendicular to the length direction of the glass tube, the upwards protruding shape of the roof portion is symmetrical with respect to the vertical line within at least the predetermined range on both sides of the vertical line passing through the general center of the glass tube, and further, in the cross section along the length direction of the glass tube including the above-mentioned vertical line, the upwards protruding shape of the roof portion is formed obliquely in the end regions on both sides, so as to downwards reflect the radiant heat from the lower side. That is, four corners of the roof portion are formed into a shape for improving reflection. Thus, the radiant heat with a small offset or deflection may be incident into a main part of the tray except a part directly below the glass tube.

[0011] Furthermore, the opening of the tray is located directly below the glass tube, and therefore, the radiant heat from the defrosting device is directly incident to the opening and a periphery thereof. Thus, the frost refrozen in the tray may be melted and reliably discharged through the opening and the drainage pipe.

[0012] As mentioned above, a defrosting device which is manufactured at a low cost and has a sufficient defrosting performance may be provided.

[0013] In addition, the present invention provides a defrosting device in which a lower end portion of the roof portion is disposed at a same position as or above an

upper end of the glass tube in a height direction, and in the height direction, the top of the roof portion is disposed at a position higher than a position of the upper end of the glass tube by a length which is 1.5 times an outer diameter of the glass tube.

[0014] According to the present invention, since the lower end portion of the roof portion is disposed at the same position as or above the upper end of the glass tube, frost adhering to an evaporator above the defrosting device may be reliably melted by the heat transferred by natural convection. Furthermore, since in the height direction, the top of the roof portion is disposed at the position higher than the position of the upper end of the glass tube by the length which is 1.5 times the outer diameter of the glass tube, the glass tube may be disposed near the evaporator, thus improving an effect of melting the frost adhering to the evaporator. Meanwhile, since the top of the roof portion is not too far away from the tray, the radiant heat from the defrosting heater may be strongly reflected towards the tray side by the roof portion, so as to improve the effect of melting the frost in the tray.

[0015] With the arrangement of the roof portion as mentioned above, the frost on the evaporator and the tray may be effectively melted to achieve a high defrosting performance.

[0016] In addition, the present invention provides a defrosting device in which a width at a lower end of the roof portion is 2 to 3 times the outer diameter of the glass tube in the cross section perpendicular to the length direction of the glass tube.

[0017] The width at the lower end of the roof portion is set to be 2 to 3 times the outer diameter of the glass tube, thus well balancing and effectively melting the frost of the evaporator and the tray.

[0018] Furthermore, the present invention provides a defrosting device further including a defrosting component made of a bent metal rod, the defrosting component having: a hook portion formed at one end portion of the metal rod and inserted into a hole portion provided at the roof portion in a free rotation state; a heat receiving portion connected with the hook portion and extending obliquely downwards while connected with the roof portion; a bypassing portion connected with the heat receiving portion and bent to bypass the glass tube; and a heat dissipation portion connected with the bypassing portion and extending downwards into the tray and the drainage pipe.

[0019] According to the present invention, in the defrosting component mounted to the roof portion by the hook portion in the free rotation state, the heat receiving portion comes into contact with the roof portion by gravity, and may receive the heat from the defrosting heater through a metal roof. Furthermore, the heat dissipation portion may be disposed inside the tray and the drainage pipe by gravity in a case where the bypassing portion does not interfere in the glass tube. The heat received by the roof portion is conducted through the bypassing por-

tion to the heat dissipation portion extending downwards, and the heat may be supplied from the heat dissipation portion to the frost or water in the tray or the drainage pipe.

5 **[0020]** As mentioned above, by using the defrosting component, manufacture may be realized at a low manufacturing cost, and the heat from the defrosting heater may be effectively supplied to the frost or water in the tray or the drainage pipe.

10 **[0021]** In addition, a refrigerator according to the present invention includes the above-mentioned defrosting device.

15 **[0022]** The refrigerator according to the present invention may also achieve any of the above-mentioned effects.

[Effects of invention]

20 **[0023]** As mentioned above, in the present invention, a defrosting device which may be manufactured at a low cost and has a sufficient defrosting performance and a refrigerator including the same may be provided.

BRIEF DESCRIPTION OF THE DRAWINGS

[0024]

FIG. 1 schematically shows a side sectional view of a refrigerator having a defrosting device according to an embodiment of the present invention.

FIG. 2 is a schematic perspective diagram schematically showing a defrosting device according to a first embodiment of the present invention.

35 FIG. 3 is a view showing a cross section perpendicular to a length direction of a glass tube as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing the defrosting device according to the first embodiment of the present invention.

40 FIG. 4 is a view showing a cross section along the length direction of the glass tube, the view including a vertical line passing through a general center of a circular shape of the glass tube, and is a side sectional view schematically showing the defrosting device according to the first embodiment of the present invention.

45 FIG. 5 is a view showing the cross section perpendicular to the length direction of the glass tube as viewed from the X-axis direction in FIG. 2, and is a side sectional view for illustrating an arrangement of a roof portion according to an embodiment of the present invention.

50 FIG. 6 is a view showing the cross section perpendicular to the length direction of the glass tube as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing a defrosting device according to a second embodiment of the present invention.

FIG. 7 is a view showing the cross section perpendicular to the length direction of the glass tube as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing a defrosting device according to a third embodiment of the present invention.

FIG. 8 is a view showing the cross section perpendicular to the length direction of the glass tube as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing a defrosting device according to a fourth embodiment of the present invention.

FIG. 9 is a perspective view for illustrating a defrosting component according to an embodiment of the present invention.

REFERENCE NUMERALS

[0025] 2-defrosting device, 10-defrosting heater, 12-glass tube, 14-cover, 20-heater cover, 22-roof portion, 22A-first region, 22B-second region, 22C-third region, 22D-fourth region, 24-bracket, 26-hole portion, 30-tray, 30A-bottom, 30B-side wall, 32-opening, 40-drainage pipe, 50-defrosting component, 52-hook portion, 54-heat receiving portion, 56-bypassing portion, 58-heat dissipation portion, 100-refrigerator, 102A-freezing chamber, 102B-refrigerating chamber, 104A, 104B-inflow passage, 106-partition, 106A-blow-out port, 110-evaporator, 120-compressor, 130-fan, 140-damper, 150-drainage pipe, 160-evaporating pan, G-general center, VL-vertical line, and S-specified range.

DETAILED DESCRIPTION

[0026] Embodiments for implementing the present invention will be described below with reference to accompanying drawings. A defrosting device described below is used for embodying the technical idea of the present invention, and the present invention is not limited to the following unless otherwise specified.

[0027] In the drawings, members having the same function may be denoted by the same reference numerals. For convenience of explanation or understanding of key points, there are cases where the description is divided into embodiments for convenience, but parts of structures shown in different embodiments may be replaced or combined. In the embodiment described below, descriptions about matters common to the above are omitted, and only different points will be described. In particular, the same effects caused by the same structure will not be mentioned in turn in each embodiment. In order to clarify the description, the sizes, positional relationships, or the like, of members shown in each drawing may be shown in an expanded manner. In the following description and drawings, an X-axis, a Y-axis, and a Z-axis are shown assuming that a refrigerator is disposed on a floor. The Z-axis is used to indicate a vertical direction, and the X-axis is used to indicate a length direction of a

glass tube 12 included in a defrosting heater 10 described below.

(Refrigerator including defrosting device according to present invention)

[0028] FIG. 1 is a side sectional view schematically showing an example of a refrigerator 100 including a defrosting device 2 according to an embodiment of the present invention. The refrigerator 100 shown in FIG. 1 includes a freezing chamber 102A and a refrigerating chamber 102B. Inflow passages 104A, 104B spaced apart by a partition 106 are provided on rear sides of the freezing chamber 102A and the refrigerating chamber 102B. An evaporator 110 is disposed in the inflow passage 104A on the freezing chamber 102A side, and a fan 130 is disposed above the evaporator 110. The defrosting device 2 according to each embodiment described below is disposed below the evaporator 110.

[0029] A compressor 120 in communication with the evaporator 110 is disposed in a machinery chamber outside the rear side of the freezing chamber 102A. The following cycle is repeated: a refrigerant (gas) compressed by the compressor 120 is liquefied by a condenser, the liquefied refrigerant absorbs heat of the gas in a tank in the evaporator 110 and is vaporized, and the vaporized refrigerant is compressed again by the compressor 120. A damper 140 is disposed between the inflow passage 104A on the freezing chamber 102A side and the inflow passage 104B on the refrigerating chamber 102B side. In FIG. 1, the damper 140 is shown in a closed state.

[0030] As shown by the dotted arrow in FIG. 1, when the compressor 120 and the fan 130 are actuated in the state where the damper is closed, the gas in the freezing chamber 102A flows, and the cold gas passing through the evaporator 110 flows into the freezing chamber 102A from a blow-out port 106A provided in the partition 106. The inflow gas circulates in the freezing chamber 102A and returns to a lower side of the evaporator 110 in the inflow passage 104A again. An interior of the freezing chamber 102A is cooled by the circulation of the gas cooled by the evaporator 110. In a state where the damper 140 is opened, cool air also circulates on the refrigerating chamber 102B side.

[0031] Moisture contained in the cooled air is condensed into frost and adheres to a surface of a heat exchange tube of the evaporator 110. A cooling performance is degraded when a large amount of frost adheres to the heat exchange tube, and therefore, the evaporator 110 is required to be defrosted periodically. Therefore, the defrosting device 2 is disposed below the evaporator 110. The defrosting device 2 includes a defrosting heater 10, and when the compressor 120 and the fan 130 do not work, the defrosting heater 10 is turned on, thus heating and defrosting the heat exchange tube. Water falling after the frost on the evaporator 110 is melted is discharged from a drainage pipe 40 of the defrosting device 2, flows in

a drainage pipe 150 of the refrigerator 100, and is discharged to a steam tray 160 disposed in the machinery chamber.

(Defrosting device according to first embodiment)

[0032] FIG. 2 is a schematic perspective diagram schematically showing a defrosting device 2 according to a first embodiment of the present invention. FIG. 3 is a view showing a cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing the defrosting device 2 according to the first embodiment of the present invention. FIG. 4 is a view showing a cross section along the length direction of the glass tube including a vertical line passing through a general center of a circular shape of the glass tube, and is a side sectional view schematically showing the defrosting device according to the first embodiment of the present invention. In FIG. 4, a description of a tray is omitted. Next, the defrosting device 2 according to the first embodiment of the present invention will be described with reference to FIGS. 2 to 4.

[0033] The defrosting device 2 according to the present embodiment includes a defrosting heater 10 having a heating element in a single-layer quartz glass tube 12. Furthermore, the defrosting device 2 includes a heater cover 20, and the heater cover 20 includes a roof portion 22 which is disposed above the glass tube 12, extends in the length direction of the glass tube 12, is made of a metal sheet and protrudes upwards. Furthermore, the defrosting device 2 includes a tray 30 disposed below the glass tube 12 and extending along the length direction of the glass tube 12, and a drainage pipe 40 extending downwards from an opening 32 provided in a bottom of the tray 30. FIG. 3 schematically shows the drainage pipe 40 shown in FIG. 2.

[0034] Further, the defrosting device 2 according to the present embodiment includes a defrosting component 50 formed by bending a metal rod. The defrosting component 50 includes: a hook portion 52 formed at one end portion of the metal rod and inserted into a hole portion 26 provided in the metal sheet forming the roof portion 22 in a free rotation state, a heat receiving portion 54 connected with the hook portion 52 and extending obliquely downwards while connected with the metal sheet forming the roof portion 22, a bypassing portion 56 connected with the heat receiving portion 54 and bent to bypass the glass tube 12, and a heat dissipation portion 58 connected with the bypassing portion 56 and extending downwards into the tray 30 and the drainage pipe 40.

<Defrosting heater>

[0035] The glass tube 12 included in the defrosting heater 10 in the present embodiment has an elongated cylindrical shape. The heating element made of a metal wire, such as a nichrome wire, is disposed inside the

glass tube 12. A coil-shaped heater made of a metal wire wound into a coil shape is disposed in a central heating region of the glass tube 12, and the metal wire extends outwards from both ends thereof. Both end portions of the glass tube 12 are covered with covers 14 made of a material having an excellent heat resistance and excellent electrical insulation, such as silicone rubber, or the like. Portions of the metal wire extending from both sides of the coil-shaped heater extend outside the glass tube 12 through the covers 14, and are electrically connected with external cables.

[0036] In order to comply with IEC regulations, input power is controlled, such that an outer surface of the heated glass tube 12 has a temperature of 360°C or lower. The evaporator 100 may be sufficiently defrosted practically even when such control is performed on the input power, which will be described in detail below.

<Heater cover>

[0037] The heater cover 20 includes the roof portion 22 extending in the length direction of the glass tube 12, made of the metal sheet and protruding upwards, and brackets 24 provided on both sides of the roof portion 22 in the length direction. The covers 14 at both ends of the glass tube 12 are inserted into substantially C-shaped openings provided in the brackets 24, and the heater cover 20 is connected to the defrosting heater 10.

[0038] In the present embodiment, an aluminum sheet having a high reflectance and a high thermal conductivity is used as the metal sheet forming the roof portion 22. However, the present invention is not limited thereto, and other arbitrary metal sheets, such as a copper sheet, may be used. The upwards protruding shape may also be formed by bending an aluminum sheet, or by joining 2 aluminum sheets.

[0039] In the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the metal sheet of the roof portion 22 is formed in the upwards protruding shape, and the upwards protruding shape is symmetrical with respect to the vertical line VL within at least a predetermined range S on both sides of the vertical line VL passing through the general center G of the circular shape of the glass tube 12. Here, the predetermined range S on both sides of the vertical line VL refers to a range with a left side and a right side at a distance S from the vertical line VL in the Y-axis direction perpendicular to the vertical line VL in 2 regions divided by the vertical line VL in the Z-axis direction. The upwards protruding shape of the roof portion 22 has 2 flat plates: a first region 22A and a second region 22B. As described below, planes or smoothly curved surfaces may be used as reflection surfaces of the first region 22A and the second region 22B.

[0040] Further, as shown in FIG. 4, in the cross section along the length direction of the glass tube 12, the roof portion 22 has a third region 22C and a fourth region 22D inclined downwards in end regions on both sides in the

length direction, so as to downwards reflect radiant heat from a lower side. That is, as shown in FIG. 2, the roof portion 22 has a structure like a hipped roof formed by 4 sheet-like members: the first to fourth regions 22A to 22D, and all side surfaces have shapes for improving reflection. Planes or smoothly curved surfaces may also be used as reflection surfaces of the third region 22C and the fourth region 22D.

[0041] With the above structure, the radiant heat from the defrosting heater 10 may be reflected downwards and incident on a main part of the tray 30 below the defrosting heater, thus melting frost refrozen in the tray 30.

<Tray and drainage pipe>

[0042] The tray 30 extends along the length direction of the glass tube 12, has the bottom 30A and a side wall 30B surrounding the bottom 30A, and opens upwards. The opening 32 is provided in a substantially central position in a length direction of the bottom 30A of the tray 30. The bottom 30A of the tray 30 is inclined to minimize a height of the opening 32. Thus, the water falling from the evaporator 110 above the defrosting device flows in the bottom 30A of the tray 30 into the opening 32. The drainage pipe 40 is mounted to the opening 32 provided in the bottom 30A of the tray 30, and extends downwards from the opening 32.

[0043] In the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the opening 32 of the tray 30 is located directly below the glass tube 12. With such an arrangement, the opening 32 and a region around the opening may directly receive the radiant heat from the defrosting heater 10, so as to melt the frost refrozen in the tray 30.

[0044] The tray 30 is preferably made of a metal material with a high thermal conductivity, such as aluminum. In consideration of ease of mounting the defrosting device 2 to the refrigerator 100, or the like, the drainage pipe 40 is preferably made of a resin material with an elasticity, or the like.

(Arrangement of roof portion)

[0045] FIG. 5 is a view showing the cross section perpendicular to the length direction of the glass tube as viewed from the X-axis direction in FIG. 2, and is a side sectional view for illustrating an arrangement of a roof portion 22 according to an embodiment of the present invention. In FIG. 5 and FIGS. 6 to 8 described below, the dotted arrow indicates the radiant heat emitted from the defrosting heater 10, and the dash-and-dot arrow indicates an upward flow of ambient gas heated by the defrosting heater 10 due to natural convection. Although FIG. 5 illustrates the defrosting device according to the first embodiment shown in FIG. 3, functions of the roof portion 22 are basically same in defrosting devices according to the second to fourth embodiments described

with reference to FIGS. 6 to 8.

[0046] In the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the upwards protruding shape of the roof portion 22 is symmetrical with respect to the vertical line VL within the predetermined range S on both sides of the vertical line VL passing through the general center G of the circular shape of the glass tube 12. In the first embodiment, the predetermined range S is uniform in an entire region of the roof portion 22, and the whole region is symmetrical with respect to the vertical line VL. However, the present invention is not limited thereto, and other cases will be described in detail below.

[0047] The predetermined range S is preferably determined in accordance with a width of the tray 30 perpendicular to the length direction as viewed from the X-axis direction. In a case where both end portions of the tray 30 in the width direction are located at a same distance from the vertical line VL, preferably, the upwards protruding shape of the roof portion 22 is symmetrical with respect to the vertical line VL up to a range where reflected light reaches both end portions of the tray 30. In a case where both end portions of the tray 30 in the width direction are located at different distances from the vertical line VL, preferably, the upwards protruding shape of the roof portion 22 is symmetrical with respect to the vertical line VL up to a range where the reflected light reaches at least the end portion close to the vertical line VL side. Thus, the radiant heat with a small offset or deviation may be incident into the main part of the tray 30, so as to efficiently melting the frost in the tray 30.

[0048] In the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the first region 22A and the second region 22B are shown as two side surfaces connected at a top P located on the vertical line VL. Moreover, an angle θ formed by the first region 22A and the vertical line VL substantially coincides with an angle θ formed by the second region 22B and the vertical line VL. Further, in an example shown in FIG. 5, the first region 22A and the second region 22B also have uniform lengths.

[0049] This case may also be considered as follows: in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the first region 22A and the second region 22B form 2 equal sides of an isosceles triangle with a vertex P located on the vertical line VL as a vertex.

[0050] As shown by the double-dot dash line in FIG. 5, the first region 22A and the second region 22B extend obliquely downwards to intersect with a horizontal line of a bottom surface of the tray 30, thus forming an upper half of a parallelogram. Moreover, a center of the opening 32 of the tray 30 substantially coincides with the position of the vertical line VL. That is, the opening 32 of the tray 30 is located at a center of a parallelogram having the roof portion 22 of the upwards protruding shape and extended lines thereof as two sides.

[0051] With such an arrangement, the radiant heat

emitted upwards from the defrosting heater 10 may be reflected downwards by the roof portion 22, and the radiant heat with the small offset or deflection may be incident on the main part of the tray 30 except a part directly below the glass tube 12. A region where the reflected light from the roof portion 22 does not reach exists directly below the glass tube 12, but the radiant heat emitted downwards from the defrosting heater 10 is directly incident on such a region, thus efficiently melting the frost refrozen in the main part of the tray 30. The melting water flows into the drainage pipe 40 through a switch 32, flows in the drainage pipe 150 of the refrigerator 100, and is discharged to an evaporation pan 160 disposed in the machinery chamber.

[0052] In the example shown in FIG. 5, a position H1 of a lower end portion of the roof portion 22 is disposed above a position H0 of an upper end of the glass tube 12 in a height direction (the Z-axis direction). However, the present invention is not limited thereto, and the position H1 of the lower end portion of the roof portion 22 may be same as the position H0 of the upper end of the glass tube 12. That is, the position H1 of the lower end portion of the roof portion 22 is the same as or above the position H0 of the upper end of the glass tube 12 in the height direction (the Z-axis direction).

[0053] With such a setting, the gas around the glass tube 12 heated by the defrosting heater 10 may efficiently flow upwards by natural convection. Thus, the heat may be provided for the evaporator 110 by natural convection heat transfer, thereby reliably melting the frost adhering to the evaporator 110.

[0054] Furthermore, in the height direction (the Z-axis direction), the top P of the roof portion 22 is disposed at a position H2 higher than the position H0 of the upper end of the glass tube 12 by a length which is 1.5 times an outer diameter of the glass tube 12. With such a setting, the defrosting heater 10 may be relatively close to the evaporator 110, thus improving the effect of melting the frost adhering to the evaporator 110. Meanwhile, since the top P of the roof portion 22 is not too far away from the tray 30, the radiant heat from the defrosting heater 10 may be strongly reflected towards the tray 30 by the roof portion 22, so as to improve the effect of melting the frost in the tray 30. With the arrangement of the roof portion 22 as mentioned above, the frost on the evaporator 110 and the tray 30 may be effectively melted to achieve a high defrosting performance.

[0055] Furthermore, in the present embodiment, a width W at a lower end of the roof portion 22 is 2 to 3 times the outer diameter D of the glass tube in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction. Furthermore, when an end portion of the lower end of the roof portion 22 in the width direction has a distance M from the shape of the glass tube 12, $0.5D \leq M \leq D$.

[0056] When the width W at the lower end of the roof portion 22 is not much greater than the outer diameter of the glass tube 12, the heat generated by the defrosting

heater 10 is unable to be sufficiently reflected downwards. On the other hand, when the width W at the lower end of the roof portion 22 is considerably greater than the outer diameter of the glass tube 12, the heat is difficult to be supplied to the evaporator 110 side above the defrosting device by natural convection. Therefore, the width W at the lower end of the roof portion 22 is set to be 2 to 3 times the outer diameter of the glass tube 12, thereby well balancing and effectively melting the frost of the evaporator 110 and the tray 30. A same relationship is also shown in a cross section perpendicular to the length direction of the glass tube 12 as viewed from a direction opposite to the X-axis direction.

(Defrosting device according to second embodiment)

[0057] FIG. 6 is a view showing the cross section perpendicular to the length direction of the glass tube as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing a defrosting device according to a second embodiment of the present invention. In the defrosting device 2 according to the second embodiment, the roof portion 22 also has an upwards protruding shape formed by connecting a first region 22A and a second region 22B which have flat plate shapes. However, in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the second region 22B has a same length as the second region in the first embodiment, but the first region 22A is longer than the first region in the first embodiment.

[0058] As shown in FIG. 6, in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the upwards protruding shape of the roof portion 22 is symmetrical with respect to the vertical line VL within the predetermined range S on both sides of the vertical line passing through the general center G of the circular shape of the glass tube 12, but not symmetrical with respect to the vertical line VL in the whole region. In one first region 22A of the roof portion 22, a width is extended by an amount T.

[0059] In the above-mentioned first embodiment, in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the end portions in the width direction of the tray 30 on the lower side have substantially the same distance from the vertical line VL in the Y-axis direction perpendicular to the vertical line VL, but the two end portions of the tray 30 in the width direction have different distances from the vertical line VL in the second embodiment. The upwards protruding shape of the roof portion 22 is symmetrical with respect to the vertical line VL in a range where the reflected light is incident on the end portion of the tray 30 in the width direction close to the vertical line VL side (the right end portion in the drawing). Then, by adjusting a length of the roof portion 22, the reflected light is also incident on the other end portion (the left end portion in the drawing). A same relationship with the left and right

reversed is shown in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the direction opposite to the X-axis direction.

(Defrosting device according to third embodiment)

[0060] FIG. 7 is a view showing the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing a defrosting device 2 according to a third embodiment of the present invention.

[0061] In the defrosting devices according to the first and second embodiments described above, the roof portion 22 is formed by the first region 22A and the second region 22B which have flat plate shapes, but in the third embodiment, the roof portion 22 is formed by a smooth curved surface.

[0062] In this case, by appropriately determining curvature of the curved surface of the roof portion 22, as shown in FIG. 7, the radiant heat emitted upwards from the defrosting heater 10 may be reflected downwards by the roof portion 22, so as to be incident on the main part of the tray 30 except the region shielded by the glass tube 12. In the third embodiment, similarly to the first embodiment, the whole region of the roof portion 22 is symmetrical with respect to the vertical line VL passing through the general center G of the circular shape of the glass tube 12. A same relationship is also shown in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the direction opposite to the X-axis direction.

(Defrosting device according to fourth embodiment)

[0063] FIG. 8 is a sectional view perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction in FIG. 2, and is a side sectional view schematically showing a defrosting device 2 according to a fourth embodiment of the present invention.

[0064] In the fourth embodiment, the roof portion 22 is also formed by a smooth curved surface. In the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction, the upwards protruding shape of the roof portion 22 is symmetrical with respect to the vertical line VL within the predetermined range S on both sides of the vertical line passing through the general center G of the circular shape of the glass tube 12, but the roof portion 22 is not symmetrical with respect to the vertical line VL in the whole region. In one first region 22A of the roof portion 22, the width is extended by an amount T.

[0065] In the fourth embodiment, in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the X-axis direction of FIG. 2, the two end portions of the tray 30 in the width direction have different distances from the vertical line VL. The upwards protruding shape of the roof portion 22 is symmetrical with

respect to the vertical line VL in the range where the reflected light is incident on the end portion of the tray 30 in the width direction close to the vertical line VL side (the right end portion in the drawing). Then, by adjusting the length of the roof portion 22, the reflected light is also incident on the other end portion (the left end portion in the drawing). A same relationship with the left and right reversed is shown in the cross section perpendicular to the length direction of the glass tube 12 as viewed from the direction opposite to the X-axis direction.

[0066] As mentioned above, the defrosting device 2 according to any one of the first to fourth embodiments of the present invention described above includes: the defrosting heater 10 having the heating element in the single-layer glass tube 12 with the circular cross section perpendicular to the length direction; the roof portion 22 disposed above the glass tube 12, extending in the length direction of the glass tube 12, made of the metal sheet and having the upwards protruding shape; the tray 30 disposed below the glass tube 12, extending in the length direction of the glass tube 12, and having the opening 32 formed in the bottom thereof; and the drainage pipe 40 extending downwards from the opening 32, wherein in the cross section perpendicular to the length direction of the glass tube 12, the top P of the roof portion 22 is located on the vertical line VL passing through the general center G of the glass tube 12, and the roof portion 22 is symmetrical with respect to the vertical line VL within at least the predetermined range on both sides of the vertical line VL, and in the cross section along the length direction of the glass tube 12 including the vertical line VL, the end regions on both sides of the roof portion 22 in the length direction are inclined downwards to downwards reflect the radiant heat from the lower side, and the opening 32 is located directly below the glass tube 12.

[0067] The single-layer glass tube 12 is used to reduce a manufacturing cost of the device. Even when input power of the defrosting heater 10 is suppressed to reduce a temperature of an outer surface of the glass tube 12, the radiant heat from the defrosting heater 10 may be reflected towards the tray 30 side by the roof portion 22, so as to melt the frost in the tray 30. In particular, the upwards protruding shape of the roof portion 22 is symmetrical with respect to the vertical line VL in at least the predetermined range S on both sides of the vertical line VL passing through the general center G of the glass tube 12, and in the length direction (the X-axis direction shown in FIG. 2) of the glass tube 12, the end regions (see 22C and 22D in FIG. 4) on both sides are inclined to downwards reflect the radiant heat from the lower side, and the opening 32 of the tray 30 is located directly below the glass tube 12, thus using the reflected heat from the roof portion 22 and the radiant heat directly received from the defrosting heater 10, and making the radiant heat with the small offset or deflection incident into the main part of the tray 30. Therefore, the frost adhering to the evaporator 110 may be melted and discharged through the opening 32 of the tray 30 and the drainage pipe 40. As mentioned

above, a defrosting device 2 which may be manufactured at a low cost and has a sufficient defrosting performance may be provided.

[0068] In addition, in the defrosting devices 2 according to the first to fourth embodiments, since the position H1 of the lower end portion of the roof portion 22 is the same as or above the position H0 of the upper end of the glass tube 22 in the height direction (the Z-axis direction), the frost adhering to the evaporator 110 may be effectively melted by the heat transferred by natural convection. Further, in the height direction (the Z-axis direction), the top P of the roof portion 22 is disposed at the position H2 higher than the position H0 of the upper end of the glass tube 12 by the length which is 1.5 times the outer diameter of the glass tube 12, thus improving the effect of melting the frost adhering to the evaporator 110 and the frost in the tray 30. With the arrangement of the above roof portion 22, the frost on the evaporator 110 and the tray 30 may be effectively melted to provide the high defrosting performance.

[0069] In addition, in the defrosting devices 2 according to the first to fourth embodiments, the width W at the lower end of the roof portion 22 is 2 to 3 times the outer diameter D of the glass tube 12, thus well balancing and effectively melting the frost of the evaporator 110 and the tray 30.

(Defrosting component)

[0070] FIG. 9 is a perspective view for illustrating a defrosting component according to an embodiment of the present invention. FIG. 9 schematically shows the shape of the roof portion 22. Any of the defrosting devices 2 according to above-mentioned embodiments includes the defrosting component 50 formed by bending the metal rod. As shown in FIG. 3 or 9, the defrosting component 50 has the hook portion 52 formed at one end portion of the metal rod and inserted into the hole portion 26 provided in the metal sheet forming the roof portion 22 in the free rotation state. Further, the defrosting component 50 has the heat receiving portion 54 connected with the hook portion 52 and extending obliquely downwards while connected with the metal sheet forming the roof portion 22. The defrosting component 50 mounted, at one end portion thereof, to the roof portion 22 by the hook portion 52 in the free rotation state is suspended by gravity, and the heat receiving portion 54 extends obliquely downwards while coming into contact with the metal sheet forming the roof portion 22.

[0071] Further, the defrosting component 50 has the bypassing portion 56 connected with the heat receiving portion 54 and bent to bypass the glass tube 12. Since the heat receiving portion 54 and the metal sheet forming the roof portion 22 come into contact by gravity to have fixed positions, the bypassing portion 56 may be reliably separated from the glass tube 12. Further, the defrosting component 50 has the heat dissipation portion 58 connected with the bypassing portion 56 and extending

downwards into the tray 30 and the drainage pipe 40. The defrosting component 50 terminates at an end portion of the heat dissipation portion 58.

[0072] In the defrosting component 50 mounted to the roof portion 22 by the hook portion 52 in the free rotation state, the heat receiving portion 54 comes into contact with the roof portion 22 by gravity, and therefore receives the heat from the defrosting heater 10 through the contact part of the metal roof portion 22. Furthermore, the heat received by the heat receiving portion 54 is conducted through the bypassing portion 56 to the heat dissipation portion 58 extending downwards. Thus, the heat is supplied from the heat dissipation portion 58 to the frost or water in the tray 30 or the drainage pipe 40. Therefore, the frost in the tray 30 or the drainage pipe 40 may be melted and discharged through the drainage pipe 40.

[0073] As mentioned above, by using the defrosting component 50 in addition to the roof portion 22, the heat from the defrosting heater 10 may be effectively supplied to the frost or water in the tray 30 or the drainage pipe 40 at a low manufacturing cost.

[0074] Further, as shown by arrows A, B in FIG. 9, the defrosting component 50 may be rotated to be disposed along a surface of the roof portion 22. Therefore, when the defrosting device 2 is mounted in the refrigerator 100, or when components are dismantled or replaced, the defrosting component 50 is placed along the surface of the roof portion 22 and fixed using adhesive tape, or the like, thus preventing the defrosting component 50 from interfering with other members, so as to improve a working efficiency.

(Refrigerator)

[0075] The refrigerator 100 shown in FIG. 1 including the defrosting device 2 according to the above-mentioned embodiment may also achieve any of the above-mentioned effects.

[0076] While the embodiments of the present invention have been described, the disclosure may vary in details of the structure, and combinations of elements, changes of sequences, or the like, of the embodiments may be realized. The protection scope of the invention is defined by the appended claims.

Claims

1. A defrosting device (2), comprising:

a defrosting heater (10) having a heating element in a single-layer glass tube (12) with a circular cross section perpendicular to a length direction;

a roof portion (22) disposed above the glass tube (12) and extending in the length direction of the glass tube (12), the roof portion (22) being made of a metal sheet and having an upwards

protruding shape;
 a tray (30) disposed below the glass tube (12),
 extending in the length direction of the glass
 tube (12), and having an opening (32) formed
 in a bottom (30A) thereof; and
 a drainage pipe (40) extending downwards from
 the opening (32),
 wherein in a cross section perpendicular to the
 length direction of the glass tube (12),
 a top of the roof portion (22) is located on a
 vertical line (VL) passing through a general center
 (G) of the glass tube (12), and the roof portion
 (22) is symmetrical with respect to the vertical
 line (VL) within at least a predetermined range
 (2) on both sides of the vertical line (VL), and the
 opening (32) is located directly below the glass
 tube (12),
 and

characterized in that

in a cross section along the length direction of
 the glass tube (12) comprising the vertical line
 (VL), end regions on both sides of the roof por-
 tion (22) in the length direction are inclined
 downwards to downwards reflect radiant heat
 from a lower side;
 wherein a lower end portion of the roof portion
 (22) is disposed at a same position as or above
 an upper end of the glass tube (12) in a height
 direction, and
 in the height direction, the top of the roof portion
 (22) is disposed at a position higher than a
 position of the upper end of the glass tube
 (12) by a length which is 1.5 times an outer
 diameter of the glass tube (12).

2. The defrosting device (2) according to claim 1,
 wherein a width at a lower end of the roof portion
 (22) is 2 to 3 times the outer diameter of the glass
 tube (12) in the cross section perpendicular to the
 length direction of the glass tube (12).

3. The defrosting device (2) according to claim 1,
 further comprising a defrosting component (50)
 made of a bent metal rod,
 the defrosting component (50) having:

a hook portion (52) formed at one end portion of
 the metal rod and inserted into a hole portion
 (26) provided at the roof portion (22) in a free
 rotation state;
 a heat receiving portion (54) connected with the
 hook portion (52) and extending obliquely down-
 wards while connected with the roof portion (22);
 a bypassing portion (56) connected with the heat
 receiving portion (54) and bent to bypass the
 glass tube (12); and
 a heat dissipation portion (58) connected with
 the bypassing portion (56) and extending down-

wards into the tray (30) and the drainage pipe
 (40).

4. The defrosting device (2) according to claim 1,
 wherein the roof portion (22) is formed by a first
 region (22A) and a second region (22B) having flat
 plate shapes; or the roof portion (22) is formed by a
 first region (22A) and a second region (22B) having
 curved surface shapes.

5. The defrosting device (2) according to claim 4,
 wherein the first region (22A) and the second region
 (22B) are symmetrically arranged with respect to the
 vertical line (VL).

6. The defrosting device (2) according to claim 4,
 wherein an angle θ formed by the first region (22A)
 and the vertical line (VL) coincides with an angle θ
 formed by the second region (22B) and the vertical
 line (VL), and the first region (22A) is longer than the
 second region (22B).

7. The defrosting device (2) according to claim 1,
 wherein the roof portion (22) has a third region
 (22C) and a fourth region (22D) inclined downwards
 in end regions on both sides in the length direction
 thereof.

8. The defrosting device (2) according to claim 7,
 wherein planes or curved surfaces serve as reflec-
 tion surfaces of the third region (22C) and the fourth
 region (22D).

9. A refrigerator comprising the defrosting device (2)
 according to claim 1.

Patentansprüche

1. Abtauvorrichtung (2) mit:

einer Abtauheizung (10) mit einem Heizelement
 in einem einwandigen Glasrohr (12) mit kreis-
 förmigem Querschnitt senkrecht zur Längsrich-
 tung;
 einem Dachabschnitt (22), der oberhalb des
 Glasrohrs (12) angeordnet ist und sich in der
 Längsrichtung des Glasrohrs (12) erstreckt, wo-
 bei der Dachabschnitt (22) aus einem Metall-
 blech gefertigt ist und eine nach oben vorsprin-
 gende Form aufweist;
 einer Schale (30), die unterhalb des Glasrohrs
 (12) angeordnet ist, sich in der Längsrichtung
 des Glasrohrs (12) erstreckt und eine in ihrem
 Boden (30A) ausgebildete Öffnung (32) auf-
 weist; und
 einem Abflussrohr (40), das sich von der Öff-
 nung (32) nach unten erstreckt,

- wobei in einem Querschnitt senkrecht zur Längsrichtung des Glasrohrs (12), eine Oberseite des Dachabschnitts (22) auf einer vertikalen Linie (VL) liegt, die durch einen allgemeinen Mittelpunkt (G) des Glasrohrs (12) verläuft, und der Dachabschnitt (22) in Bezug auf die vertikale Linie (VL) innerhalb mindestens eines vorbestimmten Bereichs (2) auf beiden Seiten der vertikalen Linie (VL) symmetrisch ist, und die Öffnung (32) sich direkt unterhalb des Glasrohrs (12) befindet, und **dadurch gekennzeichnet, dass** in einem Querschnitt entlang der Längsrichtung des Glasrohrs (12), der die vertikale Linie (VL) aufweist, Endbereiche auf beiden Seiten des Dachabschnitts (22) in der Längsrichtung nach unten geneigt sind, um Strahlungswärme von einer Unterseite nach unten zu reflektieren; wobei ein unterer Endabschnitt des Dachabschnitts (22) in einer Höhenrichtung an der derselben Position wie das obere Ende des Glasrohrs (12) oder oberhalb des oberen Endes des Glasrohrs (12) angeordnet ist, und in der Höhenrichtung die Oberseite des Dachabschnitts (22) um eine Länge, die dem 1,5-fachen des Außendurchmessers des Glasrohrs (12) entspricht, höher als die Position des oberen Endes des Glasrohrs (12) angeordnet ist.
2. Abtauvorrichtung (2) nach Anspruch 1, wobei eine Breite am unteren Ende des Dachabschnitts (22) das 2- bis 3-fache des Außendurchmessers des Glasrohrs (12) im Querschnitt senkrecht zur Längsrichtung des Glasrohrs (12) beträgt.
3. Abtauvorrichtung (2) nach Anspruch 1, die ferner eine Abtaukomponente (50) aus einem gebogenen Metallstab aufweist, wobei die Abtaukomponente (50) Folgendes aufweist:
- einen Hakenabschnitt (52), der an einem Endabschnitt des Metallstabs ausgebildet ist und in einen Lochabschnitt (26), der am Dachabschnitt (22) vorgesehen ist, in einem frei drehbaren Zustand eingeführt ist;
- einen Wärmeaufnahmeabschnitt (54), der mit dem Hakenabschnitt (52) verbunden ist und sich schräg nach unten erstreckt, während er mit dem Dachabschnitt (22) verbunden ist;
- einen Umgehungsabschnitt (56), der mit dem Wärmeaufnahmeabschnitt (54) verbunden ist und so gebogen ist, dass er das Glasrohr (12) umgeht; und
- einen Wärmeableitungsabschnitt (58), der mit dem Umgehungsabschnitt (56) verbunden ist und sich nach unten in die Schale (30) und das Abflussrohr (40) erstreckt.

4. Abtauvorrichtung (2) nach Anspruch 1, wobei der Dachabschnitt (22) aus einem ersten Bereich (22A) und einem zweiten Bereich (22B) mit flacher Plattenform gebildet ist; oder der Dachabschnitt (22) aus einem ersten Bereich (22A) und einem zweiten Bereich (22B) mit gekrümmter Oberflächenform gebildet ist.
5. Abtauvorrichtung (2) nach Anspruch 4, wobei der erste Bereich (22A) und der zweite Bereich (22B) symmetrisch zur vertikalen Linie (VL) angeordnet sind.
6. Abtauvorrichtung (2) nach Anspruch 4, wobei ein durch den ersten Bereich (22A) und die Vertikallinie (VL) gebildeter Winkel θ mit einem durch den zweiten Bereich (22B) und die Vertikallinie (VL) gebildeten Winkel θ übereinstimmt und der erste Bereich (22A) länger ist als der zweite Bereich (22B).
7. Abtauvorrichtung (2) nach Anspruch 1, wobei der Dachabschnitt (22) einen dritten Bereich (22C) und einen vierten Bereich (22D) aufweist, die an den Endbereichen auf beiden Seiten in der Längsrichtung nach unten geneigt sind.
8. Abtauvorrichtung (2) nach Anspruch 7, wobei Ebenen oder gekrümmte Flächen als Reflexionsflächen des dritten Bereichs (22C) und des vierten Bereichs (22D) dienen.
9. Kühlschrank mit der Abtauvorrichtung (2) nach Anspruch 1.

Revendications

1. Dispositif de dégivrage (2), comprenant :
- un dispositif de chauffage de dégivrage (10) présentant un élément chauffant dans un tube en verre monocouche (12) à section transversale circulaire perpendiculaire à une direction longitudinale ;
- une partie de toit (22) disposée au-dessus du tube en verre (12) et s'étendant dans la direction longitudinale du tube en verre (12), la partie de toit (22) étant constituée d'une feuille de métal et présentant une forme de saillie vers le haut ;
- un plateau (30) disposé sous le tube en verre (12), s'étendant dans la direction longitudinale du tube en verre (12) et présentant une ouverture (32) formée dans le fond (30A) de celui-ci ;
- et
- un tuyau de drainage (40) s'étendant vers le bas à partir de l'ouverture (32), dans lequel, dans une section transversale perpendiculaire à la direction longitudinale du tube

- en verre (12),
le sommet de la partie de toit (22) est situé sur une ligne verticale (VL) passant par un centre général (G) du tube en verre (12), et la partie de toit (22) est symétrique par rapport à la ligne verticale (VL) dans au moins une plage prédéterminée (2) de part et d'autre de la ligne verticale (VL), et l'ouverture (32) est située directement sous le tube en verre (12), et
- caractérisé en ce que**
- dans une section transversale le long de la direction longitudinale du tube en verre (12) comprenant la ligne verticale (VL), des régions d'extrémité de part et d'autre de la partie de toit (22) dans la direction longitudinale sont inclinées vers le bas pour réfléchir vers le bas une chaleur rayonnante provenant d'un côté inférieur ;
- dans lequel une partie d'extrémité inférieure de la partie de toit (22) est disposée à la même position ou au-dessus d'une extrémité supérieure du tube en verre (12) dans une direction de hauteur, et
- dans la direction de hauteur, le sommet de la partie de toit (22) est disposé à une position plus haute que la position de l'extrémité supérieure du tube en verre (12) selon une longueur qui est 1,5 fois le diamètre extérieur du tube en verre (12).
2. Dispositif de dégivrage (2) selon la revendication 1, dans lequel une largeur au niveau de l'extrémité inférieure de la partie de toit (22) est 2 à 3 fois le diamètre extérieur du tube en verre (12) dans la section transversale perpendiculaire à la direction longitudinale du tube en verre (12).
 3. Dispositif de dégivrage (2) selon la revendication 1, comprenant en outre un composant de dégivrage (50) constitué d'une tige métallique courbée, le composant de dégivrage (50) présentant :
 - une partie de crochet (52) formée au niveau d'une extrémité de la tige métallique et insérée dans une partie de trou (26) prévue au niveau de la partie de toit (22) dans un état de rotation libre ;
 - une partie recevant la chaleur (54) reliée à la partie de crochet (52) et s'étendant obliquement vers le bas tout en étant reliée à la partie de toit (22) ;
 - une partie de dérivation (56) reliée à la partie recevant la chaleur (54) et courbée pour contourner le tube en verre (12) ; et
 - une partie de dissipation de chaleur (58) reliée à la partie de dérivation (56) et s'étendant vers le bas jusque dans le plateau (30) et le tuyau de drainage (40).
 4. Dispositif de dégivrage (2) selon la revendication 1, dans lequel la partie de toit (22) est formée d'une première région (22A) et d'une deuxième région (22B) présentant des formes de plaque plate ; ou la partie de toit (22) est formée d'une première région (22A) et d'une deuxième région (22B) présentant des formes de surface courbes.
 5. Dispositif de dégivrage (2) selon la revendication 4, dans lequel la première région (22A) et la deuxième région (22B) sont agencées symétriquement par rapport à la ligne verticale (VL).
 6. Dispositif de dégivrage (2) selon la revendication 4, dans lequel un angle θ formé par la première région (22A) et la ligne verticale (VL) coïncide avec un angle θ formé par la deuxième région (22B) et la ligne verticale (VL), et la première région (22A) est plus longue que la deuxième région (22B).
 7. Dispositif de dégivrage (2) selon la revendication 1, dans lequel la partie de toit (22) présente une troisième région (22C) et une quatrième région (22D) inclinées vers le bas dans des régions d'extrémité de part et d'autre de la direction longitudinale de celle-ci.
 8. Dispositif de dégivrage (2) selon la revendication 7, dans lequel des plans ou des surfaces courbes servent de surfaces de réflexion de la troisième région (22C) et de la quatrième région (22D).
 9. Réfrigérateur comprenant le dispositif de dégivrage (2) selon la revendication 1.




FIG.1




FIG.2




FIG.3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2004198097 A [0004]
- JP 2000314581 A [0006]
- JP 2006010151 A [0007]
- JP 2000018799 A [0007]