



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
21.12.2022 Bulletin 2022/51

(51) International Patent Classification (IPC):
E04F 13/09 ^(2006.01) **E04F 13/08** ^(2006.01)
E04F 13/14 ^(2006.01)

(21) Application number: **22189052.8**

(52) Cooperative Patent Classification (CPC):
E04F 13/147; E04F 13/0862; E04F 13/0866;
E04F 13/0875

(22) Date of filing: **29.04.2016**

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR

- **BROWN, Paul Addison**
Salisbury, NC 28146 (US)
- **MUELLER, Berthold**
Salisbury, NC 28144 (US)
- **HOFFNER, Randal**
Salisbury, NC 28145 (US)
- **ADAMS, Stewart**
Salisbury, NC 28145 (US)

(30) Priority: **23.10.2015 US 201562245617 P**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:
16857914.2 / 3 365 511

(71) Applicant: **DDP Specialty Electronic Materials US, LLC**
Wilmington, DE 19805 (US)

(74) Representative: **Algemeen Octrooi- en Merkenbureau B.V.**
P.O. Box 645
5600 AP Eindhoven (NL)

(72) Inventors:
• **TAYLOR, Charles David**
Salisbury, NC 28144 (US)

Remarks:

This application was filed on 05.08.2022 as a divisional application to the application mentioned under INID code 62.

(54) **INSULATED FIBRE REINFORCED WALL PANEL**

(57) The invention is related to a wall panel (10) comprising a middle layer (30) comprising magnesium oxide and having a first and a second side the middle layer

comprising a glass fiber reinforcing material embedded therein; The wall panel further comprises an insulation layer (20) bonded to the second side of the middle layer.




Fig. 4

Description

Technical Field and Background of Invention:

[0001] The invention relates to the field of building construction materials. More particularly, the invention relates to the field of construction components used in the construction of walls, ceilings, and other planar, angled, and curved surfaces for buildings.

[0002] Humans have utilized bricks and other hard surfaces as construction components for buildings for thousands of years. The earliest sun dried bricks were made in Ancient Egypt. Later, bricks were dried using a fuel source. The Book of Genesis records that burnt brick was used in the construction of the Tower of Babel. Thus, from ancient times to the present, brick has remained a popular building material.

[0003] The enduring presence of brick is due in no small part to its stellar properties as an exterior surface. Bricks are capable of resisting high summer heat as well as cold winters and changes there between. In addition to such thermal properties, brick provides a strong outer shell to a building. Brick resists wind, rain, snow, dust and other detrimental environmental elements. Brick can be fire retardant surface for buildings. Bricks can be manufactured in a myriad of sizes, textures, and colors. Further, though it need not be painted, when brick is painted, the paint adheres well to the brick.

[0004] However, despite such positive characteristics, brick has a few drawbacks, mostly related to installation. For instance, whereas other exterior surfaces may be relatively easily applied to an existing building structure, brick is much more difficult to install on an existing building as an alternate siding choice during a renovation. Further, the laying of brick during the construction of a building is a labor intensive operation. Each brick must be mortared and laid, one on another, brick by brick, by a skilled brick mason. As manual labor prices rise in a given market, so do the costs associated with using brick as a building material. It is also difficult or impossible to install brick during the winter because mortar does not cure well or at all in freezing temperatures.

[0005] Thus, there exists a need for a building product that has the same or better building characteristics and aesthetic appeal as traditional brick but also can be applied without the need for an extensive skilled labor team of brick masons. Further, there exists a need for a building product that has the same or better building characteristics and aesthetic appeal as traditional brick that may be used as a retro-fit product for providing a siding to an existing building structure. Further, as energy costs and environmental consciousness increase, so to does the demand for better insulation. Thus, there is also a need for building materials offering improved insulation of a building's envelope.

Summary of the Invention:

[0006] The present invention is thus a wall panel system that exhibits many of the same characteristics as traditional brick without the need for extensive labor costs associated with traditional brick masonry. Further, the invention is not limited to new construction applications but may be utilized in existing construction as a retrofit application.

[0007] The invention has the same aesthetic appeal as traditional brick and has the same or better engineering benefits. The invention functions as a structural element of the building, a water-resistive barrier, a fire retardant layer, an insulating envelope, and an aesthetic finished exterior surface. The invention is lightweight and energy efficient.

[0008] The invention may include an outer veneer layer, a middle cement layer, and an inner insulation layer.

[0009] The outer veneer layer may be thin brick, stone, tile, or other such material (hereinafter referred to as "brick" unless otherwise specified) as desired for both aesthetic and engineering appeal. These may be referred to as an architectural or aesthetic element. Alternatively, the outer veneer layer may be two parts comprising thin brick, stone, tile or other material which is embedded in a substrate. This substrate may be a polyurethane or other plastic. According to this two part veneer layer embodiment of the invention, the brick is placed in a mold according to a desired pattern and the polyurethane, plastic, or other material is pour into the mold and bonds to the brick. A finished surface of the brick will extend above the level of the poured substrate once the substrate hardens. According to another embodiment of the invention, the substrate may have sand added so that a top surface of the substrate, visible between the brick, has the appearance mortar. In the above example, additional mortar or mortar substitute (such as a sanded glue) may be used to cover any screw holes or gaps between sections.

[0010] The middle cement layer may be glass fiber reinforced concrete. Alternatively, the middle cement layer may be Magnesium Oxide. The middle cement layer may be poured and cured in place or it may be sourced as a pre-fabricated product, particularly with respect to the Magnesium Oxide material.

[0011] The inner insulation layer may include a rigid pour foam which may be a two part rigid pour urethane foam.

[0012] According to one embodiment of the invention, a wall panel may include a poured substrate selected from the group consisting of polyurethane and plastic. The wall panel may further include a plurality of aesthetic elements, embedded in and bonded to the poured substrate. According to such an embodiment, the aesthetic elements may be selected from the group consisting of brick, ceramic tile, porcelain tile, natural stone, engineered stone, wood, ceramic, plastic, and vinyl. According to such an embodiment, a finished surface of the aes-

thetic elements may extend above a top surface of the poured substrate. According to such an embodiment, each one of the aesthetic elements may be arranged in spaced-apart relation to another one of the aesthetic elements.

[0013] According to another embodiment of the invention, the wall panel may include a middle layer having a first side which is attached to a rear surface of the poured substrate. The wall panel may also include an insulation layer having a first side chemically bonded to a second side of the middle layer. According to such an embodiment, the insulation layer may include a two part rigid urethane pour foam the insulation layer may be chemically bonded to the middle layer during a pour.

[0014] According to another embodiment of the invention the middle layer may be magnesium oxide.

[0015] According to another embodiment of the invention, the middle layer may be fiber reinforced cement.

[0016] According to another embodiment of the invention, the middle layer may be attached to the poured substrate using an attachment means such as screws, nails, bolts, welds, construction adhesive, rivets, and clasps.

[0017] According to another embodiment of the invention, the wall panel may be attached to a building structure using an attachment means such as screws, nails, bolts, welds, construction adhesive, rivets, and clasps.

[0018] According to another embodiment of the invention, the poured substrate may also include sand, causing the top surface of the poured substrate to have an appearance of mortar.

[0019] According to another embodiment of the invention, the wall panel may further include sanded glue for covering imperfections in the top surface of the poured substrate and for causing the top surface of the poured substrate to have an appearance of mortar.

[0020] According to one embodiment of the invention, a wall panel may include a middle layer made from magnesium oxide. The middle layer may have a first and a second side. A veneer layer may be attached to the first side of the middle layer. According to such an embodiment, the veneer layer may include one or more of brick, ceramic tile, porcelain tile, natural stone, engineered stone, wood, ceramic, plastic, vinyl, and paint.

[0021] According to another embodiment of the invention, an insulation layer may have a first side chemically bonded to a second side of the middle layer. The insulation layer may include a two part rigid urethane pour foam and the insulation layer may be chemically bonded to the middle layer during a pour.

[0022] According to one embodiment of the invention, a wall panel may include a middle layer made from a magnesium oxide. The middle layer may have a first and a second side. The wall panel may also include a veneer layer attached to the first side of the middle layer. The wall panel may also have an insulation layer. The insulation layer may have a first side chemically bonded to a second side of the middle layer. The insulation layer may be made from a two part rigid urethane pour foam may

be chemically bonded to the middle layer during a pour.

[0023] In one embodiment, the inner insulation layer is poured onto and is fixedly attached to the middle cement layer. The outer veneer layer is attached to the middle cement layer with mortar or other cement product. Alternatively, in the embodiment that utilizes the two-part veneer layer, the substrate of the veneer layer may be attached to the middle cement layer via attachment screws (or nails, wall ties, or other similar attachment means). Such attachment screws may be positioned between spacing in the brick and extend through the substrate of the veneer layer into the cement layer and even into the insulation layer. Preferably, the screws of the veneer do not extend beyond the insulation layer in exterior applications.

[0024] According to another embodiment, the veneer layer may be attached to the middle layer with a chemical or other construction adhesive. The adhesive may be either one part design or of multi-part design.

[0025] According to another embodiment of the invention, the veneer layer may be brick, tile, stone, engineered stone, or other such product as desired for aesthetic purposes. The mortar or other adhesive used to attach the veneer layer may also be used to grout lines between the bricks, stone, or tile of the veneer layer or another product may be applied as a grout.

[0026] According to another embodiment of the invention, the veneer layer may include spaced apart latitudinal ridges on a rear surface of the veneer layer. Such latitudinal ridges may be narrower in width than the space between the ridges. The latitudinal ridges may create channels for moisture, gas, and other fluids which may accumulate between the veneer layer and the middle layer to escape.

[0027] According to one embodiment of the invention, in embodiments where a two part veneer layer is not used and the brick are adhered directly to the cement layer, the middle cement layer may include relief lines or guide lines. The relief lines function to provide a guide when attaching the veneer layer to the cement layer. For example, when the veneer layer uses rectangular brick, the relief lines will be in the shape of the rectangular brick and be just larger than the perimeter of the brick such that the brick fits snugly inside the relief lines upon application. Similarly, if stone is the veneer layer, the relief lines will match and be just larger than the perimeter of the stone to be installed.

[0028] According to another embodiment of the invention, the respective inner layer and middle cement layer are constructed into panels designed to be attached to a building frame. The panels may be attached directly to the studs of a building or they may be attached to some other structural component of the building.

[0029] According to another embodiment of the invention, the panels are attached using screws such as structural insulated panel (SIP) screws. The SIP screws attach to the building through holes in the panel. The holes may be countersunk so that the head of the screws is flush

with the surface of the panel.

[0030] According to another embodiment, attachment points, or other items such as a pvc inlay may be incorporated into middle cement layer. Such items will be of a material that does not negatively impact the performance or other property of the insulation or otherwise cause a conductive source of thermal wicking.

[0031] According to another embodiment of the invention, the panels are attached using nails, construction adhesive, bolts, rivets, clasps, or other such attachment devices.

[0032] According to another embodiment of the invention, once the panels are attached to the building, the seams between the panels are sealed.

[0033] According to another embodiment of the invention, once sealed, the veneer layer is applied over the middle cement layer. In embodiments utilizing the two-part veneer layer, screws may be used to attach the veneer layer to the middle cement layer as described above. However, in the embodiments where the brick is attached directly to the cement layer (the embodiment without the substrate in the veneer layer), during application, mortar or other attachment material is applied over the panels and the brick or other material is fitted between the relief lines. The bricks cover the holes of the SIP screws and also, importantly, cover the seams of the panels. Thus, there are no exposed joints or other openings of the panels.

[0034] According to another embodiment of the invention, trim pieces are applied around openings in the building envelope such as around windows and doors. These trim pieces may be in the form of headers and may include various shapes as desired for structural and aesthetic purposes. The trim pieces may be formed in the two part manner as described above with respect to the veneer layer. That is, the trim pieces may comprise brick embedded in a substrate. In this way, according to one manufacturing process, the brick may be arranged in a mold and may be coated with wax. The liquid substrate (such as polyurethane, plastic, cement, glue, or other material) may be poured into the mold around the brick. This substrate bonds to the brick.

[0035] According to another embodiment of the invention, corner pieces are attached to the panel ends at corners of the building, or wherever corners may be required, and then brick or other material as desired is placed over the corner pieces just with the panels. The corner pieces may alternatively be formed using the two-part veneer system as described above with respect to the trim pieces and the outer veneer layer.

[0036] According to another embodiment of the invention, the panels provide a continuous insulating envelope for the walls of a structure. The inner insulation layer may be one inch and may also be up to or greater than three inches thick. Such insulation may provide the panels with an insulation factor of R7 to R21 or greater depending on various factors of design.

[0037] Such an insulation regime applied to outer walls

of a structure may, depending on other building and environmental factors such as zoning, building codes, etc..., free up space within stud walls for other building elements such as wiring, plumbing etc... and may also reduce the size studs required for a particular building plan. For instance, whereas 2X6 or 2X8 studs may have been required to achieve a desired insulation factor, by utilizing the invention as an exterior envelope, 2X4 studs may suffice. Similarly, in a retrofit application, where an older building may have little or no insulation, significant insulation, in addition to aesthetic elements, can be gained by applying the invention to the pre-existing building.

Brief Description of the Drawings Figures:

[0038] Features, aspects, and advantages of a preferred embodiment of the invention are better understood when the detailed description is read with reference to the accompanying drawing, in which:

Fig. 1 is an exploded perspective view of an embodiment of the invention showing the layers;

Fig. 2 is a partial perspective view of an embodiment of the invention showing two adjacent panels and highlighting the attachment of the panels to a wall;

Fig. 3 is a perspective view of an embodiment of the invention showing one panel without the outer veneer layer attached;

Fig. 4 is perspective view of an embodiment of the invention showing two adjacent panels with the outer veneer layer partially attached and covering the joint between the two adjacent panels;

Fig. 5 is a perspective view of an embodiment of the invention showing adjacent panels with the outer veneer layer partially attached and covering the joint between two adjacent panels;

Fig. 6 is an exploded view of an embodiment of the invention showing the layers;

Fig. 7 is a partially exploded view of an embodiment of the invention showing the middle cement layer adhered to the insulation layer and showing the brick embedded in the substrate forming the two-part veneer layer;

Fig. 8 is a sectional view of an embodiment of the invention attached to a planar surface;

Fig. 9 is a sectional view of an embodiment of the invention attached to a plurality of studs;

Fig. 10 is a sectional view of an embodiment of the invention showing the use of dovetailed brick;

Fig. 11 is a partial front view of an embodiment of the invention showing joints between panels and attachment means; and

Fig. 12 is a partial front view of an embodiment of the invention showing mortar pointed between the brick and joints between panels and attachment means that have not yet been covered with mortar or other concealing compound;

Detailed Description:

[0039] It is to be understood by a person having ordinary skill in the art that the present discussion is a description of exemplary embodiments only and is not intended as limiting the broader aspects of the present invention. The following example is provided to further illustrate the invention and is not to be construed to unduly limit the scope of the invention.

[0040] Referring to Figs. 1-5, the invention is an insulated wall panel 10 having three layers, 20, 30, and 40. The panel 10 provides a finished aesthetic surface to a building, a structural component to a building, and an insulation factor for a building. As such, the installed wall panel 10 includes an inner insulation layer 20, a middle cement layer 30, and an outer veneer layer 40. The panel 10 may be attached to a building wall 50.

[0041] The outer veneer layer 40 may include brick (as shown in the drawings) but may also include stone, tile, engineered stone, and/or similar material depending on desired finish effect. Thus, the use of the term "brick" herein is synonymous and inclusive of other veneers thus listed. The veneer layer 40 is relatively thin and is attached to the middle cement layer 30 using mortar 44 or other appropriate material such as a chemical adhesive as best shown in Fig. 4. Each brick (or other material as desired) of the veneer layer 40 is thin and is defined by a perimeter.

[0042] The middle layer 30 provides a substrate to which the brick of the veneer 40 is applied upon installation on a building structure 50. The middle layer 30 has a plurality of sets of relief lines 32. Each set of relief lines 32 define a boundary that is just larger than the perimeter of a particular brick of the veneer layer 40 that is to be applied to the middle layer 30. The relief lines 32 may be formed to the thickness of the desired grout 42 spacing between the brick of the veneer layer 40.

[0043] The middle layer 30 is made of a cementitious product with a glass fiber reinforcing material embedded therein. The glass fiber has a high strength and is the principal load-carrying member of the middle layer 30 while the cement forms a matrix that allows the fibers to retain their desired location and orientation. The resultant product is thin and strong.

[0044] In order to form the middle layer 30, a mold is first constructed into which a slurry of uncured cementitious product of the middle layer 30 is poured. The mold will have the negatives of the relief lines 32 formed therein. These negatives will appear as small trenches within the mold such that when the cement cures and the middle layer 30 is removed from the mold, the relief lines 32 will protrude outward from the otherwise generally planar outer surface 34 of the middle layer. The inner surface 36 of the middle layer 30 will also be generally planar but will not have such relief lines 32. The middle layer 30 may remain in the mold while curing. Curing time is dependent upon the thickness, particulars of the mix design, and the environment in which the cement is being cured.

Preferably, the middle cement layer 30 is cured in a chamber.

[0045] Once cured, the middle layer 30 is then placed in a fixture that allows the inner insulation layer 20 to be applied and attached to the inner surface 36 of the middle layer 30. The inner insulation layer 20 is a rigid pour foam that is formed from a two part Class I rated urethane. The foam is non-CFC and non-HCFC. The foam is applied to the inner surface 36 of the middle layer 30 using a machine calibrated to deliver proper and consistent component mix. The finished urethane material 20 will have an in place density of approximately 2.2 pounds per cubic foot. The foam 20 adheres to the middle layer 30 such that the machine delivery and mixing of the components provides for a complete bond between the middle layer 30 and inner insulation layer 20. Thus, there are no adhesives or other chemical bonding required to achieve the strength of the final insulated panel 10. The inner insulation layer 20 may be one inch thick or up to three inches thick or greater depending on the level of insulation desired for a particular application.

[0046] Alternatively, rather than being poured, the middle layer 30 may be press-molded, extruded, vibration cast, sprayed, or slip formed. If, in alternate embodiments, attachment points or other items are incorporated into the structure they are placed in the mold prior to the injection of the urethane.

[0047] Once the cement and urethane foam of the respective middle 30 and inner 20 layers has cured, the panel 10 is in condition for application to a building 50. As shown in Fig. 2, the panels 10 are screwed with screws 52 to the wall 50 or other structural element of a building. End pieces, headers, and other trim pieces, having been similarly manufactured, are likewise attached to the building. The seams 22 between the respective panels and trim pieces are sealed with a sealing compound, such as Laticrete® Air and Water Barrier. Next, as shown in Fig. 4, an adhesive such as mortar 44 is applied to the outer surface of the middle layer 30. Next, the brick of the veneer layer 40 are applied on top of the adhesive 44 and between the relief lines 32. The brick of the veneer 40 are applied to overlap 38 the seams 22 in the panels 10. This overlapping 38 of the seams is best shown in Figs. 4 and 5. Finally, a grout 42 or other material is applied between the gaps in the brick of the veneer 40.

[0048] Referring to Figs. 6-12, the invention includes an embodiment 100 utilizing a two-part veneer layer 140. The top part of the veneer layer may brick 146 as shown. However, the invention contemplates that the concrete, tile, stone, wood, plastic, vinyl, and other materials may be utilized. As used herein, unless otherwise specified, the term "brick" will include all other such materials.

[0049] In addition to the two-part veneer layer 140, the invention may utilize a middle layer 130. This middle layer 130 may be formed from cement or from Magnesium Oxide or from another composite material. Preferably an insulating layer 120 is adhered to the middle layer 120. The inner insulation layer 120 is preferably a rigid pour

foam that is formed from a two part Class I rated urethane.

[0050] The brick 146 is embedded in a substrate 144. This substrate 144 may be a polyurethane or other plastic, cement, glass fiber reinforced concrete (GFRC), ceramic, or other composite liquid product. The two part layer is formed by having the brick 146 positioned in a mold according to desired pattern. The brick 146 may be coated with wax or other protective coating. Sand may be utilized as a release agent. The substrate 144 is then poured into the mold and surrounds a lower portion of the brick 146, thereby embedding the brick 146 in the substrate 144 as the substrate hardens. The brick 146 may have a smooth lower surface or may have notches which may be dovetail notches 145 as shown in Fig. 10.

[0051] Importantly, especially for exterior application, the mold (not shown) includes a plurality of parallel grooves which, when filled with the substrate 144 form ridges 148 in the substrate 144. These ridges 148 may be seen in the assembled sectional views of Figs. 8, 9, and 10. Between each ridge is a void 149 which forms a channel through which moisture, water, and other fluids may pass between the substrate 144 and the middle cement layer 130. Such fluid may exit through weep holes (not shown). For interior application, no such void 149 may be necessary and the substrate layer 144 may not have the ridges and may be directly attached to the middle layer 130. Likewise, for interior application, the middle layer 130 and the insulation layer 120 may not be used and the substrate may be adhered directly to an underlying construction element such as stud walls.

[0052] In practice, the two-part veneer layer 140 may be supplied to building contractors as one element and the combination of the middle layer 130 and insulation layer 120 may be supplied to building contractors as a second element. The second element 120, 130 may be attached via attachment means such as screws 152 to a block wall 150 as shown in Fig. 6 or studs 151 as shown in Fig. 9. The first element 140 may be attached to the first element 120, 130 via attachment means such as screws 154. Preferably, screws 154 do not extend all the way through the second element 120, 130 so that the thermal barrier is not breached. After these first and second elements have been added to a building structure, grout/mortar 142 may be pointed into the voids between the brick 146. This grout/mortar 142 may conceal screw heads/holes as shown in Fig. 9. Different grout/mortar joints are possible including raked, grapevine, extruded, concave, V, struck, flush, weathered, struck, and convex.

[0053] Alternatively, the substrate 144 may additionally comprise a sand additive which mimics the appearance of grout. In this embodiment, no additional grout/mortar needs to be added following installation of the top veneer layer except that a small amount of grout/mortar or an equivalent matching concealer such as caulk may be added to conceal screw/attachment heads and/or joints between panels.

[0054] The above description has contemplated use in a wall system for either exterior or interior use. However

the invention 100 contemplates use both in ceiling applications (not shown) and in paving and flooring applications (not shown). As shown in Figs. 11 and 12, the joints between panels of the top two-part veneer layer 140 may be staggered to form an interlocking pattern. It is contemplated that panels of the invention 100 may be cut as needed in a particular application. Corners, reliefs, window edging, keystones, and starter courses are also contemplated under the same methods as discussed above.

[0055] A wall panel system 10, 100 according to the invention has been described with reference to specific embodiments and examples. Various details of the invention may be changed without departing from the scope of the invention. Furthermore, the foregoing description of the preferred embodiments of the invention and best mode for practicing the invention are provided for the purpose of illustration only and not for the purpose of limitation, the invention being defined by the claims. It is envisioned that other embodiments may perform similar functions and/or achieve similar results. Any and all such equivalent embodiments and examples are within the scope of the present invention and are intended to be covered by the appended claims.

[0056] Protection may also be sought for a wall panel according to one of the following clauses:

1. A wall panel comprising:

a poured substrate selected from the group consisting of polyurethane and plastic; and
a plurality of aesthetic elements, embedded in and bonded to the poured substrate;
wherein the aesthetic elements are selected from the group consisting of brick, ceramic tile, porcelain tile, natural stone, engineered stone, wood, ceramic, plastic, and vinyl;
wherein a finished surface of the aesthetic elements extends above a top surface of the poured substrate; and
wherein each one of the aesthetic elements is in spaced-apart relation to another one of the aesthetic elements.

2. The wall panel of Clause 1 further comprising

a middle layer having a first side which is attached to a rear surface of the poured substrate; and
an insulation layer having a first side chemically bonded to a second side of the middle layer;
wherein the insulation layer comprises a two part rigid urethane pour foam; and
wherein the insulation layer is chemically bonded to the middle layer during a pour.

3. The wall panel of Clause 2 wherein the middle layer is magnesium oxide.

4. The wall panel of Clause 2 wherein the middle layer is fiber reinforced cement.

5. The wall panel of Clause 3 wherein the middle layer is attached to the poured substrate using an attachment selected from the group consisting of: screws, nails, bolts, welds, construction adhesive, rivets, and clasps.

6. The wall panel of Clause 3 wherein the wall panel is attached to a building structure using an attachment selected from the group consisting of: screws, nails, bolts, welds, construction adhesive, rivets, and clasps.

7. The wall panel of Clause 1 wherein the poured substrate further comprises sand causing the top surface of the poured substrate to have an appearance of mortar.

8. The wall panel of Clause 7 further comprising sanded glue for covering imperfections in the top surface of the poured substrate and for causing the top surface of the poured substrate to have an appearance of mortar.

9. A wall panel comprising:

a middle layer comprising magnesium oxide and having a first and a second side; and
a veneer layer attached to the first side of the middle layer;
wherein the veneer layer is selected from the group consisting of brick, ceramic tile, porcelain tile, natural stone, engineered stone, wood, ceramic, plastic, vinyl, and paint.

10. The wall panel of Clause 9 further comprising an insulation layer having a first side chemically bonded to a second side of the middle layer, wherein the insulation layer comprises a two part rigid urethane pour foam and wherein the insulation layer is chemically bonded to the middle layer during a pour.

11. A wall panel comprising:

a middle layer comprising magnesium oxide and having a first and a second side;
a veneer layer attached to the first side of the middle layer; and
an insulation layer having a first side chemically bonded to a second side of the middle layer;
wherein the insulation layer comprises a two part rigid urethane pour foam; and
wherein the insulation layer is chemically bonded to the middle layer during a pour.

12. The wall panel of Clause 11 wherein the wall

panel is attached to a building structure using an attachment selected from the group consisting of: screws, nails, bolts, welds, construction adhesive, rivets, and clasps.

13. The wall panel of Clause 11 wherein the veneer layer further comprises a plurality of aesthetic elements and a poured substrate selected from the group consisting of polyurethane and plastic, wherein a finished surface of the aesthetic elements extends above a top surface of the poured substrate, and wherein each one of the aesthetic elements is in spaced-apart relation to another one of the aesthetic elements.

14. The wall panel of Clause 13 wherein the plurality of aesthetic elements is selected from the group consisting of brick, ceramic tile, porcelain tile, natural stone, engineered stone, wood, ceramic, plastic, vinyl, and paint.

15. The wall panel of Clause 13 wherein the poured substrate further comprises sand causing the top surface of the poured substrate to have an appearance of mortar.

Claims

1. A wall panel comprising:

a middle layer comprising magnesium oxide and having a first and a second side the middle layer comprising a glass fiber reinforcing material embedded therein; and
an insulation layer bonded to the second side of the middle layer.

2. The wall panel of Claim 1 wherein a complete bond is provided between the middle layer and inner insulation layer and/or wherein the insulation layer is chemically bonded to the middle layer.

3. The wall panel of Claim 1 wherein the wall panel further comprises a veneer layer attached to the first side of the middle layer.

4. The wall panel of Claim 1 wherein the veneer layer comprises a plurality of aesthetic elements selected from the group consisting of brick, ceramic tile, porcelain tile, natural stone, engineered stone, wood, ceramic, plastic, vinyl, and paint.

5. The wall panel of Claim 3 wherein the veneer layer further comprises a plurality of aesthetic elements and a poured substrate selected from the group consisting of polyurethane and plastic, wherein a finished surface of the aesthetic elements extends

above a top surface of the poured substrate, and wherein each one of the aesthetic elements is in spaced-apart relation to another one of the aesthetic elements.

5

6. The wall panel of Claim 3 wherein the veneer layer comprises a plurality of aesthetic elements selected from the group consisting of brick, ceramic tile, porcelain tile, natural stone, engineered stone, wood, ceramic, plastic, vinyl, and paint. 10
7. The wall panel of Claim 5 wherein the poured substrate further comprises sand causing the top surface of the poured substrate to have an appearance of mortar. 15
8. The wall panel of Claim 1 wherein the inner insulation layer includes a rigid pour foam, preferably a two part rigid pour urethane foam. 20
9. The wall panel of Claim 1 wherein the inner insulation layer is one inch and up to or greater than three inches thick, the insulation layer preferably being a foam layer of uniform thickness. 25
10. The wall panel of Claim 1 wherein the insulation may provide the panels with an insulation factor of R7 to R21 or greater depending on various factors of design. 30
11. The wall panel of Claim 1 wherein the wall panel is attached to a building structure using an attachment selected from the group consisting of: screws, nails, bolts, welds, construction adhesive, rivets, and clasps 35
12. Wall panel system for either exterior or interior use comprising a plurality of wall panels according to one or more of claims 1-11. 40
13. The wall panel system according to claim 12 wherein seams between the wall panels are sealed. 45

45

50

55






Fig. 2








Fig. 4






Fig. 5

Fig. 6








Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12



EUROPEAN SEARCH REPORT

Application Number

EP 22 18 9052

5

10

15

20

25

30

35

40

45

50

55

1

EPO FORM 1503 03.82 (P04C01)

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2015/052838 A1 (RITCHIE GORDON D [CA] ET AL) 26 February 2015 (2015-02-26) * paragraph [0022] - paragraph [0025]; figures 1A, B *	1	INV. E04F13/09 E04F13/08 E04F13/14
X	US 2011/268916 A1 (PARDUE JR JOHNNY ROGER [US]) 3 November 2011 (2011-11-03) * paragraph [0032] - paragraph [0047]; figures 1-8 *	1	
Y	US 2014/069050 A1 (BOLIN JOEL W [US]) 13 March 2014 (2014-03-13) * paragraph [0046] - paragraph [0048]; figures 1-3 *	1-13	
Y	US 2010/297411 A1 (TSAI CHENG-CHUNG [TW] ET AL) 25 November 2010 (2010-11-25) * paragraph [0029] - paragraph [0031]; figures 1, 6, 7 *	1-13	
Y	AU 2010 101 323 A4 (YAO GUANGNING) 6 January 2011 (2011-01-06) * page 6, line 22 - line 25; figures 1, 2 *	1-13	TECHNICAL FIELDS SEARCHED (IPC) E04F E04C
Y	US 6 240 691 B1 (HOLZKAEMPER ROLF [CA] ET AL) 5 June 2001 (2001-06-05) * column 4, line 1 - line 29; figure 1 *	1-13	
Y	US 2014/083040 A1 (TAYLOR JR CHARLES DAVID [US] ET AL) 27 March 2014 (2014-03-27) * paragraph [0031] - paragraph [0036]; figures 1-5 *	1-13	
The present search report has been drawn up for all claims			
Place of search Munich		Date of completion of the search 25 October 2022	Examiner Khera, Daljit
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document			

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 22 18 9052

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-10-2022

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2015052838 A1	26-02-2015	NONE	
US 2011268916 A1	03-11-2011	NONE	
US 2014069050 A1	13-03-2014	US 2014069050 A1	13-03-2014
		US 2016102463 A1	14-04-2016
		US 2017254092 A1	07-09-2017
		US 2017254093 A1	07-09-2017
US 2010297411 A1	25-11-2010	NONE	
AU 2010101323 A4	06-01-2011	NONE	
US 6240691 B1	05-06-2001	CA 2206671 A1	21-12-1997
		CN 1177047 A	25-03-1998
		JP H1144036 A	16-02-1999
		KR 980002529 A	30-03-1998
		TW 338084 B	11-08-1998
		US 6240691 B1	05-06-2001
US 2014083040 A1	27-03-2014	US 2014083040 A1	27-03-2014
		US 2016237692 A1	18-08-2016
		US 2018187420 A1	05-07-2018