



(11)

EP 4 167 672 B9

(12)

CORRECTED EUROPEAN PATENT SPECIFICATION

(15) Correction information:

Corrected version no 1 (W1 B1)
Corrections, see
Claims DE 1

(51) International Patent Classification (IPC):

H04W 72/12 (2023.01) **H04W 72/04** (2023.01)
H04L 5/00 (2006.01)

(48) Corrigendum issued on:
11.12.2024 Bulletin 2024/50

(52) Cooperative Patent Classification (CPC):

H04L 5/0053; H04L 1/0016; H04L 1/1664;
H04L 1/1671; H04L 1/1861; H04L 1/1896;
H04L 65/10; H04W 72/21; H04L 1/1819;
H04W 72/1268

(45) Date of publication and mention
of the grant of the patent:
25.09.2024 Bulletin 2024/39(21) Application number: **22195377.1**(22) Date of filing: **03.04.2019**(54) **UPLINK CONTROL INFORMATION SENDING, UPLINK CONTROL INFORMATION RECEIVING METHOD, AND APPARATUS**

UPLINK-STEUERUNGSIINFORMATIONSSENDEVERFAHREN,
UPLINK-STEUERUNGSIINFORMATIONSEMPFANGSVERFAHREN UND VORRICHTUNG

PROCÉDÉ D'ENVOI D'INFORMATIONS DE COMMANDE DE LIAISON MONTANTE, PROCÉDÉ DE
RÉCEPTION D'INFORMATIONS DE COMMANDE DE LIAISON MONTANTE, ET APPAREIL

(84) Designated Contracting States:

**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

- ZHANG, Ruiqi**

Shenzhen, 518129 (CN)

- XUE, Lixia**

Shenzhen, 518129 (CN)

(30) Priority: **04.04.2018 CN 201810300222**(74) Representative: **Epping - Hermann - Fischer**
Patentanwaltsgeellschaft mbH

**Schloßschmidstraße 5
80639 München (DE)**

(43) Date of publication of application:

19.04.2023 Bulletin 2023/16

(56) References cited:

**WO-A1-2018/038758 CN-A- 107 801 246
US-A1- 2011 299 484 US-A1- 2015 249 984
US-A1- 2018 020 429**

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:

19781222.5 / 3 780 842

- QUALCOMM INCORPORATED: "Remaining issues for multiplexing UCI on PUSCH", 2 March 2018 (2018-03-02), pages 1 - 13, XP051398252, Retrieved from the Internet <URL: http://www.3gpp.org/ftp/tsg%5Fran/WG1%5FRL1/TSGR1%5F92/Docs/>**

(73) Proprietor: **Huawei Technologies Co., Ltd.**
Shenzhen, Guangdong 518129, (CN)

(72) Inventors:

- SUN, Hao**
Shenzhen, 518129 (CN)
- CAO, Yongzhao**
Shenzhen, 518129 (CN)
- LI, Hua**
Shenzhen, 518129 (CN)

Note: Within nine months of the publication of the mention of the grant of the European patent in the European Patent Bulletin, any person may give notice to the European Patent Office of opposition to that patent, in accordance with the Implementing Regulations. Notice of opposition shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

- "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Physical layer procedures for data (Release 15)", 3GPP STANDARD; TECHNICAL SPECIFICATION; 3GPP TS 38.214, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE, vol. RAN WG1, no. V15.0.0, 3 January 2018 (2018-01-03), pages 1 - 71, XP051392264
- "3rd Generation Partnership Project; Technical Specification Group Radio Access Network; NR; Multiplexing and channel coding (Release 15)", 3GPP STANDARD; TECHNICAL SPECIFICATION; 3GPP TS 38.212, 3RD GENERATION PARTNERSHIP PROJECT (3GPP), MOBILE COMPETENCE CENTRE ; 650, ROUTE DES LUCIOLES ; F-06921 SOPHIA-ANTIPOLIS CEDEX ; FRANCE, vol. RAN WG1, no. V15.0.0, 3 January 2018 (2018-01-03), pages 1 - 82, XP051392262
- CATT: "Remaining details of UCI multiplexing on PUSCH", 2 March 2018 (2018-03-02), pages 1 - 5, XP051397714, Retrieved from the Internet <URL:<http://www.3gpp.org/ftp/tsg%5Fran/WG1%5FRL1/TSGR1%5F92/Docs/>>

Description**TECHNICAL FIELD**

5 [0001] This application relates to the field of communications technologies, and in particular, to an uplink control information sending, an uplink control information receiving method, apparatuses, and a computer program product.

BACKGROUND

10 [0002] During wireless communication, a terminal device may send uplink shared channel (uplink shared channel, UL-SCH) data to a network device, and may also send control information to the network device.

[0003] Usually, the terminal device may send only uplink control information or both data and uplink control information to the network device through a physical uplink shared channel (physical uplink shared channel, PUSCH). However, the terminal device cannot currently determine to specifically send only the uplink control information or both the data and the uplink control information.

15 [0004] US 2015/0249984 A1 discloses a method and apparatus for transmitting UCI through a PUSCH. The method includes coding data bits and UCI bits, respectively; multiplexing the coded data bits and the coded UCI bits; and transmitting the multiplexed bit.

[0005] 3GPP draft R1-1802839 discusses remaining issues for multiplexing UCI on PUSCH.

20 [0006] 3GPP TS 38.214 v15.0.0 discloses a physical layer procedure for data in technical specification group radio access network.

[0007] US 2011/0299484 A1 discloses a base station including a transmit path circuitry to transmit an uplink grant in a DCI format to a subscriber station. The base station also includes a receive path circuitry to receive only UCI on a PUSCH from a subscriber station when the uplink grant includes a MCS of an enable transport block with a value of 29.

25 [0008] WO 2018/038758 A1 discloses that an evolved Node B (eNB) triggers transmission of uplink control information from a user equipment over unlicensed carrier that is applicable to, for example, MulteFire and Licensed-Assisted Access systems.

[0009] CN 107 801 246 A discloses a method, an apparatus and a user equipment for uplink transmission.

30 [0010] US 2018/0020429 A1 discloses a terminal device configured to efficiently transmit uplink control information, which uses the first PUCCH resource and a first PUCCH format for transmission on a physical downlink shared channel only in a first serving cell.

[0011] 3GPP TS 38.212 v15.0.0 discloses multiplexing and channel coding in technical specification group radio access network.

35 [0012] 3GPP draft R1-1801733 discusses remaining details of UCI multiplexing UCI on PUSCH.

SUMMARY

40 [0013] The present invention is defined by the subject-matter of the independent claims. Further details are defined in the dependent claims.

[0014] Embodiments of this application provide an uplink control information sending, an uplink control information receiving method, apparatuses, and computer program product, so as to provide a manner of determining that an uplink shared channel scheduled by a network device is used to send only uplink control information. The invention is defined in the attached set of claims. Further aspects and embodiment of the disclosure, which are helpful for understanding the invention, are presented below.

45 [0015] According to a first aspect, an uplink control information sending method is provided. In the method, a terminal device receives first DCI from a network device, where the first DCI is used to schedule an uplink shared channel; then, the terminal device determines, based on the first DCI, that the uplink shared channel is used to send only UCI; and finally, the terminal device sends first UCI to the network device through the uplink shared channel.

50 [0016] A case in which only the UCI is sent through the uplink shared channel is referred to as UCI-only. In the foregoing technical solution, the terminal device may directly determine, based on DCI sent by the network device, whether the uplink shared channel scheduled by using the DCI is UCI-only, thereby providing a determining manner in which the terminal device determines whether the uplink shared channel scheduled by the network device is UCI-only. The determining manner is a simple determining manner provided based on existing control information such as the DCI, and directly uses an existing signaling mode without increasing additional overheads. This can save transmission resources, and also can ensure a consistent understanding between the terminal device and the network device, thereby improving performance of interaction between the terminal device and the network device.

55 [0017] To support UCI-only determining based on the DCI, indication information used to indicate UCI-only may be added to the DCI. For example, the indication information is referred to as UCI-only indication information. After obtaining

the DCI, the terminal device may obtain the UCI-only indication information, and then determine, based on the UCI-only indication information, whether the uplink shared channel is UCI-only.

[0018] In a possible design, the terminal device may explicitly determine UCI-only based on information carried in the DCI. In another possible design, the terminal device may implicitly determine UCI-only based on information carried in the DCI.

[0019] In the explicit determining manner, based on the existing DCI, an extra bit field is added at a predetermined location in an existing DCI format, to carry the UCI-only indication information. The terminal device may directly determine UCI-only based on the UCI-only indication information at the predetermined location, without performing an additional calculation process. This is convenient and fast.

[0020] In the implicit determining manner, some parameters originally included in the DCI are used to implicitly indicate UCI-only. No additional modification needs to be made to the DCI, and there is a small modification to an existing standard. Optionally, when a value combination of two parameters in the DCI is an impossible combination in currently existing function combinations, that is, the value combination of the two parameters used to implicitly indicate UCI-only is not an existing function combination, for example, when the value combination of the two parameters represents two conflicting indications related to new data transmission and data retransmission, UCI-only is determined. New transmission and retransmission are not used to actually indicate new data transmission and data retransmission, in other words, the terminal device does not transmit new data or retransmit data based on the indications. In this solution, the indication combination that is impossible in the prior art is merely used to implicitly indicate UCI-only, that is, a different value combination of parameters is used to implement a new indication function.

[0021] In a possible design, an NDI and an RV that are in the DCI are used to determine UCI-only. When NDI flipping occurs, it indicates new data transmission, and when a value of the RV is a specific value (for example, 1 or 2), it indicates data retransmission. Therefore, a combination of the NDI and the RV may be used to represent conflicting indications of new data transmission and data retransmission. Then, coexistence of the two conflicting indications that is impossible in a current normal case is used to implicitly indicate UCI-only.

[0022] In a possible design, an NDI and I_{MCS} that are in the DCI are used to determine UCI-only. As described above, on a basis that new data transmission is indicated through NDI flipping, when I_{MCS} is a predetermined value, it indicates data retransmission. Then, coexistence of the two conflicting indications that is usually impossible in a normal case is used to implicitly indicate UCI-only.

[0023] To determine, based on the NDI, whether new data is transmitted, whether NDI flipping occurs needs to be determined first. To determine whether NDI flipping occurs, values of NDIs in two pieces of DCI are needed. One piece of DCI is the currently received DCI, that is, the first DCI; and the other piece of DCI is previous DCI that carries the same HARQ ID as the first DCI and that is closest to the first DCI in time. For ease of description, the other piece of DCI is referred to as second DCI in this design. Because the second DCI is a previous DCI received before the first DCI, the second DCI may be received by the terminal device before the first DCI is received. Further, whether a value of an NDI in the first DCI is the same as a value of an NDI in the second DCI may be compared to determine whether NDI flipping occurs. If the values of the two NDIs are the same, no NDI flipping occurs; or if the values of the two NDIs are different, it indicates that NDI flipping occurs.

[0024] In a possible design, when a value of I_{MCS} belongs to a set including index values indicating a highest modulation order in an MCS table, I_{MCS} may be used to indicate data retransmission. In a normal case, highest-order modulation is usually not used during retransmission and a plurality of retransmissions, that is, highest-order modulation is usually not used for retransmission in a current regular case. Therefore, in this design, a non-regular case in which I_{MCS} is an index value indicating a highest modulation order is used to indicate data retransmission, so that the data retransmission indication and the new data transmission indication represented through NDI flipping form two conflicting indications, to indicate UCI-only. In addition, based on several different existing MCS tables, there may be different sets including the index values indicating the highest modulation order in this design. For example, several sets include {17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 31}, {20, 21, 22, 23, 24, 25, 26, 27, 31}, and {17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 31}.

[0025] In a possible design, a function combination that does not exist currently and that includes NDI flipping and a condition that a value of I_{MCS} is greater than or equal to a predetermined value may be alternatively used to indicate UCI-only. The predetermined value may be a relatively large index value in an existing MCS table, for example, 30 or 31 (for example, a largest index value). In this design, for example, $I_{MCS} \in \{28, 29, 30, 31\}$ or $I_{MCS} \in \{29, 30, 31\}$. Because corresponding code rates are not set for index values 28, 29, 30, and 31, or index values 29, 30, and 31 in the existing MCS tables, in a current normal case, these index values are usually not used to indicate new data transmission. Based on this, the index values for which the corresponding code rates are not set currently are used to indicate data retransmission. Further, the data retransmission indication and the new data transmission indication represented through NDI flipping form two conflicting indications, to indicate UCI-only.

[0026] In a possible design, a combination of an NDI, an RV, and I_{MCS} may be alternatively used to determine UCI-only. In practice, whether NDI flipping occurs may be wrongly determined, for example, NDI flipping is wrongly determined as no NDI flipping. Based on this, a determining condition of I_{MCS} is added. The manner of adding the determining

condition can avoid a case in which UCI-only is inaccurately indicated and even cannot be indicated due to wrong determining, thereby improving determining accuracy.

[0027] In a possible design, a combination of an NDI, an RV, and a HARQ ID may be alternatively used to determine UCI-only. In this design, adding a determining condition of the HARQ ID can also improve UCI-only determining accuracy, thereby reducing and even eliminating impact caused by NDI wrong determining. In the newly added determining condition, a value of the HARQ ID may be 14 or 15. Because a HARQ ID having a relatively large value such as 15 or 14 is usually not used in a normal case, a currently impossible parameter combination in which the RV indicates data retransmission and the HARQ ID is 15 or 14 is used to indicate UCI-only. This can ensure UCI-only determining accuracy when the NDI cannot work due to wrong determining. Moreover, because the HARQ ID of 14 or 15 is rarely used in the normal case, even some wrong determining may not affect normal running of a HARQ.

[0028] After UCI-only is determined, a lookup may be performed in an MCS table by using the MCS index (that is, I_{MCS}) in the DCI, to obtain a corresponding code rate (which is referred to as a first code rate) and a modulation order. Then, the UCI is sent by using the obtained first code rate and modulation order.

[0029] In a possible design, a lookup is performed in a currently existing MCS table by directly using I_{MCS} in the DCI, to obtain a first code rate and a modulation order that correspond to I_{MCS} .

[0030] In a possible design, a new index value is created by using all bits indicating the HARQ ID and some of all bits indicating I_{MCS} , and then the new index value is used to perform a lookup in an MCS table, to obtain a corresponding first code rate and modulation order. Compared with table lookup by directly using I_{MCS} in the DCI, the solution in this design is more flexible, and can avoid a case in which a corresponding code rate cannot be obtained through table lookup by directly using I_{MCS} in the DCI, for example, when a value of a code rate that is in an MCS table and that corresponds to an index value is "reserved", thereby enhancing applicability of the solution. In a possible design, a 5-bit bit field is created based on all bits (that is, four bits) in the HARQ ID and one bit in I_{MCS} ; then, a value indicated by the created bit field is used as a new index value; and finally, the new index value is used for table lookup, to obtain a corresponding first code rate and modulation order.

[0031] In a possible design, one least significant bit in I_{MCS} may be used, because directly using the least significant bit in I_{MCS} is relatively convenient, and a value of the least significant bit in I_{MCS} has relatively small impact on the value of I_{MCS} . Moreover, the one least significant bit is placed after or before the four bits in the HARQ ID, that is, the one least significant bit in I_{MCS} is used as a least significant bit or a most significant bit in the created five bits. In this way, there is a relatively small modification to a structure of 4 bits in the HARQ ID.

[0032] In some possible designs, regardless of which table lookup manner is used for table lookup, both a first code rate and a modulation order may be obtained through table lookup. Further, quantities of REs that are used to send parts of the UCI may be calculated according to the following formulas. Optionally, the UCI may include three parts: a HARQ ACK, a CSI-part1, and a CSI-part2.

[0033] In a possible design, quantities of REs that are used to send the HARQ ACK, the CSI-part1, and the CSI-part2

may be calculated according to the following three formulas, respectively. Q'_{ACK} , Q'_{CSI-1} , and Q'_{CSI-2} represent the quantity of the REs used to send the HARQ ACK, the quantity of the REs used to send the CSI-part1, and the quantity of the REs used to send the CSI-part2, respectively.

$$Q'_{ACK} = \min \left\{ \left\lceil \frac{(O_{ACK} + L_{ACK}) \cdot \beta_{offset}^{ACK}}{\gamma_{ref} \cdot Q_m} \right\rceil, \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) \right\},$$

$$Q'_{CSI-1} = \min \left\{ \left\lceil \frac{(O_{CSI-1} + L_{CSI-1}) \cdot \beta_{offset}^{CSI-part1}}{\gamma_{ref} \cdot Q_m} \right\rceil, \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) - Q'_{ACK} \right\},$$

and

$$Q'_{CSI-2} = \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) - Q'_{CSI-1} - Q'_{ACK},$$

where γ_{ref} represents a first code rate obtained through table lookup, Q_m represents a modulation order obtained through

$$\sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}-1}} M_{\text{sc}}^{\text{UCI}}$$

table lookup, and (l) represents a quantity of all REs on the PUSCH, that is, a total quantity of REs that are allocated by the network device to the PUSCH; $O_{\text{CSI-2-ref}}$ represents a reference payload size of the CSI-part2, and $L_{\text{CSI-2-ref}}$ represents a corresponding quantity of CRC bits; and $O_{\text{CSI-1}}$ represents a payload size of the CSI-part1, and $L_{\text{CSI-1}}$ represents a corresponding quantity of CRC bits. $O_{\text{CSI-1}} + L_{\text{CSI-1}}$ may be understood as a total payload size of

10 $\beta_{\text{offset}}^{\text{CSI-part1}}$
the CSI-part1, and $O_{\text{CSI-2-ref}} + L_{\text{CSI-2-ref}}$ may be understood as a total reference payload size of the CSI-part2.

15 $\beta_{\text{offset}}^{\text{CSI-part2}}$
and β_{offset} represent code rate compensation parameters of the CSI-part1 and the CSI-part2, respectively, and are semi-statically preconfigured by a wireless higher layer of the network device or dynamically indicated by using the DCI subsequently.

[0034] In addition, a $\min\{\}$ function in the formula means that a value of a parameter on the left of "=" is the smaller one of two values included in the \min function.

[0035] In a possible design, after the quantities of REs that are used to send the parts included in the UCI are obtained, the first code rate and the modulation order obtained through table lookup may be directly used to send corresponding information to the network device.

[0036] In another possible design, another code rate may be generated first based on the first code rate, that is, the another code rate is obtained through code rate conversion on the first code rate, and then the another code rate, the corresponding quantity of REs, and the modulation order are used to send information about the corresponding part. For example, a second code rate is generated based on the first code rate, or a third code rate is generated based on the first code rate. Then, the first code rate, or the second code rate, or the first code rate and the third code rate, or the second code rate and the third code rate is/are used to send information about the corresponding part in the UCI.

[0037] In a possible design, code rate conversion may be performed according to the following formulas, where γ_{ref} represents the first code rate obtained through table lookup, $\gamma_{\text{CSI-1}}$ represents the second code rate obtained by performing code rate conversion based on the first code rate, and C_T represents the third code rate obtained by performing code rate conversion on the first code rate:

$$35 \quad \gamma_{\text{CSI-1}} = \frac{\gamma_{\text{ref}}}{\beta_{\text{offset}}^{\text{CSI-part1}}},$$

$$40 \quad C_T = \frac{\beta_{\text{offset}}^{\text{CSI-part1}}}{\beta_{\text{offset}}^{\text{CSI-part2}}} \cdot \gamma_{\text{CSI-1}},$$

and

$$45 \quad C_T = \frac{\gamma_{\text{ref}}}{\beta_{\text{offset}}^{\text{CSI-part2}}}.$$

[0038] In a possible design, the second code rate is a code rate used to send the CSI-part1 in the UCI, the third code rate is a threshold code rate, and the threshold code rate restricts a code rate of the CSI-part2 to be not higher than the threshold code rate. If the code rate of the CSI-part2 is higher than the threshold code rate, some information in the CSI-part2 may be dropped based on a priority.

[0039] Performing specific code rate conversion can make code rate determining more flexible, and a code rate obtained through code rate conversion may be used to send the UCI, instead of using the first code rate, obtained through a direct lookup in an MCS table, to send the UCI. This can improve accuracy of scheduling by the network device.

[0040] According to a second aspect, a UCI receiving method is provided. In the method, a network device first sends first downlink control information DCI to a terminal device, where the first DCI is used to schedule an uplink shared channel, and is used to indicate that the uplink shared channel is used to send only UCI; and then, may receive first UCI sent by the terminal device through the uplink shared channel.

[0041] Before sending the first DCI to the terminal device, the network device may determine that the uplink shared channel scheduled for the terminal device is used to send only the UCI, and then generate the first DCI based on the foregoing determining result.

[0042] In the solution, the network device may notify, by using the UCI, the terminal device of an indication that the uplink shared channel scheduled for the terminal device is used to send only the UCI. This can enhance a capability of the network device to control and indicate to the terminal device, so that the terminal device can have a consistent understanding as the network device, thereby improving performance of interaction between the network device and the terminal device.

[0043] In a possible design, the network device may further send second DCI to the terminal device, and when a value of an NDI included in the first DCI is different from a value of an NDI included in the second DCI, an RV is 1 or 2, and an MCS index is 28, 29, 30, 31, or any one of indexes indicating a highest modulation order in an MCS table, indicate that the uplink shared channel is used to send only the UCI. In other words, the network device may indicate UCI-only to the terminal device by using a value combination of the foregoing parameters. The second DCI is a previous DCI received before the first DCI, the second DCI includes a HARQ ID, and the first DCI includes the NDI, the RV, the HARQ ID, and I_{MCS} .

[0044] In a possible design, the first DCI includes the HARQ ID and the MCS index, and the HARQ ID and the MCS index may be used to indicate a first code rate. In other words, the network device may indicate the first code rate to the terminal device by using the HARQ ID and the MCS index. For example, the network device may add the HARQ ID and the MCS index to the first DCI; and the terminal device may obtain the HARQ ID and the MCS index after receiving the first DCI, and then determine the first code rate based on the obtained HARQ ID and MCS index.

[0045] In a possible design, the network device may receive the first UCI sent by the terminal device by using the first code rate, or the network device receives the first UCI sent by the terminal device by using a second code rate, or the network device receives the first UCI sent by the terminal device by using the first code rate and a third code rate, or the network device receives the first UCI sent by the terminal device by using a second code rate and a third code rate, where both the second code rate and the third code rate are determined based on the first code rate.

[0046] In a possible design, the network device indicates the first code rate based on all bits in the HARQ ID and some of all bits in the MCS index. In other words, all the bits in the existing HARQ ID are directly used. In this way, a structure of four bits included in the HARQ ID does not need to be modified.

[0047] In a possible design, some of all the bits in the MCS index include one bit in all the bits in the MCS index. In other words, the network device may indicate the first code rate based on all the bits in the HARQ ID and the one bit in the MCS index. For example, the one bit in the MCS index may be a least significant bit of all the bits in the MCS index, or may be another bit; and the one bit in the MCS index may be placed before or after the four bits in the HARQ ID, so that the one bit in the MCS index can act as a most significant bit or a least significant bit of a finally constructed five bits.

[0048] In a possible design, the network device may further send second DCI to the terminal device, and when a value of an NDI included in the first DCI is different from a value of an NDI included in the second DCI, an RV is 1 or 2, and a HARQ ID is 14 or 15, indicate that the uplink shared channel is used to send only the UCI. In other words, the network device may indicate UCI-only to the terminal device by using a value combination of the foregoing parameters. The second DCI is a previous DCI received before the first DCI, the second DCI includes the HARQ ID, and the first DCI includes the NDI, the RV, and the HARQ ID.

[0049] The method in the second aspect corresponds to the method in the first aspect. Therefore, for the descriptions of the method in the second aspect, refer to the descriptions of the method in the first aspect.

[0050] According to a third aspect, an apparatus is provided. The apparatus may be a terminal device, or may be an apparatus in a terminal device. The apparatus may include a receiving module, a first determining module, and a sending module. The modules may perform corresponding functions performed by the terminal device in any design example in the first aspect.

[0051] Specifically, the receiving module is configured to receive first DCI from a network device, where the first DCI is used to schedule an uplink shared channel.

[0052] The first determining module is configured to determine, based on the first DCI, that the uplink shared channel is used to send only UCI.

[0053] The sending module is configured to send first UCI to the network device through the uplink shared channel.

[0054] According to a fourth aspect, an apparatus is provided. The apparatus may be a network device, or may be an apparatus in a network device. The apparatus may include a sending module and a receiving module. The modules may perform corresponding functions performed by the terminal device in any design example in the second aspect. Specifically, the sending module is configured to send first DCI to the terminal device, where the first DCI is used to schedule an uplink shared channel, and is used to indicate that the uplink shared channel is used to send only UCI. The receiving module is configured to receive first UCI sent by the terminal device through the uplink shared channel.

[0055] According to a fifth aspect, an apparatus is provided. The apparatus includes a processor, configured to implement functions of the terminal device in the method described in the first aspect. The apparatus may further include

a memory, configured to store a program instruction and data. The memory is coupled to the processor. The processor may invoke and execute the program instruction stored in the memory, so as to implement functions of the terminal device in the method described in the first aspect. The apparatus may further include a communications interface, and the communications interface is configured for communication between the apparatus and another apparatus. For example, the another apparatus may be a network device.

[0056] According to a sixth aspect, an apparatus is provided. The apparatus includes a processor, configured to implement functions of the network device in the method described in the second aspect. The apparatus may further include a memory, configured to store a program instruction and data. The memory is coupled to the processor. The processor may invoke and execute the program instruction stored in the memory, so as to implement functions of the network device in the method described in the second aspect. The apparatus may further include a communications interface, and the communications interface is configured for communication between the apparatus and another apparatus. For example, the another apparatus may be a terminal device.

[0057] According to a seventh aspect, a readable storage medium is provided. The readable storage medium includes an instruction, and when run on a computer, the instruction enables the computer to perform the steps included in the method according to any design example in the first aspect.

[0058] According to an eighth aspect, a readable storage medium is provided. The readable storage medium includes an instruction, and when run on a computer, the instruction enables the computer to perform the steps included in the method according to any design example in the second aspect.

[0059] According to a ninth aspect, an apparatus is provided. The apparatus includes at least one processor and a readable storage medium, and when an instruction included in the readable storage medium is executed by the at least one processor, the steps included in the method according to any design example in the first aspect may be performed. The apparatus may include a chip, or may include a chip and another discrete device.

[0060] According to a tenth aspect, an apparatus is provided. The apparatus includes at least one processor and a readable storage medium, and when an instruction included in the readable storage medium is executed by the at least one processor, the steps included in the method according to any design example in the second aspect may be performed.

[0061] The apparatus may include a chip, or may include a chip and another discrete device.

[0062] According to an eleventh aspect, a chip system is provided. The chip system includes a processor, and may further include a memory, so as to implement the method according to the first aspect. The chip system may include a chip, or may include a chip and another discrete device.

[0063] According to a twelfth aspect, a chip system is provided. The chip system includes a processor, and may further include a memory, so as to implement the method according to the second aspect. The chip system may include a chip, or may include a chip and another discrete device.

[0064] According to a thirteenth aspect, a system is provided. The system includes the apparatus according to the third aspect and the apparatus according to the fourth aspect.

[0065] According to a fourteenth aspect, a system is provided. The system includes the apparatus according to the fifth aspect and the apparatus according to the sixth aspect.

[0066] According to a fifteenth aspect, a system is provided. The system includes the apparatus according to the ninth aspect and the apparatus according to the tenth aspect.

[0067] It should be understood that the foregoing general descriptions and the following detailed descriptions are merely illustrative and explanatory, and are not intended to limit this disclosure.

BRIEF DESCRIPTION OF DRAWINGS

[0068]

FIG. 1 is a schematic diagram of a possible application scenario in an embodiment of this application;
 FIG. 2 is a flowchart of an uplink control information sending method according to an embodiment of this application;
 FIG. 3 is a schematic diagram of sending and receiving DCI between a network device and a terminal device by using a same HARQ ID in an embodiment of this application;
 FIG. 4 is a schematic diagram of creating a new MCS index based on a HARQ ID and an MCS index in an embodiment of this application;
 FIG. 5 is a schematic structural diagram of an apparatus according to an embodiment of this application;
 FIG. 6 is a schematic structural diagram of another apparatus according to an embodiment of this application;
 FIG. 7 is a schematic structural diagram of another apparatus according to an embodiment of this application; and
 FIG. 8 is a schematic structural diagram of another apparatus according to an embodiment of this application.

DESCRIPTION OF EMBODIMENTS

[0069] To make the objectives, technical solutions, and advantages of the embodiments of this application clearer, the following clearly and completely describes the technical solutions in the embodiments of this application with reference to the accompanying drawings in the embodiments of this application.

[0070] In the embodiments of this application, "plurality" may represent at least two, for example, may be two, three, or more. This is not limited in the embodiments of this application.

[0071] In addition, the term "and/or" in this specification describes only an association relationship for associated objects and represents that three relationships may exist. For example, A and/or B may represent the following three cases: Only A exists, both A and B exist, and only B exists. In addition, the character "/" in this specification usually indicates an "or" relationship between the associated objects unless otherwise stated.

[0072] Unless otherwise stated, in the embodiments of this application, ordinal numbers such as "first", "second", and "third" are intended to distinguish between a plurality of objects, and not intended to limit a sequence, a time sequence, a priority, or an importance degree of the plurality of the objects.

[0073] In the following, some terms in the embodiments of this application are described, so as to help a person skilled in the art have a better understanding.

1. Terminal device: A terminal device used in the embodiments of this application may also be referred to as a terminal, and may be a device having wireless receiving and sending functions. The terminal device may be deployed on land, including deployed indoors or outdoors, held in hand or mounted in vehicle; may be deployed on the surface of water (for example, in a steamship); or may be deployed in the air (such as on an airplane, a balloon, and a satellite). The terminal device may be user equipment (user equipment, UE). The UE includes a handheld device, a vehicle-mounted device, a wearable device, or a computing device that has a wireless communication function.

For example, the UE may be a mobile phone (mobile phone), a tablet computer, or a computer having wireless receiving and sending functions. Alternatively, the terminal device may be a virtual reality (virtual reality, VR) terminal device, an augmented reality (augmented reality, AR) terminal device, a wireless terminal in industrial control, a wireless terminal in self driving, a wireless terminal in telemedicine, a wireless terminal in a smart grid, a wireless terminal in a smart city (smart city), a wireless terminal in a smart home (smart home), or the like. In the embodiments of this application, an apparatus that implements a function of the terminal may be a terminal, or may be an apparatus that supports the terminal to implement the function, such as a chip, a circuit, or another apparatus. In the embodiments of this application, the technical solutions provided in the embodiments of this application are described by using an example in which the apparatus that implements the function of the terminal device is a terminal device.

2. Network device: A network device used in the embodiments of this application includes a base station (base station, BS), and may be a device that is deployed in a radio access network and that can perform wireless communication with a terminal. The base station may be in a plurality of forms, for example, a macro base station, a micro base station, a relay station, and an access point. For example, the base station used in the embodiments of this application may be a gNB (gNB) in a 5th generation mobile communication (the 5th generation, 5G) new radio (new radio, NR) system, a base station (for example, an eNB) in long term evolution (long term evolution, LTE), or a base station in an LTE advanced (LTE-advanced, LTE-A) system. The gNB in the NR system may also be referred to as a transmission reception point (transmission reception point, TRP). In the embodiments of this application, an apparatus that implements a function of the network device may be a network device, or may be an apparatus that supports the network device to implement the function, such as a chip, a circuit, or another apparatus. In the embodiments of this application, the technical solutions provided in the embodiments of this application are described by using an example in which the apparatus that implements the function of the network device is a network device.

3. Uplink shared channel resource: An uplink shared channel resource, for example, a PUSCH resource, may be scheduled by a network device to a terminal device, and the terminal device may send data and/or control information by using the uplink shared channel resource.

[0074] The following briefly describes the technical background of the embodiments of this application.

[0075] In a current communications system, uplink control information (uplink control information, UCI) sent by a terminal device may be sent to a network device through a physical uplink control channel (physical uplink control channel, PUCCH), or may be sent to a network device through a PUSCH. Generally, the PUCCH has higher reliability, but a capacity of information that can be carried on the PUCCH is less than that of the PUSCH. Therefore, some UCI with a relatively large payload (payload) is usually sent to the network device through the PUSCH. For example, channel state information (channel state information, CSI), as a type of UCI with a relatively large payload size, is sent to the network device through the PUSCH in some cases.

[0076] The sending, by the terminal device, the UCI to the network device through the PUSCH includes two cases: (1) UL-SCH data and the UCI are sent together; and (2) UL-SCH data is not included, but only the UCI is sent. In the

embodiments of this application, the case in which only the UCI is sent, but the UL-SCH data is not sent is referred to as UCI-only or a UCI-only PUSCH. The "UCI-only PUSCH" means that the PUSCH is a channel used to send only the UCI. In practice, the terminal device currently cannot determine whether to send the UL-SCH data and the UCI together as in the case (1) or send only the UCI as in the case (2).

5 [0077] In view of the foregoing descriptions, the embodiments of this application provide an uplink control information sending method. In the method, the terminal device may receive first downlink control information (downlink control information, DCI) from the network device; determine, based on the received first DCI, that an uplink shared channel scheduled by using the first DCI is used to send only the UCI; and send first UCI to the network device through the uplink shared channel scheduled by using the first DCI. In other words, the network device may indicate to the terminal device 10 by using the DCI, so that the terminal device can determine, based on the indication of the network device, whether to send only the UCI to the network device. To be specific, the terminal device may determine, based on a DCI indication of the network device, whether the uplink shared channel is UCI-only; and when the uplink shared channel is UCI-only, send the UCI to the network device through the uplink shared channel scheduled by using the DCI.

15 [0078] The technical solutions in the embodiments of this application may be applied to various communications systems, for example, may be applied to an NR system, an LTE system, or an LTE-A system.

20 [0079] In addition, the communications system to which the technical solutions in the embodiments of this application are applied may also be applicable to a future-proofed communications technology. The system described in the technical solutions in the embodiments of this application is intended to more clearly describe the technical solutions in the embodiments of this application, and does not constitute any limitation on the technical solutions provided in the 25 embodiments of this application. A person of ordinary skill in the art may know that, with evolution of a network architecture, the technical solutions provided in the embodiments of this application are also applicable to a similar technical problem.

30 [0080] Next, an application scenario of the embodiments of this application is briefly described.

35 [0081] FIG. 1 is a schematic diagram of a possible application scenario according to an embodiment of this application. A network device and a terminal device are included. Functions of the network device and the terminal device have been described above, and details are not described herein again. The application scenario shown in FIG. 1 may be an application scenario in an NR system, an application scenario in an LTE system, or the like. For example, the application scenario shown in FIG. 1 is the application scenario in the NR system. In this case, the network device may be a gNB in the NR system, and the terminal device may be a terminal device in the NR system.

40 [0082] In the application scenario shown in FIG. 1, the network device may schedule a resource used by the terminal device, for example, allocate an uplink shared channel resource (for example, a PUSCH resource) for the terminal device. After allocating the uplink shared channel resource for the terminal device, the network device may notify the terminal device of the allocated uplink shared channel resource by using DCI. After receiving the DCI, the terminal device may learn of the uplink shared channel resource allocated by the network device, and then transmit information by using the allocated uplink shared channel resource, for example, send UL-SCH data and/or UCI to the network device by 45 using the allocated uplink shared channel resource.

45 [0083] It should be noted that, the scenario shown in FIG. 1 should not constitute any limitation on the application scenario of this embodiment of this application. In actual application, a plurality of network devices and a plurality of terminal devices may be included. For example, one terminal device may transmit data to only one network device, or may transmit data to a plurality of network devices; alternatively, one network device may transmit data to one terminal device, or may transmit data to a plurality of terminal devices. This is not specifically limited in this embodiment of this application.

50 [0084] FIG. 2 is a flowchart of an uplink control information sending method according to an embodiment of this application. In the following descriptions, that the method is applied to the scenario shown in FIG. 1 is used as an example. A procedure of the method is described as follows.

55 [0085] Step 21: A network device determines that an uplink shared channel scheduled for a terminal device is used to send only UCI.

[0086] First, for a terminal device, the network device may schedule a resource for the terminal device, for example, determine that the uplink shared channel scheduled for the terminal device is a channel used to send only the UCI, such as the foregoing UCI-only PUSCH.

50 [0087] Step 22: The network device sends first DCI to the terminal device, and the terminal device receives the first DCI from the network device.

55 [0088] The network device may send DCI to the terminal device through a physical downlink control channel (physical downlink control channel, PDCCH). For example, the DCI is referred to as the first DCI, and the first DCI may include resource allocation information and other control information. Because the DCI includes the resource allocation information, the uplink shared channel scheduled by the network device may be indicated by using the DCI. In other words, the DCI may be used to schedule the uplink shared channel.

[0089] In this embodiment of this application, if the network device needs to schedule the terminal device to perform transmission by using UCI-only, the terminal device may be scheduled by using the DCI. Specifically, the network device

may first determine that the uplink shared channel scheduled for the terminal device is the channel used to send only the UCI; then, the network device generates the first DCI based on a determining result; and finally, the network device sends the first DCI to the terminal device, and the terminal device receives the first DCI.

[0090] In this embodiment of this application, the network device determines whether the uplink shared channel scheduled by using the DCI is UCI-only, and the network device may notify the terminal device. Specifically, the network device notifies the terminal device by using the DCI. The DCI not only can be used to schedule the uplink shared channel, but also can be used to indicate whether the uplink shared channel scheduled by using the DCI is UCI-only. Therefore, to enable the terminal device to clearly know an UCI-only indication of the network device, the network device may send, to the terminal device, the DCI (for example, the first DCI) including the indication, thereby enhancing an interactive understanding between the network device and the terminal device.

[0091] In a specific implementation process, to indicate UCI-only by using the DCI, the network device may add indication information to the DCI when generating the DCI, where the indication information is used to indicate UCI-only. For ease of description, the indication information that is carried in the DCI and that is used to indicate UCI-only is referred to as UCI-only indication information. In other words, UCI-only may be determined by directly using the existing DCI and adding the UCI-only indication information to the DCI.

[0092] Step 23: The terminal device determines that the uplink shared channel scheduled by using the first DCI is used to send only the UCI.

[0093] Further, after receiving the first DCI sent by the network device, the terminal device may parse the first DCI to obtain the UCI-only indication information carried in the first DCI, and then determine, based on the UCI-only indication information, whether the uplink shared channel scheduled by using the first DCI is the channel used to send only the UCI. In other words, the terminal device may directly determine, based on the DCI sent by the network device, a type of information that is sent through the uplink shared channel scheduled by using the DCI. A possible result is that the terminal device determines, based on the DCI sent by the network device, that the uplink shared channel scheduled by using the DCI is the channel used to send only the UCI, thereby ensuring a consistent understanding between the network device and the terminal device, and enhancing capabilities of the network device for scheduling and controlling the terminal device.

[0094] It can be learned that, this embodiment of this application provides a manner in which the terminal device determines whether the uplink shared channel scheduled by the network device is used to send only the UCI, so as to enhance a function of the network device for indicating to the terminal device, and improve interaction performance of the network device and the terminal device. Moreover, the UCI-only determining manner provided in this embodiment of this application is a simple manner provided based on existing control information (that is, the DCI), and directly uses an existing signaling mode without increasing additional overheads, thereby helping save transmission resources.

[0095] Step 24: The terminal device sends first UCI to the network device through the uplink shared channel scheduled by using the first DCI, and the network device receives the first UCI on the uplink shared channel.

[0096] Further, after determining that the uplink shared channel scheduled by using the first DCI is the channel used to send only the UCI, the terminal device may send the UCI to the network device through the uplink shared channel scheduled by using the first DCI. For example, the UCI sent by the terminal device is referred to as the first UCI, and a corresponding type of information is transmitted by using the indication of the network device. This achieves a consistent understanding between the network device and the terminal device, and also enhances control of the terminal device by the network device.

[0097] In this embodiment of this application, the manner in which the network device indicates, to the terminal device by using the DCI, whether the scheduled uplink shared channel is UCI-only includes but is not limited to two methods. In other words, the terminal device may determine the indication of the network device according to the following two methods. For ease of understanding by a person skilled in the art, the following describes the two methods. (1) A first determining method is to directly explicitly indicate UCI-only.

[0098] The network device may add a bit field to the existing DCI, to carry the indication information used to indicate that the uplink shared channel scheduled by using the DCI is UCI-only. For example, one extra bit may be added to carry the UCI-only indication information, the newly added bit field may be placed at a specific location based on a DCI format, in other words, the existing DCI format may be modified, and the newly added bit field is used to directly indicate UCI-only. After receiving the first DCI from the network device, the terminal device may obtain the UCI-only indication information from the bit field at the specific location in the first DCI, and then determine, based on the obtained UCI-only indication information, whether the uplink shared channel scheduled by using the first DCI is UCI-only. For example, when the foregoing one bit is 1, it indicates that the uplink shared channel is UCI-only; or when the foregoing one bit is 0, it indicates that the uplink shared channel is not UCI-only. Certainly, a correspondence between a value of the bit and indication content is not limited in this embodiment of this application.

[0099] In this embodiment of this application, the extra bit added in the DCI is used to explicitly indicate UCI-only, and the terminal device can directly, easily, and quickly obtain the corresponding UCI-only indication information based on the bit field at the specific location in the DCI, without performing additional calculation and other processes. (2) A second

determining method is to implicitly indicate UCI-only by using at least two parameters originally included in the DCI.

[0100] Currently, the DCI has a plurality of formats (format), such as a format 0, a format 0-0, a format 0-1, a format 1, a format 1A, and a format 1D. DCI corresponding to different DCI formats may include different information content. For example, DCI corresponding to a format includes information such as a hybrid automatic repeat request (hybrid automatic repeat request, HARQ) process number (ID), a new data indicator (new data indicator, NDI), a redundancy version (redundancy version, RV), and a modulation and coding scheme (modulation and coding scheme, MCS) index (index), where the MCS index may be represented by, for example, I_{MCS} .

[0101] It can be learned that, the DCI originally includes some parameters. For example, as described above, the DCI usually includes parameters such as the NDI, the RV, the HARQ ID, and I_{MCS} . Therefore, in the second determining method, the network device may directly use some parameters originally included in the DCI, to implicitly indicate UCI-only. Further, after receiving the DCI, the terminal device may determine, based on the indication of the network device, whether the uplink shared channel is UCI-only. When the at least two parameters included in UCI-only are used to implicitly indicate UCI-only, information corresponding to the parameters used to implicitly indicate UCI-only may be understood as the foregoing UCI-only indication information. In this way, a modification to the DCI is relatively small.

[0102] In other words, in an existing information composition structure of the DCI, a value of a defined bit field (the defined bit field is used to carry information corresponding to a defined parameter) may be fully used to implement a new function of indicating UCI-only. Through reuse of the bit field that is in the DCI and that already carries related information, information use efficiency of the DCI can also be increased, or equivalently, signaling overheads are reduced to some extent, thereby saving resources.

[0103] In this embodiment of this application, the at least two parameters that are currently available in the DCI are used to indicate whether the uplink shared channel is UCI-only. Specifically, a value combination of two parameters in the DCI is an impossible combination in currently existing function combinations, that is, the value combination of the two parameters used to implicitly indicate UCI-only is not an existing function combination. For example, when the value combination of the two parameters represents two conflicting indications related to new data transmission and data retransmission in the prior art, it may be determined that the uplink shared channel scheduled by using the DCI is UCI-only. For example, a value of one parameter in the DCI indicates new data transmission, and a value of the other parameter in the DCI indicates data retransmission. The conflicting indications: one indicating data retransmission and the other indicating new data transmission, do not exist in a current normal case. Therefore, in this embodiment of this application, a conflicting indication combination that does not exist in the normal case is used to indicate UCI-only. However, for the terminal device, if determining that the DCI carries the two conflicting indications, the terminal device considers that the network device neither indicates data retransmission nor indicates new data transmission actually, but indicates UCI-only. That is, a function combination that does not exist currently is used to implicitly indicate UCI-only.

[0104] In addition, it should be noted that, in this embodiment of this application, for example, when the currently impossible combination that includes the two conflicting indications, new data transmission and data retransmission, is used to indicate UCI-only, the new data transmission and data retransmission herein are not used to actually indicate new data transmission and data retransmission, in other words, the terminal device does not transmit new data or retransmit data based on the indications. In this embodiment of this application, the currently impossible indication combination is merely used to implicitly indicate UCI-only, that is, a different combination of parameters is used to implement a new indication function.

[0105] In the second determining method, the DCI may include a plurality of parameters. For ease of understanding by a person skilled in the art, the following lists several parameters for description.

[0106] In a manner 1, an NDI and an RV are used to determine whether the uplink shared channel is UCI-only.

[0107] The NDI and the RV are parameters indicated by using two bit fields in the DCI. The NDI fixedly occupies one bit. whether the network device indicates new data transmission or data retransmission may be determined based on whether NDI flipping occurs. For example, compared with previous DCI, if NDI flipping occurs, it indicates new data transmission; or if no NDI flipping occurs, it indicates data retransmission. The RV usually occupies two bits, and different values of the RV represent different meanings. For example, when a value of the RV is 1 or 2, it indicates data retransmission.

[0108] In the prior art, NDI flipping may be used to indicate new data transmission, and the value 1 or 2 of the RV may be used to indicate data retransmission. Therefore, in the manner 1, the network device uses a currently impossible combination that includes the two conflicting indications, new data transmission and data retransmission, to indicate UCI-only, and the terminal device may determine UCI-only based on the indication combination.

[0109] To be specific, conditions that are provided in the manner 1 and that are used to determine UCI-only are as follows:

- 55 (1) NDI flipping occurs; and
- (2) RV = 1 or RV = 2.

[0110] Based on the foregoing descriptions, to determine, based on the NDI, whether new data is transmitted, whether NDI flipping occurs needs to be determined first. To determine whether NDI flipping occurs, values of NDIs in two pieces of DCI are needed. One piece of DCI is the currently received DCI, that is, the first DCI; and the other piece of DCI is previous DCI that carries the same HARQ ID as the first DCI and that is closest to the first DCI in time.

5 [0111] For ease of description, the other piece of DCI is referred to as second DCI in this embodiment of this application. Because the second DCI is a previous DCI received before the first DCI, the second DCI may be received by the terminal device before the first DCI is received.

10 [0112] For example, the network device sets a value of an NDI in the second DCI to 1. If expecting to indicate UCI-only by using the first DCI, the network device may set a value of an NDI in the first DCI to 0, and set a value of an RV in the first DCI to 1 or 2. Further, after receiving the first DCI, the terminal device may compare the NDI carried in the first DCI with the NDI carried in the second DCI, to determine whether NDI flipping occurs. If determining that NDI flipping occurs, the terminal device may determine whether the value of the RV in the first DCI is 1 or 2. Alternatively, the terminal device may simultaneously perform two processes of determining whether NDI flipping occurs and determining whether the value of the RV in the first DCI is 1 or 2. Alternatively, the terminal device may first determine whether the value of the RV in the first DCI is 1 or 2, and then determine whether NDI flipping occurs. In conclusion, when the two conditions are met, the terminal device may determine that the uplink shared channel scheduled by using the first DCI is used to send only the UCI.

15 [0113] In a manner 2, an NDI and I_{MCS} are used to determine whether the uplink shared channel is UCI-only.

20 [0114] I_{MCS} is an MCS index in an MCS table. The MCS table includes a plurality of MCS indexes, and each MCS index corresponds to a respective code rate (code rate), a modulation order (modulation order), spectrum efficiency, and the like, where the modulation order is represented by, for example, Q_m .

25 [0115] There are already a plurality of MCS tables currently. For example, Table 1, Table 2, and Table 3 are three common MCS tables currently. A highest modulation order supported in MCS tables shown in Table 1 and Table 3 is 6, and a highest modulation order supported in an MCS table shown in Table 2 is 8.

30 [0116] Moreover, terminal devices may correspond to respective MCS tables depending on different highest modulation orders that the terminal devices can support and whether discrete Fourier transform (discrete Fourier transformation, DFT) precoding is applied to the uplink shared channel. In other words, the terminal devices may match the respective MCS tables based on different capabilities of the terminal devices.

Table 1

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
0	2	120	0.2344
1	2	157	0.3066
2	2	193	0.3770
3	2	251	0.4902
4	2	308	0.6016
5	2	379	0.7402
6	2	449	0.8770
7	2	526	1.0273
8	2	602	1.1758
9	2	679	1.3262
10	4	340	1.3281
11	4	378	1.4766
12	4	434	1.6953
13	4	490	1.9141
14	4	553	2.1602
15	4	616	2.4063
16	4	658	2.5703
17	6	438	2.5664

(continued)

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
5	18	6	466	2.7305
10	19	6	517	3.0293
15	20	6	567	3.3223
20	21	6	616	3.6094
25	22	6	666	3.9023
30	23	6	719	4.2129
35	24	6	772	4.5234
40	25	6	822	4.8164
45	26	6	873	5.1152
50	27	6	910	5.3320
55	28	6	948	5.5547
25	29	2	Reserved	
30	30	4	Reserved	
35	31	6	Reserved	

Table 2

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
30	0	2	120	0.2344
35	1	2	193	0.3770
40	2	2	308	0.6016
45	3	2	449	0.8770
50	4	2	602	1.1758
55	5	4	378	1.4766
25	6	4	434	1.6953
30	7	4	490	1.9141
35	8	4	553	2.1602
40	9	4	616	2.4063
45	10	4	658	2.5703
50	11	6	466	2.7305
55	12	6	517	3.0293
25	13	6	567	3.3223
30	14	6	616	3.6094
35	15	6	666	3.9023
40	16	6	719	4.2129
45	17	6	772	4.5234
50	18	6	822	4.8164
55	19	6	873	5.1152

(continued)

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
5	20	8	682.5	5.3320
10	21	8	711	5.5547
15	22	8	754	5.8906
20	23	8	797	6.2266
	24	8	841	6.5703
	25	8	885	6.9141
	26	8	916.5	7.1602
	27	8	948	7.4063
	28	2	Reserved	
	29	4	Reserved	
	30	6	Reserved	
	31	8	Reserved	

Table 3

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
25	0	q	$240/q$	0.2344
30	1	q	$314/q$	0.3066
35	2	2	193	0.3770
40	3	2	251	0.4902
45	4	2	308	0.6016
50	5	2	379	0.7402
55	6	2	449	0.8770
	7	2	526	1.0273
	8	2	602	1.1758
	9	2	679	1.3262
	10	4	340	1.3281
	11	4	378	1.4766
	12	4	434	1.6953
	13	4	490	1.9141
	14	4	553	2.1602
	15	4	616	2.4063
	16	4	658	2.5703
	17	6	466	2.7305
	18	6	517	3.0293
	19	6	567	3.3223
	20	6	616	3.6094
	21	6	666	3.9023

(continued)

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
22	6	719	4.2129
23	6	772	4.5234
24	6	822	4.8164
25	6	873	5.1152
26	6	910	5.3320
27	6	948	5.5547
28	1	Reserved	
29	2	Reserved	
30	4	Reserved	
31	6	Reserved	

20 [0117] Similar to the manner 1, whether the NDI in the first DCI indicates new data transmission is determined by determining whether flipping occurs on the NDI in the first DCI compared with the NDI in the second DCI. When it is determined that NDI flipping occurs, it indicates that the first DCI indicates new data transmission.

25 [0118] Further, when a value of l_{MCS} is a predetermined value, it may indicate that the network device expects to use l_{MCS} to indicate data retransmission, so that the data retransmission indication and the new data transmission indication that is represented through NDI flipping form a function combination that does not exist currently and that includes the conflicting indications. Specifically, two conditions may be set: "the value of l_{MCS} is any one of index values indicating a highest modulation order in an MCS table" and "the value of l_{MCS} is an index value in an MCS table that is greater than a predetermined value". When at least one of the two conditions is met, it may be considered that the value of l_{MCS} is used to indicate data retransmission, so that the data retransmission indication and the new data transmission indication represented through NDI flipping form the two conflicting indications. In this case, UCI-only can be determined.

30 [0119] For ease of understanding by a person skilled in the art, the following lists several cases for description.

35 [0120] (a) $l_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\}$. To be specific, the value of l_{MCS} belongs to a set including the index values indicating the highest modulation order in the MCS table. It should be noted that, when different MCS tables are used, index values indicating a highest modulation order in the MCS tables may be different.

40 [0121] For example, in the MCS table shown in Table 1, the highest modulation order in the MCS table is 6, and a set of all index values corresponding to the modulation order 6 is {17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 31}.

45 [0122] For example, in the MCS table shown in Table 2, the highest modulation order in the MCS table is 8, and a set of index values corresponding to the modulation order 8 is {20, 21, 22, 23, 24, 25, 26, 27, 31}.

50 [0123] For example, in the MCS table shown in Table 3, the highest modulation order in the MCS table is 6, and a set of all index values corresponding to the modulation order 6 is {17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 31}.

55 [0124] For any MCS table, provided that the value of l_{MCS} belongs to a set of index values corresponding to a highest modulation order in the MCS table, it may be considered that l_{MCS} meets a condition of indicating data retransmission. Using the MCS table in Table 3 as an example, when the value of l_{MCS} in the first DCI is 27, a modulation order corresponding to l_{MCS} is 6, a highest modulation order. In this case, it may be considered that l_{MCS} with the value of 27 is used to indicate data retransmission, and further, UCI-only may be determined. For another example, when the value of l_{MCS} in the first DCI is 6, a modulation order corresponding to l_{MCS} is 2, not the highest modulation order 6. Therefore, it may be considered that l_{MCS} with the value of 6 does not indicate data retransmission, and in this case, it may be determined that the uplink shared channel is not UCI-only.

50 [0125] In a normal HARQ case, new data transmission is performed through lower-order modulation, and highest-order modulation is usually not used during retransmission or a plurality of retransmissions. Therefore, the network device fully uses a non-regular case based on the principle, that is, uses an index value corresponding to highest-order modulation to indicate data retransmission, so as to form an indication conflicting with new data transmission represented through NDI flipping. In this way, the two conflicting indications are used to indicate UCI-only to the terminal device. (b) $l_{MCS} \in \{28, 29, 30, 31\}$ or $l_{MCS} \in \{29, 30, 31\}$.

55 [0126] Each of the current MCS tables includes 31 index values, and index values 28, 29, 30, and 31 are several larger values in the MCS tables. Moreover, code rates corresponding to 28, 29, 30, and 31 in Table 2 and Table 3 and code rates corresponding to 29, 30, and 31 in Table 1 are "reserved", and "reserved" indicates that the code rates are

reserved. In other words, corresponding code rates are not set for the index values 28, 29, 30, and 31, or the index values 29, 30, and 31 in the current MCS tables. Because the code rates are not set, currently, in a normal case, the network device usually does not use the index values to indicate new data transmission. Based on this, the network device uses the index values for which the corresponding code rates are not set currently, to indicate data retransmission, so that the data retransmission indication and the new data transmission indication represented through NDI flipping form two conflicting indications. In this manner, UCI-only is determined. (c) $I_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\} \cup \{28, 29, 30, 31\}$.

[0127] The case c is a combination of the two cases: a and b. Descriptions are not repeated herein. However, it should be noted that, index values indicating a highest modulation order in an MCS table may overlap with 28, 29, 30, and 31. Using the MCS table shown in Table 2 as an example, a set of all index values indicating the highest modulation order in the MCS table shown in Table 2 is $\{20, 21, 22, 23, 24, 25, 26, 27, 31\}$, and 31 in the set is an element that overlaps with that in a set $\{28, 29, 30, 31\}$ including large index values. Because there is "U" relationship between the two sets, 31 is used only once finally, that is, a final set after "U" is $\{20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31\}$. According to the foregoing descriptions, in the manner 2, conditions that are used to determine UCI-only are as follows:

(1) NDI flipping occurs; and
 (2) $I_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\}; \text{ or } I_{MCS} \in \{28, 29, 30, 31\} \text{ or } I_{MCS} \in \{29, 30, 31\}; \text{ or } I_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\} \cup \{28, 29, 30, 31\}$.

[0128] In addition, in the UCI-only determining manners described above, there may be a PDCCH miss-detection, and the PDCCH miss-detection may result in wrong determining of UCI-only. For example, FIG. 3 is a schematic diagram of sending and receiving, from left to right in chronological order, DCI between the network device and the terminal device by using a same HARQ ID.

[0129] First, the network device uses a DCI₁ to indicate a PUSCH used to transmit new data, and RV = 0. After the terminal device sends data of the PUSCH based on an indication of the DCI₁, the network device fails to decode the received data, where failing to decode the received data means that a cyclic redundancy check (cyclic redundancy check, CRC) check fails. In this case, the network device uses a DCI₂ to indicate that retransmission is required, and RV = 2. Afterwards, the network device fails to decode the received data again, and uses a DCI₃ to indicate that retransmission is required, and RV = 3. In this case, decoding succeeds.

[0130] Then, the network device uses a DCI₄ to indicate next data that needs to be newly transmitted (NDI flipping), but the DCI₄ is lost.

[0131] Finally, the network device uses a DCI₅ to indicate a UCI-only PUSCH, that is, sets a value different from a value of an NDI in the DCI₄ for an NDI in the DCI₅, and sets RV = 1. Because the value of the NDI in the DCI₄ is 1, the value of the NDI in the DCI₅ is set to 0. In other words, the network device expects to indicate UCI-only through NDI flipping and RV = 1. However, the DCI₄ is lost, and the terminal device does not receive the DCI₄. Therefore, when the DCI₅ is received, the DCI₅ is compared with the previously received DCI₃, and it is found that the NDIs are both 0, that is, no NDI flipping occurs. In this case, the DCI₅ is wrongly considered to be used to indicate retransmission of previous PUSCH data.

[0132] It can be learned that, the terminal device may wrongly determine UCI-only due to a loss of the DCI in a transmission process. Specifically, NDI flipping actually occurs, but it is wrongly considered that no NDI flipping occurs. In view of this, in this embodiment of this application, another determining condition of determining UCI-only is further added. Adding a determining condition can reduce impact of wrong determining on a final determining result, thereby improving determining accuracy and avoiding a case in which UCI-only cannot be indicated due to wrong determining. For ease of understanding by a person skilled in the art, the following uses a manner 3 and a manner 4 as examples to describe a determining manner in which a new determining condition is added.

[0133] In the manner 3, an NDI, an RV, and I_{MCS} are used to determine whether the uplink shared channel is UCI-only.

[0134] For example, in the foregoing manner 1, because NDI flipping may be wrongly determined as shown in FIG. 3, the indication of the NDI may be ignored in this embodiment of this application. Then, I_{MCS} is used as a newly added determining condition to determine whether the uplink shared channel is UCI-only. To be specific, the indication of the NDI is ignored, and on the premise that the value of the RV is 1 or 2, I_{MCS} described in the manner 2 and the RV form a value combination that is impossible in the prior art, so as to ensure UCI-only determining accuracy when the NDI does not work due to wrong determining.

[0135] In a possible implementation, in the manner 3, conditions used to determine UCI-only are as follows:

(1) NDI flipping occurs;
 (2) RV = 1 or RV = 2; and
 (3) $I_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\}; \text{ or } I_{MCS} \in \{28, 29, 30, 31\} \text{ or } I_{MCS} \in \{29, 30, 31\}; \text{ or } I_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\} \cup \{28, 29, 30, 31\}$.

[0136] In another possible implementation, in the manner 3, conditions used to determine UCI-only are as follows:

- (1) no NDI flipping occurs;
- (2) RV = 1 or RV = 2; and
- (3) $I_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\};$ or $I_{MCS} \in \{28, 29, 30, 31\}$ or $I_{MCS} \in \{29, 30, 31\};$ or $I_{MCS} \in \{\text{index values indicating a highest modulation order in an MCS table}\} \cup \{28, 29, 30, 31\}.$

[0137] In the manner 4, an NDI, an RV, and a HARQ ID are used to determine whether the uplink shared channel is UCI-only.

[0138] Similar to the manner 3, when wrong determining shown in FIG. 3 occurs, the indication of the NDI may be ignored, and the HARQ ID is used as a newly added determining condition to determine whether the uplink shared channel is UCI-only. Specifically, when the indication of the NDI is ignored, and the value of the RV is 1 or 2, data retransmission is indicated in a normal case. Because a HARQ ID having a relatively large value such as 15 or 14 is usually not used in the normal case, a currently impossible parameter combination in which the RV indicates data retransmission and the HARQ ID is 15 or 14 is used to indicate UCI-only. This can ensure UCI-only determining accuracy when the NDI cannot work due to wrong determining. Moreover, because the HARQ ID of 14 or 15 is rarely used in the normal case, wrong determining described in FIG. 3 may not affect normal running of a HARQ.

[0139] In other words, in the manner 4, conditions used to determine UCI-only are as follows:

- (1) NDI flipping occurs;
- (2) RV = 1 or RV = 2; and
- (3) HARQ ID = 14 or HARQ ID = 15.

[0140] The foregoing descriptions are merely examples. The manner used for determining UCI-only based on the existing parameters included in the DCI in this embodiment of this application includes but is not limited to those described above. In a specific implementation process, another manner may be obtained through summarization, variation, or extension based on the several manners described above. Any determining manner based on the existing parameters in the DCI and a function combination that is not included in the current function combinations shall fall within the protection scope of this application.

[0141] As described above, after determining the UCI-only PUSCH, the terminal device may send the UCI to the network device on the PUSCH. The UCI may include several parts of information, for example, include three parts: CSI-part1, CSI-part2, and a HARQ-acknowledgement (acknowledgement, ACK). Each part in the UCI can be sent to the network device only when a quantity of REs and a corresponding code rate are known in advance. For the foregoing parts in the UCI, a payload size size of the CSI-part2 is affected by specific values of some parameters in the CSI-part1.

[0142] For example, when a rank in a rank indication (rank indication, RI) in the CSI-part1 is equal to 1, the payload size of the CSI-part2 is relatively small; or if an RI in the CSI-part1 indicates that rank = 2, the payload size of the CSI-part2 is relatively large. Because the network device cannot learn of specific sizes of parts in the CSI-part1, that is, cannot learn of payload sizes of the parts, the network device cannot obtain a total payload size size of the CSI in advance, and cannot schedule, based on the total payload size, a PUSCH resource adapted to the total payload size, to send the CSI.

[0143] Because the parts have different payload sizes and different importance degrees, respective code rates and modulation orders are needed to send the parts in the UCI.

[0144] The network device may indicate the allocated PUSCH resource to user equipment in the DCI sent to the user equipment. After receiving and parsing the DCI, the UE can know the PUSCH resource allocated by the network device, that is, can know a total quantity of REs that are used for UCI transmission. Further, because the UCI includes a plurality of parts, such as the HARQ ACK, the CSI-part1, and the CSI-part2, the user equipment needs to allocate, to the parts in the UCI according to a specific rule, the PUSCH resource allocated by the network device. Therefore, determining quantities of REs that are allocated to the parts in the UCI is also a mandatory step before the UCI is sent.

[0145] In other words, sending the UCI may be understood as sending the parts of information that are included in the UCI. In a possible implementation, the three parts: the CSI-part1, the CSI-part2, and the HARQ ACK included in the UCI are sent. Moreover, to send any part in the UCI, a quantity of REs that are used to send each part and a corresponding code rate need to be determined in advance. With respect to the quantity of REs that are used to send each part, because the DCI sent by the network device already includes the total quantity of REs that are used to send the UCI, if quantities of REs that are used to send two of the three parts are known, a quantity of REs that are used to send a third part may be known naturally.

[0146] Currently, a quantity Q_{ACK} of REs that are allocated to the HARQ ACK may be calculated according to a

formula (1), a quantity $Q'_{\text{CSI-1}}$ of REs that are allocated to the CSI-part1 may be calculated according to a formula (2), and a code rate $\gamma_{\text{CSI-1}}$ used to send the CSI-part1 may be calculated according to a formula (3):

5

10

$$Q'_{\text{ACK}} = \min \left\{ \left\lceil \frac{(O_{\text{ACK}} + L_{\text{ACK}}) \cdot \beta_{\text{offset}}^{\text{ACK}} \cdot \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l)}{(O_{\text{CSI-1}} + L_{\text{CSI-1}}) \beta_{\text{offset}}^{\text{CSI-part1}}} \right\rceil, \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l) \right\} \quad \text{formula (1),}$$

15

20

$$Q'_{\text{CSI-1}} = \min \left\{ \left\lceil \frac{(O_{\text{CSI-1}} + L_{\text{CSI-1}}) \cdot \beta_{\text{offset}}^{\text{CSI-part1}} \cdot \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l)}{(O_{\text{CSI-2-ref}} + L_{\text{CSI-2-ref}}) \beta_{\text{offset}}^{\text{CSI-part2}}} \right\rceil, \sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l) - Q'_{\text{ACK}} \right\} \quad \text{formula (2),}$$

and

25

$$\gamma_{\text{CSI-1}} = \frac{O_{\text{CSI-1}} + L_{\text{CSI-1}}}{Q'_{\text{CSI-1}} \cdot Q_m} \quad \text{formula (3),}$$

30

$$\sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l)$$

where $\sum_{l=0}^{N_{\text{symb,all}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l)$ represents a quantity of all REs for the PUSCH, that is, the total quantity of REs that are allocated by the network device to the PUSCH; $O_{\text{CSI-2-ref}}$ represents a reference payload size of the CSI-part2, and $L_{\text{CSI-2-ref}}$ represents a corresponding quantity of CRC bits; and $O_{\text{CSI-1}}$ represents the payload size of the CSI-part1, and $L_{\text{CSI-1}}$ represents a corresponding quantity of CRC bits. $O_{\text{CSI-1}} + L_{\text{CSI-1}}$ may be understood as a total payload size of

35

the CSI-part1, and $O_{\text{CSI-2-ref}} + L_{\text{CSI-2-ref}}$ may be understood as a total reference payload size of the CSI-part2. $\beta_{\text{offset}}^{\text{CSI-part1}}$

40

and $\beta_{\text{offset}}^{\text{CSI-part2}}$ represent code rate compensation parameters of the CSI-part1 and the CSI-part2, respectively, and are semi-statically preconfigured by a wireless higher layer of the network device or dynamically indicated by using the DCI subsequently.

45

[0145] In addition, a $\min\{\cdot\}$ function in the formula (2) means that a value of a parameter on the left of " $=$ " is the smaller one of two values included in the \min function. Similarly, \min functions in the following formulas have the same meaning.

50

[0146] In a process of calculating $Q'_{\text{CSI-1}}$ according to the formula (2), the reference payload size $O_{\text{CSI-2-ref}}$ of the CSI-part2 is set to a fixed value, lacking flexibility. For example, a typical value of $O_{\text{CSI-2-ref}}$ is a payload size of the CSI-part2 when rank = 1 or rank = 2. If a payload size (relatively small) of the CSI-part2 when rank = 1 is selected as $O_{\text{CSI-2-ref}}$,

55

it may be learned from the formula (2) that $Q'_{\text{CSI-1}}$ is relatively large, and some or all of the CSI-part2 must be dropped. If a payload size (relatively large) of the CSI-part2 when rank = 2 is selected as $O_{\text{CSI-2-ref}}$, it may be learned from the formula (2) that a quantity of REs that are allocated to the CSI-part1 is relatively small. This results in insufficient protection for the CSI-part1. Especially, if rank = 1 in practice, the payload size of the CSI-part2 is not large, whereas the quantity

$Q'_{\text{CSI-2}}$ of allocated REs (that is, the quantity of REs that are allocated to the CSI-part2) is excessively large. In this

case, protection is excessively large, resulting in a waste.

[0147] In addition, the calculation formula of size $O_{ACK} + L_{ACK}$ of the HARQ-ACK also has the following problem. In the formula (1), if the payload

$$(O_{ACK} + L_{ACK}) \cdot \beta_{\text{offset}}^{\text{ACK}} > (O_{CSI-1} + L_{CSI-1}) \cdot \beta_{\text{offset}}^{\text{CSI-part1}}$$

, for the min {} function in the formula (1) only the second item on the right of the comma is selected, and the first item on the left of the comma cannot work, that is, the calculated

Q'_{ACK} is the total quantity of REs that are allocated to the PUSCH. In other words, all REs allocated to the UCI are allocated to the HARQ-ACK. Obviously, in this case, there is no RE for sending the CSI-part1 and the CSI-part2. This conflicts with an actual case.

[0148] Based on the foregoing analysis, a fixed payload size is currently used to calculate a quantity of REs. The solution is less flexible, and in some cases, there may be no available REs for sending the CSI-part1 and the CSI-part2. Therefore, the current RE calculation manner is not feasible for sending the CSI.

[0149] In view of the foregoing descriptions, a method of obtaining a reference code rate by directly performing a lookup in an MCS table, and then calculating a quantity of REs based on the corresponding obtained code rate is proposed, to resolve the problem of relatively poor flexibility and infeasibility for sending the CSI caused when the fixed payload size is used to calculate the quantity of REs. Specifically, a value of a 4-bit HARQ ID field in the DCI may be used to indicate an MCS index value, and then a corresponding code rate is obtained as a target code rate γ_{CSI-1} of the CSI-part1 through MCS table lookup based on the determined MCS index value. To be specific, the network device indicates γ_{CSI-1} to the UE by using the HARQ ID field in the DCI, and then calculates, according to a formula (4), the quantity of REs that are allocated to the CSI-part1:

$$Q'_{CSI-1} = \min \left\{ \left\lceil \frac{(O_{CSI-1} + L_{CSI-1})}{\gamma_{CSI-1} \cdot Q_m} \right\rceil, \sum_{l=0}^{N_{\text{symbol}}^{\text{PUSCH}}-1} M_{\text{sc}}^{\text{UCI}}(l) - Q'_{ACK} \right\} \text{ formula (4).}$$

[0150] The MCS index in all existing MCS tables includes five bits, and there is an MCS table mismatch when a lookup is performed on an MCS table by using four bits. Therefore, a new MCS table needs to be defined. In other words, the new MCS table needs to be introduced in the foregoing manner, indicating a significant modification to an existing standard. In addition, extra study is required to optimize the new MCS table, making it difficult to complete formulation of a standard on time. Moreover, for product implementation of the network device and the terminal device, the new MCS table needs extra storage space overheads.

[0151] In view of the foregoing descriptions, in this embodiment of this application, after UCI-only is determined, the code rate and the corresponding modulation order may be directly obtained through MCS table lookup. For ease of description, the code rate obtained through MCS table lookup is referred to as a reference code rate or a first code rate in this specification, and is represented by γ_{ref} ; and the modulation order obtained through MCS table lookup is represented by Q_m .

[0152] This embodiment of this application provides the following two specific table lookup manners.

[0153] Table lookup manner 1: In a possible implementation, a lookup may be performed in a currently existing MCS table by directly using I_{MCS} in the DCI. For example, a lookup is performed in any MCS table in Table 1, Table 2, or Table 3 described above. The corresponding code rate and modulation order may be obtained through MCS table lookup based on I_{MCS} . For example, when a value of I_{MCS} is 22, a code rate 666 and a modulation order 6 may be obtained by performing a lookup in the MCS table shown in Table 1. In addition, it should be noted that, the code rate in Table 1 is obtained by multiplying a target code rate by 1024, and therefore, a corresponding code rate found in the MCS table needs to be divided by 1024.

[0154] Table lookup manner 2: In another possible implementation, the foregoing reference code rate may be determined based on all bits indicating the HARQ ID and some of all bits indicating I_{MCS} in this embodiment of this application. Because the existing manner of performing a lookup in the MCS table by directly using the 4-bit HARQ ID results in a significant modification to the existing standard, and the HARQ ID includes four bits and I_{MCS} includes five bits, all the bits in the HARQ ID and some bits in I_{MCS} may be used to create a 5-bit MCS index value that completely conforms to the existing MCS tables. In this way, the existing MCS tables can be directly used, without having to introduce a new table, so as to minimize a modification to the existing standard. For ease of description, in this embodiment of this

application, the index value corresponding to the created five bits is represented by I'_MCS .

[0155] Specifically, all the bits (that is, four bits) in the HARQ ID and one bit in I'_MCS may be used to construct a bit field including five bits, and then, a value of the constructed bit field is used to represent an index value for table lookup, that is, I'_MCS . For example, FIG. 4 is a schematic diagram of constructing, based on the HARQ ID and I'_MCS , a bit field including 5 bits. FIG. 4 shows two methods for constructing the bit field. For either of the two methods, bits marked by slashes are the four bits in the HARQ ID, the remaining one bit is the one bit in I'_MCS . For example, as shown in FIG. 4, the one bit in I'_MCS is a least significant bit in I'_MCS , because directly using the least significant bit in I'_MCS is relatively convenient, and a value of the least significant bit in I'_MCS has relatively small impact on the value of I'_MCS . Optionally, as shown in the construction manner on the left of FIG. 4, the least significant bit in I'_MCS may be directly placed after the four bits in the HARQ ID, that is, the least significant bit in I'_MCS is used as a least significant bit in the newly constructed bit field. Alternatively, as shown in the construction manner on the right of FIG. 4, the least significant bit in I'_MCS may be directly placed before the four bits in the HARQ ID, that is, the least significant bit in I'_MCS is used as a most significant bit in the newly constructed bit field. By using the manner shown in FIG. 4, the five bits can be constructed directly by setting one bit as the least significant bit or the most significant bit on a basis of the four bits in the HARQ ID, and there is a relatively small modification to the existing four bits in the HARQ ID. Alternatively, optionally, the one bit in I'_MCS may be placed at any location among the four bits in the HARQ ID, for example, placed between a least significant bit and a last but one least significant bit of the four bits in the HARQ ID. This is not limited in this embodiment of this application, and setting may be performed based on an actual requirement in a specific implementation process.

[0156] In addition, in the manner described above in which a 5-bit new index is constructed by using the four bits in the HARQ ID and the one bit in I'_MCS , values of the four bits in the HARQ ID and the one bit in I'_MCS are merely reused, and there is no impact on structures and values of the HARQ ID and I'_MCS . For example, values of the original four bits in the HARQ ID are 1001, and values of the five bits in I'_MCS are 11111. It can be seen that the least significant bit in I'_MCS is 1. In this case, according to the manner shown on the left of FIG. 4, the newly constructed five bits are 10011, and a corresponding value of I'_MCS is 19. Because the values of the original four bits in the HARQ ID and the least significant bit in I'_MCS are merely reused, there is no impact on the structures and the values of the HARQ ID and I'_MCS , that is, the HARQ ID may still represent a process 1001 (that is, a code is 9), and I'_MCS may still represent an index value 31.

[0157] Regardless of a table lookup manner used for table lookup, both the reference code rate γ_{ref} and the modulation order Q_m may be obtained through table lookup, and further, quantities of REs that are used to send the parts in the UCI may be calculated according to the following formulas:

$$Q'_{ACK} = \min \left\{ \left\lceil \frac{(O_{ACK} + L_{ACK}) \cdot \beta_{offset}^{ACK}}{\gamma_{ref} \cdot Q_m} \right\rceil, \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) \right\} \quad \text{formula (5),}$$

$$Q'_{CSI-1} = \min \left\{ \left\lceil \frac{(O_{CSI-1} + L_{CSI-1}) \cdot \beta_{offset}^{CSI-part1}}{\gamma_{ref} \cdot Q_m} \right\rceil, \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) - Q'_{ACK} \right\} \quad \text{formula (6),}$$

and

$$Q'_{CSI-2} = \sum_{l=0}^{N_{symb,all}^{PUSCH}-1} M_{sc}^{UCI}(l) - Q'_{CSI-1} - Q'_{ACK} \quad \text{formula (7).}$$

[0158] In addition, a code rate used to send each part may be further obtained according to the following formula:

$$\gamma_{CSI-1} = \frac{\gamma_{ref}}{\beta_{offset}^{CSI-part1}} \quad \text{formula (8).}$$

[0159] In practice, a threshold code rate C_T is set for the CSI-part2. A function of the threshold code rate C_T is to restrict a code rate of the CSI-part2 to be not higher than the threshold. If the code rate of the CSI-part2 is higher than the threshold, some information in the CSI-part2 may be dropped based on a priority, until an actual code rate of the CSI-part2 is not higher than the threshold. Moreover, the threshold code rate C_T may be usually calculated according to a formula (9). In other words, the threshold code rate C_T may be calculated after a code rate γ_{CSI-1} of the CSI-part1

is obtained according to the formula (8):

$$C_T = \frac{\beta_{\text{offset}}^{\text{CSI-part1}}}{\beta_{\text{offset}}^{\text{CSI-part2}}} \cdot \gamma_{\text{CSI-1}} \quad \text{formula (9).}$$

[0160] Because $\gamma_{\text{CSI-1}}$ in the formula (9) may be calculated according to the formula (8), a formula (10) may be further obtained with reference to the formula (8) and the formula (9):

$$C_T = \frac{\gamma_{\text{ref}}}{\beta_{\text{offset}}^{\text{CSI-part2}}} \quad \text{formula (10).}$$

[0161] In this embodiment of this application, the code rate $\gamma_{\text{CSI-1}}$ of the CSI-part1 is obtained after specific code rate conversion is performed on the reference code rate γ_{ref} obtained through MCS table lookup. Therefore, the threshold code rate calculated according to the formula (9) or the formula (10) is also obtained after code rate conversion is performed on the reference code rate γ_{ref} obtained through MCS table lookup. Performing specific code rate conversion can make code rate determining more flexible.

[0162] In other words, after determining that the uplink shared channel scheduled by using the first DCI is UCI-only, the terminal device may further determine the first code rate by using either of the foregoing two table lookup manners.

[0163] In this embodiment of this application, the first code rate is the reference code rate γ_{ref} obtained through MCS table lookup.

[0164] In the first table lookup manner, I_{MCS} in the first DCI is directly used as an index value for a lookup in an MCS table, and then the first code rate and the modulation order corresponding to I_{MCS} may be obtained. For example, when I_{MCS} in the first DCI is 16, a first code rate 658 (an actual code rate needs to be obtained by dividing the first code rate by 1024) and a corresponding modulation order 4 may be obtained through a lookup in the MCS table shown in Table 3.

[0165] For example, after UCI-only is determined in the foregoing manner 1 or manner 4, the first code rate and the modulation order may be obtained through table lookup in the first table lookup manner.

[0166] For example, in the table lookup manner shown in FIG. 4, a bit field including five bits may be constructed based on the HARQ ID and I_{MCS} in the first DCI in the second table lookup manner; then, a value of the created bit field is used as a new index value; and further, the new index value is used as an index value for a lookup in an MCS table, so as to obtain a first code rate and a modulation order that correspond to the new index value. For example, when a value of the created index value is 8, a first code rate 553 (an actual code rate needs to be obtained by dividing the first code rate by 1024) and a corresponding modulation order 4 may be obtained through a lookup in the MCS table shown in FIG. 2.

[0167] For example, after UCI-only is determined in the foregoing manner 2 or manner 3, the corresponding first code rate may not be obtained from the MCS table due to a relatively large value of the original I_{MCS} in the first DCI. For example, when I_{MCS} is 31, a corresponding code rate in the MCS table shown in Table 3 is "reserved", that is, the code rate may not be obtained directly. In this case, the second table lookup manner may be used. The created index value is first obtained, and then the corresponding first code rate and modulation order are obtained through table lookup based on the created index value.

[0168] After the first code rate and the corresponding modulation order are obtained through table lookup, the obtained first code rate and corresponding modulation order may be used to send the UCI, for example, the first UCI, on the uplink shared channel scheduled by using the first DCI.

[0169] As described above, the UCI may include the three parts: the HARQ ACK, the CSI-part1, and the CSI-part2. To send each part, a quantity of REs, a code rate, and a modulation order that are used to send the part need to be known. In a specific implementation process, when each part in the UCI is sent, the first code rate obtained through table lookup may be used directly to send related information.

[0170] In addition, the existing MCS table is an MCS table in which UL-SCH data is optimized. When the code rate in the MCS table is directly used to indicate a code rate of the UCI on the PUSCH, it is difficult for the network device to implement sufficiently accurate scheduling, that is, accuracy of scheduling by the network device is relatively low. Therefore, to improve accuracy of scheduling by the network device, in this embodiment of this application, after the first code rate is obtained through table lookup, another code rate may be further generated based on the first code rate, that is, the another code rate is obtained by performing conversion on the first code rate, and then the related information of the UCI is sent by using the another code rate.

[0171] For ease of understanding by a person skilled in the art, the following describes, by using some examples, how to send information in the UCI by using the first code rate obtained through table lookup. In some examples, the first code rate is directly used to send the information in the UCI, and in some examples, another code rate obtained by

performing code rate conversion on the first code rate is used to send the information in the UCI.

5 (1) For the HARQ ACK included in the DCI, Q'_{ACK} may be calculated according to the formula (1), and then

Q'_{ACK} and the first code rate and the modulation order that are obtained through table lookup are used to send a HARQ ACK in the first UCI. In this case, it may be considered that the terminal device sends the HARQ ACK by directly using the first code rate obtained through table lookup.

10 (2) For the HARQ ACK included in the DCI, Q'_{ACK} may be alternatively calculated by using the first code rate obtained through table lookup and according to the formula (5), and then the calculated Q'_{ACK} and the first code rate and the modulation order that are obtained through table lookup are used to send a HARQ ACK in the first UCI. In this case, it may also be considered that the terminal device sends the HARQ ACK by directly using the first code rate obtained through table lookup.

15 (3) For the CSI-part1 included in the DCI, Q'_{CSI-1} may be calculated according to the formula (6), and then the calculated Q'_{CSI-1} and the first code rate and the modulation order that are obtained through table lookup are used to send the first UCI. In this case, it may also be considered that the terminal device sends the CSI-part1 by directly using the first code rate obtained through table lookup.

20 (4) For the CSI-part1 included in the DCI, Q'_{CSI-1} may be first calculated according to the formula (2); a second code rate γ_{CSI-1} is calculated by using the first code rate and according to the formula (8); and further, the calculated

25 Q'_{CSI-1} , the calculated γ_{CSI-1} , and the modulation order obtained through table lookup are used to send the first UCI. In this case, it may be considered that the terminal device sends a CSI-part1 in the first UCI by using the second code rate. The process of determining the second code rate γ_{CSI-1} by using the first code rate and according to the formula (8) may be understood as the foregoing code rate conversion process. In the following description, a process similar to the process of calculating another code rate based on the first code rate may be understood as the foregoing code rate conversion process.

30 (5) For the CSI-part1 included in the DCI, Q'_{CSI-1} may be calculated according to the formula (6), and a second code rate γ_{CSI-1} is calculated by using the first code rate and according to the formula (8). Because the first code

35 rate γ_{ref} is used in the formula (6), using the calculated Q'_{CSI-1} , the calculated γ_{CSI-1} , and the modulation order obtained through table lookup to send the first UCI may be understood as using the first code rate and the second code rate by the terminal device to send the CSI-part1.

40 (6) For the CSI-part2 included in the DCI, Q'_{CSI-2} may be calculated according to the formula (7), and γ_{CSI-1} is calculated based on the first code rate and according to the formula (8); then, a third code rate is calculated by using

45 the calculated γ_{CSI-1} and according to the formula (9) or the formula (10); and finally, the calculated Q'_{CSI-2} , the calculated third code rate, and the first code rate and the modulation order that are obtained through table lookup are used to send the CSI-part2. Because γ_{CSI-1} is the second code rate described above, this may also be understood as using the second code rate and the third code rate to send the CSI-part2.

50 [0172] The third code rate may be understood as the threshold code rate described above. Because the threshold code rate is used to determine, during sending of the CSI-part2 in the UCI, whether some information in the CSI-part2 is to be dropped, the third code rate may be usually used only when the CSI-part2 in the UCI is sent.

55 [0173] The foregoing describes only some possible cases by using examples. In a specific implementation process, certainly, a corresponding part in the first UCI may be sent based on different combinations of the formulas described above and by using different combinations of code rates. Examples are not described one by one in this embodiment

of this application. However, the manner of sending the first UCI directly based on the first code rate obtained through table lookup or sending the UCI based on the first code rate obtained through table lookup and by using the another code rate obtained through code rate conversion shall fall within the protection scope of the embodiments of this application.

5 [0174] Based on the same concept, an embodiment of this application further provides a UCI receiving method. The method may be performed by the network device in FIG. 2. For descriptions of corresponding implementations of the method, refer to the foregoing descriptions of the method steps performed by the network device in FIG. 2. Descriptions are not repeated herein. In the method according to this embodiment of this application, the network device may notify, by using UCI, a terminal device of an indication that an uplink shared channel scheduled for the terminal device is used to send only the UCI. This can enhance a capability of the network device to control and indicate to the terminal device, so that the terminal device can have a consistent understanding as the network device, thereby improving performance of interaction between the network device and the terminal device.

10 [0175] In addition, it should be noted that, Chinese explanations of some English terms and English abbreviations are merely examples in this specification. For example, Chinese explanation of MCS is modulation and coding scheme, or may be modulation and coding policy, modulation and coding policy, modulation and coding scheme, or the like in another translation version. For another example, translation of code rate is code rate, or may be bit rate or the like in another translation version. In other words, some English translations in the embodiments of this application are merely example translations. The English translations in this application do not constitute any limitation on meanings of the English terms. Alternatively, it should be understood by a person skilled in the art that, with the development of communications technologies, the English terms or the English abbreviations in the embodiments of this application may further include other Chinese explanations, and all kinds of translations do not affect characteristics of the English terms or the English abbreviations.

15 [0176] Based on the same concept, an embodiment of this application provides an apparatus. FIG. 5 is a schematic structural diagram of an apparatus 500. The apparatus 500 may be a terminal device, and is capable of implementing functions of the terminal device in the method provided in the embodiments of this application. Alternatively, the apparatus 500 may be an apparatus that is capable of supporting a terminal device to implement functions of the terminal device in the method provided in the embodiments of this application. The apparatus 500 may be a hardware structure, a software module, or a combination of a hardware structure and a software module. The apparatus 500 may be implemented by a chip system. In this embodiment of this application, the chip system may include a chip, or may include a chip and another discrete device.

20 [0177] As shown in FIG. 5, the apparatus 500 in this embodiment of this application may include a receiving module 51, a first determining module 52, and a sending module 53.

25 [0178] The receiving module 51 may be configured to receive the first DCI sent by the network device in the embodiment shown in FIG. 2, and may further receive the second DCI sent by the network device; and/or may be further configured to support another process in the technology described in this specification. The second DCI may be previous DCI that carries the same HARQ ID as the first DCI and that is closest to the first DCI in time. The receiving module 51 may be configured for communication between the apparatus in this embodiment of this application and another module, and may be a circuit, a device, an interface, a bus, a software module, a transceiver, or any other apparatus that can implement communication.

30 [0179] The first determining module 52 may be configured to perform step 23 in the embodiment shown in FIG. 2, for example, may determine, based on the first DCI, that the uplink shared channel scheduled by using the first DCI is the channel used to send only the UCI, or may determine, based on the first DCI and the second DCI, that the uplink shared channel scheduled by using the first DCI is the channel used to send only the UCI; and/or may be further configured to support another process in the technology described in this specification. The first determining module 52 may be configured for communication between the apparatus in this embodiment of this application and another module, and may be a circuit, a device, an interface, a bus, a software module, a transceiver, or any other apparatus that can implement communication.

35 [0180] The sending module 53 may be configured to perform step 24 in the embodiment shown in FIG. 2, that is, may send the UCI to the network device through the uplink shared channel scheduled by using the first DCI, for example, send the first UCI; and/or may be configured to support another process in the technology described in this specification. The sending module 53 may be configured for communication between the apparatus in this embodiment of this application and another module, and may be a circuit, a device, an interface, a bus, a software module, a transceiver, or any other apparatus that can implement communication.

40 [0181] In a specific implementation process, the receiving module 51 and the sending module 53 may be disposed separately. In this case, the receiving module 51 and the sending module 53 are two independent function modules. In a possible implementation, the receiving module 51 and the sending module 53 may be alternatively integrated into one function module, for example, a transceiver module. The transceiver module has both a capability of the receiving module 51 to receive information and a capability of the sending module 53 to send information.

[0182] All related content of each step in the foregoing method embodiments may be cited in function descriptions of a corresponding function module. Details are not described herein again.

[0183] Based on the same concept, an embodiment of this application provides an apparatus. FIG. 6 is a schematic structural diagram of an apparatus 600. The apparatus 600 may be a network device, and is capable of implementing functions of the network device in the method provided in the embodiments of this application. Alternatively, the apparatus 600 may be an apparatus that is capable of supporting a network device to implement functions of the network device in the method provided in the embodiments of this application. The apparatus 600 may be a hardware structure, a software module, or a combination of a hardware structure and a software module. The apparatus 600 may be implemented by a chip system. In this embodiment of this application, the chip system may include a chip, or may include a chip and another discrete device.

[0184] As shown in FIG. 6, the apparatus 600 in this embodiment of this application may include a sending module 61 and a receiving module 62.

[0185] The sending module 61 may be configured to perform step 22 in the embodiment shown in FIG. 2, that is, send the first DCI to the terminal device, and may further send the second DCI to the terminal device; and/or may be configured to support another process in the technology described in this specification. The second DCI may be previous DCI that carries the same HARQ ID as the first DCI and that is closest to the first DCI in time. The sending module 61 may be configured for communication between the apparatus in this embodiment of this application and another module, and may be a circuit, a device, an interface, a bus, a software module, a transceiver, or any other apparatus that can implement communication.

[0186] The receiving module 62 may be configured to perform the UCI sent by the terminal device in the embodiment shown in FIG. 2, for example, may receive the first DCI sent by the terminal device through the uplink shared channel scheduled by using the first DCI; and/or may be configured to support another process in the technology described in this specification. The receiving module 62 may be configured for communication between the apparatus in this embodiment of this application and another module, and may be a circuit, a device, an interface, a bus, a software module, a transceiver, or any other apparatus that can implement communication.

[0187] In addition, the apparatus 600 may further include a determining module. The determining module may perform step 21 in the embodiment shown in FIG. 2, that is, may determine that the uplink shared channel scheduled for the terminal device is used to send only the UCI.

[0188] In a specific implementation process, the sending module 61 and the receiving module 62 may be disposed separately. In this case, the sending module 61 and the receiving module 62 are two independent function modules. In a possible implementation, the sending module 61 and the receiving module 62 may be alternatively integrated into one function module, for example, a transceiver module. The transceiver module has both a capability of the receiving module 51 to send information and a capability of the receiving module 62 to receive information.

[0189] All related content of each step in the foregoing method embodiments may be cited in function descriptions of a corresponding function module. Details are not described herein again.

[0190] In this embodiment of this application, module division is an example, and is merely logical function division and may be another division manner during actual implementation. In addition, function modules in the embodiments of this application may be integrated into one processor, or each of the modules may exist alone physically, or at least two modules may be integrated into one module. The integrated module may be implemented in a form of hardware, or may be implemented in a form of a software function module.

[0191] Based on the same concept, an embodiment of this application provides an apparatus. FIG. 7 is a schematic structural diagram of an apparatus 700 according to an embodiment of this application. The apparatus 700 may be a terminal device, and is capable of implementing functions of the terminal device in the method provided in the embodiments of this application. Alternatively, the apparatus 700 may be an apparatus that is capable of supporting a terminal device to implement functions of the terminal device in the method provided in the embodiments of this application. The apparatus 700 may be a chip system. In this embodiment of this application, the chip system may include a chip, or may include a chip and another discrete device.

[0192] The apparatus 700 includes at least one processor 720, configured to implement or support the apparatus to implement functions of the terminal device in the method provided in the embodiments of this application. For example, the processor 720 may process information, for example, may correspond to the first determining module 52 in the apparatus 500 shown in FIG. 5. For example, the processor 720 may determine, based on the obtained first DCI, that the uplink shared channel scheduled by using the first DCI is used to send only the UCI. For details, refer to the detailed descriptions in the method example. Details are not described herein again.

[0193] The apparatus 700 may further include at least one memory 730, configured to store a program instruction and/or data. The memory 730 is coupled to the processor 720. Couplings in this embodiment of this application are indirect couplings or communication connections between apparatuses, units, or modules, may be electrical, mechanical, or in another form, and are used for information exchange between the apparatuses, the units, or the modules. The processor 720 may cooperate with the memory 730. The processor 720 may execute the program instruction stored in

the memory 730. At least one of the at least one memory may be included in the processor.

[0194] The apparatus 700 may further include a communications interface 710, configured to communicate with another device through a transmission medium, so that an apparatus in the apparatus 700 can communicate with the another device. The processor 720 may transmit and send data through the communications interface 710. For example, the communications interface 710 may correspond to the receiving module 51 and the sending module 53 in FIG. 5.

[0195] A specific connection medium between the communications interface 710, the processor 720, and the memory 730 is not limited in this embodiment of this application. In this embodiment of this application, the memory 730, the processor 720, and the communications interface 710 are connected by using a bus 740 in FIG. 7, where the bus is represented by a bold line in FIG. 7. This is only a schematic illustration and is not intended for limitation. There may be other connection manners between the components. The bus may be classified into an address bus, a data bus, a control bus, and the like. For ease of representation, only one bold line is used to represent the bus in FIG. 7, but this does not mean that there is only one bus or only one type of bus.

[0196] In this embodiment of this application, the processor 720 may be a general-purpose processor, a digital signal processor, an application-specific integrated circuit, a field programmable gate array or another programmable logic device, a discrete gate or transistor logic device, or a discrete hardware component, and may implement or execute the methods, steps, and logical block diagrams disclosed in the embodiments of this application. The general-purpose processor may be a microprocessor or any conventional processor or the like. The steps of the method disclosed with reference to the embodiments of this application may be directly performed by a hardware processor, or may be performed by using a combination of hardware in the processor and a software module.

[0197] In this embodiment of this application, the memory 730 may be a nonvolatile memory, for example, a hard disk drive (hard disk drive, HDD) or a solid-state drive (solid-state drive, SSD); or may be a volatile memory (volatile memory), for example, a random-access memory (random-access memory, RAM). The memory is any other medium that can be used to carry or store expected program code in a form of an instruction or a data structure and that is accessible to a computer, but is not limited thereto. The memory in this embodiment of this application may alternatively be a circuit or any other apparatus that is capable of implementing a storage function, and is configured to store a program instruction and/or data.

[0198] Based on the same concept, an embodiment of this application provides another apparatus. FIG. 8 is a schematic structural diagram of another apparatus 800 according to an embodiment of this application. The apparatus 800 may be a network device, and is capable of implementing functions of the network device in the method provided in the embodiments of this application. Alternatively, the apparatus 800 may be an apparatus that is capable of supporting a network device to implement functions of the network device in the method provided in the embodiments of this application. The apparatus 800 may be a chip system. In this embodiment of this application, the chip system may include a chip, or may include a chip and another discrete device.

[0199] The apparatus 800 includes at least one processor 820, configured to implement or support the apparatus to implement functions of the terminal device in the method provided in the embodiments of this application. For example, the processor 820 corresponds to the determining module in the embodiment shown in FIG. 6. For example, the processor 820 determines that the uplink shared channel scheduled for the terminal device is the channel used to send only the UCI. For details, refer to the detailed descriptions in the method example. Details are not described herein again.

[0200] The apparatus 800 may further include at least one memory 830, configured to store a program instruction and/or data. The memory 830 is coupled to the processor 820. Couplings in this embodiment of this application are indirect couplings or communication connections between apparatuses, units, or modules, may be electrical, mechanical, or in another form, and are used for information exchange between the apparatuses, the units, or the modules. The processor 820 may cooperate with the memory 830. The processor 820 may execute the program instruction stored in the memory 830. At least one of the at least one memory may be included in the processor.

[0201] The apparatus 800 may further include a communications interface 810, configured to communicate with another device through a transmission medium, so that an apparatus in the apparatus 800 can communicate with the another device. The processor 820 may transmit and send data through the communications interface 810. For example, the communications interface 810 may correspond to the sending module 61 and the receiving module 62 in FIG. 6.

[0202] A specific connection medium between the communications interface 810, the processor 820, and the memory 830 is not limited in this embodiment of this application. In this embodiment of this application, the memory 830, the processor 820, and the communications interface 810 are connected by using a bus 840 in FIG. 8, where the bus is represented by a bold line in FIG. 8. This is only a schematic illustration and is not intended for limitation. There may be other connection manners between the components. The bus may be classified into an address bus, a data bus, a control bus, and the like. For ease of representation, only one bold line is used to represent the bus in FIG. 8, but this does not mean that there is only one bus or only one type of bus.

[0203] In this embodiment of this application, the processor 820 may be a general-purpose processor, a digital signal processor, an application-specific integrated circuit, a field programmable gate array or another programmable logic device, a discrete gate or transistor logic device, or a discrete hardware component, and may implement or execute the

methods, steps, and logical block diagrams disclosed in the embodiments of this application. The general-purpose processor may be a microprocessor or any conventional processor or the like. The steps of the method disclosed with reference to the embodiments of this application may be directly performed by a hardware processor, or may be performed by using a combination of hardware in the processor and a software module.

5 [0204] In this embodiment of this application, the memory 830 may be a nonvolatile memory, for example, an HDD or a solid-state drive SSD; or may be a volatile memory (volatile memory), for example, a random-access memory RAM. The memory is any other medium that can be used to carry or store expected program code in a form of an instruction or a data structure and that is accessible to a computer, but is not limited thereto. The memory in this embodiment of this application may alternatively be a circuit or any other apparatus that is capable of implementing a storage function, and is configured to store a program instruction and/or data.

10 [0205] An embodiment of this application further provides a readable storage medium including an instruction. When run on a computer, the instruction enables the computer to perform the steps that are performed by the terminal device in the method shown in FIG. 2.

15 [0206] An embodiment of this application further provides a readable storage medium including an instruction. When run on a computer, the instruction enables the computer to perform the steps that are performed by the network device in the method shown in FIG. 2.

20 [0207] An embodiment of this application provides a chip system. The chip system includes a processor, may further include a memory, and is configured to implement functions of the terminal device in the foregoing method. The chip system may include a chip, or may include a chip and another discrete device.

25 [0208] An embodiment of this application provides a chip system. The chip system includes a processor, may further include a memory, and is configured to implement functions of the network device in the foregoing method. The chip system may include a chip, or may include a chip and another discrete device.

30 [0209] An embodiment of this application provides a system. The system includes the foregoing network device and the foregoing terminal device.

35 [0210] In a possible implementation, the aspects of the methods in the embodiments of this application may be alternatively implemented in a form of a program product. The program product includes program code, and when the program product is run on the terminal device or the network device, the program code is used to enable the terminal device or the network device to perform the steps of the methods according to various foregoing example embodiments in this specification.

40 [0211] All or some of the methods in the embodiments of this application may be implemented by using software, hardware, firmware, or any combination thereof. When software is used for implementation, the methods may be implemented completely or partially in a form of a computer program product. The computer program product includes one or more computer instructions. When the computer program instruction is loaded and executed on a computer, the procedure or functions according to the embodiments of the present invention are all or partially generated. The computer may be a general-purpose computer, a special-purpose computer, a computer network, a network device, user equipment, or another programmable apparatus. The computer instruction may be stored in a computer-readable storage medium or may be transmitted from a computer-readable storage medium to another computer-readable storage medium. For example, the computer instruction may be transmitted from a website, computer, server, or data center to another website, computer, server, or data center in a wired (for example, a coaxial cable, an optical fiber, or a digital subscriber line (digital subscriber line, DSL)) or wireless (for example, infrared, radio, or microwave) manner. The computer-readable storage medium may be any usable medium accessible to a computer, or a data storage device, such as a server or a data center, integrating one or more usable media. The usable medium may be a magnetic medium (for example, a floppy disk, a hard disk, or a magnetic tape), an optical medium (for example, a digital video disc (digital video disc, DVD)), a semiconductor medium (for example, an SSD), or the like.

45

Claims

1. An uplink control information sending method performed by a terminal device, the method comprising:

50 receiving first downlink control information through a physical downlink control channel from a base station, wherein the first downlink control information is used to schedule an physical uplink shared channel, the first downlink control information comprises a first indication information and a second indication information, the first indication information indicates that the physical uplink shared channel is used to send uplink control information but is not used to send data and the second indication information indicates a modulation and coding scheme index of the physical uplink shared channel;

55 determining (23), based on the first indication information, that the physical uplink shared channel is used to send uplink control information without data,

5 determining, a first code rate of the physical uplink shared channel and a modulation order of the physical uplink shared channel based on the second indication information; and
 10 sending (24) first uplink control information to the base station through the uplink shared channel, wherein the first uplink control information comprises a hybrid automatic repeat request-acknowledgement, wherein:
 15 a total quantity of resource elements in the physical uplink shared channel that are used to carry the first uplink control information is M, and a quantity of resource elements in the physical uplink shared channel that are used to carry the hybrid automatic repeat request-acknowledgement is a minimum value of a first quantity and the total quantity M, wherein the first quantity is equal to a round-up value of a ratio of a first product to a second product, wherein the first product is a product of a payload size of the hybrid automatic repeat request-acknowledgement and a code rate compensation parameter of the hybrid automatic repeat request-acknowledgement, and the second product is a product of the first code rate and the modulation order.

20

2. The method according to claim 1, wherein the first uplink control information further comprises a first part of channel state information, a quantity of resource elements that are in the physical uplink shared channel and are used to carry the first part of the channel state information is a minimum value of a second quantity and a remaining quantity, wherein the remaining quantity is equal to the total quantity M minus the quantity of the resource elements used to carry the hybrid automatic repeat request-acknowledgement, and the second quantity is equal to a round-up value of a ratio of a third product to the second product, wherein the third product is a product of a payload size of the first part of the channel state information and a code rate compensation parameter of the first part of the channel state information.

25

3. The method according to claim 2, wherein the first uplink control information further comprises a second part of the channel state information, a quantity of resource elements that are in the physical uplink shared channel and are used to carry the second part of the channel state information is equal to the total quantity M minus the quantity of the resource elements used to carry the hybrid automatic repeat request-acknowledgement and minus the quantity of the resource elements used to carry the first part of the channel state information.

30

4. The method according to claim 1, wherein the first code rate and the modulation order are determined based on the modulation and coding scheme index comprised in the first downlink control information.
5. The method according to claim 4, wherein
 35 a correspondence among the modulation and coding scheme index, the first code rate, and the modulation order meets a correspondence defined in one of the following tables:

Table 1

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
0	2	120	0.2344
1	2	157	0.3066
2	2	193	0.3770
3	2	251	0.4902
4	2	308	0.6016
5	2	379	0.7402
6	2	449	0.8770
7	2	526	1.0273
8	2	602	1.1758
9	2	679	1.3262
10	4	340	1.3281
11	4	378	1.4766
12	4	434	1.6953
13	4	490	1.9141

(continued)

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
5	14	4	553	2.1602
10	15	4	616	2.4063
15	16	4	658	2.5703
20	17	6	438	2.5664
25	18	6	466	2.7305
30	19	6	517	3.0293
	20	6	567	3.3223
	21	6	616	3.6094
	22	6	666	3.9023
	23	6	719	4.2129
	24	6	772	4.5234
	25	6	822	4.8164
	26	6	873	5.1152
	27	6	910	5.3320
	28	6	948	5.5547
	29	2	Reserved	
	30	4	Reserved	
	31	6	Reserved	

Table 2

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
35	0	2	120	0.2344
40	1	2	193	0.3770
45	2	2	308	0.6016
50	3	2	449	0.8770
55	4	2	602	1.1758
	5	4	378	1.4766
	6	4	434	1.6953
	7	4	490	1.9141
	8	4	553	2.1602
	9	4	616	2.4063
	10	4	658	2.5703
	11	6	466	2.7305
	12	6	517	3.0293
	13	6	567	3.3223
	14	6	616	3.6094
	15	6	666	3.9023

(continued)

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
5	16	6	719	4.2129
10	17	6	772	4.5234
15	18	6	822	4.8164
20	19	6	873	5.1152
25	20	8	682.5	5.3320
30	21	8	711	5.5547
35	22	8	754	5.8906
40	23	8	797	6.2266
45	24	8	841	6.5703
50	25	8	885	6.9141
55	26	8	916.5	7.1602
60	27	8	948	7.4063
65	28	2	Reserved	
70	29	4	Reserved	
75	30	6	Reserved	
80	31	8	Reserved	

Table 3

	MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
35	0	q	$240/q$	0.2344
40	1	q	$314/q$	0.3066
45	2	2	193	0.3770
50	3	2	251	0.4902
55	4	2	308	0.6016
60	5	2	379	0.7402
65	6	2	449	0.8770
70	7	2	526	1.0273
75	8	2	602	1.1758
80	9	2	679	1.3262
85	10	4	340	1.3281
90	11	4	378	1.4766
95	12	4	434	1.6953
100	13	4	490	1.9141
105	14	4	553	2.1602
110	15	4	616	2.4063
115	16	4	658	2.5703
120	17	6	466	2.7305

(continued)

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
18	6	517	3.0293
19	6	567	3.3223
20	6	616	3.6094
21	6	666	3.9023
22	6	719	4.2129
23	6	772	4.5234
24	6	822	4.8164
25	6	873	5.1152
26	6	910	5.3320
27	6	948	5.5547
28	1	Reserved	
29	2	Reserved	
30	4	Reserved	
31	6	Reserved	

25 6. The method according to claim 3, wherein

30 a code rate of the second part of the channel state information is not higher than a threshold code rate; or a code rate of the second part of the channel state information is higher than a threshold code rate, and the terminal device drops some information in the second part of the channel state information based on a priority, wherein
 35 the threshold code rate is a ratio of the first code rate to a code rate compensation parameter of the second part of the channel state information.

35 7. An uplink control information receiving method performed by a base station, the method comprising:

40 Sending (22) first downlink control information through a physical downlink control channel to a terminal device, wherein the first downlink control information is used to schedule an physical uplink shared channel, the first downlink control information comprises a first indication information and a second indication information, the first indication information indicates that the physical uplink shared channel is used to send uplink control information but is not used to send data and the second indication information indicates a modulation and coding scheme index of the physical uplink shared channel; and

45 receiving, through the physical uplink shared channel, first uplink control information from the terminal device, wherein the first uplink control information comprises a hybrid automatic repeat request-acknowledgement, wherein

50 a total quantity of resource elements in the physical uplink shared channel that are used to carry the first uplink control information is M, and a quantity of resource elements in the physical uplink shared channel that are used to carry the hybrid automatic repeat request-acknowledgement is a minimum value of a first quantity and the total quantity M, wherein the first quantity is equal to a round-up value of a ratio of a first product to a second product, wherein the first product is a product of a payload size of the hybrid automatic repeat request-acknowledgement and a code rate compensation parameter of the hybrid automatic repeat request-acknowledgement, and the second product is a product of a first code rate and a modulation order.

55 8. The method according to claim 7, wherein the first uplink control information further comprises a first part of channel state information, a quantity of resource elements that are in the physical uplink shared channel and are used to carry the first part of the channel state information is a minimum value of a second quantity and a remaining quantity, wherein the remaining quantity is equal to the total quantity M minus the quantity of the resource elements used to carry the hybrid automatic repeat request-acknowledgement, and the second quantity is equal to a round-up value

of a ratio of a third product to the second product, wherein the third product is a product of a payload size of the first part of the channel state information and a code rate compensation parameter of the first part of the channel state information.

5 9. The method according to claim 8, wherein the first uplink control information further comprises a second part of the channel state information, a quantity of resource elements that are in the physical uplink shared channel and are used to carry the second part of the channel state information is equal to the total quantity M minus the quantity of the resource elements used to carry the hybrid automatic repeat request-acknowledgement and minus the quantity of the resource elements used to carry the first part of the channel state information.

10 10. The method according to claim 7, wherein the first code rate and the modulation order are determined based on a modulation and coding scheme index comprised in the first downlink control information.

15 11. The method according to claim 10, wherein a correspondence among the modulation and coding scheme index, the first code rate, and the modulation order meets a correspondence defined in one of the following tables:

Table 1

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
0	2	120	0.2344
1	2	157	0.3066
2	2	193	0.3770
3	2	251	0.4902
4	2	308	0.6016
5	2	379	0.7402
6	2	449	0.8770
7	2	526	1.0273
8	2	602	1.1758
9	2	679	1.3262
10	4	340	1.3281
11	4	378	1.4766
12	4	434	1.6953
13	4	490	1.9141
14	4	553	2.1602
15	4	616	2.4063
16	4	658	2.5703
17	6	438	2.5664
18	6	466	2.7305
19	6	517	3.0293
20	6	567	3.3223
21	6	616	3.6094
22	6	666	3.9023
23	6	719	4.2129
24	6	772	4.5234
25	6	822	4.8164
26	6	873	5.1152

(continued)

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
27	6	910	5.3320
28	6	948	5.5547
29	2	Reserved	
30	4	Reserved	
31	6	Reserved	

Table 2

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
0	2	120	0.2344
1	2	193	0.3770
2	2	308	0.6016
3	2	449	0.8770
4	2	602	1.1758
5	4	378	1.4766
6	4	434	1.6953
7	4	490	1.9141
8	4	553	2.1602
9	4	616	2.4063
10	4	658	2.5703
11	6	466	2.7305
12	6	517	3.0293
13	6	567	3.3223
14	6	616	3.6094
15	6	666	3.9023
16	6	719	4.2129
17	6	772	4.5234
18	6	822	4.8164
19	6	873	5.1152
20	8	682.5	5.3320
21	8	711	5.5547
22	8	754	5.8906
23	8	797	6.2266
24	8	841	6.5703
25	8	885	6.9141
26	8	916.5	7.1602
27	8	948	7.4063
28	2	Reserved	

(continued)

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
29	4	Reserved	
30	6	Reserved	
31	8	Reserved	

10

Table 3

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
0	9	$240/q$	0.2344
1	9	$314/q$	0.3066
2	2	193	0.3770
3	2	251	0.4902
4	2	308	0.6016
5	2	379	0.7402
6	2	449	0.8770
7	2	526	1.0273
8	2	602	1.1758
9	2	679	1.3262
10	4	340	1.3281
11	4	378	1.4766
12	4	434	1.6953
13	4	490	1.9141
14	4	553	2.1602
15	4	616	2.4063
16	4	658	2.5703
17	6	466	2.7305
18	6	517	3.0293
19	6	567	3.3223
20	6	616	3.6094
21	6	666	3.9023
22	6	719	4.2129
23	6	772	4.5234
24	6	822	4.8164
25	6	873	5.1152
26	6	910	5.3320
27	6	948	5.5547
28	1	Reserved	
29	2	Reserved	
30	4	Reserved	

5

15

20

25

30

35

40

45

50

55

(continued)

MCS index	Modulation order	Target code rate $\times 1024$	Spectrum efficiency
31	6	Reserved	

5 **12.** The method according to claim 9, wherein

10 a code rate of the second part of the channel state information is not higher than a threshold code rate; or
 a code rate of the second part of the channel state information is higher than a threshold code rate, and the terminal device drops some information in the second part of the channel state information based on a priority, wherein
 15 the threshold code rate is a ratio of the first code rate to a code rate compensation parameter of the second part of the channel state information.

15 **13.** A terminal device apparatus, wherein the apparatus is configured to perform the method according to any one of claims 1 to 6.

20 **14.** A base station communication apparatus, wherein the communication apparatus is configured to perform the method according to any one of claims 7 to 12.

15. A computer program product, comprising instructions which, when executed by a computer, cause the computer to perform the method according to any one of claims 1 to 6 or any one of claims 7 to 12.

25 **Patentansprüche**

1. Uplink-Steuerungsinformationssendeverfahren, das durch ein Endgerät durchgeführt wird, wobei das Verfahren umfasst:

30 Empfangen erster Downlink-Steuerungsinformationen über einen physischen Downlink-Steuerkanal von einer Basisstation, wobei die ersten Downlink-Steuerungsinformationen zum Planen eines physischen gemeinsam genutzten Uplink-Kanals verwendet werden, die ersten Downlink-Steuerungsinformationen erste Angabeinformationen und zweite Angabeinformationen umfassen, die ersten Angabeinformationen angeben, dass der physische gemeinsam genutzte Uplink-Kanal zum Senden von Uplink-Steuerungsinformationen, jedoch nicht zum Senden von Daten verwendet wird, und die zweiten Angabeinformationen einen Modulations- und Codierungsschemaindex des physischen gemeinsam genutzten Uplink-Kanals angeben;
 35 Bestimmen (23), basierend auf den ersten Angabeinformationen, dass der physische gemeinsam genutzte Uplink-Kanal verwendet wird, um Uplink-Steuerungsinformationen ohne Daten zu senden,
 40 Bestimmen einer ersten Coderate des physischen gemeinsam genutzten Uplink-Kanals und einer Ordnung der Modulation des physischen gemeinsam genutzten Uplink-Kanals basierend auf den zweiten Angabeinformationen; und
 45 Senden (24) erster Uplink-Steuerungsinformationen an die Basisstation über den gemeinsam genutzten Uplink-Kanal, wobei die ersten Uplink-Steuerungsinformationen eine hybride automatische Wiederholungsanforderungsbestätigung umfassen, wobei: eine Gesamtmenge von Ressourcenelementen in dem physischen gemeinsam genutzten Uplink-Kanal, die zum Transportieren der ersten Uplink-Steuerungsinformationen verwendet werden, M ist, und eine Menge von Ressourcenelementen in dem physischen gemeinsam genutzten Uplink-Kanal, die zum Transportieren der hybriden automatischen Wiederholungsanforderungsbestätigung verwendet werden, ein Mindestwert einer ersten Menge und der Gesamtmenge M ist, wobei die erste Menge gleich einem Aufrundungswert eines Verhältnisses eines ersten Produkts zu einem zweiten Produkt ist, wobei das erste Produkt ein Produkt aus einer Nutzlastgröße der hybriden automatischen Wiederholungsanforderungsbestätigung und einem Coderatenkompensationsparameter der hybriden automatischen Wiederholungsanforderungsbestätigung ist und das zweite Produkt ein Produkt aus der ersten Coderate und der Ordnung der Modulation ist.

50 **2.** Verfahren nach Anspruch 1, wobei die ersten Uplink-Steuerungsinformationen ferner einen ersten Teil von Kanalzustandsinformationen umfassen, wobei eine Menge von Ressourcenelementen, die sich in dem physischen gemeinsam genutzten Uplink-Kanal befinden und verwendet werden, um den ersten Teil der Kanalzustandsinformationen zu transportieren, ein Mindestwert einer zweiten Menge und einer Restmenge ist, wobei die Restmenge

gleich der Gesamtmenge M minus der Menge der Ressourcenelemente ist, die verwendet werden, um die hybride automatische Wiederholungsanforderungsbestätigung zu transportieren, und die zweite Menge gleich einem Auf-
 5 rundungswert eines Verhältnisses eines dritten Produkts zu dem zweiten Produkt ist, wobei das dritte Produkt ein Produkt aus einer Nutzlastgröße des ersten Teils der Kanalzustandsinformationen und einem Coderatenkompen-
 sationsparameter des ersten Teils der Kanalzustandsinformationen ist.

10 3. Verfahren nach Anspruch 2, wobei die ersten Uplink-Steuerungsinformationen ferner einen zweiten Teil der Kanal-
 zustandsinformationen umfassen, wobei eine Menge von Ressourcenelementen, die sich in dem physischen ge-
 meinsam genutzten Uplink-Kanal befinden und verwendet werden, um den zweiten Teil der Kanalzustandsinfor-
 mationen zu transportieren, gleich der Gesamtmenge M minus der Menge der Ressourcenelemente ist, die ver-
 wendet werden, um die hybride automatische Wiederholungsanforderungsbestätigung zu transportieren, und minus
 15 der Menge der Ressourcenelemente ist, die verwendet werden, um den ersten Teil der Kanalzustandsinformationen
 zu transportieren.

20 4. Verfahren nach Anspruch 1, wobei die erste Coderate und die Ordnung der Modulation basierend auf dem Modu-
 lations- und Codierungsschemaindex bestimmt werden, der in den ersten Downlink-Steuerungsinformationen ent-
 halten ist.

25 5. Verfahren nach Anspruch 4, wobei
 20 eine Entsprechung zwischen dem Modulations- und Codierungsschemaindex, der ersten Coderate und der Ordnung
 der Modulation einer Entsprechung entspricht, die in einer der folgenden Tabellen definiert ist:

Tabelle 1

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
0	2	120	0,2344
1	2	157	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	438	2,5664
18	6	466	2,7305
19	6	517	3,0293
20	6	567	3,3223
21	6	616	3,6094
22	6	666	3,9023

(fortgesetzt)

	MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
5	23	6	719	4,2129
10	24	6	772	4,5234
15	25	6	822	4,8164
20	26	6	873	5,1152
25	27	6	910	5,3320
30	28	6	948	5,5547
35	29	2	Reserviert	
40	30	4	Reserviert	
45	31	6	Reserviert	

Tabelle 2

	MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
20	0	2	120	0,2344
25	1	2	193	0,3770
30	2	2	308	0,6016
35	3	2	449	0,8770
40	4	2	602	1,1758
45	5	4	378	1,4766
50	6	4	434	1,6953
55	7	4	490	1,9141
	8	4	553	2,1602
	9	4	616	2,4063
	10	4	658	2,5703
	11	6	466	2,7305
	12	6	517	3,0293
	13	6	567	3,3223
	14	6	616	3,6094
	15	6	666	3,9023
	16	6	719	4,2129
	17	6	772	4,5234
	18	6	822	4,8164
	19	6	873	5,1152
	20	8	682,5	5,3320
	21	8	711	5,5547
	22	8	754	5,8906
	23	8	797	6,2266
	24	8	841	6,5703

(fortgesetzt)

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
25	8	885	6,9141
26	8	916,5	7,1602
27	8	948	7,4063
28	2	Reserviert	
29	4	Reserviert	
30	6	Reserviert	
31	8	Reserviert	

15

Tabelle 3

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
0	q	$240/q$	0,2344
1	q	$314/q$	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	466	2,7305
18	6	517	3,0293
19	6	567	3,3223
20	6	616	3,6094
21	6	666	3,9023
22	6	719	4,2129
23	6	772	4,5234
24	6	822	4,8164
25	6	873	5,1152
26	6	910	5,3320

(fortgesetzt)

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
27	6	948	5,5547
28	1	Reserviert	
29	2	Reserviert	
30	4	Reserviert	
31	6	Reserviert	

6. Verfahren nach Anspruch 3, wobei

15 eine Coderate des zweiten Teils der Kanalzustandsinformationen nicht höher als eine Schwellenwert-Coderate ist; oder
 eine Coderate des zweiten Teils der Kanalzustandsinformationen höher als eine Schwellenwert-Coderate ist und die Endgerätevorrichtung einige Informationen in dem zweiten Teil der Kanalzustandsinformationen basierend auf einer Priorität ablegt, wobei
 20 die Schwellenwert-Coderate ein Verhältnis der ersten Coderate zu einem Coderatenkompensationsparameter des zweiten Teils der Kanalzustandsinformationen ist.

7. Uplink-Steuerungsinformationsempfangsverfahren, das durch eine Basisstation durchgeführt wird, wobei das Verfahren umfasst:

25 Senden (22) erster Downlink-Steuerungsinformationen über einen physischen Downlink-Steuerkanal an ein Endgerät, wobei die ersten Downlink-Steuerungsinformationen zum Planen eines physischen gemeinsam genutzten Uplink-Kanals verwendet werden, die ersten Downlink-Steuerungsinformationen erste Angabeinformationen und zweite Angabeinformationen umfassen, die ersten Angabeinformationen angeben, dass der physische gemeinsam genutzte Uplink-Kanal zum Senden von Uplink-Steuerungsinformationen, jedoch nicht zum Senden von Daten verwendet wird, und die zweiten Angabeinformationen einen Modulations- und Codierungsschemaindex des physischen gemeinsam genutzten Uplink-Kanals angeben; und
 30 Empfangen, über den physischen gemeinsam genutzten Uplink-Kanal, erster Uplink-Steuerungsinformationen von dem Endgerät, wobei die ersten Uplink-Steuerungsinformationen eine hybride automatische Wiederholungsanforderungsbestätigung umfassen, wobei
 35 eine Gesamtmenge von Ressourcenelementen in dem physischen gemeinsam genutzten Uplink-Kanal, die zum Transportieren der ersten Uplink-Steuerungsinformationen verwendet werden, M ist, und eine Menge von Ressourcenelementen in dem physischen gemeinsam genutzten Uplink-Kanal, die zum Transportieren der hybriden automatischen
 40 Wiederholungsanforderungsbestätigung verwendet werden, ein Mindestwert einer ersten Menge und der Gesamtmenge M ist, wobei die erste Menge gleich einem Aufrundungswert eines Verhältnisses eines ersten Produkts zu einem zweiten Produkt ist, wobei das erste Produkt ein Produkt aus einer Nutzlastgröße der hybriden automatischen Wiederholungsanforderungsbestätigung und einem Coderatenkompensationsparameter der hybriden automatischen Wiederholungsanforderungsbestätigung ist und das zweite Produkt ein Produkt aus einer ersten Coderate und einer Ordnung der Modulation ist.

8. Verfahren nach Anspruch 7, wobei die ersten Uplink-Steuerungsinformationen ferner einen ersten Teil von Kanalzustandsinformationen umfassen, wobei eine Menge von Ressourcenelementen, die sich in dem physischen gemeinsam genutzten Uplink-Kanal befinden und verwendet werden, um den ersten Teil der Kanalzustandsinformationen zu transportieren, ein Mindestwert einer zweiten Menge und einer Restmenge ist, wobei die Restmenge gleich der Gesamtmenge M minus der Menge der Ressourcenelemente ist, die verwendet werden, um die hybride automatische Wiederholungsanforderungsbestätigung zu transportieren, und die zweite Menge gleich einem Aufrundungswert eines Verhältnisses eines dritten Produkts zu dem zweiten Produkt ist, wobei das dritte Produkt ein Produkt aus einer Nutzlastgröße des ersten Teils der Kanalzustandsinformationen und einem Coderatenkompensationsparameter des ersten Teils der Kanalzustandsinformationen ist.

9. Verfahren nach Anspruch 8, wobei die ersten Uplink-Steuerungsinformationen ferner einen zweiten Teil der Kanalzustandsinformationen umfassen, wobei eine Menge von Ressourcenelementen, die sich in dem physischen ge-

meinsam genutzten Uplink-Kanal befinden und verwendet werden, um den zweiten Teil der Kanalzustandsinformationen zu transportieren, gleich der Gesamtmenge M minus der Menge der Ressourcenelemente ist, die verwendet werden, um die hybride automatische Wiederholungsanforderungsbestätigung zu transportieren, und minus der Menge der Ressourcenelemente ist, die verwendet werden, um den ersten Teil der Kanalzustandsinformationen zu transportieren.

- 5 10. Verfahren nach Anspruch 7, wobei die erste Coderate und die Ordnung der Modulation basierend auf einem Modulations- und Codierungsschemaindex bestimmt werden, der in den ersten Downlink-Steuerungsinformationen enthalten ist.
- 10 15. Verfahren nach Anspruch 10, wobei eine Entsprechung zwischen dem Modulations- und Codierungsschemaindex, der ersten Coderate und der Ordnung der Modulation einer Entsprechung entspricht, die in einer der folgenden Tabellen definiert ist:

Tabelle 1

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
0	2	120	0,2344
1	2	157	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	438	2,5664
18	6	466	2,7305
19	6	517	3,0293
20	6	567	3,3223
21	6	616	3,6094
22	6	666	3,9023
23	6	719	4,2129
24	6	772	4,5234
25	6	822	4,8164
26	6	873	5,1152
27	6	910	5,3320

(fortgesetzt)

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
28	6	948	5,5547
29	2	Reserviert	
30	4	Reserviert	
31	6	Reserviert	

5

10

Tabelle 2

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
0	2	120	0,2344
1	2	193	0,3770
2	2	308	0,6016
3	2	449	0,8770
4	2	602	1,1758
5	4	378	1,4766
6	4	434	1,6953
7	4	490	1,9141
8	4	553	2,1602
9	4	616	2,4063
10	4	658	2,5703
11	6	466	2,7305
12	6	517	3,0293
13	6	567	3,3223
14	6	616	3,6094
15	6	666	3,9023
16	6	719	4,2129
17	6	772	4,5234
18	6	822	4,8164
19	6	873	5,1152
20	8	682,5	5,3320
21	8	711	5,5547
22	8	754	5,8906
23	8	797	6,2266
24	8	841	6,5703
25	8	885	6,9141
26	8	916,5	7,1602
27	8	948	7,4063
28	2	Reserviert	
29	4	Reserviert	

15

20

25

30

35

40

45

50

55

(fortgesetzt)

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
30	6	Reserviert	
31	8	Reserviert	

Tabelle 3

MCS-Index	Ordnung der Modulation	Soll-Coderate $\times 1024$	Spektrale Effizienz
0	q	$240/q$	0,2344
1	q	$314/q$	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	466	2,7305
18	6	517	3,0293
19	6	567	3,3223
20	6	616	3,6094
21	6	666	3,9023
22	6	719	4,2129
23	6	772	4,5234
24	6	822	4,8164
25	6	873	5,1152
26	6	910	5,3320
27	6	948	5,5547
28	1	Reserviert	
29	2	Reserviert	
30	4	Reserviert	
31	6	Reserviert	

12. Verfahren nach Anspruch 9, wobei

eine Coderate des zweiten Teils der Kanalzustandsinformationen nicht höher als eine Schwellenwert-Coderate ist; oder

5 eine Coderate des zweiten Teils der Kanalzustandsinformationen höher als eine Schwellenwert-Coderate ist und die Endgerätevorrichtung einige Informationen in dem zweiten Teil der Kanalzustandsinformationen basierend auf einer Priorität ablegt, wobei

10 die Schwellenwert-Coderate ein Verhältnis der ersten Coderate zu einem Coderatenkompensationsparameter des zweiten Teils der Kanalzustandsinformationen ist.

13. Endgeräteinrichtung, wobei die Einrichtung konfiguriert ist, um das Verfahren nach einem der Ansprüche 1 bis 6 durchzuführen.

14. Basisstationskommunikationseinrichtung, wobei die

15 Basisstationskommunikationseinrichtung konfiguriert ist, um das Verfahren nach einem der Ansprüche 7 bis 12 durchzuführen.

15. Computerprogrammprodukt, das Anweisungen umfasst, die wenn sie durch einen Computer ausgeführt werden, den Computer veranlassen, das Verfahren nach einem der Ansprüche 1 bis 6 oder einem Ansprüche 7 bis 12 durchzuführen.

Revendications

25 1. Procédé d'envoi d'informations de liaison montante effectué par un dispositif terminal, le procédé comprenant :

la réception de premières informations de commande de liaison descendante par l'intermédiaire d'un canal de commande de liaison descendante physique en provenance d'une station de base, dans lequel les premières informations de commande de liaison descendante sont utilisées pour programmer un canal partagé de liaison montante physique, les premières informations de commande de liaison descendante comprennent des premières informations d'indication et des secondes informations d'indication, les premières informations d'indication indiquent que le canal partagé de liaison montante physique est utilisé pour envoyer des informations de commande de liaison montante, mais n'est pas utilisé pour envoyer des données, et les secondes informations d'indication indiquent un index de schéma de modulation et de codage du canal partagé de liaison montante physique ;

30 35 la détermination (23), sur la base des premières informations d'indication, du fait que le canal partagé de liaison montante physique est utilisé pour envoyer des informations de commande de liaison montante sans données, la détermination d'un premier débit de code du canal partagé de liaison montante physique et d'un ordre de modulation du canal partagé de liaison montante physique sur la base des secondes informations d'indication ; et l'envoi (24) de premières informations de commande de liaison montante à la station de base par l'intermédiaire du canal partagé de liaison montante, dans lequel les premières informations de commande de liaison montante comprennent une demande d'accusé de réception de répétition automatique hybride, dans lequel :

40 45 une quantité totale d'éléments de ressource dans le canal partagé de liaison montante physique qui sont utilisés pour transporter les premières informations de commande de liaison montante est M, et une quantité d'éléments de ressource dans le canal partagé de liaison montante physique qui sont utilisés pour transporter l'accusé de réception de demande de répétition automatique hybride est une valeur minimale d'une première quantité et de la quantité totale M, dans lequel la première quantité est égale à une valeur arrondie d'un rapport d'un premier produit à un deuxième produit, dans lequel le premier produit est un produit d'une taille de données utiles de l'accusé de réception de demande de répétition automatique hybride et d'un paramètre de compensation de débit de code de l'accusé de réception de demande de répétition automatique hybride, et le deuxième produit est un produit du premier débit de code et de l'ordre de modulation.

50 55 2. Procédé selon la revendication 1, dans lequel les premières informations de commande de liaison montante comprennent en outre une première partie d'informations d'état de canal, une quantité d'éléments de ressource qui se trouvent dans le canal partagé de liaison montante physique et sont utilisés pour transporter la première partie des informations d'état de canal est une valeur minimale d'une seconde quantité et d'une quantité restante, dans lequel la quantité restante est égale à la quantité totale M moins la quantité des éléments de ressource utilisés pour transporter l'accusé de réception de demande de répétition automatique hybride, et la seconde quantité est égale

à une valeur arrondie d'un rapport d'un troisième produit au deuxième produit, dans lequel le troisième produit est un produit d'une taille de données utiles de la première partie des informations d'état de canal et d'un paramètre de compensation de débit de code de la première partie des informations d'état de canal.

5 3. Procédé selon la revendication 2, dans lequel les premières informations de commande de liaison montante comprennent en outre une seconde partie des informations d'état de canal, une quantité d'éléments de ressource qui se trouvent dans le canal partagé de liaison montante physique et sont utilisés pour transporter la seconde partie des informations d'état de canal est égale à la quantité totale M moins la quantité des éléments de ressource utilisés pour transporter l'accusé de réception de demande de répétition automatique hybride et moins la quantité des éléments de ressource utilisés pour transporter la première partie des informations d'état de canal.

10 4. Procédé selon la revendication 1, dans lequel le premier débit de code et l'ordre de modulation sont déterminés sur la base d'un index de schéma de modulation et de codage compris dans les premières informations de commande de liaison descendante.

15 5. Procédé selon la revendication 4, dans lequel une correspondance entre l'index de schéma de modulation et de codage, le premier débit de code, et l'ordre de modulation satisfait à une correspondance définie dans l'un des tableaux suivants :

Tableau 1

Index MCS	Ordre de modulation	Débit de code cible × 1024	Efficacité spectrale
0	2	120	0,2344
1	2	157	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	438	2,5664
18	6	466	2,7305
19	6	517	3,0293
20	6	567	3,3223
21	6	616	3,6094
22	6	666	3,9023
23	6	719	4,2129
24	6	772	4,5234

(suite)

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
25	6	822	4,8164
26	6	873	5,1152
27	6	910	5,3320
28	6	948	5,5547
29	2	Réserve	
30	4	Réserve	
31	6	Réserve	

5

10

15

20

25

30

35

40

45

50

55

Tableau 2

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
0	2	120	0,2344
1	2	193	0,3770
2	2	308	0,6016
3	2	449	0,8770
4	2	602	1,1758
5	4	378	1,4766
6	4	434	1,6953
7	4	490	1,9141
8	4	553	2,1602
9	4	616	2,4063
10	4	658	2,5703
11	6	466	2,7305
12	6	517	3,0293
13	6	567	3,3223
14	6	616	3,6094
15	6	666	3,9023
16	6	719	4,2129
17	6	772	4,5234
18	6	822	4,8164
19	6	873	5,1152
20	8	682,5	5,3320
21	8	711	5,5547
22	8	754	5,8906
23	8	797	6,2266
24	8	841	6,5703
25	8	885	6,9141
26	8	916,5	7,1602

(suite)

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
27	8	948	7,4063
28	2	Réservé	
29	4	Réservé	
30	6	Réservé	
31	8	Réservé	

Tableau 3

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
0	q	$240/q$	0,2344
1	q	$314/q$	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	466	2,7305
18	6	517	3,0293
19	6	567	3,3223
20	6	616	3,6094
21	6	666	3,9023
22	6	719	4,2129
23	6	772	4,5234
24	6	822	4,8164
25	6	873	5,1152
26	6	910	5,3320
27	6	948	5,5547
28	1	Réservé	

(suite)

Index MCS	Ordre de modulation	Débit de code cible × 1024	Efficacité spectrale
29	2	Réservé	
30	4	Réservé	
31	6	Réservé	

5 10 6. Procédé selon la revendication 3, dans lequel

un débit de code de la seconde partie des informations d'état de canal n'est pas supérieur à un débit de code seuil ; ou

15 un débit de code de la seconde partie des informations d'état de canal est supérieur à un débit de code seuil, et le dispositif terminal abandonne certaines informations dans la seconde partie des informations d'état de canal sur la base d'une priorité, dans lequel
le débit de code seuil est un rapport du premier débit de code à un paramètre de compensation de débit de code de la seconde partie des informations d'état de canal.

20 7. Procédé de réception d'informations de commande de liaison montante effectué par une station de base, le procédé comprenant :

25 l'envoi (22) de premières informations de commande de liaison descendante par l'intermédiaire d'un canal de commande de liaison descendante physique à un dispositif terminal, dans lequel les premières informations de commande de liaison descendante sont utilisées pour programmer un canal partagé de liaison montante physique, les premières informations de commande de liaison descendante comprennent des premières informations d'indication et des secondes informations d'indication, les premières informations d'indication indiquent que le canal partagé de liaison montante physique est utilisé pour envoyer des informations de commande de liaison montante, mais n'est pas utilisé pour envoyer des données, et les secondes informations d'indication indiquent un index de schéma de modulation et de codage du canal partagé de liaison montante physique ; et la réception, par l'intermédiaire du canal partagé de liaison montante physique, de premières informations de commande de liaison montante en provenance du dispositif terminal, dans lequel les premières informations de commande de liaison montante comprennent une demande d'accusé de réception de répétition automatique hybride,

30 35 dans lequel une quantité totale d'éléments de ressource dans le canal partagé de liaison montante physique qui sont utilisés pour transporter les premières informations de commande de liaison montante est M, et une quantité d'éléments de ressource dans le canal partagé de liaison montante physique qui sont utilisés pour transporter l'accusé de réception de demande de répétition automatique hybride est une valeur minimale d'une première quantité et de la quantité totale M, dans lequel la première quantité est égale à une valeur arrondie d'un rapport d'un premier produit à un deuxième produit, dans lequel le premier produit est un produit d'une taille de données utiles de l'accusé de réception de demande de répétition automatique hybride et d'un paramètre de compensation de débit de code de l'accusé de réception de demande de répétition automatique hybride, et le deuxième produit est un produit d'un premier débit de code et d'un ordre de modulation.

40 45 8. Procédé selon la revendication 7, dans lequel les premières informations de commande de liaison montante comprennent en outre une première partie d'informations d'état de canal, une quantité d'éléments de ressource qui se trouvent dans le canal partagé de liaison montante physique et sont utilisés pour transporter la première partie des informations d'état de canal est une valeur minimale d'une seconde quantité et d'une quantité restante, dans lequel la quantité restante est égale à la quantité totale M moins la quantité des éléments de ressource utilisés pour transporter l'accusé de réception de demande de répétition automatique hybride, et la seconde quantité est égale à une valeur arrondie d'un rapport d'un troisième produit au deuxième produit, dans lequel le troisième produit est un produit d'une taille de données utiles de la première partie des informations d'état de canal et d'un paramètre de compensation de débit de code de la première partie des informations d'état de canal.

50 55 9. Procédé selon la revendication 8, dans lequel les premières informations de commande de liaison montante comprennent en outre une seconde partie des informations d'état de canal, une quantité d'éléments de ressource qui se trouvent dans le canal partagé de liaison montante physique et sont utilisés pour transporter la seconde partie

des informations d'état de canal est égale à la quantité totale M moins la quantité des éléments de ressource utilisés pour transporter l'accusé de réception de demande de répétition automatique hybride et moins la quantité des éléments de ressource utilisés pour transporter la première partie des informations d'état de canal.

5 10. Procédé selon la revendication 7, dans lequel le premier débit de code et l'ordre de modulation sont déterminés sur la base d'un index de schéma de modulation et de codage compris dans les premières informations de commande de liaison descendante.

10 11. Procédé selon la revendication 10, dans lequel une correspondance entre l'index de schéma de modulation et de codage, le premier débit de code et l'ordre de modulation satisfait à une correspondance définie dans l'un des tableaux suivants :

Tableau 1

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
0	2	120	0,2344
1	2	157	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	438	2,5664
18	6	466	2,7305
19	6	517	3,0293
20	6	567	3,3223
21	6	616	3,6094
22	6	666	3,9023
23	6	719	4,2129
24	6	772	4,5234
25	6	822	4,8164
26	6	873	5,1152
27	6	910	5,3320
28	6	948	5,5547
29	2	Réserve	

(suite)

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
30	4	Réserve	
31	6	Réserve	

Tableau 2

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
0	2	120	0,2344
1	2	193	0,3770
2	2	308	0,6016
3	2	449	0,8770
4	2	602	1,1758
5	4	378	1,4766
6	4	434	1,6953
7	4	490	1,9141
8	4	553	2,1602
9	4	616	2,4063
10	4	658	2,5703
11	6	466	2,7305
12	6	517	3,0293
13	6	567	3,3223
14	6	616	3,6094
15	6	666	3,9023
16	6	719	4,2129
17	6	772	4,5234
18	6	822	4,8164
19	6	873	5,1152
20	8	682,5	5,3320
21	8	711	5,5547
22	8	754	5,8906
23	8	797	6,2266
24	8	841	6,5703
25	8	885	6,9141
26	8	916,5	7,1602
27	8	948	7,4063
28	2	Réserve	
29	4	Réserve	
30	6	Réserve	
31	8	Réserve	

Tableau 3

Index MCS	Ordre de modulation	Débit de code cible $\times 1024$	Efficacité spectrale
0	q	240/ q	0,2344
1	q	314/ q	0,3066
2	2	193	0,3770
3	2	251	0,4902
4	2	308	0,6016
5	2	379	0,7402
6	2	449	0,8770
7	2	526	1,0273
8	2	602	1,1758
9	2	679	1,3262
10	4	340	1,3281
11	4	378	1,4766
12	4	434	1,6953
13	4	490	1,9141
14	4	553	2,1602
15	4	616	2,4063
16	4	658	2,5703
17	6	466	2,7305
18	6	517	3,0293
19	6	567	3,3223
20	6	616	3,6094
21	6	666	3,9023
22	6	719	4,2129
23	6	772	4,5234
24	6	822	4,8164
25	6	873	5,1152
26	6	910	5,3320
27	6	948	5,5547
28	1	Réservé	
29	2	Réservé	
30	4	Réservé	
31	6	Réservé	

12. Procédé selon la revendication 9, dans lequel

55 un débit de code de la seconde partie des informations d'état de canal n'est pas supérieur à un débit de code seuil ; ou

un débit de code de la seconde partie des informations d'état de canal est supérieur à un débit de code seuil, et le dispositif terminal abandonne certaines informations dans la seconde partie des informations d'état de

canal sur la base d'une priorité, dans lequel

le débit de code seuil est un rapport du premier débit de code à un paramètre de compensation de débit de code de la seconde partie des informations d'état de canal.

5 **13.** Appareil de dispositif de communication, dans lequel l'appareil est configuré pour effectuer le procédé selon l'une quelconque des revendications 1 à 6.

10 **14.** Appareil de communication de station de base, dans lequel l'appareil de communication est configuré pour effectuer le procédé selon l'une quelconque des revendications 7 à 12.

15 **15.** Produit-programme informatique, comprenant des instructions qui, lorsqu'elles sont exécutées par un ordinateur, amènent l'ordinateur à effectuer le procédé selon l'une quelconque des revendications 1 à 6 ou l'une quelconque des revendications 7 à 12.

15

20

25

30

35

40

45

50

55




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 20150249984 A1 [0004]
- US 20110299484 A1 [0007]
- WO 2018038758 A1 [0008]
- CN 107801246 A [0009]
- US 20180020429 A1 [0010]