(19)

## (11) **EP 4 188 023 A8**

## (12) CORRECTED EUROPEAN PATENT APPLICATION

(15) Correction information:

Corrected version no 1 (W1 A1) Corrections, see Bibliography INID code(s) 62

(48) Corrigendum issued on: 19.07.2023 Bulletin 2023/29

(43) Date of publication: **31.05.2023 Bulletin 2023/22** 

(21) Application number: 23152669.0

(22) Date of filing: 09.08.2019

(51) International Patent Classification (IPC):

H04W 72/12 (2023.01)
H04L 1/18 (2023.01)
H04W 72/04 (2023.01)
H04L 1/12 (2006.01)
H04L 1/1867 (2023.01)
H04L 1/1607 (2023.01)

H04W 74/08 (2009.01) H04L 5/00 (2006.01) H04L 1/16 (2023.01) H04L 1/1829 (2023.01) H04L 1/1822 (2023.01)

(52) Cooperative Patent Classification (CPC):

H04L 5/0055; H04L 1/1614; H04L 1/1664; H04L 1/1685; H04L 1/1822; H04L 1/1854; H04L 1/1896; H04L 1/0026; H04L 2001/125

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

(30) Priority: 09.08.2018 US 201862716978 P 11.01.2019 KR 20190004181 24.01.2019 KR 20190009388 15.02.2019 KR 20190017657 29.03.2019 KR 20190036829

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC: 19846021.4 / 3 817 494

(71) Applicant: LG Electronics, Inc. Yeongdeungpo-gu Seoul 07336 (KR) (72) Inventors:

 YANG, Suckchel 06772 Seoul (KR)

 KIM, Seonwook 06772 Seoul (KR)

 PARK, Hanjun 06772 Seoul (KR)

(74) Representative: Katérle, Axel Wuesthoff & Wuesthoff Patentanwälte PartG mbB Schweigerstraße 2 81541 München (DE)

## Remarks:

This application was filed on 20-01-2023 as a divisional application to the application mentioned under INID code 62.

## (54) METHOD AND APPARATUS FOR TRANSMITTING AND RECEIVING WIRELESS SIGNAL IN WIRELESS COMMUNICATION SYSTEM

The present invention relates to a wireless communication system and, specifically, to a method comprising the steps of transmitting first A/N information; receiving one or more data after transmitting the first A/N information; receiving downlink control information including a 1-bit indicator; and transmitting second A/N information including an A/N result for the one or more data depending on whether the 1-bit indicator is toggled, and to an apparatus therefor, wherein the second A/N information is generated by reflecting only a data reception state after the transmission of the first A/N information, on the basis of a case where the 1-bit indicator has been toggled; and the second A/N information is generated in consideration of (i) the first A/N information and (ii) the data reception state after the transmission of the first A/N information, on the basis of a case where the 1-bit indicator has not been toggled.

EP 4 188 023 A8

FIG. 17

