



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
28.06.2023 Bulletin 2023/26

(51) International Patent Classification (IPC):
F21V 1/00 ^(2006.01) **F21V 17/02** ^(2006.01)
F21V 33/00 ^(2006.01) **A61L 9/03** ^(2006.01)
F21V 17/10 ^(2006.01)

(21) Application number: **22209943.4**

(22) Date of filing: **10.08.2021**

(52) Cooperative Patent Classification (CPC):
F21V 1/00; F21V 17/02; F21V 33/0004;
F21V 17/10; F21V 17/105

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR

(30) Priority: **21.08.2020 SK 500822020 U**

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
21190637.5 / 3 957 903

(71) Applicant: **Pipta, Jaroslav**
073 01 Sobrance (SK)

(72) Inventor: **Pipta, Jaroslav**
073 01 Sobrance (SK)

(74) Representative: **Cechvalova, Dagmar**
invent
Patent & Trademark Agency
Palisady 50
811 06 Bratislava (SK)

Remarks:

This application was filed on 28-11-2022 as a
divisional application to the application mentioned
under INID code 62.

(54) **AN ADJUSTABLE FASTENING MECHANISM OF THE THERMAL VAPORATOR FOR THE SHADE OF THE LIGHT SOURCE**

(57) The present invention is directed to an adjustable fastening mechanism of a thermal evaporator for a light source shade, comprising a base (1) with an optional aperture (6) having fastening components (2) for attachment of the shade, the base (1) also comprising adjustable fastening components (7) for changing the distance of the dish of the thermal evaporator from the light source. The adjustable fastening components (7) are formed by at least two coulisses or sliders (7.1), each having a longitudinal groove (7.2) with a set of adjoining sloping grooves (7.3), and wherein a horizontally oriented adjustable dish holder (7.4) with at least two stones or studs (7.5) fitting into the sloping grooves (7.3) is located between the coulisses (7.1). The adjustable dish holder (7.4) has an operating handle (7.6). The fastening components (2) for attachment of the shade are length-adjustable telescopically with a spring. The fastening components (2) for attachment of the shade have terminal fastening elements (3), which may be hooks, clamps, screws, or magnets.




Fig. 5

Description

Technical field of the invention

[0001] The invention relates to such construction of the adjustable fastening mechanism of the thermal evaporator for the shade of the light source, where the intensity of evaporation depends on the mutual distance of the thermal evaporator from the light source. The invention falls into the area of useful interior accessories.

Background of the invention

[0002] Scented lamps, evaporators and water diffusers with possibly fragrant oils are currently common decorative and useful accessories for interiors and especially households. Thermal water evaporators based on various heat sources are known from state of the art, such as e.g. paraffin or oil burner, catalytic source, hot stones or light bulb, which results in their applicability in households, offices, saunas, etc. Scented lamps are largely based on a heat source which is a paraffin or oil burner. Water diffusers, possibly containing fragrant oils, are based on blowing a cold water vapour.

[0003] The solution described in document US 6328935 B1 is known in the state of the art, wherein the aroma batcher comprises the flame source for providing heat, the open, porous annular ceramic substrate adapted to absorb and reversibly retain an amount of at least one aromatic fluid therein and the support structure for maintaining the porous substrate in the coaxial distance above each other from the flame source. The heat generated by the flame source induces a retained aromatic fluid in the substrate to dissipate into the ambient air. The supporting structure is the vertical telescopic rod element locked by screws that manipulate the height of the annular ceramic substrate with the contained aromatic fluid.

[0004] Another solution from the state of the art described in document DE 29807474 U, where the aroma dish is attached firmly above the heat source and the height of the heat source itself is adjusted on vertical rods.

[0005] Another solution from the state of the art described in document JP 3175002 U, where an aroma dish is inserted into the tight hole in the lamp shade above the heat source without the possibility of height adjustment of the distance of the heat source from the heat evaporator dish.

[0006] The Korean patent document KR101895189 B1, British patent document GB404770 A, the Korean patent document KR2016 0028698 A and the US patent document US4493011A from the state of art disclose an adjustable fastening mechanism of a thermal evaporator for a light source shade, comprising a base with fastening components for the shade and adjustable fastening components for the thermal evaporator dish.

[0007] The deficiencies of the existing solutions described above are that the heat sources are primarily open flame burners, which do not guarantee sufficient

protection against possible fire in the event of the lamp tipping over. Also, the adjustment constructions, which change the mutual distance of the heat source from the axes of the heat evaporator dish, are open on the outside and do not have to match the design with the interior where the evaporator is located. In some solutions, the height adjustment of the mutual distance of the heat source from the axis of the heat evaporator dish requires performing the operations on several adjustment elements, which makes the handling more complicated.

Summary of the invention

[0008] The shortcomings in the state of the art in the field of thermal fragrance lamp evaporators are solved by the proposed construction of the adjustable fastening mechanism of the thermal evaporator for the light source shade, the essence of which lies in the fact that it consists of the base with the possible sight glass. The base can have different geometric shapes. It is a shape e.g. ring, disc. They are fixed to the base e.g. by means of screws, fastening components e.g. in the shape of rods. By means of these fastening members, the base is fastened to the shade via the terminal fastening elements, which can be hooks or clamps, or pliers, screws, or magnets. It is advantageous to fasten the base to the shade in the upper part of the shade. However, the base can also be fixed under the light source and attached to the shade. Furthermore, the base also has adjustable fastening components for changing the distance of the dish of the thermal evaporator from the light source in order to change the intensity of evaporation. The adjustable fastening components for changing the distance of the dish of the thermal evaporator from the light source are of the construction which is formed by at least two coulisses that are arranged parallel on the sides of the base and are also fastened by screws. Each coulisse of the adjustable fastening component has a longitudinal groove with the set of adjoining sloping grooves. The adjustable dish holder with at least two stones fitting into the sloping grooves in one plane is located between the coulisses. The dish holder is also not limited in shape, in this case, it is the coarse solid wire formed into a circle, but it can also be e.g. a short tube in height or simply a surface capable of carrying the dish. From the point of view of stability, it is advantageous to use three coulisses with three stones. The construction with two coulisses and two stones is also used. In order to facilitate handling during the height adjustment of the dish, the adjustable dish holder has the attached control handle as the holder, which can alternatively be attached also to the stones. The control handle can be used in the construction, but the adjustable dish holder can also be without the handle.

[0009] Another essential feature of the solution according to the invention is the possibility of flexible attachment of the fastening components to the shade of the light source of different diameters and from different manufacturers. This is achieved in that the fastening compo-

nents of the light source shade holder are adjustable in length. This can be realized e.g. by telescopic rods with spring.

[0010] The advantages of the adjustable fastening mechanism of the thermal evaporator for the light source shade according to the invention are evident from its effects, which are shown externally. The effects and originality of the present construction lie in the fact that it is safe because it does not use an open flame. The heat source is the light source e.g. from a tungsten filament lamp or a halogen lamp or an LED light source.

Evaporation intensity control is provided by the simple mechanism with manual adjustment of the thermal evaporator dish above the light source. It is also universal, as it can be attached to various light source shades with the use of length-adjustable fastening components. To change the relative position between the heat source and the thermal evaporator, a smaller number of actions is also required compared to other state-of-the-art solutions and is, therefore, faster and easier overall.

Overview of figures in the drawings

[0011] The adjustable fastening mechanism of the thermal evaporator for the light source shade according to the invention is shown in the drawings, wherein Fig. 1 is a view of the base with the sight glass and shade fastening components. Fig. 2 and 3 show an exploded view of two components of the adjustable fastening components for changing the distance of the dish of the thermal evaporator from the light source. Fig. 4 is a view of the complete adjustable fastening component for changing the distance of the dish of the thermal evaporator from the light source. Fig. 5 and 6 are views of the assembled adjustable evaporator fastening mechanism for the light source shade. Fig. 7 is a view of the adjustable fastening mechanism of the thermal evaporator applied in the shade of the light source.

Example of embodiments of the invention

[0012] It is understood that the individual embodiments according to the invention are presented for illustration and not as limitations of the invention. Those skilled in the art will find, or be able to ascertain using no more than routine experimentation, many equivalents to specific embodiments of the invention. Such equivalents will also fall within the scope of the protection claims. For those skilled in the state of the art, it cannot be a problem of optimal design of construction, so these features have not been addressed in detail.

Example 1

[0013] In this example of the specific embodiment of the subject of the invention, the construction of the adjustable fastening mechanism of the thermal evaporator for the light source shade 8 is described, as shown in

Fig. 2 to 6. It consists of the base 1 with the aperture 6. Base 1 has the shape of a ring. Rod-shaped fastening components 2 are fastened to the base 1 by means of screws 4. By means of these fastening components 2, the base 1 is fastened to the shade 8 via the terminal fastening elements 3, which are hooks. Alternatively, they are clamps, pins, screws or magnets, and others. Base 1 also has adjustable fastening components 7 for changing the distance of the dish of the thermal evaporator from the light source. The adjustable fastening components 7 for changing the distance of the dish of the thermal evaporator from the light source are formed by two coulisses 7.1 which are arranged vertically opposite each other on opposite sides of the base 1 and are also fastened by screws 5. Each coulisse 7.1 of the adjustable fastening component 7 has the vertical longitudinal groove 7.2 with the system of adjoining sloping grooves 7.3. Between the coulisses 7.1 there is the horizontally oriented adjustable dish holder 7.4 with two stones 7.5 on opposite sides fitting into the sloping grooves 7.3 in one plane. The dish holder 7.4 is the coarse solid wire formed into the circle.

[0014] In an alternative embodiment, the base 1 is without the sight glass, it is the disc solid body. In another alternative embodiment, the adjustable fastening components 7 for changing the distance of the dish of the thermal evaporator from the light source are formed by three coulisses 7.1 which are arranged vertically on the sides of the base 1 and are also fastened by screws 5. Also, the adjustable dish holder 7.4 has three stones 7.5 fitting into the sloping grooves 7.3 of three coulisses 7.1. The dish holder 7.4 is alternatively made as a bounded planar structure with a rebate, which is not shown in any figure.

Example 2

[0015] In this example of a specific embodiment of the subject of the invention, the improved construction of the adjustable fastening mechanism of the thermal evaporator for the light source shade 8 is described, as shown in Figs. 2 to 6 and as described in Example 1. However, there is an addition where an adjustable holder 7.4 of the dish is attached to the operating handle 7.6, which can be also alternatively attached to the stones 7.5. The operating handle 7.6 further simplifies the handling with the whole mechanism.

Example 3

[0016] In this example of the specific embodiment of the subject of the invention, another improved construction of the adjustable fastening mechanism of the thermal evaporator for the light source shade 8 is described, as shown in Figs. 2 to 6 and as described in Examples 1 and 2. However, there is such completion, where the fastening components 2 of the light source shade 8 holder are adjustable in length. This is realized by telescopic

rods with spring, which simplifies the whole adjustment process. The fastening of the base 1 to the shade 8 is in the upper part of the shade 8 as shown in Fig. 7.

[0017] In an alternative embodiment, the attachment of the base 1 to the shade 8 is in the lower part of the shade 8, which is not shown in any figure. An analogous fastening of the base 1 in the lower part of the shade 8 is also possible in other embodiments. It is thus possible to optimally adapt the fastening of the base 1 to the orientation of the shade 8, resp. light source and thus influence, for example, the required intensity of evaporation or other technical and aesthetic parameters.

Industrial applicability

[0018] The adjustable fastening mechanism of the thermal evaporator for the light source shade according to this invention are intended for the area of useful interior accessories.

Claims

1. An adjustable fastening mechanism of a thermal evaporator for a light source shade, comprising a base (1) having length-adjustable fastening components (2) of the shade attachment, wherein the base (1) also having adjustable fastening components (7) for changing the distance of a thermal evaporator dish from a light source, **characterized in that** the adjustable fastening components (7) for changing the distance of the thermal evaporator dish from the light source are formed by at least two coulisses (7.1), where each having a longitudinal groove (7.2) with a set of adjoining sloping grooves (7.3), wherein an adjustable dish holder (7.4) with at least two stones (7.5) fitting into the sloping grooves (7.3) between the coulisses (7.1).
2. An adjustable fastening mechanism of a thermal evaporator for a light source shade according to claim 1, **characterized in that** the adjustable dish holder (7.4) has an operating handle (7.6).




Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7



EUROPEAN SEARCH REPORT

Application Number

EP 22 20 9943

5

10

15

20

25

30

35

40

45

50

55

1

EPO FORM 1503 03:82 (P04C01)

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
A	KR 101 895 189 B1 (LEE JUN SIC [KR]; KIM IK HWAN [KR] ET AL.) 4 September 2018 (2018-09-04) * paragraph [0024] * * paragraph [0033] - paragraph [0063] * * figures 1-5 *	1, 2	INV. F21V1/00 F21V17/02 F21V33/00 A61L9/03
A	GB 404 770 A (LEHRS GEORGE EDWARD [GB]) 25 January 1934 (1934-01-25) * the whole document *	1, 2	ADD. F21V17/10
A	KR 2016 0028698 A (JEONG GEUN YOUNG [KR]; YOO SEUNG WON [KR]) 14 March 2016 (2016-03-14) * paragraph [0013] - paragraph [0035] * * figures 1, 2 *	1, 2	
A	US 4 493 011 A (SPECTOR DONALD [US]) 8 January 1985 (1985-01-08) * the whole document *	1, 2	
A	US 2014/118992 A1 (HSIAO MING JEN [VG]) 1 May 2014 (2014-05-01) * the whole document *	1, 2	TECHNICAL FIELDS SEARCHED (IPC) A61L F21V
A	CN 201 814 892 U (WENBO HAN) 4 May 2011 (2011-05-04) * the whole document *	1, 2	
The present search report has been drawn up for all claims			
Place of search The Hague		Date of completion of the search 11 May 2023	Examiner Soto Salvador, Jesús
CATEGORY OF CITED DOCUMENTS X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 22 20 9943

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

11-05-2023

10	Patent document cited in search report	Publication date	Patent family member(s)	Publication date
	KR 101895189 B1	04-09-2018	NONE	

15	GB 404770 A	25-01-1934	NONE	

	KR 20160028698 A	14-03-2016	NONE	

	US 4493011 A	08-01-1985	NONE	

20	US 2014118992 A1	01-05-2014	NONE	

	CN 201814892 U	04-05-2011	NONE	

25				
30				
35				
40				
45				
50				
55				

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 6328935 B1 [0003]
- DE 29807474 U [0004]
- JP 3175002 U [0005]
- KR 101895189 B1 [0006]
- GB 404770 A [0006]
- KR 20160028698 A [0006]
- US 4493011 A [0006]