



(11) **EP 4 265 771 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
25.10.2023 Bulletin 2023/43

(21) Application number: **21906930.9**

(22) Date of filing: **01.12.2021**

(51) International Patent Classification (IPC):
C22C 38/04 (2006.01) **C22C 38/02** (2006.01)
C22C 38/06 (2006.01) **C22C 38/00** (2006.01)
C21D 9/46 (2006.01) **C21D 8/02** (2006.01)

(52) Cooperative Patent Classification (CPC):
C21D 8/02; C21D 9/46; C22C 38/00; C22C 38/02;
C22C 38/04; C22C 38/06

(86) International application number:
PCT/KR2021/017992

(87) International publication number:
WO 2022/131625 (23.06.2022 Gazette 2022/25)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(30) Priority: **17.12.2020 KR 20200177516**

(71) Applicant: **POSCO Co., Ltd**
Pohang-si, Gyeongsangbuk-do 37859 (KR)

(72) Inventors:
• **LEE, Jae-Hoon**
Gwangyang-si, Jeollanam-do 57807 (KR)
• **IM, Young-Roc**
Gwangyang-si, Jeollanam-do 57807 (KR)

(74) Representative: **Meissner Bolte Partnerschaft**
mbB
Patentanwälte Rechtsanwälte
Postfach 86 06 24
81633 München (DE)

(54) **HIGH STRENGTH STEEL SHEET HAVING EXCELLENT WORKABILITY AND METHOD FOR MANUFACTURING SAME**

(57) The present invention relates to a steel sheet which can be used for automobile parts and the like, and relates to a steel sheet and a method for manufacturing same, the steel sheet having an excellent balance be-

tween strength and ductility, an excellent balance between strength and hole expansion properties, and an excellent yield ratio evaluation score.

EP 4 265 771 A1

Description

[Technical Field]

5 **[0001]** The present invention relates to a steel sheet that may be used for automobile parts and the like, and to a steel sheet having high strength characteristics and excellent workability and a method for manufacturing the same.

[Background Art]

10 **[0002]** In recent years, the automobile industry has been paying attention to ways to reduce material weight in an effort to protect the global environment and secure occupant safety. In order to meet these requirements for safety and weight reduction, the use of a high strength steel sheet is rapidly increasing. In general, it is commonly known that as the strength of the steel sheet increases, the workability of the steel sheet is lowered. Therefore, in a steel sheet for automobile parts, a steel sheet having excellent workability represented by ductility, a hole expansion ratio, and the like, while having high strength characteristics is required.

15 **[0003]** Since transformation induced plasticity (TRIP) steel, using transformation-induced plasticity of retained austenite, has a complex microstructure consisting of ferrite, bainite, martensite, retained austenite, and the like, it is known as having a certain level or more of workability, as well as high strength characteristics.

20 **[0004]** As a technique for further improving the workability of a steel sheet, a method of utilizing tempered martensite is disclosed in Patent Documents 1 and 2. Since tempered martensite made by tempering hard martensite is softened martensite, there is a difference in strength between tempered martensite and existing untempered martensite (fresh martensite). Therefore, when fresh martensite is suppressed and tempered martensite is formed, the workability may increase.

25 **[0005]** However, by the techniques disclosed in Patent Documents 1 and 2, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation does not satisfy the range of $3.0 \cdot 10^6$ to $6.2 \cdot 10^6$ ($MPa^2\%^{1/2}$), meaning that it is difficult to secure a steel sheet having both of excellent strength and excellent ductility.

30 **[0006]** Meanwhile, as another technique for improving workability of a steel sheet, Patent Document 3 discloses a method for inducing generation of bainite by means of adding boron (B). In the case of adding boron (B), a ferrite-pearlite transformation is suppressed, while generation of bainite is induced, whereby coexistence of strength and workability can be achieved.

35 **[0007]** However, by the technique disclosed in Patent Document 3, a balance (B_{TE}) of tensile strength and elongation of $3.0 \cdot 10^6$ to $6.2 \cdot 10^6$ ($MPa^2\%^{1/2}$), a balance (B_{TH}) of tensile strength and a hole expansion ratio of $6.0 \cdot 10^6$ to $11.5 \cdot 10^6$ ($MPa^2\%^{1/2}$), and a yield ratio evaluation index (I_{YR}) of 0.15 to 0.42 cannot be secured at the same time, thereby meaning it is difficult to secure a steel sheet having all of excellent strength, an excellent hole expansion ratio, excellent ductility, and an excellent yield ratio.

[0008] That is, a demand for a steel sheet having all of an excellent balance (B_{TE}) of tensile strength and elongation, an excellent balance (B_{TH}) of tensile strength and a hole expansion ratio, and an excellent yield ratio evaluation index (I_{YR}) is not satisfied.

40 (Related Art Document)

[0009]

(Patent Document 1) Korean Laid-Open Patent Publication No. 10-2006-0118602

45 (Patent Document 2) Japanese Laid-Open Patent Publication No. 2009-019258

(Patent Document 3) Japanese Laid-Open Patent Publication No. 2016-216808

[Disclosure]

50 [Technical Problem]

[0010] According to an aspect of the present invention, a steel sheet having all of an excellent balance of tensile strength and elongation, an excellent balance of tensile strength and a hole expansion ratio, and an excellent yield ratio evaluation index and a method manufacturing the same can be provided, by optimizing a composition and microstructures of the steel sheet.

55 **[0011]** An object of the present invention is not limited to the abovementioned contents. Additional objects of the present invention are described in the overall content of the specification, and those of ordinary skill in the art to which the present invention pertains will have no difficulty in understanding the additional objects of the present invention from

the contents described in the specification of the present invention.

[Technical Solution]

[0012] In an aspect of the present invention, a high strength steel sheet having excellent workability may comprise: by wt%, C: 0.1 to 0.25%, Si: 0.01 to 1.5%, Mn: 1.0 to 4.0%, Al: 0.01 to 1.5%, P: 0.15% or less, S: 0.03% or less, N: 0.03% or less, B: 0.0005 to 0.005%, a balance of Fe, and unavoidable impurities; and as microstructures, bainite, tempered martensite, fresh martensite, retained austenite and unavoidable structures, wherein the high strength steel sheet may satisfy the following relational expression 1 and relational expression 2:

[Relational Expression 1]

$$0.03 \leq [B]_{FM} / [B]_{TM} \leq 0.55$$

where $[B]_{FM}$ is a content (wt%) of boron (B) contained in the fresh martensite, and $[B]_{TM}$ is a content (wt%) of boron (B) contained in the tempered martensite; and

[Relational Expression 2]

$$V(1.2 \mu m, \gamma) / V(\gamma) \geq 0.12$$

where $V(1.2 \mu m, \gamma)$ is a fraction (vol%) of the retained austenite having an average grain size of 1.2 μm or more, and $V(\gamma)$ is a fraction (vol%) of the retained austenite of the steel sheet.

[0013] The steel sheet may further comprise, by wt%, one or more of the following (1) to (8):

- (1) one or more of Ti: 0 to 0.5%, Nb: 0 to 0.5%, and V: 0 to 0.5%;
- (2) one or more of Cr: 0 to 3.0% and Mo: 0 to 3.0%;
- (3) one or more of Cu: 0 to 4.0% and Ni: 0 to 4.0%
- (4) one or more of Ca: 0 to 0.05%, REM: 0 to 0.05% excluding Y, and Mg: 0 to 0.05%;
- (5) one or more of W: 0 to 0.5% and Zr: 0 to 0.5%;
- (6) one or more of Sb: 0 to 0.5% and Sn: 0 to 0.5%;
- (7) one or more of Y: 0 to 0.2% and Hf: 0 to 0.2%; and
- (8) Co: 0 to 1.5%.

[0014] The microstructures of the steel sheet may include, by volume fraction, 10 to 30% of bainite, 50 to 70% of tempered martensite, 10 to 30% of fresh martensite, 2 to 10% of retained austenite, and 5% or less (including 0%) of ferrite.

[0015] In the steel sheet, a balance (B_{TE}) of tensile strength and elongation expressed by the following relational expression 3 satisfies 3.0×10^6 to 6.2×10^6 ($MPa^2\%^{1/2}$), a balance (B_{TH}) of tensile strength and a hole expansion ratio expressed by the following relational expression 4 satisfies 6.0×10^6 to 11.5×10^6 ($MPa^2\%^{1/2}$), and a yield ratio evaluation index (I_{VR}) expressed by the following relational expression 5 satisfies 0.15 to 0.42:

[Relational Expression 3]

$$B_{TE} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Elongation (El, \%)}]^{1/2};$$

[Relational Expression 4]

$$B_{TH} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Hole Expansion Ratio (HER, \%)}]^{1/2};$$

and

[Relational Expression 5]

$$I_{YR} = 1 - [\text{Yield Ratio (YR)}].$$

[0016] In an aspect of the present invention, a method for manufacturing a high strength steel sheet having excellent workability may comprise: providing a cold-rolled steel sheet including, by wt%, C: 0.1 to 0.25%, Si: 0.01 to 1.5%, Mn: 1.0 to 4.0%, Al: 0.01 to 1.5%, P: 0.15% or less, S: 0.03% or less, N: 0.03% or less, B: 0.0005 to 0.005%, a balance of Fe, and unavoidable impurities; heating (primarily heating) the cold-rolled steel sheet to a temperature of 700°C at an average heating rate of 5°C/s or more, heating (secondarily heating) the primarily heated steel sheet to a temperature within a range of Ac3 to 920°C at an average heating rate of 5°C/s or less, and then maintaining (primarily maintaining) the secondarily heated steel sheet for 50 to 1200 seconds; cooling (primarily cooling) the primarily maintained steel sheet to a temperature within a range of 350 to 550°C at an average cooling rate of 2 to 100°C/s, and maintaining (secondarily maintaining) the primarily cooled steel sheet for 5 to 600 seconds; cooling (secondarily cooling) the secondarily maintained steel sheet to a temperature within a range of 200 to 400°C at an average cooling rate of 2 to 100°C/s; heating (tertiarily heating) the secondarily cooled steel sheet to a temperature within a range of 350 to 550°C at an average heating rate of 5 to 100°C/s, and then maintaining (tertiarily maintaining) the tertiary heated steel sheet for 50 seconds or more; and cooling (tertiarily cooling) the tertiary maintained steel sheet to room temperature at an average cooling rate of 1°C/s or more.

[0017] The steel slab may further comprise, by wt%, one or more of the following (1) to (8):

- (1) one or more of Ti: 0 to 0.5%, Nb: 0 to 0.5%, and V: 0 to 0.5%;
- (2) one or more of Cr: 0 to 3.0% and Mo: 0 to 3.0%;
- (3) one or more of Cu: 0 to 4.0% and Ni: 0 to 4.0%;
- (4) one or more of Ca: 0 to 0.05%, REM: 0 to 0.05% excluding Y, and Mg: 0 to 0.05%;
- (5) one or more of W: 0 to 0.5% and Zr: 0 to 0.5%;
- (6) one or more of Sb: 0 to 0.5% and Sn: 0 to 0.5%;
- (7) one or more of Y: 0 to 0.2% and Hf: 0 to 0.2%; and
- (8) Co: 0 to 1.5%.

[0018] The cold-rolled steel sheet may be provided by: heating a steel slab to 1000 to 1350°C; performing finishing hot rolling at a temperature within a range of 800 to 1000°C; coiling the hot-rolled steel sheet at a temperature within a range of 350 to 600°C; pickling the coiled steel sheet; and cold rolling the pickled steel sheet at a reduction ratio of 30 to 90%.

[Advantageous Effects]

[0019] According to an aspect of the present invention, it is possible to provide a steel sheet that may be used for automobile parts and the like, and to a steel sheet having an excellent balance of tensile strength and ductility, an excellent balance of tensile strength and hole expansion ratio, and an excellent yield ratio evaluation index, and a method for manufacturing the same.

[Best Mode]

[0020] The present invention relates to a high strength steel sheet having excellent workability and a method for manufacturing the same, and exemplary embodiments of the present invention will hereinafter be described. Exemplary embodiments of the present invention may be modified into various forms, and it is not to be interpreted that the scope of the present invention is limited to exemplary embodiments described below. The present exemplary embodiments are provided in order to further describe the present invention in detail to those skilled in the art to which the present invention pertains.

[0021] The inventors of the present invention recognized that in a boron(B)-added transformation-induced plasticity (TRIP) steel comprising bainite, tempered martensite, fresh martensite and retained austenite, when the fractions of the tempered martensite, the fresh martensite, and the retained austenite are controlled to be within certain ranges, the contents of the boron (B) contained in the tempered martensite and the fresh martensite are controlled to be within certain ranges, and a shape and a size of the retained austenite are controlled to be within certain ranges, it is possible to simultaneously secure an excellent balance of tensile strength and ductility, an excellent balance of tensile strength and a hole expansion ratio, and an excellent yield ratio evaluation index. Based thereon, the present inventors have conceived of the present invention by devising a method such that excellent strength, excellent yield ratio, excellent

ductility, and an excellent hole expansion ratio may be simultaneously provided.

[0022] Hereinafter, a high strength steel sheet having excellent workability according to an aspect of the present invention will be described in more detail.

[0023] In an aspect of the present invention, a high strength steel sheet having excellent workability may comprise: by wt%, C: 0.1 to 0.25%, Si: 0.01 to 1.5%, Mn: 1.0 to 4.0%, Al: 0.01 to 1.5%, P: 0.15% or less, S: 0.03% or less, N: 0.03% or less, B: 0.0005 to 0.005%, a balance of Fe, and unavoidable impurities; and as microstructures, bainite, tempered martensite, fresh martensite, retained austenite and unavoidable structures, wherein the high strength steel sheet may satisfy the following relational expression 1 and relational expression 2:

[Relational Expression 1]

$$0.03 \leq [B]_{FM} / [B]_{TM} \leq 0.55$$

where $[B]_{FM}$ is a content (wt%) of boron (B) contained in the fresh martensite, and $[B]_{TM}$ is a content (wt%) of boron (B) contained in the tempered martensite; and

[Relational Expression 2]

$$V(1.2 \mu\text{m}, \gamma) / V(\gamma) \geq 0.12$$

where $V(1.2 \mu\text{m}, \gamma)$ is a fraction (vol%) of the retained austenite having an average grain size of 1.2 μm or more, and $V(\gamma)$ is a fraction (vol%) of the retained austenite of the steel sheet.

[0024] Hereinafter, compositions of steel according to the present invention will be described in more detail. Hereinafter, unless otherwise indicated, % indicating a content of each element is based on weight.

[0025] The high strength steel sheet having excellent workability according to an aspect of the present invention includes: by wt%, C: 0.1 to 0.25%, Si: 0.01 to 1.5%, Mn: 1.0 to 4.0%, Al: 0.01 to 1.5%, P: 0.15% or less, S: 0.03% or less, N: 0.03% or less, B: 0.0005 to 0.005%, a balance of Fe, and unavoidable impurities. In addition, the high strength steel sheet may further include one or more of Ti: 0.5% or less (including 0%), Nb: 0.5% or less (including 0%), V: 0.5% or less (including 0%), Cr: 3.0% or less (including 0%), Mo: 3.0% or less (including 0%), Cu: 4.0% or less (including 0%), Ni: 4.0% or less (including 0%), Ca: 0.05% or less (including 0%), REM: 0.05% or less (including 0%) excluding Y, Mg: 0.05% or less (including 0%), W: 0.5% or less (including 0%), Zr: 0.5% or less (including 0%), Sb: 0.5% or less (including 0%), Sn: 0.5% or less (including 0%), Y: 0.2% or less (including 0%), Hf: 0.2% or less (including 0%), and Co: 1.5% or less (including 0%).

Carbon (C): 0.1 to 0.25%

[0026] Carbon (C) is an unavoidable element for securing strength of a steel sheet, and is also an element for stabilizing retained austenite that contributes to the improvement in ductility of the steel sheet. Accordingly, in the present invention, 0.1% or more of carbon (C) may be added in order to achieve such an effect. A preferable content of carbon (C) may be greater than 0.1%, may be 0.11% or more, and may be 0.12% or more. On the other hand, when the content of carbon (C) exceeds a certain level, ductility may be lowered and weldability may be degraded due to an excessive increase in strength. Therefore, an upper limit of the content of carbon (C) of the present invention may be limited to 0.25%. The content of carbon (C) may be 0.24% or less, and a more preferable content of carbon (C) may be 0.23% or less.

Silicon (Si): 0.01 to 1.5% or less

[0027] Silicon (Si) is an element that contributes to improvement in strength by solid solution strengthening, and is also an element improving workability by homogenizing a structure. In addition, silicon (Si) is an element contributing to generation of retained austenite by suppressing precipitation of cementite. Therefore, in the present invention, silicon (Si) of 0.01% or more may be added in order to achieve such an effect. A preferable content of silicon (Si) may be 0.02% or more, and a more preferable content of silicon (Si) may be 0.04% or more. However, when the content of silicon (Si) exceeds a certain level, a problem of plating defects, such as non-plating, may be induced during plating, and weldability of a steel sheet may be lowered, so the present invention may limit an upper limit of the content of silicon (Si) to 1.5%. A preferable upper limit of the content of silicon (Si) may be 1.48%, and a more preferable upper limit of the content of silicon (Si) may be 1.46%.

Manganese (Mn): 1.0 to 4.0%

[0028] Manganese (Mn) is a useful element for increasing both strength and ductility. Therefore, in the present invention, manganese (Mn) of 1.0% or more may be added in order to achieve such an effect. A preferable lower limit of the content of manganese (Mn) may be 1.2%, and a more preferable lower limit of the content of manganese (Mn) may be 1.4%. On the other hand, when manganese (Mn) is excessively added, a bainite transformation time increases and concentration of carbon (C) in austenite becomes insufficient, so there exists a problem in which a desired austenite fraction may not be secured. Therefore, in the present invention, an upper limit of the content of manganese (Mn) of the present invention may be limited to 4.0%. A preferable upper limit of the content of manganese (Mn) may be 3.9%.

Aluminum (Al): 0.01 to 1.5%

[0029] Aluminum (Al) is an element performing deoxidation by combining with oxygen in steel. In addition, aluminum (Al) is also an element for stabilizing retained austenite by suppressing precipitation of cementite like silicon (Si). Therefore, in the present invention, aluminum (Al) of 0.01% or more may be added in order to achieve such an effect. A preferable content of aluminum (Al) may be 0.03% or more, and a more preferable content of aluminum (Al) may be 0.05% or more. On the other hand, when aluminum (Al) is excessively added, inclusions in a steel sheet increase, and workability of the steel sheet may be lowered, so the present invention may limit an upper limit of the content of aluminum (Al) to 1.5%. A preferable upper limit of the content of aluminum (Al) may be 1.48%.

Phosphorus (P): 0.15% or less (including 0%)

[0030] Phosphorus (P) is an element which is contained as an impurity and deteriorates impact toughness. Therefore, it is preferable to manage the content of phosphorus (P) to 0.15% or less.

Sulfur (S): 0.03% or less (including 0%)

[0031] Sulfur (S) is an element which is contained as an impurity to form MnS in a steel sheet and deteriorate ductility. Therefore, it is preferable that the content of sulfur (S) is 0.03% or less.

Nitrogen (N): 0.03% or less (including 0%)

[0032] Nitrogen (N) is an element which is contained as an impurity and forms nitride during continuous casting to cause cracks in a slab. Therefore, it is preferable that the content of nitrogen (N) is 0.03% or less.

Boron (B): 0 to 0.005%

[0033] Boron (B) is an element improving hardenability to increase strength, and is also an element suppressing nucleation of grain boundaries. In addition, in the present invention, it is intended to simultaneously secure an excellent balance of tensile strength and elongation, an excellent balance of tensile strength and a hole expansion ratio, and an excellent yield ratio evaluation index, and therefore, boron (B) is to be necessarily added in the present invention. Therefore, in the present invention, 0.0005% or more of boron (B) may be added in order to achieve such an effect. However, when the content of boron (B) is added beyond a certain level, not only excessive characteristic effects, but also an increase in manufacturing costs is incurred, so the present invention may limit an upper limit of the content of boron (B) to 0.005%.

[0034] Meanwhile, the steel sheet of the present invention has an alloy composition that may be additionally included in addition to the above-described alloy components, which will be described in detail below.

One or more of titanium (Ti): 0 to 0.5%, niobium (Nb): 0 to 0.5%, and vanadium (V): 0 to 0.5%

[0035] Titanium (Ti), niobium (Nb), and vanadium (V) are elements that make precipitates and refine crystal grains, and are elements that also contribute to the improvement in strength and impact toughness of a steel sheet, and therefore, in the present invention, one or more of titanium (Ti), niobium (Nb), and vanadium (V) may be added in order to achieve such an effect. However, when each of the contents of titanium (Ti), niobium (Nb), and vanadium (V) exceeds a certain level, excessive precipitates are formed to lower impact toughness and increase manufacturing costs, so the present invention may limit the contents of titanium (Ti), niobium (Nb), and vanadium (V) to 0.5% or less, respectively.

One or more of chromium (Cr): 0 to 3.0% and molybdenum (Mo): 0 to 3.0%

[0036] Since chromium (Cr) and molybdenum (Mo) are elements that not only suppress austenite decomposition during alloying treatment, but also stabilize austenite like manganese (Mn), in the present invention, one or more of chromium (Cr) and molybdenum (Mo) may be added in order to achieve such an effect. However, when the contents of chromium (Cr) and molybdenum (Mo) exceed certain levels, the bainite transformation time increases and the concentration of carbon (C) in austenite becomes insufficient, so the desired retained austenite fraction may not be secured. Therefore, the present invention may limit the contents of chromium (Cr) and molybdenum (Mo) to 3.0% or less, respectively.

One or more of Cu: 0 to 4.0% and Ni: 0 to 4.0%

[0037] Copper (Cu) and nickel (Ni) are elements that stabilize austenite and suppress corrosion. In addition, copper (Cu) and nickel (Ni) are also elements that are concentrated on a surface of a steel sheet to prevent hydrogen from intruding into the steel sheet, thereby suppressing hydrogen delayed destruction. Therefore, in the present invention, one or more of copper (Cu) and nickel (Ni) may be added in order to achieve such an effect. However, when the contents of copper (Cu) and nickel (Ni) exceed certain levels, not only excessive characteristic effects, but also an increase in manufacturing costs is incurred, so the present invention may limit the contents of copper (Cu) and nickel (Ni) to 4.0% or less, respectively.

One or more of calcium (Ca): 0 to 0.05%, Magnesium (Mg): 0 to 0.05%, and rare earth element (REM) excluding yttrium (Y): 0 to 0.05%

[0038] Here, the rare earth element (REM) is scandium (Sc), yttrium (Y), and a lanthanide element. Since calcium (Ca), magnesium (Mg), and the rare earth element (REM) excluding yttrium (Y) are elements that contribute to the improvement in ductility of a steel sheet by spheroidizing sulfides, in the present invention, one or more of calcium (Ca), magnesium (Mg), and the rare earth element (REM) excluding yttrium (Y) may be added in order to achieve such an effect. However, when the contents of calcium (Ca), magnesium (Mg), and the rare earth element (REM) excluding yttrium (Y) exceed certain levels, not only excessive characteristic effects, but also an increase in manufacturing costs is incurred, so the present invention may limit the contents of calcium (Ca), magnesium (Mg), and the rare earth element (REM) excluding yttrium (Y) to 0.05% or less, respectively.

One or more of tungsten (W): 0 to 0.5% and zirconium (Zr): 0 to 0.5%

[0039] Since tungsten (W) and zirconium (Zr) are elements that increase strength of a steel sheet by improving hardenability, in the present invention, one or more of tungsten (W) and zirconium (Zr) may be added in order to achieve such an effect. However, when the contents of tungsten (W) and zirconium (Zr) exceed certain levels, not only excessive characteristic effects, but also an increase in manufacturing costs is incurred, so the present invention may limit the contents of tungsten (W) and zirconium (Zr) to 0.5% or less, respectively.

One or more of antimony (Sb): 0 to 0.5% and tin (Sn): 0 to 0.5%

[0040] Since antimony (Sb) and tin (Sn) are elements that improve plating wettability and plating adhesion of a steel sheet, in the present invention, one or more of antimony (Sb) and tin (Sn) may be added in order to achieve such an effect. However, when the contents of antimony (Sb) and tin (Sn) exceed certain levels, brittleness of a steel sheet increases, and thus, cracks may occur during hot working or cold working, so the present invention may limit the contents of antimony (Sb) and tin (Sn) to 0.5% or less, respectively.

One or more of yttrium (Y): 0 to 0.2% and hafnium (Hf): 0 to 0.2%

[0041] Since yttrium (Y) and hafnium (Hf) are elements that improve corrosion resistance of a steel sheet, in the present invention, one or more of the yttrium (Y) and hafnium (Hf) may be added in order to achieve such an effect. However, when the contents of yttrium (Y) and hafnium (Hf) exceed certain levels, ductility of the steel sheet may deteriorate, so the present invention may limit the contents of yttrium (Y) and hafnium (Hf) to 0.2% or less, respectively.

Cobalt (Co): 0 to 1.5%

[0042] Since cobalt (Co) is an element that promotes a bainite transformation to increase a TRIP effect, in the present

invention, cobalt (Co) may be added in order to achieve such an effect. However, when the content of cobalt (Co) exceeds a certain level, since weldability and ductility of a steel sheet may deteriorate, the present invention may limit the content of cobalt (Co) to 1.5% or less.

[0043] The high strength steel sheet having excellent workability according to an aspect of the present invention may include a balance of Fe and other unavoidable impurities in addition to the components described above. However, in a general manufacturing process, unintended impurities may inevitably be mixed from raw materials or the surrounding environment, and thus, these impurities may not be completely excluded. Since these impurities are known to those skilled in the art, all the contents are not specifically mentioned in the present specification. In addition, a further addition of effective components other than the above-described components is not entirely excluded.

[0044] The high strength steel sheet having excellent workability according to an aspect of the present invention may include, as microstructures, bainite, tempered martensite, fresh martensite, retained austenite and unavoidable structures.

[0045] Both untempered martensite (fresh martensite, FM) and tempered martensite (TM) are microstructures that improve the strength of a steel sheet. However, compared with tempered martensite, fresh martensite has a characteristic of greatly reducing ductility and burring workability of a steel sheet. In addition, compared with tempered martensite, fresh martensite has a tendency of reducing a yield ratio of a steel sheet. These are because a microstructure of tempered martensite is softened by a tempering heat treatment. Therefore, in the present invention, it is preferable to control fractions of tempered martensite and fresh martensite in order to secure a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio, and a yield ratio evaluation index (1-YR) targeted by the present invention. In order to satisfy a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation of $3.0 \cdot 10^6$ or more, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of $6.0 \cdot 10^6$ or more, and a yield ratio evaluation index (1-YR) of 0.42 or less, it is preferable to limit a fraction of the tempered martensite to 50 vol% or more, and to limit a fraction of the fresh martensite to 10 vol% or more. A more preferable fraction of tempered martensite may be 52 vol% or more, or 54 vol% or more, and a more preferable fraction of fresh martensite may be 12 vol% or more. On the other end, when tempered martensite or fresh martensite is excessively formed, ductility and burring workability are lowered, so that a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation of $3.0 \cdot 10^6$ or more, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of $6.0 \cdot 10^6$ or more, and a yield ratio evaluation index (1-YR) of 0.42 or less cannot be satisfied at the same time. Therefore, the present invention may limit a fraction of tempered martensite to 70 vol% or less, and limit a fraction of fresh martensite to 30 vol% or less. A more preferable fraction of tempered martensite may be 68 vol% or less, or 65 vol% or less, and more preferable fraction of fresh martensite may be 25 vol% or less.

[0046] It is necessary to optimize a fraction of bainite in order to secure a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio, and a yield ratio evaluation index (1-YR) at levels targeted by the present invention. In order to secure a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation of $3.0 \cdot 10^6$ or more, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of $6.0 \cdot 10^6$ or more, and a yield ratio evaluation index (1-YR) of 0.42 or less, it is preferable to control a fraction of bainite to 10 vol% or more. A more preferable fraction of bainite may be 12 vol% or more, or 14 vol% or more. On the other end, when bainite is excessively formed, it causes a fraction reduction of tempered martensite, so that a fraction of bainite may be limited to 30 vol% or less, in order to secure a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio, and a yield ratio evaluation index (1-YR) targeted by the present invention. A preferable fraction of the bainite may be 12 vol% or more, 14 vol% or more, 28 vol% or less, or 26 vol% or less.

[0047] A steel sheet including retained austenite has excellent ductility and bending workability due to transformation-induced plasticity occurring during transformation from austenite to martensite during processing. When a fraction of the retained austenite is lower than a certain level, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation may be less than $3.0 \cdot 10^6$ (MPa²%^{1/2}), and is not preferably. On the other hand, when a fraction of retained austenite exceeds a certain level, local elongation may be lowered, or point weldability may be lowered. Therefore, in the present invention, a fraction of retained austenite may be limited to be in a range of 2 to 10 vol% in order to obtain a steel sheet having an excellent balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation. A preferable fraction of retained austenite is 3 vol% or more, or 8 vol% or less.

[0048] As the unavoidable structure, the steel sheet of the present invention may include ferrite, pearlite, martensite austenite constituent (M-A), and the like. When ferrite is excessively formed, strength of the steel sheet may be lowered, so the present invention may limit a fraction of ferrite to 5 vol% (including 0%). Moreover, when pearlite is excessively formed, workability of the steel sheet may be lowered or a fraction of retained austenite may be lowered, so the present invention intends to limit the formation of pearlite as much as possible.

[0049] The high strength steel sheet having excellent workability according to an aspect of the present invention may satisfy the following relational expression 1 and relational expression 2:

[Relational Expression 1]

$$0.03 \leq [B]_{FM} / [B]_{TM} \leq 0.55$$

where $[B]_{FM}$ is a content (wt%) of boron (B) contained in the fresh martensite, and $[B]_{TM}$ is a content (wt%) of boron (B) contained in the tempered martensite; and

[Relational Expression 2]

$$V(1.2 \mu\text{m}, \gamma) / V(\gamma) \geq 0.12$$

where $V(1.2 \mu\text{m}, \gamma)$ is a fraction (vol%) of the retained austenite having an average grain size of $1.2 \mu\text{m}$ or more, and $V(\gamma)$ is a fraction (vol%) of the retained austenite of the steel sheet.

[0050] The present invention not only controls the fractions of the tempered martensite, the fresh martensite, and the retained austenite to be in certain ranges, but also controls the content ratios of the boron (B) contained in the tempered martensite, and the fresh martensite to be in certain ranges, while controlling a ratio of the retained austenite of specific size, shape and type with respect to the entire retained austenite to be in a certain range, in order to secure a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio, and a yield ratio evaluation index (1-YR) targeted thereby.

[0051] The present invention controls a ratio of the content ($[B]_{TM}$, wt%) of boron (B) contained in the fresh martensite to the content ($[B]_{FM}$, wt%) of boron (B) contained in the tempered martensite to be in a range of 0.03 to 0.55 as shown in relational expression 1, so as to secure a balance (B_{TE}) of tensile strength and elongation of $3.0 \cdot 10^6$ to $6.2 \cdot 10^6$ ($\text{MPa}^2\%^{1/2}$), a balance (B_{TH}) of tensile strength and a hole expansion ratio of $6.0 \cdot 10^6$ to $11.5 \cdot 10^6$ ($\text{MPa}^2\%^{1/2}$), and a yield ratio evaluation index (I_{YR}) of 0.15 to 0.42 at the same time.

[0052] The inventors of the present invention conducted in-depth research on a method for securing physical properties of a boron(B)-added TRIP steel, and as a result, noted that the physical properties targeted by the present invention may be secured only when a ratio of a content of boron (B) contained in fresh martensite to a content of boron (B) contained in tempered martensite satisfies a certain range, even though the theoretical basis thereof is not clearly identified. In particular, it was able to identify that a yield ratio of a steel sheet has a constant tendency according to a content ratio of boron (B) contained in tempered martensite and fresh martensite. Therefore, the present invention limits the ratio of the content of boron (B) contained in the fresh martensite to the content of boron (B) contained in the tempered martensite to be in a range of 0.03 to 0.55 as shown in relational expression 1, thereby securing a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio, and a yield ratio evaluation index (1-YR) targeted thereby.

[0053] In addition, the inventors of the present invention could know that not only a fraction of retained austenite, a ratio of retained austenite having a specific size to the entire retained austenite is a factor for securing strength and workability.

[0054] As a ratio of retained austenite having an average grain size of $1.2 \mu\text{m}$ or more to the retained austenite increases, it helps enhancement in workability of a steel sheet. Retained austenite having an average grain size of $1.2 \mu\text{m}$ or more is retained austenite that is heat-treated at a bainite forming temperature, and has an increased average size, and is a structure in which transformation driving force to martensite is suppressed relative to retained austenite having an average grain size of $1.2 \mu\text{m}$ or less. Therefore, since transformation from retained austenite having an average grain size of $1.2 \mu\text{m}$ or more to martensite is suppressed, when a ratio of retained austenite having an average grain size of $1.2 \mu\text{m}$ or more is greater than a certain level, workability of a steel sheet may be more effectively enhanced.

[0055] As in relational expression 2, the present invention controls a ratio of a fraction ($V(1.2 \mu\text{m}, \gamma)$, vol%) of retained austenite having an average grain size of $1.2 \mu\text{m}$ or more to a fraction ($V(\gamma)$, vol%) of the entire retained austenite contained in a steel sheet to be 0.12 or more, and therefore, may effectively secure a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio.

[0056] In the high strength steel sheet having excellent workability according to an aspect of the present invention, a balance (B_{TE}) of tensile strength and elongation expressed by the following relational expression 3 may satisfy $3.0 \cdot 10^6$ to $6.2 \cdot 10^6$ ($\text{MPa}^2\%^{1/2}$), a balance (B_{TH}) of tensile strength and a hole expansion ratio expressed by the following relational expression 4 may satisfy $6.0 \cdot 10^6$ to $11.5 \cdot 10^6$ ($\text{MPa}^2\%^{1/2}$), and a yield ratio evaluation index (I_{YR}) expressed by the following relational expression 5 may satisfy 0.15 to 0.42:

[Relational Expression 3]

$$B_{TE} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Elongation (El, \%)}]^{1/2h};$$

[Relational Expression 4]

$$B_{TH} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Hole Expansion Ratio (HER, \%)}]^{1/2};$$

and

[Relational Expression 5]

$$I_{YR} = 1 - [\text{Yield Ratio (YR)}].$$

[0057] Hereinafter, an example of a method for manufacturing a steel sheet of the present invention will be described in detail.

[0058] A method for manufacturing a high strength steel sheet having excellent workability according to an aspect of the present invention may comprises: heating (primarily heating) a cold-rolled steel sheet having a predetermined alloy composition to a temperature of 700°C at an average heating rate of 5°C/s or more, heating (secondarily heating) the primarily heated steel sheet to a temperature within a range of Ac3 to 920°C at an average heating rate of 5°C/s or less, and then maintaining (primarily maintaining) the secondarily heated steel sheet for 50 to 1200 seconds; cooling (primarily cooling) the primarily maintained steel sheet to a temperature within a range of 350

to 550°C at an average cooling rate of 2 to 100°C/s, and maintaining (secondarily maintaining) the primarily cooled steel sheet for 5 to 600 seconds; cooling (secondarily cooling) the secondarily maintained steel sheet to a temperature within a range of 200 to 400°C at an average cooling rate of 2 to 100°C/s; heating (tertiarily heating) the secondarily cooled steel sheet to a temperature within a range of 350 to 550°C at an average heating rate of 5 to 100°C/s, and then maintaining (tertiarily maintaining) the tertiary heated steel sheet for 50 seconds or more; and cooling (tertiarily cooling) the tertiary maintained steel sheet to room temperature at an average cooling rate of 1°C/s or more.

[0059] The cold-rolled steel sheet may be provided by: heating steel slab having a predetermined alloy composition to 1000 to 1350°C; performing finishing hot rolling at a temperature within a range of 800 to 1000°C; coiling the hot-rolled steel sheet at a temperature within a range of 350 to 600°C; pickling the coiled steel sheet; and cold rolling the pickled steel sheet at a reduction ratio of 30 to 90%.

Preparation and heating of steel slab

[0060] A steel slab having a predetermined alloy composition is prepared. Since the steel slab according to the present invention includes an alloy composition corresponding to an alloy composition of the steel sheet described above, the description of the alloy compositions of the slab is replaced by the description of the alloy composition of the steel sheet described above.

[0061] The prepared steel slab may be heated to a temperature within a certain range, and the heating temperature of the steel slab at this time may be in the range of 1000 to 1350°C.

[0062] When the heating temperature of the steel slab is less than 1000°C, the steel slab may be hot rolled at a temperature within a range below a desired finish hot rolling temperature range, and when the heating temperature of the steel slab exceeds 1350°C, the temperature reaches a melting point of steel, and thus, the steel slab may be melted.

Hot rolling and coiling

[0063] The heated steel slab may be hot rolled, and thus, provided as a hot-rolled steel sheet. During the hot rolling, the finish hot rolling temperature is preferably in the range of 800 to 1000°C. When the finish hot rolling temperature is lower than 800°C, an excessive rolling load may be a problem, and when the finish hot rolling temperature exceeds 1000°C, grains of the hot-rolled steel sheet are coarsely formed, which may cause a deterioration in physical properties

of the final steel sheet.

[0064] After the hot rolling has been completed, the hot-rolled steel sheet may be cooled at an average cooling rate of 10°C/s or more, and may be coiled at a temperature within a range of 350 to 650°C. When the coiling temperature is lower than 350°C, coiling is not easy, and when the coiling temperature exceeds 650°C, surface scale may be formed into the inside of the hot-rolled steel sheet, which may make pickling difficult.

Pickling and cold rolling

[0065] After uncoiling the coiled hot-rolled coil, in order to remove the scale generated on the surface of the steel sheet, the pickling may be performed, and the cold rolling may be performed. Although the conditions of the pickling and the cold rolling are not particularly limited in the present invention, the cold rolling is preferably performed at a cumulative reduction ratio of 30 to 90%. When the cumulative reduction ratio of the cold rolling exceeds 90%, it may be difficult to perform the cold rolling in a short time due to the high strength of the steel sheet.

[0066] The cold-rolled steel sheet may be manufactured as a non-plated cold-rolled steel sheet through the annealing heat treatment process, or may be manufactured as a plated steel sheet through a plating process to impart corrosion resistance. As the plating, plating methods such as hot-dip galvanizing, electro-galvanizing, and hot-dip aluminum plating may be applied, and the method and the type are not particularly limited.

Annealing heat treatment

[0067] In the present invention, in order to simultaneously secure the strength and workability of the steel sheet, the annealing heat treatment process is performed.

[0068] The cold-rolled steel sheet is heated (primarily heated) to a temperature of 700°C at an average heating rate of 5°C/s or more, is heated (secondarily heated) to a temperature within a range of Ac3 to 920°C at an average heating rate of 5°C/s or less, and then is maintained (primarily maintained) for 50 to 1200 seconds.

[0069] When the average heating rate to a temperature of 700°C of the primary heating is less than 5°C/s, lump austenite is formed from ferrite and cementite generated during heating, and as a result, fine tempered martensite and retained austenite cannot be formed as a final structure. Therefore, a targeted balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, and a targeted balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio cannot be implemented. In addition, when the secondary heating rate up to the primary maintaining temperature exceeds 5°C/s, transformation from cementite generated during heating to austenite is accelerated, so that a large amount of lump austenite is formed, the final structure is coarsened, and boron (B) may not be sufficiently concentrated into tempered martensite. As a result, $[B]_{FM}/[B]_{TM}$ exceeds 0.55, and targeted levels of a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio, and a yield ratio evaluation index (I_{YR}) cannot be implemented.

[0070] When the primary maintaining temperature is lower than Ac3 (two-phase region), 5 vol% or more of ferrite is formed, and therefore, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio may be lowered. In addition, when the primary maintaining time is less than 50 seconds, the structure may not be sufficiently homogenized and the physical properties of the steel sheet may be lowered. Upper limits of the primary maintaining temperature and the primary maintaining time are not particularly limited, but it is preferable that the primary maintaining temperature is limited to 920°C or less, and the primary maintaining time is limited to 1200 seconds or less, in order to prevent toughness reduction due to coarsened grains.

[0071] After the primary maintaining, the primarily maintained steel sheet may be cooled (primarily cooled) to a temperature within a range of 350 to 550°C at a primary cooling rate with an average cooling rate of 2°C or more, and then may be maintained (secondarily maintained) for 5 seconds or more. When the average cooling rate of the primary cooling is less than 2°C/s, a fraction of retained austenite becomes insufficient due to a slow cooling, and therefore, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered. An upper limit of the average cooling rate of the primary cooling does not need to be particularly specified, but is preferably set to be 100°C or less. When the secondary maintaining temperature is less than 350°C, $V(1.2 \mu m, \gamma)/V(\gamma)$ and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered due to a low heat treatment temperature. On the other hand, when the secondary maintaining temperature is greater than 550°C, retained austenite becomes insufficient, whereby a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered. In addition, when the secondary maintaining time is less than 5 seconds, a heat treatment time becomes insufficient, whereby $V(1.2 \mu m, \gamma)/V(\gamma)$ and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered. An upper limit of the secondary maintaining time does not need to be particularly specified, but is preferably set to be 600 seconds or less.

[0072] After the secondary maintaining, the secondarily maintained steel sheet may be cooled (secondarily cooled)

to a primary cooling stop temperature in a range of 200 to 400°C at an average cooling rate of 2°C/s or more. When the average cooling rate of the secondary cooling is less than 2°C/s, a fraction of retained austenite becomes insufficient due to a slow cooling, and therefore, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation, and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered. An upper limit of the average cooling rate of the secondary cooling does not need to be particularly specified, but is preferably set to be 100°C/s or less. When the primary cooling stop temperature is lower than 200°C, tempered martensite is excessively formed, and retained austenite becomes insufficient, whereby $V(1.2 \mu m, \gamma)/V(\gamma)$, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered. On the other hand, when the primary cooling stop temperature exceeds 400°C, bainite is excessively formed, and tempered martensite becomes insufficient, whereby a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered.

[0073] After the secondary cooling, the secondarily cooled steel sheet may be heated (tertiarily heated) to a temperature within a range of 350 to 550°C at an average heating rate of 5°C/s or more, and then the tertiary heated steel sheet may be maintained (tertiarily maintained) for 50 seconds or more. An upper limit of the average heating rate of the tertiary heating does not need to be particularly specified, but is preferably set to be 100°C/s or less. When the tertiary maintaining temperature is lower than 350°C or the tertiary maintaining time is less than 50 seconds, tempered martensite is excessively formed, and therefore, it is difficult to secure a fraction of retained austenite. As a result, $V(1.2 \mu m, \gamma)/V(\gamma)$, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio may be lowered. When the tertiary maintaining temperature exceeds 550°C or the tertiary maintaining time exceeds 155,000 seconds, a fraction of retained austenite becomes insufficient, and therefore, $V(1.2 \mu m, \gamma)/V(\gamma)$, a balance ($TS^2 \cdot EL^{1/2}$) of tensile strength and elongation of the steel sheet, and a balance ($TS^2 \cdot HER^{1/2}$) of tensile strength and a hole expansion ratio of the steel sheet may be lowered.

[0074] After the tertiary maintaining, the tertiary maintained steel sheet may be cooled (tertiarily cooled) to room temperature at an average cooling rate of 1°C/s or more.

[0075] The high strength steel sheet having excellent workability manufactured by the aforementioned manufacturing method may comprise, as microstructures, bainite, tempered martensite, fresh martensite, retained austenite and unavoidable structures, and as a preferable example, may comprise, by volume fraction, 10 to 30% of bainite, 50 to 70% of tempered martensite, 10 to 30% of fresh martensite, 2 to 10% of retained austenite, and 5% or less (including 0%) of ferrite.

[0076] In the high strength steel sheet having excellent workability manufactured by the aforementioned manufacturing method, a balance (B_{TE}) of tensile strength and elongation expressed by the following relational expression 3 may satisfy $3.0 \cdot 10^6$ to $6.2 \cdot 10^6$ ($MPa^2\%^{1/2}$), a balance (B_{TH}) of tensile strength and a hole expansion ratio expressed by the following relational expression 4 may satisfy $6.0 \cdot 10^6$ to $11.5 \cdot 10^6$ ($MPa^2\%^{1/2}$), and a yield ratio evaluation index (I_{YR}) expressed by the following relational expression 5 may satisfy 0.15 to 0.42:

[Relational Expression 3]

$$B_{TE} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Elongation (El, \%)}]^{1/2};$$

[Relational Expression 4]

$$B_{TH} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Hole Expansion Ratio (HER, \%)}]^{1/2};$$

and

[Relational Expression 5]

$$I_{YR} = 1 - [\text{Yield Ratio (YR)}].$$

[Mode for Invention]

[0077] Hereinafter, a high strength steel sheet having excellent workability and a method for manufacturing same according to an aspect of the present invention will be described in more detail. It should be noted that the following examples are only for the understanding of the present invention, and are not intended to specify the scope of the present invention. The scope of the present invention is determined by matters described in claims and matters reasonably inferred therefrom.

(Inventive Examples)

[0078] A steel slab having a thickness of 100 mm having alloy compositions (a balance of Fe and unavoidable impurities) shown in Table 1 below was prepared, heated at 1200°C, and then subjected to finish hot rolling at 900°C. Thereafter, the steel slab was cooled at an average cooling rate of 30°C/s, and coiled at a coiling temperature of Tables 2 and 3 to manufacture a hot-rolled steel sheet having a thickness of 3 mm. Thereafter, after removing a surface scale by pickling, cold rolling was performed to a thickness of 1.5 mm.

[0079] Thereafter, the heat treatment was performed under the annealing heat treatment conditions shown in Tables 2 to 5 to manufacture the steel sheet. In Tables 2 and 3, the single-phase region means a temperature range of Ac3 to 920°C, and the two-phase region means a temperature range below Ac3°C.

[0080] The microstructure of the thus prepared steel sheet was observed, and the results were shown in Tables 6 and 7. Among the microstructures, ferrite (F), bainite (B), tempered martensite (TM), fresh martensite (FM) and pearlite (P) were observed through SEM after nital-etching a polished specimen cross section. After nital-etching, a structure having no concave-convex portions on a surface of a specimen was classified as ferrite, and a structure having a lamella structure of cementite and ferrite is classified as pearlite. Since both of bainite (B) and tempered martensite (TM) were observed in a form of lath and block, and were difficult to distinguish each other, the fractions of bainite and tempered martensite were calculated using an expansion curve after evaluating dilatation. That is, a value obtained by subtracting the fraction of tempered martensite calculated using the expansion curve from the fraction of bainite and tempered martensite measured by the SEM observation was determined as fraction of bainite. Meanwhile, since fresh martensite (FM) and retained austenite (retained γ) are also difficult to distinguish each other, a value obtained by subtracting the fraction of retained austenite calculated by an X-ray diffraction method from the fraction of martensite and retained austenite observed by the SEM was determined as the fraction of the fresh martensite.

[0081] Meanwhile, $[B]_{FM}/[B]_{TM}$, $V(1.2 \mu m, \gamma)/V(\gamma)$, a balance $(TS^2 \cdot EL^{1/2})$ of tensile strength and elongation, a balance $(TS^2 \cdot HER^{1/2})$ of tensile strength and a hole expansion ratio, and a yield ratio evaluation index (I_{YR}) of the steel sheet were measured and evaluated, and the results thereof were shown in Tables 8 and 9.

[0082] The concentrations of boron (B) in fresh martensite and tempered martensite measured using an electron probe microanalyser (EPMA) were determined as a content ($[B]_{FM}$) of boron (B) contained in fresh martensite, and a content ($[B]_{TM}$) of boron (B) contained in tempered martensite. A fraction ($V(1.2 \mu m, \gamma)$) of retained austenite having an average grain size of 1.2 μm or more was measured by using a phase map of an electron backscatter diffraction (EBSD).

[0083] Tensile strength (TS) and elongation (EI) were evaluated through a tensile test, and the tensile strength (TS) and the elongation (EI) were measured by evaluating the specimens collected in accordance with JIS No. 5 standard based on a 90° direction with respect to a rolling direction of a rolled sheet. The hole expansion ratio (HER) was evaluated through a hole expansion test, and was calculated by the following relational expression 6, after forming a punching hole (die inner diameter of 10.3mm, clearance of 12.5%) of 10 mm Ψ , inserting a conical punch having an apex angle of 60° into a punching hole in a direction in which a burr of the punching hole faces outward, and then compressing and expanding a peripheral portion of the punching hole at a moving speed of 20 mm/min:

[Relational Expression 6]

$$\text{Hole Expansion Ratio (HER, \%)} = \{(D - D_0) / D_0\} \times 100$$

[0084] In the above relational expression 6, D is a hole diameter (mm) when cracks penetrate through the steel sheet along the thickness direction, and D_0 is the initial hole diameter (mm).

EP 4 265 771 A1

[Table 1]

Steel Type	Chemical Components (wt%)										
	C	Si	Mn	P	S	Al	N	Cr	Mo	B	Others
A	0.15	0.48	2.26	0.012	0.0008	0.41	0.0030			0.0024	
B	0.17	0.45	2.38	0.008	0.0010	0.50	0.0029	0.25	0.31	0.0021	
C	0.14	0.60	2.19	0.009	0.0011	0.44	0.0032		0.52	0.0025	
D	0.13	0.52	1.28	0.011	0.0009	0.82	0.0028	0.82		0.0028	
E	0.16	1.44	2.26	0.010	0.0008	0.11	0.0031			0.0043	
F	0.22	0.12	1.94	0.009	0.0010	1.45	0.0027			0.0046	
G	0.14	0.38	2.46	0.010	0.0012	0.72	0.0028			0.0020	Ti: 0.05
H	0.11	0.36	2.39	0.011	0.0011	0.38	0.0031			0.0035	Nb: 0.04
I	0.19	0.49	2.55	0.008	0.0007	0.35	0.0027			0.0032	V: 0.04
J	0.23	0.27	1.76	0.009	0.0012	0.47	0.0029			0.0016	Ni: 0.35
K	0.16	0.58	2.58	0.009	0.0008	0.52	0.0029			0.0013	Cu: 0.36
L	0.18	0.75	2.74	0.011	0.0011	0.63	0.0031			0.0008	
M	0.14	0.44	3.87	0.010	0.0009	0.54	0.0030			0.0007	Ca: 0.002
N	0.17	0.91	2.36	0.011	0.0010	0.50	0.0032			0.0022	REM: 0.001
O	0.14	0.64	2.62	0.008	0.0013	0.47	0.0029			0.0025	Mg: 0.002
P	0.15	0.52	2.46	0.011	0.0009	0.51	0.0027			0.0028	W: 0.14
Q	0.12	0.66	2.70	0.009	0.0011	0.49	0.0028			0.0023	Zr: 0.12
R	0.18	0.04	2.35	0.010	0.0007	1.46	0.0030			0.0029	Sb: 0.02
S	0.20	1.42	2.52	0.009	0.0010	0.05	0.0032			0.0021	Sn: 0.03
T	0.23	0.95	2.48	0.009	0.0009	0.47	0.0029			0.0034	Y: 0.02
U	0.16	0.71	2.66	0.011	0.0012	0.58	0.0031			0.0032	Hf: 0.01
V	0.15	0.62	2.61	0.008	0.0009	0.46	0.0028			0.0031	Co: 0.35
XA	0.07	0.53	2.39	0.009	0.0010	0.54	0.0031			0.0023	
XB	0.27	0.58	2.13	0.011	0.0009	0.42	0.0028			0.0024	
XC	0.16	0.002	2.26	0.010	0.0007	0.001	0.0029			0.0028	
XD	0.15	1.54	2.05	0.009	0.0008	0.58	0.0032			0.0027	
XE	0.19	0.52	2.18	0.011	0.0011	1.55	0.0031			0.0034	
XF	0.20	0.49	0.88	0.010	0.0010	0.41	0.0027			0.0035	
XG	0.14	0.65	4.24	0.009	0.0012	0.63	0.0029			0.0031	
XH	0.17	0.58	2.37	0.011	0.0009	0.57	0.0033	3.22		0.0022	
XI	0.15	0.46	2.42	0.010	0.0008	0.52	0.0028		3.17	0.0024	
XJ	0.14	0.53	2.47	0.012	0.0011	0.46	0.0031			0.0003	
XK	0.16	0.51	2.52	0.009	0.0010	0.43	0.0032			0.0052	

[Table 2]

EP 4 265 771 A1

Specimen No.	Steel Type	Coiling Temp. of Hot-rolled Steel Sheet (°C)	Primary Average Heating Rate (°C/s)	Primary Heating Stop Temp. (°C)	Secondary Average Heating Rate (°C/s)	Primary Maintaining Temp. Region	Primary Maintaining Time (s)	Primary Average Cooling Rate (°C/s)	Secondary Maintaining Temp. (°C)
1	A	550	15	700	0.5	Single-phase Region	180	20	450
2	A	550	1	700	0.5	Single-phase Region	180	20	450
3	A	550	15	700	10	Single-phase Region	180	20	400
4	A	550	15	700	0.5	Two-phase Region	180	20	400
5	A	550	15	700	0.5	Single-phase Region	180	0.5	400
6	A	550	15	700	0.5	Single-phase Region	180	20	320
7	A	550	15	700	0.5	Single-phase Region	180	20	530
8	A	550	15	700	0.5	Single-phase	180	20	400

EP 4 265 771 A1

5							Region			
	9	A	500	15	700	0.5	Single-phase Region	180	20	450
10	10	A	500	15	700	0.5	Single-phase Region	180	20	450
15	11	A	500	15	700	0.5	Single-phase Region	180	20	500
20	12	A	500	15	700	0.5	Single-phase Region	180	20	400
25	13	A	500	15	700	0.5	Single-phase Region	180	20	400
30	14	A	550	15	700	0.5	Single-phase Region	180	20	450
35	15	A	550	15	700	0.5	Single-phase Region	180	20	500
40	16	B	550	15	700	0.5	Single-phase Region	180	20	400
45	17	C	500	15	700	0.5	Single-phase Region	180	20	450
50	18	D	500	15	700	0.5	Single-	180	20	500

55

EP 4 265 771 A1

						phase Region			
19	E	400	15	700	0.5	Single- phase Region	180	20	500
20	F	600	15	700	0.5	Single- phase Region	180	20	450
21	G	450	15	700	0.5	Single- phase Region	180	20	450
22	H	500	15	700	0.5	Single- phase Region	180	20	400
23	I	500	15	700	0.5	Single- phase Region	180	20	400
24	J	500	15	700	0.5	Single- phase Region	180	20	450
25	K	550	15	700	0.5	Single- phase Region	180	20	450

[Table 3]

EP 4 265 771 A1

Specimen No.	Steel Type	Coiling Temp. of Hot-rolled steel sheet (°C)	Primary Average Heating Rate (°C/s)	Primary Heating Stop Temp. (°C)	Secondary Average Heating Rate (°C/s)	Primary Maintaining Temp. Region	Primary Maintaining Time (s)	Primary Average Cooling Rate (°C/s)	Secondary Maintaining Temp. (°C)
26	L	550	15	700	0.5	Single-phase Region	180	20	500
27	M	550	15	700	0.5	Single-phase Region	180	20	500
28	N	550	15	700	0.5	Single-phase Region	180	20	450
29	O	500	15	700	0.5	Single-phase Region	180	20	450
30	P	500	15	700	0.5	Single-phase Region	180	20	400
31	Q	550	15	700	0.5	Single-phase Region	180	20	500
32	R	550	15	700	0.5	Single-phase Region	180	20	450
33	S	500	15	700	0.5	Single-phase	180	20	450

EP 4 265 771 A1

5							Region			
	34	T	550	15	700	0.5	Single-phase Region	180	20	400
10	35	U	450	15	700	0.5	Single-phase Region	180	20	400
15	36	V	600	15	700	0.5	Single-phase Region	180	20	500
20	37	XA	550	15	700	0.5	Single-phase Region	180	20	450
25	38	XB	550	15	700	0.5	Single-phase Region	180	20	400
30	39	XC	550	15	700	0.5	Single-phase Region	180	20	450
35	40	XD	500	15	700	0.5	Single-phase Region	180	20	500
40	41	XE	500	15	700	0.5	Single-phase Region	180	20	450
45	42	XF	500	15	700	0.5	Single-phase Region	180	20	400
50	43	XG	550	15	700	0.5	Single-	180	20	450

55

EP 4 265 771 A1

						phase Region			
44	XH	550	15	700	0.5	Single- phase Region	180	20	400
45	XI	500	15	700	0.5	Single- phase Region	180	20	450
46	XJ	500	15	700	0.5	Single- phase Region	180	20	450
47	XK	500	15	700	0.5	Single- phase Region	180	20	450

[Table 4]

Specimen No.	Steel Type	Secondary Maintaining Time (s)	Secondary Average Cooling Rate (°C/s)	Primary Cooling Stop Temp. (°C)	Tertiary Average Heating Rate (°C/s)	Tertiary Maintaining Temp. (°C)	Tertiary Maintaining Time (s)	Tertiary Average Cooling Rate (°C/s)
1	A	50	20	350	15	400	400	10
2	A	50	20	300	15	450	400	10
3	A	50	20	350	15	450	400	10
4	A	50	20	350	15	400	400	10
5	A	50	20	300	15	400	400	10
6	A	50	20	300	15	400	400	10
7	A	50	20	350	15	400	400	10

EP 4 265 771 A1

8	A	2	20	300	15	450	400	10
9	A	50	0.5	300	15	450	400	10
10	A	50	20	170	15	400	400	10
11	A	50	20	430	15	400	400	10
12	A	50	20	300	15	320	400	10
13	A	50	20	350	15	580	400	10
14	A	50	20	350	15	450	30	10
15	A	50	20	300	15	400	160,000	10
16	B	50	20	300	15	400	400	10
17	C	50	20	300	15	450	400	10
18	D	50	20	350	15	450	400	10
19	E	50	20	250	15	500	400	10
20	F	50	20	300	15	450	400	10
21	G	50	20	350	15	450	400	10
22	H	50	20	300	15	400	400	10
23	I	50	20	300	15	400	400	10
24	J	50	20	230	15	500	400	10
25	K	50	20	370	15	450	400	10

[Table 5]

Specimen No.	Steel Type	Secondary Maintaining Time (s)	Secondary Average Cooling Rate (°C/s)	Primary Cooling Stop Temp. (°C)	Tertiary Average Heating Rate (°C/s)	Tertiary Maintaining Temp. (°C)	Tertiary Maintaining Time (s)	Tertiary Average Cooling Rate (°C/s)
26	L	50	20	300	15	450	400	10
27	M	50	20	350	15	450	400	10

EP 4 265 771 A1

5	28	N	50	20	350	15	500	400	10
	29	O	50	20	300	15	500	400	10
	30	P	50	20	300	15	450	400	10
	31	Q	50	20	250	15	400	400	10
10	32	R	50	20	350	15	400	400	10
	33	S	50	20	230	15	450	400	10
15	34	T	50	20	370	15	450	400	10
	35	U	50	20	300	15	400	400	10
	36	V	50	20	250	15	400	400	10
20	37	XA	50	20	350	15	450	400	10
	38	XB	50	20	300	15	450	400	10
	39	XC	50	20	300	15	400	400	10
25	40	XD	50	20	350	15	400	400	10
	41	XE	50	20	350	15	450	400	10
	42	XF	50	20	300	15	450	400	10
30	43	XG	50	20	300	15	500	400	10
	44	XH	50	20	350	15	400	400	10
	45	XI	50	20	350	15	400	400	10
35	46	XJ	50	20	350	15	400	400	10
	47	XK	50	20	350	15	400	400	10

[Table 6]

Specimen No.	Steel Type	F (vol%)	B (vol%)	TM (vol%)	FM (vol%)	Y (vol%)	P (vol%)
1	A	0	20	58	15	0	7
2	A	0	28	46	25	0	1
3	A	0	19	55	18	3	5
4	A	16	14	53	13	0	4
5	A	0	25	59	15	0	1
6	A	0	22	56	19	0	3
7	A	0	21	59	19	0	1
8	A	0	18	62	17	0	3
9	A	0	22	61	16	0	1
10	A	0	15	72	12	0	1

EP 4 265 771 A1

(continued)

Specimen No.	Steel Type	F (vol%)	B (vol%)	TM (vol%)	FM (vol%)	Y (vol%)	P (vol%)
11	A	0	33	45	15	0	7
12	A	0	13	74	12	0	1
13	A	0	18	65	16	0	1
14	A	0	13	72	14	0	1
15	A	0	20	62	17	0	1
16	B	0	17	61	16	0	6
17	C	0	20	59	17	0	4
18	D	0	22	55	15	0	8
19	E	0	18	61	14	0	7
20	F	0	21	58	16	0	5
21	G	0	18	61	15	0	6
22	H	0	16	59	17	0	8
23	I	0	20	60	14	0	6
24	J	0	18	62	16	0	4
25	K	0	19	57	15	0	9

[Table 7]

Specimen No.	Steel Type	F (vol%)	B (vol%)	TM (vol%)	FM (vol%)	Y (vol%)	P (vol%)
26	L	0	21	55	17	0	7
27	M	0	22	54	18	0	6
28	N	0	19	62	15	0	4
29	O	0	20	57	16	0	7
30	P	0	21	56	18	0	5
31	Q	0	20	59	17	0	4
32	R	0	17	63	14	0	6
33	S	0	19	55	23	0	3
34	T	0	21	56	18	0	5
35	U	0	23	55	16	0	6
36	V	0	18	59	15	0	8
37	XA	0	22	57	16	0	5
38	XB	0	16	39	33	0	12
39	XC	0	21	61	17	0	1
40	XD	0	12	52	33	0	3
41	XE	0	11	53	32	0	4
42	XF	0	15	60	13	11	1
43	XG	0	13	52	32	0	3
44	XH	0	12	54	31	0	3

EP 4 265 771 A1

(continued)

Specimen No.	Steel Type	F (vol%)	B (vol%)	TM (vol%)	FM (vol%)	Y (vol%)	P (vol%)
45	XI	0	11	53	32	0	4
46	XJ	0	20	61	16	0	3
47	XK	0	21	62	13	0	4

[Table 8]

No.	Steel Type	$[B]_{FM}/[B]_{TM}$	$V(1.2\mu m, \gamma)/V(\gamma)$	$B_{TE} (10^6 \text{ Mpa}^{2\%1/2})$	$B_{TH} (10^6 \text{ Mpa}^{2\%1/2})$	1-YR
1	A	0.32	0.23	4.1	9.4	0.35
2	A	0.11	0.24	2.2	4.1	0.26
3	A	0.59	0.21	1.6	5.5	0.49
4	A	0.22	0.26	2.1	4.3	0.33
5	A	0.09	0.18	2.3	4.8	0.28
6	A	0.24	0.06	3.9	3.7	0.31
7	A	0.17	0.19	1.7	4.2	0.34
8	A	0.19	0.10	4.2	4.0	0.27
9	A	0.28	0.27	2.6	3.5	0.31
10	A	0.30	0.08	2.0	4.7	0.25
11	A	0.35	0.22	2.3	5.4	0.20
12	A	0.26	0.05	2.2	4.9	0.23
13	A	0.22	0.04	1.8	5.3	0.36
14	A	0.25	0.09	1.5	4.5	0.28
15	A	0.28	0.07	2.3	4.9	0.33
16	B	0.23	0.24	3.5	9.7	0.27
17	C	0.49	0.28	5.4	11.2	0.21
18	D	0.06	0.25	4.4	10.1	0.18
19	E	0.52	0.23	6.1	6.9	0.39
20	F	0.31	0.13	5.0	11.0	0.28
21	G	0.35	0.17	5.2	8.5	0.32
22	H	0.07	0.19	3.9	7.8	0.34
23	I	0.53	0.15	4.5	9.2	0.22
24	J	0.24	0.24	5.3	7.3	0.29
25	K	0.30	0.22	5.7	8.4	0.35

[Table 9]

No.	Steel Type	$[B]_{FM}/[B]_{TM}$	$V(1.2\mu m, \gamma)/V(\gamma)$	$B_{TE} (10^6 \text{ MPa}^{2\%1/2})$	$B_{TH} (10^6 \text{ MPa}^{2\%1/2})$	1-YR
26	L	0.27	0.16	5.6	10.2	0.31
27	M	0.32	0.15	3.8	9.5	0.28
28	N	0.25	0.18	4.5	8.8	0.22

(continued)

No.	Steel Type	$[B]_{FM}/[B]_{TM}$	$V(1.2\mu m, \gamma) / V(\gamma)$	B_{TE} (10^6 MPa $^{2\%1/2}$)	B_{TH} (10^6 MPa $^{2\%1/2}$)	1-YR
29	O	0.07	0.23	5.0	9.1	0.27
30	P	0.30	0.21	4.6	8.3	0.36
31	Q	0.48	0.20	4.9	7.9	0.52
32	R	0.52	0.26	5.4	6.5	0.07
33	S	0.47	0.24	4.7	7.4	0.30
34	T	0.42	0.23	3.3	11.3	0.27
35	U	0.36	0.14	3.8	10.7	0.24
36	V	0.28	0.16	6.0	9.6	0.32
37	XA	0.29	0.17	2.5	4.1	0.28
38	XB	0.24	0.19	2.3	5.0	0.21
39	XC	0.15	0.21	1.8	5.2	0.36
40	XD	0.17	0.20	2.2	4.7	0.25
41	XE	0.23	0.24	1.5	5.8	0.33
42	XF	0.12	0.26	2.4	5.3	0.29
43	XG	0.25	0.25	2.0	4.9	0.24
44	XH	0.22	0.23	1.6	4.3	0.32
45	XI	0.19	0.17	2.2	5.5	0.28
46	XJ	0.57	0.15	3.8	6.2	0.45
47	XK	0.01	0.18	3.3	6.4	0.12

[0085] As shown in Tables 1 to 9 above, it could be seen that in the case of the specimens complying with the conditions presented in the present invention, both of relational expression 1 and relational expression 2 are satisfied, a balance (B_{TE}) of tensile strength and elongation satisfies 3.0×10^6 to 6.2×10^6 (MPa $^{2\%1/2}$), a balance (B_{TH}) of tensile strength and a hole expansion ratio satisfies 6.0×10^6 to 11.5×10^6 (MPa $^{2\%1/2}$), and a yield ratio evaluation index (I_{YR}) satisfies 0.15 to 0.42.

[0086] In specimen 2, the primary average heating rate was less than 5°C/s , so that tempered martensite and retained austenite were insufficient. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 2.

[0087] In specimen 3, the secondary average heating rate was more than 5°C/s , so that lump austenite was formed, and boron (B) was not concentrated into tempered martensite. As a result, $[B]_{FM}/[B]_{TM}$ was more than 0.55, a yield ratio evaluation index (I_{YR}) was more than 0.42, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 3.

[0088] In specimen 4, the primary maintaining temperature was in a two-phase region less than A_{c3} , so that a fraction of ferrite was excessive. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 4.

[0089] In specimen 5, the primary average cooling rate was less than 1°C/s , so that a fraction of retained austenite was insufficient. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 5.

[0090] In specimen 6, the secondary maintaining temperature was less than 350°C , so that a heat treatment temperature was insufficient. As a result, $V(1.2 \mu m, \gamma)$ was less than 0.12, and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 6.

[0091] In specimen 7, the secondary maintaining temperature was more than 550°C , so that a fraction of retained austenite was insufficient. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 7.

[0092] In specimen 8, the secondary maintaining time was less than 5 seconds, so that a heat treatment time was insufficient. As a result, $V(1.2 \mu m, \gamma)$ was less than 0.12, and a balance (B_{TH}) of tensile strength and a hole expansion

ratio was less than 6.0×10^6 , in specimen 8.

[0093] In specimen 9, the secondary average cooling rate was less than 2°C/s , so that a fraction of retained austenite was insufficient. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 9.

[0094] In specimen 10, the primary cooling stop temperature was less than 200°C , so that a fraction of tempered martensite was excessive, and a fraction of retained austenite was insufficient. As a result, $V(1.2 \mu\text{m}, y)$ was less than 0.12, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 10.

[0095] In specimen 11, the primary cooling stop temperature was more than 400°C , so that a fraction of bainite was excessive, and a fraction of tempered martensite was insufficient. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 11.

[0096] In specimen 12, the tertiary maintaining temperature was less than 350°C , so that a fraction of tempered martensite was excessive, and a fraction of retained austenite was insufficient. As a result, $V(1.2 \mu\text{m}, y)$ was less than 0.12, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 12.

[0097] In specimen 13, the tertiary maintaining temperature was more than 550°C , so that a fraction of retained austenite was insufficient. As a result, $V(1.2 \mu\text{m}, y)$ was less than 0.12, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 13.

[0098] In specimen 14, the tertiary maintaining time was less than 50 seconds, so that a fraction of tempered martensite was excessive, and a fraction of retained austenite was insufficient. As a result, $V(1.2 \mu\text{m}, y)$ was less than 0.12, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 14.

[0099] In specimen 15, the tertiary maintaining time was more than 155,000 seconds, so that a fraction of retained austenite was insufficient. As a result, $V(1.2 \mu\text{m}, y)$ was less than 0.12, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 15.

[0100] In specimen 37, a content of carbon (C) was low, so that a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 .

[0101] In specimen 38, a content of carbon (C) was high, so that a fraction of tempered martensite was insufficient, a fraction of fresh martensite was excessive, and a fraction of retained austenite was excessive. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 38.

[0102] In specimen 39, a content of silicon (Si) was low, so that a fraction of retained austenite was insufficient. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 39.

[0103] In specimen 40, a content of silicon (Si) was high, so that a fraction of fresh martensite was excessive. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 40.

[0104] In specimen 41, a content of Aluminum (Al) was high, so that a fraction of fresh martensite was excessive. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 41.

[0105] In specimen 42, a content of manganese (Mn) was low, so that pearlite was generated, and a fraction of retained austenite was insufficient. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 42.

[0106] In specimen 43, a content of manganese (Mn) was high, so that a fraction of fresh martensite was excessive. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 43.

[0107] In specimen 44, a content of chromium (Cr) was high, so that a fraction of fresh martensite was excessive. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 44.

[0108] In specimen 45, a content of molybdenum (Mo) was high, so that a fraction of fresh martensite was excessive. As a result, a balance (B_{TE}) of tensile strength and elongation was less than 3.0×10^6 , and a balance (B_{TH}) of tensile strength and a hole expansion ratio was less than 6.0×10^6 , in specimen 45.

[0109] In specimen 46, a content of boron (B) was low, so that boron (B) was not concentrated into tempered martensite. As a result, $[B]_{FM}/[B]_{TM}$ was more than 0.55, and a yield ratio evaluation index (I_{YR}) was more than 0.42, in specimen 51.

[0110] In specimen 47, a content of boron (B) was high, so that boron (B) was excessively concentrated into tempered

martensite. As a result, $[B]_{FM}/[B]_{TM}$ was less than 0.03, and a yield ratio evaluation index (I_{YR}) was less than 0.15, in specimen 52.

[0111] While the present invention has been described in detail through exemplary embodiment, other types of exemplary embodiments are also possible. Therefore, the technical spirit and scope of the claims set forth below are not limited to exemplary embodiments.

Claims

1. A high strength steel sheet having excellent workability, comprising:

by wt%, C: 0.1 to 0.25%, Si: 0.01 to 1.5%, Mn: 1.0 to 4.0%, Al: 0.01 to 1.5%, P: 0.15% or less, S: 0.03% or less, N: 0.03% or less, B: 0.0005 to 0.005%, a balance of Fe, and unavoidable impurities; and as microstructures, bainite, tempered martensite, fresh martensite, retained austenite and unavoidable structures, wherein the high strength steel sheet satisfies the following [Relational expression 1] and [Relational expression 2]:

[Relational Expression 1]

$$0.03 \leq [B]_{FM}/[B]_{TM} \leq 0.55$$

where $[B]_{FM}$ is a content (wt%) of Boron (B) contained in the fresh martensite, and $[B]_{TM}$ is a content (wt%) of Boron (B) contained in the tempered martensite; and

[Relational Expression 2]

$$V(1.2 \mu\text{m}, \gamma)/V(\gamma) \geq 0.12$$

where $V(1.2 \mu\text{m}, \gamma)$ is a fraction (vol%) of the retained austenite having an average grain size of 1.2 μm or more, and $V(\gamma)$ is a fraction (vol%) of the retained austenite of the steel sheet.

2. The high strength steel sheet having excellent workability of claim 1, further comprising: by wt%, one or more of the following (1) to (8):

- (1) one or more of Ti: 0 to 0.5%, Nb: 0 to 0.5%, and V: 0 to 0.5%;
- (2) one or more of Cr: 0 to 3.0% and Mo: 0 to 3.0%;
- (3) one or more of Cu: 0 to 4.0% and Ni: 0 to 4.0%;
- (4) one or more of Ca: 0 to 0.05%, REM: 0 to 0.05% excluding Y, and Mg: 0 to 0.05%;
- (5) one or more of W: 0 to 0.5% and Zr: 0 to 0.5%;
- (6) one or more of Sb: 0 to 0.5% and Sn: 0 to 0.5%;
- (7) one or more of Y: 0 to 0.2% and Hf: 0 to 0.2%; and
- (8) Co: 0 to 1.5%.

3. The high strength steel sheet having excellent workability of claim 1, wherein the microstructures of the steel sheet include, by volume fraction, 10 to 30% of bainite, 50 to 70% of tempered martensite, 10 to 30% of fresh martensite, 2 to 10% of retained austenite, and 5% or less (including 0%) of ferrite.

4. The high strength steel sheet having excellent workability of claim 1, wherein a balance (B_{TE}) of tensile strength and elongation expressed by the following [Relational expression 3] satisfies 3.0×10^6 to 6.2×10^6 ($\text{MPa}^{2\%1/2}$), a balance (B_{TH}) of tensile strength and a hole expansion ratio expressed by the following [Relational expression 4] satisfies 6.0×10^6 to 11.5×10^6 ($\text{MPa}^{2\%1/2}$), and a yield ratio evaluation index (I_{YR}) expressed by the following [Relational expression 5] satisfies 0.15 to 0.42:

[Relational Expression 3]

$$B_{TE} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Elongation (El, \%)}]^{1/2};$$

[Relational Expression 4]

$$B_{TH} = [\text{Tensile Strength (TS, MPa)}]^2 * [\text{Hole Expansion Ratio (HER, \%)}]^{1/2};$$

and

[Relational Expression 5]

$$I_{YR} = 1 - [\text{Yield Ratio (YR)}]$$

5. A method for manufacturing a high strength steel sheet having excellent workability, the method comprising:

providing a cold-rolled steel sheet including, by wt%, C: 0.1 to 0.25%, Si: 0.01 to 1.5%, Mn: 1.0 to 4.0%, Al: 0.01 to 1.5%, P: 0.15% or less, S: 0.03% or less, N: 0.03% or less, B: 0.0005 to 0.005%, a balance of Fe, and unavoidable impurities;

heating (primarily heating) the cold-rolled steel sheet to a temperature of 700°C at an average heating rate of 5°C/s or more, heating (secondarily heating) the primarily heated steel sheet to a temperature within a range of Ac3 to 920°C at an average heating rate of 5°C/s or less, and then maintaining (primarily maintaining) the secondarily heated steel sheet for 50 to 1200 seconds;

cooling (primarily cooling) the primarily maintained steel sheet to a temperature within a range of 350 to 550°C at an average cooling rate of 2 to 100°C/s, and maintaining (secondarily maintaining) the primarily cooled steel sheet for 5 to 600 seconds;

cooling (secondarily cooling) the secondarily maintained steel sheet to a temperature within a range of 200 to 400°C at an average cooling rate of 2 to 100°C/s;

heating (tertiarily heating) the secondarily cooled steel sheet to a temperature within a range of 350 to 550°C at an average heating rate of 5 to 100°C/s, and then maintaining (tertiarily maintaining) the tertiary heated steel sheet for 50 seconds or more; and

cooling (tertiarily cooling) the tertiary maintained steel sheet to room temperature at an average cooling rate of 1°C/s or more.

6. The method for manufacturing a high strength steel sheet having excellent workability of claim 5, wherein the steel slab further includes one or more of the following (1) to (8):

(1) one or more of Ti: 0 to 0.5%, Nb: 0 to 0.5%, and V: 0 to 0.5%;

(2) one or more of Cr: 0 to 3.0% and Mo: 0 to 3.0%;

(3) one or more of Cu: 0 to 4.0% and Ni: 0 to 4.0%;

(4) one or more of Ca: 0 to 0.05%, REM: 0 to 0.05% excluding Y, and Mg: 0 to 0.05%;

(5) one or more of W: 0 to 0.5% and Zr: 0 to 0.5%;

(6) one or more of Sb: 0 to 0.5% and Sn: 0 to 0.5%;

(7) one or more of Y: 0 to 0.2% and Hf: 0 to 0.2%; and

(8) Co: 0 to 1.5%.

7. The method for manufacturing a high strength steel sheet having excellent workability of claim 5, wherein the cold-rolled steel sheet is provided by:

heating steel slab to 1000 to 1350°C;

performing finishing hot rolling at a temperature within a range of 800 to 1000°C;

EP 4 265 771 A1

coiling the hot-rolled steel sheet at a temperature within a range of 350 to 600°C;
pickling the coiled steel sheet; and
cold rolling the pickled steel sheet at a reduction ratio of 30 to 90%.

5

10

15

20

25

30

35

40

45

50

55

INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR2021/017992

A. CLASSIFICATION OF SUBJECT MATTER

C22C 38/04(2006.01)i; **C22C 38/02**(2006.01)i; **C22C 38/06**(2006.01)i; **C22C 38/00**(2006.01)i; **C21D 9/46**(2006.01)i;
C21D 8/02(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

C22C 38/04(2006.01); C21D 9/00(2006.01); C21D 9/46(2006.01); C22C 38/00(2006.01); C22C 38/06(2006.01);
 C22C 38/58(2006.01); C22C 38/60(2006.01)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean utility models and applications for utility models: IPC as above
 Japanese utility models and applications for utility models: IPC as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

eKOMPASS (KIPO internal) & keywords: 강판(steep sheet), 고강도(high strength), 가공성(workability), 베이나이트(bainite),
 마르텐사이트(martensite), 오스테나이트(austenite)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	KR 10-2018-0125560 A (KABUSHIKI KAISHA KOBE SEIKO SHO (KOBE STEEL, LTD.)) 23 November 2018 (2018-11-23) See paragraph [0103], claims 1 and 4-5 and table 2-1.	1-7
A	KR 10-2019-0107089 A (JFE STEEL CORPORATION) 18 September 2019 (2019-09-18) See claims 1-3 and 5 and table 2-1.	1-7
A	KR 10-2014-0041838 A (NIPPON STEEL & SUMITOMO METAL CORPORATION) 04 April 2014 (2014-04-04) See claims 1-8 and tables 8 and 9.	1-7
A	WO 2011-093490 A1 (NIPPON STEEL CORPORATION et al.) 04 August 2011 (2011-08-04) See claims 1-8 and tables 2 and 3.	1-7
A	JP 2016-194138 A (KOBE STEEL LTD.) 17 November 2016 (2016-11-17) See claims 1-10 and table 2-1.	1-7

☐ Further documents are listed in the continuation of Box C. ☒ See patent family annex.

* Special categories of cited documents:

“A” document defining the general state of the art which is not considered to be of particular relevance

“D” document cited by the applicant in the international application

“E” earlier application or patent but published on or after the international filing date

“L” document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

“O” document referring to an oral disclosure, use, exhibition or other means

“P” document published prior to the international filing date but later than the priority date claimed

“T” later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

“X” document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

“Y” document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

“&” document member of the same patent family

Date of the actual completion of the international search

10 March 2022

Date of mailing of the international search report

10 March 2022

Name and mailing address of the ISA/KR

**Korean Intellectual Property Office
 Government Complex-Daejeon Building 4, 189 Cheongsaro, Seo-gu, Daejeon 35208**

Facsimile No. +82-42-481-8578

Authorized officer

Telephone No.

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2021/017992

Patent document cited in search report	Publication date (day/month/year)	Patent family member(s)	Publication date (day/month/year)
KR 10-2018-0125560 A	23 November 2018	CN 108779533 A	09 November 2018
		CN 108779533 B	03 November 2020
		EP 3438309 A1	06 February 2019
		EP 3438309 B1	12 May 2021
		JP 2017-186647 A	12 October 2017
		JP 6762868 B2	30 September 2020
		KR 10-2184257 B1	30 November 2020
		MX 2018010467 A	29 November 2018
		US 2019-0071757 A1	07 March 2019
KR 10-2019-0107089 A	18 September 2019	WO 2017-169329 A1	05 October 2017
		CN 110312813 A	08 October 2019
		CN 110312813 B	20 July 2021
		EP 3581670 A1	18 December 2019
		EP 3581670 B1	07 April 2021
		JP 6384641 B1	05 September 2018
		JP WO2018-147400 A1	14 February 2019
		KR 10-2225998 B1	09 March 2021
		MX 2019009599 A	14 October 2019
KR 10-2014-0041838 A	04 April 2014	US 2020-0040420 A1	06 February 2020
		WO 2018-147400 A1	16 August 2018
		BR 112014002023 A2	21 February 2017
		BR 112014002023 B1	26 March 2019
		CA 2840816 A1	07 February 2013
		CA 2840816 C	31 May 2016
		CN 103717771 A	09 April 2014
		CN 103717771 B	01 June 2016
		EP 2740812 A1	11 June 2014
KR 10-2013-018740 A1	04 August 2011	EP 2740812 B1	11 September 2019
		ES 2755414 T3	22 April 2020
		JP 5240421 B1	17 July 2013
		JP WO2013-018740 A1	05 March 2015
		KR 10-1598307 B1	26 February 2016
		MX 2014000919 A	12 May 2014
		MX 360333 B	29 October 2018
		PL 2740812 T3	31 March 2020
		RU 2014107493 A	10 September 2015
WO 2011-093490 A1	04 August 2011	RU 2573154 C2	20 January 2016
		TW 201313919 A	01 April 2013
		TW I471425 B	01 February 2015
		US 10351937 B2	16 July 2019
		US 2014-0205855 A1	24 July 2014
		WO 2013-018740 A1	07 February 2013
		ZA 201401401 B	30 September 2015
		BR 112012018697 A2	03 May 2016
		BR 112012018697 B1	21 November 2018
WO 2011-093490 A1	04 August 2011	CA 2788095 A1	04 August 2011
		CA 2788095 C	23 December 2014
		CN 102770571 A	07 November 2012
		CN 102770571 B	09 July 2014
WO 2011-093490 A1	04 August 2011	EP 2530180 A1	05 December 2012

Form PCT/ISA/210 (patent family annex) (July 2019)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2021/017992

Patent document cited in search report	Publication date (day/month/year)	Patent family member(s)	Publication date (day/month/year)
		EP 2530180 B1	14 November 2018
		ES 2705232 T3	22 March 2019
		JP 4902026 B2	21 March 2012
		JP WO2011-093490 A1	06 June 2013
		KR 10-1477877 B1	30 December 2014
		KR 10-2012-0107003 A	27 September 2012
		MX 20120008690 A	23 August 2012
		PL 2530180 T3	31 May 2019
		US 2012-0305144 A1	06 December 2012
		US 9410231 B2	09 August 2016
JP 2016-194138 A	17 November 2016	CN 107429370 A	01 December 2017
		CN 107429370 B	24 January 2020
		EP 3279362 A1	07 February 2018
		EP 3279362 B1	21 April 2021
		JP 6554396 B2	31 July 2019
		KR 10-2017-0131606 A	29 November 2017
		KR 10-2174558 B1	05 November 2020
		MX 2017012442 A	26 January 2018
		US 2018-0037964 A1	08 February 2018
		WO 2016-158159 A1	06 October 2016

Form PCT/ISA/210 (patent family annex) (July 2019)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- JP 2009019258 A [0009]
- JP 2016216808 A [0009]