



(12) **CORRECTED EUROPEAN PATENT APPLICATION**  
published in accordance with Art. 153(4) EPC

(15) Correction information:  
**Corrected version no 1 (W1 A1)**  
**Corrections, see**  
**Bibliography INID code(s) 71**

(51) International Patent Classification (IPC):  
**C10M 169/04 (2006.01)** **C10N 30/12 (2006.01)**  
**C10N 40/00 (2006.01)** **C10M 129/26 (2006.01)**  
**C10M 129/36 (2006.01)** **C10M 129/68 (2006.01)**  
**C10M 133/16 (2006.01)** **C10M 137/04 (2006.01)**

(48) Corrigendum issued on:  
**13.12.2023 Bulletin 2023/50**

(52) Cooperative Patent Classification (CPC):  
**C10M 171/001; C10M 157/08; C10M 2207/026;**  
**C10M 2207/125; C10M 2207/283; C10M 2207/289;**  
**C10M 2215/04; C10M 2215/10; C10M 2223/04;**  
**C10M 2223/041; C10N 2020/02; C10N 2030/12;**  
**C10N 2030/24; C10N 2040/00**

(43) Date of publication:  
**01.11.2023 Bulletin 2023/44**

(21) Application number: **21910991.5**

(86) International application number:  
**PCT/JP2021/047982**

(22) Date of filing: **23.12.2021**

(87) International publication number:  
**WO 2022/138852 (30.06.2022 Gazette 2022/26)**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB**  
**GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO**  
**PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**  
Designated Validation States:  
**KH MA MD TN**

(72) Inventors:  
• **SATO, Tokue**  
**Ichihara-shi, Chiba 299-0107 (JP)**  
• **GOTO, Kenji**  
**Ichihara-shi, Chiba 299-0107 (JP)**

(30) Priority: **25.12.2020 JP 2020217796**

(74) Representative: **Hoffmann Eitle**  
**Patent- und Rechtsanwälte PartmbB**  
**Arabellastraße 30**  
**81925 München (DE)**

(71) Applicant: **Idemitsu Kosan Co.,Ltd.**  
**Tokyo 100-8321 (JP)**

(54) **LUBRICATING OIL COMPOSITION, METHOD FOR USING LUBRICATING OIL COMPOSITION, AND METHOD FOR PRODUCING LUBRICATING OIL COMPOSITION**

(57) A problem is to provide a lubricating oil composition having an excellent rust inhibiting capability even containing a base oil containing a polar substance that has a function significantly deteriorating the rust inhibiting capability, and a use method and a production method of the lubricating oil composition. The problem is solved by a lubricating oil composition containing a base oil (A) and a rust inhibitor (B), in which the base oil (A) has a gas chromatogram measured by gas chromatography satisfying the particular condition ( $\alpha$ ), and the rust inhibitor (B) is one or more kind selected from the group consisting of a first rust inhibitor (B1), a second rust inhibitor (B2), a third rust inhibitor (B3), and a fourth rust inhibitor (B4), and satisfies the particular condition ( $\beta$ ).

Fig. 1

