



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:  
**20.03.2024 Bulletin 2024/12**

(51) International Patent Classification (IPC):  
**E01C 13/08<sup>(2006.01)</sup>**

(21) Application number: **23164428.7**

(52) Cooperative Patent Classification (CPC):  
**E01C 13/08**

(22) Date of filing: **09.09.2022**

(84) Designated Contracting States:  
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR**  
Designated Extension States:  
**BA ME**  
Designated Validation States:  
**KH MA MD TN**

- **GROCHLA, Dario**  
**44869 Bochum (DE)**
- **HAMANN, Sven**  
**45472 Mülheim (DE)**

(74) Representative: **Richardt Patentanwälte PartG mbB**  
**Wilhelmstraße 7**  
**65185 Wiesbaden (DE)**

(62) Document number(s) of the earlier application(s) in accordance with Art. 76 EPC:  
**22194961.3 / 4 335 969**

(71) Applicant: **Polytex Sportbeläge Produktions-GmbH**  
**47929 Grefrath (DE)**


(72) Inventors:  
• **SICK, Stephan**  
**76532 Baden-Baden (DE)**

Remarks:

- Amended claims in accordance with Rule 137(2) EPC.
- This application was filed on 27.03.2023 as a divisional application to the application mentioned under INID code 62.
- Claims filed after the date of filing of the application / after the date of receipt of the divisional application (Rule 68(4) EPC).

(54) **ARTIFICIAL TURF INFILL WITH OLIVE PIT FRAGMENTS AND MICROPOROUS ZEOLITE PARTICLES**

(57) An artificial turf infill comprising olive pit fragments and microporous zeolite particles.



**FIG. 1**

## Description

### Field of the invention

[0001] The invention relates generally to an artificial turf, and, more particularly, to an artificial turf infill comprising olive pit material, to an artificial turf using said artificial turf infill, and a method of making said artificial turf infill.

### Background

[0002] Use of artificial turf for the surface of sport fields, natural lawn replacement for back yards and public squares, etc. is increasing rather rapidly due to the convenience and economic efficiency of maintenance compared to natural turf.

[0003] One of the problems associated with existing artificial turf designs is the use of synthetic materials like rubber and elastic particles as infill which can find their way into various waterways and water reservoirs.

[0004] Heretofore some efforts have been made for the development of an infill that uses organic materials rather than elastic synthetic materials. See, for example, EP2917413B1 ("EP'413"), US10822751B2 ("US'751"), and US 10822752B2 ("US'752") proposing various bio-based materials. The EP'413 and the US'751 patents describe the use of vegetable material comprising the rachis of cereal ear as infill, while the US'752 patent describes an infill which uses cellulosic fiber material from pine wood.

[0005] EP3868955A1 patent application describes using olive pit particles as infill for artificial turf which are produced by crushing naturally occurring pits in a grinder, granulator, or cracker mill. The general concept of using olive pit particles is rather known since at least 2010 by the publication of US2010/055461 patent application which describes an artificial turf having organic particles of a group consisting of, coconut shells, ground pecan shells, ground peanut shells, ground corn cobs, and ground olive stones. See also the US2018/0080183, US6,632,527, US2002/0048676, US2006/0121236, US2008/0176010, and US2015/0252537 patent references which describe various bio-based material infills for artificial turfs.

[0006] The article "Sustainable infill from natural olive pits," published in the Kompendium Sportplatz journal 3<sup>rd</sup> Edition 2022, p. 107, describes grinding olive pits and using the generated olive particles as infill for an artificial turf.

[0007] Despite the above rather limited attempts to produce an artificial turf infill purely or predominantly comprising organic materials that has satisfactory performance characteristics in varying weather conditions over an extended period of time, to date there is no practical solution that can satisfy these requirements. Improved solutions are needed that employ organic infill that protects the environment, provides proper foot traction, re-

duced biodegradation and enhanced resistance to microbial infestations in moist and wet conditions.

### Summary of the Invention

[0008] The present invention provides an artificial turf infill, an artificial turf employing the artificial turf infill, and a method of forming the artificial turf infill in the independent claims. Various embodiments of the present invention are given in the dependent claims. Embodiments of the present invention provide new, improved solutions to the above problems associated with the prior art.

[0009] According to an aspect of the present invention an artificial turf infill is provided comprising an olive pit material, and microporous zeolite particles.

[0010] The olive pit material may comprise rounded and thermally treated olive pit fragments having a size of 0.5 mm or greater, in particular 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, in an amount of at least 80.0 wt%, in particular 90.0 wt% to 99.0 wt%, more in particular 95.0 wt% to 99.0 wt%, and most in particular 98.0 wt% to 99.0 wt% of the total weight of the total olive pit material in the infill. The olive pit material may further comprise olive pit particles having a size of less than 63  $\mu$ m in an amount of at least 0.5 wt%, in particular 1.0 wt% to 20.0 wt%, more in particular 1.0 wt% to 10.0 wt %, and most in particular 1.0 wt% to 2.0 wt% of the total olive pit material in the infill.

[0011] The olive pit material may have a bimodal size distribution with a major mode and a minor mode, wherein the major mode comprises the rounded, thermally treated olive pit fragments and has a peak between 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, and wherein the minor mode comprises the olive pit particles and has a peak at less than 63  $\mu$ m.

[0012] The olive pit material may be thermally treated at a temperature of 80 °C to 250 °C.

[0013] The rounded, and thermally treated olive pit fragments may be obtained by a tumbling treatment of fractured olive pits together with the microporous zeolite particles. The olive pit fragments may be formed by fracturing in an olive oil extraction process during a compression operation of the olives for extracting oil from the olives and have sharp edges due to the fracturing. The thermo-tumbling process smoothens the sharp edges by attrition by rubbing the olive pit particles against each other and against the microporous zeolite particles to form the rounded, thermally treated olive pit fragments.

[0014] The microporous zeolite particles may be added in the infill in an amount of 1.0 to 30.0 wt%, in particular 5.0 to 25.0 wt%, and more in particular 10.0 to 20.0 wt% of the total amount of the infill.

[0015] The microporous zeolite particles may have a grain size between 0.1 mm and 1.5 mm, in particular between 0.4 mm to 1.2 mm, and more in particular between 0.9 mm and 1.2 mm, and a maximum surface spe-

cific surface area of 21 m<sup>2</sup>/g.

**[0016]** The microporous zeolite particles may have a porosity between 15% and 20% volume parts.

**[0017]** In some embodiments, the microporous zeolite particles may have a grain size distribution wherein 70% to 90% of the grains by weight have a size in the range of 0.4 mm to 1.5 mm and 10% to 30% of the grains by weight have a size smaller than 0.4 mm.

**[0018]** The microporous zeolite particles may have a hardness between 3.5 and 5.5 on the Mohs scale and a moisture level smaller than 6 wt% as measured by the wet method, i.e., based on the total weight of the zeolite solids and moisture.

**[0019]** The artificial turf infill may further comprise at least one further bio-based material including pit fragments of at least one other stone-containing fruit, wherein the pit fragments of the further bio-based material have a different elasticity than the rounded, and thermally treated olive pit fragments, and wherein the at least one further bio-based material comprises cork particles, rounded cherry pit fragments, and combinations thereof.

**[0020]** The artificial turf infill may comprise only bio-based materials and being free of any rubber, elastomeric, or polymer-based infill, and, in particular also free of any sand.

**[0021]** Another aspect of the present invention is directed to an artificial turf comprising the artificial turf infill as described above and in any of the claims 1-12.

**[0022]** The artificial turf may further comprise:

a stabilization layer comprising or consisting of at least one of sand, the olive pit particles, and at least a portion of the microporous zeolite particles; and a performance layer positioned on the stabilizing layer, wherein the performance layer comprises or consists of the artificial turf infill of any of the preceding claims or comprises or consists of the rounded and thermally treated olive pit fragments and is basically free of the olive pit particles.

**[0023]** Yet another aspect of the present invention is directed to a method of creating an artificial turf, the method comprising:

installing an artificial turf,  
applying the artificial turf infill of any one of claims 1-14 on the installed artificial turf, wherein the infill comprises at least a mixture of the rounded, olive pit fragments, the olive pit particles and the microporous zeolite particles, wherein the applying the artificial turf infill on the installed artificial turf is performed in a single step,  
allowing the olive pit particles in the applied infill to automatically trickle down into the voids between the fragments, thereby automatically forming a stabilizing layer consisting essentially of the trickled-down particles, and a performance layer containing the rounded olive pit fragments,

wherein at least a portion of the microporous zeolite particles trickles down and settles into the stabilizing layer.

5 Yet another aspect of the present invention is directed to a kit for manufacturing an artificial turf, the kit comprising the artificial turf infill of any of the claims 1 to 16 and at least one other component for making the artificial turf.

10 **[0024]** Unlike the prior art, where olive pits are crushed into sharp, and comparatively very small infill particles using an extra crushing step, the present invention uses larger size olive pit fragments from olive oil extraction processes without applying an additional crushing step. The sharp edges of the olive pit particles may make them 15 uncomfortable to the skin of the artificial turf users and may even injure the skin of the artificial turf users.

**[0025]** Unlike the prior art, the present invention further treats the olive pit fragments for rounding their edges, make them smoother before using them as infill.

20 **[0026]** Unlike the prior art, the present invention olive pit fragments are thermally treated for removing the residual odor from the olives, increasing their surface hardness and tenacity, and making them antimicrobially resistant, and attrition resistant.

25 **[0027]** Unlike the prior art, the method of the present invention is free of a step which crushes or grinds the not-yet rounded olive pit fragments or the rounded olive-pit fragments.

30 **[0028]** These and other features and advantages of the present invention will become better understood from the following detailed description of the invention in conjunction with the accompanying drawings.

### **Brief Description of the Drawings**

35 **[0029]** In the following, embodiments of the invention are explained in greater detail, by way of example only, making reference to the drawings in which:

40 Figure 1 shows an artificial turf having an infill from rounded and thermally treated olive pit fragments according to some embodiments of the present invention;

45 Figure 2A is a simplified schematic of an olive extraction process according to some embodiments of the present invention;

Figure 2B is a simplified schematic of a thermo-tumbling process according to some embodiments of the present invention followed by a sieving operation;

50 Figure 3 shows a further embodiment of an artificial turf with an infill comprising a stabilization layer and a performance layer;

55 Figures 4A and 4B illustrate a single step application of an infill mixture on the artificial turf and its subse-

quent self-segregation into a stabilizing and a performance layer;

Figure 5 is a simplified flow chart of a method of making an infill according to some embodiments of the present invention; and

Figures 6A to 6E shows rounded and thermally treated olive pit fragments produced by the thermo-tumbling process at different magnifications in an infill layer formation.

### **Detailed Description of the Invention**

**[0030]** Like numbered elements in these figures are either equivalent elements or perform the same function. Elements which have been discussed previously may not necessarily be discussed in later figures.

**[0031]** According to its broadest aspects the present invention provides a bio-based infill that exhibits improved performance characteristics in varying weather conditions over an extended period of time. The bio-based infill includes an olive pit material and, in some embodiments, at least one other bio-based infill. In some embodiments the bio-based material includes microporous zeolite particles. The present invention further provides a method for making the artificial turf infillartificial turf infillinfill.

**[0032]** In some embodiments, the olive pit material is prepared using olive pit fragments generated in an oil extraction process which uses compression for extracting the olive oil. For example, the oil extraction process may employ an olive press. The olive pit fragments may have sharp edges which are created when the olive pits break under the compression force in the olive press. In some embodiments, the present invention uses a tumbling treatment of the olive pit fragments to smoothen their sharp edges, and provide rounded olive pit fragments which are substantially free of any sharp edges. The same tumbling process may also be used for any additional bio-based material. In some embodiments, the additional bio-based material may be tumbled together with the olive pit fragments to enhance the effectiveness of the tumbling process in rounding the sharp edges of the olive pit fragments. In some embodiments, the artificial turf infill comprises the rounded olive pit fragments prepared by the tumbling treatment process.

**[0033]** Rounded as this term is used here, means that the fragments do not have sharp edges which can cause skin injury to the users of the artificial turf.

**[0034]** According to embodiments, rounded fragments are fragments generated in an abrasive process, in particular by tumbling. As a consequence of tumbling, traces of tumbling may be visible on the surface of the fragments.

**[0035]** The tumbling of the olive pit fragments generates an olive pit material having bimodal size distribution with a major mode comprising rounded olive pit frag-

ments having a size greater than 0.5 mm, in particular 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm. A minor mode of the bimodal distribution comprises olive pit particles having a size of less than 63  $\mu\text{m}$ .

**[0036]** According to embodiments, the tumbling is controlled to generate the olive pit particles having a size less than 63  $\mu\text{m}$  in an amount of at least 0.5 wt%, in particular 1.0 wt% to 20.0 wt%, more in particular 1.0 wt% to 10.0 wt %, and most in particular 1.0 wt% to 2.0 wt% of a total olive pit material generated by the tumbling. Controlling the tumbling includes controlling the tumbling intensity and the duration of the tumbling among other things. Other parameters may include the presence or absence of other materials and the design characteristics of the tumbling apparatus such as internal design, size, and the presence of any baffles.

**[0037]** In some embodiments, the olive pit material comprising the olive pit fragments is thermally treated. The thermal treatment may be performed simultaneously with the tumbling treatment or separately from the tumbling treatment.

**[0038]** The conditions of the thermal treatment may be modified to adjust its effects on the moisture and chemical composition of the olive pit material which in turn affect the properties of the olive pit fragments.

**[0039]** The tumbling and/or thermal treatments allow adjusting the properties of the infill to improve the overall design of an artificial turf. For example, depending on turf blade length, density and other characteristics of an artificial turf, the infill may be modified as may be needed by changing the size, roundness, surface hardness, tenacity, moisture content and even chemical composition of the olive pit fragments. These adjustments can be done by changing the time, and intensity of the tumbling and/or of the thermal treatments.

**[0040]** The removal of the sharp edges via the tumbling process in combination with the thermal treatment of the olive pit fragments results in an olive pit material that when added as infill in an artificial turf exhibits an exceptional balance of traction, energy absorption, stable foot and energy restitution characteristics which can meet the standards for professional sport fields artificial turfs, including soccer, rugby, American football and the like. In this regard, it is believed, without wishing to be bound by theory, that the rounded surface hardened fragments allow a controlled rolling movement against each other, thus preventing excessive friction with the shoes of the athletes using the turf. At the same time the rounded surface hardened fragments provide sufficient support and stable footing.

**[0041]** The olive pit material of the invention can be used as infill for artificial turfs for professional sport fields, however, it can also be used in other applications such as, for example, artificial turfs in parks and private gardens.

**[0042]** According to some embodiments of the present invention, an artificial turf infill is provided comprising

rounded and thermally treated olive pit fragments.

**[0043]** According to some embodiments, the infill comprises rounded and thermally treated olive pit fragments and optionally whole olive pits. The whole pits are olive pits which did not break during the oil extraction process or during the thermo-tumbling treatment.

**[0044]** According to some embodiments, the infill comprises rounded and thermally treated olive pit fragments, olive pit particles and optionally also some whole olive pits.

**[0045]** It is noted that the size of the fragments can be adjusted within the aforementioned ranges to meet the specific design requirements of an artificial turf which may also depend on the length of the turf fibers and the density of the turf fibers. One of the advantages of the present invention is that the size, surface hardness, and degree of smoothness (or roughness) of the fragments, can be customized to meet the requirements of any particular artificial turf design by adjusting the processing conditions of the tumbling and thermal treatments.

**[0046]** According to some embodiments, an "olive pit particle" is a piece of olive pit material with a size of less than 63  $\mu\text{m}$  in size (larger dimension or diameter). It is noted that having the olive pit particles in the infill is generally advantageous because they tend to settle and form a lower stabilization layer which can eliminate the need for a stabilization layer of sand which is used conventionally in existing artificial turf infill systems. An infill without sand is desirable because sand tends to stick very tightly to the other artificial turf material (especially to the backing of the artificial turf) and can damage the shredders used to shred the artificial turf material when the artificial turf is recycled at the end of its useful life. Also, the process of installing the artificial turf is simplified because a step of adding a sand layer can be eliminated.

**[0047]** According to some embodiments, the total amount of olive pit material in the infill comprises at least 80.0 wt%, in particular 90.0 wt% to 99.0 wt%, more in particular 95.0 wt% to 99.0 wt%, and most in particular 98.0 wt% to 99.0 wt% of the rounded and thermally treated olive pit fragments. Also, the olive pit particles may be in an amount of at least 0.5 wt%, in particular 1.0 wt% to 20.0 wt%, more in particular 1.0 wt% to 10.0 wt%, and most in particular about 1.0 wt% to 2.0 wt% of the total weight of the olive pit material.

**[0048]** According to some embodiments, the total amount of olive pit material in the infill comprises 95.0 wt% to 99 wt% of the rounded and thermally treated olive pit fragments having a size of 0.5 mm to 2.0 mm and olive pit particles having a size of less than 63  $\mu\text{m}$ , in an amount of 1.0 wt% to 2.0 wt% of the total weight of the olive pit material.

**[0049]** According to some embodiments, the total amount of olive pit material in the infill comprises 98.0 wt% to 99.0 wt% of the rounded and thermally treated olive pit fragments having a size of 0.5 mm to 2.0 mm and olive pit particles having a size of less than 63  $\mu\text{m}$ , in an amount of 1.0 wt% to 2.0 wt % of the total weight

of the olive pit material.

**[0050]** According to some embodiments, the rounded and thermally treated olive pit fragments are obtained by a thermo-tumbling treatment of olive pit fragments. The olive pit fragments are formed in an olive oil extraction process which employs a compression operation of the olives for extracting oil from the olives. The compression oil extraction process causes the olive pits to break creating the olive pit fragments which generally may have sharp edges. The olive pit fragments are separated from the other products of the olive oil extraction process, i.e., the extracted olive oil, the pulp and the skin of the olives and are subjected to the thermo-tumbling treatment. The thermo-tumbling treatment smoothens the sharp edges of the fragments. Olive pit particles having a size of less than 63  $\mu\text{m}$  may be generated during the tumbling treatment. According to some embodiments, the thermo-tumbler product including the rounded olive pit fragments and the olive pit particles obtained from the thermo-tumbling treatment are sieved to remove at least partially some of the olive pit particles.

**[0051]** According to some embodiments, an artificial turf infill is provided which comprises, in addition to the rounded and thermally treated olive pit fragments, at least one further biobased material including pit fragments of at least one other stone-containing fruit (i.e., other than olives), wherein the pit fragments of the further bio-based material have a different elasticity than the rounded and thermally treated olive pit fragments.

**[0052]** According to some embodiments, the at least one further bio-based material comprises cork particles, cherry pit fragments and combinations thereof. The cork and cherry pit fragments may be subjected to the same tumbling and thermal treatments as the olive pit fragments. The cork and cherry pit fragments may be subjected to the same tumbling and thermal treatments as the olive pit fragments, for example, by adding them in the same thermo-tumbler apparatus together with the olive pit fragments. According to some embodiments, the infill fragments made of the further bio-based material may be larger than the rounded and thermally treated olive pit fragments. According to some embodiments, the infill fragments made of the further bio-based material may have a size (largest dimension or diameter) of 0.5 to 4.0 mm, in particular 0.5 to 3.0 mm.

**[0053]** According to an aspect of the present invention, an artificial turf is provided using the inventive artificial turf infill. According to some embodiments, the artificial turf may comprise a stabilization layer comprising or consisting of the olive pit particles. In some embodiments, the stabilization layer may also include particles of the at least one other bio-based material. The olive pit particles and when used the particles of the at least one other bio-based material may be obtained from the thermo-tumbling treatment. The artificial turf may also comprise a performance infill layer positioned over the stabilization infill layer. The rounded and thermally treated olive pit fragments may form the performance infill layer. The per-

formance infill layer may cover the stabilization layer. In some embodiments, the performance infill layer may also include fragments of the at least one other bio-based material in addition to the rounded and thermally treated olive pit fragments. The rounded and thermally treated olive pit fragments and the fragments of the other bio-based material may be obtained from the same tumbling and thermal treatments.

**[0054]** According to some other embodiments the artificial turf may comprise an infill layer made of the rounded and thermally treated olive pit fragments. In yet some other embodiments the artificial turf may comprise an infill layer made of the rounded and thermally treated olive pit fragments and fragments of the at least one other bio-based material.

**[0055]** Preferably, the artificial turf comprises an infill which consists entirely of bio-based materials.

**[0056]** A "bio-based material" as used herein is a material wholly or partly derived from materials of biological origin, excluding materials embedded in geological formations and/or fossilized materials. In particular, bio-based materials can be materials which predominantly (> 50 wt%) comprise or consist of biodegradable and/or compostable materials, and, in some embodiments, materials only consisting of compostable materials.

**[0057]** Hence, unlike typical artificial turf infill, the present invention infill can be made totally free of any sand, or of any non-bio-based, synthetic infill like the rubber, elastomeric, or polymer-based materials used in infills of the state of the art.

**[0058]** According to another aspect of the present invention, zeolite particles may be added in the infill of the artificial turf. Preferably, the zeolite particles are added in the stabilization layer. Preferably, the zeolite particles may be microporous zeolite particles. These microporous zeolite particles provide a cooling effect via storing water in their pores during rainy weather conditions or when the turf is watered, and slowly releasing via evaporation of the stored water during hot days.

**[0059]** In some embodiments, an infill is provided which is made of biodegradable material, and is essentially free of any synthetic, non-biodegradable material. Essentially free means that less than 1 wt%, preferably less than 0.5 wt% of the infill may be synthetic, non-biodegradable material. Other natural materials such as zeolite and sand may be added in the infill.

**[0060]** In some embodiments, an infill is provided which is made of compostable material, and is essentially free of any synthetic, non-biodegradable material. Essentially free means that less than 1 wt%, preferably less than 0.5 wt% of the infill may be synthetic, non-biodegradable material. Other natural materials such as zeolite and sand may be added in the infill.

**[0061]** According to yet another aspect of the present invention, the rounded and thermally treated olive pit fragments are made accordingly to a method comprising providing olive pit fragments from an oil extraction process employing compressing the olives for extracting the

olive oil, and tumbling the olive pit fragments to smoothen sharp edges of the olive pit fragments to produce rounded olive pit fragments. For example, the method may include feeding the olive pit fragments in a tumbler, and tumbling them at an effective tumbling intensity and for an effective amount of time to smooth out substantially all sharp edges of the olive pit fragments and produce rounded and thermally treated olive pit fragments.

**[0062]** According to some embodiments, the tumbling intensity may be adjusted to effectively remove all sharp edges of the olive pit fragments. The tumbling is performed at an effective tumbling intensity and for an effective amount of time inside the tumbler apparatus to generate rounded olive pit fragments which are substantially free of any sharp edges. As a result of the smoothening of the sharp edges the very small size olive pit particles are formed.

**[0063]** The tumbling generates an olive pit material having a bimodal size distribution.

**[0064]** In some embodiments, the method may further comprise thermally treating the olive pit fragments. According to some embodiments, thermal treatment involves heating to a temperature of 80 °C to 130 °C, in particular 100 °C to 130 °C, and more in particular 110 °C to 130 °C.

**[0065]** Thermal treatment in this temperature range between 80 °C and 130 °C may remove any residual natural smell of the olive pits and may also reduce the amount of equilibrium moisture in the olive pit material.

**[0066]** In some embodiments, heat treatment means that the olive pit fragments are heated to a sufficiently high temperature, that the heat treatment not only reduces the equilibrium moisture of the olive pit material and eliminates any residual olive odor, but also modifies their chemical structure. Chemical modification of the olive pit structure may be measured by X-ray photoelectron analysis (XPS) of the oxygen to carbon ratio of the material. In some embodiments, thermally treated olive pit material means that the olive pit material has been sufficiently heated to show at least a 3%, preferably at least 5%, and more preferably 5% to 10 % reduction in the oxygen to carbon ratio compared to thermally untreated olive pit material as measured by XPS analysis. It has been found that such higher temperature thermal treatment transforms the olive pit material to become (like tropical wood) more durable and resistant to decay in a moist/humid environment. It has been found that heating above a temperature of 130 °C, and preferably 150 °C is needed for this chemical modification to occur.

**[0067]** Thermal treatment at higher temperatures than 150 °C, in particular 160 °C to 250 °C, and more in particular of 180 °C to 250 °C has the advantage that the antimicrobial resistance of the olive pit fragments is increased, and their hygroscopicity is reduced significantly. Also, the surface hardness and tenacity of the treated material is increased. The olive pit fragments become more durable, more resistant to biodegradation in moist and humid conditions and also more resistant to addi-

tional fracturing or attrition when used as infill in an artificial turf.

**[0068]** In some embodiments, the thermal treatment heats the olive pit material to a temperature higher than 150 °C, in particular 160 °C to 250 °C, and more in particular 180 °C to 250 °C.

**[0069]** Thermal treatment at these higher temperatures has the benefit of increasing the resistance of the olive pit fragments against moisture-induced biodegradation, which is particularly beneficial in humid regions or when the artificial turf infill comprises a zeolite which is irrigated frequently before and during a game to cool the sports field and the players.

**[0070]** Although not wishing to be bound by any particular theory, it is believed that heat treatment at the elevated temperature above 130 °C and in particular at a temperature of 150 °C to 250 °C not only removes any residual moisture or odors but, more importantly, also changes the chemical structure/composition of the hemicellulose, cellulose and lignin components of the olive pit fragments which results in substantially reduced hygroscopicity or effectively almost zero hygroscopicity for the thermally treated olive pit material at such temperatures. As a result, the olive pit material becomes resistant to natural biodegradation and is also much less likely to suffer from microbial infestations. These properties make the thermally treated artificial turf infill of the present invention particularly suitable to be used with microporous zeolite particles that can be used to store water during watering of the turf and release it gradually thereafter, thus, cooling the turf and the athletes (or users) of the turf without reducing the useful lifespan of the infill (and of the turf) due to the increased moisture conditions. Thus, the artificial turf infill and artificial turf using the artificial turf infill of the present invention can be watered more frequently and also last longer than existing turfs.

**[0071]** Heating for the thermal treatment may be performed with any suitable means. In some embodiments, hot air, steam or superheated steam may be fed inside a tumbling apparatus and the heat treatment may be performed simultaneously with the tumbling treatment. In some other embodiments the heat treatment may be performed separately and independently of any tumbling treatment, for example in an oven. The temperature and duration of the thermal treatment may be adjusted as may be needed for adjusting the effects of the heat treatment on the properties of the olive pit material.

**[0072]** In some embodiments the duration of the tumbling treatment of the olive pit fragments may range for a period of 1 minute to 8 minutes, and in particular for a period of 2 minutes to 6 minutes. For example, the tumbling treatment may in some embodiments last for a period of 2.5 minutes to 3 minutes. However, these time periods are provided only as examples, and longer periods may be used without departing from the scope of the present invention. For example, generally, the tumbling and/or thermal treatment may last from a few minutes to a few hours.

**[0073]** According to some embodiments, the method comprises sieving the thermo-tumbler product to remove at least some of the thermo-tumbler product olive pit particles having a size of less than 63 µm. The removed olive pit particles may be used for forming a stabilization layer for the infill.

**[0074]** In a preferred embodiment, the product from the thermo-tumbler is used without separation or sieving to form an infill layer for an artificial turf. According to some embodiments, the method further comprises mixing together with the olive pit fragments, or the rounded olive pit fragments or the rounded and thermally treated olive pit fragments, at least one other bio-based material including cork particles, and cherry pits whole, fragments, or mixtures thereof.

**[0075]** For example, fragments of at least one other bio-based material may also be fed in a thermo-tumbler and mixed together with the olive pit fragments.

**[0076]** According to some embodiments, at least one of sand, and zeolite, preferably just zeolite and, in particular, microporous zeolite particles, may be mixed together with the olive pit fragments, or the rounded olive pit fragments or the rounded and thermally treated olive pit fragments and the at least one other bio-based material.

**[0077]** The microporous zeolite particles are added in an amount of 1.0 to 30.0 wt%, in particular 5.0 to 25.0 wt%, and more in particular 10.0 to 20.0 wt% of the total amount of the infill. The zeolite is added for providing a cooling effect in the infill because the zeolite microporous material absorbs water in rainy, wet conditions and releases by evaporation in hot sunny days to cool down the infill and the turf. The zeolite may also improve the overall shaping of the olive pit fragments and of any additional bio-based additional stones by providing added abrasion during the tumbling process.

**[0078]** According to some embodiments, the infill comprises only bio-based materials and is free of any rubber, elastomeric, or polymer-based infill, and is preferably also free of any sand.

**[0079]** The method for making the artificial turf infill according to the present invention does not include any step of crushing or grinding the not-yet rounded olive pit fragments or the rounded olive-pit fragments.

**[0080]** According to another aspect of the present invention, a method of use of the artificial turf infill is provided wherein the artificial turf infill can be used to form the infill of an artificial turf.

**[0081]** According to some embodiments, a method for forming an infill for an artificial turf is provided, the method comprising:

providing an infill mixture comprising:

component a including the rounded and thermally treated olive pit fragments and optionally fragments of at least one additional bio-based material, component b comprising microporous zeolite particles, and

component c comprising olive pit particles, and applying the infill mixture of components, a, b and c in a single-step on an installed artificial turf system comprising a plurality of turf fibers secured to a backing material, wherein within a period of time of one month or less, preferably 1 week or less, and more preferably 1 day or less the components a, b, and c separate into at least a stabilization layer, and a performance layer which forms over the stabilization layer, wherein the stabilization layer comprises the thermo-tumbler product olive pit particles, and the microporous zeolite particles, and wherein the performance layer comprises the rounded and thermally treated olive pit fragments and when used the particles of the at least one other bio-based material. According to some embodiments, sand may be used as part of the component b and may settle to become part of the stabilization layer, however, such embodiment is less preferred.

**[0082]** Via the thermo-tumbling treatment, the olive pits and olive pit fragments obtain a rounded shape which is designed to protect the skin of the players from injury, improves the packing density of the infill, reduces undesired water splashing in rainy conditions, and minimizes infill migration into the environment. In addition, the rounded and thermally treated olive pit material has no residual olive odor, has antimicrobial resistance, enhanced surface hardness and tenacity.

**[0083]** The thermo-tumbler product may be used directly or after subsequent post-processing removal of the olive pit particles as artificial turf infill.

**[0084]** The thermo-tumbler product comprises olive pit particles (dust-like particles generated by abrasion). According to some embodiments, the method of preparing the infill, further comprises a sieving operation of the thermo-tumbler product to reduce the amount of the olive pit particles having a size of less than 63  $\mu\text{m}$  to an amount of 2.0 % or less of the thermo-tumbler product, preferably to an amount of 1.0 to 2.0 % by weight of the thermo-tumbler product. Keeping this level of olive pit particles has been found to be beneficial because the olive pit particles allow for a higher packing density of the infill. According to some embodiments, further sieving is possible to reduce the amount of olive pit particles to less than 1.0 wt %.

**[0085]** The removed olive pit particles from the thermo-tumbler product can be used as infill for a stabilization layer either alone or together with sand and/or zeolite, preferably with zeolite only.

**[0086]** When zeolite and/or sand are used, they are also preferably added in the thermo-tumbler to increase the abrasive effect/rounding effect of the thermo-tumbler treatment step.

**[0087]** According to some embodiments, a sand, zeolite, and rounded olive pit fragment mixture is used in particular as the stabilization layer. The zeolite has the

additional advantage of cooling the artificial turf. In another embodiment, a zeolite and rounded olive pit fragment mixture is used in particular as the stabilization layer.

**[0088]** According to some embodiments, a method of creating an artificial turf, comprises installing an artificial turf, and applying the artificial turf infill on the artificial turf. The infill comprises at least a mixture of the rounded and thermally treated olive pit fragments and of the olive pit particles, whereby the application is performed in a single step. The method further comprises allowing the olive pit particles in the applied infill to automatically trickle down into the voids between the fragments, thereby automatically forming a stabilization layer consisting essentially of the trickled-down particles, and a performance layer containing the rounded olive pit fragments. The infill mixture may further include zeolite which may also settle and become part of the stabilization layer. The infill mixture may also comprise at least one other bio-based material which can form the performance layer. It has been found, rather unexpectedly that the tumbling treatment of the olive pit fragments helps this segregation and trickle-down effect, possibly because in addition to the large difference in the relative size of the fragments and the particles their enhanced round shape obtained by the tumbling helps the movement of the small size particles through the much larger fragments. Referring now to figure 1, an artificial turf 10 is provided which comprises an infill 12 comprised of rounded and thermally treated olive pit fragments 24 obtained by a thermo-tumbling treatment of olive pit fragments. The infill 12 further contains olive pit particles 26 also obtained from the thermo-tumbling process. The olive pit particles 26 are smaller in size than the rounded and thermally treated olive pit fragments 24. The olive pit particles 26 have a size of less than 63  $\mu\text{m}$ . In the illustrated embodiment, the olive pit particles 26 may be in an amount of 0.5 wt% to 2.0 wt% and the rounded and thermally treated fragments 24 may be in an amount of 98.0 wt% or greater of the total olive pit material. The olive pit particles 26 may eventually settle to a lower part of the infill 12. In FIG. 1, an enlarged image of the rounded, and thermally treated olive pit fragments are shown from a section of the infill. More images of the olive pit infill in different magnifications are shown in figures 6A to 6E.

**[0089]** Referring now to figure 2A, the olive pit fragments 6 are formed in an olive oil extraction process 2, for example, during a compression operation of olives 1 for the extraction of the olive oil 3 from the olives. Olive oil extraction processes using compression of the olives are well known and, therefore, are not described here in detail. It should also be understood that the olive pit fragments 6 may contain some whole pits, i.e., non-fractured pits.

**[0090]** As illustrated in Figure 2A, the olive pit fragments 6 are separated from the other products, i.e., the extracted olive oil 3, and the olive pulp and skin 4. As shown in FIG. 2B, the olive pit fragments 6 are fed to a



thermo-tumbler 21 to be subjected to a thermo-tumbling treatment.

**[0091]** In a preferred embodiment, the infill 12 of figure 1 consists of a single layer of infill formed of only rounded and thermally treated olive pit fragments 24 and olive pit particles 26 from the thermo-tumbling process, without any rubber-based infill, or polymer-based infill and, more preferably, without any non-bio-based material including any sand.

**[0092]** In a variation of the embodiment of figure 1, the olive pit particles 26 in the infill 12 may be reduced or totally removed by subjecting the thermo-tumbler product 29 to at least one sieving operation to remove some or all of the olive pit particles 26.

**[0093]** The artificial turf 10 comprises a plurality of the artificial turf fibers 16 securely attached to the backing 11. The fibers 16 may be texturized with a non-straight shape such as curly, wavy, or folded shape. The texturization can be produced mechanically or chemically using well-known methods during the fiber manufacturing. The artificial turf fibers may have a density (number of fibers per artificial turf area) and/or degree of texturization that under a bird's eye perspective, at least 60%, more preferentially at least 70% of the size of the area covered by the artificial turf consists of the fibers and the rest consists of the carrier mesh or the backing or the infill.

**[0094]** The turf fibers 16 may be made of synthetic polymer material such as, for example, polyethylene ("PE"), polypropylene ("PP"), polyamide ("PA"), or combinations thereof. The fibers 16 may be mono filament, slit film, fibrillated, texturized, or combinations thereof. The backing 11 may be made of any suitable material. For example, the backing 11 may comprise a thermoset polymer material. According to some embodiments, the backing 11 may comprise a polyurethane resin. However, it is noted that the invention is not limited in any particular turf fiber or backing materials and other suitable turf fiber and backing materials may be used.

**[0095]** The pile height of the artificial turf may vary by design and may be, for example, between about 10.0 mm to about 100.0 mm, preferably between 15.0 mm to 70.0 mm. The pile height is the distance measured from the bottom surface of the turf backing 11 to the tip of the fibers 16. The fibers 16 can be attached to the turf backing 11 by any suitable method including, for example, tufting, weaving, knitting, needle punching, or a combination thereof.

**[0096]** The height of the infill 12 may vary by design and also the pile height. A typical infill height is from about 10.0 mm to 50.0 mm. The infill height is designed to provide adequate weight of the infill per square area of the infill to prevent movement and wrinkles on the artificial turf surface.

**[0097]** Referring to figure 2B, the thermo-tumbling treatment of the olive pit fragments 24 comprises placing them inside a rotating thermo-tumbler 21 and tumbling them while at the same time flowing hot air through the thermo-tumbler 21 to obtain a mixture of rounded and

thermally treated olive pit fragments, and olive pit particles. The olive pit articles may also be referred to as olive pit dust and are basically created in the thermo-tumbler through the abrasion of the sharp edges of the fragments.

5 The intensity and duration of the tumbling can be adjusted to avoid excessive formation of olive pit particles 26. Typically, the intensity, and duration of the tumbling are controlled to keep the amount of olive pit particles to less than 5.0 wt%, and, more preferably, to less than 2.0 wt% of the total olive pit material.

10 **[0098]** According to some embodiments, hot air or steam may be used for thermally treating the olive pit fragments. The olive pit particles are olive pit fragments of less than 63  $\mu\text{m}$ . The thermo-tumbling treatment may be a batch or a continuous process. Preferably, the thermo-tumbling treatment is a continuous process. Any suitable thermo-tumbling apparatus may be used.

15 **[0099]** Although, the tumbling and the thermal treatment in the described embodiments are performed simultaneously and in the same apparatus, it is to be understood, that this is just an example of a preferred embodiment and that these treatments could also be performed separately without departing from the scope of the present invention.

20 **[0100]** According to some embodiments, following the treatment in the thermo-tumbler 21, the thermo-tumbler product 29 is sieved via a sieve 31 to remove the thermo-tumbler product olive pit particles 26. The rounded and thermally treated olive pit fragments 24 are used as infill for an artificial turf. The removed olive pit particles may be used for a stabilization layer of the infill. The rounded and thermally treated olive pit fragments 24 are used for the performance layer of the infill. For example, referring to figure 3, the rounded and thermally treated olive pit fragments 24 free of the olive pit particles 26 can be used in a performance layer 38 for an artificial turf 30 either alone or together with a second bio-based material, such as, for example, cork particles and/or cherry pits 25. When a second bio-based material such as the cork particles and/or the cherry pits 25 are used in the infill, they are preferably added in the thermo-tumbler 21 together with the olive pit fragments. In some embodiments, zeolite in the form of microporous zeolite particles is also added in the thermo-tumbler 21. As shown in figure 2B, the rounded and thermally treated olive pit fragments, when used the second bio-based material fragments 25 and the microporous zeolite particles can be separated from the olive pit particles 26 using the sieve 31. The use of cherry pits may further improve the infill shock absorption and force reduction.

30 **[0101]** The use of the cork particles and/or cherry pits 25 as a second bio-based material is advantageous because they may allow better packing of the infill and better customization of the overall elasticity of the infill (i.e., the mixture of olive pit fragments cork particles and/or cherry pits) by adjusting the weight ratio of each of the rounded and thermally treated olive pit fragments and of the at least one other bio-based material in the infill to obtain

the desired overall elasticity for the infill. The cork particles and/or the cherry pits may be subjected to the same thermo-tumbling process as the olive pit fragments by adding them into the thermo-tumbler 21. The cherry pits may be whole pits or fragmented pits before fed into the thermo-tumbler 21. The cherry pits may be the remnants of cherry pit commercial processes for making cherry juice, and the like. In a preferred embodiment, the olive pit fragments 24 and the cherry pits 25 are mixed together within the thermo-tumbler 21 which may further enhance the rounding of the olive pit fragments 24.

**[0102]** According to the embodiment of figure 3, the separated olive pit particles 26 using a sieving process (see figure 2B) are used as infill for a stabilization layer 35 preferably alone or together with any particles (of less than 63  $\mu\text{m}$  size) of another bio-based material, while the rounded and thermally treated olive pit fragments 24 free of the olive pit particles 26 are used to form the performance layer 38 either alone or together with a second biobased material fragments (of a size of 0.5 mm or greater) such as, cork particles and cherry pits 25. According to this embodiment, the artificial turf 30 comprises the stabilization layer 35 formed on the backing 11 of the artificial turf 30 exclusively with the olive pit particles or in a mixture with a second stabilizing bio-based material, and the performance layer 38 formed on the stabilization layer 35 formed exclusively with the rounded and thermally treated olive pit fragments 24 or with a mixture of the rounded and thermally treated olive pit fragments 24 and a second bio-based material particles, such as, preferably the cork particles and/or the cherry pit particles. Preferably, the performance layer 38 comprises the rounded olive pit fragments 24 and second bio-based material of the cork fragments and/or cherry pit fragments 25 in a mixture prepared, for example, in the thermo-tumbler 21 and sieving the thermo-tumbler product to separate the olive pit particles 26 which are used for forming the stabilization layer 35. The stabilization layer 35 may optionally include sand which is currently widely used in state of the art infills, however, the present invention allows completely eliminating the need for using sand in the stabilization layer. Eliminating the sand is advantageous because it is non-bio-based material and creates problems in the shredders used in the recycling of the artificial turf at the end of the useful life of the artificial turf.

**[0103]** According to some embodiments, microporous zeolite particles may be added in the infill for providing a cooling effect for the artificial turf. Optionally particles of a reflective material may also be added. The grain size of the microporous zeolite particles is determined such that the resulting specific surface area of the particles is smaller than a maximum specific surface area. The maximum specific surface area of the microporous zeolite particles is the specific surface area that enables the water in the particles to release, under an ambient temperature, at a predefined minimum rate. A progressive release of the water by the microporous zeolite particles

and avoidance of rapid evaporation of the water after the surface has been watered is desirable in order to allow a lower temperature to be maintained at the level of the field surface compared to the ambient temperature. In other words, the controlled release of absorbed water causes progressive cooling under evaporation for some time. Thus, the amount of watering usually necessary to refresh a field surface can be reduced.

**[0104]** The grain structure of the microporous zeolite particles enables the formation of bound water surrounding particles surfaces and maintained by weak force of van der Waals force. This renders the release or desorption of the water easier in particular under ambient temperature (e.g., the solar energy is enough to desorb the water). Naturally, the specific surface area of the microporous zeolite particles varies with its structure. For example, the finer the particles are, the larger the specific surface area is (i.e., the smaller the grain size is, the larger the specific surface area is). For example, the specific surface area of the microporous zeolite particles may not exceed a minimum specific surface area. The minimum specific surface area may be the smallest possible specific surface area. In this case, the determined grain size may be the lower limit of a range of sizes, wherein the upper limit of the range may be determined using the minimum specific surface area. The microporous zeolite particles may for example have a grain size between 0.1 mm and 1.5 mm, in particular between 0.4 mm to 1.2 mm, more in particular between 0.9 mm and 1.2 mm, and a maximum surface specific surface area of 21m<sup>2</sup>/g. For example, a selected specific surface area may be 20 m<sup>2</sup>/g.

**[0105]** According to some embodiments, the artificial turf infill artificial turf infill comprises microporous zeolite particles having a selected grain size smaller than 1.5 mm and a porosity between 15% and 20% volume parts. In an embodiment, the microporous zeolite particles may have a grain size distribution wherein 70% to 90% of the grains by weight have a size in the range of 0.4 mm to 1.5 mm and 10.0% to 30% of the grains by weight have a size smaller than 0.4 mm.

**[0106]** According to some embodiments, 0.6 wt% of the zeolite particles at most is not retainable on a 10-mesh screen. Preferably, the microporous zeolite particles have a hardness between 3.5 and 5.5 on the Mohs scale. Preferably, the moisture level in the microporous zeolite particles is smaller than 6 wt%.

**[0107]** The microporous zeolite particles allow a lower temperature to be maintained at the level of the field surface compared to the ambient temperature by the controlled release of water via evaporation. Thus, the amount of watering usually necessary to refresh a field surface may be reduced.

**[0108]** According to some embodiments, the mixture of rounded and thermally treated olive pit fragments obtained from the thermo-tumbler is not sieved at all and is applied as obtained from the thermo-tumbler once the thermo-tumbling treatment is completed, on the backing

of the artificial turf. It has been found that in a relative short time, the olive pit particles and the fragments separate with the olive pit particles settling at the bottom of the infill layer forming a stabilization layer and the larger rounded and thermally treated olive pit fragments form a performance layer over the stabilization layer with the olive pit particles. It should be understood that the transition from the olive pit particles layer to the rounded and thermally treated olive pit fragments layer may be gradual and that there may be an intermediate layer between the olive pit particles layer and the rounded olive pit particles comprising the two different particle size groups. In some embodiments, a zeolite and optionally sand, preferably of zeolite may also be added.

**[0109]** Hence, according to some embodiments, the following mixture is generated and applied on the artificial turf:

- a) rounded and thermally treated olive pit fragments 24,
- b) zeolite 28 (medium sized) (sand may also be added in the component b as optional) and
- c) olive pit particles 26.

**[0110]** Referring to figure 4, after having applied the whole mixture including the components a, b, and c on the artificial turf, the components a, b and c will automatically separate into different stabilizing and performance layers 45 and 48, respectively, with the olive pit particles 26 moving downward next to the carrier/backing 11 of the artificial turf because of their small particle size which makes them fall down filling the cavities between the larger objects and eventually make it all the way down shifting the larger particles upwards. It is noted that the artificial turf fibers are not shown in figure 3 for simplicity of presentation. Also, the various components are presented in a simplified schematic manner and not according to their actual shapes, and sizes.

**[0111]** This embodiment, (with or without the component 'b') is advantageous because the mixture is applied on the carrier or backing 11 of the artificial turf 40 in a single step and within a short period of use it separates by itself in a stabilization layer 45 comprising primarily olive pit particles 26 and when used the microporous zeolite particles 28, and a performance layer 45 comprising primarily of the rounded and thermally treated olive pit fragments 24.

**[0112]** The microporous zeolite particles 28 of the component b, when used, they separate also with the main bulk of it settling primarily within the stabilization layer 45. The microporous zeolite particles 28 provide a cooling effect in the infill of the artificial turf 40 and can also help the artificial turf stay drier in a rainy day because of their ability to soak water (through absorption) due to their microporous structure. The result is an artificial turf with less variable performance characteristic between

warm, sunny days and cooler rainy days. Thus, the proposed infill comprising components a, b and c is advantageous because:

- 1) it is made through a simplified manufacturing mixing process,
- 2) it is applied through a "single-step" application on the backing of the artificial turf,
- 3) it self-separates into a stabilization layer and a performance layer, and
- 4) it reduces performance variability in different weather conditions.

Thus, unlike many state of the art artificial turf types which require separate formation of a stabilization layer and a performance layer, according to a preferred embodiment of the present invention these layers are formed automatically by a single-step application of the above-mentioned mixture comprising only components 'a' and 'c,' or a mixture comprising 'a', 'b' and 'c' and self-separation into the stabilizing and performance layers based on object size and specific gravity will achieve at least similar mechanical properties like a conventional two-layer artificial turf system with a stabilizing and performance layer. The infill mixture may include at least one other bio-based material such as cork particles and/or cherry pits 25 which after an initial settling period form part of the performance layer 48.

**[0113]** The infill of the present invention comprises thermally treated bio-based materials including rounded olive pit fragments and exhibits excellent antimicrobial resistance, and attrition resistance. It also has no remaining olive odor or other odors from any additional bio-based materials used. Finally, because of the rounded larger size fragments obtained by the thermo-tumbling process the infill is less likely to cause any skin injuries or foot injuries to the users of the artificial turf.

**[0114]** The infill may further include any other suitable components such as an antimicrobial agent used for preventing the growth of bacteria, fungi, mold, or other microorganisms. Any suitable antimicrobial agent may be used and, according to some embodiments, the antimicrobial agent may also be added in the turf backing and/or turf fibers.

**[0115]** The artificial turf may further include other components such as a reflective agent. The reflective agent may be added in the infill and/or in the polymer mixture for making the artificial turf fibers 16, for further preventing overheating of the fiber in warm and sunny conditions. The reflective agent may reduce the heat on the artificial turf field. Suitable reflective agents include titanium dioxide, zinc sulfide, tin oxide, aluminum oxide, zinc oxide, calcium sulfate, barium sulfate, calcium carbonate, antimony oxide, sodium silicate, aluminum silicate, silica, mica, clay, and the like.

**[0116]** In a preferred embodiment an infrared (IR) reflective agent is a mixed metal oxide type chosen from the group of the rutile (MeO<sub>2</sub>), hematite (Me<sub>2</sub>O<sub>3</sub>), or spi-

nel (Me<sub>3</sub>O<sub>4</sub>) type with metals comprising cobalt, iron, trivalent chrome, tin, antimony, titanium, manganese and aluminum.

**[0117]** For example, the reflective agent may be used in an amount from 0.01 wt% to 8.0 wt%, preferably from 0.3 wt% to 5.0 wt%, more preferably from 0.3 wt% to 3.0 wt% based on the total fiber weight.

**[0118]** Referring to figure 5, a method of fabricating an infill for an artificial turf is provided, the method comprising, providing olive pit fragments separated from an olive extraction process compressing olives to extract olive oil from the olives (S50), feeding the olive pit fragments in a thermo-tumbler (S52), feeding hot air or steam through the thermo-tumbler (S54), tumbling the olive pit fragments (S56), and producing rounded and thermally treated olive pit fragments including olive pit particles (S58).

**[0119]** According to some embodiments, the rounded and thermally treated olive pit fragments including the olive pit particles are used to form an infill for an artificial turf.

**[0120]** According to some embodiments, the olive pit particles are separated from the thermo-tumbler product using sieving to remove all olive pit particles having a size of less than 63  $\mu$ m.

**[0121]** According to some embodiments, cherry pits whole, fragments, or mixtures thereof are also fed in the thermo-tumbler and are mixed together with the olive pit fragments.

**[0122]** According to some embodiments, in addition to the olive pit fragments (with or without the cherry pits), at least one of sand, and zeolite are added as a second component in the thermo-tumbler and mixed together with the olive pit fragments an/or the cherry pits.

**[0123]** In a preferred embodiment, the product from the thermo-tumbler includes rounded and thermally treated olive pit fragments and/or cherry pits (component a, bio-based material), at least one of sand and zeolite, preferably zeolite only or zeolite and sand (component b) and the olive pit particles (component c), and this mixture of components a, b and c is applied in a single-step on the backing of the artificial turf, wherein within a short period time separate into at least a stabilization layer which forms over the backing, and a performance layer which forms adjacent the stabilization layer. The stabilization layer comprises the olive pit particles and the sand when sand is used as at least one part of the component b. The performance layer includes the larger size bio-based material, i.e., the rounded olive fragments and when used also the cherry pits and when used also the zeolite particles. It should be understood that the thermo-tumbler process may also generate olive pit particles not only from the olive pits but also from the other components when used, i.e., the cherry pits, and the zeolites, and all these olive pit particles will settle at to form the stabilization layer, together with the most part or all of the sand used.

**[0124]** Typically, incorporating the turf fiber into the carrier includes positioning the fiber so that a first fraction

of the fiber is located at the back side of a carrier, a second fraction of the fiber is protruding to the front side of the carrier and a third fraction of the fiber is inside the carrier (referred to also as the middle fraction of the fiber or the carrier portion of the fiber).

**[0125]** According to some embodiments, the artificial turf fibers are integrated into the backing and have a density (number of fibers per artificial turf area) and/or degree of texturization that under a bird's eye perspective, at least 60%, more preferentially at least 70% of the size of the area covered by the artificial turf consists of the fibers and the rest consists of the backing or the infill.

**[0126]** The backing of the artificial turf is made of a thermoset polymer material, however the invention is not limited in this way and other suitable backing materials may be used. The thermoset material may include, for example, a polyurethane resin.

**[0127]** The term "tufting" as used herein refers to a method of incorporating a fiber into an existing carrier. Short U-shaped loops of fibers are introduced through the carrier from one side so that their ends point outside of the carrier in the other direction. Usually, the tuft yarns form a regular array of "dots" on the other side. On the one side of the carrier where the U-shaped loops are located, the tuft fibers may be tied for security, although they need not be. The ends of the tuft yarns can then optionally be frayed or otherwise processed, so that they will subsequently create a dense layer of fibers protruding from the carrier.

**[0128]** The term "weaving" as used herein is a method of incorporating an artificial turf fiber (which can be a monofilament or a bundle of monofilaments) into an existing carrier, whereby the artificial turf fiber and the fiber(s) that built the carrier are interlaced. The interlaced fibers and the mesh form a fabric like or cloth like structure. When an artificial tuft fiber is incorporated by weaving, the fiber interlaces a series of mesh fibers at least three times. Thus, when a fiber is incorporated by weaving rather than tufting, a higher fraction of the artificial turf fiber is interlaced in the carrier material. This may increase the resistance to wear and tear of the artificial turf.

**[0129]** According to some embodiments, incorporating the artificial turf fiber into the carrier comprises tufting the artificial turf fiber into the carrier. According to alternative embodiments, incorporating the artificial turf fiber into the carrier comprises weaving the artificial turf fiber into the carrier.

**[0130]** The formation of the artificial turf may be made using any suitable manufacturing process. For example, a polymer mixture comprising at least one polymer such as a polyethylene, and various additives including, for example, a friction control additive, a reflective agent, an antioxidant, a coloring agent and the like is made by putting all these components that make it up together and is thoroughly mixed in a mixer device. The desired distribution of the components can be achieved by using the proper rate or amount of mixing. The generated mix-

ture is then forwarded to a one-screw feed or a two-screw feed to be extruded into a monofilament. The monofilament is quenched or rapidly cooled down, then reheated and oriented by stretching it into an artificial turf fiber is bundled with additional monofilaments into an artificial turf fiber.

**[0131]** Next the artificial turf fiber is incorporated into an artificial turf backing. The incorporation may comprise arranging a plurality of the artificial turf fibers on a carrier so that first parts of the monofilaments are exposed to a bottom side of the carrier and second parts of said monofilaments are exposed to a top side of the carrier. The arranging could be accomplished by tufting or weaving the artificial turf fiber into the carrier, but other methods of arranging the fibers within the carrier are also possible. Then a resin reaction fluid mixture is added on the bottom side of the carrier such that least the first parts become embedded in the fluid. Finally, the fluid mixture is caused to solidify into a film and surround and thereby mechanically fix the fibers on the backing.

### Examples

#### Examples 1

**[0132]** Figures 6A to 6E are images at different magnifications of an infill layer formed of rounded and thermally treated olive pit material comprising rounded and thermally treated olive pit fragments having a size of 0.5 to 2.0 mm in an amount of 99.0 wt% of the total olive pit material, and olive pit particles of a size of less than 63  $\mu\text{m}$  in an amount of 1 wt% of the total olive pit material. The olive material is obtained after a thermo-tumbling simultaneous treatment in a thermo-tumbler of olive pit fragments from an olive extraction process for a period of 2.7 minutes at a temperature of 120 °C. These images show that the thermo-tumbling treatment smoothens the rough edges of the olive pit fragments and provides more rounded olive pit fragments without sharp edges. Moreover, the infill is free of any remaining olive odor, and is less likely to cause skin or foot injuries to the users of the artificial turf compared to an artificial turf using the untreated olive pit fragments. The olive pit material is applied in a single step over the thermoset polyurethane backing of an artificial turf comprising turf fibers of polyethylene having a pile height of 70 mm to form an infill having a height of 30 mm. The artificial turf made with the infill of the thermo-tumbled olive pit material shows a substantially improved balance of traction, energy absorption, stable foot and energy restitution characteristics compared to same artificial turf made with the untreated olive pit material. Untreated olive pit material refers to the olive pit material prior to the thermo-tumbling process.

#### Example 2

**[0133]** The same processes as in Example 1 are re-

peated except that microporous zeolite particles are added in an amount of 10.0 wt% of the total infill. The microporous zeolite particles have a grain size distribution wherein 80.0 wt% of the grains have a size in the range of 0.4 mm to 1.5 mm and 20 wt% of the grains have a size smaller than 0.4 mm. The infill mixture of the olive pit material and the microporous zeolite particles are processed together in the thermo-tumbler under the same conditions as in example 1 and the thermo-tumbler product without any sieving is applied on the thermoset polyurethane backing as in example 1. The infills of examples 1 and 2 are watered and their temperatures are measured at a center point of the infills under the same ambient temperatures 2 and 4 hours later after the watering of the infill whereas the infill of example 2 demonstrates consistently lower temperature than example 1.

#### Example 3, 4 and 5

**[0134]** An olive pit material is obtained after a thermo-tumbling simultaneous treatment in a thermo-tumbler of olive pit fragments from an olive extraction process as in example 1 except for a period of 60 minutes, and that the olive pit material is heated to a temperature of 160 °C (for example 3), 180 °C (for example 4) and 200 °C (for example 5). The olive pit materials from examples 3-5 are substantially free of any sharp edges and any remaining olive odor and like the olive pit material of Example 1 are less likely to cause skin or foot injuries to the users of the artificial turf compared to an artificial turf using the untreated olive pit material.

**[0135]** In addition, the olive pit materials of examples 3-5, compared to the olive pit material of Example 1, exhibit substantially improved antimicrobial resistance, enhanced abrasion resistance, and reduced hygroscopicity. The olive pit material of example 3 has significantly reduced hygroscopicity when compared to the olive pit material of example 1 while the olive pit materials of examples 4 and 5 exhibit almost no hygroscopicity at all. Because of the aforementioned significantly improved characteristics and in particular the reduced hygroscopicity, the olive pit material of example 3 is expected to exhibit significantly improved resistance to biodegradability and prolonged lifespan compared to the olive pit material of example 1. Likewise, the olive pit materials of examples 4, and 5 because of their substantially zero hygroscopicity, are expected to exhibit exceptional resistance to biodegradation in moist and humid conditions making particularly suitable for artificial turfs used in applications where frequent watering is needed. XPS analysis shows that examples 3, 4, 5 have substantially reduced O/C (oxygen/carbon) ratio compared to the O/C ratio of example 1. NMR analysis showed that examples 3, 4, 5 have substantially higher levels of crystalline cellulose measured at 89 ppm compared to the crystalline levels example 1. The olive pit materials are applied in a single step over the thermoset polyurethane backing of an artificial turf comprising turf fibers of polyethylene hav-

ing a pile height of 70 mm to form an infill having a height of 30 mm. The artificial turf made with the infill of the thermo-tumbled olive pit material of examples 3, 4, and 5 show a substantially improved balance of traction, energy absorption, stable foot and energy restitution characteristics compared to same artificial turf made with the untreated olive pit material.

#### Example 6, 7, and 8

**[0136]** Microporous zeolite particles are added in an amount of 10.0 wt% of the total infill which employs the olive pit materials from examples 3, 4, and 5, respectively. The microporous zeolite particles have a grain size distribution wherein 80.0 wt% of the grains have a size in the range of 0.4 mm to 1.5 mm and 20 wt% of the grains have a size smaller than 0.4 mm. The infill mixture of the olive pit material and the microporous zeolite particles are processed together in the thermo-tumbler under the same conditions as in example 1 and the thermo-tumbler product without any sieving is applied on the thermoset polyurethane backing as in example 1. The infills of 6, 7, and 8 are watered and their temperatures are measured at a center point of the infills under the same ambient temperatures 2 and 4 hours later after the watering of the infill whereas the infill of examples 6, 7 and 8 demonstrate consistently lower temperatures than example 1.

**[0137]** Although the invention has been described in reference to specific embodiments, it should be understood that the invention is not limited to these examples only and that many variations of these embodiments may be readily envisioned by the skilled person after having read the present disclosure. The invention may thus further be described without limitation and by way of example only by the following embodiments. The following embodiments may contain preferred embodiments. Accordingly, the term "clause" as used therein may refer to such a "preferred embodiment".

**[0138]** Clause 1. An artificial turf infill comprising: an olive pit material; and microporous zeolite particles.

**[0139]** Clause 2. The artificial turf infill of clause 1, wherein the olive pit material comprises olive pit fragments having a size of 0.5 mm or greater, in particular 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, in an amount of at least 80.0 wt%, in particular 90.0 wt% to 99.0 wt%, more in particular 95.0 wt% to 99.0 wt%, and most in particular 98.0 wt% to 99.0 wt% of the total weight of the total olive pit material in the infill.

**[0140]** Clause 3. The artificial turf infill of clauses 1 or 2, wherein the olive pit material comprises olive pit particles having a size of less than 63  $\mu\text{m}$  in an amount of at least 0.5 wt%, in particular 1.0 wt% to 20.0 wt%, more in particular 1.0 wt% to 10.0 wt %, and most in particular 1.0 wt% to 2.0 wt% of the total olive pit material in the infill.

**[0141]** Clause 4. The artificial turf infill of any of the preceding claims, wherein the olive pit material has a

bimodal size distribution with a major mode and a minor mode, wherein the major mode comprises the rounded, thermally treated olive pit fragments and has a peak between 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, and wherein the minor mode comprises the olive pit particles and has a peak at less than 63  $\mu\text{m}$ .

**[0142]** Clause 5. The artificial turf infill of any of the preceding clauses, wherein the olive pit material is thermally treated.

**[0143]** Clause 6. The artificial turf infill of clause 5, the thermally treating can be performed at a temperature of 80 °C to 130 °C, in particular 100 °C to 130 °C, and more in particular 110 °C to 130 °C.

**[0144]** Clause 7. The artificial turf infill of clause 5, wherein the olive pit material is thermally treated at a temperature of 150 °C to 250 °C, in particular 160 °C to 250 °C, and more in particular 180 °C to 250 °C.

**[0145]** Clause 8. The artificial turf infill of any one of the preceding clauses, wherein the infill comprises rounded olive pit fragments, in particular olive pit fragments having been rounded in a tumbler.

**[0146]** Clause 9. The artificial turf infill of the preceding clauses, wherein the rounded, and thermally treated olive pit fragments are obtained by a thermo-tumbling treatment of fractured olive pits together with the microporous zeolite particles, wherein the olive pit fragments are formed by fracturing in an olive oil extraction process during a compression operation of the olives for extracting oil from the olives and have sharp edges due to the fracturing, and wherein the thermo-tumbling process smoothens the sharp edges by attrition by rubbing the olive pit particles against each other and against the microporous zeolite particles to form the rounded, thermally treated olive pit fragments.

**[0147]** Clause 10. The artificial turf infill of any one of the preceding clauses, wherein the artificial turf infill is free of olive pit particles having a size less than 63  $\mu\text{m}$ .

**[0148]** Clause 11. The artificial turf infill of any of the preceding clauses, wherein the artificial turf infill comprises the microporous zeolite particles in an amount of 1.0 to 30.0 wt%, in particular 5.0 to 25.0 wt%, and more in particular 10.0 to 20.0 wt% of the total amount of the infill.

**[0149]** Clause 12. The artificial turf infill of any of the preceding clauses, wherein the microporous zeolite particles have a grain size between 0.1 mm and 1.5 mm, in particular between 0.4 mm to 1.2 mm, more in particular between 0.9 mm and 1.2 mm, and a maximum surface specific surface area of 21  $\text{m}^2/\text{g}$ .

**[0150]** Clause 13. The artificial turf infill of any of the preceding clauses, wherein the microporous zeolite particles have a porosity between 15% and 20% volume parts.

**[0151]** Clause 14. The artificial turf infill of any of the preceding clauses, wherein the microporous zeolite particles have a grain size distribution wherein 70% to 90% of the grains by weight have a size in the range of 0.4

mm to 1.5 mm and 10% to 30% of the grains by weight have a size smaller than 0.4 mm.

**[0152]** Clause 15. The artificial turf infill of any of the preceding clauses, wherein the microporous zeolite particles have a hardness between 3.5 and 5.5 on the Mohs scale and a moisture level smaller than 6 wt%.

**[0153]** Clause 16. The artificial turf infill of any of the preceding clauses,

further comprising at least one further bio-based material including pit fragments of at least one other stone-containing fruit, and wherein the pit fragments of the further bio-based material have a different elasticity than the rounded, and thermally treated olive pit fragments.

**[0154]** Clause 17. The artificial turf infill of clause 16, wherein the at least one further bio-based material comprises cork particles, rounded cherry pit fragments, and combinations thereof.

**[0155]** Clause 18. The artificial turf infill of any of the preceding clauses, comprising only bio-based materials and being free of any rubber, elastomeric, or polymer-based infill, and, in particular also free of any sand.

**[0156]** Clause 19. An artificial turf comprising the artificial turf infill of any of the clauses 1-18.

**[0157]** Clause 20. The artificial turf of clause 19, further comprising:

a stabilization layer comprising or consisting of at least one of sand, the olive pit particles of clause 3, and at least a portion of the microporous zeolite particles; and  
a performance layer positioned on the stabilizing layer, wherein the performance layer comprises or consists of the artificial turf infill of any of the preceding clauses or comprises or consists of the rounded and thermally treated olive pit fragments and is basically free of the olive pit particles.

**[0158]** Clause 21. The artificial turf of clauses 19 or 20, wherein the artificial turf infill is substantially free of any rubber, elastomeric, or polymer-based infill, and, in particular, also free of any sand.

**[0159]** Clause 22. A method of creating an artificial turf, comprising: installing an artificial turf and applying the artificial turf infill of any one of clauses 1-18 on the installed artificial turf.

**[0160]** Clause 23. The method of clause 22,

wherein the infill comprises at least a mixture of the rounded, olive pit fragments, the olive pit particles and the microporous zeolite particles, wherein the applying the artificial turf infill on the installed artificial turf is performed in a single step, and wherein the method further comprises: allowing the olive pit particles in the applied infill to automatically

trickle down into the voids between the fragments, thereby automatically forming a stabilizing layer consisting essentially of the trickled-down particles, and a performance layer containing the rounded olive pit fragments.

**[0161]** Clause 24. The method of clause 23, wherein at least a portion of the microporous zeolite particles trickles down and settles into the stabilizing layer.

**[0162]** Clause 25. A kit for manufacturing an artificial turf, the kit comprising the artificial turf infill of any of the clauses 1 to 19 and at least one other component for making the artificial turf.

**[0163]** Clause 26: Clause 1. Use of a mixture comprising olive pit material and microporous zeolite particles as an artificial turf infill.

**[0164]** By way of example, embodiments of the invention comprise the following features:

1. An artificial turf infill comprising:

- an olive pit material (24, 26); and
- microporous zeolite particles (28).

2. The artificial turf infill of claim 1, wherein the olive pit material (24, 26) comprises olive pit fragments (24) having a size of 0.5 mm or greater, in particular 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, in an amount of at least 80.0 wt%, in particular 90.0 wt% to 99.0 wt%, more in particular 95.0 wt% to 99.0 wt%, and most in particular 98.0 wt% to 99.0 wt% of the total weight of the total olive pit material in the infill.

3. The artificial turf infill of any of the preceding claims, wherein the olive pit material has a bimodal size distribution with a major mode and a minor mode,

wherein the major mode comprises rounded, thermally treated olive pit fragments (24) and has a peak between 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, and

wherein the minor mode comprises olive pit particles (26) of less than 63  $\mu\text{m}$  in an amount of at least 0.5 wt% and has a peak at less than 63  $\mu\text{m}$ .

4. The artificial turf infill of any of the preceding claims, wherein the olive pit material is thermally treated (S54), in particular at a temperature of 80 °C to 250 °C.

5. The artificial turf infill of any of the preceding claims, wherein the olive pit material comprises abrasively rounded olive pit fragments (24), in particular

rounded olive pit fragments rounded in a tumbler.

6. The artificial turf infill of claims 2-5,

wherein the rounded, and thermally treated olive pit fragments (24) are obtained by a thermo-tumbling treatment of fractured olive pits together with the microporous zeolite particles (28),

wherein the olive pit fragments (6) are formed by fracturing in an olive oil extraction process (2) during a compression operation of the olives (1) for extracting oil (3) from the olives and have sharp edges due to the fracturing, and

wherein the thermo-tumbling process smoothens the sharp edges by attrition by rubbing the olive pit fragments (6) against each other and against the microporous zeolite particles (28) to form the rounded, thermally treated olive pit fragments (24).

7. The artificial turf infill of any of the claims 1-6, wherein the microporous zeolite particles (28) are added in the infill in an amount of 1.0 to 30.0 wt%, in particular 5.0 to 25.0 wt%, and more in particular 10.0 to 20.0 wt% of the total amount of the infill (12).

8. The artificial turf infill of any of the claims 1-7, wherein the microporous zeolite particles (28) have a grain size between 0.1 mm and 1.5 mm, in particular between 0.4 mm and 1.2 mm, more in particular between 0.9 mm and 1.2 mm, and a maximum surface specific surface area of 21m<sup>2</sup>/g.

9. The artificial turf infill of any of the claims 1-8, wherein the microporous zeolite particles (28) have a porosity between 15% and 20% volume parts.

10. The artificial turf infill of any of the claims 1-9, wherein the microporous zeolite particles (28) have a grain size distribution wherein 70% to 90% of the grains by weight have a size in the range of 0.4 mm to 1.5 mm and 10% to 30% of the grains by weight have a size smaller than 0.4 mm.

11. The artificial turf infill of any of the claims 1-10, wherein at least 10%, in particular at least 50%, in particular at least 70%, or at least 90% by weight of the infill consists of olive pit material.

12. The artificial turf infill of any of the claims 1-11, wherein the microporous zeolite particles (28) have a hardness between 3.5 and 5.5 on the Mohs scale and a moisture level smaller than 6 wt%.

13. The artificial turf infill of any of the claims 1-12,

- further comprising at least one further bio-based material (25) including pit fragments of at least one other stone-containing fruit,

wherein the pit fragments of the further bio-based material (25) have a different elasticity than the rounded, and thermally treated olive pit fragments, and

wherein in particular the at least one further bio-based material (25) is selected from a group comprising cork particles, rounded cherry pit fragments, and combinations thereof.

14. The artificial turf infill of any of the claims 1-11, comprising only bio-based materials (25) and being free of any rubber, elastomeric, or polymer-based infill, and, in particular also free of any sand.

15. An artificial turf or artificial turf kit comprising the artificial turf infill of any of the claims 1-14.

16. The artificial turf of claim 15, further comprising:

- a stabilization layer (35, 45) comprising or consisting of at least one of sand, the olive pit particles (26) of claim 2, and at least a portion of the microporous zeolite particles (28);
- a performance layer (38, 48) positioned on the stabilizing layer,

wherein the performance layer (38, 48) comprises or consists of the artificial turf infill of any of the preceding claims or comprises or consists of the rounded and thermally treated olive pit fragments (24) and is basically free of the olive pit particles (26).

17. A method of creating an artificial turf, comprising:

- installing an artificial turf comprising a plurality of artificial turf fibers attached on a carrier;
- applying the artificial turf infill of any one of claims 1-13 on the installed artificial turf between the turf fibers, wherein the infill comprises at least a mixture of the rounded, and thermally treated olive pit fragments (24), the olive pit particles (26) and the microporous zeolite particles (28), wherein the applying the artificial turf infill on the installed artificial turf is performed in a single step, and
- allowing the olive pit particles (26) in the applied infill to automatically trickle down into voids between the olive pit fragments (24), thereby automatically forming a stabilizing layer (35, 45) consisting essentially of the trickled-down particles, and a performance layer (38, 48) containing the rounded olive pit fragments (24), wherein at least a portion of the microporous zeolite particles (28) trickles down and settles



into the stabilizing layer (35, 45).

#### List of reference numerals

##### [0165]

|            |                                                   |    |
|------------|---------------------------------------------------|----|
| 1          | olives                                            |    |
| 2          | olive oil extraction process                      |    |
| 3          | olive oil                                         |    |
| 4          | olive pulp and skin                               | 10 |
| 6          | olive pit fragments                               |    |
| 10, 30, 40 | artificial turf (AT)                              |    |
| 11         | backing of AT                                     |    |
| 12         | infill layer                                      |    |
| 24         | rounded and thermally treated olive pit fragments | 15 |
| 35, 45     | stabilization layer                               |    |
| 38, 48     | performance layer                                 |    |
| 26         | olive pit particles                               |    |
| 25         | at least one other bio-based material             | 20 |
| 21         | thermo-tumbler                                    |    |
| 23         | air flowing in the thermo-tumbler                 |    |
| 32         | air flowing out the thermo-tumbler                |    |
| 28         | microporous zeolite particles                     |    |
| 29         | thermo-tumbler product                            | 25 |
| 31         | sieve for olive pit particles                     |    |

#### Claims

##### 1. An artificial turf infill comprising:

- an olive pit material (24, 26); and
- microporous zeolite particles (28).

##### 2. The artificial turf infill of claim 1, wherein the olive pit material (24, 26) comprises olive pit fragments (24) having a size of 0.5 mm or greater, in particular 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, in an amount of at least 80.0 wt%, in particular 90.0 wt% to 99.0 wt%, more in particular 95.0 wt% to 99.0 wt%, and most in particular 98.0 wt% to 99.0 wt% of the total weight of the total olive pit material in the infill.

##### 3. The artificial turf infill of any of the preceding claims, wherein the olive pit material has a bimodal size distribution with a major mode and a minor mode,

wherein the major mode comprises rounded, thermally treated olive pit fragments (24) and has a peak between 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, and wherein the minor mode comprises olive pit particles (26) of less than 63  $\mu\text{m}$  in an amount of at least 0.5 wt% and has a peak at less than 63  $\mu\text{m}$ .

##### 4. The artificial turf infill of any of the preceding claims, wherein the olive pit material is thermally treated (S54), in particular at a temperature of 80 °C to 250 °C.

##### 5. The artificial turf infill of any of the preceding claims, wherein the olive pit material comprises abrasively rounded olive pit fragments (24), in particular rounded olive pit fragments rounded in a tumbler.

##### 6. The artificial turf infill of claims 2-5,

wherein the rounded, and thermally treated olive pit fragments (24) are obtained by a thermo-tumbling treatment of fractured olive pits together with the microporous zeolite particles (28), wherein the olive pit fragments (6) are formed by fracturing in an olive oil extraction process (2) during a compression operation of the olives (1) for extracting oil (3) from the olives and have sharp edges due to the fracturing, and wherein the thermo-tumbling process smoothens the sharp edges by attrition by rubbing the olive pit fragments (6) against each other and against the microporous zeolite particles (28) to form the rounded, thermally treated olive pit fragments (24).

##### 7. The artificial turf infill of any of the claims 1-6, wherein the microporous zeolite particles (28) are added in the infill in an amount of 1.0 to 30.0 wt%, in particular 5.0 to 25.0 wt%, and more in particular 10.0 to 20.0 wt% of the total amount of the infill (12).

##### 8. The artificial turf infill of any of the claims 1-7, wherein the microporous zeolite particles (28) have a grain size between 0.1 mm and 1.5 mm, in particular between 0.4 mm to 1.2 mm, more in particular between 0.9 mm and 1.2 mm, and a maximum surface specific surface area of 21m<sup>2</sup>/g.

##### 9. The artificial turf infill of any of the claims 1-8, wherein the microporous zeolite particles (28) have a porosity between 15% and 20% volume parts.

##### 10. The artificial turf infill of any of the claims 1-9, wherein the microporous zeolite particles (28) have a grain size distribution wherein 70% to 90% of the grains by weight have a size in the range of 0.4 mm to 1.5 mm and 10% to 30% of the grains by weight have a size smaller than 0.4 mm.

##### 11. The artificial turf infill of any of the claims 1-10, wherein at least 10%, in particular at least 50%, in particular at least 70%, or at least 90% by weight of the infill consists of olive pit material.

##### 12. The artificial turf infill of any of the claims 1-11, where-

in the microporous zeolite particles (28) have a hardness between 3.5 and 5.5 on the Mohs scale and a moisture level smaller than 6 wt%.

13. The artificial turf infill of any of the claims 1-12, 5

- further comprising at least one further bio-based material (25) including pit fragments of at least one other stone-containing fruit, wherein the pit fragments of the further bio-based material (25) have a different elasticity than the rounded, and thermally treated olive pit fragments, and  
wherein in particular the at least one further bio-based material (25) is selected from a group comprising cork particles, rounded cherry pit fragments, and combinations thereof.

14. The artificial turf infill of any of the claims 1-11, comprising only bio-based materials (25) and being free of any rubber, elastomeric, or polymer-based infill, and, in particular also free of any sand. 20

15. An artificial turf or artificial turf kit comprising the artificial turf infill of any of the claims 1-14. 25

16. The artificial turf of claim 15, further comprising:

- a stabilization layer (35, 45) comprising or consisting of at least one of sand, the olive pit particles (26) of claim 2, and at least a portion of the microporous zeolite particles (28);  
- a performance layer (38, 48) positioned on the stabilizing layer, 30

wherein the performance layer (38, 48) comprises or consists of the artificial turf infill of any of the preceding claims or comprises or consists of the rounded and thermally treated olive pit fragments (24) and is basically free of the olive pit particles (26). 40

17. A method of creating an artificial turf, comprising:

- installing an artificial turf comprising a plurality of artificial turf fibers attached on a carrier; 45  
- applying the artificial turf infill of any one of claims 1-13 on the installed artificial turf between the turf fibers, wherein the infill comprises at least a mixture of the rounded, and thermally treated olive pit fragments (24), the olive pit particles (26) and the microporous zeolite particles (28), wherein the applying the artificial turf infill on the installed artificial turf is performed in a single step, and  
- allowing the olive pit particles (26) in the applied infill to automatically trickle down into voids between the olive pit fragments (24), thereby automatically forming a stabilizing layer (35, 45) 50  
55

consisting essentially of the trickled-down particles, and a performance layer (38, 48) containing the rounded olive pit fragments (24), wherein at least a portion of the microporous zeolite particles (28) trickles down and settles into the stabilizing layer (35, 45).

# **Amended claims in accordance with Rule 137(2) EPC.**

1. An artificial turf infill comprising:

- an olive pit material (24, 26); and  
- microporous zeolite particles (28), **characterized in that:**  
- the olive pit material comprises rounded olive pit fragments (24) obtained by tumbling together with the microporous zeolite particles (28) fractured olive pits obtained from an olive oil extraction process.

2. The artificial turf infill of claim 1, wherein the olive pit material (24, 26) comprises olive pit fragments (24) having a size of 0.5 mm or greater, in particular 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, in an amount of at least 80.0 wt%, in particular 90.0 wt% to 99.0 wt%, more in particular 95.0 wt% to 99.0 wt%, and most in particular 98.0 wt% to 99.0 wt% of the total weight of the total olive pit material in the infill.

3. The artificial turf infill of any of the preceding claims, wherein the olive pit material has a bimodal size distribution with a major mode and a minor mode, 35

wherein the major mode comprises rounded, thermally treated olive pit fragments (24) and has a peak between 0.5 mm to 4.0 mm, more in particular 0.5 mm to 2.5 mm, and most in particular 0.5 mm to 2.0 mm, and  
wherein the minor mode comprises olive pit particles (26) of less than 63  $\mu\text{m}$  in an amount of at least 0.5 wt% and has a peak at less than 63  $\mu\text{m}$ .

4. The artificial turf infill of any of the preceding claims, wherein the olive pit material is thermally treated (S54) to a temperature of 80 °C to 250 °C.

5. The artificial turf infill of any of the preceding claims, wherein the microporous zeolite particles (28) are added in the infill in an amount of 1.0 to 30.0 wt%, in particular 5.0 to 25.0 wt%, and more in particular 10.0 to 20.0 wt% of the total amount of the infill (12).

6. The artificial turf infill of any of the preceding claims, wherein the microporous zeolite particles (28) have

a grain size between 0.1 mm and 1.5 mm, in particular between 0.4 mm to 1.2 mm, more in particular between 0.9 mm and 1.2 mm, and a maximum surface specific surface area of 21m<sup>2</sup>/g.

7. The artificial turf infill of any of the preceding claims, wherein the microporous zeolite particles (28) have a porosity between 15% and 20% volume parts. 5
8. The artificial turf infill of any of the preceding claims, wherein the microporous zeolite particles (28) have a grain size distribution wherein 70% to 90% of the grains by weight have a size in the range of 0.4 mm to 1.5 mm and 10% to 30% of the grains by weight have a size smaller than 0.4 mm. 10  
15
9. The artificial turf infill of any of the preceding claims, wherein at least 10%, in particular at least 50%, in particular at least 70%, or at least 90% by weight of the infill consists of olive pit material. 20
10. The artificial turf infill of any of the preceding claims, wherein the microporous zeolite particles (28) have a hardness between 3.5 and 5.5 on the Mohs scale and a moisture level smaller than 6 wt%. 25
11. The artificial turf infill of any of the preceding claims,
  - further comprising at least one further bio-based material (25) including pit fragments of at least one other stone-containing fruit, 30
  - wherein the pit fragments of the further bio-based material (25) have a different elasticity than the rounded, and thermally treated olive pit fragments, and 35
  - wherein in particular the at least one further bio-based material (25) is selected from a group comprising cork particles, rounded cherry pit fragments, and combinations thereof. 40
12. The artificial turf infill of any of the preceding claims, comprising only bio-based materials (25) and being free of any rubber, elastomeric, or polymer-based infill, and, in particular also free of any sand. 45
13. An artificial turf or artificial turf kit comprising the artificial turf infill of any of the preceding claims. 50
14. The artificial turf of claim 13, further comprising:
  - a stabilization layer (35, 45) comprising or consisting of at least one of sand, the olive pit particles (26) of claim 2, and at least a portion of the microporous zeolite particles (28); 55
  - a performance layer (38, 48) positioned on the stabilizing layer,


wherein the performance layer (38, 48) comprises

or consists of the artificial turf infill of any of the preceding claims or comprises or consists of the rounded and thermally treated olive pit fragments (24) and is basically free of the olive pit particles (26).


15. A method of creating an artificial turf, comprising:

- installing an artificial turf comprising a plurality of artificial turf fibers attached on a carrier;
- applying the artificial turf infill of any one of claims 1 to 12 on the installed artificial turf between the turf fibers, wherein the infill comprises at least a mixture of the rounded, and thermally treated olive pit fragments (24), the olive pit particles (26) and the microporous zeolite particles (28), wherein the applying the artificial turf infill on the installed artificial turf is performed in a single step, and
- allowing the olive pit particles (26) in the applied infill to automatically trickle down into voids between the olive pit fragments (24), thereby automatically forming a stabilizing layer (35, 45) consisting essentially of the trickled-down particles, and a performance layer (38, 48) containing the rounded olive pit fragments (24),


wherein at least a portion of the microporous zeolite particles (28) trickles down and settles into the stabilizing layer (35, 45).




**FIG. 1**




**FIG. 2A**




**FIG. 2B**



**FIG. 3**




**FIG. 4A**




**FIG. 4B**







**FIG. 5**




**FIG. 6A**




**FIG. 6B**



**FIG. 6C**



**FIG. 6D**



**FIG. 6E**



## EUROPEAN SEARCH REPORT

Application Number

EP 23 16 4428

5

10

15

20

25

30

35

40

45

1

50

55

EPO FORM 1503 03.82 (P04C01)

| DOCUMENTS CONSIDERED TO BE RELEVANT                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                       |                                                     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|
| Category                                                                                                                                                                                                                                               | Citation of document with indication, where appropriate, of relevant passages                                                                                                                                                                                                                                                   | Relevant to claim                                                                                                                                                                                                                                                                     | CLASSIFICATION OF THE APPLICATION (IPC)             |
| X                                                                                                                                                                                                                                                      | US 2021/254290 A1 (SMOLLETT JASON [CA] ET AL) 19 August 2021 (2021-08-19)                                                                                                                                                                                                                                                       | 1                                                                                                                                                                                                                                                                                     | INV.<br>E01C13/08                                   |
| Y                                                                                                                                                                                                                                                      | * paragraphs [0001], [0004], [0005], [0029], [0031], [0032], [0033], [0034], [0043]; figures 1-3 *                                                                                                                                                                                                                              | 1, 2, 4, 5, 7-16                                                                                                                                                                                                                                                                      |                                                     |
| A                                                                                                                                                                                                                                                      | -----                                                                                                                                                                                                                                                                                                                           | 3, 6, 17                                                                                                                                                                                                                                                                              |                                                     |
| Y                                                                                                                                                                                                                                                      | US 2018/347122 A1 (PINTAT BENOIT [FR]) 6 December 2018 (2018-12-06)                                                                                                                                                                                                                                                             | 1, 7-16                                                                                                                                                                                                                                                                               |                                                     |
| A                                                                                                                                                                                                                                                      | * paragraphs [0005], [0013], [0020], [0036], [0037], [0039], [0040], [0079]; claim 19 *                                                                                                                                                                                                                                         | 2-6, 17                                                                                                                                                                                                                                                                               |                                                     |
| Y                                                                                                                                                                                                                                                      | WO 2018/183756 A1 (BROCK USA LLC [US]) 4 October 2018 (2018-10-04)                                                                                                                                                                                                                                                              | 1, 5, 7                                                                                                                                                                                                                                                                               |                                                     |
|                                                                                                                                                                                                                                                        | * paragraphs [0002], [0062], [0109] *                                                                                                                                                                                                                                                                                           |                                                                                                                                                                                                                                                                                       |                                                     |
|                                                                                                                                                                                                                                                        | * figure 1 *                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                       |                                                     |
| Y                                                                                                                                                                                                                                                      | GÓMEZ-DE LA CRUZ FRANCISCO J ET AL: "New Experimental Rotary Dryer of Olive Stone: Design, Control and Modeling", WASTE AND BIOMASS VALORIZATION, SPRINGER NETHERLANDS, NL, vol. 9, no. 3, 17 November 2016 (2016-11-17), pages 443-449, XP036428307, ISSN: 1877-2641, DOI: 10.1007/S12649-016-9777-9 [retrieved on 2016-11-17] | 4                                                                                                                                                                                                                                                                                     | TECHNICAL FIELDS SEARCHED (IPC)<br><br>G10L<br>E01C |
| A                                                                                                                                                                                                                                                      | * abstract *                                                                                                                                                                                                                                                                                                                    | 1-3, 5-17                                                                                                                                                                                                                                                                             |                                                     |
|                                                                                                                                                                                                                                                        | * page 446; figure 3; table 1 *                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                       |                                                     |
|                                                                                                                                                                                                                                                        | * page 447, right-hand column, last paragraph - page 448, left-hand column, paragraph first *                                                                                                                                                                                                                                   |                                                                                                                                                                                                                                                                                       |                                                     |
| Y                                                                                                                                                                                                                                                      | EP 4 001 506 A1 (TARKETT SPORTS CANADA INC [CA]) 25 May 2022 (2022-05-25)                                                                                                                                                                                                                                                       | 1, 2, 4, 5, 7-16                                                                                                                                                                                                                                                                      |                                                     |
| A                                                                                                                                                                                                                                                      | * paragraphs [0001], [0006], [0008], [0033] *                                                                                                                                                                                                                                                                                   | 3, 6, 17                                                                                                                                                                                                                                                                              |                                                     |
|                                                                                                                                                                                                                                                        | * claims 1, 14 *                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                       |                                                     |
| The present search report has been drawn up for all claims                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                       |                                                     |
| Place of search<br><b>Munich</b>                                                                                                                                                                                                                       |                                                                                                                                                                                                                                                                                                                                 | Date of completion of the search<br><b>6 July 2023</b>                                                                                                                                                                                                                                | Examiner<br><b>Kremsler, Stefan</b>                 |
| CATEGORY OF CITED DOCUMENTS<br>X : particularly relevant if taken alone<br>Y : particularly relevant if combined with another document of the same category<br>A : technological background<br>O : non-written disclosure<br>P : intermediate document |                                                                                                                                                                                                                                                                                                                                 | T : theory or principle underlying the invention<br>E : earlier patent document, but published on, or after the filing date<br>D : document cited in the application<br>L : document cited for other reasons<br>.....<br>& : member of the same patent family, corresponding document |                                                     |

# **ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.**

EP 23 16 4428

5 This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

06-07-2023

| Patent document<br>cited in search report | Publication<br>date | Patent family<br>member(s) | Publication<br>date |
|-------------------------------------------|---------------------|----------------------------|---------------------|
| <b>US 2021254290 A1</b>                   | <b>19-08-2021</b>   | <b>NONE</b>                |                     |
| <b>US 2018347122 A1</b>                   | <b>06-12-2018</b>   | <b>NONE</b>                |                     |
| <b>WO 2018183756 A1</b>                   | <b>04-10-2018</b>   | <b>AU 2018243393 A1</b>    | <b>24-10-2019</b>   |
|                                           |                     | <b>BR 112019020332 A2</b>  | <b>28-04-2020</b>   |
|                                           |                     | <b>CA 3058414 A1</b>       | <b>04-10-2018</b>   |
|                                           |                     | <b>DK 3601658 T3</b>       | <b>20-03-2023</b>   |
|                                           |                     | <b>EP 3601658 A1</b>       | <b>05-02-2020</b>   |
|                                           |                     | <b>EP 4036298 A1</b>       | <b>03-08-2022</b>   |
|                                           |                     | <b>ES 2941466 T3</b>       | <b>23-05-2023</b>   |
|                                           |                     | <b>FI 3601658 T3</b>       | <b>25-03-2023</b>   |
|                                           |                     | <b>PT 3601658 T</b>        | <b>29-03-2023</b>   |
|                                           |                     | <b>US 2020102707 A1</b>    | <b>02-04-2020</b>   |
|                                           |                     | <b>WO 2018183756 A1</b>    | <b>04-10-2018</b>   |
| <b>EP 4001506 A1</b>                      | <b>25-05-2022</b>   | <b>EP 4001506 A1</b>       | <b>25-05-2022</b>   |
|                                           |                     | <b>WO 2022101430 A1</b>    | <b>19-05-2022</b>   |

**REFERENCES CITED IN THE DESCRIPTION**

*This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.*

**Patent documents cited in the description**

- EP 2917413 B1 [0004]
- US 10822751 B2 [0004]
- US 10822752 B2 [0004]
- EP 3868955 A1 [0005]
- US 2010055461 A [0005]
- US 20180080183 A [0005]
- US 6632527 B [0005]
- US 20020048676 A [0005]
- US 20060121236 A [0005]
- US 20080176010 A [0005]
- US 20150252537 A [0005]