(11) EP 4 427 820 A1

(12)

EUROPEAN PATENT APPLICATION published in accordance with Art. 153(4) EPC

(43) Date of publication: 11.09.2024 Bulletin 2024/37

(21) Application number: 22909108.7

(22) Date of filing: 25.04.2022

(51) International Patent Classification (IPC): A63B 22/02 (2006.01)

(52) Cooperative Patent Classification (CPC): A63B 22/02

(86) International application number: **PCT/CN2022/089111**

(87) International publication number: WO 2023/115771 (29.06.2023 Gazette 2023/26)

(84) Designated Contracting States:

AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO PL PT RO RS SE SI SK SM TR

Designated Extension States:

BAMF

Designated Validation States:

KH MA MD TN

(30) Priority: 23.12.2021 CN 202123300376 U

(71) Applicant: Beijing Xiaomi Mobile Software Co.,

Ltd.

Beijing 100085 (CN)

(72) Inventors:

 JIANG, Junpeng Beijing 100085 (CN)

 WANG, Yunsong Beijing 100085 (CN)


 LI, Hui Beijing 100085 (CN)

(74) Representative: Frommberger, Moritz

Dehns Germany Theresienstr. 6-8 80333 Munich (DE)

(54) **FOLDABLE TREADMILL**

(57)The disclosure relates to a foldable treadmill. The foldable treadmill includes: a front running plate assembly, a middle running plate assembly, and a rear running plate assembly, where the front running plate assembly and the rear running plate assembly are hingedly connected to two ends of the middle running plate assembly in a front-back direction, respectively; a first drive mechanism connected to the front running plate assembly or the rear running plate assembly; and a linkage mechanism separately connected to the front running plate assembly, the middle running plate assembly, and the rear running plate assembly, so that when the first drive mechanism drives the front running plate assembly or the rear running plate assembly, the front running plate assembly and the rear running plate assembly can synchronously rotate relative to the middle running plate assembly to be switched between a folding position and an unfolding position. In the unfolding position, upper surfaces of the front running plate assembly, the middle running plate assembly, and the rear running plate assembly are coplanar, and in the folding position, the front running plate assembly and the rear running plate assembly get close to each other so as to lift the middle running plate assembly upwards. The foldable treadmill of the disclosure can be automatically folded in three sections, is small in the overall size, reduces the occupied space, and is convenient to store and carry.



Description

CROSS-REFERENCE TO RELATED APPLICATIONS

1

[0001] The disclosure is provided based on and claims priority to Chinese patent application No. 202123300376.9 filed on December 23, 2021, the entire contents of which are incorporated here by reference.

TECHNICAL FIELD

[0002] The disclosure relates to the technical field of treadmills, in particular to a foldable treadmill.

BACKGROUND

[0003] Running as a national sport with physical fitness, making people get exercise and relax after the busy work, a treadmill can meet the need of people for running while staying at home, and becomes more and more popular.

[0004] However, an existing treadmill is very large in size and occupied area, if the home space is insufficient, it will affect indoor activities. Although there are already various foldable treadmills on the market, most of them are merely folded between a handrail and a running plate or the running plate is also turned over and erected, which still occupies a large space and is inconvenient to store.

SUMMARY

[0005] An objective of the disclosure is to provide a foldable treadmill, and the foldable treadmill may be automatically folded in three sections of a running plate, is small in the overall size, saves the space, and is convenient to store and carry.

[0006] In order to achieve the above objective, the disclosure provides a foldable treadmill. The foldable treadmill includes a front running plate assembly, a middle running plate assembly and a rear running plate assembly, where the front running plate assembly and the rear running plate assembly are hingedly connected to two ends of the middle running plate assembly in a front-back direction respectively;

[0007] The foldable treadmill further includes:

a first drive mechanism, connected to the front running plate assembly or the rear running plate assembly; and

a linkage mechanism, separately connected to the front running plate assembly, the middle running plate assembly, and the rear running plate assembly, so that when the first drive mechanism drives the front running plate assembly or the rear running plate assembly, the front running plate assembly and the rear running plate assembly can synchronously rotate relative to the middle running plate assembly to

be switched between a folding position and an unfolding position;

In the unfolding position, upper surfaces of the front running plate assembly, the middle running plate assembly, and the rear running plate assembly are coplanar, and in the folding position, the front running plate assembly and the rear running plate assembly get close to each other so as to lift the middle running plate assembly upwards.

[0008] Optionally, in the folding position, an angle between the front running plate assembly and the middle running plate assembly and/or between the rear running plate assembly and the middle running plate assembly is 90°.

[0009] Optionally, the first drive mechanism is constructed as a linear drive unit, a stay bar and a first rolling wheel; and

a fixed end of the linear drive unit is hingedly connected to the front running plate assembly, one end of the stay bar is hingedly connected to the front running plate assembly, the first rolling wheel is rotatably arranged at the other end of the stay bar and abuts against the ground, and a drive end of the linear drive unit is hingedly connected to the stay bar.

[0010] Optionally, the first drive mechanism further includes a fixed base, one end of the front running plate assembly away from the middle running plate assembly is rotatably connected to the fixed base, and the fixed end of the linear drive unit is hingedly connected to the fixed base.

[0011] Optionally, the linear drive unit includes an electric push rod, a linear module or a driving cylinder.

[0012] Optionally, the foldable treadmill further includes a second rolling wheel rotatably arranged at one end of the rear running plate assembly away from the middle running plate assembly.

[0013] Optionally, two first drive mechanisms and two linkage mechanisms are arranged, and the two first drive mechanisms and the two linkage mechanisms are respectively and symmetrically arranged on two sides of the front running plate assembly and the middle running plate assembly in a left-right direction.

[0014] Optionally, the front running plate assembly is rotatably connected with the middle running plate assembly through a first hinge, and the rear running plate assembly is rotatably connected with the middle running plate assembly through a second hinge;

the linkage mechanism is constructed as a first connecting piece, a second connecting piece, an Hshaped connecting rod and a slide rail;

the H-shaped connecting rod is arranged below the middle running plate assembly, a front end of the H-shaped connecting rod is hingedly connected to one end of the first connecting piece, the other end of the

2

50

first connecting piece is hingedly connected to the first hinge, a rear end of the H-shaped connecting rod is hingedly connected to one end of the second connecting piece, and the other end of the second connecting piece is hingedly connected to the second hinge; and

one end of the slide rail is connected to the middle running plate assembly and extends downwards, a sliding hole through which the slide rail penetrates is formed in the H-shaped connecting rod, and the slide rail is slidably inserted in the sliding hole.

[0015] Optionally, an avoidance space for moving of the H-shaped connecting rod and the slide rail is arranged at a bottom of the middle running plate assembly.

[0016] Optionally, the foldable treadmill further includes handles arranged on the middle running plate assembly.

[0017] Optionally, the foldable treadmill further includes:

a running belt; and

a second drive mechanism, including a drive motor, a drive belt, a first roller and a second roller; where the first roller is rotatably arranged on the front running plate assembly, the second roller is rotatably arranged on the rear running plate assembly, and the running belt surrounds the first roller and the second roller; and the drive belt respectively sleeves the first roller and a drive shaft of the drive motor.

[0018] Optionally, the front running plate assembly includes a front running plate, a front fixed support and a front decorating plate;

the front running plate is fixedly arranged on the front fixed support, and the front decorating plate is arranged on the front fixed support in a covering mode;

and/or, the rear running plate assembly includes a rear running plate, a rear fixed support and a rear decorating plate;

the rear running plate is fixedly arranged on the rear fixed support, and the rear decorating plate is arranged on the rear fixed support in a covering mode;

and/or, the middle running plate assembly includes a middle running plate, a middle fixed support and a middle decorating plate; and

the middle running plate is fixedly arranged on the middle fixed support, and the middle decorating plate is arranged on the middle fixed support in a covering mode.

[0019] Through the above technical solution, namely the foldable treadmill of the disclosure, the first drive mechanism is used for driving one end, close to the middle running plate assembly, of one of the front running plate assembly and the rear running plate assembly to rotate upwards and be lifted relative to the other end, and the middle running plate assembly is folded with one of the front running plate assembly and the rear running plate assembly; at the same time, the front running plate assembly, the middle running plate assembly and the rear running plate assembly are connected through the linkage mechanism, such that when the middle running plate assembly is folded with one of the front running plate assembly and the rear running plate assembly, the other one of the front running plate assembly and the rear running plate assembly is also synchronously folded with the middle running plate assembly, and thus, the front running plate assembly and the rear running plate assembly get close to each other so as to lift the middle running plate assembly upwards to be folded; and similarly, when the first drive mechanism drives one of the front running plate assembly and the rear running plate assembly to be unfolded, the other one may also be synchronously unfolded. The foldable treadmill of the disclosure may be automatically folded in three sections, is small in height and thickness of the overall size, reduces the occupied space, and is convenient to store and carry. [0020] Other features and strengths of the disclosure will be described in detail in the subsequent specific implementation.

BRIEF DESCRIPTION OF DRAWINGS

[0021] Accompanying drawings are intended to provide a further understanding of the disclosure, constitute a part of the specification, for explaining the disclosure with the following specific implementation, but not constitute limitation on the disclosure. In the accompanying drawings:

Fig. 1 is a schematic structural diagram of a running state of a foldable treadmill provided by some examples of the disclosure.

Fig. 2 is a schematic structural diagram of a storage state of a foldable treadmill provided by some examples of the disclosure.

Fig. 3 is a schematic structural diagram of a linkage mechanism of a foldable treadmill provided by some examples of the disclosure.

Fig. 4 is an enlarged diagram of a part A in Fig. 3. Fig. 5 is a structural diagram of a second drive mechanism of a foldable treadmill provided by some examples of the disclosure.

Fig. 6 is a structural diagram of a second roller and a second rolling wheel of a foldable treadmill provided by some examples of the disclosure.

40

45

50

Reference numerals in the accompanying drawing are explained:

[0022] 100-front running plate assembly; 110-front running plate; 120-front fixed support; 130-front decorating plate; 140-fixed base; 200-middle running plate assembly; 210-middle running plate; 211-avoidance space; 220-middle fixed support; 230-middle decorating plate; 240-handle; 300-rear running plate assembly; 310-rear running plate; 320-rear fixed support; 330-rear decorating plate; 340-second rolling wheel; 410-linear drive unit; 420-stay bar; 430-first rolling wheel; 440-support frame; 510-drive motor; 520-drive belt; 530-first roller; 540-second roller; 610-first connecting piece; 620-H-shaped connecting rod; 630-second connecting piece; 640-slide rail; 650-fixed plate; 660-first hinge; 670-second hinge; and 700-running belt.

DETAILED DESCRIPTION OF THE INVENTION

[0023] Examples will be illustrated in detail here, and their instances are represented in the accompanying drawings. Unless otherwise indicated, when the following description refers to the accompanying drawings, the same number in the different accompanying drawings represents the same or similar elements. Implementations described in the following examples do not represent all implementations consistent with the examples of the disclosure. Rather, they are merely examples of an apparatus and method consistent with some aspects of the disclosure as detailed in appended claims.

[0024] In the disclosure, without a statement to the contrary, used positional words such as "up, down, left and right" usually refer to be defined based on a drawing direction of the corresponding accompanying drawing; "inner and outer" refer to an interior and an exterior of a profile of a corresponding component; "far and near" refer to a corresponding structure or a corresponding component away from or close to another structure or component; "front and rear" refer to a front and a rear of a human body when a treadmill is in a using state; "left and right" refer to a left side and a right side of the human body when the treadmill is in a using state; and "width" refers to a direction of two sides of the human body when the treadmill is in a using state. Moreover, it needs to be explained that used terms "first", "second" and the like are intended to distinguish one element from another element.

[0025] As shown in Fig. 1 to Fig. 6, some examples of the disclosure provide a foldable treadmill. The foldable treadmill includes a front running plate assembly 100, a middle running plate assembly 200 and a rear running plate assembly 300, where the front running plate assembly 100 and the rear running plate assembly 300 are hingedly connected to two ends of the middle running plate assembly 200 in a front-back direction respectively; the foldable treadmill further includes: a first drive mechanism, connected to the front running plate assembly 100

or the rear running plate assembly 300; and a linkage mechanism, separately connected to the front running plate assembly 100, the middle running plate assembly 200, and the rear running plate assembly 300, so that when the first drive mechanism drives the front running plate assembly 100 or the rear running plate assembly 300, the front running plate assembly 100 and the rear running plate assembly 300 can synchronously rotate relative to the middle running plate assembly 200 to be switched between a folding position and an unfolding position. In the unfolding position, upper surfaces of the front running plate assembly 100, the middle running plate assembly 200, and the rear running plate assembly 300 are coplanar, and in the folding position, the front running plate assembly 100 and the rear running plate assembly 300 get close to each other so as to lift the middle running plate assembly 200 upwards.

[0026] Through the above technical solution, namely the foldable treadmill of the disclosure, the first drive mechanism is used for driving one end, close to the middle running plate assembly 200, of one of the front running plate assembly 100 and the rear running plate assembly 300 to rotate upwards and be lifted relative to the other end, and the middle running plate assembly 200 is folded with one of the front running plate assembly 100 and the rear running plate assembly 300; at the same time, the front running plate assembly 100, the middle running plate assembly and the rear running plate assembly 300 are connected through the linkage mechanism, such that when the middle running plate assembly 200 is folded with one of the front running plate assembly 100 and the rear running plate assembly 300, the other one of the front running plate assembly 100 and the rear running plate assembly 300 is also synchronously folded with the middle running plate assembly 200, and thus, the front running plate assembly 100 and the rear running plate assembly 300 get close to each other so as to lift the middle running plate assembly 200 upwards to be folded; and similarly, when the first drive mechanism drives one of the front running plate assembly 100 and the rear running plate assembly 300 to be unfolded, the other one may also be synchronously unfolded. The foldable treadmill of the disclosure may be automatically folded in three sections, is small in height and thickness of the overall size, reduces the occupied space, and is convenient to store and carry.

[0027] It needs to be explained that the inventive concept of the disclosure may simultaneously further be expanded to a walking machine, a walking and running machine and other sport fitness equipment.

[0028] In some examples of the disclosure, the first drive mechanism may be connected to the front running plate assembly 100, for driving the front running plate assembly 100 to rotate relative to the middle running plate assembly 200 to fold the front running plate assembly 100 and the middle running plate assembly 200; and meanwhile, since the rear running plate assembly 300 is hingedly connected to the middle running plate assembly

200, in conjunction with the linkage mechanism, the rear running plate assembly 300 and the middle running plate assembly 200 may also be synchronously folded, such that the treadmill is automatically folded in three sections, and the space is optimally saved.

[0029] In some other examples of the disclosure, the first drive mechanism may also be connected to the rear running plate assembly 300, for driving the rear running plate assembly 300 to rotate relative to the middle running plate assembly 200 to fold the rear running plate assembly 300 and the middle running plate assembly 200; and meanwhile, since the front running plate assembly 100 is hingedly connected to the middle running plate assembly 200, in conjunction with the linkage mechanism, the front running plate assembly 100 and the middle running plate assembly 200 may also be synchronously folded, such that the treadmill is automatically folded in three sections as well.

[0030] Optionally, in the folding position, an angle between the front running plate assembly 100 and the middle running plate assembly 200 and/or between the rear running plate assembly 300 and the middle running plate assembly 200 is 90°. That is, in some examples, when the front running plate assembly 100 and the rear running plate assembly 300 rotate by 90° towards a direction close to a bottom face of the middle running plate assembly 200, the front running plate assembly 100 and the rear running plate assembly 300 are both at a position perpendicular to the middle running plate assembly 200, and the foldable treadmill is folded. When the front running plate assembly 100 and the rear running plate assembly 300 rotate towards a direction away from the bottom face of the middle running plate assembly 200 to when upper surfaces of the front running plate assembly 100 and the rear running plate assembly 300 are both coplanar with an upper surface of the middle running plate assembly 200, namely, the front running plate assembly 100, the middle running plate assembly 200 and the rear running plate assembly 300 are in a same horizontal plane, the foldable treadmill is unfolded.

[0031] The first drive mechanism may be constructed in any mode, as shown in Fig. 1 and Fig. 2, in some examples of the disclosure, the first drive mechanism is constructed as a linear drive unit 410, a stay bar 420 and a first rolling wheel 430; and the linear drive unit 410 includes but is not limited to an electric push rod, a linear module or a driving cylinder, and the driving cylinder may be a hydraulic cylinder, an air cylinder or an electric cylinder, etc. A fixed end of the linear drive unit 410 is hingedly connected to the front running plate assembly 100, one end of the stay bar 420 is hingedly connected to the front running plate assembly 100, the first rolling wheel 430 is rotatably arranged at the other end of the stay bar 420 and abuts against the ground, and a drive end of the linear drive unit 410 is hingedly connected to the stay bar 420.

[0032] One end of the stay bar 420 is hingedly connected to an upper end of a support frame 440 fixedly

arranged on the front running plate assembly 100, the other end of the stay bar 420 is connected to the rotatable first rolling wheel 430, and the first rolling wheel 430 makes contact with the ground, and can roll on the ground. When the first drive mechanism works, the stay bar 420 connected to the first rolling wheel 430 may reduce frictional force with the ground, which facilitates rotating of the stay bar 420. The fixed end of the linear drive unit 410 is hingedly connected to a front end of the front running plate assembly 100, a drive end of the linear drive unit 410 is hingedly connected to the stay bar 420, and the stay bar 420 is driven by extending and retracting of the linear drive unit 410 to rotate relative to a hinge position of the stay bar 420 and the support frame 440. such that the first rolling wheel 430 moves on the ground in a front-rear direction. When the treadmill needs to be folded, the first rolling wheel 430 is driven by the linear drive unit 410 to move to a direction of the front end of the front running plate assembly 100, one end of the front running plate assembly 100 close to the middle running plate assembly 200 rotates and is lifted upwards relative to the other end, that is, under the action of the stay bar 420, a rear end of the front running plate assembly 100 rotates upwards relative to the front end, such that the front running plate assembly 100 and the middle running plate assembly 200 are folded; meanwhile, by arranging the linkage mechanism, in this time, the rear running plate assembly 300 is driven by the middle running plate assembly 200 to move towards a direction close to the front running plate assembly 100, and the rear running plate assembly 300 rotates and is folded relative to the middle running plate assembly 200; and finally, when the front running plate assembly 100 is at a position perpendicular to the middle running plate assembly 200, the rear running plate assembly 300 is also at the position perpendicular to the middle running plate assembly 200, which is equivalent to that the front running plate assembly 100 and the rear running plate assembly 300 get close to each other to jack up the middle running plate assembly 200 upwards, such that the treadmill is folded, and the foldable treadmill may be stored as a cuboid shape, which reduces sizes in the front-rear direction and a height direction.

[0033] When the foldable treadmill needs to be unfolded, the first rolling wheel 430 is driven by the linear drive unit 410 to move to a direction of the rear end of the front running plate assembly 100, one end of the front running plate assembly 100 close to the middle running plate assembly 200 rotates and is lowered downwards relative to the other end, that is, under the action of the stay bar 420, the rear end of the front running plate assembly 100 rotates downwards relative to the front end, such that the front running plate assembly 100 and the middle running plate assembly 200 are unfolded; meanwhile, by arranging the linkage mechanism, in this time, the rear running plate assembly 300 is driven by a middle running plate to move towards a direction away from the front running plate assembly 100, and the rear running plate assembly

300 rotates and is unfolded relative to the middle running plate assembly 200; and finally, when the upper surface of the front running plate assembly 100 and the upper surface of the middle running plate assembly 200 are within the same horizontal plane, the upper surface of the rear running plate assembly 300 and the upper surface of the middle running plate assembly 200 are also within the same horizontal plane, and thus the treadmill is unfolded.

[0034] In some other examples of the disclosure, the

first drive mechanism further includes a fixed base 140,

9

one end of the front running plate assembly 100 away from the middle running plate assembly 200 is rotatably connected to the fixed base 140, and a fixed end of the linear drive unit 410 is hingedly connected to the fixed base 140. The fixed base 140 makes contact with the ground, the front end of the front running plate assembly 100 is hingedly connected to the fixed base 140, such that the front running plate assembly 100 is capable of rotating relative to the fixed base 140, and the fixed end of the linear drive unit 410 is hingedly connected to the fixed base 140, so as to adapt to change of a position of the linear drive unit 410 when the stay bar 420 rotates. [0035] As shown in Fig. 1 and Fig. 6, in some examples of the disclosure, the foldable treadmill further includes a second rolling wheel 340 rotatably arranged at one end of the rear running plate assembly 300 away from the middle running plate assembly 200. In a process of folding and unfolding the treadmill, the treadmill may be conveniently stored and moved, when the foldable treadmill is not stored, since the second rolling wheel 340 is arranged at a rear end of the rear running plate assembly 300, a front end of the foldable treadmill may be lifted, and the treadmill is moved depending on the second rolling wheel 340. The treadmill may be conveniently carried, moved, stored to lean against the wall, placed on the ground or hided under a bed, etc. through rotation of the second rolling wheel 340 after being folded and stored. [0036] It may be understood that the plurality of second rolling wheels 340 may be arranged at intervals in a width direction of the rear running plate assembly 300, and when in use, a user can better grasp the balance. Optionally, two second rolling wheels 340 are arranged, and rotatably arranged at the rear end of the rear running plate assembly 300 in a spaced mode.

[0037] In some implementations of the disclosure, two first drive mechanisms and two linkage mechanisms are arranged, and the two first drive mechanisms and the two linkage mechanisms are respectively and symmetrically arranged on two sides of the front running plate assembly 100 and the middle running plate assembly 200 in a left-right direction. The two first drive mechanisms are respectively arranged on two sides of a width direction of the front running plate assembly 100, so as to more stably and reliably drive the front running plate assembly 100 to rotate; and the two linkage mechanisms are respectively on two sides of a width direction of the middle running plate assembly 200, so as to more

smoothly drive the rear running plate assembly 300 to be linked to the front running plate assembly 100.

[0038] The front running plate assembly 100 is rotatably connected to the middle running plate assembly 200 through a first hinge 660, and the rear running plate assembly 300 is rotatably connected to the middle running plate assembly 200 through a second hinge 670. The first hinge 660 and the second hinge 670 may be constructed in any mode in the related art as long as the above folding and unfolding may be achieved, which is not limited in the disclosure. In some examples, the first hinge 660 and the second hinge 670 in the disclosure may select a 90° internally-folded hinge, such that the front running plate assembly 100 and the rear running plate assembly 300 may both rotate by 90° relative to the middle running plate assembly 200, namely, rotate to a position perpendicular to the middle running plate assembly 200.

[0039] The linkage mechanism may be constructed in any mode, as shown in Fig. 3 and Fig. 4, in some implementations of the disclosure, the linkage mechanism may be constructed as a first connecting piece 610, a second connecting piece 630, an H-shaped connecting rod 620 and a slide rail 640; the H-shaped connecting rod 620 is arranged below the middle running plate assembly 200, a front end of the H-shaped connecting rod 620 is hingedly connected to one end of the first connecting piece 610, the other end of the first connecting piece 610 is hingedly connected to the first hinge 660, a rear end of the Hshaped connecting rod 620 is hingedly connected to one end of the second connecting piece 630, and the other end of the second connecting piece 630 is hingedly connected to the second hinge 670; and one end of the slide rail 640 is connected to the middle running plate assembly 200 via a fixed plate 650, and extends downwardly with respect to the middle running plate assembly 200, a sliding hole through which the slide rail 640 penetrates is formed in the H-shaped connecting rod 620, and the slide rail 640 is slidably inserted in the sliding hole. When the first drive mechanism drives the front running plate assembly 100 to rotate and be lifted, the first connecting piece 610 drives the H-shaped connecting rod 620 to move upwards along the slide rail 640, meanwhile, the H-shaped connecting rod 620 drives an end portion of the second connecting piece 630 connected with the Hshaped connecting rod to move upwards similarly, one end of the second connecting piece 630 connected to the second hinge 670 rotates and is folded relative to the middle running plate assembly 200 while driving the rear running plate assembly 300 to move towards a direction of the front running plate assembly 100, and thus, the front running plate assembly 100 and the rear running plate assembly 300 are capable of synchronized action. When the H-shaped connecting rod 620 moves to an upper end of the slide rail 640, the front running plate assembly 100 and the rear running plate assembly 300 both rotate to the position perpendicular to the middle running plate assembly 200, and the treadmill is folded.

25

40

45

When the treadmill needs to be unfolded and the first drive mechanism drives the front running plate assembly 100 to rotate and descend, the first connecting piece 610 drives the H-shaped connecting rod 620 to move downwards along the slide rail 640, the H-shaped connecting rod 620 drives the second connecting piece 630 to move reversely, one end connected to the second hinge 670 rotates and is unfolded relative to the middle running plate assembly 200 while driving the rear running plate assembly 300 to move towards a direction away from the front running plate assembly 100, and the front running plate assembly 100 and the rear running plate assembly 300 are capable of synchronized action. When the H-shaped connecting rod 620 moves to a lower end of the slide rail 640, the upper surfaces of the front running plate assembly 100 and the rear running plate assembly 300 both rotate to the same horizontal plane with the upper surface of the middle running plate assembly 200, and the treadmill is unfolded.

[0040] Considering that the arrangement of the slide rail 640 will increase a thickness of the middle running plate assembly 200 to a certain degree, which is not beneficial for lightness and thinness of the treadmill. Thus, in some other examples of the disclosure, an avoidance space 211 for moving of the H-shaped connecting rod 620 and the slide rail 640 is arranged at a bottom of the middle running plate assembly 200. That is, a groove with a downward opening is formed in the bottom of the middle running plate assembly 200, the H-shaped connecting rod 620 and the slide rail 640 are arranged in the groove, and the groove forms the above avoidance space 211, such that the H-shaped connecting rod 620 and the slide rail 640 may further be mounted and arranged on the premise of the smaller thickness of the middle running plate assembly 200.

[0041] In some examples of the disclosure, the foldable treadmill further includes handles 240 arranged on the middle running plate assembly 200. After the foldable treadmill is folded, a user may apply a force through the handles 240, the user may conveniently carry or move the folded treadmill to other positions, and the use experience of the user is improved.

[0042] As shown in Fig. 5, in some examples, the foldable treadmill further includes a running belt 700 and a second drive mechanism. The second drive mechanism includes a drive motor 510, a drive belt 520, a first roller 530 and a second roller 540; the first roller 530 is rotatably arranged on the front running plate assembly 100, the second roller 540 is rotatably arranged on the rear running plate assembly 300, and the running belt 700 surrounds the first roller 530 and the second roller 540; and the drive belt 520 respectively sleeves the first roller 530 and a drive shaft of the drive motor 510. The running belt 700 respectively sleeves the first roller 530 and the second roller 540, the first roller 530 is rotatably arranged on the front running plate assembly 100, the second roller 540 is rotatably arranged on the rear running plate assembly 300, and the drive motor 510 drives the first roller 530 to rotate through the drive belt 520, such that the running belt 700 is driven to rotate around the first roller 530 and the second roller 540.

[0043] The front running plate assembly, the middle running plate assembly and the rear running plate assembly may be constructed in any mode. In some examples, the front running plate assembly 100 may include a front running plate 110, a front fixed support 120 and a front decorating plate 130. The front running plate 110 is fixedly arranged on the front fixed support 120, and the front decorating plate 130 is arranged on the front fixed support 120 in a covering mode. The front fixed support 120 is rotatably connected to the above fixed base 140, and meanwhile, the front decorating plate 130 may further shield the drive motor 510, the drive belt 520 and the first roller 530 of the second drive mechanism so as to improve an artistic effect of the foldable treadmill. [0044] In some other examples, the rear running plate assembly 300 may also include a rear running plate 310, a rear fixed support 320 and a rear decorating plate 330. The rear running plate 310 is fixedly arranged on the rear fixed support 320. the rear decorating plate 330 is arranged on the rear fixed support 320 in a covering mode, and similarly, the rear decorating plate 330 may further shield the above second roller 540 so as to improve the aesthetics.

[0045] In some other examples, the middle running plate assembly 200 includes a middle running plate 210, a middle fixed support 220 and a middle decorating plate 230. The middle running plate 210 is fixedly arranged on the middle fixed support 220, and the middle decorating plate 230 is arranged on the middle fixed support 220 in a covering mode. The handles 240 may be fixedly connected to the middle fixed support 220 or the middle decorating plate 230, two handles 240 may be arranged, and the two handles 240 are symmetrically arranged with respect to a central axis of a width direction of the middle running plate 210.

[0046] According to the foldable treadmill provided by the example of the disclosure, the front running plate assembly 100 and the rear running plate assembly 300 are both connected to the middle running plate assembly 200 by adopting the 90° internally-folded hinge, and the three running plate assemblies may be folded to be a U shape by internally rotating 90 degrees. The front running plate assembly 100 is rotatably connected to the middle running plate assembly 200 through the first hinge 660, and the rear running plate assembly 300 is rotatably connected to the middle running plate assembly 200 through the second hinge 670. The linkage mechanism includes the first connecting piece 610, the second connecting piece 630, the H-shaped connecting rod 620 and the slide rail 640; and two ends of the H-shaped connecting rod 620 are respectively connected to the front running plate assembly 100 and the rear running plate assembly 300 through the first connecting piece 610 and the second connecting piece 630, the sliding hole is formed in the H-shaped connecting rod 620, the slide rail 640 is slidably

inserted in the sliding hole, and the upper end of the slide rail 640 is fixedly connected to the middle running plate assembly 200 through a fixed plate 650. The H-shaped connecting rod 620 can slide up and down along the slide rail 640 to ensure that the front running board assembly 100 and the rear running board assembly 300 can synchronize their movements. The first drive mechanism includes the linear drive unit 410, the stay bar 420 and the first rolling wheel 430. A bottom face of the fixed base 140 makes contact with the ground, and a relative position of the fixed base is kept unchanged through the frictional force with the ground. The front end of the front running plate assembly 100 may be rotatably connected to an inner side of the fixed base 140, the linear drive unit 410 may select an electric push rod, one end of the electric push rod may be rotatably connected to an outer side of the fixed base 140, the other end of the electric push rod is hingedly connected to the stay bar 420, one end of the stay bar 420 is hingedly connected to the support frame 440, the support frame 440 is fixed to the front decorating plate 130 of the front running plate assembly 100, the other end of the stay bar 420 is connected to the first rolling wheel 430 capable of freely rotating, and thus, the electric push rod drives the stay bar 420 to move when retracts so as to achieve a folding and storage process of the treadmill. The drive motor 510, the drive belt 520 and the first roller 530 are fixed to the front running plate assembly 100, which matches with the second roller 540 of the rear running plate assembly 300 to achieve moving of the running belt 700. The rear end of the rear running plate assembly 300 is rotatably connected to a pair of second rolling wheels 340, in the automatic folding process, the front end of the front running plate assembly 100 is hingedly connected to the fixed base 140, the fixed base 140 does not move relative to the ground due to the frictional force, and when the front running plate assembly 100 rotates, the rear running plate assembly 300 gradually gets close to the front running plate assembly 100 under driving of the linkage mechanism to be folded. A pair of handles 240 are fixedly arranged on the middle decorating plate 230 of the middle running plate assembly 200, after being stored, the first rolling wheel 430 of the stay bar 420 is located at the bottom of the folded treadmill, and the treadmill may be conveniently carried and moved. When being not stored, the second rolling wheels 340 are similarly arranged at a rear end of the foldable treadmill, such that people may lift the front end of the treadmill when the treadmill is not stored so as to move the treadmill depending on the second rolling wheels 340. The foldable treadmill may be automatically folded in three sections, a dirty surface making contact with the ground cannot be exposed, the foldable treadmill is finally stored in a cuboid shape, the first rolling wheel 430 and the second rolling wheels 340 are arranged at the bottom, and the user may conveniently carry the foldable treadmill, move it, store it to lean against the wall, place it on the ground, or hide it under the bed.

[0047] After considering the specification and practic-

ing the disclosure, those skilled in the art may easily think of other implementation solutions of the disclosure. The present application is intended to contain any variation, application or adaptive change of the disclosure, and these variations, applications or adaptive changes follow general principles of the disclosure and include commonly-known knowledge or conventional technical means in the technical field not disclosed in the disclosure. The specification and examples are merely regarded as illustrative, the true scope and spirit of the disclosure are indicated by the claims below.

[0048] It needs to be understood that the disclosure is not limited to an accurate structure described above and shown in the accompanying drawings, and various modifications and changes can be made without departing away from the scope of the disclosure. The scope of the disclosure is merely limited by the appended claims.

[0049] Preferred implementations of the disclosure are described in detail above in conjunction with the accompanying drawings, however, the disclosure is not limited to specific details in the above implementation, within the technical conception scope of the disclosure, various simple variations can be made to the technical solution of the disclosure, and all these simple variations belong to the scope of protection of the disclosure.

[0050] In addition, it needs to be noted that various specific technical features described in the above specific implementation may be combined in any appropriate mode without conflict, and in order to avoid needless repetitions, the disclosure does not explain various possible combination modes.

[0051] In addition, the various different implementations of the disclosure may also be combined arbitrarily, as long as they do not contradict the idea of the disclosure, and they also are to be regarded as contents disclosed in the disclosure.

Claims

35

40

45

50

 A foldable treadmill, is characterized in that the foldable treadmill comprises a front running plate assembly (100), a middle running plate assembly (200) and a rear running plate assembly (300), the front running plate assembly (100) and the rear running plate assembly (300) are hingedly connected to two ends of the middle running plate assembly (200) in a front-back direction respectively;

the foldable treadmill further comprises:

a first drive mechanism, connected to the front running plate assembly (100) or the rear running plate assembly (300); and

a linkage mechanism, separately connected to the front running plate assembly (100), the middle running plate assembly (200), and the rear running plate assembly (300), so that when the first drive mechanism drives the front running

15

20

25

35

plate assembly (100) or the rear running plate assembly (300), the front running plate assembly (100) and the rear running plate assembly (300) can synchronously rotate relative to the middle running plate assembly (200) to be switched between a folding position and an unfolding position; and

in the unfolding position, upper surfaces of the front running plate assembly (100), the middle running plate assembly (200), and the rear running plate assembly (300) are coplanar, and in the folding position, the front running plate assembly (100) and the rear running plate assembly (300) get close to each other to lift the middle running plate assembly (200) upwards.

- 2. The foldable treadmill according to claim 1, characterized in that in the folding position, an angle between the front running plate assembly (100) and the middle running plate assembly (200) and/or between the rear running plate assembly (300) and the middle running plate assembly (200) is 90°.
- 3. The foldable treadmill according to claim 1, characterized in that the first drive mechanism is constructed as a linear drive unit (410), a stay bar (420) and a first rolling wheel (430); and a fixed end of the linear drive unit (410) is hingedly connected to the front running plate assembly (100), one end of the stay bar (420) is hingedly connected to the front running plate assembly (100), the first rolling wheel (430) is rotatably arranged at the other end of the stay bar (420) and abuts against the ground, and a drive end of the linear drive unit (410) is hingedly connected to the stay bar (420).
- 4. The foldable treadmill according to claim 3, characterized in that the first drive mechanism further comprises a fixed base (140), one end of the front running plate assembly (100) away from the middle running plate assembly (200) is rotatably connected to the fixed base (140), and the fixed end of the linear drive unit (410) is hingedly connected to the fixed base (140).
- 5. The foldable treadmill according to claim 3, characterized in that the linear drive unit (410) comprises an electric push rod, a linear module or a driving cylinder.
- 6. The foldable treadmill according to claim 3, characterized in that the foldable treadmill further comprises a second rolling wheel (340) being rotatably arranged at one end of the rear running plate assembly (300) away from the middle running plate assembly (200).
- 7. The foldable treadmill according to claim 1, charac-

terized in that two first drive mechanisms and two linkage mechanisms are arranged, and the two first drive mechanisms and the two linkage mechanisms are respectively and symmetrically arranged on two sides of the front running plate assembly (100) and the middle running plate assembly (200) in a leftright direction.

The foldable treadmill according to claim 1, characterized in that the front running plate assembly (100) is rotatably connected with the middle running plate assembly (200) through a first hinge (660), and the rear running plate assembly (300) is rotatably connected with the middle running plate assembly (200) through a second hinge (670);

> the linkage mechanism is constructed as a first connecting piece (610), a second connecting piece (630), an H-shaped connecting rod (620) and a slide rail (640);

> the H-shaped connecting rod (620) is arranged below the middle running plate assembly (200), a front end of the H-shaped connecting rod (620) is hingedly connected to one end of the first connecting piece (610), the other end of the first connecting piece (610) is hingedly connected to the first hinge (660), a rear end of the H-shaped connecting rod (620) is hingedly connected to one end of the second connecting piece (630), and the other end of the second connecting piece (630) is hingedly connected to the second hinge (670); and

> one end of the slide rail (640) is connected to the middle running plate assembly (200) and extends downwards, a sliding hole through which the slide rail (640) penetrates is formed in the H-shaped connecting rod (620), and the slide rail (640) is slidably inserted in the sliding hole.

- 40 9. The foldable treadmill according to claim 8, characterized in that an avoidance space (211) for moving of the H-shaped connecting rod (620) and the slide rail (640) is arranged at a bottom of the middle running plate assembly (200).
 - 10. The foldable treadmill according to any one of claims 1 to 9, characterized in that the foldable treadmill further comprises handles (240) arranged on the middle running plate assembly (200).
 - 11. The foldable treadmill according to any one of claims 1 to 9, characterized in that the foldable treadmill further comprises:

a running belt (700); and a second drive mechanism; comprising a drive motor (510), a drive belt (520), a first roller (530) and a second roller (540); the first roller (530)

9

50

being rotatably arranged on the front running plate assembly (100), the second roller (540) being rotatably arranged on the rear running plate assembly (300), and the running belt (700) surrounding the first roller (530) and the second roller (540); and the drive belt (520) respectively sleeving the first roller (530) and a drive shaft of the drive motor (510).

12. The foldable treadmill according to any one of claims 1 to 9, characterized in that the front running plate assembly (100) comprises a front running plate (110), a front fixed support (120) and a front decorating plate (130);

the front running plate (110) is fixedly arranged on the front fixed support (120), and the front decorating plate (130) is arranged on the front fixed support (120) in a covering mode; and/or, the rear running plate assembly (300) comprises a rear running plate (310), a rear fixed support (320) and a rear decorating plate (330); the rear running plate (310) is fixedly arranged on the rear fixed support (320), and the rear decorating plate (330) is arranged on the rear fixed support (320) in a covering mode; and/or, the middle running plate assembly (200) comprises a middle running plate (210), a middle fixed support (220) and a middle decorating plate (230); and

the middle running plate (210) is fixedly arranged on the middle fixed support (220), and the middle decorating plate (230) is arranged on the middle fixed support (220) in a covering mode.








Fig. 1














INTERNATIONAL SEARCH REPORT

International application No.

PCT/CN2022/089111

Relevant to claim No.

1, 2, 7-12

1, 2, 7-12

1-12

1-12

1-12

5

CLASSIFICATION OF SUBJECT MATTER

A63B 22/02(2006.01)i

According to International Patent Classification (IPC) or to both national classification and IPC

10

FIELDS SEARCHED

Category*

X

X

A

Α

A

Α

CN)

100088, China

Minimum documentation searched (classification system followed by classification symbols) A63B22

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

15

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) CNTXT, ENTXTC, VEN, CNKI: 跑步机, 折叠, 直线, 驱动, 杆, 滚轮, 底座, 推杆, 液压缸, folding, treadmill, line, driving, pole, trolley?, pulley, roller, wheel?, base, push, rod, cylinder

Citation of document, with indication, where appropriate, of the relevant passages

CN 215231895 U (BEIJING XIAOMI MOBILE SOFTWARE CO., LTD.) 21 December 2021

CN 211434919 U (BEIJING KINGSMITH TECHNOLOGY CO., LTD.) 08 September 2020

CN 211434920 U (BEIJING KINGSMITH TECHNOLOGY CO., LTD.) 08 September 2020

US 2006003869 A1 (JOHNSON TECH CO., LTD.) 05 January 2006 (2006-01-05)

US 2008280734 A1 (SPARK INNOVATIONS INC.) 13 November 2008 (2008-11-13)

CN 113384847 A (BEIJING XIAOMI MOBILE SOFTWARE CO., LTD.) 14 September

20

DOCUMENTS CONSIDERED TO BE RELEVANT

description, paragraphs 45-65, and figures 1-7

description, specific embodiments, and figures 1-8

2021 (2021-09-14)

(2021-12-21)

(2020-09-08) entire document

(2020-09-08)entire document

Special categories of cited documents

to be of particular relevance

entire document

entire document

Further documents are listed in the continuation of Box C.

document defining the general state of the art which is not considered

earlier application or patent but published on or after the international filing date

document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

document referring to an oral disclosure, use, exhibition or other document published prior to the international filing date but later than the priority date claimed

25

50

55

30 35

40

45

Form PCT/ISA/210 (second sheet) (January 2015)

Name and mailing address of the ISA/CN

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

16 September 2022

document member of the same patent family

Date of mailing of the international search report

See patent family annex.

Authorized officer

Telephone No.

Facsimile No. (86-10)62019451

Date of the actual completion of the international search

03 September 2022

China National Intellectual Property Administration (ISA/

No. 6, Xitucheng Road, Jimenqiao, Haidian District, Beijing

EP 4 427 820 A1

International application No.

INTERNATIONAL SEARCH REPORT

Information on patent family members PCT/CN2022/089111 5 Patent document Publication date Publication date Patent family member(s) cited in search report (day/month/year) (day/month/year) CN 113384847 14 September 2021 None CN 215231895 U 21 December 2021 None 211434919 08 September 2020 CN U None 10 08 September 2020 CN 211434920 U None US 2006003869 **A**1 05 January 2006 2009163327 **A**1 25 June 2009 US 2008280734 WO **A**1 $\mathbf{A}1$ 13 November 2008 200813812120 November 2008 15 20 25 30 35 40 45 50

55

Form PCT/ISA/210 (patent family annex) (January 2015)

EP 4 427 820 A1

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

• CN 202123300376 [0001]