



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 71

(48) Corrigendum issued on:
27.11.2024 Bulletin 2024/48

(43) Date of publication:
02.10.2024 Bulletin 2024/40

(21) Application number: **22898166.8**

(22) Date of filing: **12.07.2022**

(51) International Patent Classification (IPC):
B65D 77/06 ^(2006.01) **B67D 1/04** ^(2006.01)
B65D 83/00 ^(2006.01) **B65D 85/72** ^(2006.01)

(52) Cooperative Patent Classification (CPC):
B67D 1/04; B65D 77/06; B65D 83/00; B65D 85/72;
B67D 1/0801; B67D 1/0804

(86) International application number:
PCT/JP2022/027408

(87) International publication number:
WO 2023/095381 (01.06.2023 Gazette 2023/22)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA ME
Designated Validation States:
KH MA MD TN

(30) Priority: **25.11.2021 JP 2021191543**

(71) Applicants:
• **Asahi Group Holdings, Ltd.**
Tokyo 130-8602 (JP)

• **Asahi Breweries, Ltd.**
Tokyo 130-8602 (JP)

(72) Inventors:
• **MIYATANI, Tomohisa**
3020106 Ibaraki (JP)
• **YAMAGISHI, Masanori**
1430024 Tokyo (JP)
• **INAGAKI, Motohiro**
1430024 Tokyo (JP)

(74) Representative: **Hoffmann Eitle**
Patent- und Rechtsanwälte PartmbB
Arabellastraße 30
81925 München (DE)

(54) **BEVERAGE CONTAINER AND METHOD FOR ASSEMBLING BEVERAGE CONTAINER**

(57) A beverage container includes an outer container having a first mouth portion, a lid member attached to the outer container, and a replaceable component attached to the lid member. The lid member includes an attachment portion attached to the first mouth portion, an upper pipe portion arranged outside the outer container, an annular portion extending outward from the upper pipe portion and connecting the upper pipe portion and the attachment portion, and a lower pipe portion extending downward from the annular portion. The replaceable component includes a sealing member slidable with respect to the lower pipe portion and being in annular contact with an outer surface of the lower pipe portion at an installation position, a tubular body holding the sealing member and being supported by the lower pipe portion via the sealing member located at the installation position, and a bag for containing a beverage attached to the tubular body.

Fig. 1

