



(12) **CORRECTED EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(15) Correction information:
Corrected version no 1 (W1 A1)
Corrections, see
Bibliography INID code(s) 72

(48) Corrigendum issued on:
09.04.2025 Bulletin 2025/15

(43) Date of publication:
19.02.2025 Bulletin 2025/08

(21) Application number: **24754541.1**

(22) Date of filing: **30.04.2024**

(51) International Patent Classification (IPC):
F04D 29/54^(2006.01) F04D 29/44^(2006.01)
F04D 29/66^(2006.01)

(52) Cooperative Patent Classification (CPC):
F04D 29/4213; F04D 29/023; F04D 29/526;
F04D 29/626; F04D 29/646; F05D 2250/51;
F05D 2260/36; F05D 2300/514

(86) International application number:
PCT/JP2024/016646

(87) International publication number:
WO 2025/004525 (02.01.2025 Gazette 2025/01)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL
NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA
Designated Validation States:
GE KH MA MD TN

(30) Priority: **30.06.2023 JP 2023108180**

(71) Applicant: **DAIKIN INDUSTRIES, LTD.**
Osaka-shi, Osaka 530-0001 (JP)

(72) Inventors:
• **TERAKAWA, Azumi**
Osaka-shi, Osaka 5300001 (JP)
• **TOMIOKA, Hirotaka**
Osaka-shi, Osaka 5300001 (JP)
• **MIFUNE, Yurie**
Osaka-shi, Osaka 5300001 (JP)
• **KASHIHARA, Takashi**
Osaka-shi, Osaka 5300001 (JP)

(74) Representative: **Hoffmann Eitle**
Patent- und Rechtsanwälte PartmbB
Arabellastraße 30
81925 München (DE)

(54) **BLOWER DEVICE, HEAT SOURCE-SIDE UNIT, USE-SIDE UNIT, AND METHOD FOR MANUFACTURING BLOWER DEVICE**

(57) A first bell mouth (20) has a first peripheral wall portion (21) that forms a first air passage (22). The first peripheral wall portion (21) has an opening (51) penetrating in the thickness direction. A porous part (50) is positioned to cover the opening (51). The first peripheral wall portion (21) has the attachment portion (55) configured to attach the porous part (50).

FIG.5

