



(11) **EP 4 514 039 A1**

(12) **EUROPEAN PATENT APPLICATION**
published in accordance with Art. 153(4) EPC

(43) Date of publication:
26.02.2025 Bulletin 2025/09

(51) International Patent Classification (IPC):
H04W 72/25 ^(2023.01) **H04L 5/00** ^(2006.01)
H04W 72/02 ^(2009.01) **H04W 64/00** ^(2009.01)
H04W 92/18 ^(2009.01)

(21) Application number: **23792151.5**

(22) Date of filing: **18.04.2023**

(52) Cooperative Patent Classification (CPC):
H04L 5/00; H04W 64/00; H04W 72/02;
H04W 72/25; H04W 92/18

(86) International application number:
PCT/KR2023/005235

(87) International publication number:
WO 2023/204575 (26.10.2023 Gazette 2023/43)

(84) Designated Contracting States:
AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL
NO PL PT RO RS SE SI SK SM TR
Designated Extension States:
BA
Designated Validation States:
KH MA MD TN

(72) Inventors:
• **KO, Woosuk**
Seoul 06772 (KR)
• **SEO, Hanbyul**
Seoul 06772 (KR)
• **LEE, Seungmin**
Seoul 06772 (KR)

(30) Priority: **21.04.2022 US 202263333512 P**

(74) Representative: **Plasseraud IP**
104 Rue de Richelieu
CS92104
75080 Paris Cedex 02 (FR)


(71) Applicant: **LG Electronics Inc.**
Yeongdeungpo-gu
Seoul 07336 (KR)

(54) **METHOD AND APPARATUS FOR TRANSMITTING OR RECEIVING SL PRS**

(57) Provided are a method by which a first apparatus performs wireless communication, and an apparatus supporting same. The method may comprise the steps of acquiring information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); acquiring sidelink (SL) positioning reference

signal (PRS) configuration information including information related to a set of RBs for an SL PRS; and on the basis of the SL PRS configuration information, transmitting the SL PRS to a second apparatus within the set of RBs for the SL PRS, wherein the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

FIG. 22



EP 4 514 039 A1

Description**TECHNICAL FIELD**

5 [0001] This disclosure relates to a wireless communication system.

BACKGROUND ART

10 [0002] Sidelink (SL) communication is a communication scheme in which a direct link is established between User Equipments (UEs) and the UEs exchange voice and data directly with each other without intervention of a base station. SL communication is under consideration as a solution to the overhead of a base station caused by rapidly increasing data traffic. Vehicle-to-everything (V2X) refers to a communication technology through which a vehicle exchanges information with another vehicle, a pedestrian, an object having an infrastructure (or infra) established therein, and so on. The V2X may be divided into 4 types, such as vehicle-to-vehicle (V2V), vehicle-to-infrastructure (V2I), vehicle-to-network (V2N), and
 15 vehicle-to-pedestrian (V2P). The V2X communication may be provided via a PC5 interface and/or Uu interface.

[0003] Meanwhile, as a wider range of communication devices require larger communication capacities, the need for mobile broadband communication that is more enhanced than the existing Radio Access Technology (RAT) is rising. Accordingly, discussions are made on services and user equipment (UE) that are sensitive to reliability and latency. And, a next generation radio access technology that is based on the enhanced mobile broadband communication, massive
 20 Machine Type Communication (MTC), Ultra-Reliable and Low Latency Communication (URLLC), and so on, may be referred to as a new radio access technology (RAT) or new radio (NR).

DISCLOSURE**25 TECHNICAL SOLUTION**

[0004] In an embodiment, provided is a method for performing wireless communication by a first device. The method may comprise: obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information
 30 related to a set of RBs for a SL PRS; and transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information, wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

[0005] In an embodiment, provided is a first device adapted to perform wireless communication. The first device may comprise: at least one transceiver; at least one processor; and at least one memory connected to the at least one processor
 35 and storing instructions that, based on being executed by the at least one processor, cause the first device to perform operations comprising: obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information, wherein the set of RBs for the SL PRS does not overlap with the set
 40 of RBs for the PSFCH.

[0006] In an embodiment, provided is a processing device adapted to control a first device. The processing device may comprise: at least one processor; and at least one memory connected to the at least one processor and storing instructions that, based on being executed by the at least one processor, cause the first device to perform operations comprising:
 45 obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information, wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

[0007] In an embodiment, provided is a non-transitory computer-readable storage medium storing instructions. The instructions, when executed, may cause a first device to perform operations comprising: obtaining information related to a
 50 set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information, wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

55 BRIEF DESCRIPTION OF THE DRAWINGS

[0008]

FIG. 1 shows a communication structure providable in a 6G system, based on an embodiment of the present disclosure.

FIG. 2 shows an electromagnetic spectrum, based on an embodiment of the present disclosure.

FIG. 3 shows a structure of an NR system, based on an embodiment of the present disclosure.

FIG. 4 shows a radio protocol architecture, based on an embodiment of the present disclosure.

FIG. 5 shows a structure of a radio frame of an NR, based on an embodiment of the present disclosure.

FIG. 6 shows a structure of a slot of an NR frame, based on an embodiment of the present disclosure.

FIG. 7 shows an example of a BWP, based on an embodiment of the present disclosure.

FIG. 8 shows a procedure of performing V2X or SL communication by a UE based on a transmission mode, based on an embodiment of the present disclosure.

FIG. 9 shows an example of an architecture of a 5G system capable of positioning a UE having access to a next generation-radio access network (NG-RAN) or an E-UTRAN based on an embodiment of the present disclosure.

FIG. 10 shows an example of implementing a network for measuring a location of a UE based on an embodiment of the present disclosure.

FIG. 11 shows an example of a protocol layer used to support LTE positioning protocol (LPP) message transmission between an LMF and a UE based on an embodiment of the present disclosure.

FIG. 12 shows an example of a protocol layer used to support NR positioning protocol A (NRPPa) PDU transmission between an LMF and an NG-RAN node based on an embodiment of the present disclosure.

FIG. 13 is a drawing for explaining an OTDOA positioning method based on an embodiment of the present disclosure.

FIG. 14 shows an example of allocating RBs other than RBs used for PSFCH transmission to SL PRS resource transmission and transmitting SL PRS resources with comb size = 2 using 2 symbols, when 2 PSFCH symbols are used within one slot, based on an embodiment of the present disclosure.

FIG. 15 shows an example of applying slot aggregation for SLPRS resource transmission with a staggered pattern, based on an embodiment of the present disclosure.

FIG. 16 shows an example of staggering SL PRS resources in units of RE rather than units of RB, based on an embodiment of the present disclosure.

FIG. 17 shows an example of applying PSFCH slot aggregation for SL PRS transmission in order to allow the first PSFCH symbol to operate as an AGC symbol by making PSFCH symbols transmitted within one PSFCH slot the same, based on an embodiment of the present disclosure.

FIG. 18 shows an example of allocating SL PRS in units of RE in PSFCH symbols, based on an embodiment of the present disclosure.

FIG. 19 shows an example of applying PSFCH slot aggregation for SL PRS transmission, when multiple UEs transmit SL PRS simultaneously, in order to allow the first PSFCH symbol to operate as an AGC symbol by making PSFCH symbols transmitted within one PSFCH slot the same, based on an embodiment of the present disclosure.

FIGs. 20 and 21 show an example of transmitting SL PRS in units of a set of 3 REs, based on an embodiment of the present disclosure.

FIG. 22 shows a method for a first device to perform wireless communication, based on an embodiment of the present disclosure.

FIG. 23 shows a method for a second device to perform wireless communication, based on an embodiment of the present disclosure.

FIG. 24 shows a communication system 1, based on an embodiment of the present disclosure.

FIG. 25 shows wireless devices, based on an embodiment of the present disclosure.

FIG. 26 shows a signal process circuit for a transmission signal, based on an embodiment of the present disclosure.

FIG. 27 shows another example of a wireless device, based on an embodiment of the present disclosure.

FIG. 28 shows a hand-held device, based on an embodiment of the present disclosure.

FIG. 29 shows a vehicle or an autonomous vehicle, based on an embodiment of the present disclosure.

MODE FOR INVENTION

[0009] In the present disclosure, "A or B" may mean "only A", "only B" or "both A and B." In other words, in the present disclosure, "A or B" may be interpreted as "A and/or B". For example, in the present disclosure, "A, B, or C" may mean "only A", "only B", "only C", or "any combination of A, B, C".

[0010] A slash (/) or comma used in the present disclosure may mean "and/or". For example, "A/B" may mean "A and/or B". Accordingly, "A/B" may mean "only A", "only B", or "both A and B". For example, "A, B, C" may mean "A, B, or C".

[0011] In the present disclosure, "at least one of A and B" may mean "only A", "only B", or "both A and B". In addition, in the present disclosure, the expression "at least one of A or B" or "at least one of A and/or B" may be interpreted as "at least one of A and B".

[0012] In addition, in the present disclosure, "at least one of A, B, and C" may mean "only A", "only B", "only C", or "any

combination of A, B, and C". In addition, "at least one of A, B, or C" or "at least one of A, B, and/or C" may mean "at least one of A, B, and C".

[0013] In addition, a parenthesis used in the present disclosure may mean "for example". Specifically, when indicated as "control information (PDCCH)", it may mean that "PDCCH" is proposed as an example of the "control information". In other words, the "control information" of the present disclosure is not limited to "PDCCH", and "PDCCH" may be proposed as an example of the "control information". In addition, when indicated as "control information (i.e., PDCCH)", it may also mean that "PDCCH" is proposed as an example of the "control information".

[0014] In the following description, 'when, if, or in case of' may be replaced with 'based on'.

[0015] A technical feature described individually in one figure in the present disclosure may be individually implemented, or may be simultaneously implemented.

[0016] In the present disclosure, a higher layer parameter may be a parameter which is configured, pre-configured or pre-defined for a UE. For example, a base station or a network may transmit the higher layer parameter to the UE. For example, the higher layer parameter may be transmitted through radio resource control (RRC) signaling or medium access control (MAC) signaling.

[0017] The technology described below may be used in various wireless communication systems such as code division multiple access (CDMA), frequency division multiple access (FDMA), time division multiple access (TDMA), orthogonal frequency division multiple access (OFDMA), single carrier frequency division multiple access (SC-FDMA), and so on. The CDMA may be implemented with a radio technology, such as universal terrestrial radio access (UTRA) or CDMA-2000. The TDMA may be implemented with a radio technology, such as global system for mobile communications (GSM)/general packet radio service (GPRS)/enhanced data rate for GSM evolution (EDGE). The OFDMA may be implemented with a radio technology, such as institute of electrical and electronics engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, evolved UTRA (E-UTRA), and so on. IEEE 802.16m is an evolved version of IEEE 802.16e and provides backward compatibility with a system based on the IEEE 802.16e. The UTRA is part of a universal mobile telecommunication system (UMTS). 3rd generation partnership project (3GPP) long term evolution (LTE) is part of an evolved UMTS (E-UMTS) using the E-UTRA. The 3GPP LTE uses the OFDMA in a downlink and uses the SC-FDMA in an uplink. LTE-advanced (LTE-A) is an evolution of the LTE.

[0018] 5G NR is a successive technology of LTE-A corresponding to a new Clean-slate type mobile communication system having the characteristics of high performance, low latency, high availability, and so on. 5G NR may use resources of all spectrum available for usage including low frequency bands of less than 1GHz, middle frequency bands ranging from 1GHz to 10GHz, high frequency (millimeter waves) of 24GHz or more, and so on.

[0019] A 6G (wireless communication) system has purposes such as (i) very high data rate per device, (ii) a very large number of connected devices, (iii) global connectivity, (iv) very low latency, (v) decrease in energy consumption of battery-free IoT devices, (vi) ultra-reliable connectivity, and (vii) connected intelligence with machine learning capacity. The vision of the 6G system may include four aspects such as intelligent connectivity, deep connectivity, holographic connectivity and ubiquitous connectivity, and the 6G system may satisfy the requirements shown in Table 1 below. That is, Table 1 shows the requirements of the 6G system.

[Table 1]

Per device peak data rate	1 Tbps
E2E latency	1 ms
Maximum spectral efficiency	100bps/Hz
Mobility support	Up to 1000km/hr
Satellite integration	Fully
AI	Fully
Autonomous vehicle	Fully
XR	Fully
Haptic Communication	Fully

[0020] The 6G system may have key factors such as enhanced mobile broadband (eMBB), ultra-reliable low latency communications (URLLC), massive machine type communications (mMTC), AI integrated communication, tactile internet, high throughput, high network capacity, high energy efficiency, low backhaul and access network congestion, and enhanced data security.

[0021] FIG. 1 shows a communication structure providable in a 6G system, based on an embodiment of the present disclosure. The embodiment of FIG. 1 may be combined with various embodiments of the present disclosure.

[0022] The 6G system will have 50 times higher simultaneous wireless communication connectivity than a 5G wireless communication system. URLLC, which is the key feature of 5G, will become more important technology by providing end-to-end latency less than 1 ms in 6G communication. The 6G system may have much better volumetric spectrum efficiency unlike frequently used domain spectrum efficiency. The 6G system may provide advanced battery technology for energy harvesting and very long battery life and thus mobile devices may not need to be separately charged in the 6G system. In 6G, new network characteristics may be as follows.

- Satellites integrated network: To provide a global mobile group, 6G will be integrated with satellite. Integrating terrestrial waves, satellites and public networks as one wireless communication system may be very important for 6G.
- Connected intelligence: Unlike the wireless communication systems of previous generations, 6G is innovative and wireless evolution may be updated from "connected things" to "connected intelligence". AI may be applied in each step (or each signal processing procedure which will be described below) of a communication procedure.
- Seamless integration of wireless information and energy transfer: A 6G wireless network may transfer power in order to charge the batteries of devices such as smartphones and sensors. Therefore, wireless information and energy transfer (WIET) will be integrated.
- Ubiquitous super 3-dimension connectivity: Access to networks and core network functions of drones and very low earth orbit satellites will establish super 3D connection in 6G ubiquitous.

[0023] In the new network characteristics of 6G, several general requirements may be as follows.

- Small cell networks: The idea of a small cell network was introduced in order to improve received signal quality as a result of throughput, energy efficiency and spectrum efficiency improvement in a cellular system. As a result, the small cell network is an essential feature for 5G and beyond 5G (5 GB) communication systems. Accordingly, the 6G communication system also employs the characteristics of the small cell network.
- Ultra-dense heterogeneous network: Ultra-dense heterogeneous networks will be another important characteristic of the 6G communication system. A multi-tier network composed of heterogeneous networks improves overall QoS and reduces costs.
- High-capacity backhaul: Backhaul connection is characterized by a high-capacity backhaul network in order to support high-capacity traffic. A high-speed optical fiber and free space optical (FSO) system may be a possible solution for this problem.
- Radar technology integrated with mobile technology: High-precision localization (or location-based service) through communication is one of the functions of the 6G wireless communication system. Accordingly, the radar system will be integrated with the 6G network.
- Softwarization and virtualization: Softwarization and virtualization are two important functions which are the bases of a design process in a 5 GB network in order to ensure flexibility, reconfigurability and programmability.

[0024] Core implementation technology of 6G system is described below.

- Artificial Intelligence (AI): Technology which is most important in the 6G system and will be newly introduced is AI. AI was not involved in the 4G system. A 5G system will support partial or very limited AI. However, the 6G system will support AI for full automation. Advance in machine learning will create a more intelligent network for real-time communication in 6G. When AI is introduced to communication, real-time data transmission may be simplified and improved. AI may determine a method of performing complicated target tasks using countless analysis. That is, AI may increase efficiency and reduce processing delay. Operation consuming time such as handover, network selection, and resource scheduling immediately performed by using AI. AI may also play an important role in M2M, machine-to-human, and human-to-machine. In addition, AI may be a prompt communication in brain computer interface (BCI). An AI based communication system may be supported by metamaterial, intelligence structure, intelligence network, intelligence device, intelligence cognitive radio, self-maintaining wireless network, and machine learning.
- Terahertz (THz) communication: A data rate may increase by increasing bandwidth. This may be performed by using sub-TH communication with wide bandwidth and applying advanced massive MIMO technology. THz waves which are known as sub-millimeter radiation, generally indicates a frequency band between 0.1 THz and 10 THz with a corresponding wavelength in a range of 0.03 mm to 3 mm. A band range of 100 GHz to 300 GHz (sub THz band) is regarded as a main part of the THz band for cellular communication. When the sub-THz band is added to the mmWave band, the 6G cellular communication capacity increases. 300 GHz to 3 THz of the defined THz band is in a far infrared (IR) frequency band. A band of 300 GHz to 3 THz is a part of an optical band but is at the border of the optical band and is just behind an RF band. Accordingly, the band of 300 GHz to 3 THz has similarity with RF. FIG. 2 shows an electromagnetic spectrum, based on an embodiment of the present disclosure. The embodiment of FIG. 2 may be

combined with various embodiments of the present disclosure. The main characteristics of THz communication include (i) bandwidth widely available to support a very high data rate and (ii) high path loss occurring at a high frequency (a high directional antenna is indispensable). A narrow beam width generated in the high directional antenna reduces interference. The small wavelength of a THz signal allows a larger number of antenna elements to be integrated with a device and BS operating in this band. Therefore, an advanced adaptive arrangement technology capable of overcoming a range limitation may be used.

- Massive MIMO technology (large-scale MIMO)
- Hologram beamforming (HBF)
- Optical wireless technology
- Free space optical backhaul network (FSO Backhaul Network)
- Non-terrestrial networks (NTN)
- Quantum communication
- Cell-free communication
- Integration of wireless information and power transmission
- Integration of wireless communication and sensing
- Integrated access and backhaul network
- Big data analysis
- Reconfigurable intelligent surface
- Metaverse
- Block-chain
- Unmanned aerial vehicle (UAV): An unmanned aerial vehicle (UAV) or drone will be an important factor in 6G wireless communication. In most cases, a high-speed data wireless connection is provided using UAV technology. A base station entity is installed in the UAV to provide cellular connectivity. UAVs have certain features, which are not found in fixed base station infrastructures, such as easy deployment, strong line-of-sight links, and mobility-controlled degrees of freedom. During emergencies such as natural disasters, the deployment of terrestrial telecommunications infrastructure is not economically feasible and sometimes services cannot be provided in volatile environments. The UAV can easily handle this situation. The UAV will be a new paradigm in the field of wireless communications. This technology facilitates the three basic requirements of wireless networks, such as eMBB, URLLC and mMTC. The UAV can also serve a number of purposes, such as network connectivity improvement, fire detection, disaster emergency services, security and surveillance, pollution monitoring, parking monitoring, and accident monitoring. Therefore, UAV technology is recognized as one of the most important technologies for 6G communication.
- Autonomous driving (self-driving): For perfect autonomous driving, it is necessary to notify dangerous situation of each other through communication between vehicle and vehicle, to check information like parking information location and signal change time through communication between vehicle and infrastructure such as parking lots and/or traffic lights. Vehicle to everything (V2X) that is a core element for establishing an autonomous driving infrastructure is a technology that vehicle communicates and shares with various elements in road for autonomous driving such as vehicle to vehicle (V2V), vehicle to infrastructure (V2I). To maximize a performance of autonomous driving and to secure high safety, high transmission speed and low latency technology have to be needed. Furthermore, to directly control vehicle in dangerous situation and to actively intervene vehicle driving beyond a level of a warning or a guidance message to driver, as the amount of the information to transmit and receive is larger, autonomous driving is expected to be maximized in 6G being higher transmission speed and lower latency than 5G.

[0025] For clarity in the description, 5G NR is mainly described, but the technical idea according to an embodiment of the present disclosure is not limited thereto. Various embodiments of the present disclosure can also be applied to 6G communication systems.

[0026] FIG. 3 shows a structure of an NR system, based on an embodiment of the present disclosure. The embodiment of FIG. 3 may be combined with various embodiments of the present disclosure.

[0027] Referring to FIG. 3, a next generation-radio access network (NG-RAN) may include a BS 20 providing a UE 10 with a user plane and control plane protocol termination. For example, the BS 20 may include a next generation-Node B (gNB) and/or an evolved-NodeB (eNB). For example, the UE 10 may be fixed or mobile and may be referred to as other terms, such as a mobile station (MS), a user terminal (UT), a subscriber station (SS), a mobile terminal (MT), wireless device, and so on. For example, the BS may be referred to as a fixed station which communicates with the UE 10 and may be referred to as other terms, such as a base transceiver system (BTS), an access point (AP), and so on.

[0028] The embodiment of FIG. 3 exemplifies a case where only the gNB is included. The BSs 20 may be connected to one another via Xn interface. The BS 20 may be connected to one another via 5th generation (5G) core network (5GC) and NG interface. More specifically, the BSs 20 may be connected to an access and mobility management function (AMF) 30 via NG-C interface, and may be connected to a user plane function (UPF) 30 via NG-U interface.

[0029] Layers of a radio interface protocol between the UE and the network can be classified into a first layer (layer 1, L1),

a second layer (layer 2, L2), and a third layer (layer 3, L3) based on the lower three layers of the open system interconnection (OSI) model that is well-known in the communication system. Among them, a physical (PHY) layer belonging to the first layer provides an information transfer service by using a physical channel, and a radio resource control (RRC) layer belonging to the third layer serves to control a radio resource between the UE and the network. For this,

[0030] FIG. 4 shows a radio protocol architecture, based on an embodiment of the present disclosure. The embodiment of FIG. 4 may be combined with various embodiments of the present disclosure. Specifically, (a) of FIG. 4 shows a radio protocol stack of a user plane for Uu communication, and (b) of FIG. 4 shows a radio protocol stack of a control plane for Uu communication, (c) of FIG. 4 shows a radio protocol stack of a user plane for SL communication, and (d) of FIG. 4 shows a radio protocol stack of a control plane for SL communication.

[0031] Referring to FIG. 4, a physical layer provides an upper layer with an information transfer service through a physical channel. The physical layer is connected to a medium access control (MAC) layer which is an upper layer of the physical layer through a transport channel. Data is transferred between the MAC layer and the physical layer through the transport channel. The transport channel is classified according to how and with what characteristics data is transmitted through a radio interface.

[0032] Between different physical layers, i.e., a physical layer of a transmitter and a physical layer of a receiver, data are transferred through the physical channel. The physical channel is modulated using an orthogonal frequency division multiplexing (OFDM) scheme, and utilizes time and frequency as a radio resource.

[0033] The MAC layer provides services to a radio link control (RLC) layer, which is a higher layer of the MAC layer, via a logical channel. The MAC layer provides a function of mapping multiple logical channels to multiple transport channels. The MAC layer also provides a function of logical channel multiplexing by mapping multiple logical channels to a single transport channel. The MAC layer provides data transfer services over logical channels.

[0034] The RLC layer performs concatenation, segmentation, and reassembly of Radio Link Control Service Data Unit (RLC SDU). In order to ensure diverse quality of service (QoS) required by a radio bearer (RB), the RLC layer provides three types of operation modes, i.e., a transparent mode (TM), an unacknowledged mode (UM), and an acknowledged mode (AM). An AM RLC provides error correction through an automatic repeat request (ARQ).

[0035] A radio resource control (RRC) layer is defined only in the control plane. The RRC layer serves to control the logical channel, the transport channel, and the physical channel in association with configuration, reconfiguration and release of RBs. The RB is a logical path provided by the first layer (i.e., the physical layer or the PHY layer) and the second layer (i.e., a MAC layer, an RLC layer, a packet data convergence protocol (PDCP) layer, and a service data adaptation protocol (SDAP) layer) for data delivery between the UE and the network.

[0036] Functions of a packet data convergence protocol (PDCP) layer in the user plane include user data delivery, header compression, and ciphering. Functions of a PDCP layer in the control plane include control-plane data delivery and ciphering/integrity protection.

[0037] A service data adaptation protocol (SDAP) layer is defined only in a user plane. The SDAP layer performs mapping between a Quality of Service (QoS) flow and a data radio bearer (DRB) and QoS flow ID (QFI) marking in both DL and UL packets.

[0038] The configuration of the RB implies a process for specifying a radio protocol layer and channel properties to provide a particular service and for determining respective detailed parameters and operations. The RB can be classified into two types, i.e., a signaling RB (SRB) and a data RB (DRB). The SRB is used as a path for transmitting an RRC message in the control plane. The DRB is used as a path for transmitting user data in the user plane.

[0039] When an RRC connection is established between an RRC layer of the UE and an RRC layer of the E-UTRAN, the UE is in an RRC_CONNECTED state, and, otherwise, the UE may be in an RRC_IDLE state. In case of the NR, an RRC_INACTIVE state is additionally defined, and a UE being in the RRC_INACTIVE state may maintain its connection with a core network whereas its connection with the BS is released.

[0040] Data is transmitted from the network to the UE through a downlink transport channel. Examples of the downlink transport channel include a broadcast channel (BCH) for transmitting system information and a downlink-shared channel (SCH) for transmitting user traffic or control messages. Traffic of downlink multicast or broadcast services or the control messages can be transmitted on the downlink-SCH or an additional downlink multicast channel (MCH). Data is transmitted from the UE to the network through an uplink transport channel. Examples of the uplink transport channel include a random access channel (RACH) for transmitting an initial control message and an uplink SCH for transmitting user traffic or control messages.

[0041] Examples of logical channels belonging to a higher channel of the transport channel and mapped onto the transport channels include a broadcast channel (BCCH), a paging control channel (PCCH), a common control channel (CCCH), a multicast control channel (MCCH), a multicast traffic channel (MTCH), etc.

[0042] FIG. 5 shows a structure of a radio frame of an NR, based on an embodiment of the present disclosure. The embodiment of FIG. 5 may be combined with various embodiments of the present disclosure.

[0043] Referring to FIG. 5, in the NR, a radio frame may be used for performing uplink and downlink transmission. A radio

frame has a length of 10ms and may be defined to be configured of two half-frames (HFs). A half-frame may include five 1ms subframes (SFs). A subframe (SF) may be divided into one or more slots, and the number of slots within a subframe may be determined based on subcarrier spacing (SCS). Each slot may include 12 or 14 OFDM(A) symbols according to a cyclic prefix (CP).

[0044] In case of using a normal CP, each slot may include 14 symbols. In case of using an extended CP, each slot may include 12 symbols. Herein, a symbol may include an OFDM symbol (or CP-OFDM symbol) and a Single Carrier-FDMA (SC-FDMA) symbol (or Discrete Fourier Transform-spread-OFDM (DFT-s-OFDM) symbol).

[0045] Table 2 shown below represents an example of a number of symbols per slot ($N_{\text{slot, symb}}^{\text{slot}}$), a number slots per frame ($N_{\text{frame, u}}^{\text{frame, u}}$), and a number of slots per subframe ($N_{\text{subframe, u}}^{\text{subframe, u}}$) based on an SCS configuration (u), in a case where a normal CP or an extended CP is used.

[Table 2]

CP type	SCS ($15 \cdot 2^u$)	$N_{\text{slot, symb}}^{\text{slot}}$	$N_{\text{frame, u}}^{\text{frame, u}}$	$N_{\text{subframe, u}}^{\text{subframe, u}}$
normal CP	15kHz (u=0)	14	10	1
	30kHz (u=1)	14	20	2
	60kHz (u=2)	14	40	4
	120kHz (u=3)	14	80	8
	240kHz (u=4)	14	160	16
extended CP	60kHz (u=2)	12	40	4

[0046] In an NR system, OFDM(A) numerologies (e.g., SCS, CP length, and so on) between multiple cells being integrate to one UE may be differently configured. Accordingly, a (absolute time) duration (or section) of a time resource (e.g., subframe, slot or TTI) (collectively referred to as a time unit (TU) for simplicity) being configured of the same number of symbols may be differently configured in the integrated cells.

[0047] In the NR, multiple numerologies or SCSs for supporting diverse 5G services may be supported. For example, in case an SCS is 15kHz, a wide area of the conventional cellular bands may be supported, and, in case an SCS is 30kHz/60kHz a dense-urban, lower latency, wider carrier bandwidth may be supported. In case the SCS is 60kHz or higher, a bandwidth that is greater than 24.25GHz may be used in order to overcome phase noise.

[0048] An NR frequency band may be defined as two different types of frequency ranges. The two different types of frequency ranges may be FR1 and FR2. The values of the frequency ranges may be changed (or varied), and, for example, the two different types of frequency ranges may be as shown below in Table 3. Among the frequency ranges that are used in an NR system, FR1 may mean a "sub 6GHz range", and FR2 may mean an "above 6GHz range" and may also be referred to as a millimeter wave (mmW).

[Table 3]

Frequency Range designation	Corresponding frequency range	Subcarrier Spacing (SCS)
FR1	450MHz - 6000MHz	15, 30, 60kHz
FR2	24250MHz - 52600MHz	60, 120, 240kHz

[0049] As described above, the values of the frequency ranges in the NR system may be changed (or varied). For example, as shown below in Table 4, FR1 may include a band within a range of 410MHz to 7125MHz. More specifically, FR1 may include a frequency band of 6GHz (or 5850, 5900, 5925 MHz, and so on) and higher. For example, a frequency band of 6GHz (or 5850, 5900, 5925 MHz, and so on) and higher being included in FR1 may include an unlicensed band. The unlicensed band may be used for diverse purposes, e.g., the unlicensed band for vehicle-specific communication (e.g., automated driving).

[Table 4]

Frequency Range designation	Corresponding frequency range	Subcarrier Spacing (SCS)
FR1	410MHz - 7125MHz	15, 30, 60kHz
FR2	24250MHz - 52600MHz	60, 120, 240kHz

[0050] FIG. 6 shows a structure of a slot of an NR frame, based on an embodiment of the present disclosure. The embodiment of FIG. 6 may be combined with various embodiments of the present disclosure.

[0051] Referring to FIG. 6, a slot includes a plurality of symbols in a time domain. For example, in case of a normal CP, one slot may include 14 symbols. However, in case of an extended CP, one slot may include 12 symbols. Alternatively, in case of a normal CP, one slot may include 7 symbols. However, in case of an extended CP, one slot may include 6 symbols.

[0052] A carrier includes a plurality of subcarriers in a frequency domain. A Resource Block (RB) may be defined as a plurality of consecutive subcarriers (e.g., 12 subcarriers) in the frequency domain. A Bandwidth Part (BWP) may be defined as a plurality of consecutive (Physical) Resource Blocks ((P)RBs) in the frequency domain, and the BWP may correspond to one numerology (e.g., SCS, CP length, and so on). A carrier may include a maximum of N number BWPs (e.g., 5 BWPs). Data communication may be performed via an activated BWP. Each element may be referred to as a Resource Element (RE) within a resource grid and one complex symbol may be mapped to each element.

[0053] Hereinafter, a bandwidth part (BWP) and a carrier will be described.

[0054] The BWP may be a set of consecutive physical resource blocks (PRBs) in a given numerology. The PRB may be selected from consecutive sub-sets of common resource blocks (CRBs) for the given numerology on a given carrier

[0055] For example, the BWP may be at least any one of an active BWP, an initial BWP, and/or a default BWP. For example, the UE may not monitor downlink radio link quality in a DL BWP other than an active DL BWP on a primary cell (PCell). For example, the UE may not receive PDCCH, physical downlink shared channel (PDSCH), or channel state information - reference signal (CSI-RS) (excluding RRM) outside the active DL BWP. For example, the UE may not trigger a channel state information (CSI) report for the inactive DL BWP. For example, the UE may not transmit physical uplink control channel (PUCCH) or physical uplink shared channel (PUSCH) outside an active UL BWP. For example, in a downlink case, the initial BWP may be given as a consecutive RB set for a remaining minimum system information (RMSI) control resource set (CORESET) (configured by physical broadcast channel (PBCH)). For example, in an uplink case, the initial BWP may be given by system information block (SIB) for a random access procedure. For example, the default BWP may be configured by a higher layer. For example, an initial value of the default BWP may be an initial DL BWP. For energy saving, if the UE fails to detect downlink control information (DCI) during a specific period, the UE may switch the active BWP of the UE to the default BWP.

[0056] Meanwhile, the BWP may be defined for SL. The same SL BWP may be used in transmission and reception. For example, a transmitting UE may transmit a SL channel or a SL signal on a specific BWP, and a receiving UE may receive the SL channel or the SL signal on the specific BWP. In a licensed carrier, the SL BWP may be defined separately from a Uu BWP, and the SL BWP may have configuration signaling separate from the Uu BWP. For example, the UE may receive a configuration for the SL BWP from the BS/network. For example, the UE may receive a configuration for the Uu BWP from the BS/network. The SL BWP may be (pre-)configured in a carrier with respect to an out-of-coverage NR V2X UE and an RRC_IDLE UE. For the UE in the RRC_CONNECTED mode, at least one SL BWP may be activated in the carrier.

[0057] FIG. 7 shows an example of a BWP, based on an embodiment of the present disclosure. The embodiment of FIG. 7 may be combined with various embodiments of the present disclosure. It is assumed in the embodiment of FIG. 7 that the number of BWPs is 3.

[0058] Referring to FIG. 7, a common resource block (CRB) may be a carrier resource block numbered from one end of a carrier band to the other end thereof. In addition, the PRB may be a resource block numbered within each BWP. A point A may indicate a common reference point for a resource block grid.

[0059] The BWP may be configured by a point A, an offset $N_{\text{start}}^{\text{BWP}}$ from the point A, and a bandwidth $N_{\text{size}}^{\text{BWP}}$. For example, the point A may be an external reference point of a PRB of a carrier in which a subcarrier 0 of all numerologies (e.g., all numerologies supported by a network on that carrier) is aligned. For example, the offset may be a PRB interval between a lowest subcarrier and the point A in a given numerology. For example, the bandwidth may be the number of PRBs in the given numerology.

[0060] Hereinafter, V2X or SL communication will be described.

[0061] A sidelink synchronization signal (SLSS) may include a primary sidelink synchronization signal (PSSS) and a secondary sidelink synchronization signal (SSSS), as a SL-specific sequence. The PSSS may be referred to as a sidelink primary synchronization signal (S-PSS), and the SSSS may be referred to as a sidelink secondary synchronization signal (S-SSS). For example, length-127 M-sequences may be used for the S-PSS, and length-127 gold sequences may be used for the S-SSS. For example, a UE may use the S-PSS for initial signal detection and for synchronization acquisition. For example, the UE may use the S-PSS and the S-SSS for acquisition of detailed synchronization and for detection of a synchronization signal ID.

[0062] A physical sidelink broadcast channel (PSBCH) may be a (broadcast) channel for transmitting default (system) information which must be first known by the UE before SL signal transmission/reception. For example, the default information may be information related to SLSS, a duplex mode (DM), a time division duplex (TDD) uplink/downlink (UL/DL) configuration, information related to a resource pool, a type of an application related to the SLSS, a subframe offset, broadcast information, or the like. For example, for evaluation of PSBCH performance, in NR V2X, a payload size of the PSBCH may be 56 bits including 24-bit cyclic redundancy check (CRC).

[0063] The S-PSS, the S-SSS, and the PSBCH may be included in a block format (e.g., SL synchronization signal (SS)/PSBCH block, hereinafter, sidelink-synchronization signal block (S-SSB)) supporting periodical transmission. The S-SSB may have the same numerology (i.e., SCS and CP length) as a physical sidelink control channel (PSCCH)/physical sidelink shared channel (PSSCH) in a carrier, and a transmission bandwidth may exist within a (pre-)configured sidelink (SL) BWP. For example, the S-SSB may have a bandwidth of 11 resource blocks (RBs). For example, the PSBCH may exist across 11 RBs. In addition, a frequency position of the S-SSB may be (pre-)configured. Accordingly, the UE does not have to perform hypothesis detection at frequency to discover the S-SSB in the carrier.

[0064] FIG. 8 shows a procedure of performing V2X or SL communication by a UE based on a transmission mode, based on an embodiment of the present disclosure. The embodiment of FIG. 8 may be combined with various embodiments of the present disclosure. In various embodiments of the present disclosure, the transmission mode may be called a mode or a resource allocation mode. Hereinafter, for convenience of explanation, in LTE, the transmission mode may be called an LTE transmission mode. In NR, the transmission mode may be called an NR resource allocation mode.

[0065] For example, (a) of FIG. 8 shows a UE operation related to an LTE transmission mode 1 or an LTE transmission mode 3. Alternatively, for example, (a) of FIG. 8 shows a UE operation related to an NR resource allocation mode 1. For example, the LTE transmission mode 1 may be applied to general SL communication, and the LTE transmission mode 3 may be applied to V2X communication.

[0066] For example, (b) of FIG. 8 shows a UE operation related to an LTE transmission mode 2 or an LTE transmission mode 4. Alternatively, for example, (b) of FIG. 8 shows a UE operation related to an NR resource allocation mode 2.

[0067] Referring to (a) of FIG. 8, in the LTE transmission mode 1, the LTE transmission mode 3, or the NR resource allocation mode 1, a base station may schedule SL resource(s) to be used by a UE for SL transmission. For example, in step S800, a base station may transmit information related to SL resource(s) and/or information related to UL resource(s) to a first UE. For example, the UL resource(s) may include PUCCH resource(s) and/or PUSCH resource(s). For example, the UL resource(s) may be resource(s) for reporting SL HARQ feedback to the base station.

[0068] For example, the first UE may receive information related to dynamic grant (DG) resource(s) and/or information related to configured grant (CG) resource(s) from the base station. For example, the CG resource(s) may include CG type 1 resource(s) or CG type 2 resource(s). In the present disclosure, the DG resource(s) may be resource(s) configured/allocated by the base station to the first UE through a downlink control information (DCI). In the present disclosure, the CG resource(s) may be (periodic) resource(s) configured/allocated by the base station to the first UE through a DCI and/or an RRC message. For example, in the case of the CG type 1 resource(s), the base station may transmit an RRC message including information related to CG resource(s) to the first UE. For example, in the case of the CG type 2 resource(s), the base station may transmit an RRC message including information related to CG resource(s) to the first UE, and the base station may transmit a DCI related to activation or release of the CG resource(s) to the first UE.

[0069] In step S810, the first UE may transmit a PSCCH (e.g., sidelink control information (SCI) or 1st-stage SCI) to a second UE based on the resource scheduling. In step S820, the first UE may transmit a PSSCH (e.g., 2nd-stage SCI, MAC PDU, data, etc.) related to the PSCCH to the second UE. In step S830, the first UE may receive a PSFCH related to the PSCCH/PSSCH from the second UE. For example, HARQ feedback information (e.g., NACK information or ACK information) may be received from the second UE through the PSFCH. In step S840, the first UE may transmit/report HARQ feedback information to the base station through the PUCCH or the PUSCH. For example, the HARQ feedback information reported to the base station may be information generated by the first UE based on the HARQ feedback information received from the second UE. For example, the HARQ feedback information reported to the base station may be information generated by the first UE based on a pre-configured rule. For example, the DCI may be a DCI for SL scheduling. For example, a format of the DCI may be a DCI format 3_0 or a DCI format 3_1.

[0070] Hereinafter, an example of DCI format 3_0 will be described.

[0071] DCI format 3_0 is used for scheduling of NR PSCCH and NR PSSCH in one cell.

[0072] The following information is transmitted by means of the DCI format 3_0 with CRC scrambled by SL-RNTI or SL-CS-RNTI:

- Resource pool index - ceiling ($\log_2 I$) bits, where I is the number of resource pools for transmission configured by the higher layer parameter sl-TxPoolScheduling.
- Time gap - 3 bits determined by higher layer parameter sl-DCI-ToSL-Trans
- HARQ process number - 4 bits
- New data indicator - 1 bit
- Lowest index of the subchannel allocation to the initial transmission - ceiling ($\log_2(N_{\text{subChannel}}^{\text{SL}})$) bits
- SCI format 1-A fields: frequency resource assignment, time resource assignment
- PSFCH-to-HARQ feedback timing indicator - ceiling ($\log_2 N_{\text{fb_timing}}$) bits, where $N_{\text{fb_timing}}$ is the number of entries in the higher layer parameter sl-PSFCH-ToPUCCH.
- PUCCH resource indicator - 3 bits
- Configuration index - 0 bit if the UE is not configured to monitor DCI format 3_0 with CRC scrambled by SL-CS-RNTI;

otherwise 3 bits. If the UE is configured to monitor DCI format 3_0 with CRC scrambled by SL-CS-RNTI, this field is reserved for DCI format 3_0 with CRC scrambled by SL-RNTI.

- Counter sidelink assignment index - 2 bits, 2 bits if the UE is configured with pdsch-HARQ-ACK-Codebook = dynamic, 2 bits if the UE is configured with pdsch-HARQ-ACK-Codebook = semi-static
- Padding bits, if required

[0073] Referring to (b) of FIG. 8, in the LTE transmission mode 2, the LTE transmission mode 4, or the NR resource allocation mode 2, a UE may determine SL transmission resource(s) within SL resource(s) configured by a base station/network or pre-configured SL resource(s). For example, the configured SL resource(s) or the pre-configured SL resource(s) may be a resource pool. For example, the UE may autonomously select or schedule resource(s) for SL transmission. For example, the UE may perform SL communication by autonomously selecting resource(s) within the configured resource pool. For example, the UE may autonomously select resource(s) within a selection window by performing a sensing procedure and a resource (re)selection procedure. For example, the sensing may be performed in a unit of subchannel(s). For example, in step S810, a first UE which has selected resource(s) from a resource pool by itself may transmit a PSCCH (e.g., sidelink control information (SCI) or 1st-stage SCI) to a second UE by using the resource(s). In step S820, the first UE may transmit a PSSCH (e.g., 2nd-stage SCI, MAC PDU, data, etc.) related to the PSCCH to the second UE. In step S830, the first UE may receive a PSFCH related to the PSCCH/PSSCH from the second UE.

[0074] Referring to (a) or (b) of FIG. 8, for example, the first UE may transmit a SCI to the second UE through the PSCCH. Alternatively, for example, the first UE may transmit two consecutive SCIs (e.g., 2-stage SCI) to the second UE through the PSCCH and/or the PSSCH. In this case, the second UE may decode two consecutive SCIs (e.g., 2-stage SCI) to receive the PSSCH from the first UE. In the present disclosure, a SCI transmitted through a PSCCH may be referred to as a 1st SCI, a first SCI, a 1st-stage SCI or a 1st-stage SCI format, and a SCI transmitted through a PSSCH may be referred to as a 2nd SCI, a second SCI, a 2nd-stage SCI or a 2nd-stage SCI format. For example, the 1st-stage SCI format may include a SCI format 1-A, and the 2nd-stage SCI format may include a SCI format 2-A and/or a SCI format 2-B.

[0075] Hereinafter, an example of SCI format 1-A will be described.

[0076] SCI format 1-A is used for the scheduling of PSSCH and 2nd-stage-SCI on PSSCH.

[0077] The following information is transmitted by means of the SCI format 1-A:

- Priority - 3 bits
- Frequency resource assignment - ceiling ($\log_2(N_{\text{subChannel}}^{\text{SL}}(N_{\text{subChannel}}^{\text{SL}}+1)/2)$) bits when the value of the higher layer parameter sl-MaxNumPerReserve is configured to 2; otherwise ceiling $\log_2(N_{\text{subChannel}}^{\text{SL}}(N_{\text{subChannel}}^{\text{SL}}+1)(2N_{\text{subChannel}}^{\text{SL}}+1)/6)$ bits when the value of the higher layer parameter sl-MaxNumPerReserve is configured to 3
- Time resource assignment - 5 bits when the value of the higher layer parameter sl-MaxNumPerReserve is configured to 2; otherwise 9 bits when the value of the higher layer parameter sl-MaxNumPerReserve is configured to 3
- Resource reservation period - ceiling ($\log_2 N_{\text{rsv_period}}$) bits, where $N_{\text{rsv_period}}$ is the number of entries in the higher layer parameter sl-ResourceReservePeriodList, if higher layer parameter sl-MultiReserveResource is configured; 0 bit otherwise
- DMRS pattern - ceiling ($\log_2 N_{\text{pattern}}$) bits, where N_{pattern} is the number of DMRS patterns configured by higher layer parameter sl-PSSCH-DMRS-TimePatternList
- 2nd-stage SCI format - 2 bits as defined in Table 5
- Beta_offset indicator - 2 bits as provided by higher layer parameter sl-BetaOffsets2ndSCI
- Number of DMRS port - 1 bit as defined in Table 6
- Modulation and coding scheme - 5 bits
- Additional MCS table indicator - 1 bit if one MCS table is configured by higher layer parameter sl-Additional-MCS-Table; 2 bits if two MCS tables are configured by higher layer parameter sl-Additional-MCS-Table; 0 bit otherwise
- PSFCH overhead indication - 1 bit if higher layer parameter sl-PSFCH-Period = 2 or 4; 0 bit otherwise
- Reserved - a number of bits as determined by higher layer parameter sl-NumReservedBits, with value set to zero.

[Table 5]

Value of 2nd-stage SCI format field	2nd-stage SCI format
00	SCI format 2-A
01	SCI format 2-B
10	Reserved

(continued)

Value of 2nd-stage SCI format field	2nd-stage SCI format
11	Reserved

[Table 6]

Value of the Number of DMRS port field	Antenna ports
0	1000
1	1000 and 1001

[0078] Hereinafter, an example of SCI format 2-A will be described.

[0079] SCI format 2-A is used for the decoding of PSSCH, with HARQ operation when HARQ-ACK information includes ACK or NACK, when HARQ-ACK information includes only NACK, or when there is no feedback of HARQ-ACK information.

[0080] The following information is transmitted by means of the SCI format 2-A:

- HARQ process number - 4 bits
- New data indicator - 1 bit
- Redundancy version - 2 bits
- Source ID - 8 bits
- Destination ID - 16 bits
- HARQ feedback enabled/disabled indicator - 1 bit
- Cast type indicator - 2 bits as defined in Table 7
- CSI request - 1 bit

[Table 7]

Value of Cast type indicator	Cast type
00	Broadcast
01	Groupcast when HARQ-ACK information includes ACK or NACK
10	Unicast
11	Groupcast when HARQ-ACK information includes only NACK

[0081] Hereinafter, an example of SCI format 2-B will be described.

[0082] SCI format 2-B is used for the decoding of PSSCH, with HARQ operation when HARQ-ACK information includes only NACK, or when there is no feedback of HARQ-ACK information.

[0083] The following information is transmitted by means of the SCI format 2-B:

- HARQ process number - 4 bits
- New data indicator - 1 bit
- Redundancy version - 2 bits
- Source ID - 8 bits
- Destination ID - 16 bits
- HARQ feedback enabled/disabled indicator - 1 bit
- Zone ID - 12 bits
- Communication range requirement - 4 bits determined by higher layer parameter sl-ZoneConfigMCR-Index

[0084] Referring to (a) or (b) of FIG. 8, in step S830, the first UE may receive the PSFCH. For example, the first UE and the second UE may determine a PSFCH resource, and the second UE may transmit HARQ feedback to the first UE using the PSFCH resource.

[0085] Referring to (a) of FIG. 8, in step S840, the first UE may transmit SL HARQ feedback to the base station through the PUCCH and/or the PUSCH.

[0086] Hereinafter, a hybrid automatic repeat request (HARQ) procedure will be described.

[0087] For example, the SL HARQ feedback may be enabled for unicast. In this case, in a non-code block group (non-CBG) operation, if the receiving UE decodes a PSSCH of which a target is the receiving UE and if the receiving UE successfully decodes a transport block related to the PSSCH, the receiving UE may generate HARQ-ACK. In addition, the receiving UE may transmit the HARQ-ACK to the transmitting UE. Otherwise, if the receiving UE cannot successfully decode the transport block after decoding the PSSCH of which the target is the receiving UE, the receiving UE may generate the HARQ-NACK. In addition, the receiving UE may transmit HARQ-NACK to the transmitting UE.

[0088] For example, the SL HARQ feedback may be enabled for groupcast. For example, in the non-CBG operation, two HARQ feedback options may be supported for groupcast.

(1) Groupcast option 1: After the receiving UE decodes the PSSCH of which the target is the receiving UE, if the receiving UE fails in decoding of a transport block related to the PSSCH, the receiving UE may transmit HARQ-NACK to the transmitting UE through a PSFCH. Otherwise, if the receiving UE decodes the PSSCH of which the target is the receiving UE and if the receiving UE successfully decodes the transport block related to the PSSCH, the receiving UE may not transmit the HARQ-ACK to the transmitting UE.

(2) Groupcast option 2: After the receiving UE decodes the PSSCH of which the target is the receiving UE, if the receiving UE fails in decoding of the transport block related to the PSSCH, the receiving UE may transmit HARQ-NACK to the transmitting UE through the PSFCH. In addition, if the receiving UE decodes the PSSCH of which the target is the receiving UE and if the receiving UE successfully decodes the transport block related to the PSSCH, the receiving UE may transmit the HARQ-ACK to the transmitting UE through the PSFCH.

[0089] For example, if the groupcast option 1 is used in the SL HARQ feedback, all UEs performing groupcast communication may share a PSFCH resource. For example, UEs belonging to the same group may transmit HARQ feedback by using the same PSFCH resource.

[0090] For example, if the groupcast option 2 is used in the SL HARQ feedback, each UE performing groupcast communication may use a different PSFCH resource for HARQ feedback transmission. For example, UEs belonging to the same group may transmit HARQ feedback by using different PSFCH resources.

[0091] In the present disclosure, HARQ-ACK may be referred to as ACK, ACK information, or positive-ACK information, and HARQ-NACK may be referred to as NACK, NACK information, or negative-ACK information.

[0092] Hereinafter, UE procedure for reporting HARQ-ACK on sidelink will be described.

[0093] A UE can be indicated by an SCI format scheduling a PSSCH reception, in one or more sub-channels from a number of $N_{\text{PSSCH}}^{\text{subch}}$ sub-channels, to transmit a PSFCH with HARQ-ACK information in response to the PSSCH reception. The UE provides HARQ-ACK information that includes ACK or NACK, or only NACK.

[0094] A UE can be provided, by sl-PSFCH-Period-r16, a number of slots in a resource pool for a period of PSFCH transmission occasion resources. If the number is zero, PSFCH transmissions from the UE in the resource pool are disabled. A UE expects that a slot t_k^{SL} ($0 \leq k < T'_{\text{max}}$) has a PSFCH transmission occasion resource if $k \bmod N_{\text{PSFCH}}^{\text{PSSCH}} = 0$, where t_k^{SL} is a slot that belongs to the resource pool, T'_{max} is a number of slots that belong to the resource pool within 10240 msec, and $N_{\text{PSFCH}}^{\text{PSSCH}}$ is provided by sl-PSFCH-Period-r16. A UE may be indicated by higher layers to not transmit a PSFCH in response to a PSSCH reception. If a UE receives a PSSCH in a resource pool and the HARQ feedback enabled/disabled indicator field in an associated SCI format 2-A or a SCI format 2-B has value 1, the UE provides the HARQ-ACK information in a PSFCH transmission in the resource pool. The UE transmits the PSFCH in a first slot that includes PSFCH resources and is at least a number of slots, provided by sl-MinTimeGapPSFCH-r16, of the resource pool after a last slot of the PSSCH reception.

[0095] A UE is provided by sl-PSFCH-RB-Set-r16 a set of $M_{\text{PSFCH}}^{\text{PRB,set}}$ PRBs in a resource pool for PSFCH transmission in a PRB of the resource pool. For a number of N_{subch} sub-channels for the resource pool, provided by sl-NumSubchannel, and a number of PSSCH slots associated with a PSFCH slot that is less than or equal to $N_{\text{PSFCH}}^{\text{PSSCH}}$, the UE allocates the $[(i+j \cdot N_{\text{PSFCH}}^{\text{PSSCH}}) \cdot M_{\text{PSFCH}}^{\text{subch,slot}}, (i+1+j \cdot N_{\text{PSFCH}}^{\text{PSSCH}}) \cdot M_{\text{PSFCH}}^{\text{subch,slot}} - 1]$ PRBs from the $M_{\text{PRB,set}}^{\text{PSFCH}}$ PRBs to slot i among the PSSCH slots associated with the PSFCH slot and sub-channel j , where $M_{\text{PSFCH}}^{\text{subch,slot}} = M_{\text{PSFCH}}^{\text{PRB,set}} / (N_{\text{subch}} \cdot N_{\text{PSFCH}}^{\text{PSSCH}})$, $0 \leq i < N_{\text{PSFCH}}^{\text{PSSCH}}$, $0 \leq j \leq N_{\text{subch}}$, and the allocation starts in an ascending order of i and continues in an ascending order of j . The UE expects that $M_{\text{PSFCH}}^{\text{PRB,set}}$ is a multiple of $N_{\text{subch}} \cdot N_{\text{PSFCH}}^{\text{PSSCH}}$.

[0096] A UE determines a number of PSFCH resources available for multiplexing HARQ-ACK information in a PSFCH transmission as $R_{\text{PSFCH}}^{\text{PRB,CS}} = N_{\text{PSFCH}}^{\text{type}} \cdot M_{\text{PSFCH}}^{\text{subch,slot}} \cdot N_{\text{PSFCH}}^{\text{CS}}$ where $N_{\text{PSFCH}}^{\text{CS}}$ is a number of cyclic shift pairs for the resource pool and, based on an indication by higher layers,

- $N_{\text{PSFCH}}^{\text{type}} = 1$ and the $M_{\text{PSFCH}}^{\text{subch,slot}}$ PRBs are associated with the starting sub-channel of the corresponding PSSCH
- $N_{\text{PSFCH}}^{\text{type}} = N_{\text{PSSCH}}^{\text{subch}}$ and the $N_{\text{PSSCH}}^{\text{subch}} \cdot M_{\text{PSFCH}}^{\text{subch,slot}}$ PRBs are associated with one or more sub-

channels from the $N_{\text{subch}}^{\text{PSSCH}}$ sub-channels of the corresponding PSSCH

[0097] The PSFCH resources are first indexed according to an ascending order of the PRB index, from the $N_{\text{ty}}^{\text{PSFCH}}$ $\cdot M_{\text{subch,slot}}^{\text{PSFCH}}$ PRBs, and then according to an ascending order of the cyclic shift pair index from the $N_{\text{CS}}^{\text{PSFCH}}$ cyclic shift pairs.

[0098] A UE determines an index of a PSFCH resource for a PSFCH transmission in response to a PSSCH reception as $(P_{\text{ID}} + M_{\text{ID}}) \bmod R_{\text{PRB,CS}}^{\text{PSFCH}}$ where P_{ID} is a physical layer source ID provided by SCI format 2-A or 2-B scheduling the PSSCH reception, and M_{ID} is the identity of the UE receiving the PSSCH as indicated by higher layers if the UE detects a SCI format 2-A with Cast type indicator field value of "01"; otherwise, M_{ID} is zero.

[0099] A UE determines a m_0 value, for computing a value of cyclic shift α , from a cyclic shift pair index corresponding to a PSFCH resource index and from $N_{\text{CS}}^{\text{PSFCH}}$ using Table 8.

[Table 8]

$N_{\text{CS}}^{\text{PSFCH}}$	m_0					
	cyclic shift pair index 0	cyclic shift pair index 1	cyclic shift pair index 2	cyclic shift pair index 3	cyclic shift pair index 4	cyclic shift pair index 5
1	0	-	-	-	-	-
2	0	3	-	-	-	-
3	0	2	4	-	-	-
6	0	1	2	3	4	5

[0100] A UE determines a m_{CS} value, for computing a value of cyclic shift α , as in Table 9 if the UE detects a SCI format 2-A with Cast type indicator field value of "01" or "10", or as in Table 10 if the UE detects a SCI format 2-B or a SCI format 2-A with Cast type indicator field value of "11". The UE applies one cyclic shift from a cyclic shift pair to a sequence used for the PSFCH transmission.

[Table 9]

HARQ-ACK Value	0 (NACK)	1 (ACK)
Sequence cyclic shift	0	6

[Table 10]

HARQ-ACK Value	0 (NACK)	1 (ACK)
Sequence cyclic shift	0	N/A

[0101] Hereinafter, positioning will be described.

[0102] FIG. 9 shows an example of an architecture of a 5G system capable of positioning a UE having access to a next generation-radio access network (NG-RAN) or an E-UTRAN based on an embodiment of the present disclosure. The embodiment of FIG. 9 may be combined with various embodiments of the present disclosure.

[0103] Referring to FIG. 9, an AMF may receive a request for a location service related to a specific target UE from a different entity such as a gateway mobile location center (GMLC), or may determine to start the location service in the AMF itself instead of the specific target UE. Then, the AMF may transmit a location service request to a location management function (LMF). Upon receiving the location service request, the LMF may process the location service request and return a processing request including an estimated location or the like of the UE to the AMF. Meanwhile, if the location service request is received from the different entity such as GMLC other than the AMF, the AMF may transfer to the different entity the processing request received from the LMF.

[0104] A new generation evolved-NB (ng-eNB) and a gNB are network elements of NG-RAN capable of providing a measurement result for location estimation, and may measure a radio signal for a target UE and may transfer a resultant value to the LMF. In addition, the ng-eNB may control several transmission points (TPs) such as remote radio heads or PRS-dedicated TPs supporting a positioning reference signal (PRS)-based beacon system for E-UTRA.

[0105] The LMF may be connected to an enhanced serving mobile location centre (E-SMLC), and the E-SMLC may allow the LMF to access E-UTRAN. For example, the E-SMLC may allow the LMF to support observed time difference of arrival (OTDOA), which is one of positioning methods of E-UTRAN, by using downlink measurement obtained by a target

UE through a signal transmitted from the gNB and/or the PRS-dedicated TPs in the E-UTRAN.

[0106] Meanwhile, the LMF may be connected to an SUPL location platform (SLP). The LMF may support and manage different location determining services for respective target UEs. The LMF may interact with a serving ng-eNB or serving gNB for the target UE to obtain location measurement of the UE. For positioning of the target UE, the LMF may determine a positioning method based on a location service (LCS) client type, a requested quality of service (QoS), UE positioning capabilities, gNB positioning capabilities, and ng-eNB positioning capabilities, or the like, and may apply such a positioning method to the serving gNB and/or the serving ng-eNB. In addition, the LMF may determine additional information such as a location estimation value for the target UE and accuracy of location estimation and speed. The SLP is a secure user plane location (SUPL) entity in charge of positioning through a user plane.

[0107] The UE may measure a downlink signal through NG-RAN, E-UTRAN, and/or other sources such as different global navigation satellite system (GNSS) and terrestrial beacon system (TBS), wireless local access network (WLAN) access points, Bluetooth beacons, UE barometric pressure sensors or the like. The UE may include an LCS application. The UE may communicate with a network to which the UE has access, or may access the LCS application through another application included in the UE. The LCS application may include a measurement and calculation function required to determine a location of the UE. For example, the UE may include an independent positioning function such as a global positioning system (GPS), and may report the location of the UE independent of NG-RAN transmission. Positioning information obtained independently as such may be utilized as assistance information of the positioning information obtained from the network.

[0108] FIG. 10 shows an example of implementing a network for measuring a location of a UE based on an embodiment of the present disclosure. The embodiment of FIG. 10 may be combined with various embodiments of the present disclosure.

[0109] When the UE is in a connection management (CM)-IDLE state, if an AMF receives a location service request, the AMF may establish a signaling connection with the UE, and may request for a network trigger service to allocate a specific serving gNB or ng-eNB. Such an operational process is omitted in FIG. 10. That is, it may be assumed in FIG. 10 that the UE is in a connected mode. However, due to signaling and data inactivation or the like, the signaling connection may be released by NG-RAN while a positioning process is performed.

[0110] A network operation process for measuring a location of a UE will be described in detail with reference to FIG. 10. In step a1, a 5GC entity such as GMLC may request a serving AMF to provide a location service for measuring a location of a target UE. However, even if the GMLC does not request for the location service, based on step 1b, the serving AMF may determine that the location service for measuring the location of the target UE is required. For example, to measure the location of the UE for an emergency call, the serving AMF may determine to directly perform the location service.

[0111] Thereafter, the AMF may transmit the location service request to an LMF based on step 2, and the LMF may start location procedures to obtain location measurement data or location measurement assistance data together with a serving ng-eNB and a serving gNB. Additionally, based on step 3b, the LMF may start location procedures for downlink positioning together with the UE. For example, the LMF may transmit assistance data defined in 3GPP TS 36.355, or may obtain a location estimation value or a location measurement value. Meanwhile, step 3b may be performed additionally after step 3a is performed, or may be performed instead of step 3a.

[0112] In step 4, the LMF may provide a location service response to the AMF. In addition, the location service response may include information on whether location estimation of the UE is successful and a location estimation value of the UE. Thereafter, if the procedure of FIG. 10 is initiated by step a1, the AMF may transfer the location service response to a 5GC entity such as GMLC, and if the procedure of FIG. 10 is initiated by step 1b, the AMF may use the location service response to provide a location service related to an emergency call or the like.

[0113] FIG. 11 shows an example of a protocol layer used to support LTE positioning protocol (LPP) message transmission between an LMF and a UE based on an embodiment of the present disclosure. The embodiment of FIG. 11 may be combined with various embodiments of the present disclosure.

[0114] An LPP PDU may be transmitted through a NAS PDU between an AMF and the UE. Referring to FIG. 11, an LPP may be terminated between a target device (e.g., a UE in a control plane or an SUPL enabled terminal (SET) in a user plane) and a location server (e.g., an LMF in the control plane and an SLP in the user plane). The LPP message may be transferred in a form of a transparent PDU through an intermediary network interface by using a proper protocol such as an NG application protocol (NGAP) through an NG-control plane (NG-C) interface and NAS/RRC or the like through an NR-Uu interface. The LPP protocol may enable positioning for NR and LTE by using various positioning methods.

[0115] For example, based on the LPP protocol, the target device and the location server may exchange mutual capability information, assistance data for positioning, and/or location information. In addition, an LPP message may be used to indicate exchange of error information and/or interruption of the LPP procedure.

[0116] FIG. 12 shows an example of a protocol layer used to support NR positioning protocol A (NRPPa) PDU transmission between an LMF and an NG-RAN node based on an embodiment of the present disclosure. The embodiment of FIG. 12 may be combined with various embodiments of the present disclosure.

[0117] The NRPPa may be used for information exchange between the NG-RAN node and the LMF. Specifically, the

NRPPa may exchange an enhanced-cell ID (E-CID) for measurement, data for supporting an OTDOA positioning method, and a cell-ID, cell location ID, or the like for an NR cell ID positioning method, transmitted from the ng-eNB to the LMF. Even if there is no information on an associated NRPPa transaction, the AMF may route NRPPa PDUs based on a routing ID of an associated LMR through an NG-C interface.

[0118] A procedure of an NRPPa protocol for location and data collection may be classified into two types. A first type is a UE associated procedure for transferring information on a specific UE (e.g., location measurement information or the like), and a second type is a non UE associated procedure for transferring information (e.g., gNB/ng-eNB/TP timing information, etc.) applicable to an NG-RAN node and associated TPs. The two types of the procedure may be independently supported or may be simultaneously supported.

[0119] Meanwhile, examples of positioning methods supported in NG-RAN may include GNSS, OTDOA, enhanced cell ID (E-CID), barometric pressure sensor positioning, WLAN positioning, Bluetooth positioning and terrestrial beacon system (TBS), uplink time difference of arrival (UTDOA), etc.

(1) OTDOA (Observed Time Difference Of Arrival)

[0120] FIG. 13 is a drawing for explaining an OTDOA positioning method based on an embodiment of the present disclosure. The embodiment of FIG. 13 may be combined with various embodiments of the present disclosure.

[0121] The OTDOA positioning method uses measurement timing of downlink signals received by a UE from an eNB, an ng-eNB, and a plurality of TPs including a PRS-dedicated TP. The UE measures timing of downlink signals received by using location assistance data received from a location server. In addition, a location of the UE may be determined based on such a measurement result and geometric coordinates of neighboring TPs.

[0122] A UE connected to a gNB may request for a measurement gap for OTDOA measurement from the TP. If the UE cannot recognize a single frequency network (SFN) for at least one TP in the OTDOA assistance data, the UE may use an autonomous gap to obtain an SNF of an OTDOA reference cell before the measurement gap is requested to perform reference signal time difference (RSTD) measurement.

[0123] Herein, the RSTD may be defined based on a smallest relative time difference between boundaries of two subframes received respectively from a reference cell and a measurement cell. That is, the RSTD may be calculated based on a relative time difference between a start time of a subframe received from the measurement cell and a start time of a subframe of a reference cell closest to the start time of the subframe received from the measurement cell. Meanwhile, the reference cell may be selected by the UE.

[0124] For correct OTDOA measurement, it may be necessary to measure a time of arrival (TOA) of a signal received from three or more TPs or BSs geometrically distributed. For example, a TOA may be measured for each of a TP1, a TP2, and a TP3, and RSTD for TP 1-TP 2, RSTD for TP 2-TP 3, and RSTD for TP 3-TP 1 may be calculated for the three TOAs. Based on this, a geometric hyperbola may be determined, and a point at which these hyperbolas intersect may be estimated as a location of a UE. In this case, since accuracy and/or uncertainty for each TOA measurement may be present, the estimated location of the UE may be known as a specific range based on measurement uncertainty.

[0125] For example, RSTD for two TPs may be calculated based on Equation 1.

[Equation 1]

$$RSTD_{i,1} = \frac{\sqrt{(x_t - x_i)^2 + (y_t - y_i)^2}}{c} - \frac{\sqrt{(x_t - x_1)^2 + (y_t - y_1)^2}}{c} + (T_i - T_1) + (n_i - n_1)$$

[0126] Herein, c may be the speed of light, $\{x_t, y_t\}$ may be a (unknown) coordinate of a target UE, $\{x_i, y_i\}$ may be a coordinate of a (known) TP, and $\{x_1, y_1\}$ may be a coordinate of a reference TP (or another TP). Herein, $(T_i - T_1)$ may be referred to as "real time differences (RTDs)" as a transmission time offset between two TPs, and n_i, n_1 may represent values related to UE TOA measurement errors.

(2) E-CID (Enhanced Cell ID)

[0127] In a cell ID (CID) positioning method, a location of a UE may be measured through geometric information of a serving ng-eNB, serving gNB, and/or serving cell of the UE. For example, the geometric information of the serving ng-eNB, serving gNB, and/or serving cell may be obtained through paging, registration, or the like.

[0128] Meanwhile, in addition to the CID positioning method, an E-CID positioning method may use additional UE measurement and/or NG-RAN radio resources or the like to improve a UE location estimation value. In the E-CID positioning method, although some of the measurement methods which are the same as those used in a measurement control system of an RRC protocol may be used, additional measurement is not performed in general only for location

measurement of the UE. In other words, a measurement configuration or a measurement control message may not be provided additionally to measure the location of the UE. Also, the UE may not expect that an additional measurement operation only for location measurement will be requested, and may report a measurement value obtained through measurement methods in which the UE can perform measurement in a general manner.

[0129] For example, the serving gNB may use an E-UTRA measurement value provided from the UE to implement the E-CID positioning method.

[0130] Examples of a measurement element that can be used for E-CID positioning may be as follows.

- UE measurement: E-UTRA reference signal received power (RSRP), E-UTRA reference signal received quality (RSRQ), UE E-UTRA Rx-Tx Time difference, GSM EDGE random access network (GERAN)/WLAN reference signal strength indication (RSSI), UTRAN common pilot channel (CPICH) received signal code power (RSCP), UTRAN CPICH Ec/Io
- E-UTRAN measurement: ng-eNB Rx-Tx Time difference, timing advance (TADV), angle of arrival (AoA)

[0131] Herein, the TADV may be classified into Type 1 and Type 2 as follows.

[0132]

$$\text{TADV Type 1} = (\text{ng-eNB Rx-Tx time difference}) + (\text{UE E-UTRA Rx-Tx time difference})$$

[0133]

$$\text{TADV Type 2} = \text{ng-eNB Rx-Tx time difference}$$

[0134] Meanwhile, AoA may be used to measure a direction of the UE. The AoA may be defined as an estimation angle with respect to the location of the UE counterclockwise from a BS/TP. In this case, a geographic reference direction may be north. The BS/TP may use an uplink signal such as a sounding reference signal (SRS) and/or a demodulation reference signal (DMRS) for AoA measurement. In addition, the larger the arrangement of the antenna array, the higher the measurement accuracy of the AoA. When the antenna arrays are arranged with the same interval, signals received from adjacent antenna elements may have a constant phase-rotate.

(3) UTDOA (Uplink Time Difference of Arrival)

[0135] UTDOA is a method of determining a location of a UE by estimating an arrival time of SRS. When calculating an estimated SRS arrival time, the location of the UE may be estimated through an arrival time difference with respect to another cell (or BS/TP) by using a serving cell as a reference cell. In order to implement the UTDOA, E-SMLC may indicate a serving cell of a target UE to indicate SRS transmission to the target UE. In addition, the E-SMLC may provide a configuration such as whether the SRS is periodical/apperiodical, a bandwidth, frequency/group/sequence hopping, or the like.

[0136] Table 11 shows an example of reference signal time difference (RSTD). The RSTD in Table 11 may be applied for SL positioning.

[Table 11]

Definition	The relative timing difference between the E-UTRA neighbour cell j and the E-UTRA reference cell i, defined as $T_{\text{SubframeRxj}} - T_{\text{SubframeRxi}}$, where: $T_{\text{SubframeRxj}}$ is the time when the UE receives the start of one subframe from E-UTRA cell j, $T_{\text{SubframeRxi}}$ is the time when the UE receives the corresponding start of one subframe from E-UTRA cell i that is closest in time to the subframe received from E-UTRA cell j. The reference point for the observed subframe time difference shall be the antenna connector of the UE.
Applicable for	RRC_CONNECTED inter-RAT

[0137] Table 12 shows an example of DL PRS reference signal received power (RSRP). The DL PRS RSRP in Table 12 may be applied for SL positioning.

[Table 12]

Definition	DL PRS reference signal received power (DL PRS-RSRP), is defined as the linear average over the power contributions (in [W]) of the resource elements that carry DL PRS reference signals configured for RSRP measurements within the considered measurement frequency bandwidth. For frequency range 1, the reference point for the DL PRS-RSRP shall be the antenna connector of the UE. For frequency range 2, DL PRS-RSRP shall be measured based on the combined signal from antenna elements corresponding to a given receiver branch. For frequency range 1 and 2, if receiver diversity is in use by the UE, the reported DL PRS-RSRP value shall not be lower than the corresponding DL PRS-RSRP of any of the individual receiver branches.
Applicable for	RRC_CONNECTED intra-frequency, RRC_CONNECTED inter-frequency

[0138] Table 13 shows an example of DL relative signal time difference (RSTD). The DLRSTD in Table 13 may be applied for SL positioning.

[Table 13]

Definition	DL relative timing difference (DL RSTD) between the positioning node j and the reference positioning node i , is defined as $T_{\text{subframeRxj}} - T_{\text{SubframeRxi}}$. Where: $T_{\text{subframeRxj}}$ is the time when the UE receives the start of one subframe from positioning node j . $T_{\text{SubframeRxi}}$ is the time when the UE receives the corresponding start of one subframe from positioning node i that is closest in time to the subframe received from positioning node j . Multiple DL PRS resources can be used to determine the start of one subframe from a positioning node. For frequency range 1, the reference point for the DL RSTD shall be the antenna connector of the UE. For frequency range 2, the reference point for the DL RSTD shall be the antenna of the UE.
Applicable for	RRC_CONNECTED intra-frequency RRC_CONNECTED inter-frequency

[0139] Table 14 shows an example of UE Rx-Tx time difference. The UE Rx-Tx time difference in Table 14 may be applied for SL positioning.

[Table 14]

Definition	The UE Rx - Tx time difference is defined as $T_{\text{UE-RX}} - T_{\text{UE-TX}}$ Where: $T_{\text{UE-RX}}$ is the UE received timing of downlink subframe $\#i$ from a positioning node, defined by the first detected path in time. $T_{\text{UE-TX}}$ is the UE transmit timing of uplink subframe $\#j$ that is closest in time to the subframe $\#i$ received from the positioning node. Multiple DL PRS resources can be used to determine the start of one subframe of the first arrival path of the positioning node. For frequency range 1, the reference point for $T_{\text{UE-RX}}$ measurement shall be the Rx antenna connector of the UE and the reference point for $T_{\text{UE-TX}}$ measurement shall be the Tx antenna connector of the UE. For frequency range 2, the reference point for $T_{\text{UE-RX}}$ measurement shall be the Rx antenna of the UE and the reference point for $T_{\text{UE-TX}}$ measurement shall be the Tx antenna of the UE.
Applicable for	RRC_CONNECTED intra-frequency RRC_CONNECTED inter-frequency

[0140] Table 15 shows an example of UL Relative Time of Arrival (UL RTOA) ($T_{\text{UL-RTOA}}$). The UL RTOA in Table 15 may be applied for SL positioning.

[Table 15]

Definition	<p>[The UL Relative Time of Arrival ($T_{UL-RTOA}$) is the beginning of subframe i containing SRS received in positioning node j, relative to the configurable reference time.]</p> <p>Multiple SRS resources for positioning can be used to determine the beginning of one subframe containing SRS received at a positioning node.</p> <p>The reference point for $T_{UL-RTOA}$ shall be:</p> <ul style="list-style-type: none"> - for type 1-C base station TS 38.104 [9]: the Rx antenna connector, - for type 1-O or 2-O base station TS 38.104 [9]: the Rx antenna, - for type 1-H base station TS 38.104 [9]: the Rx Transceiver Array Boundary connector.
------------	---

[0141] Table 16 shows an example of gNB Rx-Tx time difference. The gNB Rx-Tx time difference in Table 16 may be applied for SL positioning.

[Table 16]

Definition	<p>The gNB Rx - Tx time difference is defined as $T_{gNB-RX} - T_{gNB-TX}$</p> <p>Where:</p> <p>T_{gNB-RX} is the positioning node received timing of uplink subframe $\#i$ containing SRS associated with UE, defined by the first detected path in time.</p> <p>T_{gNB-TX} is the positioning node transmit timing of downlink subframe $\#j$ that is closest in time to the subframe $\#i$ received from the UE.</p> <p>Multiple SRS resources for positioning can be used to determine the start of one subframe containing SRS.</p> <p>The reference point for T_{gNB-RX} shall be:</p> <ul style="list-style-type: none"> - for type 1-C base station TS 38.104 [9]: the Rx antenna connector, - for type 1-O or 2-O base station TS 38.104 [9]: the Rx antenna, - for type 1-H base station TS 38.104 [9]: the Rx Transceiver Array Boundary connector. <p>The reference point for T_{gNB-TX} shall be:</p> <ul style="list-style-type: none"> - for type 1-C base station TS 38.104 [9]: the Tx antenna connector, - for type 1-O or 2-O base station TS 38.104 [9]: the Tx antenna, - for type 1-H base station TS 38.104 [9]: the Tx Transceiver Array Boundary connector.
------------	--

[0142] Table 17 shows an example of UL Angle of Arrival (AoA). The UL AoA in Table 17 may be applied for SL positioning.

[Table 17]

Definition	<p>UL Angle of Arrival (UL AoA) is defined as the estimated azimuth angle and vertical angle of a UE with respect to a reference direction, wherein the reference direction is defined:</p> <ul style="list-style-type: none"> - In the global coordinate system (GCS), wherein estimated azimuth angle is measured relative to geographical North and is positive in a counter-clockwise direction and estimated vertical angle is measured relative to zenith and positive to horizontal direction - In the local coordinate system (LCS), wherein estimated azimuth angle is measured relative to x-axis of LCS and positive in a counter-clockwise direction and estimated vertical angle is measured relative to z-axis of LCS and positive to x-y plane direction. The bearing, downtilt and slant angles of LCS are defined according to TS 38.901 [14]. <p>The UL AoA is determined at the gNB antenna for an UL channel corresponding to this UE.</p>
------------	--

[0143] Table 18 shows an example of UL SRS reference signal received power (RSRP). The UL SRS RSRP in Table 18 may be applied for SL positioning.

[Table 18]

5	Definition	UL SRS reference signal received power (UL SRS-RSRP) is defined as linear average of the power contributions (in [W]) of the resource elements carrying sounding reference signals (SRS). UL SRS-RSRP shall be measured over the configured resource elements within the considered measurement frequency bandwidth in the configured measurement time occasions. For frequency range 1, the reference point for the UL SRS-RSRP shall be the antenna connector of the gNB. For frequency range 2, UL SRS-RSRP shall be measured based on the combined signal from antenna elements corresponding to a given receiver branch. For frequency range 1 and 2, if receiver diversity is in use by the gNB, the reported UL SRS-RSRP value shall not be lower than the corresponding UL SRS-RSRP of any of the individual receiver branches.
10		

[0144] Meanwhile, in order to perform SL positioning in a resource pool for SL data communication, a method for performing SL positioning in a manner that does not affect existing SL data communication needs to be defined.

[0145] Based on an embodiment of the present disclosure, in order to perform SL positioning in a resource pool for SL data communication, a method for transmitting SL PRS for SL positioning using PSFCH symbols and a device supporting the same are proposed.

[0146] In the present disclosure, the following terms may be used.

- UE-triggered SL positioning: sidelink (SL) positioning where the procedure is triggered by the UE.
- Base station/LMF-triggered SL positioning: SL positioning where the procedure is triggered by the base station/LMF
- UE-controlled SL positioning: SL positioning where the SL positioning group is created by the UE
- Base station-controlled SL positioning: SL positioning where the SL positioning group is created by the base station
- UE-based SL positioning: SL positioning where the UE position is calculated by the UE
- UE-assisted SL positioning: SL positioning where the UE position is calculated by the base station/LS
- SL positioning group: UEs that participates in SL positioning
- Target UE (T-UE): UE whose position is calculated
- Server UE (S-UE): UE that assists T-UE's SL positioning
- MG: measurement gap where only SL PRS transmission is allowed
- MW: measurement window where both SL data and SL PRS can be transmitted in a multiplexed way

[0147] For example, a SL PRS transmission resource may include SL PRS resource set(s) comprising the following information.

- SL PRS resource set ID
- SL PRS resource ID list: a list of SL PRS resource IDs in a SL PRS resource set
- SL PRS resource type: which can be set to periodic, aperiodic, semi-persistent or on-demand
- Alpha for SL PRS power control
- P0 for SL PRS power control
- Path loss reference for SL PRS power control: which can be set to SL SSB or DL PRS or UL SRS or UL SRS for positioning or PSCCH DMRS or PSSCH DMRS or PSFCH or SL CSI RS, etc.

[0148] For example, the SL PRS resource set may include SL PRS resource(s) comprising the following information.

- SL PRS resource ID
- SL PRS comb size: an interval between REs for SL PRS transmission within a symbol
- SL PRS comb offset: an RE index in which the SL PRS is first transmitted within the symbol
- SL PRS comb cyclic shift: a cyclic shift used to generate a sequence that makes up the SL PRS
- SL PRS start position: an index of the first symbol in which the SL PRS is transmitted within one slot
- Number of SL PRS symbols: the number of symbols configured for the SL PRS within one slot
- Frequency domain shift: the lowest frequency position (index) in the frequency domain in which the SL PRS is transmitted
- SL PRS BW: frequency bandwidth used for SL PRS transmission
- SL PRS resource type: which can be set to periodic, aperiodic, semi-persistent or on-demand
- SL PRS periodicity: periodicity in the time domain between SL PRS resources, in a unit of physical slot or a unit of logical slot in a resource pool in which the SL PRS is transmitted
- SL PRS offset: an offset in the time domain to the start of the first SL PRS resource relative to reference timing, in a unit of physical slot or a unit of logical slot in a resource pool in which the SL PRS is transmitted. The reference timing may

be SFN=0 or DFN=0 or the time of successful reception or decoding of RRC / MAC-CE / DCI / SCI associated with the SL PRS resource.

- SL PRS sequence ID
- SL PRS spatial relation: which can be set to SL SSB or DL PRS or UL SRS or UL SRS for positioning or PSCCH DMRS or PSSCH DMRS or PSFCH or SL CSI RS, etc.

[0149] Meanwhile, when performing SL PRS transmission in a resource pool for SL data communication, if the UE transmits SL PRS using some symbols within a SL slot, the SL PRS may affect the timing of SL channels defined by logical slot units belonging to the SL resource pool for SL data communication. As a result, proper SL data communication may not be performed.

[0150] To address this issue, for example, when performing SL positioning in the resource pool for SL data communication, SL PRS may be transmitted using frequency resources that are not used to transmit PSFCH in the previously defined PSFCH symbols. For example, if the base station configures periodic PSFCH slots, and configures RBs that can be used to transmit PSFCH, using a bitmap or the like, for PSFCH symbols within the slots, RBs other than the RBs assigned to transmit PSFCH within the PSFCH symbols may be used to transmit SL PRS. For example, some RBs may be configured to be used for SL PRS transmission, using a bitmap or the like, for the excluded RBs.

[0151] For example, the number of PSFCH symbols configured within the PSFCH slot may not fill the entire PSFCH slot. For example, since the number of PSFCH symbols per slot may be 2, the number of PSFCH symbols configured within the PSFCH slot may not fill the entire PSFCH slot. Therefore, for SL PRS transmissions using the number of symbols greater than or equal to the number of PSFCH symbols, one or more PSFCH slots may be aggregated to form a single SL PRS resource.

[0152] For example, information on PSFCH slot aggregation used to form the single SL PRS resource may be signaled through SCI in the first PSFCH slot belonging to the aggregated PSFCH slots. For example, the SL PRS aggregation information may be transmitted through 1st-stage SCI in a PSCCH. For example, the SL PRS aggregation information may be transmitted through 2nd-stage SCI in a PSSCH. For example, the SL PRS aggregation information may include the number of aggregated slots required to comprise the single SL PRS resource, or an aggregation index (representing what number slot it is among the aggregated slots) transmitted through the corresponding PSFCH slot.

[0153] For example, the SCI signaling the SL PRS aggregation information may signal information on a reserved PSFCH slot for transmitting the next SL PRS resource. For example, the information on the reserved PSFCH slot may indicate aggregated PSFCH slots that constitute part of SL PRS resources associated with the current PSFCH slot. For example, the information on the reserved PSFCH slot may indicate reservation information for aggregated PSFCH slots that constitute SL PRS resources to be transmitted after the currently transmitted SL PRS. For example, the first PSFCH slot of the aggregated PSFCH slots may indicate reservation information for the first aggregated PSFCH slot that constitutes SL PRS resources to be transmitted after the currently transmitted SL PRS, and the second PSFCH slot may indicate reservation information for the second aggregated PSFCH slot that constitutes SL PRS resources to be transmitted after the currently transmitted SL PRS. In this form, the PSFCH slot aggregation index may sequentially indicate reservation information for the PSFCH slot, which constitutes the next SL PRS resource.

[0154] For example, when transmitting SL PRS through the PSFCH symbols, a separate control channel (e.g., SCI) for indicating SL PRS information may not be used, and only SL PRS resources may be transmitted using the PSFCH symbols. In this case, the UE may obtain information on SL PRS resources transmitted by other UEs by sensing RBs on which SL PRS resources are transmitted within the PSFCH symbols. For example, the UE may measure RSRP in units of RB used to transmit SL PRS resources, based on SL PRS resource configuration information that the UE intends to transmit, within the PSFCH symbols. In this case, if the (average) RSRP value is greater than or equal to a specific threshold value, the UE may determine that other UEs are using those RBs to transmit SL PRS resources, and the UE may exclude those RBs from being candidate resources for transmitting SL PRS resources during a (pre-)configured or signaled SL PRS periodicity.

[0155] For example, within the PSFCH symbols, RBs in the frequency domain greater (or less) than a specific threshold may be used to transmit SL PRS resources, and RBs in the frequency domain less (or greater) than a specific threshold (the specific threshold) may be used to transmit PSFCH. Through this type of FDM-formed RB domain division, RE-level flexibility can be obtained in configuring the SL comb size, the SL comb offset, etc. that constitute SL PRS resources.

[0156] For example, within the PSFCH symbols, RBs for transmitting PSFCH and RBs for transmitting SL PRS resources may be transmitted in an interleaved form.

[0157] FIG. 14 shows an example of allocating RBs other than RBs used for PSFCH transmission to SL PRS resource transmission and transmitting SL PRS resources with comb size = 2 using 2 symbols, when 2 PSFCH symbols are used within one slot, based on an embodiment of the present disclosure. The embodiment of FIG. 14 may be combined with various embodiments of the present disclosure.

[0158] Referring to FIG. 14, SL PRS resources may be transmitted in a staggered pattern within one slot. FIG. 14 shows an example for comb size = 2, the operation described above may be applied for any comb size. For example, for comb size

= 4, SL PRS may be transmitted once every 4 RBs within RBs for SL PRS resource transmission. All subsequent examples can also be applied to any comb size, as described above.

[0159] For example, since the first PSFCH symbol in a SL slot serves as an AGC symbol for receiving the second PSFCH symbol, the first PSFCH symbol may be filled with the same symbol as the second PSFCH symbol. For example, in this case, PSFCH slot aggregation may be applied as shown in FIG. 15 for SL PRS resource transmission with a staggered pattern as described above.

[0160] FIG. 15 shows an example of applying slot aggregation for SL PRS resource transmission with a staggered pattern, based on an embodiment of the present disclosure. The embodiment of FIG. 15 may be combined with various embodiments of the present disclosure.

[0161] Referring to FIG. 15, the locations of RBs for SL PRS resource transmission within the first and second PSFCH symbols within each slot may be the same, and SL PRS resources may be transmitted in a staggered manner between aggregated slots. FIG. 15 shows an example where two PSFCH slots are aggregated, and the above-described operation can be generalized to an aggregation of any number of PSFCH slots.

[0162] For example, as described above, SL PRS transmission using PSFCH symbols may be performed in units of RB rather than units of RE. and a staggered pattern based on comb size may also be staggered in units of RB rather than units of RE. In this case, for example, due to staggering in units of RB, the number of UEs that can transmit SL PRS resources within the fixed number of aggregated PSFCH slots may be limited. Accordingly, for example, a form of staggered transmission of SL PRS resources may be performed in units of RE rather than units of RB, as shown in FIG. 16.

[0163] FIG. 16 shows an example of staggering SL PRS resources in units of RE rather than units of RB, based on an embodiment of the present disclosure. The embodiment of FIG. 16 may be combined with various embodiments of the present disclosure.

[0164] Referring to FIG. 16, resources for PSFCH transmission are drawn in units of RB and resources for SL PRS transmission are drawn in units of RE. As shown in FIG. 16, since the SL PRS has RE-level granularity rather than RB-level granularity, there may be no RB-level burst in which frequency resources are empty and SL PRS is not transmitted within one PSFCH symbol, and SL PRS may be transmitted more distributed over all possible frequency components.

[0165] FIG. 17 shows an example of applying PSFCH slot aggregation for SL PRS transmission in order to allow the first PSFCH symbol to operate as an AGC symbol by making PSFCH symbols transmitted within one PSFCH slot the same, based on an embodiment of the present disclosure. The embodiment of FIG. 17 may be combined with various embodiments of the present disclosure.

[0166] FIG. 18 shows an example of allocating SL PRS in units of RE in PSFCH symbols, based on an embodiment of the present disclosure. The embodiment of FIG. 18 may be combined with various embodiments of the present disclosure.

[0167] In the case of allocating SL PRS in units of RE in PSFCH symbols, the number of UEs that can simultaneously transmit SL PRS may be increased, as shown in FIG. 18. In FIG. 18, since SL PRS #N refers to SL PRS resources allocated to the Nth UE, more UEs (6 UEs in the figure) can transmit SL PRS simultaneously in a staggered pattern, compared to the figure above.

[0168] FIG. 19 shows an example of applying PSFCH slot aggregation for SL PRS transmission, when multiple UEs transmit SL PRS simultaneously, in order to allow the first PSFCH symbol to operate as an AGC symbol by making PSFCH symbols transmitted within one PSFCH slot the same, based on an embodiment of the present disclosure. The embodiment of FIG. 19 may be combined with various embodiments of the present disclosure.

[0169] For example, when performing SL PRS transmission within PSFCH symbols by allocating it in units of RE, as shown in FIG. 19, SL PRS may be transmitted in units of one RE, but SL PRS may also be transmitted in units of a set of N consecutive REs, up to 12 in number, belonging to one RB.

[0170] FIGs. 20 and 21 show an example of transmitting SL PRS in units of a set of 3 REs, based on an embodiment of the present disclosure. The embodiments of FIGs. 20 and 21 may be combined with various embodiments of the present disclosure.

[0171] FIG. 20 shows the operation of transmitting SL PRS with comb size = 2 using 2 PSFCH symbols within one PSFCH slot, and FIG. 21 shows a form of implementing SL PRS transmission with comb size = 2 by aggregating 2 PSFCH slots. As described above, in this case, by transmitting two PSFCH symbols in the same form within one PSFCH slot, the first symbol may have the advantage of being able to be used as the AGC symbol. FIGs. 20 and 21 show cases where comb size = 2, and SL PRS resources can be allocated in a similarly extended form for any comb size.

[0172] For example, when transmitting SL PRS in units of a set of N REs as shown in FIG. 20 or FIG. 21, the number of UEs that can perform transmission simultaneously can be increased by allocating each RE set unit to SL PRS transmission of different UEs.

[0173] When transmitting SL PRS using PSFCH symbols as described above, a UE that receives the SL PRS may transmit a SL PRS ACK/NACK signal to feedback whether the SL PRS has been received or not in the following manner.

[0174] The first PSFCH symbol within one PSFCH slot may act as the AGC symbol for the second PSFCH symbol. In this case, if PSFCH RBs or SL PRS RBs are allocated in an interleaved pattern as described above, it may appear as a signal that is repeated by the interleaving interval in units of RB (2 in the example above) within the original symbol length in the

time domain. Thus, the preceding repeated signal within the original symbol length may be used as an AGC signal, and the latter part not used as AGC may be used as a signal indicating ACK/NACK for the SL PRS.

[0175] In the present disclosure, the PRS resource transmission may refer to PRS transmission using PRS resources.

[0176] Based on various embodiments of the present disclosure, in order to perform SL positioning in a resource pool for SL data communication, the UE may transmit SL PRS for SL positioning using PSFCH symbols. For this purpose, the SL PRS may be transmitted in units of RB, and/or the SL PRS may be transmitted in a staggered pattern in units of RB, and/or the SL PRS with any comb size may be transmitted by aggregating one or more PSFCH slots.

[0177] For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a service type. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a (LCH or service) priority. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a QoS requirement (e.g., latency, reliability, minimum communication range). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a PQI parameter. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL HARQ feedback ENABLED LCH/MAC PDU (transmission). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL HARQ feedback DISABLED LCH/MAC PDU (transmission). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a CBR measurement value of a resource pool. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL cast type (e.g., unicast, groupcast, broadcast). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL groupcast HARQ feedback option (e.g., NACK only feedback, ACK/NACK feedback, NACK only feedback based on TX-RX distance). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL mode 1 CG type (e.g., SL CG type 1 or SL CG type 2). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL mode type (e.g., mode 1 or mode 2). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a resource pool. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for whether a PSFCH resource is a configured resource pool. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a source (L2) ID. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a destination (L2) ID. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a PC5 RRC connection link. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL link. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a connection state (e.g., RRC CONNECTED state, IDLE state, INACTIVE state) (with a base station). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a SL HARQ process (ID). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for whether to perform SL DRX operation (of TX UE or RX UE). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for whether a power saving (TX or RX) UE. For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a case where (from a specific UE perspective) PSFCH TX and PSFCH RX (and/or a plurality of PSFCH TX (exceeding UE capabilities)) overlap (and/or PSFCH TX (and/or PSFCH RX) is omitted). For example, whether the rule is applied and/or the proposed method/rule related parameter value of the present disclosure may be configured/allowed specifically (or differently or independently) for a case where the RX UE actually (successfully) receives PSCCH (and/or PSSCH) (re)transmission from the TX UE.

[0178] For example, in the present disclosure, the term "configure/configured (or designate/designated)" may be

extended and interpreted as a form in which the base station informs the UE through a pre-defined (physical layer or higher layer) channel/signal (e.g., SIB, RRC, MAC CE) (and/or a form in which the UE informs other UEs through a pre-defined (physical layer or higher layer) channel/signal (e.g., SL MAC CE, PC5 RRC)).

[0179] For example, in the present disclosure, the term "PSFCH" may be extended and interpreted as (NR or LTE) PSSCH (and/or (NR or LTE) PSCCH) (and/or (NR or LTE) SL SSB (and/or UL channel/signal)). In addition, the proposed methods of the present disclosure may be used in combination with each other (as a new type).

[0180] For example, in the present disclosure, a specific threshold may refer to a threshold pre-defined or (pre-) configured by the network or the base station or the upper layer (including the application layer) of the UE. For example, in the present disclosure, a specific configured threshold may refer to a value pre-defined or (pre-)configured by the network or the base station or the upper layer (including the application layer) of the UE. For example, the operation configured by the network/base station may refer to the operation in which the base station (pre-)configures to the UE through higher layer RRC signaling, configures/signals to the UE through MAC CE, or signals the UE through DCI.

[0181] FIG. 22 shows a method for a first device to perform wireless communication, based on an embodiment of the present disclosure. The embodiment of FIG. 22 may be combined with various embodiments of the present disclosure.

[0182] Referring to FIG. 22, in step S2210, the first device may obtain information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH). In step S2220, the first device may obtain sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS. In step S2230, the first device may transmit the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0183] For example, the set of RBs for the PSFCH may be a set of RBs related to a value of 1 in a first bitmap. For example, the set of RBs for the SL PRS may be a set of RBs related to a value of 0 in the first bitmap. For example, the set of RBs for the SL PRS may be a set of RBs related to a value of 1 in a second bitmap, and the set of RBs related to the value of 1 in the first bitmap and the set of RBs related to the value of 1 in the second bitmap may not overlap.

[0184] For example, the SL PRS may be transmitted within at least one PSFCH symbol within one PSFCH slot.

[0185] For example, the SL PRS may be transmitted within a plurality of PSFCH symbols within a PSFCH aggregation slot in which a plurality of PSFCH slots are aggregated. Additionally, for example, the first device may transmit control information related to the SL PRS to the second device. For example, the control information may be transmitted within the first PSFCH slot among the plurality of PSFCH slots within the PSFCH aggregation slot. For example, the control information may include information related to a number of the plurality of PSFCH slots included in the PSFCH aggregation slot or information related to an aggregation order of a PSFCH slot in which the SL PRS is transmitted among the plurality of PSFCH slots included in the PSFCH aggregation slot. For example, the control information may include information related to a PSFCH aggregation slot after the PSFCH aggregation slot.

[0186] For example, an RB in which a reference signal received power (RSRP) greater than or equal to a threshold is measured among the set of RBs for the SL PRS may be excluded from the set of RBs for the SL PRS.

[0187] For example, the SL PRS may be transmitted interleaved in units of resource block (RB) or resource element (RE) based on a comb size.

[0188] For example, based on the SL PRS being mapped to two PSFCH symbols within one PSFCH slot, the second PSFCH symbol may be duplicated in the first PSFCH symbol.

[0189] The proposed method can be applied to devices based on various embodiments of the present disclosure. First, the processor 102 of the first device 100 may obtain information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH). In addition, the processor 102 of the first device 100 may obtain sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS. In addition, the processor 102 of the first device 100 may control transceiver 106 to transmit the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0190] Based on an embodiment of the present disclosure, a first device adapted to perform wireless communication may be provided. For example, the first device may comprise: at least one transceiver; at least one processor; and at least one memory connected to the at least one processor and storing instructions. For example, the instructions, based on being executed by the at least one processor, may cause the first device to perform operations comprising: obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0191] Based on an embodiment of the present disclosure, a processing device adapted to control a first device may be provided. For example, the processing device may comprise: at least one processor; and at least one memory connected to the at least one processor and storing instructions. For example, the instructions, based on being executed by the at least one processor, may cause the first device to perform operations comprising: obtaining information related to a set of

resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0192] Based on an embodiment of the present disclosure, a non-transitory computer-readable storage medium storing instructions may be provided. For example, the instructions, when executed, may cause a first device to perform operations comprising: obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0193] FIG. 23 shows a method for a second device to perform wireless communication, based on an embodiment of the present disclosure. The embodiment of FIG. 23 may be combined with various embodiments of the present disclosure.

[0194] Referring to FIG. 23, in step S2310, the second device may obtain information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH). In step S2320, the second device may obtain sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS. In step S2330, the second device may receive the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0195] For example, the set of RBs for the PSFCH may be a set of RBs related to a value of 1 in a first bitmap. For example, the set of RBs for the SL PRS may be a set of RBs related to a value of 0 in the first bitmap. For example, the set of RBs for the SL PRS may be a set of RBs related to a value of 1 in a second bitmap, and the set of RBs related to the value of 1 in the first bitmap and the set of RBs related to the value of 1 in the second bitmap may not overlap.

[0196] For example, the SL PRS may be received within at least one PSFCH symbol within one PSFCH slot.

[0197] For example, the SL PRS may be received within a plurality of PSFCH symbols within a PSFCH aggregation slot in which a plurality of PSFCH slots are aggregated. Additionally, for example, the second device may receive control information related to the SL PRS from the first device. For example, the control information may be received within the first PSFCH slot among the plurality of PSFCH slots within the PSFCH aggregation slot. For example, the control information may include information related to a number of the plurality of PSFCH slots included in the PSFCH aggregation slot or information related to an aggregation order of a PSFCH slot in which the SL PRS is transmitted among the plurality of PSFCH slots included in the PSFCH aggregation slot. For example, the control information may include information related to a PSFCH aggregation slot after the PSFCH aggregation slot.

[0198] For example, an RB in which a reference signal received power (RSRP) greater than or equal to a threshold is measured among the set of RBs for the SL PRS may be excluded from the set of RBs for the SL PRS.

[0199] For example, the SL PRS may be transmitted interleaved in units of resource block (RB) or resource element (RE) based on a comb size.

[0200] For example, based on the SL PRS being mapped to two PSFCH symbols within one PSFCH slot, the second PSFCH symbol may be duplicated in the first PSFCH symbol.

[0201] The proposed method can be applied to devices based on various embodiments of the present disclosure. First, the processor 202 of the second device 200 may obtain information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH). In addition, the processor 202 of the second device 200 may obtain sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS. In addition, the processor 202 of the second device 200 may control transceiver 206 to receive the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0202] Based on an embodiment of the present disclosure, a second device adapted to perform wireless communication may be provided. For example, the second device may comprise: at least one transceiver; at least one processor; and at least one memory connected to the at least one processor and storing instructions. For example, the instructions, based on being executed by the at least one processor, may cause the second device to perform operations comprising: obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and receiving the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0203] Based on an embodiment of the present disclosure, a processing device adapted to control a second device may be provided. For example, the processing device may comprise: at least one processor; and at least one memory connected to the at least one processor and storing instructions. For example, the instructions, based on being executed by the at least one processor, may cause the second device to perform operations comprising: obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL)

positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and receiving the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0204] Based on an embodiment of the present disclosure, a non-transitory computer-readable storage medium storing instructions may be provided. For example, the instructions, when executed, may cause a second device to perform operations comprising: obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH); obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and receiving the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS configuration information. For example, the set of RBs for the SL PRS may not overlap with the set of RBs for the PSFCH.

[0205] Various embodiments of the present disclosure may be combined with each other.

[0206] Hereinafter, device(s) to which various embodiments of the present disclosure can be applied will be described.

[0207] The various descriptions, functions, procedures, proposals, methods, and/or operational flowcharts of the present disclosure described in this document may be applied to, without being limited to, a variety of fields requiring wireless communication/connection (e.g., 5G) between devices.

[0208] Hereinafter, a description will be given in more detail with reference to the drawings. In the following drawings/-description, the same reference symbols may denote the same or corresponding hardware blocks, software blocks, or functional blocks unless described otherwise.

[0209] FIG. 24 shows a communication system 1, based on an embodiment of the present disclosure. The embodiment of FIG. 24 may be combined with various embodiments of the present disclosure.

[0210] Referring to FIG. 24, a communication system 1 to which various embodiments of the present disclosure are applied includes wireless devices, Base Stations (BSs), and a network. Herein, the wireless devices represent devices performing communication using Radio Access Technology (RAT) (e.g., 5G New RAT (NR)) or Long-Term Evolution (LTE)) and may be referred to as communication/radio/SG devices. The wireless devices may include, without being limited to, a robot 100a, vehicles 100b-1 and 100b-2, an eXtended Reality (XR) device 100c, a hand-held device 100d, a home appliance 100e, an Internet of Things (IoT) device 100f, and an Artificial Intelligence (AI) device/server 400. For example, the vehicles may include a vehicle having a wireless communication function, an autonomous vehicle, and a vehicle capable of performing communication between vehicles. Herein, the vehicles may include an Unmanned Aerial Vehicle (UAV) (e.g., a drone). The XR device may include an Augmented Reality (AR)/Virtual Reality (VR)/Mixed Reality (MR) device and may be implemented in the form of a Head-Mounted Device (HMD), a Head-Up Display (HUD) mounted in a vehicle, a television, a smartphone, a computer, a wearable device, a home appliance device, a digital signage, a vehicle, a robot, etc. The hand-held device may include a smartphone, a smartpad, a wearable device (e.g., a smartwatch or a smartglasses), and a computer (e.g., a notebook). The home appliance may include a TV, a refrigerator, and a washing machine. The IoT device may include a sensor and a smartmeter. For example, the BSs and the network may be implemented as wireless devices and a specific wireless device 200a may operate as a BS/network node with respect to other wireless devices.

[0211] Here, wireless communication technology implemented in wireless devices 100a to 100f of the present disclosure may include Narrowband Internet of Things for low-power communication in addition to LTE, NR, and 6G. In this case, for example, NB-IoT technology may be an example of Low Power Wide Area Network (LPWAN) technology and may be implemented as standards such as LTE Cat NB1, and/or LTE Cat NB2, and is not limited to the name described above. Additionally or alternatively, the wireless communication technology implemented in the wireless devices 100a to 100f of the present disclosure may perform communication based on LTE-M technology. In this case, as an example, the LTE-M technology may be an example of the LPWAN and may be called by various names including enhanced Machine Type Communication (eMTC), and the like. For example, the LTE-M technology may be implemented as at least any one of various standards such as 1) LTE CAT 0, 2) LTE Cat M1, 3) LTE Cat M2, 4) LTE non-Bandwidth Limited (non-BL), 5) LTE-MTC, 6) LTE Machine Type Communication, and/or 7) LTE M, and is not limited to the name described above. Additionally or alternatively, the wireless communication technology implemented in the wireless devices 100a to 100f of the present disclosure may include at least one of Bluetooth, Low Power Wide Area Network (LPWAN), and ZigBee considering the low-power communication, and is not limited to the name described above. As an example, the ZigBee technology may generate personal area networks (PAN) related to small/low-power digital communication based on various standards including IEEE 802.15.4, and the like, and may be called by various names.

[0212] The wireless devices 100a to 100f may be connected to the network 300 via the BSs 200. An AI technology may be applied to the wireless devices 100a to 100f and the wireless devices 100a to 100f may be connected to the AI server 400 via the network 300. The network 300 may be configured using a 3G network, a 4G (e.g., LTE) network, or a 5G (e.g., NR) network. Although the wireless devices 100a to 100f may communicate with each other through the BSs 200/network 300, the wireless devices 100a to 100f may perform direct communication (e.g., sidelink communication) with each other without passing through the BSs/network. For example, the vehicles 100b-1 and 100b-2 may perform direct communication (e.g. Vehicle-to-Vehicle (V2V)/Vehicle-to-everything (V2X) communication). The IoT device (e.g., a sensor) may

perform direct communication with other IoT devices (e.g., sensors) or other wireless devices 100a to 100f.

[0213] Wireless communication/connections 150a, 150b, or 150c may be established between the wireless devices 100a to 100f/BS 200, or BS 200/BS 200. Herein, the wireless communication/connections may be established through various RATs (e.g., 5G NR) such as uplink/downlink communication 150a, sidelink communication 150b (or, D2D communication), or inter BS communication (e.g. relay, Integrated Access Backhaul (IAB)). The wireless devices and the BSs/the wireless devices may transmit/receive radio signals to/from each other through the wireless communication/connections 150a and 150b. For example, the wireless communication/connections 150a and 150b may transmit/receive signals through various physical channels. To this end, at least a part of various configuration information configuring processes, various signal processing processes (e.g., channel encoding/decoding, modulation/demodulation, and resource mapping/demapping), and resource allocating processes, for transmitting/receiving radio signals, may be performed based on the various proposals of the present disclosure.

[0214] FIG. 25 shows wireless devices, based on an embodiment of the present disclosure. The embodiment of FIG. 25 may be combined with various embodiments of the present disclosure.

[0215] Referring to FIG. 25, a first wireless device 100 and a second wireless device 200 may transmit radio signals through a variety of RATs (e.g., LTE and NR). Herein, {the first wireless device 100 and the second wireless device 200} may correspond to {the wireless device 100x and the BS 200} and/or {the wireless device 100x and the wireless device 100x} of FIG. 24.

[0216] The first wireless device 100 may include one or more processors 102 and one or more memories 104 and additionally further include one or more transceivers 106 and/or one or more antennas 108. The processor(s) 102 may control the memory(s) 104 and/or the transceiver(s) 106 and may be configured to implement the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document. For example, the processor(s) 102 may process information within the memory(s) 104 to generate first information/signals and then transmit radio signals including the first information/signals through the transceiver(s) 106. The processor(s) 102 may receive radio signals including second information/signals through the transceiver 106 and then store information obtained by processing the second information/signals in the memory(s) 104. The memory(s) 104 may be connected to the processor(s) 102 and may store a variety of information related to operations of the processor(s) 102. For example, the memory(s) 104 may store software code including commands for performing a part or the entirety of processes controlled by the processor(s) 102 or for performing the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document. Herein, the processor(s) 102 and the memory(s) 104 may be a part of a communication modem/circuit/chip designed to implement RAT (e.g., LTE or NR). The transceiver(s) 106 may be connected to the processor(s) 102 and transmit and/or receive radio signals through one or more antennas 108. Each of the transceiver(s) 106 may include a transmitter and/or a receiver. The transceiver(s) 106 may be interchangeably used with Radio Frequency (RF) unit(s). In the present disclosure, the wireless device may represent a communication modem/circuit/chip.

[0217] The second wireless device 200 may include one or more processors 202 and one or more memories 204 and additionally further include one or more transceivers 206 and/or one or more antennas 208. The processor(s) 202 may control the memory(s) 204 and/or the transceiver(s) 206 and may be configured to implement the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document. For example, the processor(s) 202 may process information within the memory(s) 204 to generate third information/signals and then transmit radio signals including the third information/signals through the transceiver(s) 206. The processor(s) 202 may receive radio signals including fourth information/signals through the transceiver(s) 106 and then store information obtained by processing the fourth information/signals in the memory(s) 204. The memory(s) 204 may be connected to the processor(s) 202 and may store a variety of information related to operations of the processor(s) 202. For example, the memory(s) 204 may store software code including commands for performing a part or the entirety of processes controlled by the processor(s) 202 or for performing the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document. Herein, the processor(s) 202 and the memory(s) 204 may be a part of a communication modem/circuit/chip designed to implement RAT (e.g., LTE or NR). The transceiver(s) 206 may be connected to the processor(s) 202 and transmit and/or receive radio signals through one or more antennas 208. Each of the transceiver(s) 206 may include a transmitter and/or a receiver. The transceiver(s) 206 may be interchangeably used with RF unit(s). In the present disclosure, the wireless device may represent a communication modem/circuit/chip.

[0218] Hereinafter, hardware elements of the wireless devices 100 and 200 will be described more specifically. One or more protocol layers may be implemented by, without being limited to, one or more processors 102 and 202. For example, the one or more processors 102 and 202 may implement one or more layers (e.g., functional layers such as PHY, MAC, RLC, PDCP, RRC, and SDAP). The one or more processors 102 and 202 may generate one or more Protocol Data Units (PDUs) and/or one or more Service Data Unit (SDUs) according to the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document. The one or more processors 102 and 202 may generate messages, control information, data, or information according to the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document. The one or more processors 102 and 202 may generate signals (e.g., baseband signals) including PDUs, SDUs, messages, control information, data, or

information according to the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document and provide the generated signals to the one or more transceivers 106 and 206. The one or more processors 102 and 202 may receive the signals (e.g., baseband signals) from the one or more transceivers 106 and 206 and acquire the PDUs, SDUs, messages, control information, data, or information according to the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document.

[0219] The one or more processors 102 and 202 may be referred to as controllers, microcontrollers, microprocessors, or microcomputers. The one or more processors 102 and 202 may be implemented by hardware, firmware, software, or a combination thereof. As an example, one or more Application Specific Integrated Circuits (ASICs), one or more Digital Signal Processors (DSPs), one or more Digital Signal Processing Devices (DSPDs), one or more Programmable Logic Devices (PLDs), or one or more Field Programmable Gate Arrays (FPGAs) may be included in the one or more processors 102 and 202. The descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document may be implemented using firmware or software and the firmware or software may be configured to include the modules, procedures, or functions. Firmware or software configured to perform the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document may be included in the one or more processors 102 and 202 or stored in the one or more memories 104 and 204 so as to be driven by the one or more processors 102 and 202. The descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document may be implemented using firmware or software in the form of code, commands, and/or a set of commands.

[0220] The one or more memories 104 and 204 may be connected to the one or more processors 102 and 202 and store various types of data, signals, messages, information, programs, code, instructions, and/or commands. The one or more memories 104 and 204 may be configured by Read-Only Memories (ROMs), Random Access Memories (RAMs), Electrically Erasable Programmable Read-Only Memories (EPROMs), flash memories, hard drives, registers, cash memories, computer-readable storage media, and/or combinations thereof. The one or more memories 104 and 204 may be located at the interior and/or exterior of the one or more processors 102 and 202. The one or more memories 104 and 204 may be connected to the one or more processors 102 and 202 through various technologies such as wired or wireless connection.

[0221] The one or more transceivers 106 and 206 may transmit user data, control information, and/or radio signals/channels, mentioned in the methods and/or operational flowcharts of this document, to one or more other devices. The one or more transceivers 106 and 206 may receive user data, control information, and/or radio signals/channels, mentioned in the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document, from one or more other devices. For example, the one or more transceivers 106 and 206 may be connected to the one or more processors 102 and 202 and transmit and receive radio signals. For example, the one or more processors 102 and 202 may perform control so that the one or more transceivers 106 and 206 may transmit user data, control information, or radio signals to one or more other devices. The one or more processors 102 and 202 may perform control so that the one or more transceivers 106 and 206 may receive user data, control information, or radio signals from one or more other devices. The one or more transceivers 106 and 206 may be connected to the one or more antennas 108 and 208 and the one or more transceivers 106 and 206 may be configured to transmit and receive user data, control information, and/or radio signals/channels, mentioned in the descriptions, functions, procedures, proposals, methods, and/or operational flowcharts disclosed in this document, through the one or more antennas 108 and 208. In this document, the one or more antennas may be a plurality of physical antennas or a plurality of logical antennas (e.g., antenna ports). The one or more transceivers 106 and 206 may convert received radio signals/channels etc. from RF band signals into baseband signals in order to process received user data, control information, radio signals/channels, etc. using the one or more processors 102 and 202. The one or more transceivers 106 and 206 may convert the user data, control information, radio signals/channels, etc. processed using the one or more processors 102 and 202 from the base band signals into the RF band signals. To this end, the one or more transceivers 106 and 206 may include (analog) oscillators and/or filters.

[0222] FIG. 26 shows a signal process circuit for a transmission signal, based on an embodiment of the present disclosure. The embodiment of FIG. 26 may be combined with various embodiments of the present disclosure.

[0223] Referring to FIG. 26, a signal processing circuit 1000 may include scramblers 1010, modulators 1020, a layer mapper 1030, a precoder 1040, resource mappers 1050, and signal generators 1060. An operation/function of FIG. 26 may be performed, without being limited to, the processors 102 and 202 and/or the transceivers 106 and 206 of FIG. 25. Hardware elements of FIG. 26 may be implemented by the processors 102 and 202 and/or the transceivers 106 and 206 of FIG. 25. For example, blocks 1010 to 1060 may be implemented by the processors 102 and 202 of FIG. 25. Alternatively, the blocks 1010 to 1050 may be implemented by the processors 102 and 202 of FIG. 25 and the block 1060 may be implemented by the transceivers 106 and 206 of FIG. 25.

[0224] Codewords may be converted into radio signals via the signal processing circuit 1000 of FIG. 26. Herein, the codewords are encoded bit sequences of information blocks. The information blocks may include transport blocks (e.g., a UL-SCH transport block, a DL-SCH transport block). The radio signals may be transmitted through various physical channels (e.g., a PUSCH and a PDSCH).

[0225] Specifically, the codewords may be converted into scrambled bit sequences by the scramblers 1010. Scramble sequences used for scrambling may be generated based on an initialization value, and the initialization value may include ID information of a wireless device. The scrambled bit sequences may be modulated to modulation symbol sequences by the modulators 1020. A modulation scheme may include pi/2-Binary Phase Shift Keying (pi/2-BPSK), m-Phase Shift Keying (m-PSK), and m-Quadrature Amplitude Modulation (m-QAM). Complex modulation symbol sequences may be mapped to one or more transport layers by the layer mapper 1030. Modulation symbols of each transport layer may be mapped (precoded) to corresponding antenna port(s) by the precoder 1040. Outputs z of the precoder 1040 may be obtained by multiplying outputs y of the layer mapper 1030 by an $N \times M$ precoding matrix W . Herein, N is the number of antenna ports and M is the number of transport layers. The precoder 1040 may perform precoding after performing transform precoding (e.g., DFT) for complex modulation symbols. Alternatively, the precoder 1040 may perform precoding without performing transform precoding.

[0226] The resource mappers 1050 may map modulation symbols of each antenna port to time-frequency resources. The time-frequency resources may include a plurality of symbols (e.g., a CP-OFDMA symbols and DFT-s-OFDMA symbols) in the time domain and a plurality of subcarriers in the frequency domain. The signal generators 1060 may generate radio signals from the mapped modulation symbols and the generated radio signals may be transmitted to other devices through each antenna. For this purpose, the signal generators 1060 may include Inverse Fast Fourier Transform (IFFT) modules, Cyclic Prefix (CP) inserters, Digital-to-Analog Converters (DACs), and frequency up-converters.

[0227] Signal processing procedures for a signal received in the wireless device may be configured in a reverse manner of the signal processing procedures 1010 to 1060 of FIG. 26. For example, the wireless devices (e.g., 100 and 200 of FIG. 25) may receive radio signals from the exterior through the antenna ports/transceivers. The received radio signals may be converted into baseband signals through signal restorers. To this end, the signal restorers may include frequency downlink converters, Analog-to-Digital Converters (ADCs), CP remover, and Fast Fourier Transform (FFT) modules. Next, the baseband signals may be restored to codewords through a resource demapping procedure, a postcoding procedure, a demodulation processor, and a descrambling procedure. The codewords may be restored to original information blocks through decoding. Therefore, a signal processing circuit (not illustrated) for a reception signal may include signal restorers, resource demappers, a postcoder, demodulators, descramblers, and decoders.

[0228] FIG. 27 shows another example of a wireless device, based on an embodiment of the present disclosure. The wireless device may be implemented in various forms according to a use-case/service (refer to FIG. 24). The embodiment of FIG. 27 may be combined with various embodiments of the present disclosure.

[0229] Referring to FIG. 27, wireless devices 100 and 200 may correspond to the wireless devices 100 and 200 of FIG. 25 and may be configured by various elements, components, units/portions, and/or modules. For example, each of the wireless devices 100 and 200 may include a communication unit 110, a control unit 120, a memory unit 130, and additional components 140. The communication unit may include a communication circuit 112 and transceiver(s) 114. For example, the communication circuit 112 may include the one or more processors 102 and 202 and/or the one or more memories 104 and 204 of FIG. 25. For example, the transceiver(s) 114 may include the one or more transceivers 106 and 206 and/or the one or more antennas 108 and 208 of FIG. 25. The control unit 120 is electrically connected to the communication unit 110, the memory 130, and the additional components 140 and controls overall operation of the wireless devices. For example, the control unit 120 may control an electric/mechanical operation of the wireless device based on programs/code/commands/information stored in the memory unit 130. The control unit 120 may transmit the information stored in the memory unit 130 to the exterior (e.g., other communication devices) via the communication unit 110 through a wireless/wired interface or store, in the memory unit 130, information received through the wireless/wired interface from the exterior (e.g., other communication devices) via the communication unit 110.

[0230] The additional components 140 may be variously configured according to types of wireless devices. For example, the additional components 140 may include at least one of a power unit/battery, input/output (I/O) unit, a driving unit, and a computing unit. The wireless device may be implemented in the form of, without being limited to, the robot (100a of FIG. 24), the vehicles (100b-1 and 100b-2 of FIG. 24), the XR device (100c of FIG. 24), the hand-held device (100d of FIG. 24), the home appliance (100e of FIG. 24), the IoT device (100f of FIG. 24), a digital broadcast terminal, a hologram device, a public safety device, an MTC device, a medicine device, a fintech device (or a finance device), a security device, a climate/environment device, the AI server/device (400 of FIG. 24), the BSs (200 of FIG. 24), a network node, etc. The wireless device may be used in a mobile or fixed place according to a use-example/service.

[0231] In FIG. 27, the entirety of the various elements, components, units/portions, and/or modules in the wireless devices 100 and 200 may be connected to each other through a wired interface or at least a part thereof may be wirelessly connected through the communication unit 110. For example, in each of the wireless devices 100 and 200, the control unit 120 and the communication unit 110 may be connected by wire and the control unit 120 and first units (e.g., 130 and 140) may be wirelessly connected through the communication unit 110. Each element, component, unit/portion, and/or module within the wireless devices 100 and 200 may further include one or more elements. For example, the control unit 120 may be configured by a set of one or more processors. As an example, the control unit 120 may be configured by a set of a communication control processor, an application processor, an Electronic Control Unit (ECU), a graphical processing unit,

and a memory control processor. As another example, the memory 130 may be configured by a Random Access Memory (RAM), a Dynamic RAM (DRAM), a Read Only Memory (ROM), a flash memory, a volatile memory, a non-volatile memory, and/or a combination thereof.

[0232] Hereinafter, an example of implementing FIG. 27 will be described in detail with reference to the drawings.

[0233] FIG. 28 shows a hand-held device, based on an embodiment of the present disclosure. The hand-held device may include a smartphone, a smartpad, a wearable device (e.g., a smartwatch or a smartglasses), or a portable computer (e.g., a notebook). The hand-held device may be referred to as a mobile station (MS), a user terminal (UT), a Mobile Subscriber Station (MSS), a Subscriber Station (SS), an Advanced Mobile Station (AMS), or a Wireless Terminal (WT). The embodiment of FIG. 28 may be combined with various embodiments of the present disclosure.

[0234] Referring to FIG. 28, a hand-held device 100 may include an antenna unit 108, a communication unit 110, a control unit 120, a memory unit 130, a power supply unit 140a, an interface unit 140b, and an I/O unit 140c. The antenna unit 108 may be configured as a part of the communication unit 110. Blocks 110 to 130/140a to 140c correspond to the blocks 110 to 130/140 of FIG. 27, respectively.

[0235] The communication unit 110 may transmit and receive signals (e.g., data and control signals) to and from other wireless devices or BSs. The control unit 120 may perform various operations by controlling constituent elements of the hand-held device 100. The control unit 120 may include an Application Processor (AP). The memory unit 130 may store data/parameters/programs/code/commands needed to drive the hand-held device 100. The memory unit 130 may store input/output data/information. The power supply unit 140a may supply power to the hand-held device 100 and include a wired/wireless charging circuit, a battery, etc. The interface unit 140b may support connection of the hand-held device 100 to other external devices. The interface unit 140b may include various ports (e.g., an audio I/O port and a video I/O port) for connection with external devices. The I/O unit 140c may input or output video information/signals, audio information/signals, data, and/or information input by a user. The I/O unit 140c may include a camera, a microphone, a user input unit, a display unit 140d, a speaker, and/or a haptic module.

[0236] As an example, in the case of data communication, the I/O unit 140c may acquire information/signals (e.g., touch, text, voice, images, or video) input by a user and the acquired information/signals may be stored in the memory unit 130. The communication unit 110 may convert the information/signals stored in the memory into radio signals and transmit the converted radio signals to other wireless devices directly or to a BS. The communication unit 110 may receive radio signals from other wireless devices or the BS and then restore the received radio signals into original information/signals. The restored information/signals may be stored in the memory unit 130 and may be output as various types (e.g., text, voice, images, video, or haptic) through the I/O unit 140c.

[0237] FIG. 29 shows a vehicle or an autonomous vehicle, based on an embodiment of the present disclosure. The vehicle or autonomous vehicle may be implemented by a mobile robot, a car, a train, a manned/unmanned Aerial Vehicle (AV), a ship, etc. The embodiment of FIG. 29 may be combined with various embodiments of the present disclosure.

[0238] Referring to FIG. 29, a vehicle or autonomous vehicle 100 may include an antenna unit 108, a communication unit 110, a control unit 120, a driving unit 140a, a power supply unit 140b, a sensor unit 140c, and an autonomous driving unit 140d. The antenna unit 108 may be configured as a part of the communication unit 110. The blocks 110/130/140a to 140d correspond to the blocks 110/130/140 of FIG. 27, respectively.

[0239] The communication unit 110 may transmit and receive signals (e.g., data and control signals) to and from external devices such as other vehicles, BSs (e.g., gNBs and road side units), and servers. The control unit 120 may perform various operations by controlling elements of the vehicle or the autonomous vehicle 100. The control unit 120 may include an Electronic Control Unit (ECU). The driving unit 140a may cause the vehicle or the autonomous vehicle 100 to drive on a road. The driving unit 140a may include an engine, a motor, a powertrain, a wheel, a brake, a steering device, etc. The power supply unit 140b may supply power to the vehicle or the autonomous vehicle 100 and include a wired/wireless charging circuit, a battery, etc. The sensor unit 140c may acquire a vehicle state, ambient environment information, user information, etc. The sensor unit 140c may include an Inertial Measurement Unit (IMU) sensor, a collision sensor, a wheel sensor, a speed sensor, a slope sensor, a weight sensor, a heading sensor, a position module, a vehicle forward/backward sensor, a battery sensor, a fuel sensor, a tire sensor, a steering sensor, a temperature sensor, a humidity sensor, an ultrasonic sensor, an illumination sensor, a pedal position sensor, etc. The autonomous driving unit 140d may implement technology for maintaining a lane on which a vehicle is driving, technology for automatically adjusting speed, such as adaptive cruise control, technology for autonomously driving along a determined path, technology for driving by automatically setting a path if a destination is set, and the like.

[0240] For example, the communication unit 110 may receive map data, traffic information data, etc. from an external server. The autonomous driving unit 140d may generate an autonomous driving path and a driving plan from the obtained data. The control unit 120 may control the driving unit 140a such that the vehicle or the autonomous vehicle 100 may move along the autonomous driving path according to the driving plan (e.g., speed/direction control). In the middle of autonomous driving, the communication unit 110 may aperiodically/periodically acquire recent traffic information data from the external server and acquire surrounding traffic information data from neighboring vehicles. In the middle of autonomous driving, the sensor unit 140c may obtain a vehicle state and/or surrounding environment information. The

autonomous driving unit 140d may update the autonomous driving path and the driving plan based on the newly obtained data/information. The communication unit 110 may transfer information about a vehicle position, the autonomous driving path, and/or the driving plan to the external server. The external server may predict traffic information data using AI technology, etc., based on the information collected from vehicles or autonomous vehicles and provide the predicted traffic information data to the vehicles or the autonomous vehicles.

[0241] Claims in the present description can be combined in a various way. For instance, technical features in method claims of the present description can be combined to be implemented or performed in an apparatus, and technical features in apparatus claims can be combined to be implemented or performed in a method. Further, technical features in method claim(s) and apparatus claim(s) can be combined to be implemented or performed in an apparatus. Further, technical features in method claim(s) and apparatus claim(s) can be combined to be implemented or performed in a method.

Claims

1. A method for performing wireless communication by a first device, the method comprising:
 - obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH);
 - obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and
 - transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information,
 - wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.
2. The method of claim 1, wherein the set of RBs for the PSFCH is a set of RBs related to a value of 1 in a first bitmap.
3. The method of claim 2, wherein the set of RBs for the SL PRS is a set of RBs related to a value of 0 in the first bitmap.
4. The method of claim 2, wherein the set of RBs for the SL PRS is a set of RBs related to a value of 1 in a second bitmap, and
 - wherein the set of RBs related to the value of 1 in the first bitmap and the set of RBs related to the value of 1 in the second bitmap do not overlap.
5. The method of claim 1, wherein the SL PRS is transmitted within at least one PSFCH symbol within one PSFCH slot.
6. The method of claim 1, wherein the SL PRS is transmitted within in a plurality of PSFCH symbols within a PSFCH aggregation slot in which a plurality of PSFCH slots are aggregated.
7. The method of claim 6, further comprising:
 - transmitting control information related to the SL PRS to the second device.
8. The method of claim 7, wherein the control information is transmitted within the first PSFCH slot among the plurality of PSFCH slots within the PSFCH aggregation slot.
9. The method of claim 7, wherein the control information includes information related to a number of the plurality of PSFCH slots included in the PSFCH aggregation slot or information related to an aggregation order of a PSFCH slot in which the SL PRS is transmitted among the plurality of PSFCH slots included in the PSFCH aggregation slot.
10. The method of claim 7, wherein the control information includes information related to a PSFCH aggregation slot after the PSFCH aggregation slot.
11. The method of claim 1, wherein an RB in which a reference signal received power (RSRP) greater than or equal to a threshold is measured among the set of RBs for the SL PRS is excluded from the set of RBs for the SL PRS.
12. The method of claim 1, wherein the SL PRS is transmitted interleaved in units of resource block (RB) or resource element (RE) based on a comb size.
13. The method of claim 1, wherein, based on the SL PRS being mapped to two PSFCH symbols within one PSFCH slot, the second PSFCH symbol is duplicated in the first PSFCH symbol.

14. A first device adapted to perform wireless communication, the first device comprising:

at least one transceiver;
at least one processor; and
at least one memory connected to the at least one processor and storing instructions that, based on being executed by the at least one processor, cause the first device to perform operations comprising:

obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH);
obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and
transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information,
wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

15. A processing device adapted to control a first device, the processing device comprising:

at least one processor; and
at least one memory connected to the at least one processor and storing instructions that, based on being executed by the at least one processor, cause the first device to perform operations comprising:

obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH);
obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and
transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information,
wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

16. A non-transitory computer-readable storage medium storing instructions that, when executed, cause a first device to perform operations comprising:

obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH);
obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and
transmitting the SL PRS to a second device, within the set of RBs for the SL PRS, based on the SL PRS configuration information,
wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

17. A method for performing wireless communication by a second device, the method comprising:

obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH);
obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related to a set of RBs for a SL PRS; and
receiving the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS configuration information,
wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

18. A second device adapted to perform wireless communication, the second device comprising:

at least one transceiver;
at least one processor; and
at least one memory connected to the at least one processor and storing instructions that, based on being executed by the at least one processor, cause the second device to perform operations comprising:

obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH);
obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information

related to a set of RBs for a SL PRS; and
 receiving the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS
 configuration information,
 wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

19. A processing device adapted to control a second device, the processing device comprising:

at least one processor; and
 at least one memory connected to the at least one processor and storing instructions that, based on being
 executed by the at least one processor, cause the second device to perform operations comprising:

obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel
 (PSFCH);
 obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information
 related to a set of RBs for a SL PRS; and
 receiving the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS
 configuration information,
 wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

20. A non-transitory computer-readable storage medium storing instructions that, when executed, cause a second device
 to perform operations comprising:

obtaining information related to a set of resource blocks (RBs) for a physical sidelink feedback channel (PSFCH);
 obtaining sidelink (SL) positioning reference signal (PRS) configuration information including information related
 to a set of RBs for a SL PRS; and
 receiving the SL PRS from a first device, within the set of RBs for the SL PRS, based on the SL PRS configuration
 information,
 wherein the set of RBs for the SL PRS does not overlap with the set of RBs for the PSFCH.

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13





FIG. 14




: resource for PSFCH transmission and reception



: resource other than resource for PSFCH transmission and reception

FIG. 16





 : resource for PSFCH transmission and reception
 : resource other than resource for PSFCH transmission and reception

FIG. 17




FIG. 18




FIG. 19






FIG. 20



 : resource for PSFCH transmission and reception


 : resource other than resource for PSFCH transmission and reception

FIG. 22




FIG. 23





FIG. 24



1

FIG. 25




FIG. 26

1000(102/106, 202/206)




FIG. 27

Device (100,200)




FIG. 28





FIG. 29



INTERNATIONAL SEARCH REPORT

International application No.

PCT/KR2023/005235

5	A. CLASSIFICATION OF SUBJECT MATTER		
	H04W 72/25(2023.01)i; H04L 5/00(2006.01)i; H04W 72/02(2009.01)i; H04W 64/00(2009.01)i; H04W 92/18(2009.01)i		
	According to International Patent Classification (IPC) or to both national classification and IPC		
10	B. FIELDS SEARCHED		
	Minimum documentation searched (classification system followed by classification symbols) H04W 72/25(2023.01); H04L 1/18(2006.01); H04L 5/00(2006.01); H04W 4/40(2018.01); H04W 72/04(2009.01)		
	Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched Korean utility models and applications for utility models: IPC as above Japanese utility models and applications for utility models: IPC as above		
15	Electronic data base consulted during the international search (name of data base and, where practicable, search terms used) eKOMPASS (KIPO internal) & keywords: PSFCH, SL PRS, RB set, not overlapping, bitmap, aggregated slot, symbol, RSRP, comb size, duplicate		
20	C. DOCUMENTS CONSIDERED TO BE RELEVANT		
	Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	X	WO 2021-066592 A1 (LG ELECTRONICS INC.) 08 April 2021 (2021-04-08) See paragraph [0114]; and claims 1-2.	1,14-20
25	Y		2-13
	Y	WO 2021-141468 A1 (LG ELECTRONICS INC.) 15 July 2021 (2021-07-15) See paragraphs [0141], [0206] and [0388]; and claims 9 and 12.	2-11,13
30	Y	WO 2021-223072 A1 (QUALCOMM INCORPORATED) 11 November 2021 (2021-11-11) See paragraphs [0146]-[0148]; and claim 15.	5-10.13
	Y	WO 2021-112610 A1 (LG ELECTRONICS INC.) 10 June 2021 (2021-06-10) See paragraph [0222]; and claim 1.	12
35	A	US 2021-0084462 A1 (LG ELECTRONICS INC.) 18 March 2021 (2021-03-18) See paragraphs [0206]-[0207]; and claim 1.	1-20
	<input type="checkbox"/> Further documents are listed in the continuation of Box C. <input checked="" type="checkbox"/> See patent family annex.		
40	* Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "D" document cited by the applicant in the international application "E" earlier application or patent but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art "&" document member of the same patent family		
45			
50	Date of the actual completion of the international search 20 July 2023		Date of mailing of the international search report 20 July 2023
55	Name and mailing address of the ISA/KR Korean Intellectual Property Office Government Complex-Daejeon Building 4, 189 Cheongsaro, Seo-gu, Daejeon 35208 Facsimile No. +82-42-481-8578		Authorized officer Telephone No.

Form PCT/ISA/210 (second sheet) (July 2022)

INTERNATIONAL SEARCH REPORT
Information on patent family members

International application No.

PCT/KR2023/005235

5

10

15

20

25

30

35

40

45

50

55

Patent document cited in search report				Publication date (day/month/year)		Patent family member(s)		Publication date (day/month/year)
WO	2021-066592	A1	08 April 2021	US	2022-0353035	A1	03 November 2022	
WO	2021-141468	A1	15 July 2021	US	2023-0101824	A1	30 March 2023	
WO	2021-223072	A1	11 November 2021	None				
WO	2021-112610	A1	10 June 2021	EP	4072195	A1	12 October 2022	
				KR	10-2022-0091509	A	30 June 2022	
US	2021-0084462	A1	18 March 2021	EP	3920452	A1	08 December 2021	
				JP	2022-522836	A	20 April 2022	
				JP	7154436	B2	17 October 2022	
				US	10873838	B2	22 December 2020	
				US	2020-0288286	A1	10 September 2020	

Form PCT/ISA/210 (patent family annex) (July 2022)

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Non-patent literature cited in the description

- 3GPP TS 36.355 [0111]