



(11) **EP 4 521 595 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
12.03.2025 Bulletin 2025/11

(51) International Patent Classification (IPC):
H02J 7/00^(2006.01)

(21) Application number: **25153079.6**

(52) Cooperative Patent Classification (CPC):
**A61B 17/07207; A61B 90/98; H02J 7/00036;
H02J 50/005; H02J 50/12; A61B 2017/00026;
A61B 2017/00084; A61B 2017/00221;
A61B 2017/00725; A61B 2017/00734;
A61B 2017/00929; A61B 2017/07264;
A61B 2017/07271; A61B 2017/07278;
A61B 2090/037;**

(Cont.)

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC MK MT NL NO
PL PT RO RS SE SI SK SM TR**

(30) Priority: **26.02.2021 US 202117186345**

(62) Document number(s) of the earlier application(s) in
accordance with Art. 76 EPC:
22707865.6 / 4 185 214

(71) Applicant: **Cilag GmbH International
6300 Zug (CH)**

(72) Inventors:
• **CREAMER, Patrick L.
New Orleans, 70118 (US)**

- **HUNTER, Morgan R.
Cincinnati, 45242 (US)**
- **SHELTON, IV, Frederick E.
Cincinnati, 45242 (US)**
- **HARRIS, Jason L.
Cincinnati, 45242 (US)**

(74) Representative: **Carpmaels & Ransford LLP
One Southampton Row
London WC1B 5HA (GB)**

Remarks:

This application was filed on 21-01-2025 as a
divisional application to the application mentioned
under INID code 62.

(54) **SURGICAL INSTRUMENT COMPRISING MEANS TO MEASURE A PHYSICAL PARAMETER**

(57) Disclosed is a surgical end effector for use with a surgical instrument. The surgical end effector comprises a jaw, and a staple cartridge seatable in the jaw. The staple cartridge comprises a sensor array configured to take measurements corresponding to a parameter associated with a function of the surgical instrument, a processor, and a memory storing program instructions. The

memory storing program instructions that, when executed by the processor, cause the processor to perform an initial calibration of the sensor array, determine an initial adjustment to the measurements based on the initial calibration, perform an in-use calibration of the sensor array, and modify the initial adjustment based on the in-use calibration.

(52) Cooperative Patent Classification (CPC): (Cont.)
A61B 2090/038; A61B 2090/065; H02J 1/14;
H02J 7/0013; H02J 7/0044; H02J 2310/23;
H02J 2310/52; H02J 2310/60

Description

BACKGROUND

[0001] The present invention relates to surgical instruments and, in various arrangements, to surgical stapling and cutting instruments and staple cartridges for use therewith that are designed to staple and cut tissue.

BRIEF DESCRIPTION OF THE DRAWINGS

[0002] Various features of the embodiments described herein, together with advantages thereof, may be understood in accordance with the following description taken in conjunction with the accompanying drawings as follows:

FIG. 1 is a perspective view of a surgical instrument in accordance with at least one embodiment;

FIG. 2 is a perspective view of a controller of a robotic surgical system;

FIG. 3 is a perspective view of the robotic surgical system of FIG. 2 comprising a plurality of robotic surgical arms which each operably support a surgical instrument thereon;

FIG. 4 is a side view of a robotic surgical arm illustrated in FIG. 3;

FIG. 5 is a perspective view of a staple cartridge in accordance with at least one embodiment;

FIG. 5A is an exploded view of the staple cartridge of FIG. 5;

FIG. 5B is a perspective view of the distal end of the staple cartridge of FIG. 5;

FIG. 5C is an elevational view of the distal end of the staple cartridge of FIG. 5;

FIG. 6 is a schematic of a communications system between a surgical instrument and a staple cartridge in accordance with at least one embodiment;

FIG. 7 is a schematic of a communications system between a surgical instrument and a staple cartridge in accordance with at least one embodiment;

FIG. 8 is a schematic of a communications system between a surgical instrument and a staple cartridge in accordance with at least one embodiment;

FIG. 8A is a segment of the schematic of FIG. 8;

FIG. 8B is a partial perspective view of the surgical instrument of FIG. 8 illustrated with some components removed;

FIG. 8C is a partial perspective view of a cartridge jaw of the surgical instrument of FIG. 8 illustrated with the staple cartridge removed;

FIG. 8D is a partial perspective view of the surgical instrument of FIG. 8 illustrated in a closed, or clamped, configuration;

FIG. 9 is a schematic of a communications system between a surgical instrument and a staple cartridge in accordance with at least one embodiment;

FIG. 10 is a schematic of a communications system

between a surgical instrument and a staple cartridge in accordance with at least one embodiment;

FIG. 11 is a perspective view of a staple cartridge positioned in a cartridge jaw in accordance with at least one embodiment;

FIG. 11A is a partial cross-sectional view of the staple cartridge of FIG. 11;

FIG. 11B is a perspective view of the staple cartridge of FIG. 11 removed from the cartridge jaw;

FIG. 11C is an exploded view of the staple cartridge of FIG. 11;

FIG. 11D is a perspective view of a sled of the staple cartridge of FIG. 11;

FIG. 12 is a perspective view of a staple cartridge in accordance with at least one embodiment;

FIG. 13 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for optimizing sensor data collection, transmission, and/or processing, in accordance with at least one aspect of the present disclosure;

FIG. 14 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for optimizing sensor data collection, transmission, and/or processing, in accordance with at least one aspect of the present disclosure;

FIG. 15 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for optimizing sensor data collection, transmission, and/or processing, in accordance with at least one aspect of the present disclosure;

FIG. 16 is a simplified schematic diagram illustrating various features of a surgical system, in accordance with at least one aspect of the present disclosure;

FIG. 17 is a simplified schematic diagram illustrating various features of a staple cartridge, in accordance with at least one aspect of the present disclosure;

FIG. 18 is a table illustrating a correlation between a sampling rate (S) of a sensor array and corresponding values of a bandwidth capacity (B), a discharge rate (D), and a remaining capacity (R), in accordance with at least one aspect of the present disclosure;

FIG. 19 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for monitoring and addressing signal interference in wireless power and/or data signal transmission, in accordance with at least one aspect of the present disclosure;

FIG. 20 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for transfer efficiency in wireless power transmission, in accordance with at least one aspect of the present disclosure;

FIG. 21 illustrates an implementation of a first antenna circuit and a second antenna circuit of a wireless transmission system of for power transfer between a surgical instrument 1022 and a staple cartridge, in accordance with at least one aspect of the present disclosure;

FIG. 22 illustrates an adjustable series RLC (resistor, inductor, capacitor) circuit, in accordance with at least one aspect of the present disclosure;

FIG. 23 illustrates an adjustable parallel RLC circuit, in accordance with at least one aspect of the present disclosure;

FIG. 24 is a graph illustrating a resonant state of the adjustable series RLC circuit 1130, in accordance with at least one aspect of the present disclosure;

FIG. 25 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for improving power conservation or optimizing power consumption by a staple cartridge, in accordance with at least one aspect of the present disclosure;

FIG. 26 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for optimizing a wireless transmission of power and/or data signal across a transmission system 1045, in accordance with at least one aspect of the present disclosure;

FIG. 27 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for calibrating a sensor array of a surgical instrument, in accordance with at least one aspect of the present disclosure;

FIG. 28 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for modulating a control parameter of the surgical instrument, in accordance with at least one aspect of the present disclosure;

FIG. 29 is a partial cross-sectional view of an end effector including a staple cartridge and an anvil separated by a stop member, in a closed configuration of the end effector with no tissue therebetween, in accordance with at least one aspect of the present disclosure;

FIG. 30 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for modulating a control parameter of the surgical instrument, in accordance with at least one aspect of the present disclosure;

FIG. 31 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for modulating a sensor parameter of the sensor array, in accordance with at least one aspect of the present disclosure;

FIG. 32 is a logic flow diagram of an algorithm depicting a control program or a logic configuration for modulating a sensor parameter of the sensor array, in accordance with at least one aspect of the present disclosure;

FIG. 33 is a top schematic view of a staple cartridge, in accordance with at least one aspect of the present disclosure;

FIG. 34 illustrates a diagram of a cartridge comprising a plurality of sensors coupled to a control circuit through a set of coils to transfer power and data

between the cartridge and a control circuit located in an instrument housing, in accordance with at least one aspect of the present disclosure;

FIG. 35 illustrates a block diagram of a surgical instrument configured or programmed to control the distal translation of a displacement member, in accordance with at least one aspect of the present disclosure;

FIG. 36 illustrates a perspective view of an end effector of a surgical stapling and cutting instrument, in accordance with at least one aspect of the present disclosure;

FIG. 37 depicts an example tissue compression sensor system, in accordance with at least one aspect of the present disclosure;

FIGS. 38A and 38B are schematic illustrations of a tissue contact circuit showing the completion of the circuit upon contact with tissue a pair of spaced apart contact plates, in accordance with at least one aspect of the present disclosure;

FIG. 39 is a schematic illustration of a surgical instrument comprising a sensor monitoring and processing circuit, in accordance with at least one aspect of the present disclosure;

FIG. 40 is a schematic illustration of a portion of an end effector comprising an anvil and staple cartridge including sensor arrays, in accordance with at least one aspect of the present disclosure;

FIG. 41 is a partial cutaway view of the cartridge of FIG. 40 comprising a plurality of independently addressable sensors, in accordance with at least one aspect of the present disclosure;

FIG. 42 illustrates a flow diagram of a method of monitoring multiple sensors, in accordance with at least one aspect of the present disclosure;

FIG. 43 illustrates a flow diagram of a method of monitoring multiple sensors, in accordance with at least one aspect of the present disclosure;

FIG. 44 illustrates a flow diagram of a method of monitoring multiple sensors, in accordance with at least one aspect of the present disclosure;

FIG. 45 illustrates a flow diagram of a method of monitoring multiple sensors, in accordance with at least one aspect of the present disclosure;

FIG. 46 is an exploded view of an end effector comprising a plurality of sensor arrays, in accordance with at least one aspect of the present disclosure;

FIG. 47 is a schematic illustration of the first and second sensor arrays positioned in the pan or retainer of the cartridge base, the first and second sensor arrays shown coupled to an electronic circuit, in accordance with at least one aspect of the present disclosure;

FIG. 48 illustrates a perspective view of a staple-forming pocket of an anvil of including an electrically conductive circuit element, in accordance with one or more aspects of the present disclosure;

FIG. 49 illustrates a perspective view of the staple-forming pocket of FIG. 48 after the electrically conductive circuit element has been severed by a staple leg during proper formation of the staple leg, in accordance with one or more aspects of the present disclosure;

FIG. 50 illustrates a distal sensor plug comprising an electronic circuit configured to monitor and process signals from the first and second sensor arrays, in accordance with at least one aspect of the present disclosure; and

FIG. 51 is a method of monitoring internal systems of a staple cartridge to detect and track motion status of cartridge components, in accordance with at least one aspect of the present disclosure.

[0003] Corresponding reference characters indicate corresponding parts throughout the several views. The exemplifications set out herein illustrate various embodiments of the invention, in one form, and such exemplifications are not to be construed as limiting the scope of the invention in any manner.

DETAILED DESCRIPTION

[0004] Applicant of the present application also owns the following U.S. Patent Applications that were filed on even date herewith and which are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application, entitled METHOD OF POWERING AND COMMUNICATING WITH A STAPLE CARTRIDGE; Attorney Docket No. END9295USNP1/200837-1M;
- U.S. Patent Application, entitled METHOD OF POWERING AND COMMUNICATING WITH A STAPLE CARTRIDGE; Attorney Docket No. END9295USNP2/200837-2M;
- U.S. Patent Application, entitled ADJUSTABLE COMMUNICATION BASED ON AVAILABLE BANDWIDTH AND POWER CAPACITY; Attorney Docket No. END9295USNP3/200837-3;
- U.S. Patent Application, entitled ADJUSTMENT TO TRANSFER PARAMETERS TO IMPROVE AVAILABLE POWER; Attorney Docket No. END9295USNP4/200837-4;
- U.S. Patent Application, entitled MONITORING OF MULTIPLE SENSORS OVER TIME TO DETECT MOVING CHARACTERISTICS OF TISSUE; Attorney Docket No. END9295USNP6/200837-6;
- U.S. Patent Application, entitled MONITORING OF INTERNAL SYSTEMS TO DETECT AND TRACK CARTRIDGE MOTION STATUS; Attorney Docket No. END9295USNP7/200837-7;
- U.S. Patent Application, entitled DISTAL COMMUNICATION ARRAY TO TUNE FREQUENCY OF RF SYSTEMS; Attorney Docket No. END9295USNP8/200837-8;

- U.S. Patent Application, entitled STAPLE CARTRIDGE COMPRISING A SENSOR ARRAY; Attorney Docket No. END9295USNP9/200837-9;
- U.S. Patent Application, entitled STAPLE CARTRIDGE COMPRISING A SENSING ARRAY AND A TEMPERATURE CONTROL SYSTEM; Attorney Docket No. END9295USNP10/200837-10;
- U.S. Patent Application, entitled STAPLE CARTRIDGE COMPRISING AN INFORMATION ACCESS CONTROL SYSTEM; Attorney Docket No. END9295USNP11/200837-11;
- U.S. Patent Application, entitled STAPLE CARTRIDGE COMPRISING A POWER MANAGEMENT CIRCUIT; Attorney Docket No. END9295USNP12/200837-12;
- U.S. Patent Application, entitled STAPLING INSTRUMENT COMPRISING A SEPARATE POWER ANTENNA AND A DATA TRANSFER ANTENNA; Attorney Docket No. END9295USNP13/200837-13;
- U.S. Patent Application, entitled SURGICAL INSTRUMENT SYSTEM COMPRISING A POWER TRANSFER COIL; Attorney Docket No. END9295USNP14/200837-14; and
- U.S. Patent Application, entitled STAPLING INSTRUMENT COMPRISING A SIGNAL ANTENNA; Attorney Docket No. END9295USNP15/200837-15.

[0005] Applicant of the present application also owns the following U.S. Patent Applications that were filed on October 29, 2020 and which are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application Serial No. 17/084,179, entitled SURGICAL INSTRUMENT COMPRISING A RELEASABLE CLOSURE DRIVE LOCK;
- U.S. Patent Application Serial No. 17/084,190, entitled SURGICAL INSTRUMENT COMPRISING A STOWED CLOSURE ACTUATOR STOP;
- U.S. Patent Application Serial No. 17/084,198, entitled SURGICAL INSTRUMENT COMPRISING AN INDICATOR WHICH INDICATES THAT AN ARTICULATION DRIVE IS ACTUATABLE;
- U.S. Patent Application Serial No. 17/084,205, entitled SURGICAL INSTRUMENT COMPRISING AN ARTICULATION INDICATOR;
- U.S. Patent Application Serial No. 17/084,258, entitled METHOD FOR OPERATING A SURGICAL INSTRUMENT;
- U.S. Patent Application Serial No. 17/084,206, entitled SURGICAL INSTRUMENT COMPRISING AN ARTICULATION LOCK;
- U.S. Patent Application Serial No. 17/084,215, entitled SURGICAL INSTRUMENT COMPRISING A JAW ALIGNMENT SYSTEM;
- U.S. Patent Application Serial No. 17/084,229, entitled SURGICAL INSTRUMENT COMPRISING SEALABLE INTERFACE;
- U.S. Patent Application Serial No. 17/084,180, en-

titled SURGICAL INSTRUMENT COMPRISING A LIMITED TRAVEL SWITCH;

- U.S. Design Patent Application Serial No. 29/756,615, Application entitled SURGICAL STAPLING ASSEMBLY;
- U.S. Design Patent Application Serial No. 29/756,620, entitled SURGICAL STAPLING ASSEMBLY;
- U.S. Patent Application Serial No. 17/084,188, entitled SURGICAL INSTRUMENT COMPRISING A STAGED VOLTAGE REGULATION START-UP SYSTEM; and
- U.S. Patent Application Serial No. 17/084,193, entitled SURGICAL INSTRUMENT COMPRISING A SENSOR CONFIGURED TO SENSE WHETHER AN ARTICULATION DRIVE OF THE SURGICAL INSTRUMENT IS ACTUATABLE.

[0006] Applicant of the present application also owns the following U.S. Patent Applications that were filed on April 11, 2020 and which are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application Serial No. 16/846,303, entitled METHODS FOR STAPLING TISSUE USING A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345353;
- U.S. Patent Application Serial No. 16/846,304, entitled ARTICULATION ACTUATORS FOR A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345354;
- U.S. Patent Application Serial No. 16/846,305, entitled ARTICULATION DIRECTIONAL LIGHTS ON A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345446;
- U.S. Patent Application Serial No. 16/846,307, entitled SHAFT ROTATION ACTUATOR ON A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/03453549;
- U.S. Patent Application Serial No. 16/846,308, entitled ARTICULATION CONTROL MAPPING FOR A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345355;
- U.S. Patent Application Serial No. 16/846,309, entitled INTELLIGENT FIRING ASSOCIATED WITH A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345356;
- U.S. Patent Application Serial No. 16/846,310, entitled INTELLIGENT FIRING ASSOCIATED WITH A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345357;
- U.S. Patent Application Serial No. 16/846,311, entitled ROTATABLE JAW TIP FOR A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345358;
- U.S. Patent Application Serial No. 16/846,312, entitled TISSUE STOP FOR A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No.

2020/0345359; and

- U.S. Patent Application Serial No. 16/846,313, entitled ARTICULATION PIN FOR A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0345360.

[0007] The entire disclosure of U.S. Provisional Patent Application Serial No. 62/840,715, entitled SURGICAL INSTRUMENT COMPRISING AN ADAPTIVE CONTROL SYSTEM, filed April 30, 2019, is hereby incorporated by reference herein.

[0008] Applicant of the present application owns the following U.S. Patent Applications that were filed on February 21, 2019 and which are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application Serial No. 16/281,658, entitled METHODS FOR CONTROLLING A POWERED SURGICAL STAPLER THAT HAS SEPARATE ROTARY CLOSURE AND FIRING SYSTEMS, now U.S. Patent Application Publication No. 2019/0298350;
- U.S. Patent Application Serial No. 16/281,670, entitled STAPLE CARTRIDGE COMPRISING A LOCKOUT KEY CONFIGURED TO LIFT A FIRING MEMBER, now U.S. Patent Application Publication No. 2019/0298340;
- U.S. Patent Application Serial No. 16/281,675, entitled SURGICAL STAPLERS WITH ARRANGEMENTS FOR MAINTAINING A FIRING MEMBER THEREOF IN A LOCKED CONFIGURATION UNLESS A COMPATIBLE CARTRIDGE HAS BEEN INSTALLED THEREIN, now U.S. Patent Application Publication No. 2019/0298354;
- U.S. Patent Application Serial No. 16/281,685, entitled SURGICAL INSTRUMENT COMPRISING CO-OPERATING LOCKOUT FEATURES, now U.S. Patent Application Publication No. 2019/0298341;
- U.S. Patent Application Serial No. 16/281,693, entitled SURGICAL STAPLING ASSEMBLY COMPRISING A LOCKOUT AND AN EXTERIOR ACCESS ORIFICE TO PERMIT ARTIFICIAL UNLOCKING OF THE LOCKOUT, now U.S. Patent Application Publication No. 2019/0298342;
- U.S. Patent Application Serial No. 16/281,704, entitled SURGICAL STAPLING DEVICES WITH FEATURES FOR BLOCKING ADVANCEMENT OF A CAMMING ASSEMBLY OF AN INCOMPATIBLE CARTRIDGE INSTALLED THEREIN, now U.S. Patent Application Publication No. 2019/0298356;
- U.S. Patent Application Serial No. 16/281,707, entitled STAPLING INSTRUMENT COMPRISING A DEACTIVATABLE LOCKOUT, now U.S. Patent Application Publication No. 2019/0298347;
- U.S. Patent Application Serial No. 16/281,741, entitled SURGICAL INSTRUMENT COMPRISING A JAW CLOSURE LOCKOUT, now U.S. Patent Appli-

cation Publication No. 2019/0298357;

- U.S. Patent Application Serial No. 16/281,762, entitled SURGICAL STAPLING DEVICES WITH CARTRIDGE COMPATIBLE CLOSURE AND FIRING LOCKOUT ARRANGEMENTS, now U.S. Patent Application Publication No. 2019/0298343;
- U.S. Patent Application Serial No. 16/281,666, entitled SURGICAL STAPLING DEVICES WITH IMPROVED ROTARY DRIVEN CLOSURE SYSTEMS, now U.S. Patent Application Publication No. 2019/0298352;
- U.S. Patent Application Serial No. 16/281,672, entitled SURGICAL STAPLING DEVICES WITH ASYMMETRIC CLOSURE FEATURES, now U.S. Patent Application Publication No. 2019/0298353;
- U.S. Patent Application Serial No. 16/281,678, entitled ROTARY DRIVEN FIRING MEMBERS WITH DIFFERENT ANVIL AND CHANNEL ENGAGEMENT FEATURES, now U.S. Patent Application Publication No. 2019/0298355; and
- U.S. Patent Application Serial No. 16/281,682, entitled SURGICAL STAPLING DEVICE WITH SEPARATE ROTARY DRIVEN CLOSURE AND FIRING SYSTEMS AND FIRING MEMBER THAT ENGAGES BOTH JAWS WHILE FIRING, now U.S. Patent Application Publication No. 2019/0298346.

[0009] Applicant of the present application owns the following U.S. Provisional Patent Applications that were filed on February 19, 2019 and which are each herein incorporated by reference in their respective entireties:

- U.S. Provisional Patent Application Serial No. 62/807,310, entitled METHODS FOR CONTROLLING A POWERED SURGICAL STAPLER THAT HAS SEPARATE ROTARY CLOSURE AND FIRING SYSTEMS;
- U.S. Provisional Patent Application Serial No. 62/807,319, entitled SURGICAL STAPLING DEVICES WITH IMPROVED LOCKOUT SYSTEMS; and
- U.S. Provisional Patent Application Serial No. 62/807,309, entitled SURGICAL STAPLING DEVICES WITH IMPROVED ROTARY DRIVEN CLOSURE SYSTEMS.

[0010] Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on March 28, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/649,302, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;
- U.S. Provisional Patent Application Serial No. 62/649,294, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND

CREATE ANONYMIZED RECORD;

- U.S. Provisional Patent Application Serial No. 62/649,300, entitled SURGICAL HUB SITUATIONAL AWARENESS;
- U.S. Provisional Patent Application Serial No. 62/649,309, entitled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;
- U.S. Provisional Patent Application Serial No. 62/649,310, entitled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS;
- U.S. Provisional Patent Application Serial No. 62/649,291, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;
- U.S. Provisional Patent Application Serial No. 62/649,296, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;
- U.S. Provisional Patent Application Serial No. 62/649,333, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;
- U.S. Provisional Patent Application Serial No. 62/649,327, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES;
- U.S. Provisional Patent Application Serial No. 62/649,315, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK;
- U.S. Provisional Patent Application Serial No. 62/649,313, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES;
- U.S. Provisional Patent Application Serial No. 62/649,320, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS;
- U.S. Provisional Patent Application Serial No. 62/649,307, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and
- U.S. Provisional Patent Application Serial No. 62/649,323, entitled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

[0011] Applicant of the present application owns the following U.S. Provisional Patent Application, filed on March 30, 2018, which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/650,887, entitled SURGICAL SYSTEMS WITH OPTIMIZED SENSING CAPABILITIES.

[0012] Applicant of the present application owns the following U.S. Patent Application, filed on December 4, 2018, which is herein incorporated by reference in its

entirety:

- U.S. Patent Application Serial No. 16/209,423, entitled METHOD OF COMPRESSING TISSUE WITHIN A STAPLING DEVICE AND SIMULTANEOUSLY DISPLAYING THE LOCATION OF THE TISSUE WITHIN THE JAWS, now U.S. Patent

[0013] Application Publication No. 2019/0200981.

[0014] Applicant of the present application owns the following U.S. Patent Applications that were filed on August 20, 2018 and which are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application Serial No. 16/105,101, entitled METHOD FOR FABRICATING SURGICAL STAPLER ANVILS, now U.S. Patent Application Publication No. 2020/0054323;
- U.S. Patent Application Serial No. 16/105,183, entitled REINFORCED DEFORMABLE ANVIL TIP FOR SURGICAL STAPLER ANVIL, now U.S. Patent No. 10,912,559;
- U.S. Patent Application Serial No. 16/105,150, entitled SURGICAL STAPLER ANVILS WITH STAPLE DIRECTING PROTRUSIONS AND TISSUE STABILITY FEATURES, now U.S. Patent Application Publication No. 2020/0054326; - U.S. Patent Application Serial No. 16/105,098, entitled FABRICATING TECHNIQUES FOR SURGICAL STAPLER ANVILS, now U.S. Patent Application Publication No. 2020/0054322;
- U.S. Patent Application Serial No. 16/105,140, entitled SURGICAL STAPLER ANVILS WITH TISSUE STOP FEATURES CONFIGURED TO AVOID TISSUE PINCH, now U.S. Patent No. 10,779,821;
- U.S. Patent Application Serial No. 16/105,081, entitled METHOD FOR OPERATING A POWERED ARTICULATABLE SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2020/0054320;
- U.S. Patent Application Serial No. 16/105,094, entitled SURGICAL INSTRUMENTS WITH PROGRESSIVE JAW CLOSURE ARRANGEMENTS, now U.S. Patent Application Publication No. 2020/0054321;
- U.S. Patent Application Serial No. 16/105,097, entitled POWERED SURGICAL INSTRUMENTS WITH CLUTCHING ARRANGEMENTS TO CONVERT LINEAR DRIVE MOTIONS TO ROTARY DRIVE MOTIONS, now U.S. Patent Application Publication No. 2020/0054328;
- U.S. Patent Application Serial No. 16/105,104, entitled POWERED ARTICULATABLE SURGICAL INSTRUMENTS WITH CLUTCHING AND LOCKING ARRANGEMENTS FOR LINKING AN ARTICULATION DRIVE SYSTEM TO A FIRING DRIVE SYSTEM, now U.S. Patent No. 10,842,492;
- U.S. Patent Application Serial No. 16/105,119, en-

titled ARTICULATABLE MOTOR POWERED SURGICAL INSTRUMENTS WITH DEDICATED ARTICULATION MOTOR ARRANGEMENTS, now U.S. Patent Application Publication No. 2020/0054330;

- U.S. Patent Application Serial No. 16/105,160, entitled SWITCHING ARRANGEMENTS FOR MOTOR POWERED ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Patent No. 10,856,870; and
- U.S. Design Patent Application Serial No. 29/660,252, entitled SURGICAL STAPLER ANVILS.

[0015] Applicant of the present application owns the following U.S. Patent Applications and U.S. Patents that are each herein incorporated by reference in their respective entireties:

- U.S. Patent Application Serial No. 15/386,185, entitled SURGICAL STAPLING INSTRUMENTS AND REPLACEABLE TOOL ASSEMBLIES THEREOF, now U.S. Patent No. 10,639,035;
- U.S. Patent Application Serial No. 15/386,230, entitled ARTICULATABLE SURGICAL STAPLING INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168649;
- U.S. Patent Application Serial No. 15/386,221, entitled LOCKOUT ARRANGEMENTS FOR SURGICAL END EFFECTORS, now U.S. Patent No. 10,835,247;
- U.S. Patent Application Serial No. 15/386,209, entitled SURGICAL END EFFECTORS AND FIRING MEMBERS THEREOF, now U.S. Patent No. 10,588,632;
- U.S. Patent Application Serial No. 15/386,198, entitled LOCKOUT ARRANGEMENTS FOR SURGICAL END EFFECTORS AND REPLACEABLE TOOL ASSEMBLIES, now U.S. Patent No. 10,610,224;
- U.S. Patent Application Serial No. 15/386,240, entitled SURGICAL END EFFECTORS AND ADAPTABLE FIRING MEMBERS THEREFOR, now U.S. Patent Application Publication No. 2018/0168651;
- U.S. Patent Application Serial No. 15/385,939, entitled STAPLE CARTRIDGES AND ARRANGEMENTS OF STAPLES AND STAPLE CAVITIES THEREIN, now U.S. Patent No. 10,835,246;
- U.S. Patent Application Serial No. 15/385,941, entitled SURGICAL TOOL ASSEMBLIES WITH CLUTCHING ARRANGEMENTS FOR SHIFTING BETWEEN CLOSURE SYSTEMS WITH CLOSURE STROKE REDUCTION FEATURES AND ARTICULATION AND FIRING SYSTEMS, now U.S. Patent No. 10,736,629;
- U.S. Patent Application Serial No. 15/385,943, entitled SURGICAL STAPLING INSTRUMENTS AND STAPLE-FORMING ANVILS, now U.S. Patent No. 10,667,811;
- U.S. Patent Application Serial No. 15/385,950, en-

- titled SURGICAL TOOL ASSEMBLIES WITH CLOSURE STROKE REDUCTION FEATURES, now U.S. Patent No. 10,588,630;
- U.S. Patent Application Serial No. 15/385,945, entitled STAPLE CARTRIDGES AND ARRANGEMENTS OF STAPLES AND STAPLE CAVITIES THEREIN, now U.S. Patent No. 10,893,864;
 - U.S. Patent Application Serial No. 15/385,946, entitled SURGICAL STAPLING INSTRUMENTS AND STAPLE-FORMING ANVILS, now U.S. Patent Application Publication No. 2018/0168633;
 - U.S. Patent Application Serial No. 15/385,951, entitled SURGICAL INSTRUMENTS WITH JAW OPENING FEATURES FOR INCREASING A JAW OPENING DISTANCE, now U.S. Patent No. 10,568,626;
 - U.S. Patent Application Serial No. 15/385,953, entitled METHODS OF STAPLING TISSUE, now U.S. Patent No. 10,675,026;
 - U.S. Patent Application Serial No. 15/385,954, entitled FIRING MEMBERS WITH NON-PARALLEL JAW ENGAGEMENT FEATURES FOR SURGICAL END EFFECTORS, now U.S. Patent No. 10,624,635;
 - U.S. Patent Application Serial No. 15/385,955, entitled SURGICAL END EFFECTORS WITH EXPANDABLE TISSUE STOP ARRANGEMENTS, now U.S. Patent No. 10,813,638;
 - U.S. Patent Application Serial No. 15/385,948, entitled SURGICAL STAPLING INSTRUMENTS AND STAPLE-FORMING ANVILS, now U.S. Patent Application Publication No. 2018/0168584;
 - U.S. Patent Application Serial No. 15/385,956, entitled SURGICAL INSTRUMENTS WITH POSITIVE JAW OPENING FEATURES, now U.S. Patent No. 10,588,631 ;
 - U.S. Patent Application Serial No. 15/385,958, entitled SURGICAL INSTRUMENTS WITH LOCKOUT ARRANGEMENTS FOR PREVENTING FIRING SYSTEM ACTUATION UNLESS AN UNSPENT STAPLE CARTRIDGE IS PRESENT, now U.S. Patent No. 10,639,034;
 - U.S. Patent Application Serial No. 15/385,947, entitled STAPLE CARTRIDGES AND ARRANGEMENTS OF STAPLES AND STAPLE CAVITIES THEREIN, now U.S. Patent No. 10,568,625;
 - U.S. Patent Application Serial No. 15/385,896, entitled METHOD FOR RESETTING A FUSE OF A SURGICAL INSTRUMENT SHAFT, now U.S. Patent Application Publication No. 2018/0168597;
 - U.S. Patent Application Serial No. 15/385,898, entitled STAPLE-FORMING POCKET ARRANGEMENT TO ACCOMMODATE DIFFERENT TYPES OF STAPLES, now U.S. Patent No. 10,537,325;
 - U.S. Patent Application Serial No. 15/385,899, entitled SURGICAL INSTRUMENT COMPRISING IMPROVED JAW CONTROL, now U.S. Patent No. 10,758,229;
- U.S. Patent Application Serial No. 15/385,901, entitled STAPLE CARTRIDGE AND STAPLE CARTRIDGE CHANNEL COMPRISING WINDOWS DEFINED THEREIN, now U.S. Patent No. 10,667,809;
 - U.S. Patent Application Serial No. 15/385,902, entitled SURGICAL INSTRUMENT COMPRISING A CUTTING MEMBER, now U.S. Patent No. 10,888,322;
 - U.S. Patent Application Serial No. 15/385,904, entitled STAPLE FIRING MEMBER COMPRISING A MISSING CARTRIDGE AND/OR SPENT CARTRIDGE LOCKOUT, now U.S. Patent No. 10,881,401;
 - U.S. Patent Application Serial No. 15/385,905, entitled FIRING ASSEMBLY COMPRISING A LOCKOUT, now U.S. Patent No. 10,695,055;
 - U.S. Patent Application Serial No. 15/385,907, entitled SURGICAL INSTRUMENT SYSTEM COMPRISING AN END EFFECTOR LOCKOUT AND A FIRING ASSEMBLY LOCKOUT, now U.S. Patent Application Publication No. 2018/0168608;
 - U.S. Patent Application Serial No. 15/385,908, entitled FIRING ASSEMBLY COMPRISING A FUSE, now U.S. Patent Application Publication No. 2018/0168609;
 - U.S. Patent Application Serial No. 15/385,909, entitled FIRING ASSEMBLY COMPRISING A MULTIPLE FAILED-STATE FUSE, now U.S. Patent Application Publication No. 2018/0168610;
 - U.S. Patent Application Serial No. 15/385,920, entitled STAPLE-FORMING POCKET ARRANGEMENTS, now U.S. Patent No. 10,499,914;
 - U.S. Patent Application Serial No. 15/385,913, entitled ANVIL ARRANGEMENTS FOR SURGICAL STAPLERS, now U.S. Patent Application Publication No. 2018/0168614;
 - U.S. Patent Application Serial No. 15/385,914, entitled METHOD OF DEFORMING STAPLES FROM TWO DIFFERENT TYPES OF STAPLE CARTRIDGES WITH THE SAME SURGICAL STAPLING INSTRUMENT, now U.S. Patent Application Publication No. 2018/0168615;
 - U.S. Patent Application Serial No. 15/385,893, entitled BILATERALLY ASYMMETRIC STAPLE-FORMING POCKET PAIRS, now U.S. Patent No. 10,682,138;
 - U.S. Patent Application Serial No. 15/385,929, entitled CLOSURE MEMBERS WITH CAM SURFACE ARRANGEMENTS FOR SURGICAL INSTRUMENTS WITH SEPARATE AND DISTINCT CLOSURE AND FIRING SYSTEMS, now U.S. Patent No. 10,667,810;
 - U.S. Patent Application Serial No. 15/385,911, entitled SURGICAL STAPLERS WITH INDEPENDENTLY ACTUATABLE CLOSING AND FIRING SYSTEMS, now U.S. Patent No. 10,448,950;
 - U.S. Patent Application Serial No. 15/385,927, entitled SURGICAL STAPLING INSTRUMENTS WITH

- SMART STAPLE CARTRIDGES, now U.S. Patent Application Publication No. 2018/0168625;
- U.S. Patent Application Serial No. 15/385,917, entitled STAPLE CARTRIDGE COMPRISING STAPLES WITH DIFFERENT CLAMPING BREADTHS, now U.S. Patent Application Publication No. 2018/0168617; 5
 - U.S. Patent Application Serial No. 15/385,900, entitled STAPLE-FORMING POCKET ARRANGEMENTS COMPRISING PRIMARY SIDEWALLS AND POCKET SIDEWALLS, now U.S. Patent No. 10,898,186; 10
 - U.S. Patent Application Serial No. 15/385,931, entitled NO-CARTRIDGE AND SPENT CARTRIDGE LOCKOUT ARRANGEMENTS FOR SURGICAL STAPLERS, now U.S. Patent Application Publication No. 2018/0168627; 15
 - U.S. Patent Application Serial No. 15/385,915, entitled FIRING MEMBER PIN ANGLE, now U.S. Patent No. 10,779,823; 20
 - U.S. Patent Application Serial No. 15/385,897, entitled STAPLE-FORMING POCKET ARRANGEMENTS COMPRISING ZONED FORMING SURFACE GROOVES, now U.S. Patent Application Publication No. 2018/0168598; 25
 - U.S. Patent Application Serial No. 15/385,922, entitled SURGICAL INSTRUMENT WITH MULTIPLE FAILURE RESPONSE MODES, now U.S. Patent No. 10,426,471;
 - U.S. Patent Application Serial No. 15/385,924, entitled SURGICAL INSTRUMENT WITH PRIMARY AND SAFETY PROCESSORS, now U.S. Patent No. 10,758,230; 30
 - U.S. Patent Application Serial No. 15/385,910, entitled ANVIL HAVING A KNIFE SLOT WIDTH, now U.S. Patent No. 10,485,543; 35
 - U.S. Patent Application Serial No. 15/385,903, entitled CLOSURE MEMBER ARRANGEMENTS FOR SURGICAL INSTRUMENTS, now U.S. Patent No. 10,617,414; 40
 - U.S. Patent Application Serial No. 15/385,906, entitled FIRING MEMBER PIN CONFIGURATIONS, now U.S. Patent No. 10,856,868;
 - U.S. Patent Application Serial No. 15/386,188, entitled STEPPED STAPLE CARTRIDGE WITH ASYMMETRICAL STAPLES, now U.S. Patent No. 10,537,324; 45
 - U.S. Patent Application Serial No. 15/386,192, entitled STEPPED STAPLE CARTRIDGE WITH TISSUE RETENTION AND GAP SETTING FEATURES, now U.S. Patent No. 10,687,810; 50
 - U.S. Patent Application Serial No. 15/386,206, entitled STAPLE CARTRIDGE WITH DEFORMABLE DRIVER RETENTION FEATURES, now U.S. Patent Application Publication No. 2018/0168586; 55
 - U.S. Patent Application Serial No. 15/386,226, entitled DURABILITY FEATURES FOR END EFFECTORS AND FIRING ASSEMBLIES OF SURGICAL
- STAPLING INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168648;
- U.S. Patent Application Serial No. 15/386,222, entitled SURGICAL STAPLING INSTRUMENTS HAVING END EFFECTORS WITH POSITIVE OPENING FEATURES, now U.S. Patent Application Publication No. 2018/0168647;
 - U.S. Patent Application Serial No. 15/386,236, entitled CONNECTION PORTIONS FOR DEPOSABLE LOADING UNITS FOR SURGICAL STAPLING INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168650;
 - U.S. Patent Application Serial No. 15/385,887, entitled METHOD FOR ATTACHING A SHAFT ASSEMBLY TO A SURGICAL INSTRUMENT AND, ALTERNATIVELY, TO A SURGICAL ROBOT, now U.S. Patent No. 10,835,245;
 - U.S. Patent Application Serial No. 15/385,889, entitled SHAFT ASSEMBLY COMPRISING A MANUALLY-OPERABLE RETRACTION SYSTEM FOR USE WITH A MOTORIZED SURGICAL INSTRUMENT SYSTEM, now U.S. Patent Application Publication No. 2018/0168590;
 - U.S. Patent Application Serial No. 15/385,890, entitled SHAFT ASSEMBLY COMPRISING SEPARATELY ACTUATABLE AND RETRACTABLE SYSTEMS, now U.S. Patent No. 10,675,025;
 - U.S. Patent Application Serial No. 15/385,891, entitled SHAFT ASSEMBLY COMPRISING A CLUTCH CONFIGURED TO ADAPT THE OUTPUT OF A ROTARY FIRING MEMBER TO TWO DIFFERENT SYSTEMS, now U.S. Patent Application Publication No. 2018/0168592;
 - U.S. Patent Application Serial No. 15/385,892, entitled SURGICAL SYSTEM COMPRISING A FIRING MEMBER ROTATABLE INTO AN ARTICULATION STATE TO ARTICULATE AN END EFFECTOR OF THE SURGICAL SYSTEM, now U.S. Patent No. 10,918,385;
 - U.S. Patent Application Serial No. 15/385,894, entitled SHAFT ASSEMBLY COMPRISING A LOCKOUT, now U.S. Patent No. 10,492,785;
 - U.S. Patent Application Serial No. 15/385,895, entitled SHAFT ASSEMBLY COMPRISING FIRST AND SECOND ARTICULATION LOCKOUTS, now U.S. Patent No. 10,542,982;
 - U.S. Patent Application Serial No. 15/385,916, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168575;
 - U.S. Patent Application Serial No. 15/385,918, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168618;
 - U.S. Patent Application Serial No. 15/385,919, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168619;
 - U.S. Patent Application Serial No. 15/385,921, entitled SURGICAL STAPLE CARTRIDGE WITH MOVABLE CAMMING MEMBER CONFIGURED TO

- DISENGAGE FIRING MEMBER LOCKOUT FEATURES, now U.S. Patent No. 10,687,809;
- U.S. Patent Application Serial No. 15/385,923, entitled SURGICAL STAPLING SYSTEMS, now U.S. Patent Application Publication No. 2018/0168623;
 - U.S. Patent Application Serial No. 15/385,925, entitled JAW ACTUATED LOCK ARRANGEMENTS FOR PREVENTING ADVANCEMENT OF A FIRING MEMBER IN A SURGICAL END EFFECTOR UNLESS AN UNFIRED CARTRIDGE IS INSTALLED IN THE END EFFECTOR, now U.S. Patent No. 10,517,595;
 - U.S. Patent Application Serial No. 15/385,926, entitled AXIALLY MOVABLE CLOSURE SYSTEM ARRANGEMENTS FOR APPLYING CLOSURE MOTIONS TO JAWS OF SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2018/0168577;
 - U.S. Patent Application Serial No. 15/385,928, entitled PROTECTIVE COVER ARRANGEMENTS FOR A JOINT INTERFACE BETWEEN A MOVABLE JAW AND ACTUATOR SHAFT OF A SURGICAL INSTRUMENT, now U.S. Patent Application Publication No. 2018/0168578;
 - U.S. Patent Application Serial No. 15/385,930, entitled SURGICAL END EFFECTOR WITH TWO SEPARATE COOPERATING OPENING FEATURES FOR OPENING AND CLOSING END EFFECTOR JAWS, now U.S. Patent Application Publication No. 2018/0168579;
 - U.S. Patent Application Serial No. 15/385,932, entitled ARTICULATABLE SURGICAL END EFFECTOR WITH ASYMMETRIC SHAFT ARRANGEMENT, now U.S. Patent Application Publication No. 2018/0168628;
 - U.S. Patent Application Serial No. 15/385,933, entitled ARTICULATABLE SURGICAL INSTRUMENT WITH INDEPENDENT PIVOTABLE LINKAGE DISTAL OF AN ARTICULATION LOCK, now U.S. Patent No. 10,603,036;
 - U.S. Patent Application Serial No. 15/385,934, entitled ARTICULATION LOCK ARRANGEMENTS FOR LOCKING AN END EFFECTOR IN AN ARTICULATED POSITION IN RESPONSE TO ACTUATION OF A JAW CLOSURE SYSTEM, now U.S. Patent No. 10,582,928;
 - U.S. Patent Application Serial No. 15/385,935, entitled Laterally Actuable Articulation Lock Arrangements for Locking an End Effector of a Surgical Instrument in an Articulated Configuration, now U.S. Patent No. 10,524,789;
 - U.S. Patent Application Serial No. 15/385,936, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH ARTICULATION STROKE AMPLIFICATION FEATURES, now U.S. Patent No. 10,517,596;
 - U.S. Patent Application Serial No. 14/318,996, en-

titled FASTENER CARTRIDGES INCLUDING EXTENSIONS HAVING DIFFERENT CONFIGURATIONS, now U.S. Patent Application Publication No. 2015/0297228;

- 5 - U.S. Patent Application Serial No. 14/319,006, entitled FASTENER CARTRIDGE COMPRISING FASTENER CAVITIES INCLUDING FASTENER CONTROL FEATURES, now U.S. Patent No. 10,010,324;
- 10 - U.S. Patent Application Serial No. 14/318,991, entitled SURGICAL FASTENER CARTRIDGES WITH DRIVER STABILIZING ARRANGEMENTS, now U.S. Patent No. 9,833,241 ;
- U.S. Patent Application Serial No. 14/319,004, entitled SURGICAL END EFFECTORS WITH FIRING ELEMENT MONITORING ARRANGEMENTS, now U.S. Patent No. 9,844,369;
- U.S. Patent Application Serial No. 14/319,008, entitled FASTENER CARTRIDGE COMPRISING NON-UNIFORM FASTENERS, now U.S. Patent No. 10,299,792;
- U.S. Patent Application Serial No. 14/318,997, entitled FASTENER CARTRIDGE COMPRISING DEPLOYABLE TISSUE ENGAGING MEMBERS, now U.S. Patent No. 10,561,422;
- 25 - U.S. Patent Application Serial No. 14/319,002, entitled FASTENER CARTRIDGE COMPRISING TISSUE CONTROL FEATURES, now U.S. Patent No. 9,877,721;
- 30 - U.S. Patent Application Serial No. 14/319,013, entitled FASTENER CARTRIDGE ASSEMBLIES AND STAPLE RETAINER COVER ARRANGEMENTS, now U.S. Patent Application Publication No. 2015/0297233; and
- 35 - U.S. Patent Application Serial No. 14/319,016, entitled FASTENER CARTRIDGE INCLUDING A LAYER ATTACHED THERETO, now U.S. Patent No. 10,470,768.

40 **[0016]** Applicant of the present application owns the following U.S. Patent Applications that were filed on June 24, 2016 and which are each herein incorporated by reference in their respective entireties:

- 45 - U.S. Patent Application Serial No. 15/191,775, entitled STAPLE CARTRIDGE COMPRISING WIRE STAPLES AND STAMPED STAPLES, now U.S. Patent Application Publication No. 2017/0367695;
- U.S. Patent Application Serial No. 15/191,807, entitled STAPLING SYSTEM FOR USE WITH WIRE STAPLES AND STAMPED STAPLES, now U.S. Patent No. 10,702,270;
- 50 - U.S. Patent Application Serial No. 15/191,834, entitled STAMPED STAPLES AND STAPLE CARTRIDGES USING THE SAME, now U.S. Patent No. 10,542,979;
- 55 - U.S. Patent Application Serial No. 15/191,788, entitled STAPLE CARTRIDGE COMPRISING OVER-

DRIVEN STAPLES, now U.S. Patent No. 10,675,024; and

- U.S. Patent Application Serial No. 15/191,818, entitled STAPLE CARTRIDGE COMPRISING OFF-SET LONGITUDINAL STAPLE ROWS, now U.S. Patent No. 10,893,863.

[0017] Applicant of the present application owns the following U.S. Patent Applications that were filed on June 24, 2016 and which are each herein incorporated by reference in their respective entireties:

- U.S. Design Patent Application Serial No. 29/569,218, entitled SURGICAL FASTENER, now U.S. Design Patent No. D826,405;
- U.S. Design Patent Application Serial No. 29/569,227, entitled SURGICAL FASTENER, now U.S. Design Patent No. D822,206;
- U.S. Design Patent Application Serial No. 29/569,259, entitled SURGICAL FASTENER CARTRIDGE, now U.S. Design Patent No. D847,989; and
- U.S. Design Patent Application Serial No. 29/569,264, entitled SURGICAL FASTENER CARTRIDGE, now U.S. Design Patent No. D850,617.

[0018] Applicant of the present application owns the following patent applications that were filed on April 1, 2016 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 15/089,325, entitled METHOD FOR OPERATING A SURGICAL STAPLING SYSTEM, now U.S. Patent Application Publication No. 2017/0281171;
- U.S. Patent Application Serial No. 15/089,321, entitled MODULAR SURGICAL STAPLING SYSTEM COMPRISING A DISPLAY, now U.S. Patent No. 10,271,851;
- U.S. Patent Application Serial No. 15/089,326, entitled SURGICAL STAPLING SYSTEM COMPRISING A DISPLAY INCLUDING A RE-ORIENTABLE DISPLAY FIELD, now U.S. Patent No. 10,433,849;
- U.S. Patent Application Serial No. 15/089,263, entitled SURGICAL INSTRUMENT HANDLE ASSEMBLY WITH RECONFIGURABLE GRIP PORTION, now U.S. Patent No. 10,307,159;
- U.S. Patent Application Serial No. 15/089,262, entitled ROTARY POWERED SURGICAL INSTRUMENT WITH MANUALLY ACTUATABLE BAILOUT SYSTEM, now U.S. Patent No. 10,357,246;
- U.S. Patent Application Serial No. 15/089,277, entitled SURGICAL CUTTING AND STAPLING END EFFECTOR WITH ANVIL CONCENTRIC DRIVE MEMBER, now U.S. Patent No. 10,531,874;
- U.S. Patent Application Serial No. 15/089,296, entitled INTERCHANGEABLE SURGICAL TOOL ASSEMBLY WITH A SURGICAL END EFFECTOR

THAT IS SELECTIVELY ROTATABLE ABOUT A SHAFT AXIS, now U.S. Patent No. 10,413,293;

- U.S. Patent Application Serial No. 15/089,258, entitled SURGICAL STAPLING SYSTEM COMPRISING A SHIFTABLE TRANSMISSION, now U.S. Patent No. 10,342,543;
- U.S. Patent Application Serial No. 15/089,278, entitled SURGICAL STAPLING SYSTEM CONFIGURED TO PROVIDE SELECTIVE CUTTING OF TISSUE, now U.S. Patent No. 10,420,552;
- U.S. Patent Application Serial No. 15/089,284, entitled SURGICAL STAPLING SYSTEM COMPRISING A CONTOURABLE SHAFT, now U.S. Patent Application Publication No. 2017/0281186;
- U.S. Patent Application Serial No. 15/089,295, entitled SURGICAL STAPLING SYSTEM COMPRISING A TISSUE COMPRESSION LOCKOUT, now U.S. Patent 10,856,867;
- U.S. Patent Application Serial No. 15/089,300, entitled SURGICAL STAPLING SYSTEM COMPRISING AN UNCLAMPING LOCKOUT, now U.S. Patent No. 10,456,140;
- U.S. Patent Application Serial No. 15/089,196, entitled SURGICAL STAPLING SYSTEM COMPRISING A JAW CLOSURE LOCKOUT, now U.S. Patent No. 10,568,632;
- U.S. Patent Application Serial No. 15/089,203, entitled SURGICAL STAPLING SYSTEM COMPRISING A JAW ATTACHMENT LOCKOUT, now U.S. Patent No. 10,542,991;
- U.S. Patent Application Serial No. 15/089,210, entitled SURGICAL STAPLING SYSTEM COMPRISING A SPENT CARTRIDGE LOCKOUT, now U.S. Patent No. 10,478,190;
- U.S. Patent Application Serial No. 15/089,324, entitled SURGICAL INSTRUMENT COMPRISING A SHIFTING MECHANISM, now U.S. Patent No. 10,314,582;
- U.S. Patent Application Serial No. 15/089,335, entitled SURGICAL STAPLING INSTRUMENT COMPRISING MULTIPLE LOCKOUTS, now U.S. Patent No. 10,485,542;
- U.S. Patent Application Serial No. 15/089,339, entitled SURGICAL STAPLING INSTRUMENT, now U.S. Patent Application Publication No. 2017/0281173;
- U.S. Patent Application Serial No. 15/089,253, entitled SURGICAL STAPLING SYSTEM CONFIGURED TO APPLY ANNULAR ROWS OF STAPLES HAVING DIFFERENT HEIGHTS, now U.S. Patent No. 10,413,297;
- U.S. Patent Application Serial No. 15/089,304, entitled SURGICAL STAPLING SYSTEM COMPRISING A GROOVED FORMING POCKET, now U.S. Patent No. 10,285,705;
- U.S. Patent Application Serial No. 15/089,331, entitled ANVIL MODIFICATION MEMBERS FOR SURGICAL STAPLERS, now U.S. Patent No.

- 10,376,263;
- U.S. Patent Application Serial No. 15/089,336, entitled STAPLE CARTRIDGES WITH ATRAUMATIC FEATURES, now U.S. Patent No. 10,709,446;
 - U.S. Patent Application Serial No. 15/089,312, entitled CIRCULAR STAPLING SYSTEM COMPRISING AN INCISABLE TISSUE SUPPORT, now U.S. Patent Application Publication No. 2017/0281189;
 - U.S. Patent Application Serial No. 15/089,309, entitled CIRCULAR STAPLING SYSTEM COMPRISING ROTARY FIRING SYSTEM, now U.S. Patent No. 10,675,021; and
 - U.S. Patent Application Serial No. 15/089,349, entitled CIRCULAR STAPLING SYSTEM COMPRISING LOAD CONTROL, now U.S. Patent No. 10,682,136.

[0019] Applicant of the present application also owns the U.S. Patent Applications identified below which were filed on December 30, 2015 which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/984,488, entitled MECHANISMS FOR COMPENSATING FOR BATTERY PACK FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent No. 10,292,704;
- U.S. Patent Application Serial No. 14/984,525, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent No. 10,368,865; and
- U.S. Patent Application Serial No. 14/984,552, entitled SURGICAL INSTRUMENTS WITH SEPARABLE MOTORS AND MOTOR CONTROL CIRCUITS, now U.S. Patent No. 10,265,068.

[0020] Applicant of the present application also owns the U.S. Patent Applications identified below which were filed on February 9, 2016, which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 15/019,220, entitled SURGICAL INSTRUMENT WITH ARTICULATING AND AXIALLY TRANSLATABLE END EFFECTOR, now U.S. Patent No. 10,245,029;
- U.S. Patent Application Serial No. 15/019,228, entitled SURGICAL INSTRUMENTS WITH MULTIPLE LINK ARTICULATION ARRANGEMENTS, now U.S. Patent No. 10,433,837;
- U.S. Patent Application Serial No. 15/019,196, entitled SURGICAL INSTRUMENT ARTICULATION MECHANISM WITH SLOTTED SECONDARY CONSTRAINT, now U.S. Patent No. 10,413,291;
- U.S. Patent Application Serial No. 15/019,206, entitled SURGICAL INSTRUMENTS WITH AN END EFFECTOR THAT IS HIGHLY ARTICULATABLE RELATIVE TO AN ELONGATE SHAFT ASSEMBLY,

- now U.S. Patent No. 10,653,413;
- U.S. Patent Application Serial No. 15/019,215, entitled SURGICAL INSTRUMENTS WITH NON-SYMMETRICAL ARTICULATION ARRANGEMENTS, now U.S. Patent Application Publication No. 2017/0224332;
- U.S. Patent Application Serial No. 15/019,227, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH SINGLE ARTICULATION LINK ARRANGEMENTS, now U.S. Patent Application Publication No. 2017/0224334;
- U.S. Patent Application Serial No. 15/019,235, entitled SURGICAL INSTRUMENTS WITH TENSIONING ARRANGEMENTS FOR CABLE DRIVEN ARTICULATION SYSTEMS, now U.S. Patent No. 10,245,030;
- U.S. Patent Application Serial No. 15/019,230, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH OFF-AXIS FIRING BEAM ARRANGEMENTS, now U.S. Patent No. 10,588,625; and
- U.S. Patent Application Serial No. 15/019,245, entitled SURGICAL INSTRUMENTS WITH CLOSURE STROKE REDUCTION ARRANGEMENTS, now U.S. Patent No. 10,470,764.

[0021] Applicant of the present application also owns the U.S. Patent Applications identified below which were filed on February 12, 2016, which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 15/043,254, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent No. 10,258,331;
- U.S. Patent Application Serial No. 15/043,259, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent No. 10,448,948;
- U.S. Patent Application Serial No. 15/043,275, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2017/0231627; and
- U.S. Patent Application Serial No. 15/043,289, entitled MECHANISMS FOR COMPENSATING FOR DRIVETRAIN FAILURE IN POWERED SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2017/0231628.

[0022] Applicant of the present application owns the following patent applications that were filed on June 18, 2015 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/742,925, entitled SURGICAL END EFFECTORS WITH POSITIVE JAW OPENING ARRANGEMENTS, now U.S.

- Patent No. 10,182,818;
- U.S. Patent Application Serial No. 14/742,941, entitled SURGICAL END EFFECTORS WITH DUAL CAM ACTUATED JAW CLOSING FEATURES, now U.S. Patent No. 10,052,102;
 - U.S. Patent Application Serial No. 14/742,933, entitled SURGICAL STAPLING INSTRUMENTS WITH LOCKOUT ARRANGEMENTS FOR PREVENTING FIRING SYSTEM ACTUATION WHEN A CARTRIDGE IS SPENT OR MISSING, now U.S. Patent No. 10,154,841 ;
 - U.S. Patent Application Serial No. 14/742,914, entitled MOVABLE FIRING BEAM SUPPORT ARRANGEMENTS FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Patent No. 10,405,863;
 - U.S. Patent Application Serial No. 14/742,900, entitled ARTICULATABLE SURGICAL INSTRUMENTS WITH COMPOSITE FIRING BEAM STRUCTURES WITH CENTER FIRING SUPPORT MEMBER FOR ARTICULATION SUPPORT, now U.S. Patent No. 10,335,149;
 - U.S. Patent Application Serial No. 14/742,885, entitled DUAL ARTICULATION DRIVE SYSTEM ARRANGEMENTS FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Patent No. 10,368,861 ; and
 - U.S. Patent Application Serial No. 14/742,876, entitled PUSH/PULL ARTICULATION DRIVE SYSTEMS FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Patent No. 10,178,992.

[0023] Applicant of the present application owns the following patent applications that were filed on March 6, 2015 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/640,746, entitled POWERED SURGICAL INSTRUMENT, now U.S. Patent No. 9,808,246;
- U.S. Patent Application Serial No. 14/640,795, entitled MULTIPLE LEVEL THRESHOLDS TO MODIFY OPERATION OF POWERED SURGICAL INSTRUMENTS, now U.S. Patent No. 10,441,279;
- U.S. Patent Application Serial No. 14/640,832, entitled ADAPTIVE TISSUE COMPRESSION TECHNIQUES TO ADJUST CLOSURE RATES FOR MULTIPLE TISSUE TYPES, now U.S. Patent No. 10,687,806;
- U.S. Patent Application Serial No. 14/640,935, entitled OVERLAID MULTI SENSOR RADIO FREQUENCY (RF) ELECTRODE SYSTEM TO MEASURE TISSUE COMPRESSION, now U.S. Patent No. 10,548,504;
- U.S. Patent Application Serial No. 14/640,831, entitled MONITORING SPEED CONTROL AND PRECISION INCREMENTING OF MOTOR FOR POWERED SURGICAL INSTRUMENTS, now U.S. Pa-

tent No. 9,895,148;

- U.S. Patent Application Serial No. 14/640,859, entitled TIME DEPENDENT EVALUATION OF SENSOR DATA TO DETERMINE STABILITY, CREEP, AND VISCOELASTIC ELEMENTS OF MEASURES, now U.S. Patent No. 10,052,044;
- U.S. Patent Application Serial No. 14/640,817, entitled INTERACTIVE FEEDBACK SYSTEM FOR POWERED SURGICAL INSTRUMENTS, now U.S. Patent No. 9,924,961;
- U.S. Patent Application Serial No. 14/640,844, entitled CONTROL TECHNIQUES AND SUB-PROCESSOR CONTAINED WITHIN MODULAR SHAFT WITH SELECT CONTROL PROCESSING FROM HANDLE, now U.S. Patent No. 10,045,776;
- U.S. Patent Application Serial No. 14/640,837, entitled SMART SENSORS WITH LOCAL SIGNAL PROCESSING, now U.S. Patent No. 9,993,248;
- U.S. Patent Application Serial No. 14/640,765, entitled SYSTEM FOR DETECTING THE MIS-INSERTION OF A STAPLE CARTRIDGE INTO A SURGICAL STAPLER, now U.S. Patent No. 10,617,412;
- U.S. Patent Application Serial No. 14/640,799, entitled SIGNAL AND POWER COMMUNICATION SYSTEM POSITIONED ON A ROTATABLE SHAFT, now U.S. Patent No. 9,901,342; and
- U.S. Patent Application Serial No. 14/640,780, entitled SURGICAL INSTRUMENT COMPRISING A LOCKABLE BATTERY HOUSING, now U.S. Patent No. 10,245,033.

[0024] Applicant of the present application owns the following patent applications that were filed on February 27, 2015, and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/633,576, entitled SURGICAL INSTRUMENT SYSTEM COMPRISING AN INSPECTION STATION, now U.S. Patent No. 10,045,779;
- U.S. Patent Application Serial No. 14/633,546, entitled SURGICAL APPARATUS CONFIGURED TO ASSESS WHETHER A PERFORMANCE PARAMETER OF THE SURGICAL APPARATUS IS WITHIN AN ACCEPTABLE PERFORMANCE BAND, now U.S. Patent No. 10,180,463;
- U.S. Patent Application Serial No. 14/633,560, entitled SURGICAL CHARGING SYSTEM THAT CHARGES AND/OR CONDITIONS ONE OR MORE BATTERIES, now U.S. Patent Application Publication No. 2016/0249910;
- U.S. Patent Application Serial No. 14/633,566, entitled CHARGING SYSTEM THAT ENABLES EMERGENCY RESOLUTIONS FOR CHARGING A BATTERY, now U.S. Patent No. 10,182,816;
- U.S. Patent Application Serial No. 14/633,555, entitled SYSTEM FOR MONITORING WHETHER A SURGICAL INSTRUMENT NEEDS TO BE SER-

VICED, now U.S. Patent No. 10,321,907;

- U.S. Patent Application Serial No. 14/633,542, entitled REINFORCED BATTERY FOR A SURGICAL INSTRUMENT, now U.S. Patent No. 9,931,118;
- U.S. Patent Application Serial No. 14/633,548, entitled POWER ADAPTER FOR A SURGICAL INSTRUMENT, now U.S. Patent No. 10,245,028;
- U.S. Patent Application Serial No. 14/633,526, entitled ADAPTABLE SURGICAL INSTRUMENT HANDLE, now U.S. Patent No. 9,993,258;
- U.S. Patent Application Serial No. 14/633,541, entitled MODULAR STAPLING ASSEMBLY, now U.S. Patent No. 10,226,250; and
- U.S. Patent Application Serial No. 14/633,562, entitled SURGICAL APPARATUS CONFIGURED TO TRACK AN END-OF-LIFE PARAMETER, now U.S. Patent No. 10,159,483.

[0025] Applicant of the present application owns the following patent applications that were filed on December 18, 2014 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/574,478, entitled SURGICAL INSTRUMENT SYSTEMS COMPRISING AN ARTICULABLE END EFFECTOR AND MEANS FOR ADJUSTING THE FIRING STROKE OF A FIRING MEMBER, now U.S. Patent No. 9,844,374;
- U.S. Patent Application Serial No. 14/574,483, entitled SURGICAL INSTRUMENT ASSEMBLY COMPRISING LOCKABLE SYSTEMS, now U.S. Patent No. 10,188,385;
- U.S. Patent Application Serial No. 14/575,139, entitled DRIVE ARRANGEMENTS FOR ARTICULABLE SURGICAL INSTRUMENTS, now U.S. Patent No. 9,844,375;
- U.S. Patent Application Serial No. 14/575,148, entitled LOCKING ARRANGEMENTS FOR DETACHABLE SHAFT ASSEMBLIES WITH ARTICULABLE SURGICAL END EFFECTORS, now U.S. Patent No. 10,085,748;
- U.S. Patent Application Serial No. 14/575,130, entitled SURGICAL INSTRUMENT WITH AN ANVIL THAT IS SELECTIVELY MOVABLE ABOUT A DISCRETE NON-MOVABLE AXIS RELATIVE TO A STAPLE CARTRIDGE, now U.S. Patent No. 10,245,027;
- U.S. Patent Application Serial No. 14/575,143, entitled SURGICAL INSTRUMENTS WITH IMPROVED CLOSURE ARRANGEMENTS, now U.S. Patent No. 10,004,501;
- U.S. Patent Application Serial No. 14/575,117, entitled SURGICAL INSTRUMENTS WITH ARTICULABLE END EFFECTORS AND MOVABLE FIRING BEAM SUPPORT ARRANGEMENTS, now U.S. Patent No. 9,943,309;
- U.S. Patent Application Serial No. 14/575,154, en-

titled SURGICAL INSTRUMENTS WITH ARTICULABLE ENDEFFECTORS AND IMPROVED FIRING BEAM SUPPORT ARRANGEMENTS, now U.S. Patent No. 9,968,355;

- U.S. Patent Application Serial No. 14/574,493, entitled SURGICAL INSTRUMENT ASSEMBLY COMPRISING A FLEXIBLE ARTICULATION SYSTEM, now U.S. Patent No. 9,987,000; and
- U.S. Patent Application Serial No. 14/574,500, entitled SURGICAL INSTRUMENT ASSEMBLY COMPRISING A LOCKABLE ARTICULATION SYSTEM, now U.S. Patent No. 10,117,649.

[0026] Applicant of the present application owns the following patent applications that were filed on March 1, 2013 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 13/782,295, entitled ARTICULABLE SURGICAL INSTRUMENTS WITH CONDUCTIVE PATHWAYS FOR SIGNAL COMMUNICATION, now U.S. Patent No. 9,700,309;
- U.S. Patent Application Serial No. 13/782,323, entitled ROTARY POWERED ARTICULATION JOINTS FOR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,782,169;
- U.S. Patent Application Serial No. 13/782,338, entitled THUMBWHEEL SWITCH ARRANGEMENTS FOR SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2014/0249557;
- U.S. Patent Application Serial No. 13/782,499, entitled ELECTROMECHANICAL SURGICAL DEVICE WITH SIGNAL RELAY ARRANGEMENT, now U.S. Patent No. 9,358,003;
- U.S. Patent Application Serial No. 13/782,460, entitled MULTIPLE PROCESSOR MOTOR CONTROL FOR MODULAR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,554,794;
- U.S. Patent Application Serial No. 13/782,358, entitled JOYSTICK SWITCH ASSEMBLIES FOR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,326,767;
- U.S. Patent Application Serial No. 13/782,481, entitled SENSOR STRAIGHTENED END EFFECTOR DURING REMOVAL THROUGH TROCAR, now U.S. Patent No. 9,468,438;
- U.S. Patent Application Serial No. 13/782,518, entitled CONTROL METHODS FOR SURGICAL INSTRUMENTS WITH REMOVABLE IMPLEMENT PORTIONS, now U.S. Patent Application Publication No. 2014/0246475;
- U.S. Patent Application Serial No. 13/782,375, entitled ROTARY POWERED SURGICAL INSTRUMENTS WITH MULTIPLE DEGREES OF FREEDOM, now U.S. Patent No. 9,398,911; and
- U.S. Patent Application Serial No. 13/782,536, entitled SURGICAL INSTRUMENT SOFT STOP, now

U.S. Patent No. 9,307,986.

[0027] Applicant of the present application also owns the following patent applications that were filed on March 14, 2013 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 13/803,097, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING A FIRING DRIVE, now U.S. Patent No. 9,687,230;
- U.S. Patent Application Serial No. 13/803,193, entitled CONTROL ARRANGEMENTS FOR A DRIVE MEMBER OF A SURGICAL INSTRUMENT, now U.S. Patent No. 9,332,987;
- U.S. Patent Application Serial No. 13/803,053, entitled INTERCHANGEABLE SHAFT ASSEMBLIES FOR USE WITH A SURGICAL INSTRUMENT, now U.S. Patent No. 9,883,860;
- U.S. Patent Application Serial No. 13/803,086, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING AN ARTICULATION LOCK, now U.S. Patent Application Publication No. 2014/0263541;
- U.S. Patent Application Serial No. 13/803,210, entitled SENSOR ARRANGEMENTS FOR ABSOLUTE POSITIONING SYSTEM FOR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,808,244;
- U.S. Patent Application Serial No. 13/803,148, entitled MULTI-FUNCTION MOTOR FOR A SURGICAL INSTRUMENT, now U.S. Patent No. 10,470,762;
- U.S. Patent Application Serial No. 13/803,066, entitled DRIVE SYSTEM LOCKOUT ARRANGEMENTS FOR MODULAR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,629,623;
- U.S. Patent Application Serial No. 13/803,117, entitled ARTICULATION CONTROL SYSTEM FOR ARTICULATABLE SURGICAL INSTRUMENTS, now U.S. Patent No. 9,351,726;
- U.S. Patent Application Serial No. 13/803,130, entitled DRIVE TRAIN CONTROL ARRANGEMENTS FOR MODULAR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,351,727; and
- U.S. Patent Application Serial No. 13/803,159, entitled METHOD AND SYSTEM FOR OPERATING A SURGICAL INSTRUMENT, now U.S. Patent No. 9,888,919.

[0028] Applicant of the present application also owns the following patent application that was filed on March 7, 2014 and is herein incorporated by reference in its entirety:

- U.S. Patent Application Serial No. 14/200,111, entitled CONTROL SYSTEMS FOR SURGICAL INSTRUMENTS, now U.S. Patent No. 9,629,629.

[0029] Applicant of the present application also owns the following patent applications that were filed on March 26, 2014 and are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/226,106, entitled POWER MANAGEMENT CONTROL SYSTEMS FOR SURGICAL INSTRUMENTS, now U.S. Patent Application Publication No. 2015/0272582;
- U.S. Patent Application Serial No. 14/226,099, entitled STERILIZATION VERIFICATION CIRCUIT, now U.S. Patent No. 9,826,977;
- U.S. Patent Application Serial No. 14/226,094, entitled VERIFICATION OF NUMBER OF BATTERY EXCHANGES/PROCEDURE COUNT, now U.S. Patent Application Publication No. 2015/0272580;
- U.S. Patent Application Serial No. 14/226,117, entitled POWER MANAGEMENT THROUGH SLEEP OPTIONS OF SEGMENTED CIRCUIT AND WAKE UP CONTROL, now U.S. Patent No. 10,013,049;
- U.S. Patent Application Serial No. 14/226,075, entitled MODULAR POWERED SURGICAL INSTRUMENT WITH DETACHABLE SHAFT ASSEMBLIES, now U.S. Patent No. 9,743,929;
- U.S. Patent Application Serial No. 14/226,093, entitled FEEDBACK ALGORITHMS FOR MANUAL BAILOUT SYSTEMS FOR SURGICAL INSTRUMENTS, now U.S. Patent No. 10,028,761;
- U.S. Patent Application Serial No. 14/226,116, entitled SURGICAL INSTRUMENT UTILIZING SENSOR ADAPTATION, now U.S. Patent Application Publication No. 2015/0272571;
- U.S. Patent Application Serial No. 14/226,071, entitled SURGICAL INSTRUMENT CONTROL CIRCUIT HAVING A SAFETY PROCESSOR, now U.S. Patent No. 9,690,362;
- U.S. Patent Application Serial No. 14/226,097, entitled SURGICAL INSTRUMENT COMPRISING INTERACTIVE SYSTEMS, now U.S. Patent No. 9,820,738;
- U.S. Patent Application Serial No. 14/226,126, entitled INTERFACE SYSTEMS FOR USE WITH SURGICAL INSTRUMENTS, now U.S. Patent No. 10,004,497;
- U.S. Patent Application Serial No. 14/226,133, entitled MODULAR SURGICAL INSTRUMENT SYSTEM, now U.S. Patent Application Publication No. 2015/0272557;
- U.S. Patent Application Serial No. 14/226,081, entitled SYSTEMS AND METHODS FOR CONTROLLING A SEGMENTED CIRCUIT, now U.S. Patent No. 9,804,618;
- U.S. Patent Application Serial No. 14/226,076, entitled POWER MANAGEMENT THROUGH SEGMENTED CIRCUIT AND VARIABLE VOLTAGE PROTECTION, now U.S. Patent No. 9,733,663;
- U.S. Patent Application Serial No. 14/226,111, en-

titled SURGICAL STAPLING INSTRUMENT SYSTEM, now U.S. Patent No. 9,750,499; and

- U.S. Patent Application Serial No. 14/226,125, entitled SURGICAL INSTRUMENT COMPRISING A ROTATABLE SHAFT, now U.S. Patent No. 10,201,364.

[0030] Applicant of the present application also owns the following patent applications that were filed on September 5, 2014 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/479,103, entitled CIRCUITRY AND SENSORS FOR POWERED MEDICAL DEVICE, now U.S. Patent No. 10,111,679;
- U.S. Patent Application Serial No. 14/479,119, entitled ADJUNCT WITH INTEGRATED SENSORS TO QUANTIFY TISSUE COMPRESSION, now U.S. Patent No. 9,724,094;
- U.S. Patent Application Serial No. 14/478,908, entitled MONITORING DEVICE DEGRADATION BASED ON COMPONENT EVALUATION, now U.S. Patent No. 9,737,301;
- U.S. Patent Application Serial No. 14/478,895, entitled MULTIPLE SENSORS WITH ONE SENSOR AFFECTING A SECOND SENSOR'S OUTPUT OR INTERPRETATION, now U.S. Patent No. 9,757,128;
- U.S. Patent Application Serial No. 14/479,110, entitled POLARITY OF HALL MAGNET TO IDENTIFY CARTRIDGE TYPE, now U.S. Patent No. 10,016,199;
- U.S. Patent Application Serial No. 14/479,098, entitled SMART CARTRIDGE WAKE UP OPERATION AND DATA RETENTION, now U.S. Patent No. 10,135,242;
- U.S. Patent Application Serial No. 14/479,115, entitled MULTIPLE MOTOR CONTROL FOR POWERED MEDICAL DEVICE, now U.S. Patent No. 9,788,836; and
- U.S. Patent Application Serial No. 14/479,108, entitled LOCAL DISPLAY OF TISSUE PARAMETER STABILIZATION, now U.S. Patent Application Publication No. 2016/0066913.

[0031] Applicant of the present application also owns the following patent applications that were filed on April 9, 2014 and which are each herein incorporated by reference in their respective entirety:

- U.S. Patent Application Serial No. 14/248,590, entitled MOTOR DRIVEN SURGICAL INSTRUMENTS WITH LOCKABLE DUAL DRIVE SHAFTS, now U.S. Patent No. 9,826,976;
- U.S. Patent Application Serial No. 14/248,581, entitled SURGICAL INSTRUMENT COMPRISING A CLOSING DRIVE AND A FIRING DRIVE OPERATED FROM THE SAME ROTATABLE OUTPUT,

now U.S. Patent No. 9,649,110;

- U.S. Patent Application Serial No. 14/248,595, entitled SURGICAL SYSTEM COMPRISING FIRST AND SECOND DRIVE SYSTEMS, now U.S. Patent No. 9,844,368;
- U.S. Patent Application Serial No. 14/248,588, entitled POWERED LINEAR SURGICAL STAPLER, now U.S. Patent No. 10,405,857;
- U.S. Patent Application Serial No. 14/248,591, entitled SURGICAL INSTRUMENT COMPRISING A GAP SETTING SYSTEM, now U.S. Patent No. 10,149,680;
- U.S. Patent Application Serial No. 14/248,584, entitled MODULAR MOTOR DRIVEN SURGICAL INSTRUMENTS WITH ALIGNMENT FEATURES FOR ALIGNING ROTARY DRIVE SHAFTS WITH SURGICAL END EFFECTOR SHAFTS, now U.S. Patent No. 9,801,626;
- U.S. Patent Application Serial No. 14/248,587, entitled POWERED SURGICAL STAPLER, now U.S. Patent No. 9,867,612;
- U.S. Patent Application Serial No. 14/248,586, entitled DRIVE SYSTEM DECOUPLING ARRANGEMENT FOR A SURGICAL INSTRUMENT, now U.S. Patent No. 10,136,887; and
- U.S. Patent Application Serial No. 14/248,607, entitled MODULAR MOTOR DRIVEN SURGICAL INSTRUMENTS WITH STATUS INDICATION ARRANGEMENTS, now U.S. Patent No. 9,814,460.

[0032] Applicant of the present application also owns the following patent applications that were filed on April 16, 2013 and which are each herein incorporated by reference in their respective entirety:

- U.S. Provisional Patent Application Serial No. 61/812,365, entitled SURGICAL INSTRUMENT WITH MULTIPLE FUNCTIONS PERFORMED BY A SINGLE MOTOR;
- U.S. Provisional Patent Application Serial No. 61/812,376, entitled LINEAR CUTTER WITH POWER;
- U.S. Provisional Patent Application Serial No. 61/812,382, entitled LINEAR CUTTER WITH MOTOR AND PISTOL GRIP;
- U.S. Provisional Patent Application Serial No. 61/812,385, entitled SURGICAL INSTRUMENT HANDLE WITH MULTIPLE ACTUATION MOTORS AND MOTOR CONTROL; and
- U.S. Provisional Patent Application Serial No. 61/812,372, entitled SURGICAL INSTRUMENT WITH MULTIPLE FUNCTIONS PERFORMED BY A SINGLE MOTOR.

[0033] Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on December 28, 2017, the disclosure of each of which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/611,341, entitled INTERACTIVE SURGICAL PLATFORM;
- U.S. Provisional Patent Application Serial No. 62/611,340, entitled CLOUD-BASED MEDICAL ANALYTICS; and
- U.S. Provisional Patent Application Serial No. 62/611,339, entitled ROBOT ASSISTED SURGICAL PLATFORM.

[0034] Applicant of the present application owns the following U.S. Provisional Patent Applications, filed on March 28, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Provisional Patent Application Serial No. 62/649,302, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES;
- U.S. Provisional Patent Application Serial No. 62/649,294, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD;
- U.S. Provisional Patent Application Serial No. 62/649,300, entitled SURGICAL HUB SITUATIONAL AWARENESS;
- U.S. Provisional Patent Application Serial No. 62/649,309, entitled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER;
- U.S. Provisional Patent Application Serial No. 62/649,310, entitled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS;
- U.S. Provisional Patent Application Serial No. 62/649,291, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT;
- U.S. Provisional Patent Application Serial No. 62/649,296, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES;
- U.S. Provisional Patent Application Serial No. 62/649,333, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER;
- U.S. Provisional Patent Application Serial No. 62/649,327, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES;
- U.S. Provisional Patent Application Serial No. 62/649,315, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK;
- U.S. Provisional Patent Application Serial No. 62/649,313, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES;
- U.S. Provisional Patent Application Serial No. 62/649,320, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLAT-

FORMS;

- U.S. Provisional Patent Application Serial No. 62/649,307, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS; and
- U.S. Provisional Patent Application Serial No. 62/649,323, entitled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS.

[0035] Applicant of the present application owns the following U.S. Patent Applications, filed on March 29, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Patent Application Serial No. 15/940,641, entitled INTERACTIVE SURGICAL SYSTEMS WITH ENCRYPTED COMMUNICATION CAPABILITIES, now U.S. Patent Application Publication No. 2019/0207911;
- U.S. Patent Application Serial No. 15/940,648, entitled INTERACTIVE SURGICAL SYSTEMS WITH CONDITION HANDLING OF DEVICES AND DATA CAPABILITIES, now U.S. Patent Application Publication No. 2019/0206004;
- U.S. Patent Application Serial No. 15/940,656, entitled SURGICAL HUB COORDINATION OF CONTROL AND COMMUNICATION OF OPERATING ROOM DEVICES, now U.S. Patent Application Publication No. 2019/0201141;
- U.S. Patent Application Serial No. 15/940,666, entitled SPATIAL AWARENESS OF SURGICAL HUBS IN OPERATING ROOMS, now U.S. Patent Application Publication No. 2019/0206551;
- U.S. Patent Application Serial No. 15/940,670, entitled COOPERATIVE UTILIZATION OF DATA DERIVED FROM SECONDARY SOURCES BY INTELLIGENT SURGICAL HUBS, now U.S. Patent Application Publication No. 2019/0201116;
- U.S. Patent Application Serial No. 15/940,677, entitled SURGICAL HUB CONTROL ARRANGEMENTS, now U.S. Patent Application Publication No. 2019/0201143;
- U.S. Patent Application Serial No. 15/940,632, entitled DATA STRIPPING METHOD TO INTERROGATE PATIENT RECORDS AND CREATE ANONYMIZED RECORD, now U.S. Patent Application Publication No. 2019/0205566;
- U.S. Patent Application Serial No. 15/940,640, entitled COMMUNICATION HUB AND STORAGE DEVICE FOR STORING PARAMETERS AND STATUS OF A SURGICAL DEVICE TO BE SHARED WITH CLOUD BASED ANALYTICS SYSTEMS, now U.S. Patent Application Publication No. 2019/0200863;
- U.S. Patent Application Serial No. 15/940,645, entitled SELF DESCRIBING DATA PACKETS GENERATED AT AN ISSUING INSTRUMENT, now U.S. Patent No. 10,892,899;

- U.S. Patent Application Serial No. 15/940,649, entitled DATA PAIRING TO INTERCONNECT A DEVICE MEASURED PARAMETER WITH AN OUTCOME, now U.S. Patent Application Publication No. 2019/0205567;
- U.S. Patent Application Serial No. 15/940,654, entitled SURGICAL HUB SITUATIONAL AWARENESS, now U.S. Patent Application Publication No. 2019/0201140;
- U.S. Patent Application Serial No. 15/940,663, entitled SURGICAL SYSTEM DISTRIBUTED PROCESSING, now U.S. Patent Application Publication No. 2019/0201033;
- U.S. Patent Application Serial No. 15/940,668, entitled AGGREGATION AND REPORTING OF SURGICAL HUB DATA, now U.S. Patent Application Publication No. 2019/0201115;
- U.S. Patent Application Serial No. 15/940,671, entitled SURGICAL HUB SPATIAL AWARENESS TO DETERMINE DEVICES IN OPERATING THEATER, now U.S. Patent Application Publication No. 2019/0201104;
- U.S. Patent Application Serial No. 15/940,686, entitled DISPLAY OF ALIGNMENT OF STAPLE CARTRIDGE TO PRIOR LINEAR STAPLE LINE, now U.S. Patent Application Publication No. 2019/0201105;
- U.S. Patent Application Serial No. 15/940,700, entitled STERILE FIELD INTERACTIVE CONTROL DISPLAYS, now U.S. Patent Application Publication No. 2019/0205001;
- U.S. Patent Application Serial No. 15/940,629, entitled COMPUTER IMPLEMENTED INTERACTIVE SURGICAL SYSTEMS, now U.S. Patent Application Publication No. 2019/0201112;
- U.S. Patent Application Serial No. 15/940,704, entitled USE OF LASER LIGHT AND RED-GREEN-BLUE COLORATION TO DETERMINE PROPERTIES OF BACK SCATTERED LIGHT, now U.S. Patent Application Publication No. 2019/0206050;
- U.S. Patent Application Serial No. 15/940,722, entitled CHARACTERIZATION OF TISSUE IRREGULARITIES THROUGH THE USE OF MONO-CHROMATIC LIGHT REFRACTIVITY, now U.S. Patent Application Publication No. 2019/0200905; and
- U.S. Patent Application Serial No. 15/940,742, entitled DUAL CMOS ARRAY IMAGING, now U.S. Patent Application Publication No. 2019/0200906.

[0036] Applicant of the present application owns the following U.S. Patent Applications, filed on March 29, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Patent Application Serial No. 15/940,636, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL DEVICES, now U.S. Patent Application Publication No. 2019/0206003;

- U.S. Patent Application Serial No. 15/940,653, entitled ADAPTIVE CONTROL PROGRAM UPDATES FOR SURGICAL HUBS, now U.S. Patent Application Publication No. 2019/0201114;
- 5 - U.S. Patent Application Serial No. 15/940,660, entitled CLOUD-BASED MEDICAL ANALYTICS FOR CUSTOMIZATION AND RECOMMENDATIONS TO A USER, now U.S. Patent Application Publication No. 2019/0206555;
- 10 - U.S. Patent Application Serial No. 15/940,679, entitled CLOUD-BASED MEDICAL ANALYTICS FOR LINKING OF LOCAL USAGE TRENDS WITH THE RESOURCE ACQUISITION BEHAVIORS OF LARGER DATA SET, now U.S. Patent Application Publication No. 2019/0201144;
- 15 - U.S. Patent Application Serial No. 15/940,694, entitled CLOUD-BASED MEDICAL ANALYTICS FOR MEDICAL FACILITY SEGMENTED INDIVIDUALIZATION OF INSTRUMENT FUNCTION, now U.S. Patent Application Publication No. 2019/0201119;
- 20 - U.S. Patent Application Serial No. 15/940,634, entitled CLOUD-BASED MEDICAL ANALYTICS FOR SECURITY AND AUTHENTICATION TRENDS AND REACTIVE MEASURES, now U.S. Patent Application Publication No. 2019/0201138;
- 25 - U.S. Patent Application Serial No. 15/940,706, entitled DATA HANDLING AND PRIORITIZATION IN A CLOUD ANALYTICS NETWORK, now U.S. Patent Application Publication No. 2019/0206561; and
- 30 - U.S. Patent Application Serial No. 15/940,675, entitled CLOUD INTERFACE FOR COUPLED SURGICAL DEVICES, now U.S. Patent No. 10,849,697.

[0037] Applicant of the present application owns the following U.S. Patent Applications, filed on March 29, 2018, each of which is herein incorporated by reference in its entirety:

- U.S. Patent Application Serial No. 15/940,627, entitled DRIVE ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201111;
- 40 - U.S. Patent Application Serial No. 15/940,637, entitled COMMUNICATION ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201139;
- 45 - U.S. Patent Application Serial No. 15/940,642, entitled CONTROLS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201113;
- 50 - U.S. Patent Application Serial No. 15/940,676, entitled AUTOMATIC TOOL ADJUSTMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201142;
- 55 - U.S. Patent Application Serial No. 15/940,680, entitled CONTROLLERS FOR ROBOT-ASSISTED

SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201135;

- U.S. Patent Application Serial No. 15/940,683, entitled COOPERATIVE SURGICAL ACTIONS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201145;
- U.S. Patent Application Serial No. 15/940,690, entitled DISPLAY ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201118; and
- U.S. Patent Application Serial No. 15/940,711, entitled SENSING ARRANGEMENTS FOR ROBOT-ASSISTED SURGICAL PLATFORMS, now U.S. Patent Application Publication No. 2019/0201120.

[0038] Numerous specific details are set forth to provide a thorough understanding of the overall structure, function, manufacture, and use of the embodiments as described in the specification and illustrated in the accompanying drawings. Well-known operations, components, and elements have not been described in detail so as not to obscure the embodiments described in the specification. The reader will understand that the embodiments described and illustrated herein are non-limiting examples, and thus it can be appreciated that the specific structural and functional details disclosed herein may be representative and illustrative. Variations and changes thereto may be made without departing from the scope of the claims.

[0039] The terms "comprise" (and any form of comprise, such as "comprises" and "comprising"), "have" (and any form of have, such as "has" and "having"), "include" (and any form of include, such as "includes" and "including") and "contain" (and any form of contain, such as "contains" and "containing") are open-ended linking verbs. As a result, a surgical system, device, or apparatus that "comprises," "has," "includes" or "contains" one or more elements possesses those one or more elements, but is not limited to possessing only those one or more elements. Likewise, an element of a system, device, or apparatus that "comprises," "has," "includes" or "contains" one or more features possesses those one or more features, but is not limited to possessing only those one or more features.

[0040] The terms "proximal" and "distal" are used herein with reference to a clinician manipulating the handle portion of the surgical instrument. The term "proximal" refers to the portion closest to the clinician and the term "distal" refers to the portion located away from the clinician. It will be further appreciated that, for convenience and clarity, spatial terms such as "vertical", "horizontal", "up", and "down" may be used herein with respect to the drawings. However, surgical instruments are used in many orientations and positions, and these terms are not intended to be limiting and/or absolute.

[0041] Various exemplary devices and methods are provided for performing laparoscopic and minimally in-

vasive surgical procedures. However, the reader will readily appreciate that the various methods and devices disclosed herein can be used in numerous surgical procedures and applications including, for example, in connection with open surgical procedures. As the present Detailed Description proceeds, the reader will further appreciate that the various instruments disclosed herein can be inserted into a body in any way, such as through a natural orifice, through an incision or puncture hole formed in tissue, etc. The working portions or end effector portions of the instruments can be inserted directly into a patient's body or can be inserted through an access device that has a working channel through which the end effector and elongate shaft of a surgical instrument can be advanced.

[0042] A surgical stapling system can comprise a shaft and an end effector extending from the shaft. The end effector comprises a first jaw and a second jaw. The first jaw comprises a staple cartridge. The staple cartridge is insertable into and removable from the first jaw; however, other embodiments are envisioned in which a staple cartridge is not removable from, or at least readily replaceable from, the first jaw. The second jaw comprises an anvil configured to deform staples ejected from the staple cartridge. The second jaw is pivotable relative to the first jaw about a closure axis; however, other embodiments are envisioned in which the first jaw is pivotable relative to the second jaw. The surgical stapling system further comprises an articulation joint configured to permit the end effector to be rotated, or articulated, relative to the shaft. The end effector is rotatable about an articulation axis extending through the articulation joint. Other embodiments are envisioned which do not include an articulation joint.

[0043] The staple cartridge comprises a cartridge body. The cartridge body includes a proximal end, a distal end, and a deck extending between the proximal end and the distal end. In use, the staple cartridge is positioned on a first side of the tissue to be stapled and the anvil is positioned on a second side of the tissue. The anvil is moved toward the staple cartridge to compress and clamp the tissue against the deck. Thereafter, staples removably stored in the cartridge body can be deployed into the tissue. The cartridge body includes staple cavities defined therein wherein staples are removably stored in the staple cavities. The staple cavities are arranged in six longitudinal rows. Three rows of staple cavities are positioned on a first side of a longitudinal slot and three rows of staple cavities are positioned on a second side of the longitudinal slot. Other arrangements of staple cavities and staples may be possible.

[0044] The staples are supported by staple drivers in the cartridge body. The drivers are movable between a first, or unfired position, and a second, or fired, position to eject the staples from the staple cavities. The drivers are retained in the cartridge body by a retainer which extends around the bottom of the cartridge body and includes resilient members configured to grip the cartridge body

and hold the retainer to the cartridge body. The drivers are movable between their unfired positions and their fired positions by a sled. The sled is movable between a proximal position adjacent the proximal end and a distal position adjacent the distal end. The sled comprises a plurality of ramped surfaces configured to slide under the drivers and lift the drivers, and the staples supported thereon, toward the anvil.

[0045] Further to the above, the sled is moved distally by a firing member. The firing member is configured to contact the sled and push the sled toward the distal end. The longitudinal slot defined in the cartridge body is configured to receive the firing member. The anvil also includes a slot configured to receive the firing member. The firing member further comprises a first cam which engages the first jaw and a second cam which engages the second jaw. As the firing member is advanced distally, the first cam and the second cam can control the distance, or tissue gap, between the deck of the staple cartridge and the anvil. The firing member also comprises a knife configured to incise the tissue captured intermediate the staple cartridge and the anvil. It is desirable for the knife to be positioned at least partially proximal to the ramped surfaces such that the staples are ejected ahead of the knife.

[0046] A surgical instrument 10000 is illustrated in FIG. 1. The surgical instrument 10000 comprises a handle 10100 including a handle housing 10120, a shaft 10200 extending from the handle 10100, and an end effector 10400. The end effector 10400 comprises a first jaw 10410 configured to receive a staple cartridge and a second jaw 10420 movable relative to the first jaw 10410. The second jaw 10420 comprises an anvil including staple forming pockets defined therein. The surgical instrument 10000 further comprises a closure actuator 10140 configured to drive a closure system of the surgical instrument 10000 and move the second jaw 10420 between an unclamped position and a clamped position. The closure actuator 10140 is operably coupled with a closure tube 10240 that is advanced distally when the closure actuator 10140 is closed. In such instances, the closure tube 10240 contacts the second jaw and cams and/or pushes the second jaw 10420 downwardly into its clamped position.

[0047] Further to the above, the second jaw 10420 is pivotably coupled to the first jaw 10410 about a pivot axis. In various embodiments, the second jaw can both translate and rotate as it is being moved into its clamped position. In various alternative embodiments, a surgical instrument comprises a staple cartridge jaw that is movable between an unclamped position and a clamped position relative to an anvil jaw. In any event, the handle 10100 comprises a lock configured to releasably hold the closure actuator 10140 in its clamped position. The handle 10100 further comprises release actuators 10180b on opposite sides thereof which, when actuated, unlock the closure actuator 10140 such that the end effector 10400 can be re-opened. In various alternative embodiments,

the handle 10100 comprises an electric motor configured to move the closure tube 10240 proximally and/or distally when actuated by the clinician.

[0048] The end effector 10400 is attached to the shaft 10200 about an articulation joint 10500 and is rotatable within a plane about an articulation axis. The shaft 10200 defines a longitudinal axis and the end effector 10400 is articulatable between an unarticulated position in which the end effector 10400 is aligned with the longitudinal axis and articulated positions in which the end effector 10400 extends at a transverse angle relative to the longitudinal axis. In various embodiments, the surgical instrument 10000 comprises a first articulation joint which permits the end effector 10400 to be articulated in a first plane and a second articulation joint which permits the end effector 10400 to be articulated in a second plane which is orthogonal to the first plane, for example. The handle 10100 comprises at least one electric motor and a control system configured to control the operation of the electric motor in response to articulation actuators 10160 and 10170. The electric motor comprises a brushless DC motor; however, the electric motor can comprise any suitable motor, such as a brushed DC motor, for example.

[0049] The entire disclosure of U.S. Patent No. 10,149,683, entitled POWERED SURGICAL CUTTING AND STAPLING APPARATUS WITH MANUALLY RETRACTABLE FIRING SYSTEM, which issued on December 11, 2018, is incorporated by reference herein. The entire disclosure of U.S. Patent Application Publication No. 2018/0125481, entitled MOTOR-DRIVEN SURGICAL CUTTING INSTRUMENT, which published on May 10, 2018, is incorporated by reference herein. The handle 10100 further comprises a replaceable and/or rechargeable battery 10300 attachable to the handle housing which powers the surgical instrument 10000. The entire disclosure of U.S. Patent No. 8,632,525, entitled POWER CONTROL ARRANGEMENTS FOR SURGICAL INSTRUMENTS AND BATTERIES, which issued on January 21, 2014, is incorporated by reference herein.

[0050] Further to the above, the shaft 10200 is rotatable about a longitudinal axis extending through the shaft 10200. The shaft 10200 is rotatably connected to the handle 10100 about a rotation joint 10220 and the shaft 10200 comprises one or more finger grooves defined therein which facilitate a clinician using the stapling instrument 10000 to rotate the shaft 10200. In various embodiments, the surgical instrument 10000 comprises an electric motor and a rotation actuator that, when actuated by the clinician, powers the electric motor to rotate the shaft 10200 in a first direction or a second direction depending on the direction in which the rotation actuator is actuated.

[0051] Further to the above, the surgical instrument 10000 comprises a staple firing drive configured to eject the staples out of the staple cartridge. The staple firing drive comprises an electric motor and a firing member which is driven distally through a staple firing stroke by

the electric motor. During the staple firing stroke, the firing member pushes the sled in the staple cartridge distally to eject the staples from the staple cartridge. The entire disclosure of U.S. Patent No. 9,629,629, entitled CONTROL SYSTEMS FOR SURGICAL INSTRUMENTS, which issued on April 25, 2017, is incorporated by reference herein.

[0052] The surgical instrument systems described herein are motivated by an electric motor; however, the surgical instrument systems described herein can be motivated in any suitable manner. In certain instances, the motors disclosed herein may comprise a portion or portions of a robotically controlled system. U.S. Patent Application Serial No. 13/118,241, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, now U.S. Patent No. 9,072,535, for example, discloses several examples of a robotic surgical instrument system in greater detail, the entire disclosure of which is incorporated by reference herein. The disclosures of International Patent Publication No. WO 2017/083125, entitled STAPLER WITH COMPOSITE CARDAN AND SCREW DRIVE, published May 18, 2017, International Patent Publication No. WO 2017/083126, entitled STAPLE PUSHER WITH LOST MOTION BETWEEN RAMPS, published May 18, 2017, International Patent Publication No. WO 2015/153642, entitled SURGICAL INSTRUMENT WITH SHIFTABLE TRANSMISSION, published October 8, 2015, U.S. Patent Application Publication No. 2017/0265954, filed March 17, 2017, entitled STAPLER WITH CABLE-DRIVEN ADVANCEABLE CLAMPING ELEMENT AND DUAL DISTAL PULLEYS, now U.S. Patent No. 10,350,016, U.S. Patent Application Publication No. 2017/0265865, filed February 15, 2017, entitled STAPLER WITH CABLE-DRIVEN ADVANCEABLE CLAMPING ELEMENT AND DISTAL PULLEY, now U.S. Patent No. 10,631,858, and U.S. Patent Application Publication No. 2017/0290586, entitled STAPLING CARTRIDGE, filed on March 29, 2017, now U.S. Patent No. 10,722,233, are incorporated herein by reference in their entireties.

[0053] Various embodiments disclosed herein may be employed in connection with a robotic surgical system, such as the robotic system 1000 depicted in FIGS. 1-3, for example. FIG. 1 depicts a master controller 5001 that may be used in connection with a robotic arm cart 5100 depicted in FIG. 2. The master controller 5001 and the robotic arm cart 5100, as well as their respective components and control systems, are collectively referred to herein as a robotic system 5000. Examples of such systems and devices are disclosed in U.S. Patent No. 7,524,320, entitled MECHANICAL ACTUATOR INTERFACE SYSTEM FOR ROBOTIC SURGICAL TOOLS, as well as U.S. Patent No. 9,072,535, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, which are each hereby incorporated by reference herein in their respective entireties. The details of such systems and devices

are not repeated herein for the sake of brevity. The master controller 5001 includes controls 5003 which are grasped and manipulated by the surgeon while the surgeon views the patient via a display 1002. The controls 5003 can comprise manual input devices which move with multiple degrees of freedom, for example, and can further comprise an actuatable trigger for actuating surgical instruments, or tools, to close grasping jaws, staple and incise tissue, and/or apply an electrical potential to an electrode, for example.

[0054] With reference to FIGS. 2 and 3, the robotic arm cart 5100 is configured to actuate one or more surgical instruments, such as surgical instruments 6000, for example, in response to inputs from the master controller 5001. In various forms, the robotic arm cart 5100 includes a base 5002, arm linkages including set-up joints 5104, and instrument manipulators 5106. Such an arrangement can facilitate the rotation of a surgical instrument 6000 around a point in space, which is described in U.S. Patent No. 5,817,084, entitled REMOTE CENTER POSITIONING DEVICE WITH FLEXIBLE DRIVE, the entire disclosure of which is hereby incorporated by reference herein. This arrangement provides for pivoting rotation of a surgical instrument 6000 about an axis 5112a, or pitch axis. The arrangement also provides for rotation of the surgical instrument 6000 about an axis 5112b, or yaw axis. The pitch and yaw axes 5112a, 5112b intersect at a remote center 5114, which is aligned along an elongate shaft of the surgical instrument 6000. A surgical instrument 6000 may have further degrees of driven freedom, including sliding motion along a longitudinal axis LT-LT. As the surgical instrument 6000 slides along the longitudinal axis LT-LT relative to the instrument manipulator 5106 (arrow 5112c), the remote center 5114 remains fixed relative to a base 5116 of the instrument manipulator 5106. To move the remote center 5114, linkage 5108 is driven by one or more motors 5120 which move the linkage 5108 in response to commands from the master controller 5001 to position and/or manipulate the surgical instrument 6000 within the surgical site. Various other arrangements are disclosed in U.S. Patent No. 5,878,193, entitled AUTOMATED ENDOSCOPE SYSTEM FOR OPTIMAL POSITIONING, the entire disclosure of which is hereby incorporated by reference herein.

[0055] Additionally, while the data communication between a robotic component and the processor of the robotic surgical system is primarily described herein with reference to communication between a surgical instrument, or tool, and the master controller 5001, it should be understood that similar communication may take place between the circuitry of a manipulator, a set-up joint, an endoscope or other image capture device, or the like, and the processor of the robotic surgical system for component compatibility verification, component-type identification, component calibration (such as off-set or the like) communication, confirmation of coupling of the component to the robotic surgical system, or the like. In accordance with at least one aspect, various surgical instru-

ments disclosed herein may be used in connection with other robotically-controlled or automated surgical systems and are not necessarily limited to use with the specific robotic system components shown in FIGS. 1-3 and described in the aforementioned references. Various robotic surgery systems and methods are disclosed in U.S. Patent No. 6,132,368, entitled MULTI-COMPONENT TELEPRESENCE SYSTEM AND METHOD, the entire disclosure of which is hereby incorporated by reference herein.

[0056] A staple cartridge 11000 is illustrated in FIGS. 5-5C. The staple cartridge 11000 comprises a cartridge body 11100 including a proximal end 11110 and a distal end 11120. The cartridge body 11100 further comprises a deck 11130 extending between the proximal end 11110 and the distal end 11120 and staple cavities 11140 defined in the deck 11130. The staple cavities 11140 are arranged in longitudinal rows on opposite sides of a longitudinal slot 11150 defined in the cartridge body 11100. The longitudinal slot 11150 is configured to receive a tissue cutting knife therein which is pushed distally during the staple firing stroke to cut tissue captured against the deck 11130 of the staple cartridge 11000. The staple cartridge 11000 further comprises a staple 11200 positioned in each staple cavity 11140 and staple drivers 11300 which support the staples 11200 and drive the staples 11200 out of the staple cavities 11140 during the staple firing stroke. The staple cartridge 11000 further comprises a sled 11400 which is pushed distally by a firing member of the staple firing drive to contact and lift the staple drivers 11300 toward the deck 11130 of the cartridge body 11100 during the staple firing stroke. The staple cartridge 11000 further comprises a pan 11700 attached to the cartridge body 11100 which is configured to retain the drivers 11300 and/or staples 11200 from falling out of the bottom of the cartridge body 11100.

[0057] The staple cartridge 11000 further comprises an electronic circuit. Although not illustrated in FIGS. 5-5C, the staple cartridge 11000 comprises the electronic circuit 11500 depicted in FIGS. 11-11C. Referring to FIGS. 11-11C, the electronic circuit 11500 comprises a proximal end 11510 and a second end 11520. The proximal end 11510 comprises a cartridge antenna 11530 that is placed in communication with an instrument antenna 10530 of the surgical instrument 10000 when the staple cartridge 11000 is seated in a jaw 10410 of the end effector 10400. The electronic circuit 11500 comprises a flexible substrate, such as a flex circuit, for example, conductive traces defined in and/or on the flexible substrate, and electronic components mounted to the flexible substrate that are in electrical communication with the conductive traces. In various embodiments, the electronic circuit 11500 is comprised of an insulator, conductive traces defined in and/or on the insulator, and electronic components mounted to the flexible substrate that are in electrical communication with the conductive traces.

[0058] Further to the above, referring again to FIGS. 11-11C, the electronic circuit 11500 is embedded in the

cartridge body 11100. The cartridge body 11100 comprises a circuit slot 11160 defined in the deck 11130 and the electronic circuit 11500 is positioned in the circuit slot 11160. The cartridge body 11100 further comprises a first lateral side 11170, a second lateral side 11180, and the distal portion 11120 connecting the first lateral side 11170 and the second lateral side 11180. The circuit slot 11160 extends around and/or between the longitudinal rows of staple cavities 11140 on the first lateral side 11170 of the cartridge body 11100, around the distal portion 11120, and then proximally into the second lateral side 11180. Similar to the first lateral side 11170, the circuit slot 11160 extends around and/or between the longitudinal rows of staple cavities 11140 on the second lateral side 11180. As a result of this arrangement, the electronic circuit 11500 can extend within both lateral sides of the cartridge body 11100 without having to cross over the longitudinal slot 11150. Moreover, such an arrangement permits the electronic circuit 11500 to extend into the distal portion 11120 of the cartridge body 11100. In various embodiments, the electronic circuit 11500 is embedded in the cartridge body 11100. In at least one embodiment, the electronic circuit 11500 is snap-fit and/or press-fit into the circuit slot 11160. In at least one embodiment, the cartridge body 11100 is comprised of plastic that is injection molded around at least a portion of the electronic circuit 11500.

[0059] In various embodiments, referring again to FIGS. 11-11C, the staple cartridge 11000 comprises elastomeric connectors which mechanically and electrically connect sensors 11600 to the cartridge body 11100. In at least one embodiment, the elastomeric connectors comprise conductive and insulative regions in a rubber or elastomeric matrix to produce overall anisotropic conductive properties. The matrix is molded into a three-dimensional shape and then attached to the cartridge body 11100. In various embodiments, the shape of the matrix matches features on the cartridge body. In at least one embodiment, short, fine metallic wires are embedded in a rubber sheet to connect the sensors 11600 to a control system of the staple cartridge 11000. In at least one instance, the metallic wires are comprised of silver, for example. In at least one instance, the density of the metallic wires in the matrix is between about 300 wires/cm² and about 2000/cm², for example. At the surfaces of the rubber sheet, the ends of the wires either extend from the surfaces or are bent back toward the rubber substrate. At least one material, trademarked ZEBRA, is available from Fuji Polymer Industries Company.

[0060] In various embodiments, a sensor system comprises a plurality of sections which are selectively powered by the control system of the staple cartridge. In at least one embodiment, the sensor system comprises a first sensor section and a second sensor section and a processor of the control system is configured to power only the first sensor section during a first operating mode, only the second sensor section during a second operating mode, and both sensor sections during a third oper-

ating mode, for example. Such embodiments can reduce the amount of heat produced by the staple cartridge, among other things. In various embodiments, the first sensor section and the second sensor section comprise the same number of sensors while, in other embodiments, the first sensor section and the second sensor section have a different number of sensors. In certain embodiments, the first sensor section comprises a first density of connection wires therein and the second sensor section comprises a second density of connection wires therein which is different than the first density.

[0061] Referring to FIG. 6, the cartridge antenna 11530 comprises a coil 11540 that is defined in a plane which is parallel to a plane defined by a coil 10540 of the instrument antenna 10530. The coils 10540 and 11540 are sized, configured, and positioned to provide a sufficient and/or optimal transfer coefficient such that data and/or power can be efficiently transmitted between the instrument antenna 10530 and the cartridge antenna 11530. In various instances, the instrument coil 10540 comprises a primary coil and the cartridge coil 11540 comprises a secondary coil and, in use, power is transmitted wirelessly from the instrument coil 10540 to the cartridge coil 11540. In at least this embodiment, data signals can also be transmitted between the instrument coil 10540 and the cartridge coil 11540. More specifically, data signals can be transmitted from the surgical instrument 10000 to the staple cartridge 11000 and/or from the staple cartridge 11000 to the surgical instrument 10000. Any suitable software protocol and/or hardware components can be used to co-ordinate the transmission of power and data across the single pair of coils comprising the instrument coil 10540 and the cartridge coil 11540. In at least one embodiment, power and data signals are transmitted simultaneously between the instrument coil 10540 and the cartridge coil 11540. In at least one alternative embodiment, referring to FIG. 7, power and data signals are transmitted sequentially between the instrument coil 10540 and the cartridge coil 11540. In various embodiments, the instrument antenna 10530 and/or the cartridge antenna 11530 comprises a multiplexer, for example, which co-ordinates the transmission of signals between the antennas 10530 and 11530.

[0062] Referring again to FIG. 6, the surgical instrument 10000 comprises a processor 10610 in communication with the instrument antenna 10530. In at least one embodiment, the processor 10610 comprises a near field communication (NFC) reader chip, for example. A NFC reader chip uses high frequency radio frequency identification at a frequency of 13.56 MHz at a data rate of about 426 kbits/s, for example. In various instances, the processor 10610 comprises a low frequency RFID reader which communicates at a frequency between about 120 kHz and about 150 kHz, for example. In various instances, the processor 10610 comprises a high frequency RFID reader which communicates at a frequency of about 13.6 MHz, for example. In various instances, the processor 10610 comprises an ultra-high frequency

RFID reader which communicates at a frequency of about 868 MHz, for example. The entire disclosure of U.S. Patent Application Publication No. 2020/0405301, entitled METHOD FOR AUTHENTICATING THE COMPATIBILITY OF A STAPLE CARTRIDGE WITH A SURGICAL INSTRUMENT, which published on December 31, 2020, is incorporated by reference herein. In various instances, the processor 10610 comprises a Bluetooth component which communicates at a frequency of about 2.4 GHz, for example. In various instances, the processor 10610 comprises a Qi wireless charging component which communicates at a frequency between about 105 kHz and about 205 kHz, for example. In any event, the processor 10610 comprises input channels and output channels in communication with the instrument antenna 10530 which facilitate direct peer-to-peer communication with a NFC tag, for example, in communication with the cartridge antenna 11530, as discussed below.

[0063] Further to the above, the instrument antenna 10530 is configured to supply power and data signals to the staple cartridge 11000 via the cartridge antenna 11530. As discussed above, the staple cartridge circuit 11500 comprises a plurality of sensors 11600 which measure at least one property of the staple cartridge 11000 and/or at least one property of the tissue supported by the staple cartridge 11000. In at least one embodiment, the sensors 11600 comprise capacitance sensors configured to detect the thickness of the tissue and/or the amount of fluid, or edema, contained in the tissue, for example. In at least one embodiment, the sensors 11600 comprise resistance sensors, such as strain gauges, for example, which measure the strain, or force loading, within the cartridge body 11100, for example. In any event, the sensors 11600 require power to measure a property and produce an output voltage that is detectable by a cartridge processor 11610 of the staple cartridge 11000. In use, power is delivered to the cartridge coil 11540 from the instrument coil 10540, rectified by a rectifier 11620, and then filtered by a capacitor 11630 before it is supplied to the sensors 11600. The rectifier 11620 is configured to rectify an AC input to a DC output for at least one of the output channels of the rectifier 11620. In various instances, the rectifier 11620 is also configured to conduct the AC input to at least one of its output channels without rectification. The capacitor 11630 can comprise a low-pass filter and/or a high-pass filter which can filter out noise and/or extraneous signals received by the cartridge antenna 11530. The above-described arrangement, and/or any other suitable arrangement, can be used to supply an appropriate voltage potential and current to the sensors 11600 and/or the cartridge processor 11610. The output voltages of the sensors 11600 are supplied to input gates of the cartridge processor 11610. In at least one instance, the processor 11610 comprises a multiplexer (MUX), for example, configured to co-ordinate the output signals of the sensors 11600 into a single data signal that is transmitted back to the instrument antenna 10530 via the cartridge antenna

11530.

[0064] Further to the above, the staple cartridge 11000 comprises a NFC tag 11640 in communication with the instrument antenna 10530, the rectifier 11620, the processor 11610, and the cartridge antenna 11530. The NFC tag 11640 comprises an input in communication with the rectifier 11620 which is configured to control and/or limit the voltage potential applied to the NFC tag 11640. In at least one instance, the NFC tag 11640 comprises its own rectifier. Upon receiving an input from the rectifier 11620, the NFC tag 11640 is configured to output a data signal to the cartridge antenna 11530 which includes data regarding the staple cartridge 11000. The NFC tag 11640 has information stored therein regarding the identification of the staple cartridge 11000 stored therein which is included in the data signal. The data signal output by the NFC tag 11640 is transmitted to the instrument antenna 10530 via the cartridge antenna 11530 which is then transmitted to a control system of the surgical instrument 10000, such as the instrument processor 10610, for example, to verify the identification of, or authenticate, the staple cartridge 11000.

[0065] In various instances, further to the above, many different types of staple cartridges may be useable with the surgical instrument 10000. For instance, some staple cartridges may not comprise a sensor array while other staple cartridges, such as staple cartridge 11000, for example, may comprise one or more sensor arrays. If a staple cartridge does not comprise a sensor array, the staple cartridge may not need, or cannot use, the power that can be supplied by the surgical instrument 10000. As such, the control system of the surgical instrument 10000 is configured to supply, or not supply, a power signal to the staple cartridge seated in the surgical instrument 10000 if the staple cartridge does not properly respond to an interrogation signal supplied to the staple cartridge by the surgical instrument 10000 during an interrogation procedure. After a staple cartridge is seated in the surgical instrument 10000, in at least one such instance, the control system of the surgical instrument 10000 can instruct the instrument processor 10610 to send an interrogation signal to the instrument antenna 10530 which is emitted to and received by the cartridge antenna 11530. In various instances, the interrogation signal is emitted with a low power of about 10 mW to about 30 mW, for example, at a frequency that will pass through the filtering in the cartridge circuit 11500 so that the interrogation signal reaches the NFC tag 11640. The NFC tag 11640 is configured to transmit a response signal to the cartridge antenna 11530 upon receiving the interrogation signal. The response signal is emitted by the cartridge antenna 11530, received by the instrument antenna 10530, and conducted to the instrument processor 10610. If the response signal received by the instrument processor 10610 matches a response signal expected by the instrument processor, the staple cartridge 11000 is identified, or authenticated, by the surgical instrument 10000 and the instrument processor 10610 can supply a high-

wattage power signal to the instrument antenna 10530 to power the staple cartridge 11000. In at least one instance, the high-wattage power signal can be about 1 W and/or in excess of 1 W, for example. In various instances, the wattage of the power signal supplied to the instrument antenna 10530 can depend on the staple cartridge that has been identified. For instance, if a first type of staple cartridge is identified, then a first wattage is used and, if a second type of staple cartridge is identified, then a second, or different, wattage is used. However, the control system of the surgical instrument 10000 is configured to not supply a power signal to the instrument antenna 10530 if a response signal is not received from the staple cartridge. If a response signal is received from the staple cartridge seated in the surgical instrument 10000, but not recognized, then the control system can be configured to perform one of two responses. In a first instance, the control system is configured to not supply a power signal to the staple cartridge if the received response signal is not recognized while, in a second instance, the control system is configured to supply a low-power signal if the received response signal is not recognized. In at least one instance, the lower power signal can be about 0.1 W, for example. In such instances, the sensors and electronic circuit may be sufficiently powered to transmit a return data signal that includes data from the sensors while reducing the risk of overpowering the staple cartridge.

[0066] In various instances, the surgical instrument 10000 is configured to initiate a cartridge interrogation routine when the surgical instrument 10000 is initially powered on and/or when the surgical instrument 10000 is woken up from a low-power sleep mode. In such instances, the surgical instrument 10000 interrogates the staple cartridge to assess whether to supply power to the staple cartridge and the level of power to supply to the surgical instrument 10000. That said, absent additional information, the control system of the surgical instrument 10000 may be unable to differentiate between whether the staple cartridge is not identifiable or it is missing altogether if a response signal is not received following the interrogation signal. To this end, the surgical instrument 10000 comprises a cartridge presence sensor configured to detect whether a staple cartridge is seated in the cartridge jaw of the end effector 10400. In at least one instance, the cartridge presence sensor comprises a Hall Effect sensor mounted in the cartridge jaw of the end effector 10400 which is configured to detect a metallic element in the staple cartridge, for example. In at least one instance, the cartridge presence sensor comprises a pressure sensor that is compressed by the staple cartridge when the staple cartridge is seated in the cartridge jaw of the end effector 10400. In either event, the cartridge presence sensor is in communication with the control system of the surgical instrument 10000. If the control system receives a signal that a staple cartridge is seated in the cartridge jaw but does not receive a response signal from the staple cartridge, in various instances, then the control system does not supply a power

signal to the staple cartridge but permits the surgical instrument 10000 to be operated to fire the staples from the staple cartridge. If the control system receives a signal that a staple cartridge is missing from the cartridge jaw, then the control system does not supply a power signal and it also electronically locks out the staple firing system until a staple cartridge is seated in the cartridge jaw.

[0067] When the staple cartridge 11000 is seated in the cartridge jaw of the surgical instrument 10000, referring again to FIG. 6, the power signal and the data signal can be transmitted simultaneously from the instrument antenna 10530 to the cartridge antenna 11530. Moreover, a data signal can be transmitted from the staple cartridge 11000 to the surgical instrument 10000 at the same time that power is being delivered from the surgical instrument 10000 to the staple cartridge 11000. Referring now to FIG. 7, the control system of a surgical instrument 10000' is configured and arranged to supply power and data signals intermittently to a staple cartridge 11000'. In at least one instance, the control system is configured to alternately deliver low-power signals and high-power signals to the instrument antenna 10530 to respectively transmit data and power to an electronic circuit 11500' of the staple cartridge 11000', but not at the same time. In at least one such instance, the control system delivers low-power signals having a power of about 0.1 W and high-power signals over 1 W, for example. As discussed above in connection with FIG. 6, the instrument processor 10610 comprises a NFC reader chip that generates and supplies both the power and data signals to the staple cartridge 11000 simultaneously. On the other hand, FIG. 7 depicts a control system including a NFC reader chip 10610' that generates a data signal and a separate power driver 10620' that generates a power signal. The NFC reader chip 10610' and the power driver 10620' are in communication with the instrument antenna 10530 and are configured to sequentially supply the separate data and power signals to the cartridge antenna 11530 via the instrument antenna 10530. In at least one instance, the NFC reader chip 10610' and the power driver 10620' are in communication with a multiplexer, for example, which co-ordinates the sequential transmission of the data and power signals to the staple cartridge 11000'.

[0068] As discussed above in connection with FIG. 7, data signals and power signals are transmitted between the surgical instrument and the staple cartridge 11000' in an alternating manner. In various instances, the surgical instrument supplies power to the staple cartridge 11000' until the instrument processor has data to transmit to the staple cartridge 11000'. At such point, the instrument processor stops the power signal and then emits the data signal. After the instrument processor has emitted the data signal, the instrument processor is configured to resume the power signal. The data signal and the power signal are transmitted at different frequencies, but could be emitted at the same frequency in other embodiments.

In either event, the power signal is emitted at a higher intensity than the data signal. In various embodiments, the processor of the staple cartridge 11000' is configured to emit a pause signal to the surgical instrument when the processor has data to transmit to the surgical instrument. After receiving the pause signal, the instrument processor stops the power signal or does not generate the power signal until after receiving the data from the staple cartridge 11000'. In at least one such embodiment, the surgical instrument can emit a paused signal back to the staple cartridge 11000' after receiving the pause signal from the staple cartridge. Upon receiving the paused signal from the surgical instrument, the staple cartridge is configured to emit the data signal to the surgical instrument.

[0069] Referring now to FIGS. 8 and 8A, a surgical instrument 10000" comprises a data antenna 10530" and a separate power transmission antenna 10535" that are used to communicate with and supply power to a staple cartridge 11000" seated in a cartridge jaw of the surgical instrument 10000". The data antenna 10530" is in communication with the NFC reader chip 10610'. The power driver 10620' is in communication with the power transmission antenna 10535". The data antenna 10530" comprises a coil 10540" that is aligned with a coil 11540" of a cartridge data antenna 11530" when the staple cartridge 11000" is seated in the cartridge jaw. In at least one instance, the coil 10540" is wound in a plane which is parallel to, or at least substantially parallel to, a plane that defines the cartridge coil 11540". The instrument coil 10540" and the cartridge coil 11540" are the same size, or at least substantially the same size, but can be any suitable size. The instrument coil 10540" comprises a primary coil that comprises a first number of windings and the cartridge coil 11540" comprises a secondary coil that comprises a second number of windings which, in at least one embodiment, is greater than the first number of windings. Such an arrangement can improve the transmission coefficient between the instrument data antenna 10530" and the cartridge data antenna 11530". The power transmission antenna 10535" comprises a coil 10545" that is aligned with a coil 11545" of a cartridge power antenna 11535" when the staple cartridge 11000" is seated in the cartridge jaw. In at least one instance, the instrument coil 10545" is wound in a plane which is parallel to, or at least substantially parallel to, a plane that defines the cartridge coil 11545". The instrument coil 10545" and the cartridge coil 11545" are the same size, or at least substantially the same size, but can be any suitable size. The instrument coil 10545" comprises a primary coil that comprises a first number of windings and the cartridge coil 11545" comprises a secondary coil that comprises a second number of windings which, in at least one embodiment, is greater than the first number of windings. Such an arrangement can improve the transmission coefficient between the power transmission antenna 10535" and the cartridge power antenna 11535".

[0070] Further to the above, the staple cartridge

11000" comprises a rectifier 11620 and a capacitor 11630 in communication with the cartridge power antenna 11535". Similar to the above, the rectifier 11620 and the capacitor 11630 are configured to rectify, filter, and/or modify the power signal supplied to the staple cartridge 11000" from the power transmission antenna 10535" before the power is supplied to a sensor of the staple cartridge 11000". The staple cartridge 11000" further comprises a NFC tag 11640 in communication with the cartridge data antenna 11530". Similar to the above, the control system of the surgical instrument 10000" can interrogate the NFC tag 11640 with an interrogation signal that is generated by the NFC reader chip 10610" and emitted to the NFC tag 11640 via the coupled data antennas 10530" and 11530". Upon receiving the interrogation signal, the NFC tag 11640 is configured to generate a response signal that is emitted back to the NFC reader chip 10610" via the coupled data antennas 10530" and 11530". The NFC tag 11640 is also in communication with a cartridge processor 11610" of the staple cartridge 11000" which, similar to the above, is configured to receive data from the cartridge sensors, generate a data signal comprising the sensor data, and supply the data signal to the NFC tag 11640 and the cartridge data antenna 11530". The data signal supplied to the cartridge data antenna 11530" is transmitted to the NFC reader chip 10610" via the instrument data antenna 10530" and is then used by the control system to interpret a property of the surgical instrument 10000", the staple cartridge 11000", and/or the tissue captured against the staple cartridge 11000", for example. Notably, the cartridge processor 11610" is also in communication with the cartridge power antenna 11535" of the staple cartridge 11000" and can, in various embodiments, supply power to the NFC tag 11640 from the cartridge power antenna 11535".

[0071] As detailed above, the surgical instrument 10000" and the staple cartridge 11000" comprise a first paired antenna system for communicating data and a second paired antenna system for communicating power. In various embodiments, the first paired antenna system is positioned on a first lateral side 11170 of the staple cartridge 11000" and the second paired antenna system is positioned on a second, or opposite, lateral side 11180 of the staple cartridge 11000". In at least one such embodiment, the cartridge jaw of the surgical instrument 10000" comprises a channel including a bottom wall, a first lateral sidewall extending from a first side of the bottom wall, and a second lateral sidewall extending from a second, or opposite, side of the bottom wall. When the staple cartridge 11000" is seated in the cartridge jaw, the staple cartridge 11000" is positioned between the first lateral sidewall and the second lateral sidewall and pushed downwardly toward the bottom wall until snap features and/or lock features of the staple cartridge 11000" engage the cartridge jaw which releasably lock the staple cartridge 11000" in place in the cartridge jaw. In at least one such embodiment, the first instrument an-

tenna is mounted to the first sidewall and the second instrument antenna is mounted to the second sidewall and, moreover, the first cartridge antenna is mounted to a first lateral side of the cartridge body and the second cartridge antenna is mounted to a second lateral side of the cartridge body. When the staple cartridge 11000" is seated in the cartridge jaw, the first cartridge antenna becomes aligned with the first instrument antenna and, likewise, the second cartridge antenna becomes aligned with the second instrument antenna. By placing the first paired antenna system on one lateral side and the second paired antenna system on the opposite lateral side, the possibility of one paired antenna system interfering with the other is reduced. In various instances, the first paired antenna system is operated within a first frequency range and the second paired antenna system is operated within a second, or different, frequency range that does not overlap with the first frequency range such that the possibility of one paired antenna system interfering with the other is reduced. To this end, further to the above, the instrument antennas and/or the cartridge antennas can comprise one or more capacitors which can filter frequencies outside of the intended operating frequency range for each of the paired antenna systems.

[0072] In various instances, further to the above, the cartridge data antenna 11530" is mounted to the first lateral side of the cartridge body 11100 and the cartridge power antenna 11535" is mounted to the second lateral side of the cartridge body 11100. More specifically, the coils 11540" and 11545" of the antennas 11530" and 11535", respectively, are mounted on the proximal ends of their respective sides, i.e., they are positioned much closer to the proximal end 11110 of the staple cartridge 11000" than the distal end 11120. As a result, the cartridge data antenna 11530" and the cartridge power antenna 11535" can be shorter than if they were positioned at the distal end 11120 of the staple cartridge 11000" and are, as a result, less susceptible to interference. In various alternative embodiments, the coils 11540" and 11545" are mounted at or near the centerline between the proximal end 11110 and the distal end 11120 of the staple cartridge 11000". In such an arrangement, the distance between the cartridge data coil 11540" and the sensors mounted to the cartridge body 11100 can be shortened as compared to when the cartridge data coil 11540" is mounted to the proximal end 11110 of the cartridge body 11100, thereby reducing the possibility of the sensor outputs being corrupted before the sensor outputs are processed and transmitted via the cartridge data coil 11540".

[0073] In various embodiments, further to the above, the coils 11540" and 11545" are mounted to the cartridge body 11100 and/or the pan 11700 (FIG. 5A) of the staple cartridge. In at least one embodiment, the cartridge body 11100 comprises a recessed pocket defined in the lateral side thereof and the coils 11540" and 11545" are positioned in the recessed pocket. In at least one such embodiment, a potting material is poured into the re-

cessed pocket to secure, seal, and/or protect the coils 11540" and 11545" within the pocket. The potting material can comprise a sealing glue such as TECHNOMELT from Eastern Adhesive Systems Technology, Inc., for example, a light-cured acrylic adhesive such as LOCTITE 3321 from Henkel Corporation, for example, wax, and/or paraffin, for example. In various instances, the potting material can comprise an air-cured material.

[0074] In various embodiments, the antenna coils 11540" and 11545" are enclosed in the cartridge body using one or more manufacturing processes. In at least one embodiment, the cartridge body 11100 is formed by a two-shot injection molding process. In at least one such embodiment, a first plastic component, or core, is molded during a first injection molding process, the coils 11540" and 11545" are attached to the core, and then a second injection molding process is used to at least partially cover, enclose, seal, and/or protect the coils 11540" and 11545". In at least one embodiment, the coils 11540" and 11545" are positioned in a recess or pocket defined in the cartridge body and a cover is attached to the cartridge body 11100 which at least partially covers, encloses, seals, and/or protects the coils 11540" and 11545". In at least one such embodiment, the cover is snap-fit and/or press-fit to the cartridge body 11100. In certain embodiments, an ultrasonic staking process is used to attach the cover to the cartridge body 11000.

[0075] The above-described materials and methods for attaching the antenna coils 11540" and 11545" to the cartridge body 11100 can also be used to attach RFID tags to the sled 11400 and/or staple drivers 11300. In such embodiments, the positions and/or motions of the sled 11400 and/or staple drivers 11300 can be tracked by the control system of the staple cartridge 11000 using the RFID tags attached to and/or embedded within the sled 11400 and/or staple drivers 11300.

[0076] As discussed above, the surgical instrument 10000 comprises a shaft 10200 extending distally from a handle and/or an instrument housing configured to be mounted to the arm of a robotic surgical system. In various instances, the shaft 10200, the handle 10100, the instrument housing, and/or the robotic surgical system can comprise an instrument processor in communication with the staple cartridge through one or more antenna couples, as discussed above. To facilitate communication between the instrument processor and the cartridge processor, the shaft 10200 comprises a wiring harness including the instrument antennas. In at least one such embodiment, the wiring harness comprises a flex circuit 10900 (FIG. 11B) including a flexible substrate and conductive wires, or traces, extending within the flexible substrate. In various embodiments, the flex circuit 10900 comprises a stack of conductive and insulative layers, for example. Referring to FIG. 8C, the distal end of a flex circuit of the surgical instrument 10000" includes the coils 11540" and 11545" which comprise embedded wires within the non-conductive substrate of the flex circuit.

[0077] Further to the above, the distal end of the flex circuit is mounted to the sidewall of the first jaw 10410 by one or more adhesives, for example. In at least one embodiment, ferrite components can be mounted to and/or embedded within the substrate of the flex circuit to control the fields emitted by the coils 11540" and 11545". In at least one embodiment, the ferrite components are positioned intermediate the first jaw 10410 and the coils 11540" and 11545". Moreover, electronic components can be mounted to and/or embedded within the substrate of the flex circuit which condition and/or amplify the signals emitted by the coils 11540" and 11545". In at least one such embodiment, one or more capacitors are embedded in the flex circuit which filter out low and/or high frequencies. Moreover, in at least one such embodiment, one or more amplification circuits are embedded in the flex circuit which can boost and/or control the power of the signals being emitted by the coils 11540" and 11545". In various embodiments, the first jaw 10410 and/or the second jaw 10420 are comprised of metal and are configured to minimize the impact of the metal jaws on the fields emitted by the coils 11540" and 11545". In at least one embodiment, the cross-sections of the metal jaws are designed to create a uniform, or substantially uniform, area that shields, or substantially shields, external signals from interfering with signals within the end effector 10400.

[0078] In embodiments where the coils 11540" and 11545" are mounted to the cartridge body 11000 and the coils 10540" and 10545" are mounted to the first jaw 10410, the pan 11700 can comprise one or more windows defined therein such that the coils 10540" and 11540" of the data coil set have a direct line-of-sight with one another and the coils 10545" and 11545" of the power coil set have a direct line-of-sight with one another. In embodiments where the coils 11540" and 11545" are mounted to the pan 11700, the coils 10540" and 11540" of the data coil set have a direct line-of-sight with one another and the coils 10545" and 11545" of the power coil set have a direct line-of-sight with one another.

[0079] In various embodiments, the antennas of the surgical instrument 10000" and/or the antennas of the staple cartridge 11000" comprise coil antennas. That said, a surgical instrument and/or staple cartridge can comprise any suitable type of antennas. In at least one instance, the surgical instrument and/or the staple cartridge can comprise a slot antenna. In at least one such embodiment, a slot antenna comprises a flat plate with one or more holes or slots cut out. One or more slot antennas can be mounted to the sidewalls and/or bottom wall of the first jaw 10410 while one or more slot antennas can be mounted to the pan 11700. In various embodiments, a slot antenna can be integrally-formed with the first jaw 10410 and/or the pan 11700, for example.

[0080] In various embodiments, a surgical instrument and/or staple cartridge can comprise an active cancellation system including a control system which monitors for environmental magnetic and/or electrical fields and their

frequencies and emits signals through one or more antennas to cancel, or at least partially cancel, the environmental fields.

[0081] In various embodiments, the cartridge body of a staple cartridge comprises conductive traces plated on a plastic substrate, which can be made of a liquid crystal polymer such as VECTRA from Ticona, for example. In at least one embodiment, the conductive traces are electroplated on the plastic substrate and/or plated onto the plastic substrate using a vapor deposition process, for example. In at least one embodiment, the electrical traces are comprised of a conductive ink that is printed onto the plastic substrate, for example. In various instances, the traces are comprised of silver and/or copper, for example. In various embodiments, the cartridge body comprises recesses defined in the plastic substrate where conductive traces are plated onto the plastic substrate in the recesses. In at least one embodiment, the recesses are laser-etched into the plastic substrate. In various embodiments, a non-conductive material is printed onto the conductive traces to cover the conductive traces where it is not desired for the tissue, for example, to touch the conductive traces. Such a non-conductive material can also control the fields produced by the conductive traces. In various embodiments, the plastic substrate is formed by a three-dimensional printing process using a non-conductive material and a conductive material, such as graphene-imbedded polylactic acid (PLA). In at least one such embodiment, conductive material is printed into conductive traces that are at least partially embedded in the non-conductive material.

[0082] In various embodiments, further to the above, the staple cavities 11140 are arranged in three longitudinal rows on a first side of the cartridge deck 11130 and three longitudinal rows on a second, or opposite side, of the cartridge deck 11130. After the staple firing stroke has been performed, the patient tissue has been incised with three rows of staples on both sides of the incision to seal, or at least substantially seal, the tissue. That said, implanting two rows of staples on both sides of the incision, instead of three, has been shown to be clinically acceptable. As such, the third row of staples does not need to comprise a continuous row of staples. Instead, in at least one embodiment, at least some of the staple cavities 11140 in the outermost rows house a sensor therein instead of staple and a staple driver. In at least one such embodiment, a force-sensitive sensor is positioned in a staple cavity 11140. The force-sensitive sensor comprises a tissue contact element slideable within the staple cavity 11140 that is sized and configured to match, or at least substantially match, the perimeter of the staple cavity 11140 such that the motion of the tissue contact element is limited, or at least substantially limited, to the ejection axis of the staple cavity 11140. The force-sensitive sensor further comprises a base mounted to the cartridge deck 11130 and a spring, such as a linear coil spring, for example, positioned intermediate the base and the tissue contact element. When the end effector

10400 is clamped onto the patient tissue, the tissue contacts the tissue contact element and compresses the spring. The force-sensitive sensor further comprises a magnetic element mounted to the tissue contact element, the motion of which is detectable and measurable by a Hall Effect circuit in the cartridge deck 11130, for example. The Hall Effect circuit is in communication with the cartridge processor which is configured to analyze the voltage output to assess whether there is tissue positioned over the force-sensitive sensor and the force being applied to the tissue at the force-sensitive sensor. The staple cartridge 11000 can comprise any suitable number of force-sensitive sensors. For instance, in at least one embodiment, both of the outermost rows of staple cavities 11140 comprises a sensor at the distal end of the staple cartridge 11000, a sensor at the proximal end of the staple cartridge 11000, and at least one sensor positioned intermediate the distal sensor and the proximal sensor. The above being said, the staple cartridge can comprise any suitable type of sensor and/or number of sensors in the staple cavities.

[0083] In at least one embodiment, further to the above, some of the staple cavities 11300 can include a typical staple driver positioned therein, but not a staple, and at least a portion of a sensor extending over the staple cavity. In at least one such embodiment, the portion of the sensor extending over the staple cavity is frangible and is configured to break, or snap, when the staple driver is driven upwardly toward the anvil during the staple firing stroke. Such an arrangement can be used to progressively cut off sensors from the cartridge processor as the staple firing stroke progresses. Such an arrangement can be used to conserve processing power and/or track the progress of the staple firing stroke, among other things.

[0084] The entire disclosures of U.S. Patent No. 8,622,274, entitled MOTORIZED CUTTING AND FASTENING INSTRUMENT HAVING CONTROL CIRCUIT FOR OPTIMIZING BATTERY USAGE, U.S. Patent No. 10,135,242, entitled SMART CARTRIDGE WAKE UP OPERATION AND DATA RETENTION, U.S. Patent No. 10,548,504, entitled OVERLAID MULTI SENSOR RADIO FREQUENCY (RF) ELECTRODE SYSTEM TO MEASURE TISSUE COMPRESSION, U.S. Patent No. 9,993,248, entitled SMART SENSORS WITH LOCAL SIGNAL PROCESSING, U.S. Patent Application Publication No. 2016/0256071, entitled OVERLAID MULTI SENSOR RADIO FREQUENCY (RF) ELECTRODE SYSTEM TO MEASURE TISSUE COMPRESSION, now U.S. Patent No. 10,548,504, U.S. Patent Application No. 2018/0168625, entitled SURGICAL STAPLING INSTRUMENTS WITH SMART STAPLE CARTRIDGES, U.S. Patent Application No. 2018/0250002, entitled POWERED SURGICAL DEVICES HAVING TISSUE SENSING FUNCTION, and International Patent Publication No. WO 2018/049206, entitled STAPLER RELOAD DETECTION AND IDENTIFICATION, are incorporated by reference herein.

[0085] In various instances, referring to FIG. 9, a staple cartridge 12000 comprises an identification circuit 12100 and a power supply circuit 12200 which are independent from one other. The identification circuit 12100 comprises a passive RFID system 12110, for example, which is energized when an interrogation signal is transmitted to the cartridge data antenna 11530" from the instrument data antenna 10530". The identification circuit 12100 is self-contained and does not receive power from the power supply circuit. The passive RFID system 12110 does not comprise a power source and is powered by the interrogation signal. Once the passive RFID system 12110 has received the interrogation signal, the passive RFID system 12110 transmits a response signal back to the surgical instrument via the cartridge data antenna 11530" that includes data regarding the identification of the staple cartridge 12000. The surgical instrument comprises an RFID reader chip 12610 which is configured to receive and process the response signal from the passive RFID system 12110. In at least one alternative embodiment, the independent identification circuit comprises an active RFID system that includes its own power source. In such an embodiment, the active RFID system can comprise a beacon that periodically emits an identification signal that has enough power to be received by the instrument data antenna 10530".

[0086] In various embodiments, further to the above, the independent power supply circuit 12200 of the staple cartridge 12000 comprises a cartridge power antenna 11535" configured to receive power from the power transmission antenna 10535" of the surgical instrument. In various instances, similar to the above, the staple cartridge 12000 is configured to transmit a data signal back to the surgical instrument across the power antenna couple including the antennas 10535" and 11535" that includes data from the sensor array 11600 of the staple cartridge 12000. In certain instances, the staple cartridge 12000 comprises a third antenna configured to transmit sensor data back to the surgical instrument across a low-power antenna couple which is separate and independent from the power antenna couple of the power circuit 12200 and the cartridge identification circuit 12100. In such instances, power is transmitted from the surgical instrument to the staple cartridge across a power antenna couple, identification signals are transmitted between the surgical instrument and the staple cartridge across an identification signal antenna couple, and sensor data is transmitted from the staple cartridge to the surgical instrument across a sensor data signal antenna couple.

[0087] In various embodiments, referring to FIG. 10, a staple cartridge 13000 comprises a cartridge power antenna 11535" and a cartridge data antenna 11530" which are both coupled to a single instrument antenna 13530. In at least one such embodiment, the single instrument antenna 13530 comprises a coil 13540 which is defined in an instrument coil plane, the cartridge data antenna 11530" comprises a coil 11540" defined in a data coil plane, and the cartridge power antenna 11535" com-

prises a coil 11545" defined in a power coil plane. The coils 13540, 11540", and 11545" are stacked such that signals transmitted by the single instrument antenna 13530 are received by the cartridge data antenna 11530" and the cartridge power antenna 11535". In at least one instance, the coils 13540, 11540", and 11545" may be positioned on one lateral side of the staple cartridge 13000. In various instances, the coils 13540, 11540", and 11545" may be positioned on the bottom of the staple cartridge 13000. In various instances, it may be desirable for the cartridge data antenna 11530" to receive signals at a lower power than the cartridge power antenna 11535". In at least one such instance, the coils 13540, 11540", and 11545" are stacked such that the cartridge power coil 11545" is positioned intermediate the instrument antenna coil 13540 and the cartridge data coil 11540". In such instances, as a result, the intensity of the signals emitted by the instrument antenna coil 13540 is greater at the cartridge power coil 11545" than at the cartridge data coil 11540". In various instances, the coils 13540, 11540", and 11545" are spaced equally, or equidistant, from one another. In other instances, the gap between the cartridge data coil 11540" and the cartridge power coil 11545" is larger than the gap between the cartridge power coil 11545" and the instrument antenna coil 13540. In such instances, the power transmitted to the cartridge data coil 11540" may be substantially lower than the power transmitted to the cartridge power coil 11545". In various alternative embodiments, the instrument antenna coil 13540 is positioned intermediate the cartridge data coil 11540" and the cartridge power coil 11545" and the coils 11540" and 11545" can be positioned at any suitable distance from the instrument antenna coil 13540.

[0088] Referring to FIG. 10 once again, the instrument antennas 10530" and 10535" are used to emit fields that interact with the cartridge antennas 11530" and 11535". In various instances, the fields emitted by the instrument antennas 10530" and 10535" are emitted omni-directionally. As a result, a significant amount of power may be emitted by the instrument antennas 10530" and 10535" which is not received by the cartridge antennas 11530" and 11535". In various instances, the surgical instrument is configured to shape the fields emitted by the instrument antennas 10530" and 10535". In at least one instance, the surgical instrument comprises one or more metal walls which surround the instrument data antenna 10530" and/or the power transmission antenna 10535", for example. Such metal walls can limit the intensity of the emitted fields in directions which are not toward the cartridge antennas 11530" and 11535". In at least one instance, the metal walls form a horn which directs the emitted fields from the coil of an instrument antenna toward the coil of the corresponding cartridge antenna. In at least one such instance, the metal walls extend from a metal sidewall and/or metal bottom wall of the cartridge jaw, for example. In various instances, a ferrite ring, for example, can be positioned around the coil of an instru-

ment antenna to tunnel the emitted field toward the coil of the corresponding cartridge antenna. In at least one such instance, the ferrite ring is mounted to the sidewall and/or bottom wall of the cartridge jaw, for example. In various instances, the staple cartridge 11000" comprises metal walls which direct the fields emitted from an instrument antenna toward the coil of the corresponding cartridge antenna. In at least one such instance, the metal walls form a horn mounted to the cartridge body of the staple cartridge which is comprised of plastic, for example. Also, in various instances, the staple cartridge comprises ferrite material which is configured to direct and/or amplify the fields emitted by the coils of the instrument antennas to the corresponding cartridge antennas. The entire disclosures of U.S. Patent No. 10,135,242, entitled SMART CARTRIDGE WAKE UP OPERATION AND DATA RETENTION, which issued on November 20, 2018, U.S. Patent No. 9,345,481, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, which issued on May 24, 2016, and U.S. Patent No. 9,872,722, entitled WAKE-UP SYSTEM AND METHOD FOR POWERED SURGICAL INSTRUMENTS, which issued on January 23, 2018, are incorporated by reference herein.

[0089] As discussed above, referring again to FIG. 5A, the staple cartridge 11000 comprises a metal pan 11700 attached to the cartridge body 11100. The metal pan 11700 comprises a floor 11710 that extends around the bottom of the cartridge body 11100 and is configured to prevent the staple drivers 11300 and/or the staples from falling out of the bottom of the staple cartridge 11000. The metal pan 11700 comprises a first sidewall 11720 that extends alongside the first lateral side of the cartridge body 11100 and a second sidewall 11720 that extends alongside the second lateral side of the cartridge body 11100. The first sidewall 11720 is attached to the cartridge body 11100 via one or more attachment features 11730 such as a hook and/or shoulder retainer, for example. Similar to the first sidewall 11720, the second sidewall 11720 is attached to the cartridge body 11100 via one or more attachment features 11730 such as a hook and/or shoulder retainer, for example. The metal pan 11700 is comprised of any suitable metal, such as stainless steel, for example. In various embodiments, the metal pan 11700 can also include portions comprised of plastic and/or any other suitable material. In various instances, the cartridge antennas are mounted to the metal pan 11700. In at least one such instance, the cartridge data coil 11540" and/or the cartridge power coil 11545" is mounted to the metal pan 11700 which can position the coils closer to their respective instrument antennas and improve the transmission efficiency of the antennas.

[0090] In various embodiments, a surgical instrument and/or staple cartridge can comprise a mask or shield configured to control, block, and/or direct signals emitted by the surgical instrument and/or the staple cartridge. In at least one embodiment, a mask is comprised of ferrite, for example. In at least one embodiment, the cartridge

jaw comprises metal wall shields extending from the sidewalls and/or bottom walls. In at least one embodiment, the pan and/or cartridge body of a staple cartridge comprises metal wall shields contained therein and/or extending therefrom. In at least one embodiment, the mask is configured to limit the direction in which the signal is emitted and/or received. In various embodiments, a surgical instrument and/or staple cartridge comprises a horn antenna configured to direct a signal emitted therefrom. In at least one embodiment, a surgical instrument and/or staple cartridge can comprise an antenna comprised of a metal wall. In at least one such embodiment, the cartridge jaw of the surgical instrument is comprised of metal walls, at least one of which is used as an antenna. Moreover, in at least one such embodiment, the pan of the staple cartridge is comprised of metal walls, at least one of which is used as an antenna. In various embodiments, one or more capacitors or capacitive elements are soldered to the pan of the staple cartridge which can filter out unwanted frequencies being conducted within and/or transmitted through the pan.

[0091] Referring to FIG. 11, a staple cartridge, such as staple cartridge 14000, for example, comprises a cartridge body 11100 and an electronic circuit 11500 including sensors 11600. The staple cartridge 14000 is similar to the other staple cartridges disclosed herein in many respects and such respects are not discussed herein for the sake of brevity. As discussed above, the cartridge body 11100 comprises a deck 11130 and longitudinal rows of staple cavities 11140 defined in the deck 11130. Each staple cavity 11140 comprises a staple stored therein that is driven upwardly out of the staple cavity 11140 by a staple driver during a staple firing stroke. Each staple comprises a base and two legs extending from the base such that the legs extend generally upwardly and outwardly to form a V-shape configuration. In various instances, the legs of the staple are resiliently deflected inwardly by the proximal and distal end walls of the staple cavity 11140 when the staple is stored in the staple cavity 11140. When the staple is driven upwardly out of the staple cavity 11140, the legs of the staple emerge from the staple cavity 11140 and extend above the deck 11130 while the rest of the staple is pushed upwardly out of the staple cavity 11140. The cartridge body 11100 comprises projections 11132 (FIG. 5B) extending from the deck 11130 which are configured to guide and/or control the legs of the staples as the staples are being ejected from the staple cavities 11140. A projection 11132 is positioned at the distal end of each staple cavity 11140 and at the proximal end of each staple cavity 11140. However, alternative embodiments are envisioned in which a projection 11132 is positioned at only one end of each staple cavity 11140. Moreover, various embodiments are envisioned in which some of the staple cavities 11140 do not comprise projections 11132 at the ends thereof. The projections 11132 are further configured to engage the patient tissue positioned against the deck 11130 and limit the flow or movement of the patient

tissue relative to the deck 11130.

[0092] In various embodiments, the electronic circuit 11500 comprises a substrate including features engaged with the projections 11132. In at least one embodiment, the substrate comprises apertures defined therein, the sidewalls of which are engaged with the projections 11132. The apertures are in a snap-fit and/or press-fit arrangement with the projections 11132 such that the electronic circuit 11500 is held in position relative to the cartridge body 11100. In at least one embodiment, the projections 11132 comprise at least partially annular or circumferential shoulders which hold the sensor circuit 11500 against the cartridge body 11100.

[0093] In various embodiments, a sensor circuit of a staple cartridge is comprised of a conductive material printed on the deck of the cartridge body. In at least one embodiment, the conductive material is comprised of metal particles bonded to the deck which form an electrical circuit connecting the sensors. In at least one such embodiment, the printed electrical circuit is printed onto the cartridge body with a three-dimensional printer. In various embodiments, the sensor circuit comprises electrodes, or contacts, that are printed onto the cartridge body. In at least one embodiment, the sensor circuit comprises electrodes which comprise a polygonal surface configured to contact the tissue. In at least one alternative embodiment, the electrodes comprise a curved and/or tortuous path on the deck surface which, in various instances, can increase the contact area between the electrodes and the tissue. In at least one embodiment, the electrodes comprise needles extending therefrom which are configured to penetrate the tissue. In at least one embodiment, the needles comprise a diameter of about 1 μm , for example. In various instances, the needles provide parallel signal paths between the tissue and the sensor circuit within one electrode to improve the sensitivity of the sensor circuit. In at least one embodiment, a conductive grease or conductive viscous agent covers the tissue contact points of the sensor circuit which improves the contact between the electrodes and the tissue. In various embodiments, portions of the sensor circuit are embedded in the cartridge body. In at least one such embodiment, the sensor circuit comprises flat, thin conductors that are embedded into the cartridge body when a plastic material, for example, is overmolded onto portions of the conductors. Portions of the conductors, however, remain exposed to provide tissue engaging pads and/or electrically-conductive attachment points for soldering sensors thereto. In at least one embodiment, part of the cartridge sensor circuit can be defined on the lateral sidewalls of the cartridge jaw. In at least one such embodiment, a proximal portion and a distal portion of the sensor circuit are defined on the cartridge body and an intermediate portion of the sensor circuit is defined on the cartridge jaw that electrically connects the proximal portion and the distal portion of the sensor circuit. In at least one embodiment, the portions of the sensor circuit mounted to the cartridge jaw

comprise conductive strips mounted to the sidewalls. When the staple cartridge is seated in the cartridge jaw, the cartridge sensor circuit engages the conductive strips to complete the circuit.

[0094] As discussed above, a sensor circuit can include conductive tissue-contacting surfaces. In various embodiments, a sensor circuit can include non-conductive tissue-contacting surfaces. In at least one embodiment, a sensor circuit comprises one or more capacitive electrodes. In various instances, projected capacitance measurement techniques are used to measure the presence of the tissue over the capacitive electrodes and/or a property of the tissue over the capacitive electrodes. In at least one embodiment, each capacitive electrode comprises an insulative covering which covers capacitive pads contained therein. In various instances, further to the above, surface capacitance measurement techniques can be used. In various embodiments, a sensor circuit comprises one or more inductive sensors. In at least one embodiment, an eddy current is induced in each of the inductive sensors which changes when the tissue contacts the sensors. In such embodiments, the changes to the sensor eddy currents are detected by the control system of the staple cartridge. In various embodiments, the sensor circuit can comprise temperature sensors which are used to detect the presence of tissue over the temperature sensors. In at least one embodiment, the sensor circuit comprises electrodes comprised of a doped polycrystalline ceramic comprising barium titanate (BaTiO_3), for example. The resistance of these ceramic materials changes in response to temperature changes, such as when patient tissue is positioned against the electrodes. The cartridge processor is configured to employ an algorithm to monitor the resistance fluctuations in the ceramic materials to assess whether or not tissue was positioned against the electrodes. In various instances, the electrodes of the sensor circuit are in a parallel arrangement such that a detected resistance, capacitance, voltage, and/or current change can be directly related to the position of a sensor. With this information, the processor can assess whether and where tissue is positioned over the staple cartridge.

[0095] Referring to FIGS. 11A and 11D, the staple cartridge 14000 further comprises a laminate material 14900 mounted to one or more components of the staple cartridge 14000 to control the electrical effects created within the cartridge components by the fields emitted from and/or surrounding the staple cartridge 14000. In at least one instance, the laminate material 14900 comprises a flux field directional material including at least two layers - a first layer 14910, or cover, and a second layer 14920 of magnetic material attached to the first layer 14910. The first layer 14910 is comprised of polyethylene terephthalate, for example, which protects the second layer 14920, but can be comprised of any suitable material. The second layer 14920 is comprised of a sintered ferrite sheet, for example, but can be comprised of any suitable material. In at least one instance, an

adhesive layer 14930 comprised of a pressure-sensitive adhesive, for example, is bonded to the second layer 14920 and is used to attach the laminate material 14900 to one or more components of the staple cartridge 14000, as discussed further below. In at least one instance, the laminate material 14900 is a Flux Field Directional Material EM15TF manufactured by 3M, for example.

[0096] In various embodiments, further to the above, laminate material 14900 is bonded to the cartridge body 11100 and is arranged to change and/or control the shape of the fields extending from the cartridge antennas. In at least one embodiment, the laminate material 14900 focuses the fields away from the metal cartridge jaw of the surgical instrument 10000 in which the staple cartridge 14000 is seated. In at least one instance, the cartridge body 11100 is comprised of plastic and the laminate material 14900 is mounted to the cartridge body 11100 such that the laminate material 14900 surrounds, or at least substantially surrounds, the cartridge antennas. In at least one instance, laminate material 14900 is mounted to the cartridge body 11100 at a location which is intermediate the cartridge data coil 11540" and the cartridge power coil 11545" such that the cartridge coils 11540" and 11545" are separated by the laminate material 14900. In various embodiments, laminate material 14900 is bonded to the metal walls of the cartridge jaw 10410. In at least one instance, laminate material 14900 is mounted to the metal walls of the cartridge jaw 10410 at a location which is intermediate the instrument data coil 10540" and the power transmission coil 10545". In various embodiments, the laminate material 14900 bonds the cartridge data antenna 11530" and/or the cartridge power antenna 11535" to the cartridge body 11100. In at least one embodiment, the laminate material 14900 bonds the instrument data antenna 10530" and/or the instrument power antenna 10535" to the metal cartridge jaw 10410.

[0097] In various embodiments, further to the above, laminate material 14900 is mounted to the metal pan 11700. In at least one such instance, laminate material 14900 is positioned intermediate the metal pan 11700 and the cartridge data antenna 11530" and, also, intermediate the metal pan 11700 and the cartridge power antenna 11535". Such an arrangement can focus the fields created by the antennas 11530" and 11535" away from the metal pan 11700 to minimize the electrical effects that the fields have on the metal pan 11700. In various embodiments, laminate material 14900 is mounted to the movable components of the staple cartridge 14000. In at least one instance, referring to FIG. 11D, laminate material 14900 is mounted to the sled 11400. In at least one such instance, laminate material 14900 is mounted to the lateral sides 11410 of the sled 11400, for example. In at least one instance, referring to FIG. 11A, laminate material 14900 is mounted to one or more of the staple drivers 11300, for example. In at least one such instance, laminate material 14900 is mounted to the lateral sides 11310 of the staple drivers 11300.

Laminate material 14900 can be mounted to all of the staple drivers 11300, or just the staple drivers 11300 adjacent the cartridge antennas 11530" and 11535", for example.

[0098] Further to the above, the fields generated by the cartridge antennas and/or instrument antennas can affect the output of the sensors 11600. Such an effect can be reduced or mitigated by the laminate material 14900, for example. In various instances, the processor of the staple cartridge 14000 is configured to electronically account for the effect that the antenna fields will have on the sensors 11600. In at least one such instance, the cartridge processor can monitor when signals are being transmitted between the antenna couples and, in such instances, modify the sensor outputs being received from the sensors 11600 before transmitting the sensor outputs to the surgical instrument processor and/or recording the sensor outputs in a memory device in the staple cartridge 14000. When signals are not being transmitted between the antenna couples, the sensor outputs may not need to be modified by the processor before being transmitted to the surgical instrument processor and/or recorded in a memory device in the staple cartridge 14000. In various instances, the processor can apply a first compensation factor to the sensor outputs when the power antenna couple is transmitting signals, a second compensation factor to the sensor outputs when the signal antenna couple is transmitting signals, and a third compensation factor to the sensor outputs when both antennas are transmitting signals. In at least one such instance, the third compensation factor is larger than the first compensation factor and the first compensation factor is larger than the second compensation factor, for example.

[0099] Further to the above, the circuit 11500 is flush with the top surface of the deck 11130 and/or recessed with respect to the top surface of the deck 11130. In various instances, the staple cartridge 11000 further comprises latches rotatably mounted thereto which are rotatable from an unlatched position to a latched position to hold the circuit 11500 in the circuit slot 11160. The latches engage the cartridge body 11100 in a press-fit and/or snap-fit manner when the latches are in their latched position. When the latches are in their latched position, the latches are flush with and/or recessed below the top surface of the deck 11130. In at least one embodiment, the projections 11132 are mounted to and/or integrally-formed with the latches and/or any other suitable restraining features. In any event, the circuit 11500 comprises one or more sensors which are held in place relative to the cartridge body 11100 as a result of the above.

[0100] As discussed above, the sensors 11600 may be effected by their surrounding environment. In various instances, the sensors 11600 may be effected by temperature changes when the end effector 10400 of the surgical instrument is inserted into a patient. Referring to FIG. 12, a staple cartridge, such as staple cartridge 15000, for example, can comprise a thermal manage-

ment system. The staple cartridge 15000 is similar to the other staple cartridges disclosed herein in many respects, and such respects are not repeated for the sake of brevity. The staple cartridge 15000 comprises a cartridge body 15100 and sensors 11600 mounted to the cartridge body 15100. The staple cartridge 15000 further comprises a heat sink system 15800 that moves and/or equalizes thermal energy with the cartridge body 15100. The cartridge body 15100 comprises a first lateral side 15170 and a second lateral side 15180 and the heat sink system 15800 comprises a first heat sink 15870 embedded in the first lateral side 15170 and a second heat sink 15880 embedded in the second lateral side 15180. The first heat sink 15870 comprises a first longitudinal rail 15872 extending along the first lateral side 15170 of the cartridge body 15100 and lateral rails 15874 extending laterally from the first longitudinal rail 15872. The lateral rails 15874 extend between and around the staple cavities 11140 and conduct heat outwardly away from the sensors 11600 which are positioned adjacent the first longitudinal rail 15872. That said, other embodiments are envisioned in which the rails 15872 and 15874 are arranged to conduct heat inwardly away from sensors 11600 positioned along the outer perimeter of the cartridge body 15100. The second heat sink 15880 comprises a second longitudinal rail 15882 extending along the second lateral side 15180 and lateral rails 15884 extending from the second longitudinal rail 15882. The lateral rails 15884 extend between and around the staple cavities 11400 and conduct heat outwardly away from the sensors 11600 which are positioned adjacent the second longitudinal rail 15882. That said, other embodiments are envisioned in which the rails 15882 and 15884 are arranged to conduct heat inwardly away from sensors 11600 positioned along the outer perimeter of the cartridge body 15100.

[0101] Further to the above, the first heat sink 15870 and the second heat sink 15880 are configured to conduct heat from one region of the staple cartridge 15000 to another. In various instances, the first heat sink 15870 includes a first region comprised of a first material having a first thermal conductivity and a second region having a second thermal conductivity which is higher than the first thermal conductivity. In at least one instance, the first region is positioned adjacent the sensors 11600 such that the second region quickly draws heat out of the first region. In this way, the first heat sink 15870 comprises a heat pump. The second heat sink 15880 can comprise a similar arrangement. In various instances, the first heat sink 15870 includes a first region comprised of a first material having a first thermal capacitance and a second region comprised of a second material having a second thermal capacitance which is higher than the first thermal capacitance. In such embodiments, the second region can store heat away from the sensors 11600. The second heat sink 15880 can comprise a similar arrangement.

[0102] Further to the above, in various instances, the first longitudinal rail 15872 comprises a constant cross-

section along the length thereof. In use, thermal energy will flow along the first longitudinal rail 15872 from a location with a higher temperature along the first longitudinal rail 15872 to a location with a lower temperature.

In at least one alternative embodiment, the cross-section of the first longitudinal rail 15872 changes along the length thereof. In use, thermal energy can flow along the first longitudinal rail 15872 from a location having a small cross-section to a location having a larger cross-section. In at least one instance, the first longitudinal rail 15872 is tapered linearly from one end to the other. In at least one such instance, the larger end of the first longitudinal rail 15872 is at the distal end of the staple cartridge 15000. In such instances, heat may flow toward the distal end of the staple cartridge 15000 instead of toward the processor and/or other electronics in the proximal end of the staple cartridge 15000, for example. The second heat sink 15880 can comprise a similar arrangement.

[0103] Further to the above, in various instances, the lateral rails 15874 comprise a constant cross-section along the length thereof. In use, thermal energy will flow along the lateral rails 15874 from a location with a higher temperature to a location with a lower temperature. In at least one alternative embodiment, the cross-section of the lateral rails 15874 change along the length thereof. In use, thermal energy can flow along the lateral rails 15874 from a location having a small cross-section to a location having a larger cross-section. In at least one instance, each lateral rail 15874 is tapered linearly from one end to the other. In at least one such instance, the larger end of the lateral rail 15874 is at the lateral side of the staple cartridge 15000. In such instances, heat may flow from the first longitudinal rail 15872 toward the lateral side of the staple cartridge 15000 where the heat can be easily dissipated from the staple cartridge 15000. The second heat sink 15880 can comprise a similar arrangement. That said, any suitable configuration of heat sink can be used.

[0104] In various instances, further to the above, a portion of a heat sink is in direct contact with at least one electronic component of the staple cartridge 15000. In at least one instance, the staple cartridge 15000 comprises a microprocessor mounted to the cartridge body 15100 and the heat sink is in direct abutting contact with the microprocessor, for example. In various embodiments, the cartridge body 15100 directly contacts at least one electronic component of the staple cartridge 15000. In at least one instance, the cartridge body 15100 comprises fins extending therefrom which increase the convection surface area and the rate in which the electronic components can be cooled. In at least one such instance, referring to FIG. 11A, the cartridge body 15100 comprises longitudinal rails 11105 which define longitudinal slots 11115 configured to receive staple driving rails 11415 of the sled 11400 where the longitudinal rails 11015 are part of a thermal path for cooling the electronic components of the staple cartridge 15000. In at least one embodiment,

the longitudinal rails 11105 of the cartridge body 15100 are at least partially coated in a material which improves the thermal conductivity, convection, and/or radiation of heat between the electronic components and the longitudinal rails 11105 and between the longitudinal rails 11105 and the ambient environment. In various embodiments, the metal pan 11700 of the staple cartridge 15000 is in abutting contact with one or more electronic components of the staple cartridge and is configured to conduct heat away from the electronic components. In at least one embodiment, the cartridge body 15100 and/or the metal pan 11700 comprises windows or throughholes therein which are configured to permit body fluids to enter into the staple cartridge 15000 when the end effector 10400 is in the patient. In such embodiments, the electronic components of the staple cartridge 15000 are coated in a sealant, such as an epoxy, for example, which protects the electronic components when the body fluids enter into the staple cartridge 15000. Such openings could also be positioned and arranged to facilitate the contact of body fluids with the heat sinks of the staple cartridge 15000.

[0105] In various embodiments, the staple cartridge 15000 further comprises a temperature sensor circuit including at least one temperature sensor 15900 in communication with the processor of the staple cartridge 15000. In at least one embodiment, the temperature sensor 15900 comprises a thermistor, thermocouple, and/or resistance temperature detector, for example. In various instances, the staple processor, electronic hardware, tissue sensors, and/or antennas of the staple cartridge 15000 generate heat which, in some circumstances, can negatively impact the function of these devices. With the data provided to the staple cartridge processor from the temperature sensor 15900, the staple cartridge processor can adjust its sampling or processing rate of the tissue sensors, for example, to reduce the heat generated by the staple cartridge processor. In at least one instance, the staple cartridge processor is configured to reduce the data sampling or processing rate of the tissue sensors when the temperature sensed by the temperature sensor 15900 exceeds a threshold. In at least one embodiment, the staple cartridge processor can maintain the lower sampling rate of the tissue sensors regardless of whether the temperature stays above or falls back below the temperature threshold. In other embodiments, the staple cartridge processor can increase, or restore, the sampling rate of the tissue sensors after the temperature sensed by the temperature sensor 15900 falls back below the temperature threshold. Similarly, the staple cartridge processor can be configured to reduce the data transfer rate between the staple cartridge 15000 and the surgical instrument across the data antenna couple when the temperature sensed by the temperature sensor 15900 exceeds a threshold. In at least one embodiment, the staple cartridge processor can maintain the lower transfer rate regardless of whether the temperature stays above or falls back below the

temperature threshold. In other embodiments, the staple cartridge processor can increase, or restore, the data transfer rate across the data antenna couple after the temperature sensed by the temperature sensor 15900 falls back below the temperature threshold.

[0106] In at least one embodiment, further to the above, the processor of the staple cartridge 15000 and/or the processor of the surgical instrument 10000 is configured to reduce the power being transferred across the power antenna couple between the staple cartridge 15000 and the surgical instrument 10000 when the temperature sensed by the temperature sensor 15900 exceeds a threshold. In at least one embodiment, the processor, or processors, can maintain the lower power transfer rate regardless of whether the temperature stays above or falls back below the temperature threshold. In other embodiments, the processor, or processors, can increase, or restore, the power transfer rate after the temperature sensed by the temperature sensor 15900 falls back below the temperature threshold.

[0107] In various embodiments, the staple cartridge processor is configured to assess the operational state of the staple cartridge 15000 when the temperature sensed by the temperature sensor 15900 exceeds the temperature threshold before modifying the operation of the staple cartridge 15000. For instance, if the staple cartridge processor senses that the staple firing stroke has not yet been initiated by the surgical instrument 10000 when the sensed temperature exceeds the temperature threshold, the staple cartridge processor is configured to modify, or lower, the sensor sampling rate, the data transfer rate, and/or the power transfer rate, for example, and/or otherwise reduce the heat generated by the staple cartridge processor by altering or stopping a function of the staple cartridge processor. Such an arrangement can reduce the heat generated by the staple cartridge 15000 during use. If the staple cartridge processor senses that the staple firing stroke has already been initiated by the surgical instrument 10000 when the sensed temperature exceeds the temperature threshold, in at least one such embodiment, the staple cartridge processor does not modify the sensor sampling rate, the data transfer rate, and/or the power transfer rate, for example, during the staple firing stroke. After the staple firing stroke, in such instances, the staple cartridge processor can modify the operation of the staple cartridge 15000 in some way to reduce the heat generated by the staple cartridge 15000. In various instances, the staple cartridge 15000 comprises a sensor configured to detect the position of the sled, or at least whether the sled is in its proximal unfired position, to determine whether or not the staple firing stroke has been initiated. In various embodiments, the control system of the surgical instrument 10000 is configured to communicate to the staple cartridge processor that the staple firing stroke is being initiated. The staple cartridge 15000 can also comprise a sensor to determine when the sled has reached its fully-fired position and/or the control system of the surgical

instrument 10000 is configured to communicate to the staple cartridge processor that the retraction stroke of the staple firing system is being initiated.

[0108] In various embodiments, further to the above, the staple cartridge processor is configured to modify the operation of a first system when the sensed temperature exceeds a first temperature threshold and modify the operation of a second system when the sensed temperature exceeds a second, or higher, temperature threshold. For instance, the staple cartridge processor can reduce the sensor sampling rate when the first temperature threshold has been exceeded and then also reduce the data transfer rate to the surgical instrument when the second temperature threshold has been exceeded.

[0109] In various embodiments, further to the above, the processor of the staple cartridge 15000 comprises an internal temperature sensor that is used in co-operation with or in lieu of the temperature sensor 15900. In various embodiments, the cartridge body 15100 is comprised of a positive temperature coefficient (PTC) material that is used as a temperature sensor. In such embodiments, the cartridge body 15100 is part of a temperature sensor circuit in communication with the processor of the staple cartridge 15000. In various instances, the cartridge body 15100 comprises a temperature sensor in addition to or in lieu of the other temperature sensors disclosed herein. In at least one instance, the PTC material is comprised of a doped polycrystalline ceramic including barium titanate BaTiOs, for example. In at least one embodiment, the processor of the staple cartridge 15000 is in communication with the temperature sensor 15900 and at least one temperature sensor in the surgical instrument 10000. In such embodiments, the staple cartridge processor can evaluate the temperature at multiple locations and employ an algorithm which considers the temperature readings of both temperature sensors before modifying the operation of the staple cartridge 15000. In various embodiments, the staple cartridge 15000 can comprise two or more temperature sensors and the staple cartridge processor can employ an algorithm which considers the temperature readings of all of the temperature sensors before modifying the operation of the staple cartridge 15000.

[0110] In various embodiments, the heat generated by the cartridge processor, for example, can affect the components of the sensor circuit and/or the voltage potential produced by the sensors of the sensor circuit. In various instances, an increase in the sensed temperature may be the result of an increased magnetic or electrical, field produced by the processor, for example. In at least one embodiment, the processor employs an algorithm configured to utilize a correction factor to compensate for the effect that a temperature increase has on the sensor outputs. In at least one such embodiment, the compensation factor is applied when the sensed temperature exceeds a threshold. In various embodiments, the voltage outputs are modified according to a modification function, such as a linear and/or non-linear function, for

example. In various embodiments, the cartridge control system comprises a sensor configured to directly detect fields generated by the processor and employ an algorithm to compensate for the effect that the fields have on the sensor outputs.

[0111] In various embodiments, the staple cartridges disclosed herein are configured to be operated in a low-power mode and a high-power mode. The processor of the staple cartridge is configured to switch from the lower-power mode to the high-power mode when the staple cartridge processor has received one or more inputs, or triggers. In such embodiments, the staple cartridge consumes less power and generates a lower amount of heat while the staple cartridge processor waits for a signal, or combination of signals, to switch into the high-power mode. In the low-power mode, in at least one embodiment, the staple cartridge processor is configured to process data from the cartridge sensors at a low sampling rate and/or transmit data to the surgical instrument 10000, for example, across the data antenna couple at a low transmission rate. In the high-power mode, in at least one embodiment, the staple cartridge processor is configured to process data from the cartridge sensors at a higher sampling rate and/or transmit data to the surgical instrument 10000 across the data antenna couple at a higher transmission rate. In at least one embodiment, the staple cartridge comprises at least one strain gauge, for example, mounted to the cartridge body which is in communication with the staple cartridge processor and is configured to sense when the cartridge body is being compressed. When the voltage potential being output by the strain gauge exceeds a threshold - in response to the cartridge body being subjected to a high strain - the staple cartridge processor switches from the low-power mode to the high-power mode. In such instances, the staple cartridge can detect that the end effector 10400 of the surgical instrument 10000 has been clamped onto the patient tissue. In addition to or in lieu of the strain gauge discussed above, the processor of the surgical instrument 10000 can emit a signal to the processor of the staple cartridge across the data antenna couple, for example, when the surgical instrument 10000 has been clamped. In either event, the processor of the staple cartridge switches from its lower-power mode to its high-power mode when the processor determines that the surgical instrument 10000 is in its clamped state. In such instances, the staple cartridge processor can increase its sampling rate of the tissue sensor outputs and/or increase the data transfer rate back to the processor of the surgical instrument 10000, for example.

[0112] In at least one embodiment, further to the above, the staple cartridge is in a low-power mode when the surgical instrument 10000 is in an unclamped state and the staple cartridge is in an unfired state. When the surgical instrument 10000 is clamped, the staple cartridge enters into a first high-power mode where one or more functions, but not all of the functions, of the staple cartridge are switched on and/or modified. When the

staple firing stroke is initiated by the surgical instrument 10000, the staple cartridge enters into a second high-power mode where all of the functions of the staple cartridge are switched on and are fully-operational. In at least one such embodiment, the processor of the staple cartridge is configured to emit a first signal to the surgical instrument 10000 indicating that the staple cartridge has entered the first high-power mode and a second signal to the surgical instrument 10000 indicating that the staple cartridge has entered the second high-power mode. When the instrument processor of the surgical instrument 10000 receives the first signal, the instrument processor increases the wattage of the power signal to the staple cartridge to power the staple cartridge in its first high-power mode. Likewise, the instrument processor increases the wattage of the power signal to the staple cartridge to power the staple cartridge in its second high-power mode when the instrument processor receives the second signal.

[0113] In at least one embodiment, the surgical instrument is configured to supply power to the staple cartridge at a first wattage when the staple cartridge is seated in the end effector of the surgical instrument and the end effector is in an unclamped state, at a second wattage when the end effector is in a clamped state before the staple firing stroke, and at a third wattage during the staple firing stroke. In at least one such embodiment, the second wattage is higher than the first wattage and the third wattage such that the cartridge processor can process data from the tissue sensors at a higher rate to evaluate the tissue prior to the staple firing stroke without generating an excessive amount of heat prior to the end effector being clamped and/or during the staple firing stroke. In at least one alternative embodiment, the third wattage is higher than the first wattage and the second wattage such that the cartridge processor can process data from the tissue sensors at a higher rate to evaluate the tissue during the staple firing stroke without generating an excessive amount of heat prior to the staple firing stroke.

[0114] In at least one embodiment, the staple cartridge is in a low-power mode before the staple cartridge is seated in the surgical instrument 10000. When the staple cartridge is seated in the surgical instrument 10000, the staple cartridge enters into a first high-power mode where one or more functions, but not all of the functions, of the staple cartridge are switched on and/or modified. For instance, the identification circuit of the staple cartridge is switched on when the staple cartridge is in the first high-power mode. When the surgical instrument 10000 is clamped, the staple cartridge enters into a second high-power mode where one or more additional functions, but not all of the functions, of the staple cartridge are switched on and/or modified. For instance, the tissue sensing circuit of the staple cartridge is switched on when the staple cartridge is in the second high-power mode. When the staple firing stroke is initiated by the surgical instrument 10000, the staple cartridge enters into a third high-power mode where all of the functions of

the staple cartridge are switched on and are fully-operational. In at least one such embodiment, the processor of the staple cartridge is configured to emit a first signal to the surgical instrument 10000 indicating that the staple cartridge has entered the first high-power mode, a second signal to the surgical instrument 10000 indicating that the staple cartridge has entered the second high-power mode, and a third signal to the surgical instrument 10000 indicating that the staple cartridge has entered the third high-power mode. When the instrument processor of the surgical instrument 10000 receives the first signal, the instrument processor increases the wattage of the power signal to the staple cartridge to power the staple cartridge in its first high-power mode. Likewise, the instrument processor increases the wattage of the power signal to the staple cartridge to power the staple cartridge in its second high-power mode when the instrument processor receives the second signal. Likewise, the instrument processor increases the wattage of the power signal to the staple cartridge to power the staple cartridge in its third high-power mode when the instrument processor receives the third signal.

[0115] As discussed above, the processor of a staple cartridge is responsive to an input, or trigger, which activates one or more systems of the staple cartridge when the trigger is received. In various embodiments, the staple cartridge comprises a control system including a wake-up circuit and an on-board power source. The wake-up circuit, when energized by a power source from outside of the staple cartridge, i.e., an off-board power source, connects the on-board power source with a data transmission circuit of the control system to transmit data to the surgical instrument 10000 via the data antenna couple. In at least one instance, the data transmission circuit emits an identification beacon to the surgical instrument 10000. If the control system of the staple cartridge does not establish authenticated communication with the surgical instrument 10000 within a predefined time period after emitting the identification beacon, the control system shuts down the data transmission circuit by disconnecting the on-board power source from the data transmission circuit until the wake-up circuit is re-energized by the off-board power source. If, however, the staple cartridge does establish authenticated communication with the surgical instrument 10000 within the predefined time period after emitting the identification beacon, the control system enters into a fully-awake high-power operating mode.

[0116] In various embodiments, further to the above, the control system of the staple cartridge will switch from a low-power, or sleep, mode to a high-power, or awake, mode after receiving two inputs, or triggers. In at least one embodiment, referring to FIG. 5A, the staple cartridge comprises a retainer, or cover, 11900 attached to the cartridge body that extends over the top, or deck, of the cartridge body. The cover 11900 comprises one or more attachment features 11910 configured to releasably hold the cover 11900 to the staple cartridge. The staple car-

tridge further comprises a cover sensor circuit including a sensor, such as a Hall Effect sensor, for example, in communication with a processor of the cartridge control system. When the cover 11900 is attached to the cartridge body, a magnetic element mounted to the cover 11900 interferes with the field emitted by the Hall Effect sensor and, when the cover 11900 is removed from the cartridge body, the magnetic element no longer interferes with the Hall Effect sensor field. This change in the Hall Effect sensor field is reflected in the voltage output of the Hall Effect sensor which is one of the triggers used by the cartridge control system to switch the staple cartridge into its wake mode. In addition to the above, the cartridge jaw of the surgical instrument comprises a cartridge presence sensor circuit that is completed, or closed, when the staple cartridge is seated in the cartridge jaw. In at least one instance, the staple cartridge closes a proximity switch, for example, when the staple cartridge is seated in the cartridge jaw. Like the cover sensor circuit, the cartridge presence sensor circuit is part of a wake circuit. The processor of the control system is configured to switch from its low-power, or sleep, mode to its high-power, or wake, mode when the processor receives an input that the staple cartridge is seated in the cartridge jaw and an input that the cover 11900 has been removed from the staple cartridge. In the sleep mode, the processor is not sampling data from the tissue sensors, processing data communicated to the staple cartridge from the surgical instrument, and/or transmitting data to the surgical instrument. In the wake mode, the processor is sampling data from the tissue sensors, processing data communicated to the staple cartridge from the surgical instrument, and transmitting data to the surgical instrument.

[0117] Further to the above, any suitable combination of wake-up events, or triggers, can be used to switch the control system of a staple cartridge from its sleep mode to its wake mode. In at least one embodiment, a first trigger is the removal of a cover from the staple cartridge and the second trigger comprises a completed authentication sequence. In at least one instance, the removal of the cover from the staple cartridge is sensed by the processor of the control system which switches the staple cartridge from its sleep mode into an authentication mode. In the authentication mode, the processor of the staple cartridge emits an identification beacon through a data antenna couple. If the instrument processor recognizes the identification beacon, the instrument beacon emits a wake-up signal back to the staple cartridge. Upon receiving the wake-up signal, the processor switches from its authentication mode to its wake mode. In the wake mode, the control system of the staple cartridge is fully-functional while, in the authentication mode, the control system of the staple cartridge may not be fully-functional. For instance, in at least one embodiment, the control system of the staple cartridge does not process the inputs from the tissue sensors when the staple cartridge is in its authentication mode. Moreover, the pro-

cessor includes a timer circuit, function, and/or clock, for example, that is activated when the processor enters into its authentication mode. The processor is configured such that, if the processor does not receive the wake-up signal within a predetermined period of time as measured by the timer circuit, the processor returns back into its sleep mode. In various instances, the identification beacon and/or the wake-up signal is encoded or encrypted. In at least one such instance, the instrument processor is configured to decode or decrypt the identification beacon and/or the cartridge processor is configured to decode or decrypt the wake-up signal.

[0118] Various wake-up triggers can include, for example, installing a battery into the surgical instrument, removing the surgical instrument from a charging station, and/or attaching the surgical instrument to a robotic surgical system. In at least one embodiment, the surgical instrument comprises electrical contacts which are mated with corresponding electrical contacts on an arm of the robotic surgical system which close a circuit that is sensed by the processor of the surgical instrument and/or a processor of the robotic surgical system. In such instances, the surgical instrument and/or the robotic surgical system sends a wake-up trigger signal to the staple cartridge seated in the surgical instrument. In at least one embodiment, the robotic surgical system comprises a vision system including one or more cameras which is configured to visually confirm the attachment of the stapling instrument to the arm of the robotic surgical system and/or the presence of a staple cartridge in the cartridge jaw and then send a wake-up trigger signal to the staple cartridge seated in the surgical instrument. In at least one such embodiment, the arm of the robotic surgical system and/or the surgical instrument comprises clips which releasably retain the surgical instrument to the arm and the vision system is configured to confirm that the clips are in their locked position before emitting the wake-up trigger signal. In various embodiments, the operating theatre, or surgical suite, comprises a control system which is configured to send a wake-up signal to the staple cartridge either directly and/or through the robotic surgical system and/or surgical instrument.

[0119] In various embodiments, a staple cartridge comprises a circuit in communication with the processor of the staple cartridge. The circuit comprises two contacts on the deck of the cartridge body and a gap between the contacts. When the staple cartridge is seated in the cartridge jaw and the end effector is in an open configuration, the circuit is in an open condition. In such instances, the memory devices of the staple cartridge cannot be accessed. When the end effector is closed, the anvil jaw bridges the contacts and the circuit is in a closed condition. In such instances, the memory devices of the staple cartridge can be accessed. In various embodiments, the circuit comprises a wake-up circuit that, when closed, provides a voltage potential to an input gate of the processor which, when received, causes the processor to switch from a sleep mode to a wake mode. In at

least one such embodiment, closing the wake up circuit when the end effector is closed places a battery or power source in the staple cartridge in communication with the control system of the staple cartridge. In various other embodiments, closing the anvil opens a wake-up circuit in communication with the processor. In at least one such embodiment, the anvil comprises a cutting element, such as a knife, for example, which cuts a circuit in the staple cartridge leaving the circuit in an open state. In such instances, the processor can interpret the loss of a voltage potential at an input gate as a wake-up signal.

[0120] In various instances, further to the above, the staple cartridge is stored in a hermetically-sealed package. Before loading the staple cartridge into the surgical instrument, a clinician must open the package and remove the staple cartridge. In at least one instance, removing the staple cartridge from the package activates a wake-up trigger that causes the staple cartridge to switch from a sleep mode to a wake mode. In at least one embodiment, a sticker is attached to the package and the staple cartridge. In such instances, the sticker maintains a wake-up circuit in the staple cartridge in an open condition. When the staple cartridge is removed from the package, the sticker detaches from the staple cartridge and the wake-up circuit becomes closed. In such instances, the processor receives the wake-up trigger signal to an input thereof. In at least one such instance, the staple cartridge comprises an on-board power source, such as a battery and/or charge accumulator, for example, that delivers a voltage potential to the processor input when the sticker is detached from the staple cartridge thereby providing the wake-up trigger signal to the processor. In at least one embodiment, the staple cartridge comprises a wake-up circuit including a battery and spring-loaded battery contacts which are held in an open condition by a tab when the staple cartridge is positioned in a package. In at least one instance, the package is comprised of a plastic material, such as TYVEK, for example. The tab is attached to the package and, when the staple cartridge is removed from the package, the tab is removed from between the battery and the spring-loaded battery contacts such that the battery contacts engage the battery and close the wake-up circuit. At such point, the processor of the staple cartridge is powered and fully-functional.

[0121] As discussed above, the staple cartridge can comprise a cover, or retainer, 11900 that is attached to the cartridge body and, when the cover 11900 is removed from the cartridge body, a wake-up circuit in the staple cartridge is closed and the processor enters into a woken state. Similar to the above, in at least one embodiment, the staple cartridge comprises a wake-up circuit including a battery and spring-loaded battery contacts which are held in an open condition by a tab affixed to the cover 11900 when the cover 11900 is attached to the staple cartridge. When the cover 11900 is removed from the staple cartridge, the tab is removed from between the battery and the spring-loaded battery contacts such that

the battery contacts engage the battery and close the wake-up circuit. At such point, the processor of the staple cartridge is powered and fully-functional. In other embodiments, the processor enters into a first powered mode when the cover 11900 is removed. In at least one such embodiment, the processor enters into a second powered mode as a result of a cartridge authentication process, for example.

[0122] In various embodiments, further to the above, a staple cartridge comprises a wake up circuit including a Hall Effect sensor, for example, mounted to a first lateral side of the cartridge body and a magnet mounted to a second, or opposite lateral side of the cartridge body. When the cover 11900 of the staple cartridge is attached to the cartridge body, the cover 11900 is positioned between the Hall Effect sensor and the magnet. When the cover 11900 is removed from the cartridge body, the field detected by the Hall Effect sensor changes and, as a result, the voltage output of the Hall Effect sensor changes which is detected by the cartridge processor. Such a change in the voltage potential is interpreted as a wake-up trigger by the processor and, in response to this wake-up trigger and/or a combination of wake-up triggers including this wake-up trigger, the processor switches from a sleep mode to a wake mode. In various instances, the cover 11900 comprises a fin comprised of ferrite, for example, which is positioned between the magnet and the Hall Effect sensor when the cover 11900 is attached to the cartridge body.

[0123] Once the staple cartridge is removed from its packaging, further to the above, the staple cartridge is seated in the cartridge jaw of the surgical instrument. In various instances, there is a snap-fit and/or press-fit arrangement between the staple cartridge and the cartridge jaw. When the staple cartridge is inserted into the cartridge jaw in such instances, there may be a sudden acceleration of the staple cartridge into its seated position when a sufficient force is applied to the staple cartridge to overcome the snap-fit and/or press-fit feature by the clinician. In various embodiments, the staple cartridge comprises a power source, such as a battery and/or a charge accumulator, for example, and, in addition, a wake-up circuit including an accelerometer in communication with the processor of the staple cartridge. The accelerometer is in communication with the power source and an input gate of the processor and, when the staple cartridge is accelerated as it seated in the surgical instrument, the voltage output of the accelerometer being supplied to the input gate of the processor increases above a wake voltage threshold and, as a result, the staple cartridge switches from its sleep mode to its wake mode, for example. In other embodiments, the processor enters into a first powered mode when the staple cartridge is seated. In at least one such embodiment, the processor enters into a second powered mode as a result of a cartridge authentication process, for example.

[0124] Once the staple cartridge is seated in the car-

tridge jaw, further to the above, the end effector of the surgical instrument can be inserted into a patient. In various instances, the end effector of the surgical instrument is inserted into the patient through a large, or open, incision, and then clamped onto the patient tissue. In other instances, the end effector of the surgical instrument is inserted into the patient through a cannula, or trocar. In such instances, the end effector is closed, inserted through the trocar, and then re-opened once the end effector is in the patient. At such point, the end effector is then clamped onto the patient tissue. In either event, the end effector may be opened and closed one or more times before being used in the patient and the clamping of the end effector can supply a wake-up trigger to the staple cartridge. In at least one embodiment, a staple cartridge comprises a processor, a power source, and a wake-up circuit in communication with the processor and the power source. The wake-up circuit comprises a switch in an open state which is closed when the end effector of the surgical instrument is clamped. When the switch is closed, the processor enters into its fully-powered state. In at least one such embodiment, a movable anvil jaw physically contacts the staple cartridge to close the wake-up circuit. In at least one embodiment, the wake-up circuit comprises a Hall Effect sensor that detects the presence of a magnetic element mounted to the anvil jaw when the anvil jaw is in its closed position. When the voltage output of the Hall Effect sensor changes as a result of the presence of the magnetic element, the processor interprets the voltage output change as a wake-up trigger. In at least one embodiment, the wake-up circuit comprises an induction sensor that detects the presence of the metal anvil jaw in its closed position. When the voltage output of the induction sensor changes as a result of the anvil jaw being closed, the processor interprets the voltage output change as a wake-up trigger.

[0125] In various embodiments, further to the above, a trocar comprises a proximal end including a sealed port, a distal end including a sharp tip configured to incise patient tissue, and a tube extending between the proximal end and the distal end. The sealed port comprises an enlarged opening and a flexible seal configured to form a substantially air-tight seal against the end effector and/or the shaft of the surgical instrument as they are inserted there through. In various embodiments, the trocar comprises a data transmitter including an antenna configured to emit a wake-up signal to the staple cartridge as the staple cartridge passes through the trocar. In various instances, the wake-up signal from the trocar data transmitter is a sufficient trigger to switch the control system of the staple cartridge from its sleep mode to its wake mode and, in other instances, the wake-up signal from the trocar data transmitter is one of several triggers needed to switch the control system of the staple cartridge from its sleep mode to its wake mode. In at least one embodiment, the trocar comprises a magnetic member, such as a permanent magnet, for example, and the staple car-

tridge comprises a wake-up circuit including a sensor configured to detect the magnetic member. In at least one such embodiment, the staple cartridge comprises a power source in communication with the sensor which comprises a Hall Effect sensor, for example. When the staple cartridge is seated in the end effector and the end effector is inserted through the trocar, the field emitted by the Hall Effect sensor is distorted by the magnetic member in the trocar which changes the voltage output of the Hall Effect sensor. This change in the sensor voltage output is detected by the processor of the staple cartridge and when the change exceeds a predetermined threshold, the processor is configured to switch from its sleep mode to its wake mode. In various embodiments, the tube of the trocar comprises ferrous rings embedded therein and/or mounted thereto and the staple cartridge comprises a wake-up circuit including an inductive sensor configured to detect the ferrous rings. In at least one embodiment, the inductive sensor comprises a field sensor, an oscillator, a demodulator, a flip-flop, and an output, for example. When the staple cartridge is seated in the end effector and the end effector is inserted through the trocar, the ferrous rings change the voltage output of the inductive sensor. This change in the sensor voltage output is detected by the processor of the staple cartridge and when the change exceeds a predetermined threshold, the processor is configured to switch from its sleep mode to its wake mode. In various instances, the inductive sensor outputs a voltage pulse for each ferrous ring that the inductive sensor passes through. In such instances, the processor is configured to switch to its wake mode after it has received a number of pulses from the inductive sensor that exceeds a predetermined number of pulses.

[0126] Referring again to FIG. 7, a staple cartridge can comprise a power management system including a processor and a charge accumulator, such as the charge accumulator 11800, for example. The power management system further comprises a charging circuit in communication with the charge accumulator 11800 and includes an antenna configured to receive power from a surgical instrument when the staple cartridge is seated in the surgical instrument. In various instances, the surgical instrument is capable of supplying power to the staple cartridge at a first, or maximum, charging rate; however, there may be situations during the use of the staple cartridge in which the staple cartridge uses power at a second rate which is higher than the maximum charging rate. To accommodate this higher power usage, the charge accumulator 11800 stores power when the power usage of the staple cartridge is below the maximum charging rate. The processor of the staple cartridge is configured to manage the power being stored in the charge accumulator 11800 and, when the charge accumulator 11800 reaches its maximum capacity, the processor sends a signal to the surgical instrument to reduce the power being supplied to the staple cartridge by the surgical instrument. In at least one such instance, the

signal includes data regarding the actual power usage of the staple cartridge. The processor of the surgical instrument, upon receiving the signal, reduces the power being supplied to the staple cartridge such that the charging rate matches the staple cartridge use rate. In many instances, the power usage of the staple cartridge may increase above the charging rate and the power management system is configured to utilize power from the charge accumulator 11800 until the charge of the charge accumulator 11800 falls below a re-charge threshold. When the processor detects that the charge of the charge accumulator 11800 has fallen below the re-charge threshold, the processor of the staple cartridge sends a signal to the surgical instrument to restore the charging rate to the maximum charging rate in order to re-charge the charge accumulator 11800. In addition to or in lieu of the charge accumulator 11800, the staple cartridge can comprise any suitable power storage device, such as a charge pump, battery, and/or super-capacitor, for example.

[0127] In various instances, further to the above, the charge accumulator 11800 is not actively charged by the surgical instrument until at least one trigger event has occurred. In at least one instance, the cartridge power management system charges the charge accumulator 11800 after receiving a signal from a NFC antenna of the surgical instrument. In at least one such instance, the power transferred from the NFC antenna sufficiently charges the charge accumulator 11800 to place the staple cartridge in a charging mode before the staple cartridge enters into a fully-powered mode. In certain instances, the cartridge processor emits an identification beacon to the surgical instrument after the charge accumulator 11800 has been at least partially charged by the power transferred from the NFC antenna. When the instrument processor receives the identification beacon from the staple cartridge, the instrument processor delivers additional power to the staple cartridge across the NFC antenna and/or across a power antenna so that the cartridge power management system fully charges the charge accumulator 11800. In various instances, the charge accumulator 11800 is at least partially charged by power transmitted to the cartridge NFC antenna from the control system of the operating room.

[0128] In various embodiments, the surgical instrument is configured to supply power to the staple cartridge as soon as the staple cartridge is seated in the surgical instrument. In at least one embodiment, the surgical instrument immediately supplies power to the staple cartridge via a low-power data antenna couple, such as a NFC antenna couple, for example, when the staple cartridge is seated in the surgical instrument. In such instances, the cartridge power management system charges the charge accumulator 11800 as part of a charging mode. In at least one instance, less than 0.1 W, for example, is supplied to the cartridge power management system during the charging mode. After the processor of the staple cartridge has received the wake

trigger or the combination of wake triggers needed to switch the staple cartridge into its wake mode, the processor supplies a woken signal to the surgical instrument that the staple cartridge is in its wake mode. Once the processor of the surgical instrument receives the woken signal, the surgical instrument begins supplying power to the staple cartridge through a high-power antenna couple. In such instances, the cartridge power management system can then complete the charging of the charge accumulator 11800 if it has not already been fully-charged. In at least one instance, more than 1.0 W, is supplied to the cartridge power management system during the wake mode. In various alternative embodiments, there is only one antenna couple between the staple cartridge and the surgical instrument. In such embodiments, the surgical instrument can control whether low power or high power is supplied to the staple cartridge via the antenna based on whether the instrument processor has received the woken signal from the staple cartridge. In any event, if the cartridge power management system determines that the charge accumulator 11800 has been fully charged and the cartridge processor has not received the necessary wake trigger or triggers to switch the staple cartridge into its wake mode, the cartridge power management system can switch open the charging circuit supplying power to the charge accumulator 11800 to stop the charging of the charge accumulator 11800. In at least one embodiment, the cartridge processor can emit a charged-but-not-woken signal to the instrument processor which, upon receiving this signal, is configured to stop supplying power to the staple cartridge until the instrument processor has received the woken signal from the staple cartridge. Once the instrument processor has received the woken signal, in such circumstances, the instrument processor is configured to start supplying power to the staple cartridge at the high-power level.

[0129] In various embodiments, as described above, a processor of a staple cartridge is configured to switch from a low-power, or sleep, mode to a high-power, or wake, mode when the processor receives a combination of wake-up triggers. In various embodiments, the processor requires a specific combination of triggers to enter into its wake mode. For instance, the cartridge processor switches into its wake mode when a sufficient voltage potential is applied to a first input gate of the processor and a sufficient voltage potential is applied to a second input gate of the processor. In various embodiments, the processor is configured to switch from its sleep mode to its wake mode after a subset of triggers out of a larger set of triggers has been received by the processor. In at least one such embodiment, the processor is configured to receive three wake triggers but is configured to switch into its wake mode after any two of the wake triggers have been received. The voltage potentials do not need to be applied to the processor gates at the same time, but embodiments are envisioned in which the wake triggers must be applied to the processor simultaneously for the

processor to switch into its wake mode. In at least one embodiment, a processor is configured to receive two specific wake triggers at the same time to switch from its sleep mode to its wake mode. In at least one such embodiment, one of the wake triggers is the charge accumulator 11800 reaching a sufficient charge level and the other trigger is an event, for example. That said, the charge accumulator 11800 reaching a sufficient charge level can serve as a wake trigger in any of the embodiments disclosed herein that includes the charge accumulator 11800, and/or any other suitable power storage device. Moreover, various alternative embodiments are envisioned in which the charge accumulator 11800 is not charged until after the cartridge processor has switched from its sleep mode to its wake mode.

[0130] In various embodiments, the staple cartridges disclosed herein comprise at least one memory device configured to store data regarding a property of the staple cartridge before, during, and/or after the staple firing stroke and/or a tissue property before, during, and/or after the staple firing stroke. The memory device is in communication with the processor and the processor is configured to read data from the memory device and communicate the data in a stored data signal that is transmitted to an antenna of the staple cartridge. In various embodiments, the processor is configured to emit the stored data signal only after receiving a key, or key signal, that unlocks this function of the processor. For each time that the processor accesses the memory device to generate the stored data signal, the event is recorded on the memory device. In this way, the memory device includes data regarding the number of times that the memory device has been accessed and when. Such access data can be included in the stored data signal. If the key signal supplied to the cartridge processor does not match an anticipated key signal stored in the cartridge processor and/or memory device, the cartridge processor does not generate the stored data signal. Instead, the failed attempt is recorded on the memory device. In this way, the memory device includes data regarding the number of times that access to the memory device data was denied. Such access denial data can be included in the stored data signal when the proper key signal is supplied to the cartridge processor. In at least one embodiment, the cartridge processor enters into a locked mode after the number of failed attempts to access the memory device has exceeded a threshold. In at least one instance, the threshold is five failed attempts, for example. Once the cartridge processor is in the locked mode, the cartridge processor is configured to not generate the stored data signal even if the proper key signal is thereafter provided. In such instances, the data stored on the memory device is no longer accessible. In at least one alternative embodiment, the processor is unlockable after it has entered into its locked mode when a master key, or master key signal, is provided to the processor. The master key is different than the key and, in various instances, may only be held by the original manufacturer

of the staple cartridge, for example. Providing the processor with the master key signal would cause the processor to emit the stored data signal even if the processor is not in the locked mode.

5 **[0131]** Further to the above, the data stored on the memory device can be encrypted or encoded according to any suitable protocol. After receiving the key and/or master key, the processor is configured to decrypt or decode the data stored on the memory device and transmit the decrypted or decoded data in the stored data signal. However, various alternative embodiments are envisioned in which the processor is configured to emit encrypted or encoded data as part of the stored data signal. In at least one such embodiment, a decryption key or code stored on the memory device is included in the stored data signal. In such embodiments, the surgical instrument, and/or any suitable system, can decrypt or decode the data in the stored data system.

10 **[0132]** In various instances, the cartridge processor must receive a unique identification key to create the stored data signal discussed above. This unique identification key is predefined and static and anyone who supplies the unique identification key to the cartridge processor can access the data stored on the memory device. In other embodiments, the key needed to access the data stored on the memory device is dynamic. In at least one embodiment, the dynamic key includes performance information regarding the staple cartridge. Such performance information can comprise data regarding a mechanical feature and/or an electrical feature. For instance, the dynamic key can include information regarding the final position of the sled in the staple cartridge after the staple firing stroke, for example. Also, for instance, the dynamic key can include information regarding the maximum current drawn by the electric motor of the staple firing system drawn during the staple firing stroke, for example. In such instances, the performance information can be shared between the staple cartridge and the surgical instrument during and/or after the staple firing stroke. For instance, the staple cartridge can comprise a sled position sensor and can communicate the final position of the sled after the staple firing stroke to the surgical instrument. Also, for instance, the surgical instrument can comprise an electric motor current sensor and can communicate the peak current drawn by the electric motor during the staple firing stroke to the staple cartridge. This performance information can also be shared with the robotic surgical system and/or the operating room control system, for example. In any event, such shared performance data can comprise the dynamic key that is used to access the data stored on the memory device of the staple cartridge.

45 **[0133]** In addition to or in lieu of the above, a staple cartridge comprises a security circuit that is closed when the movable components of the staple cartridge are arranged in a specific arrangement. The security circuit is in communication with the processor and, when the security circuit is in a closed state, the processor is in an

unlocked state which permits the processor to generate the stored data signal in response to an interrogation signal and/or otherwise permit the data stored on the memory device to be accessed by the surgical instrument, the robotic surgical system, and/or the operating room control system, for example. When the security circuit is in an open state, the processor is in a locked state and is configured to not emit the stored data signal or permit the data stored on the memory device to be accessed. In at least one embodiment, the security circuit of a staple cartridge is in a closed state when the cover 11900 is not attached to the cartridge body and the sled is not in its unfired position. In various embodiments, the security circuit prevents the processor from being powered by a surgical instrument, for example, when the security circuit is in its open state. When the security circuit is in its closed state, the processor can be powered by the surgical instrument. When the processor is powered by the surgical instrument, in such embodiments, the processor can generate the stored data signal. In at least one such embodiment, the staple cartridge must be seated in the surgical instrument, for example, to complete the security circuit. In at least one embodiment, the security circuit comprises electrical contacts that engage corresponding electrical contacts in the surgical instrument, for example, which close the security circuit when the staple cartridge is seated in the surgical instrument.

[0134] In various embodiments, the security circuit comprises a security antenna which is in communication with a corresponding security antenna in the surgical instrument, for example, when the staple cartridge is seated in the surgical instrument. In at least one such embodiment, the sled is positioned between the cartridge security antenna and the instrument security antenna when the sled is in its unfired position. In such instances, the sled inhibits or prevents communication between the staple cartridge and the surgical instrument across the security antenna couple. After the sled has been moved distally, the sled no longer blocks the transmission of data and/or power between the staple cartridge and the surgical instrument.

[0135] In various embodiments, as discussed above, the security circuit of a staple cartridge is configurable in an open state and a closed state. Various alternative embodiments are envisioned in which the security circuit is in a closed state, but a detectable property of the security circuit changes as a result of the moveable components of the staple cartridge being in a specific configuration or range of configurations. In at least one embodiment, the voltage potential across the security circuit is within a first voltage range when the cover 11900 is attached to the cartridge body and the sled is in its unfired position, a second voltage range when the cover 11900 is removed from the cartridge body and the sled is in its unfired position, and a third voltage range when the cover 11900 is removed from the cartridge body and sled is in a fired position. When the voltage potential across the security circuit is within the third voltage range, the

processor is in its unlocked state. When the voltage potential across the security circuit is within the first voltage range or the second voltage range, the processor is in its locked state, for example.

[0136] In various embodiments, a staple cartridge comprises an access cover that is opened when the staple cartridge is seated in the cartridge jaw of the surgical instrument. When the access cover is opened, a data access circuit is closed which permits the surgical instrument to access the memory devices of the staple cartridge. In at least one instance, a cartridge jaw comprises a conductive contact element that bridges an opening in the data access circuit when the staple cartridge is seated in the cartridge jaw and the access cover is opened. In at least one embodiment, the access door comprises a foil sheet, for example. In at least one embodiment, the memory device comprises an RFID tag, for example. When the staple cartridge is not seated in the surgical instrument, however, the data access circuit is in an open condition and the memory devices of the surgical instrument cannot be accessed.

[0137] The entire disclosures of U.S. Patent No. 8,991,678, entitled SURGICAL INSTRUMENT WITH STOWING KNIFE BLADE, which issued on March 31, 2015, U.S. Patent No. 10,085,749, entitled SURGICAL APPARATUS WITH CONDUCTOR STRAIN RELIEF, which issued on October 2, 2018, and U.S. Patent Application Publication No. 2015/0324317, entitled AUTHENTICATION AND INFORMATION SYSTEM FOR REUSABLE SURGICAL INSTRUMENTS, which published on November 12, 2015, are incorporated by reference herein.

[0138] Further to the above, the memory device of the staple cartridge can store any suitable data. For instance, the stored data can include the size of the staples stored in the staple cartridge, the unformed height of the staples stored in the staple cartridge (which may be reflected in the color of the cartridge body), the number of staples stored in the staple cartridge, the arrangement of the staples stored in the staple cartridge, and/or the length of the staple pattern of the staples stored in the staple cartridge (such as 30 mm, 45 mm, or 60 mm, for example). Also, for instance, the stored data can include whether or not the staple cartridge has been fired, when the staple cartridge was fired, the distance traveled by the sled during the staple firing stroke, the time lapsed during the staple firing stroke, the speed of the staple firing stroke, the accelerations and decelerations of the staple firing system incurred during the staple firing stroke, the firing force experienced during the staple firing stroke, and/or whether a foreign object was encountered and/or incised during the staple firing stroke. Also, for instance, the stored data can include the number of sensors in the staple cartridge, the type of sensors, and/or the location of the sensors in the cartridge body. Also, for instance, the stored data can include the data sensed by the sensors. Also, for instance, the stored data can include the type of tissue being stapled, the thickness of the tissue being

stapled, the properties of the tissue being stapled, and/or the position of the tissue between the jaws of the end effector. Also, for instance, the stored data can include the manufacturing date of the staple cartridge, the lot to which the staple cartridge belongs, the manufacturing location of the staple cartridge, the manufacturer of the staple cartridge, the sterilization date of the staple cartridge, the type of sterilant used to sterilize the staple cartridge, the expiration date of the staple cartridge, and/or whether the staple cartridge was fired past the expiration date and by how much.

[0139] According to at least one method, a staple cartridge is removed from its package and seated in the cartridge jaw of a stapling instrument. The stapling instrument is then attached to an arm of a robotic surgical system and the robotic surgical system is powered on and/or switched from a sleep mode to a wake mode. The control system of the robotic surgical system is configured to transmit electrical power down through the surgical instrument to assess whether or not the staple cartridge is seated in the cartridge jaw and then transmit mechanical power down through the surgical instrument to assess whether or not the staple cartridge is in an unfired condition. In at least one embodiment, further to the above, the robotic surgical system sends power to the data antenna, such as an NFC antenna, for example, in the surgical instrument to supply power to the staple cartridge. As discussed above, the staple cartridge is configured to return an identification signal back to the surgical instrument. In various instances, this identification signal is processed on the surgical instrument and/or in the robotic surgical system. In either event, the staple cartridge is validated if the authentication procedure is successful. If the authentication procedure is unsuccessful, the robotic surgical system is configured to notify the clinician operating the robotic surgical system. In order to verify if the staple cartridge is unspent, i.e., not previously fired, the staple firing member is advanced distally a small stroke by a motor drive of the surgical instrument and/or robotic surgical system. If the staple firing drive is blocked by a mechanical feature in the surgical instrument, then the robotic surgical system is configured to determine that the staple cartridge has been previously spent and prevents the staple cartridge from being fired. If the staple firing system is not blocked by the mechanical feature, then the robotic surgical system is configured to stop the staple firing drive after the small stroke and determine that the staple cartridge is unfired. In addition to the identification data transmitted from the staple cartridge to the surgical instrument and/or robotic surgical system, the staple cartridge can also transmit data stored on a cartridge memory device including the expiration date of the staple cartridge, the length of the pattern of staples stored in the staple cartridge, the unformed height of the staples stored in the staple cartridge, the color of the plastic cartridge body, the manufacturer of the staple cartridge, and/or whether the staple cartridge has been fired. If the received parameters of the staple cartridge do

not match the required parameters of the staple cartridge, then the clinician operating the robotic surgical system is notified.

[0140] In addition to the above, the staple cartridge, surgical instrument, and/or robotic surgical system are configured to mitigate errors in and/or data missing from the cartridge data supplied by the staple cartridge. Data may be missing or have errors resulting from shorting within the sensors, corrosion, an incompatible or incorrect staple cartridge being used, electronic interference from adjacent surgical instruments and/or surgical systems, software bugs, defective hardware, and/or the sterilization process, for example. As such, one or more forms of redundancy can be employed to improve the likelihood that the surgical instrument and/or robotic surgical system receive the data from the staple cartridge. For instance, in at least one embodiment, the same data is stored in different locations within the stored data signal. In such instances, some data may be lost or corrupted in one part of the signal but can be obtained from another part of the signal. Also, the stored data can include data from two different sources that can be seen as functional equivalents. For instance, data from a force, or load, sensor in the staple firing drive and data from a current sensor monitoring the current drawn by the electric motor of the staple firing drive can both be part of the stored data. In such instances, if the force sensor data is lost or corrupted in the signal, the processor can rely on the current sensor data to assess the forces experienced by the staple firing drive, for example.

[0141] In at least one embodiment, a staple cartridge can comprise more than one memory device with the stored data. In at least one such embodiment, the processor of the staple cartridge emits a first stored data signal including the data from a first memory device and then a second stored data signal including the data from a second memory device as part of an authentication or interrogation process of the staple cartridge. If the data from the first memory device and the second memory device is uncorrupted, in at least one embodiment, the first stored data signal will match the second stored data signal. In at least one embodiment, the first stored data signal comprises a first signal header at the beginning of the first stored data signal and the second stored data signal comprises a second signal header at the beginning of the second stored data signal which is different than the first signal header. In such instances, the surgical instrument processor and/or the control system of the robotic surgical system are able to differentiate between the first stored data signal and the second data signal. If the surgical instrument processor and/or the control system of the robotic surgical system determine that the either of the signals was corrupted and/or missing data, they are configured to establish a preference for the other signal. In various instances, the first memory device is located on a first lateral side of the staple cartridge while the second memory device is located on a second, or opposite, lateral side of the staple cartridge. Such an arrangement

can reduce the possibility of electronic interference affecting both signals. In at least one embodiment, the staple cartridge comprises a first data antenna for transmitting the first stored data signal and a second data antenna for transmitting the second data signal.

[0142] The staple cartridge, surgical instrument, and/or robotic surgical system can be configured to take other mitigation efforts if the data contained in the stored data signal is corrupted and/or missing. In various instances, the staple cartridge can increase the power of the stored data signal if data is missing from the signal received by the surgical instrument and/or robotic surgical system. In at least one instance, the processor of the surgical instrument and/or robotic surgical system can increase its noise threshold if the data received from the staple cartridge is corrupted.

[0143] In various embodiments, the data and/or power transmitted between the surgical instrument and the staple cartridge can be continuous or intermittent. In various embodiments, the transferred data may comprise discrete digital data and/or continuous analog data, for example. When transferring digital data, RFID, NFC, Hitachi UHF, Bluetooth, Zigbee, mm wave, WiFi 802.11 and/or any other suitable wireless system can be used. Also, when transferring digital data, wired LAN communications, 1-wire communication, EPROM IC, I²C, and/or any other suitable devices can be used. The various types of digital data that can be transferred includes motor feedback comprising the current magnitude, the time rate of change of the current, the torque magnitude, the time rate of change of the torque, position data from the encoder, the torque constant, magnetic strength, number of wire turns, armature length, data regarding the torque-current curve, motor regulation, EMF constant, dynamic resistance, back EMF, angular speed, motor speed, and/or the motor speed time rate of change, for example. Other transferred data can include the instrument handle hardware configuration and/or data regarding physical contacts and/or switches, for example.

[0144] Further to the above, the transferred analog data can include electrically-derived and mechanically-derived data. Electrically-derived data can include magnetic indicators, Hall Effect sensor data, data regarding the state of switches, diode data, the opening or closing of a circuit, and/or the destruction of a circuit such as when the sled and/or tissue cutting knife cuts a circuit during the staple firing stroke, for example. Mechanically-derived data can include magnitude-based data such as the force transmitted by the motor and/or the motor current, for example, related to specific events of the staple firing stroke such as the firing member contacting the sled, the sled being dislodged from its proximal unfired position, the formation of the staples, and/or the firing member contacting and/or destroying a detent feature of the staple cartridge, for example. Mechanically-derived data can also include time-based data comparing the performance data of the motor to the time in which the event

occurred and/or position-based data comparing the performance data of the motor with the position of the staple firing drive, for example. Mechanically-derived data can also include feature-based data such as when the staple firing drive opens and/or closes a gate and/or when a detent feature of the staple cartridge is destroyed by the staple firing drive, for example.

[0145] In various embodiments, a surgical system, such as a robotic surgical system, for example, can include a visualization system including at least one camera which is configured to observe a parameter of the staple cartridge, for example, and modify the operation of the robotic surgical system, surgical instrument, and/or staple cartridge based on the observation. For instance, the visualization system is configured to detect and evaluate physical features, or markers, on the staple cartridge and the cartridge jaw to assess whether the staple cartridge is fully seated in the cartridge jaw. If the markers on the staple cartridge and cartridge jaw are not properly aligned, the visualization system can instruct the robotic surgical system to lock out the jaw clamping and/or staple firing functions of the robotic surgical system, for example. In various embodiments, the visualization system can instruct the robotic surgical system to warn the operator that the staple cartridge may not be seated correctly in the cartridge jaw. Also, for instance, the visualization system is configured to detect whether an implantable adjunct is attached to the deck of the staple cartridge and/or whether the implantable adjunct is aligned with the deck of the staple cartridge. Similar to the above, the implantable adjunct and the staple cartridge comprise markers which the visualization system can detect and compare to assess whether the implantable adjunct is sufficiently aligned and, if it is not, instruct the robotic surgical system to warn the operator.

[0146] In various embodiments, further to the above, a visualization system is configured to observe the color of the cartridge body and provide this data to the robotic surgical system which can display this data to the operator. In various instances, the color of the cartridge body signifies the size and/or unformed height of the staples contained therein. The robotic surgical system is configured to assess whether the staples contained in the staple cartridge are suitable for the surgical procedure being performed and, if they are not, warn the operator. In various instances, the visualization system is configured to read a bar code and/or a QR code, for example, on the staple cartridge and provide this data to the robotic surgical system which can display this data to the operator. Similar to the above, this data can include the size and/or unformed height of the staples contained therein. The robotic surgical system is configured to assess whether the staples contained in the staple cartridge are suitable for the surgical procedure being performed and, if they are not, warn the operator. The QR code, for example, can include the serial number of the staple cartridge, the manufacturing date, and/or data identifying the manufacturer of the staple cartridge, for example. In

various embodiments, the QR code contains the decryption key, or a portion of the decryption key, to access the memory devices in the staple cartridge. In various embodiments, the QR code, for example, is molded into the cartridge body, laser-etched into the cartridge body and/or pan, and/or printed on the cartridge body and/or pan, for example.

[0147] As discussed above, referring again to FIG. 1, the surgical instrument 10000 comprises a shaft 10200 and an end effector 10400 rotatably coupled to the shaft 10200 about an articulation joint 10500. The surgical instrument 10000", referring to FIGS. 8-8D, is similar to the surgical instrument 10000 in many respects, many of which are not discussed herein for the sake of brevity. The surgical instrument 10000", like the surgical instrument 10000, comprises a staple firing drive which is operable to perform a staple firing stroke to eject the staples from the staple cartridge 11000". The staple firing drive includes an electric motor, a tissue cutting knife 10630, and a firing bar 10640 that is driven distally by the electric motor to push the tissue cutting knife 10630 through the staple cartridge 11000" during the staple firing stroke. In such instances, the tissue cutting knife 10630 contacts the sled 11400 of the staple cartridge 11000" and pushes the sled 11400 distally to eject the staples as the tissue cutting knife 10630 is advanced distally through the staple firing stroke. The tissue cutting knife 10630 further comprises a first cam 10610 configured to engage the first jaw 10410 and a second cam 10620 configured to engage the second jaw 10420 during the staple firing stroke. The first cam 10610 and the second cam 10620 are configured to cooperatively hold the jaws 10410 and 10420 in position relative to one another as the staples are being deformed against the second jaw 10420.

[0148] In various embodiments, the staple firing drive can also be used to close the end effector 10400. In at least one such embodiment, the tissue cutting knife 10630 is advanced distally during a closure stroke such that the second cam 10620 contacts the second jaw 10420 and moves the second jaw 10420 from an open position to a closed position. After the closure stroke, the staple firing drive can be re-actuated to perform the staple firing stroke discussed above. In alternative embodiments, the surgical instrument comprises separate and distinct closing and staple firing drives. In at least one such embodiment, the closing drive is actuated to close the second jaw 10420 and the staple firing drive is then separately actuated to perform the staple firing drive. In either event, the cams 10610 and 10620 can co-operate to hold the jaws 10410 and 10420 together during the staple firing stroke. That said, other embodiments are envisioned without one or both of the cams 10610 and 10620.

[0149] Further to the above, the surgical instrument 10000", like the surgical instrument 10000, comprises a lockout 10700 which prevents the staple firing stroke from being performed if the first jaw 10410 is empty, i.e., missing a staple cartridge, the staple cartridge is

positioned in the first jaw 10410 but not fully-seated in the first jaw 10410, and/or the staple cartridge is seated in the first jaw 10410 but has been previously fired. In any of these instances, the tissue cutting knife 10630 is pushed downwardly by a spring (in the shaft 10200) into a recess 10710 defined in the first jaw 10410 when the staple firing stroke is initiated such that the tissue cutting knife 10630 contacts a lock shoulder 10720 and the tissue cutting knife 10630 is blocked from being advanced further distally. At such point, the surgical instrument 10000" is locked out and the staple firing stroke cannot be performed until an unspent staple cartridge is fully seated in the first jaw 10410. When an unspent staple cartridge is fully seated in the first jaw 10410 and the staple firing stroke is re-initiated, the tissue cutting knife 10630 passes over the lock shoulder 10720 of the lockout 10700 and the staple firing stroke can be completed. More specifically, the sled 11400 of the staple cartridge 11000" supports the tissue cutting knife 10630 above the lock shoulder 10720 when the sled 11400 is in its proximal, unfired position at the beginning of the staple firing stroke. The above being said, any suitable lockout can be used.

[0150] The entire disclosures of U.S. Patent No. 7,143,923, entitled SURGICAL STAPLING INSTRUMENT HAVING A FIRING LOCKOUT FOR AN UNCLOSED ANVIL, which issued on December 5, 2006; U.S. Patent No. 7,044,352, SURGICAL STAPLING INSTRUMENT HAVING A SINGLE LOCKOUT MECHANISM FOR PREVENTION OF FIRING, which issued on May 16, 2006; U.S. Patent No. 7,000,818, SURGICAL STAPLING INSTRUMENT HAVING SEPARATE DISTINCT CLOSING AND FIRING SYSTEMS, which issued on February 21, 2006; U.S. Patent No. 6,988,649, SURGICAL STAPLING INSTRUMENT HAVING A SPENT CARTRIDGE LOCKOUT, which issued on January 24, 2006; and U.S. Patent No. 6,978,921, SURGICAL STAPLING INSTRUMENT INCORPORATING AN E-BEAM FIRING MECHANISM, which issued on December 27, 2005, are incorporated by reference herein.

[0151] Further to the above, the cartridge body 11100 comprises a longitudinal slot 11150 defined therein which is configured to receive the tissue cutting knife 10630 during the staple firing stroke. The longitudinal slot 11150 comprises a wide proximal end 11152 leading into a longitudinal portion 11156. The longitudinal slot 11150 further comprises bumps, or projections, 11154 that extend inwardly into the longitudinal portion 11156. The bumps 11154 releasably hold the sled 11400 in its proximal, unfired position until the sled 11400 is pushed distally by the tissue cutting knife 10630 during the staple firing stroke. Such an arrangement prevents, or reduces the possibility of, the sled 11400 being accidentally pushed distally when the staple cartridge 11000" is seated in the first jaw 10410, for example. The bumps 11154 can also be contacted by the tissue cutting knife 10630 during the staple firing stroke. In such instances, the tissue cutting knife 10630 can yield, plastically de-

form, and/or destroy one or both of the bumps 11154. Such an event may create a momentary pulse or increase in the force needed to move the tissue cutting knife 10630 distally that is detectable by the control system operating the staple firing drive, as discussed further below. Notably, the bumps 11154 are positioned distally with respect to the lockout 11700 and, as such, the tissue cutting knife 10630 will pass by the lockout 11700 and then the bumps 11154 at the beginning of the staple firing stroke. The above being said, alternative embodiments of are envisioned with two sets of bumps - one set of bumps 11154 for holding the sled 11400 in position and a second set of bumps for creating the detectable force pulse.

[0152] Sensors in an end effector of a surgical instrument measure various tissue parameters and instrument parameters that allow the surgical instrument to perform a number of tasks. Although higher sensor sampling rates are generally associated with more accurate sensor data, indiscriminately maximizing the sampling rates of all the sensors within an end effector while the surgical instrument is active is quite taxing on power consumption, data transmission, and/or data processing.

[0153] Various aspects of the present disclosure are directed to circuits and/or algorithms for optimizing sensor data collection, transmission, and/or processing based on real-time constraints of data bandwidth or capacity, power transfer or discharge rate, and/or remaining power capacity.

[0154] Additionally, or alternatively, various aspects of the present disclosure are directed to circuits and/or algorithms that optimize sensor data collection, transmission, and/or processing based on one or more detected aspects of the surgical instrument, the surgical task being performed by the surgical instrument, and/or signal(s) from a situationally-aware surgical hub, which can represent a priority level of the sensor data, as discussed in greater detail below.

[0155] In various aspects, the surgical instrument may require different sensor arrangements for different tasks. Also, sensor-data resolution requirements may vary between different tasks and, in certain instances, within the duration of a single task. Various aspects of the present disclosure are directed to circuits and/or algorithms that optimize sensor data collection, transmission, and/or processing based on various contextual information derived from various sources of data, as discussed in greater detail below.

[0156] Optimizing sensor data collection, transmission, and/or processing can be achieved by modulating, adapting, or adjusting one or more sensor parameters associated with data collection, transmission, and/or processing such as, for example, sensor sampling rate, sampling drive current and/or voltage, collection rate, sensor data resolution, sensor-data transmission rate, duration of activation, and/or frequency of activation. In at least one example, a sensor, or a group of sensors, can be switched to an inactive mode, an idler mode, or an active mode to optimize sensor data collection, transmis-

sion, and/or processing.

[0157] FIG. 13 is a logic flow diagram of an algorithm 1000 depicting a control program or a logic configuration for optimizing sensor data collection, transmission, and/or processing in connection with a sensor array configured to detect one or more conditions of an end effector of a surgical instrument. In the illustrated example, the algorithm 1000 includes detecting 1002 a bandwidth or capacity (B) of data transmission between the sensor array and a remote processing unit, detecting 1004 a discharge rate (D) of a power source configured to supply power to the end effector, and modulating 1008 a sensor parameter of a sensor, or a subset of sensors, of the sensor array based on a detected value of the bandwidth (B) and a detected value of the discharge rate (D). In certain instances, the algorithm 1000 further includes detecting 1006 a remaining capacity (R) of the power source, and modulating 1008 a sensor parameter of the sensor, or the subset of sensors, of the sensor array further based on a detected value of the remaining capacity (R) of the remote power source. In certain instances, as described in greater detail below, sensor-parameter modulation can be achieved by selecting a sensor-parameter value based on detected values of bandwidth (B), discharge rate (D), and/or remaining capacity (R).

[0158] FIG. 14 is a logic flow diagram of another algorithm 1010 depicting a control program or a logic configuration for optimizing sensor data collection, transmission, and/or processing in connection with a sensor array configured to detect one or more conditions of an end effector of a surgical instrument. The algorithm 1010 includes receiving 1012 one or more signals indicative of a priority level of sensor data of a subset of sensors of the sensor array, and modulating 1014 a sensor parameter of the subset of sensors based on the detected priority level of the sensor data. Additionally, or alternatively, the algorithm 1010 may further include modulating 1016 a sensor parameter of another subset of sensors based on the priority level of the sensor data.

[0159] As discussed above, the sensor parameter modulation (e.g. 1014, 1016) can be performed on one or more sensor parameters associated with data collection, transmission, and/or processing such as, for example, sensor sampling rate, sampling drive current and/or voltage, collection rate, sensor data resolution, sensor-data transmission rate, duration of activation, and/or frequency of activation. In certain instances, the modulation (e.g. 1014, 1016) of the sensor parameter of the subset of sensors is further based on real-time constraints of data bandwidth (B), power discharge rate (D), and/or power remaining capacity (C), for example.

[0160] In certain instances, sensor-parameter modulation comprises adjusting the content of the sampling waveform/signal (i.e. spectrum of light, frequency of vibration, AC frequencies, etc.). In other instances, sensor-parameter modulation comprises adjusting sampling time of the signal analyzer, reducing the number of active

sensors, multiplexing/combining individual sensors into a single sensor, and/or analyzing different combinations of sensors.

[0161] Furthermore, sensor-parameter modulation can include one or more stepped adjustments to the sensor parameter, which may be implemented over one or more predetermined time periods. Additionally, or alternatively, sensor-parameter modulation can include one or more gradual adjustments to the sampling parameter, which may be implemented over one or more predetermined time periods.

[0162] In certain instances, a sensor parameter can be modulated to a value equal to, or at least substantially equal to, zero. Further, sensor-parameter modulations can be separated by periods of no modulation, for example. In various instances, sensor-parameter modulation can be implemented in accordance with one or more preset equations, tables, and/or databases, as discussed in greater detail below.

[0163] Further to the above, the algorithm 1010 may include adjusting a sensor parameter of a first subset of sensors of the sensor array based on the priority level of the sensor data received from a second subset of the sensor array. For example, during articulation of the end effector, the algorithm 1010 may decrease a sampling parameter of a first subset of sensors relevant to closure and/or firing of the end effector, and may increase a sampling parameter of a second subset sensors relevant to articulation. The adjustments improve the resolution of the articulation sensor data without data and/or power overtaxing. In another example, during firing of the end effector, the algorithm 1010 may decrease the sampling parameter of the second subset of sensors relevant to closure of the end effector, and may increase the sampling parameter of the first subset of sensors relevant to firing. Additionally, or alternatively, during closure, the algorithm 1010 may increase the sampling parameter of the second subset of sensors relevant to closure of the end effector, and may increase the sampling parameter of the first subset of sensors relevant to firing. In at least one example, the articulation, firing, and/or closure durations can be ascertained based on situational awareness data, as discussed in greater detail below.

[0164] FIG. 15 is a logic flow diagram of another algorithm 1080 depicting a control program or a logic configuration for optimizing sensor data collection, transmission, and/or processing in connection with a sensor array configured to detect one or more conditions of an end effector of a surgical instrument. In the illustrated example, the algorithm 1080 determines 1081 a priority level of one or more subsets of sensors of the sensor array. In certain instances, the priority level can be determined based on one or more signals indicative of the priority level such as, for example, the task being performed, or about to be performed, by the surgical instrument. In any event, if 1082 the priority level is determined to be a high priority level, the one or more subsets of sensor are switched to an active mode 1083, for example. However,

if 1082 the priority level is determined to be a low priority level, the one or more subsets of sensor are switched to an idler mode 1084, for example.

[0165] In various aspects, the active mode 1083 is defined by one or more higher values of sensor parameters associated with data collection, transmission, and/or processing such as, for example, sensor sampling rate, sampling drive current and/or voltage, collection rate, sensor data resolution, sensor-data transmission rate, duration of activation, and/or frequency of activation. On the contrary, the idler mode 1084 is defined by lower values of such sensor parameters compared to the active mode 1083. As such, sensor data in the idler mode 1084 can be associated with higher noise and a lowered resolution. In certain instances, the priority level of a subset of sensors is determined to be a high priority level, which triggers a switch to the active mode 1082, if a variation, or a spike, in the high noise/ low resolution sensor data is detected.

[0166] FIG. 16 illustrates various aspects of a surgical system 1020 configured to implement aspects of one or more algorithms for optimizing sensor data collection, transmission, and/or processing such as, for example, the algorithms 1000, 1010, 1080. In the illustrated example, the surgical system 1020 includes a surgical instrument 1022 including a control circuit 1026. The surgical instrument 1022 may also include wired and/or wireless communication circuits to communicate with a surgical hub 1024, a local server, and/or a cloud-based system. In certain instances, the surgical instrument 1022 is a handheld surgical instrument. In other instances, the surgical instrument 1022 is a robotic surgical tool.

[0167] In the illustrated example, the control circuit 1026 includes a microcontroller 1028 comprising one or more processors 1030 (e.g., microprocessor, microcontroller) coupled to at least one memory circuit 1032. The memory circuit 1032 stores machine-executable instructions that, when executed by the processor 1030, cause the processor 1030 to implement various processes or algorithms described herein. The processor 1030 may be any one of a number of single-core or multicore processors known in the art. The memory circuit 1032 may comprise volatile and non-volatile storage media. The processor 1030 may include an instruction processing unit and an arithmetic unit. The instruction processing unit may be configured to receive instructions from the memory circuit 1032 of this disclosure. The control circuit 1026 may comprise analog or digital circuits such as, for example, programmable logic devices (PLD), field programmable gate arrays (FPGA), discrete logic, or other hardware circuits, software, and/or firmware, or other machine executable instructions to perform the functions explained in the present description.

[0168] Further to the above, the control circuit 1026 is in signal communication with a motor driver 1034, a feedback system 1038, a power source 1043 (e.g. a battery, a super capacitor, or any other suitable energy

source), and a sensor array 1036 configured to detect one or more conditions of an end effector 1040 of the surgical instrument 1022. An electric motor 1042, driven by the motor driver 1034, operably couples to a longitudinally movable displacement member 1044 configured to drive firing, closure, and/or articulation motions at the end effector 1040, as explained in greater detail elsewhere herein. In certain instances, a surgical instrument 1022 may include dedicated motor drivers and/or motors for firing, closure, and/or articulation.

[0169] In certain instances, the control circuit 1026 may control the motor 1042 by generating a motor set point signal. The motor set point signal may be provided to the motor driver 1034. The motor driver 1034 may comprise one or more circuits configured to provide a motor drive signal to the motor 1042 to drive the motor 1042 as described herein. In some examples, the motor 1042 may be a brushed DC electric motor. For example, the velocity of the motor 1042 may be proportional to the motor drive signal. In some examples, the motor 1042 may be a brushless DC electric motor and the motor drive signal may comprise a PWM signal provided to one or more stator windings of the motor 1042. Also, in some examples, the motor driver 1034 may be omitted, and the control circuit 1026 may generate the motor drive signal directly.

[0170] In various arrangements, the sensor array 1036 may comprise any suitable sensor for detecting one or more conditions at the end effector 1040 including, without limitation, a tissue thickness sensor such as a Hall Effect Sensor or a reed switch sensor, an optical sensor, a magneto-inductive sensor, a force sensor, a pressure sensor, a piezo-resistive film sensor, an ultrasonic sensor, an eddy current sensor, an accelerometer, a pulse oximetry sensor, a temperature sensor, a sensor configured to detect an electrical characteristic of a tissue path (such as capacitance or resistance), or any combination thereof. In certain instances, and without limitation, the sensor array 1036 may include one or more sensors located at, or about, articulation joint of the surgical instrument 1022 such as, for example, a potentiometer, a capacitive sensor (slide potentiometer), piezo-resistive film sensor, a pressure sensor, a pressure sensor, or any other suitable sensor type. In some arrangements, the sensor array 1036 may comprise a plurality of sensors located in multiple locations in, on, the end effector 1040.

[0171] Still referring to FIG. 16, the surgical instrument 1022 further includes a transmission system 1045 configured to transfer a data/communication signal from the microcontroller 1028 to the end effector 1040. Additionally, or alternatively, the transmission system 1045 can further be configured to transfer power from the power source 1040 to the end effector 1040. In at least one exemplification, the data transfer and/or power transfer is achieved through a wired connection. In another exemplification, the data transfer and/or power transfer is achieved through a wireless connection. In certain in-

stances, the transmission system 1045 includes wireless connection portions and wired connection portions. The wireless connection portions facilitate a reliable transmission of power and/or data over moving parts of the surgical instrument 1022 such as, for example, an articulation joint.

[0172] In various exemplifications, the transmission system 1045 employs one or more wireless communication protocols such as, for example, a low frequency RFID protocol, a high frequency RFID protocol, a near field communication (NFC) protocol, an ultra-high frequency RFID protocol, a Bluetooth communication protocol, a Qi protocol, or a proprietary communication protocol, or any other suitable communication protocol. United States Patent U.S. 9,171,244, issued October 27, 2015, and titled RFID TAG, which is incorporated by reference herein in its entirety, discloses a short range wireless communication mechanism.

[0173] In at least one example, an NFC protocol may utilize a gross bit rate of 426 kbits/s. Other gross bit rates are contemplated by the present disclosure. In certain instances, the transmission system 1045 will run at lower bit rates due to excessive noise, for example. In certain instances, the NFC communication protocol utilizes a half-duplex communication.

[0174] The transmission system 1045 connects the end effector 1040 to a remote processing unit such as, for example, the processor 1030 and/or a remote power source such as, for example, the power source 1043. In certain exemplifications, the remote processing unit and/or the power source can be located at a remote proximal location from the end effector 1040 such as, for example, in a proximal housing or a handle of the surgical instrument 1022. The transmission system 1045 ensures a reliable connection between the end effector 1040 and the remote processing unit and/or the remote power source.

[0175] As discussed above, the end effector 1040 may include a sensor array 1036 configured to monitor one or more aspects of the surgical instrument 1022 and/or tissue grasped by the end effector 1040. In at least one exemplification, the sensor array 1036 is incorporated, or partially incorporated, into a staple cartridge 1046 releasably couplable to a cartridge channel 1048 of the end effector 1040. At least one of the cartridge channel 1048 and an anvil 1031 is movable relative to the other to grasp the tissue between the anvil 1031 and the staple cartridge 1046. The transmission system 1045 can be configured to transfer power to the staple cartridge 1046 for operation of the sensor array 1036. Additionally, or alternatively, the transmission system 1045 may transfer a data/communication signal between the staple cartridge 1046 and the microcontroller 1028, for example.

[0176] As described in greater detail below, various components of the transmission system 1045 are arranged, or positioned, in a manner that facilitates a wireless transmission of power and/or a data signal within the end effector 1040 such as, for example, from a

cartridge support channel of the end effector 1040 to a staple cartridge 1046 releasably insertable into the cartridge support channel. Additionally, or alternatively, the transmission system 1045 can be arranged, or positioned, in a manner that facilitates a wireless transmission of power and/or a data signal from a shaft of the surgical instrument 1022 to the end effector 1040 across an articulation joint connecting the shaft and the end effector 1040, for example.

[0177] In various instances, the staple cartridge 1046 may house, or at least partially house, the sensor array 1036. The power source 1043 can be configured to power the sensor array 1036. Power supplied by the power source 1043 can be wirelessly transferred to the staple cartridge 1046 through the transmission system 1045. Furthermore, the microcontroller 1028 can be in signal communication with the sensor array 1036. Data/communication signals can be wirelessly transferred between the surgical instrument 1022 and the staple cartridge 1046 through the transmission system 1045. Further, various command signals can also be transferred using the transmission system 1045 to the sensor array 1036.

[0178] Referring to FIGS. 16 and 17, in certain instances, the staple cartridge 1046 includes a local control circuit 1049 in communication with the sensor array 1036. The local control circuit 1049 and/or the sensor array 1036 can be powered wirelessly by the power source 1043 through the transmission system 1045. FIG. 17 illustrates an example implementation of the local control circuit 1049. In the illustrated example, the local control circuit 1049 includes a local microcontroller 1076 with a local processor 1041 and a local memory circuit 1047. The local memory circuit 1047 may store machine-executable instructions that, when executed by the processor 1041, may cause the processor 1041 to implement various processes or algorithms in accordance with the present disclosure. The processor 1041 may be any one of a number of single-core or multicore processors known in the art. The memory circuit 1047 may comprise volatile and non-volatile storage media. The processor 1041 may include an instruction processing unit and an arithmetic unit. The instruction processing unit may be configured to receive instructions from the memory circuit 1047 of this disclosure. In certain instances, the control circuit 1049 may comprise analog or digital circuits such as programmable logic devices (PLD), field programmable gate arrays (FPGA), discrete logic, or other hardware circuits, software, and/or firmware, or other machine executable instructions to perform the functions explained in the following description.

[0179] In certain instances, the control circuit 1049 comprises a sensor circuit. Signals (e.g., voltage, current, resistance, impedance, capacitance, inductance, frequency, phase, etc.) from the sensors of the sensor array 1036 can be conditioned by the sensor circuit.

[0180] Further to the above, the local microcontroller 1076 can be in wireless signal communication with the

microcontroller 1028 through the transmission system 1045. Sensor data of the sensor array 1036 can be collected and prepared for transmission by the local control circuit 1049. The local microcontroller 1076 can be configured to compress the sensor data prior to transmission to the control circuit 1026 through the transmission system 1045.

[0181] Various aspects of one, or more, algorithms described by the present disclosure can be executed by the control circuit 1026, the control circuit 1049, or both in collaboration. For brevity, the following description will only focus on an execution by the control circuit 1049 or an execution by the control circuit 1026, but this should not be construed as limiting.

[0182] FIGS. 6-8 illustrate different implementations 1051, 1052, 1053 of the transmission system 1045. The reader will understand that other implementations are contemplated by the present disclosure. FIG. 8 illustrates an example implementation 1053 of the transmission system 1045 where data and power are wirelessly transmitted separately using two independent pathways. Alternatively, FIG. 7 illustrates an example implementation 1052 of the transmission system 1045 where data and power are wirelessly transmitted sequentially using a single pathway. Alternatively, FIG. 6 illustrates an example implementation 1051 of the transmission system 1045 where data and power are wirelessly transmitted simultaneously using a single pathway.

[0183] Through the transmission system 1045, and as described in the implementations 1051, 1052, 1053 of FIGS. 6-8, the staple cartridge 1046 can be supplied by power wirelessly from the power source 1043. The supplied power is utilized in collection and/or signal processing of sensor data of the sensor array 1036. In certain instances, the power is supplied by the power source 1043 directly to the sensor array 1036. Alternatively, a local power source such as, for example, the charge accumulator 11800 (FIG. 7) may supply the power to the sensor array 1036. The charge accumulator 11800 may include a storage capacitor which can be charged by power supplied by the power source 1043. In various aspects, discharge rate (D) and/or remaining-charge capacity (C) can be detected, or monitored, by a charge meter.

[0184] Further to the above, the control circuit 1049 can be configured, or programmed, to modulate 1008 a sensor parameter of one or more subsets of sensors of the sensor array 1036 to balance power draw with remaining power capacity in accordance with one or more equations, tables, and/or databases stored, for example, in the memory circuit 1032, or the memory circuit 1047. As illustrated in FIG. 18, a sampling rate (S) can be selected from a table 1090 based on detected values of bandwidth (B), discharge rate (D), and/or remaining capacity (R). For example, detected values B1, D1, R1, cause the control circuit 1049, to select a sampling rate (S1). The sampling rate (S) of one or more subsets of sensors of the sensor array 1036 can then be adjusted to the sampling

rate (S1), for example. Accordingly, collection and/or signal processing of the sensor data of the sensor array 1036 can be automatically adjusted by the control circuit 1026, or the local control circuit 1049, to balance power draw with remaining capacity.

[0185] Referring primarily to FIGS. 15, and 16, a control circuit 1026 can be configured to determine the priority level of sensor data received from a subset of sensors of the sensor array 1036 based on one or more signals indicative of the priority level. In certain instances, the signal is transmitted to the control circuit 1026 from the surgical hub 1024. In other instances, the one or more signals are transmitted to the control circuit 1026 from one or more sensors. In other instances, the one or more signals are transmitted to the control circuit 1026 from the feedback system 1038.

[0186] In certain instances, the one or more signals communicate contextual information derived from received data concerning a surgical procedure, the surgical instrument 1022, and/or a patient. The contextual information could be derived by a situationally aware surgical hub 1024. In one exemplification, the contextual information can be derived by a control circuit of the surgical hub 1024. In another exemplification, the contextual information can be derived by a cloud computing system. In yet another exemplification, the contextual information can be derived by a distributed computing system including at least one of the aforementioned cloud computing system and/or a control circuit of the surgical hub 1024 in combination with a control circuit 1026 of the surgical instrument 1022, for example. For economy, the following description focuses on contextual information derived by the control circuit of a surgical hub 1024; however, it should be understood that deriving the contextual information can be accomplished by any of the aforementioned exemplifications.

[0187] In certain instances, the contextual information is derived from one or more data sources such as, for example, databases, patient monitoring devices, and modular devices. In one exemplification, the databases can include a patient EMR database associated with the medical facility at which the surgical procedure is being performed. The data received from the data sources can include perioperative data, which includes preoperative data, intraoperative data, and/or postoperative data associated with the given surgical procedure. The data received from the databases can include the type of surgical procedure being performed or the patient's medical history (e.g., medical conditions that may or may not be the subject of the present surgical procedure). In one exemplification, the control circuit of the surgical hub 1024 can receive the patient or surgical procedure data by querying the patient EMR database with a unique identifier associated with the patient. The surgical hub can receive the unique identifier from, for example, a scanner for scanning the patient's wristband encoding the unique identifier associated with the patient when the patient enters the operating theater.

[0188] In one exemplification, the patient monitoring devices include BP monitors, EKG monitors, and other such devices that are configured to monitor one or more parameters associated with a patient. The patient monitoring devices can be paired with the surgical hub 2034 such that the surgical hub receives data therefrom. In one exemplification, the data received from the modular devices that are paired with (i.e., communicably coupled to) the surgical hub 1024 includes, for example, activation data (i.e., whether the device is powered on or in use), data of the internal state of the modular device (e.g., force to fire or force to close for a surgical cutting and stapling device, pressure differential for an insufflator or smoke evacuator, or energy level for an RF or ultrasonic surgical instrument), or patient data (e.g., tissue type, tissue thickness, tissue mechanical properties, respiration rate, or airway volume).

[0189] In certain instances, the contextual information can include, for example, the type of procedure being performed, the particular step being performed in the surgical procedure, the patient's state (e.g., whether the patient is under anesthesia or whether the patient is in the operating room), or the type of tissue being operated on. In certain instances, the contextual information is derived from perioperative data that includes, for example, data regarding a modular device (e.g., pressure differential, motor current, internal forces, or motor torque) or data regarding the patient with which the modular device is being utilized (e.g., tissue properties, respiration rate, airway volume, or laparoscopic image data). Additional details are disclosed in U.S. Patent Application Serial No. 16/209,395, titled METHOD OF HUB COMMUNICATION, and filed December 4, 2018, now U.S. Patent Application Publication No. 2019/0201136, which is hereby incorporated by reference herein in its entirety.

[0190] In certain instances, the contextual information is derived from imaging data received from one or more imaging devices. The imaging data can represent individual images or a video stream. The medical imaging device can include an optical component and an image sensor that generates imaging data. The optical component includes a lens or a light source, for example. The image sensor includes a charge-coupled device (CCD) or a complementary metal-oxide-semiconductor (CMOS), for example. In various exemplifications, the medical imaging device includes an endoscope, a laparoscope, a thoracoscope, and other such imaging devices. The image or video data from the medical imaging device (or the data stream representing the video for a digital medical imaging device) can be processed by a pattern recognition system or a machine learning system to recognize features (e.g., organs or tissue types) in the field of view (FOV) of the medical imaging device 5108, for example. The contextual information that can be derived from the recognized features can include, for example, what type of surgical procedure (or step thereof) is being performed, what organ is being operated on,

or what body cavity is being operated in.

[0191] In various aspects, the control circuit 1026 is configured to select a priority level of one or more subsets of sensors of the sensor array 1036, in accordance with the algorithm 1010, based on the contextual information. Further, the control circuit 1026 may switch one or more subsets of sensors of the sensor array 1036 between the active mode 1083 and the idler mode 1084, in accordance with the algorithm 1080, based on the contextual information. In at least one example, the control circuit 1026 may utilize the contextual information derived from an operating room imaging/video feed to identify steps in a surgical procedure and, further, prioritize sensor data collection, transmission, and/or processing based on the step being performed. For example, the control circuit 1026 may identify a step in an anastomosis surgical procedure such as, for example, an initial tissue engaging step, based on the contextual information. The identification of the initial tissue engaging step, then causes the control circuit 1026 to switch one or more sensor subsets to the active mode 1083.

[0192] Referring still to FIGS. 13 and 16, the control circuit 1026 can be configured to determine a priority level of one or more sensor subsets of the sensor array 1036 based on one or more signals indicative of a surgical state of the surgical instrument 1022. The signals may include data relating to an operational parameter of the surgical instrument 1022. For example, the signals may include data relating to a function of a motor (e.g. motor 1042).

[0193] Motor data can indicate whether the end effector 1040 is in an articulation motion, a closure motion, or a firing motion. A control circuit (e.g. control circuits 1026, 049) may be configured, or programmed, to prioritize one or more sensors of the surgical instrument 1022 based on the type of motion undertaken by the end effector 1040. For example, closure and firing typically occur after completion of the articulation motion, when a user is fully satisfied with the articulation position of the end effector 1040. Accordingly, the control circuit can be configured, or programmed, to assign a lower priority to closure and/or firing sensor data than articulation sensor data in response to detecting an articulation motion, for example. The control circuit may adjust sensor parameters associated with a subset of sensors relevant to articulation to increase the subset's sampling rate, for example. Additionally, the control circuit may also adjust sensor parameters associated with a subset of sensors relevant to closure and/or firing to reduce the subset's sampling rate during articulation.

[0194] Similar arrangements can be undertaken to prioritize closure sensor data over firing sensor data during closure of the end effector 1040 and/or prioritize firing sensor data over closure sensor data during firing of the end effector 1040. As discussed above, this real-time balancing approach ensures that power resources and data transmission, and/or data processing resources are not overtaxed.

[0195] Referring still to FIGS. 14, 15 and 16, the control

circuit 1026 can be configured to determine 1081 a priority level of one or more sensor subsets of the sensor array 1036 based on one or more signals indicative of a gross movement of the surgical instrument 1022. The surgical instrument 1022 may include one or more sensors configured to measure a gross movement of the surgical instrument 1022 such as, for example, an accelerometer. Detecting a gross movement of the surgical instrument 1022 can indicate a condition of the end effector 1040. For example, the gross movement can indicate that the end effector 1040 is outside the patient's body cavity. Accordingly, the control circuit 1026 can be configured, or programmed, to deprioritize closure and/or firing sensor data in response to a signal indicative of a gross movement of the surgical instrument 1022. In at least one example, deprioritizing the closure and/or firing sensor data comprises switching sensors of the sensor array 1036 associated with closure and/or firing to the idler mode 1084. In at least one example, deprioritizing the closure and/or firing sensor data comprises adjusting one or more sensor parameters of sensors of the sensor array 1036 associated with closure and/or firing such as, for example, sensor parameters that control sensor data collection, processing, and/or transmission.

[0196] Further to the above, a similar approach can be taken in response to signals indicative of a loading procedure, signals comprising initiation data, and/or tool-docking data, signals indicative of a high end-effector velocity, and/or any other signals indicating that cartridge sensing is unnecessary at a particular stage. The control circuit 1026 can be configured, or programmed, to adjust one or more sensor parameters of the sensor array 1036 in response to the detection of one or more of such conditions to minimize sensor power/data overtaxing.

[0197] Determining 1081 a priority level of one or more sensor subsets, in accordance with one or more algorithms (e.g. algorithms 1010, 1080), can be achieved in multiple ways. In one example, the priority level can be a binary priority level, where the control circuit 1026 is configured to select between, for example, a high-priority level or a low-priority level. In certain instances, the high-priority level is associated with the active mode 1083, while the low-priority level is associated with the idler mode 1084. In other examples, the priority level comprises a value that can be determined based on one or more equations, tables, and/or databases stored in the memory circuit 1032, for example. One or more conditions can contribute to the priority level in accordance with preset values stored in the form of equations, tables, and/or databases.

[0198] Referring primarily to FIGS. 13 and 16, as discussed above, the algorithm 1000 includes detecting 1002 a data-transmission bandwidth (B), or maximum data-transmission rate through the transmission system 1045. The data-transmission bandwidth (B) can be detected 1002 in multiple ways. For example, data can be transferred through the transmission system 1045 at rates that are increased gradually, or incrementally, until

an error is detected, or the signal strength is no longer able to permit higher rates of transfer. With each transfer a data receipt confirmation and/or a data integrity confirmation can be requested. If confirmation is received, the transfer rate of the following transfer is increased. If, however, a confirmation is not received, it can be concluded that the most recent transfer rate is beyond the bandwidth capability of the transmission system 1045. In such instances, the transfer rate preceding the most recent transfer rate can be determined to be the data-transmission bandwidth (B) of the transmission system, for example. In certain instances, an initial transfer is performed using a default transfer rate. Following transfers are then performed using transfer rates that are increased gradually, or incrementally, in accordance with predetermined values until a data-transmission bandwidth (B) is detected by a lack of a confirmation, for example.

[0199] Additionally, or alternatively, the data-transmission bandwidth (B) can be detected 1002 during an initial acknowledgment or handshake. Acknowledgement and/or handshake signals can be transferred between the control circuit 1026 and the local control circuit 1049 through the transmission system 1045 as part of an activation, initialization, and/or wake-up sequence of the staple cartridge 1046 and/or the surgical instrument 1022, for example.

[0200] In certain instances, transmission rates associated with successful transmissions during one or more prior uses of a surgical instrument 1022 are stored, and are then used in detecting 1002 a bandwidth (B) in subsequent uses of the surgical instrument 1022, or other similar surgical instruments 1022. In one example, the successful transmission rates can be stored in the memory circuit 1032 for sharing during the initial acknowledgment or handshake in future uses. The control circuit 1026 can be configured, or programmed, to monitor the cartridge reloads used with the surgical instrument 1022 which are each trying to maximize data throughput, and can subsequently suggest to future cartridge reloads the maximum transfer rate previous cartridge reloads were capable of achieving.

[0201] In another example, the successful transmission rates can be transmitted to a surgical hub (e.g. surgical hub 1024) and/or a cloud based system for data aggregation and analysis. The data-transmission bandwidth (B) can be detected 1002 based on a signal received from the surgical hub or the cloud based system indicative of the data-transmission bandwidth (B), for example.

[0202] FIG. 19 is a logic flow diagram of an algorithm 1100 depicting a control program or a logic configuration for monitoring and addressing signal interference in power and/or data signals transmission between a staple cartridge 1046 and a surgical instrument 1022. As described elsewhere herein, reloads of the staple cartridge 1046 are releasably coupled to the surgical instrument 1022 by seating in a cartridge channel 1048 of the end

effector 1040. Further, a wireless connection can be established between the staple cartridge 1046 and the surgical instrument 1022 when the staple cartridge 1046 is seated in the cartridge channel 1048 to wirelessly transmit 1102 power and/or data signals. The power and/or data signals can be transferred through a wiring harness, extending in the cartridge channel, and then through wireless power and/or data transfer circuit(s) of the transmission system 1045. The power and/or data signals transmission is subject to various internal and external interferences.

[0203] Various internal and external factors may cause signal interference such as, for example, signal interference from environmental factors including tissue and/or fluid presence in the end effector 1040, signal interference from other surgical tools, or even other components of the surgical instrument 1022. The wireless power and/or data transfer circuit(s) can be at least partially affixed to the metallic cartridge channel 1048. In certain instances, parasitic losses through the metallic cartridge channel 1048, antenna misalignment in the wireless power and/or data transfer circuit(s), and/or secondary magnetic field generation may also contribute to signal interference.

[0204] To manage signal interferences, the algorithm 1100 monitors 1104 an interference in a transmission of electrical power and/or the data signals between the surgical instrument 1022 and the staple cartridge 1046. The algorithm 1100 further modulates 1106 an operational parameter of the surgical instrument 1022 based on the interference. In at least one exemplification, modulating 1106 the operational parameter includes adjusting a strength of the data signals, a rate of the data transmission, and/or a rate of the power transmission based on the detected interference. In certain instances, modulating 1106 the operational parameter includes adjusting one or more sensor parameters associated with data collection, transmission, and/or processing such as, for example, sensor sampling rate, sampling drive current and/or voltage, collection rate, sensor data resolution, sensor-data transmission rate, duration of activation, and/or frequency of activation. In at least one example, a sensor or a group of sensors can be switched to, an inactive mode, an idler mode, or an active mode to mitigate the interference.

[0205] Further to the above, monitoring 1104 the interference can be accomplished by comparing an anticipated data transfer and an actual data transfer by the transmission system 1045 to account for losses due to interference. If a difference between the anticipated data transfer and the actual data transfer is greater than, or equal to, a predetermined threshold, the transmission system 1045 adjusts one or more operational parameters of the surgical instrument 1022 such as, for example, a strength of the data signal to mitigate the interference. In various aspects, monitoring 1104 the interference includes monitoring signal stability, number of lost data packets, and/or ratio of distinguishable signal to random

noise. If signal stability, number of lost data packets, and/or ratio of distinguishable signal to random noise is greater than, or equal to, a predetermined threshold, the transmission system 1045 adjusts one or more operational parameters of the surgical instrument 1022, as previously discussed.

[0206] Furthermore, monitoring 1104 the interference may comprise determining an interference level based one or more factors that contribute to the inference level. The factors may include, for example, ratio of anticipated data transfer to actual data transfer, signal stability, number of lost data packets, and/or ratio of distinguishable signal to random noise. The contributions of the individual factors to the interference level can be ascertained from an interference equation, interference table, and/or interference database, which can be stored in a memory circuit (e.g. memory circuits 1032, 1047). The control circuit 1026, for example, can be configured, or programmed, to calculate an interference level based on the individual contributions of the individual factors. The control circuit 1026 may further compare the determined interference level to a predetermined threshold. If the determined interference level is greater than, or equal to, the predetermined threshold, the processor may modulate 1016, as previously discussed, one or more operational parameters of the surgical instrument 1022 until the monitored interference level decreases to a value below the predetermined threshold, for example.

[0207] Referring primarily to FIGS. 6-8 and 17, a staple cartridge 1046 can be configured to detect which of the implementations 1051, 1052, 1053 of the transmission system 1045 is available for wireless signal transmission between the staple cartridge 1046 and the surgical instrument 1022. The staple cartridge 1046 may further select various protocols and/or algorithms associated with an available implementation. In one example, a control circuit 1049 can detect the available implementation of the transmission system 1045 by detecting the presence of one or two local antenna arrays. If two antenna arrays are detected, as embodied by the implementation 1053 of FIG. 8, the control circuit 1049 may adjust one or more operational parameters of the surgical instrument 1022 and/or select one or more algorithms and/or communication protocols associated with separate power and data transfers. Alternatively, if only a single antenna array is detected, as embodied by the implementations 1051, 1052 of FIGS. 6, 7, the control circuit 1049 may adjust one or more operational parameters of the surgical instrument 1022 and/or select one or more algorithms and/or communication protocols associated with simultaneous/sequential power and data transfers.

[0208] In various aspects, antenna array detections are performed during a wakeup or activation sequence, or a handshaking protocol, implemented, or at least partially implemented, by the control circuit 1049. In at least one example, antenna array detections are performed by the control circuit 1049 using predefined test

signals. In certain instances, control circuit 1049 detects and monitors short range and/or long range data transfer activity to determine connection characteristics and/or instructional hierarchy. In certain instances, the control circuit 1049 performs selective pairing based on sensor array capabilities.

[0209] FIG. 20 is a logic flow diagram of an algorithm 1110 depicting a control program or a logic configuration for optimizing power transmission from a surgical instrument 1022 to a staple cartridge 1046. As discussed above, a transmission system 1045 can electrically couple the surgical instrument 1022 and the staple cartridge 1046 wirelessly while the staple cartridge 1046 is seated in a jaw of the end effector 1040. In at least one exemplification, one or more aspects of the algorithm 1110 are performed by a power management circuit which can be implemented, at least in part, by the control circuit 1026, the control circuit 1049, and/or a separate power management circuit. In the illustrated example, the algorithm 1110 includes wirelessly transmitting 1112 power from the surgical instrument 1022 to the staple cartridge 1046, monitoring 1114 an efficiency of a transfer of the power from the surgical instrument 1022 to the staple cartridge 1046, and adjusting 1116 an operational parameter of the surgical instrument 1022 based on the efficiency of the transfer.

[0210] In various aspects, monitoring 1114 the efficiency of the power transfer includes comparing an anticipated power transfer to an actual power transfer. In certain instances, monitoring 1114 the efficiency of the power transfer includes comparing a transfer parameter such as, for example, a rate of transfer to a predetermined threshold. Further efficiency of the power transfer can be affected a number of environmental factors including parasitic losses, interference, antenna misalignment, and/or secondary magnetic field generation. In certain instances, monitoring 1114 the efficiency of the power transfer includes monitoring one or more of such environmental factors.

[0211] Referring still to FIG. 20, the adjusted 1116 operational parameter of the surgical instrument may be a transfer parameter of the transmission system 1045. In certain instances, adjusting 1116 the operational parameter of the surgical instrument 1022 includes adjusting one or more aspects of a waveform of the power transfer, adjusting a rate of the power transfer, and/or adjusting a frequency of the power transfer. Additionally, or alternatively, adjusting 1116 the operational parameter of the surgical instrument 1022 may include an adaptive voltage scaling. Additionally, or alternatively, adjusting 1116 the operational parameter of the surgical instrument 1022 may include a real-time tuning of at least one component of the transmission system 1045, as described in greater detail below.

[0212] One or more transfer parameters associated with previous power transfers between the surgical instrument 1022 and one or more staple cartridges 1046 are stored by, for example, the memory circuit 1032.

Additionally, or alternatively, transfer parameters associated with previous power transfers can be uploaded to a local server and/or a cloud based system for data aggregation and analysis, for example. In certain instances, the power management circuit of the surgical instrument 1022 may determine transfer parameters of future power transfers based, at least in part, on the stored transfer parameters associated with previous power transfers. In at least one exemplification, the power management circuit may determine transfer parameters for a future power transfer, then compare the determined transfer parameters to the stored transfer parameters, prior to implementation of the determined transfer parameters, to ensure that the determined transfer parameter is within acceptable thresholds based on the stored transfer parameters.

[0213] In certain instances, adjusting 1116 the operational parameter of the surgical instrument 1022 includes adjusting the power drive frequency of the transmission system 1045 based on current operating conditions. Since there are restricting regulations around the use of EM frequencies, which may vary between different regions, the power management circuit may implement one or more algorithms that select an optimal power drive frequency that also complies with such regulations. Said another way, in selecting the optimal power drive frequency, the power management circuit may be limited to regionally-available unlicensed frequency bands.

[0214] Further to the above, selecting the optimal power drive frequency may also depend on which implementation of the transmission system 1045 is available. For example, in the implementation 1053 of FIG. 8, which denotes separate data and power transmission, power transfer is not limited by data-transfer frequency standards. In such instances, the optimal power drive frequency is selected from values different than data-transfer frequency. However, the implementations 1051, 1052 of FIGS. 6 and 7, which denote simultaneous or sequential power and data transfer, are limited by data-transfer frequency standards. Accordingly, the power management circuit may implement one or more algorithms that select the optimal power drive frequency, at least in part, based on available implementations of the transmission system 1045. As discussed above, detecting the available implementation of the transmission system 1045 can be performed by detecting the presence of one or two local antenna arrays. Alternatively, the power management circuit may detect the available implementation of the transmission system 1045 by various testing signals.

[0215] In certain instances, adjusting 1116 the operational parameter of the surgical instrument 1022 includes circuit tuning for resonance, frequency matching, and/or impedance matching. FIG. 21 illustrates an example implementation 1120 of a first antenna circuit 1121 and a second antenna circuit 1122 of the transmission system of 1045 for power transfer between the surgical instrument 1022 and the staple cartridge 1046. Other imple-

mentations are contemplated by the present disclosure. In the illustrated example, the first antenna circuit 1121 is connected to an input voltage V_{in} . The input voltage V_{in} can be the power source 1043, which can be positioned proximally from the end effector 1040 in a housing, or handle, of the surgical instrument 1022, for example. The second antenna circuit 1122 is connected to a load resistor R_L , which represents the sensor array 1036, the control circuit 1049, and/or other power consuming components of the staple cartridge 1046.

[0216] In the illustrated example, the antenna circuits 1121, 1122 cooperate to wirelessly transmit power supplied by the power supply 1043 to the staple cartridge 1046. The first antenna circuit 1021 further includes a voltage driver resistor R_{in} , a primary inductor L_1 , and a primary coil resistor R_1 . The second antenna circuit 1122 further includes a secondary inductor L_2 and a secondary coil resistor R_2 . Power is transferred from a first antenna implemented by the primary inductor L_1 , and the primary coil resistor R_1 to a second antenna implemented by the secondary inductor L_2 , and the secondary coil resistor R_2 . The input voltage V_{in} drives a current through the primary coil, which induces a voltage in the secondary coil, and hence a current across the load resistor R_L . As current flows in the secondary coil, the current induces a voltage in the primary coil, depending on a coupling coefficient (k).

[0217] Referring still to FIG. 21, the first antenna circuit 1121 further includes a first resonant capacitor C_1 in parallel with the primary coil. In addition, the second antenna circuit 1122 includes a second resonant capacitor C_2 in series with the secondary coil. In various instances, the power management circuit utilizes the first resonant capacitor C_1 and the second resonant capacitor C_2 in tuning for resonance, frequency matching, and/or impedance matching. Resonance is a way to compensate for a lower coupling coefficient (k) by increasing the power in the magnetic field around the primary coil. If the coupling coefficient is unchanged then the resultant power across the secondary coil is increased. Accordingly, resonance minimizes the reactive power in the primary coil, and maximizes the power across the load resistor R_L .

[0218] To optimize power transfer through the transmission system 1045, the power management circuit is configured to perform a real-time electro/mechanical algorithm driven adjustment and tuning of various components of the transmission system 1045 such as, for example, transmission capacitors, inductors, and resistors to optimize power transfer. In certain instances, the power management circuit employs various adjustment/tuning mechanisms such as, for example, potentiometers, banks of resistors, capacitors, and/or inductors. Further, the power management circuit may employ variable capacitors and/or variable inductors. In certain instances, optimizing power transfer through the transmission system 1045 comprises impedance matching. In certain instances, optimizing power transfer through

the transmission system 1045 comprises maximizing a coupling coefficient k .

[0219] FIGS. 22 and 23 illustrate an adjustable series RLC (resistor, inductor, capacitor) circuit 1130 and an adjustable parallel RLC circuit 1135, respectively, which can be employed by the power management circuit in tuning the primary, or drive, coil of the transmission system 1045 to optimize wireless power transfer there-through. The adjustable series RLC circuit 1130 and the adjustable parallel RLC circuit 1135 include adjustable components (e.g. resistor R , inductor L , capacitor C) that can be modulated to tune the primary, or drive, coil to a frequency equal to, or at least substantially equal to, that of the secondary, or receiving, coil of the transmission system 1045. In certain instances, the power management circuit is configured to employ the adjustable series RLC circuit 1130 or the adjustable parallel RLC circuit 1135 to adjust a drive frequency of the primary, or drive, coil to a resonant, or most efficient, frequency of the secondary, or receiver, coil, or at least within the resonant band. The real-time frequency matching of the transmission system 1045 optimizes power transfer by eliminating manufacturing variability such as, for example, part, installation, and/or use variability.

[0220] In various aspects, an adjustable series RLC circuit 1130 or an adjustable parallel RLC circuit 1135 can also be employed to tune the secondary, or receiver, coil of the transmission system 1045 in a similar manner to the primary, or drive, coil. Accordingly, the power management circuit can be configured to achieve frequency matching by tuning both of the primary, or drive, coil and the secondary, or receiver, coil to a desirable frequency. In various aspects, one or more RLC circuits can be employed by the power management circuit as a band-pass filter, band-stop filter, low-pass filter, or high-pass filter.

[0221] FIG. 24 is a graph 1246 illustrating a resonant state of the adjustable series RLC circuit 1130. The graph 1136 depicts frequency on the X-axis and Impedance on the Y-axis. At resonance, in a series RLC circuit, the inductor reactance X_L and the capacitor reactance X_C are equal and canceling. So in resonant series RLC circuit, the opposition to the flow of current is due to resistance R only. In addition, the inductor voltage V_L and capacitor voltage V_C are also opposite and equal in value, thereby canceling each other out. At resonance, the series RLC circuit acts purely as resistive circuit which maximizes current passing there through.

[0222] Various implementations (e.g. 1051, 1052, 1053) of the transmission system 1045, as illustrated in FIGS. 6-8, include a rectifier 11620 that is configured to rectify the AC signal to a DC output. In certain instances, the rectifier 11620 is a full bridge rectifier. The need to rectify the AC signal to a DC output may reduce the efficiency of the power transfer through the transmission system 1045 and/or detune its resonance. In certain instances, monitoring 1114 the efficiency of power transfer includes monitoring changes caused by AC to DC

regulation and/or rectification based on power levels and efficiencies of the conversion. Various controlled aspects of the transmission system 1045 can be regulated based on power conversion efficiencies.

[0223] In certain instances, adjusting 1116 the operational parameter of the surgical instrument 1022 includes adaptive voltage scaling based on the power draw of the staple cartridge 1046 and the power reservoir and/or power transfer capabilities of the power source 1043 (FIG. 16) and/or the charge accumulator 11800 (FIG. 7), for example. The power management circuit may implement algorithms for conserving power by selectively determining which systems are permitted to draw power and the voltage levels at which the power can be drawn.

[0224] In one example, the power management circuit may implement an algorithm that causes two subsets of sensors of the sensor array 1036 to draw power at different voltage levels depending, for example, on a priority level of the sensor data from the two subsets. The power management circuit may cause a first sensor subset to operate in an idler mode or an inactive mode, and may cause a second sensor subset, different from the first sensor subset, to operate in an active mode. The power management circuit may implement the active mode, idler mode, and/or inactive mode by changing power-draw permissions of the sensor subsets and/or by adjusting the voltage levels at which the sensor subsets may draw the power.

[0225] In addition to optimizing power transfer, a power management circuit of the surgical instrument 1022 may also implement one, or more, algorithms for power conservation and/or optimizing power consumption by the staple cartridge 1046. FIG. 25 is a logic flow diagram of an algorithm 1140 depicting a control program or a logic configuration for power conservation or optimizing power consumption by a staple cartridge 1046, in accordance with at least one aspect of the present disclosure. The algorithm 1140 includes monitoring 1142 a level of power available for power consumption by the staple cartridge 1046. The algorithm 1140 may further include determining 1144 a power requirement for signal processing of raw data such as, for example, sensor data of the sensor array 1036.

[0226] Further to the above, the algorithm 1140 may include selecting 1146 between local processing and remote processing of the raw data based on the available power level and/or the power requirement for locally processing the raw data. In certain instances, the selection 1146 is between performing a signal processing of the raw data locally within the staple cartridge 1046, using for example the control circuit 1049, or remotely outside the staple cartridge 1046, using, for example, the control circuit 1026.

[0227] Further to the above, monitoring 1142 the power level can be accomplished by measuring the power level using, for example, a charge meter and comparing the measured power level to a predetermined threshold.

Additionally, or alternatively, monitoring 1142 the power level can be achieved by monitoring power consumption. The present power level can then be calculated by subtracting the value of the power consumed from the total power available for consumption.

[0228] Further to the above, the power requirement for signal processing of a particular set of raw data can be determined 1146 from an equation, table, and/or database stored in the memory circuit 1047, for example. In certain instances, the power requirement can be a function of the size of the raw data set and/or the nature or type of the signal processing. Various details of local signal processing are disclosed in U.S. Patent No. 9,993,248, titled SMART SENSORS WITH LOCAL SIGNAL PROCESSING, and issued June 12, 2018, which is hereby incorporated by reference herein in its entirety.

[0229] In various instances, in situations of low power levels, the local processing unit, e.g. control circuit 1147, may perform selective data processing, instead of a wholesale transfer of the data processing to a remote processing unit, e.g. control circuit 1026. The selective data processing can be based on previously assigned priorities of different data processing tasks and/or data types. In one example, to mitigate low power levels, the control circuit 1147 may elect to maintain a previously defined sampling rate for collection of sensor data from the sensor array 1036, while forgoing, or pausing, data encryption. In another example, to mitigate low power levels, the control circuit 1147 may elect to maintain a first sampling rate by a first subset of sensors of the sensor array 1036, while adjusting a second sampling rate by a second subset of sensors of the sensor array 1036.

[0230] In various aspects, the staple cartridge 1046 includes a local charge accumulator (e.g. charge accumulator 1075 of FIG. A5) configured to locally store power supplied thereto by a remote power source (e.g. power source 1043 of FIG. 16), through the transmission system 1045. The local charge accumulator 11800 may be configured to supply power to the control circuit 1049, the sensor array 1036, and/or other power consuming components of the staple cartridge 1046. In certain instances, monitoring 1142 the power level, in accordance with the algorithm 1140, includes monitoring a charge status, a discharge rate, and/or a charge rate of the local charge accumulator. In at least one example, the monitoring 1142 is accomplished by comparing determined values of the charge status, discharge rate, and/or charge rate to predetermined charge status, discharge rate, and/or charge rate thresholds, respectively.

[0231] Further to the above, the power management circuit may adjust one or more operational parameters of the staple cartridge 1046 based on one or more of the comparisons to mitigate power consumption. For example, if a determined value of the charge status is less than or equal to the predetermined charge status threshold, if a determined value of the discharge rate is greater than or equal to the predetermined discharge rate threshold, and/or if a determined value of the charge rate is less

than or equal to the predetermined charge rate threshold, the power management circuit may adjust one or more operational parameters of the staple cartridge 1046. The adjustments may comprise a series of progressively increasing adjustments configured to mitigate power consumption.

[0232] Further to the above, adjusting the operational parameters of the staple cartridge 1046 may include adapting, or adjusting, one or more sensor parameters associated with data collection, transmission, and/or processing such as, for example, sensor sampling rate, sampling drive current and/or voltage, collection rate, sensor data resolution, sensor-data transmission rate, duration of activation, and/or frequency of activation. In certain instances, adjusting the operational parameters of the staple cartridge 1046 can be further based on situational awareness data derived by a surgical hub 1024 (FIG. 16), for example.

[0233] FIG. 26 is a logic flow diagram of an algorithm 1150 depicting a control program or a logic configuration for optimizing a wireless transmission of power and/or data signal across a transmission system 1045, in accordance with at least one aspect of the present disclosure. In the illustrated example, the algorithm 1150 includes detecting 1151 a location of the surgical instrument 1022, and selecting 1152 a frequency band based on the location of the surgical instrument 1022. Further, the algorithm 1150 may include selecting 1153 a drive frequency of the primary, or drive, coil of the transmission system 1045 from the frequency band. In addition, the algorithm 1150 may include selecting 1154 a receiving frequency of the secondary, or receiver, coil of the transmission system 1045 from the frequency band.

[0234] In various aspects, one or more aspects of the algorithm 1150 can be implemented by a control circuit such as, for example, the control circuit 1026, the control circuit 1049, or a local processing unit of the transmission system 1045. In certain instances, detecting 1151 the location of the surgical instrument 1022 comprises detecting a parameter indicative of the location such as, for example, longitude and latitude readings. The readings can be utilized by the control circuit 1049 to identify a location of the surgical instrument 1022. In other instances, the location of the surgical instrument 1022 can be entered by a user through the feedback system 1038, for example. Further, selecting 1153 the drive frequency and/or selecting 1154 the receiving frequency from the frequency band can be based on one or more operational parameters of the surgical instrument 1022.

[0235] Frequency band selection can depend on local regulations. In various aspects, a memory circuit 1032, or memory circuit 1047, may store a table or database listing various locations and corresponding available frequency bands. A control circuit executing the algorithm 1150 can be configured to utilize the table or database to select 1152 a suitable frequency band based on available frequency bands at a detected 1151 location, for example.

[0236] Referring to FIGS. 8B, 8C, and 8D various

components of an adaptive control system 1155 of the surgical instrument 1022 can be located in a cavity 1156 within a proximal portion of an end effector 10400, which is similar in many respects to the end effector 1040. The adaptive control system 1155 is configured to manage various aspects of wireless power and/or data signal transfer between the staple cartridge 1046 and the surgical instrument 1022. In the illustrated example, the adaptive control system 1155 includes a tuning electronics package 1157 for optimizing wireless power and/or data signal transfer through the transmission system 1045. The tuning electronics package 1157 is positioned in the cavity 1156 in close proximity to the antenna array(s) of the transmission system 1045 to enable locally tunable wireless power and/or data signal transfer including adjustments of frequency usage, power transfer rate, and/or data transfer rate, for example.

[0237] Further to the above, the adaptive control system 1155 may include a dedicated power management circuit and a dedicated data-signal management circuit or, alternatively, a common power and data signal management circuit. Various algorithms described elsewhere in the present disclosures can be implemented by the circuits of the adaptive control system 1155 to optimize various aspects of wireless power and/or data-signal transfer between the staple cartridge 1046 and the surgical instrument 1022. The adaptive control system 1155 may include various tuning circuits, or tuning circuit components, as described in greater detail in connection with FIGS. 21-23, such as an adjustable series RLC circuit 1130 and/or an adjustable parallel RLC circuit 1135, for example. In one exemplification, the adaptive control system 1155 implements tuning by multiple sequential adjustments of transfer parameters associated with wireless transfer of power then data, or data then power.

[0238] In one implementation, the adaptive control system 1155 includes a capacitor, an inductor, a digital-to-analog converter (DAC), a voltage regulator, and/or a local processing unit such as, for example, an integrated circuit (IC) chip, which can be configured to adjust/filter a drive frequency of the antenna array(s) of transmission system 1045 and/or adjust at least one of a capacitance and an impedance to optimize wireless power and/or data-signal transfer between the staple cartridge 1046 and the surgical instrument 1022. In certain instances, the adaptive control system 1155 optimizes the wireless power and/or data-signal transfer by adjusting one or more parameters of the surgical instrument 1022 such as wireless power and/or data-signal transfer parameters, for example, to minimize signal reflection.

[0239] To minimize latency and improve speed of dynamic balance, the electronics package 1157 of the adaptive control system 1155 and an antenna array of the transmission system 1045 (e.g. antenna array 10530", 10535") configured to be tuned by the adaptive control system 1155 are placed in closed proximity to one

another. In certain instances, as illustrated in FIG. 8C, the electronics package 1157 of the adaptive control system 1155 and the antenna array 10530", 10535" of the transmission system 1045 are spaced apart a predefined distance (D).

[0240] FIG. 8C depicts an implementation 1053 of the transmission system 1045 with separate power and data signal transfer. However, other implementations (e.g. implementations 1051, 1052 of FIGS. 6 and 7) of the transmission system 1045 may include similar arrangements where the separation between the electronics package 1157 of the adaptive control system 1155 and an antenna array is limited to the predefined distance (D). For brevity, the following discussion of the predefined distance (D) will focus on the example implementation 1053 illustrated in FIG. 8C, which includes the antenna array 10530", 10535".

[0241] As described above, the electronics package 1157 is stored in a cavity 1156 at a proximal portion of an end effector 10400 which is similar in many respects to the end effector 1040. Further, the antenna array 10530", 10535" is mounted on a sidewall of a jaw 10410. In the illustrated example, the electronics package 1157 resides in the cavity 1156 at a proximal portion of the jaw 10410, but distal to an articulation joint 10500. The placement of the electronics package 1157 within the cavity 1156 permits the electronics package 1157 to be a predefined distance (D) away from the antenna array 10530", 10535", as illustrated in FIG. 8C.

[0242] In various aspects, the predefined distance (D) is selected from a range of about 0.1" to about 1.0", a range of about 0.2" to about 0.8", a range of about 0.3" to about 0.7", a range of about 0.4" to about 0.6", or a range of about 0.45" to about 0.55", for example. In at least one example, the predefined distance (D) is 0.50", 0.51", 0.52", 0.49", or 0.48". Other values for the predefined distance (D) are also contemplated by the present disclosure.

[0243] In various aspects, the cavity 1156 is located under a distal channel retainer 1158 that provides a location where the end effector 10400 can be operatively coupled (mounted) to the articulable joint 10500. In the illustrated example, the cavity 1156 is located below a pin 1159 configured to attach the distal channel retainer 1158 to the jaw 10400. In certain instances, a firing bar 10640, which is operatively coupled to a motor (e.g. motor 1042), extends over the cavity 1156. The firing bar 10640 is driven distally by the motor 1042 to push the tissue cutting knife 10630 through a staple cartridge 11000", which is similar in many respects to the staple cartridge 1046, during a staple firing stroke.

[0244] Further to the above, the pin 1159 may be fixed to sidewalls of the jaw 10410 to prevent rotation of the distal channel retainer 1158 relative to the jaw 10410. The placement of the pin 1159 leaves a sufficient space between the pin 1159 and a base 1174 of the jaw 10410 to accommodate the electronics package 1157 within sufficient proximity from the sensor array 10530",

10535" to minimize latency and/or improve speed of dynamic balance performed by the adaptive control system 1155.

[0245] In the illustrated example, the electronics package 1157 is connected to the antenna array 10530", 10535" by a flex circuit 1175. In other examples, the electronics package 1157 is integrated onto the flex circuit 1175 with no hard circuit board. In such instances, the flex circuit 1175 may bridge the articulation joint 10500. One or more retention features can be incorporated into the articulation joint to minimize the interaction between the flex circuit 1175 and moving components within the articulation joint 10500. In certain instances, portions of the flex circuit 1175 can be coupled to biasing members that ensure that the flex circuit 1175 is retained away from pinch and/or catch points, for example.

[0246] FIG. 27 is a logic flow diagram of an algorithm 1160 depicting a control program or a logic configuration for calibrating a sensor array 1036 of a surgical instrument 1022, in accordance with at least one aspect of the present disclosure. In the illustrated example, the algorithm 1160 includes performing 1161 an initial calibration of the sensor array 1036, and determining 1162 an initial adjustment to the measurements based on the initial calibration. Additionally, the algorithm 1160 may include performing 1163 an in-use calibration of the sensor array 1036, and modifying 1164 the initial adjustment based on the in-use calibration. The modification 1164 of the initial adjustment may yield a final adjustment, for example.

[0247] In the illustrated example, the algorithm 1160 is implemented, or at least partially implemented, by the control circuit 1049. In other examples, various aspects of the algorithm 1160 can be implemented by other control circuits such as, for example, the control circuit 1026, or any other suitable control circuit. Further, in the illustrated example, the algorithm 1160 is executed in a calibration of the sensor array 1036. In other examples, the algorithm 1160 can be equally executed in a calibration of other sensors, or sensor arrays, of the surgical instrument 1022.

[0248] As discussed elsewhere in the present disclosure in greater detail, sensors of the sensor array 1036 are configured to determine a parameter associated with a function of the surgical instrument 1022. The initial adjustment and/or final adjustment normalize readings of the sensors that are utilized to determine the parameter. In one form, the parameter is a tissue parameter such as, for example, a tissue thickness. In another form, the parameter is an operational parameter of the end effector 1040 such as, for example, a parameter of a closure state of the end effector 1040.

[0249] In one form, the algorithm 1160 can be limited to performing 1161 the initial calibration, and determining 1162 the initial adjustment. In another form, the algorithm 1160 can be limited to performing 1163 an in-use calibration, and determining an adjustment based on the in-use calibration without the initial calibration.

[0250] Further to the above, the initial calibration may

include a calibration performed at a manufacturing facility, or a testing facility, outside an operating room and/or before shipping to an end user. On the other hand, the in-use calibration may include a calibration performed by an end-user, after unpacking, such as, for example, in an operating room or hospital. The in-use calibration of a sensor array 1036 of a staple cartridge 1046 can be triggered by a wake-up or an initialization signal, for example, from the surgical instrument 1022, for example. The wake-up or an initialization signal can be delivered through the transmission system 1045, for example. In certain instances, performing 1161 the initial calibration and/or performing 1163 the in-use calibration can be triggered by a user input through the feedback system 1038.

[0251] In various aspects, the algorithm 1160 includes performing 1161 the initial calibration and/or performing 1163 the in-use calibration against a cartridge retainer disposed against the sensor array 1036. Cartridge retainers are typically used to maintain staples of a staple cartridge in place during shipping and/or seating of the staple cartridge in a jaw of the surgical instrument 1022, for example. In certain instances, the cartridge retainer can be modified to include calibration features with known resistive, capacitive, and/or inductive properties. An initial calibration of the sensor array 1036 can be performed 1161 by causing one or more sensors of the sensor array 1036 to take measurements of the calibration features corresponding to their known resistive, capacitive, and/or inductive properties. The measurements can then be compared to stored values of the known resistive, capacitive, and/or inductive properties. An initial adjustment to the sensor array 1162 measurements can be determined 1162 based on the measurements and the stored values. The initial calibration may include a normalizing process using reference values to correct for capacitive bleed, variation in wiring length, and read distance across sensors, for example. In addition, the initial calibration may include a sequence of comparisons against known design variation to identify correction values.

[0252] Similarly, an in-use calibration of the sensor array 1036 can be performed 1163 using a cartridge retainer, in an operating room for example, by causing one or more sensors of the sensor array 1036 to take measurements of the calibration features of the cartridge retainer corresponding to their known resistive, capacitive, and/or inductive properties. The in-use calibration can be performed automatically as a part of an activation, initialization, and/or wake-up sequence. In one example, the measurements can be compared to stored values of the known resistive, capacitive, and/or inductive properties, and a final adjustment to the sensor array 1162 measurements can be determined 1162 based on the measurements and the stored values. In another example, the measurements of the in-use calibration are compared to the measurements of the initial calibration to detect any changes due to the sterilization, packing,

transit, shelf-life, and/or un-boxing that may have further affected the sensor array 1036.

[0253] In certain instances, a conductive medium such as, for example, an electric grease is placed between the staple cartridge and the cartridge retainer to ensure a proper electrical connection between the measured features of the cartridge retainer and corresponding sensors of the sensor array 1036. The conductive medium eliminates, or at least reduces, environmental, or contact, based variations in measurements taken by the sensors of the sensor array 1036 of the features of the cartridge retainer. In other instances, another calibration member can be employed instead of the cartridge retainer to perform 1161 the initial calibration and/or perform 1163 the in-use calibration. The measured features can be disposed onto, or under, a flat, or substantially flat, surface of the calibration member, which can be placed against the sensors of the sensor array 1036 to perform a calibration thereof.

[0254] In various aspects, the algorithm 1160 may include performing 1161 the initial calibration and/or in-use calibration in a predetermined medium such as air, saline, or any other suitable with known properties that can be measured by the sensors of the sensor array 1036. An initial calibration of the sensor array 1036 can be performed 1161 by causing one or more sensors of the sensor array 1036 to take measurements of one or more of the medium's known properties while the sensors are immersed in the medium. The measurements can then be compared to predetermined values of the known properties. An initial adjustment to the sensor array 1162 measurements can be determined 1162 based on the measurements and the predetermined values.

[0255] Similarly, an in-use calibration of the sensor array 1036 can be performed 1163 by causing one or more sensors of the sensor array 1036 to take measurements corresponding to one or more of the medium's known properties while the sensors are immersed in the medium. As discussed above, the in-use calibration can be performed automatically as a part of an activation, initialization, and/or wake-up sequence. In one example, the measurements can be compared to stored values of the known properties, and a final adjustment to the sensor array 1162 measurements can be determined 1162 based on the measurements and the stored values. In another example, the measurements of the in-use calibration are compared to the measurements of the initial calibration to detect any changes due to the sterilization, packing, transit, shelf-life, and/or un-boxing that may have further affected the sensor array 1036.

[0256] In certain instances, the control circuit 1026 may give instructions to immerse the end effector 1040 in an operating room medium such as, for example, saline prior to taking sensor measurements in accordance with the in-use calibration. The instructions can be given through the feedback system 1038, for example. The control circuit 1026 may request a confirmation of the immersion. The instructions can be issued during an

activation, initialization, and/or wake-up sequence of the staple cartridge 1046, after a seating of the staple cartridge in a jaw of the end effector 1040, for example. Upon receipt of the confirmation, the in-use calibration can then be performed as previously described.

[0257] Further to the above, the algorithm 1160 may store a determined 1162 value of the initial adjustment in a memory circuit 1047 of the staple cartridge 1046. During a wake-up or an initialization sequence of the staple cartridge 1046, the stored value of the initial adjustment can be communicated to the main control circuit 1026 of the surgical instrument 1022, for example, using the transmission system 1045, for example. The processor 1030 may employ the initial adjustment in converting readings of the sensors of the sensor array 1036 to values of a corresponding tissue parameter, for example. Alternatively, the processor 1041 may perform the conversion locally in the staple cartridge 1046. Converted values can then be communicated to the control circuit 1026 using the transmission system 1045.

[0258] Further to the above, performing 1163 the in-use calibration may include determining one or more conversion factors representing variations due to various influences such as sterilization, shipping time, shelf life, previous use time, elevation, environmental impacts such as humidity and/or temperature, physical damage, sensor degradation, and/or drift, for example. Each of these influences may contribute to a deviation that can be remedied by a modification 1064 to the initial adjustment. In certain instances, the algorithm 1160 calculates a final adjustment based on the initial adjustment and one, or more, additional conversion factors corresponding to sterilization, shipping time, shelf life, previous use time, elevation, environmental impacts such as humidity and/or temperature, physical damage, sensor degradation, and/or drift, for example.

[0259] In certain instances, the conversion factors can be determined from equations, tables, and/or databases stored in the memory circuit 1047. Information about these influences can be provided by a user input through the feedback system 1038, for example. Additionally, or alternatively, the information can be ascertained locally using internal clocks, timers/counters (e.g. timer/counter 2781), various sensors, and/or various forms of signal processing. Additionally, or alternatively, the information can be determined based on one or more signals received by the surgical instrument 1022 from a local server, a surgical hub (e.g. surgical hub 1024), and/or a cloud based system, for example.

[0260] In one example, the shipping time can be determined based on a manufacturing date, which can be stored in the memory circuit 1047 or entered by a user, and an activation date. In another example, elevation can be determined based on a geographical location of the surgical instrument 1022. In other examples, environmental parameters such as humidity and/or temperature parameters can be entered by a user or can be ascertained from environmental sensors on the staple car-

tridge 1046, outer packaging, and/or the surgical instrument 1022. In other examples, physical damage and/or sensor degradation can be determined by detecting a lack of a sensor signal after activation and/or by detecting a lack of a response signal following a transmission of an interrogation signal to the sensors of the sensor array 1036.

[0261] In any event, the control circuit 1026 may utilize the information received regarding the one or more influences to develop individual conversion factors for the influences based on one or more equations, tables, and/or databases stored in the memory circuit 1032, for example. The control circuit 1026 may then determine a final adjustment based on the initial adjustment and one, or more, conversion factors of the individual influences.

[0262] FIG. 28 is a logic flow diagram of an algorithm 1165 depicting a control program or a logic configuration for modulating a control parameter of the surgical instrument 1022, in accordance with at least one aspect of the present disclosure. In the illustrated example, the algorithm 1165 includes measuring 1166 a physical parameter of a staple cartridge 1046 seated in a jaw of the end effector 1040, for example. The algorithm 116 further includes adjusting 1167 a control parameter of the surgical instrument 1022 based on the measured physical parameter of the staple cartridge 1046.

[0263] In the illustrated example, the algorithm 1160 is implemented, or at least partially implemented, by the control circuit 1026. In other examples, various aspects of the algorithm 1160 can be implemented by other control circuits such as, for example, the control circuit 1049, or any other suitable control circuit. For brevity the following description will focus on executing various aspects of the algorithm 1160 by the control circuit 1026.

[0264] In various aspects, the physical parameter is a tissue gap. In certain exemplifications, the tissue gap is a minimum gap (G) between the anvil 1031 and the staple cartridge 1046 determined at a closed configuration of the end effector 1040, as illustrated in FIG. 29. In the illustrated example, the minimum gap (G) is defined by a stop member 1039 configured to interfere with closure of the end effector 1040. The stop member 1039 protrudes from the staple cartridge 1046, and is contacted by the anvil 1031 at the closed configuration. In certain instances, the stop member 1039 is positioned at proximal location of the end effector 1040 such as, for example, behind tissue stops. In other instances, the stop member 1039 can be positioned at a distal end portion of the staple cartridge 1046 or the anvil 1031, for example.

[0265] FIG. 30 is a logic flow diagram of an algorithm 1170 depicting a control program or a logic configuration similar in many respects to the algorithm 1165. Like the algorithm 1165, various aspects of the algorithm 1170 can be implemented, or at least partially implemented, by the control circuit 1026, the control circuit 1049, and/or any other suitable control circuit. The algorithm 1165 exemplifies a specific execution of the measuring 1166

of the physical parameter of the staple cartridge 1046, in accordance with the algorithm 1165, wherein the physical parameter is a tissue gap. In the illustrated example, the algorithm 1170 includes detecting 1171 the closed configuration based on a current draw of the motor 1042, and determining 1172 the minimum gap between the anvil 1031 and the staple cartridge 1046 at the closed configuration. In one example, as described in greater detail below, the minimum gap (G) is determined based on an output signal of a sensor 1035 at the closed configuration.

[0266] During closure of the end effector 1040, the control circuit 1026 is configured to cause the motor 1042 to generate a closure motion that motivates the longitudinally movable displacement member 1044 to transition the end effector 1040 to the closed configuration, as illustrated in FIG. 29. The stop member 1039 is configured to resist the closure motion of the end effector 1040 at the closed configuration. The resistance can be detected by an increase in the current draw of the motor 1042 during a closure of the end effector 1040 to a value greater than, or equal to, a predetermined threshold, which represents reaching the closed configuration. In various aspects, the control circuit 1026 is configured to determine 1173 the minimum gap (G) between the staple cartridge 1046 and the anvil 1031 when the current draw of the motor 1042 is greater than, or equal to, the predetermined threshold.

[0267] The control circuit 1026 may further adjust one or more control parameters of the surgical instrument 1022 based on the determined minimum gap (G). In certain exemplifications, the control parameter can be a parameter of an algorithm executable to perform a function of the surgical instrument 1022. In certain exemplifications, the control parameter is a threshold, or a predetermined algorithm reaction, for example.

[0268] Referring still to FIGS. 29 and 30, the control circuit 1026 can be configured to monitor the gap between the staple cartridge 1046 and the anvil 1031 using one or more sensors 1035. In the illustrated example, the sensor 1035 is a magnetic sensor such as, for example, a Hall Effect sensor. A corresponding magnet 1069 is placed on the anvil 1031. The sensor 1035 can be configured to measure the strength of a magnetic field produced by the magnet 1069. As the gap between the anvil 1031 and the staple cartridge 1046 decreases, the strength of the magnetic field increases. Accordingly, the control circuit 1026 can be configured to monitor the gap between the staple cartridge 1046 and the anvil 1031 by monitoring output signals of the sensor 1035.

[0269] Other sensors for detecting the minimum gap (G) are contemplated by the present disclosure. In one example, the sensor 1035 comprises a strain gage, a photoelectric sensor, a pressure sensor, an inductive sensor, such as an eddy current sensor, a resistive sensor, a capacitive sensor, an optical sensor, and/or any other suitable sensor.

[0270] In various instances, the control circuit 1026 can utilize an algorithm to determine the change in current

drawn by the motor 1042. For example, a current sensor can detect the current drawn by the motor 1042 during the closure motion. The current sensor can continually detect and/or can intermittently detect the current drawn by electric motor 1042. In various instances, the algorithm can compare the most recent current reading to the immediately preceding current reading, for example. Additionally or alternatively, the algorithm can compare a sample reading within a time period X to a previous current reading. For example, the algorithm can compare the sample reading to a previous sample reading within a previous time period X, such as the immediately preceding time period X, for example. In other instances, the algorithm can calculate the trending average of current drawn by the motor 1042. The algorithm can calculate the average current draw during a time period X that includes the most recent current reading, for example, and can compare that average current draw to the average current draw during an immediately preceding time period X, for example.

[0271] In one exemplification, the control circuit 1026 is configured to receive a first signal indicative of the current draw of the motor 1042 during a closure of the end effector 1040, and receive a second signal indicative of the gap between the staple cartridge 1046 and the anvil 1031. The first signal can represent an output of a current sensor configured to monitor a current draw of the motor 1042 during the closure motion, while the second signal can represent an output of the sensor 1035. Further, the control circuit 1026 can be configured to measure a physical parameter of the staple cartridge 1046 by determining the minimum gap (G) between the staple cartridge 1046 and the anvil 1031 at a closed configuration identified by a current draw of the motor 1042 greater than, or equal to, a predetermined threshold.

[0272] The control circuit 1026 may be configured to compare the current draw of the motor 1042 to a predetermined threshold stored in the memory circuit 1032, for example. The control circuit 1026 may further be configured to store a value of the minimum gap (G) between the staple cartridge 1046 and the anvil 1031 when the current draw of the motor 1042 is greater than, or equal to, a predetermined threshold. The stored value can then be employed to modulate one or more control parameters of the surgical instrument 1022.

[0273] Referring still to FIG. 30, the algorithm 1170 may include verifying a tissue compression parameter of the tissue grasped by the end effector 1040 based on the minimum gap (G) and an initial tissue thickness. In certain instances, the algorithm 1170 may verify that the tissue compression parameter is as expected. In one example, the tissue compression parameter is a tissue compression creep which occurs when tissue grasped by the end effector 1040 is allowed time for fluid egress.

[0274] The tissue compression creep depends on the minimum gap (G) and an initial tissue thickness. The initial tissue thickness can be measured using one or more suitable sensors or sensor arrangements such as

those described in U.S. Patent No. 9,345,481, titled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, which issued on May 24, 2016, which is herein incorporated by reference in its entirety; U.S. Patent Application Publication No. 2014/0263552, titled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, which published on September 18, 2014, now U.S. Patent No. 10,032,719, which is herein incorporated by reference in its entirety; and U.S. Patent Application Serial No. 15/628,175, titled TECHNIQUES FOR ADAPTIVE CONTROL OF MOTOR VELOCITY OF A SURGICAL STAPLING AND CUTTING INSTRUMENT, filed June 20, 2017, now U.S. Patent No. 10,881,399, which is herein incorporated by reference in its entirety. In any event, the control circuit 1026 may be configured to verify the tissue compression creep by comparing an expected value of the tissue compression creep, which can be stored in the memory circuit 1032 for example, with a value the tissue compression creep determined based on the minimum gap (G) and an initial tissue thickness.

[0275] In various aspects, as illustrated in FIG. 28, the algorithm 1165 may include verifying 1168, or identifying, the type of staple cartridge 1046 seated in a jaw of the end effector 1040 based on a measured 1166 physical parameter of the staple cartridge 1046. In one example, the physical parameter is a tissue gap, or a minimum gap (G) between the staple cartridge 1046 and the anvil 1031 at the closed configuration.

[0276] As described above, the control circuit 1026 is configured to determine a tissue gap, or a minimum gap (G) between the staple cartridge 1046 and the anvil 1031 at the closed configuration. Different staple cartridge types may include different stop members configured to define different tissue gaps, or minimum gaps (G). Accordingly, the control circuit 1026 may utilize the determined minimum gap (G) to verify the type of the staple cartridge 1046. In one example, the control circuit 1026 is configured to verify 1168, or identify, a type of the staple cartridge 1046 by using a look-up table or database that stores staple cartridge types and corresponding minimum gap (G) values, for example.

[0277] In various aspects, the algorithm 1165 includes modulating one or more control parameters of the surgical instrument 1022 based on the verified 1168, or identified, staple cartridge type. In one example, the control circuit 1026 is configured to select between different algorithms depending on the identified staple cartridge type. The different algorithms can be different sensing algorithms configured to control the sensor array 1036 differently. In another example, the control circuit 1026 is configured to select between different operating modes for sensors, or groups of sensors, of the sensor array 1036 depending on the identified staple cartridge type. The operating mode can include an idler mode, an inactive mode, and/or an active mode. In one example, the control circuit 1026 is configured to adjust algorithm parameter based on the identified staple cartridge type. The algorithm parameter can be a predetermined thresh-

old, for example. In one example, the control circuit 1026 is configured to adjust one or more sensor parameters based on the identified staple cartridge type. Adjustable sensor parameters may include ones associated with data collection, transmission, and/or processing such as, for example, sensor sampling rate, sampling drive current and/or voltage, collection rate, sensor data resolution, sensor-data transmission rate, duration of activation, and/or frequency of activation.

[0278] FIG. 31 is a logic flow diagram of an algorithm 1180 depicting a control program or a logic configuration for modulating a sensor parameter of the sensor array 1036, in accordance with at least one aspect of the present disclosure. In the illustrated example, the algorithm 1180 includes detecting 1181 closure states of the end effector 1040 based on an operational parameter of the motor 1042. The algorithm 1180 further includes selectively modulating 1182 a sensor parameter of sensors of the sensor array 1036 in accordance with the detected closure states. In the illustrated example, the algorithm 1180 is implemented, or at least partially implemented, by the control circuit 1026. In other examples, various aspects of the algorithm 1180 can be implemented by other control circuits such as, for example, the control circuit 1049, or any other suitable control circuit. For brevity the following description will focus on executing various aspects of the algorithm 1180 by the control circuit 1026.

[0279] During closure, the control circuit 1026 is configured to cause the motor 1042 to generate a closure motion that transitions the end effector 1040 from an open configuration toward a closed configuration to grasp tissue between the jaws of the end effector 1040. The transition to the closed configuration includes a plurality of closure states. For example, a first closure state can be characterized by making a first tissue contact which is achieved when both of the anvil 1031 and the staple cartridge 1046 are first simultaneously in contact with the tissue. In certain instances, the staple cartridge 1046 is first placed in contact with a target tissue. The anvil 1031 is then moved toward the target tissue to grasp the tissue between the staple cartridge 1046 and the anvil 1031. In such instances, the first closure state is detected when the anvil 1031 makes first contact with the target tissue placed against the staple cartridge 1046. In other instances, the anvil 1031 is first placed in contact with a target tissue, and the staple cartridge 1046 is then moved toward the target tissue. In such instances, the first closure state is detected when the staple cartridge 1046 makes first contact with the target tissue placed against the anvil 1031.

[0280] In any event, the initial contact with the tissue can yield an increase in the current draw of the motor 1042 during the closure of the end effector due to an initial resistance of the tissue. In certain instances, the increase is in the form of an uptick, or a step-up, which can be detected by the control circuit 1026 as indicative of reaching the first closure state. In other instances, one or both

of the jaws of the end effector 1040 may include one or more sensors configured to detect an initial tissue contact. In one example, the initial tissue contact can be detected when the target tissue closes a tissue contact detection circuit located on a tissue contacting surface of one or both of the jaws of the end effector 1040. When closed, the tissue contact detection circuit may transmit a signal indicative of a first tissue contact, for example. The control circuit 1026 can be configured to detect a second closure state in response to the signal from the tissue contact detection circuit.

[0281] Further to the above, the closure motion generated by the motor 1042 further causes the end effector 1040 to transition from the first closure state to a second closure state characterized by a fully-clamped condition, for example. At the second closure state, a closure force applied to the tissue is equal to, or greater than, a predetermined threshold. Accordingly, the control circuit 1026 can be configured to detect the second closure state by monitoring the closure force. The closure force can be measured by one or more force sensors responsive to a clamping load applied by the motor 1042. In various examples, the one or more force sensors may comprise a force transducer, a torque cell, a load cell, a strain gauge, a Wheatstone bridge, or any other suitable force sensor, for example. The control circuit 1026 can be configured to detect the second closure state in response to a sensor signal generated by the one or more force sensor that indicates a closure force equal to, or greater than, the predetermined threshold, for example.

[0282] Further to the above, the second closure state can be followed by a third closure state characterized by a fully-stabilized tissue creep. During the initial clamping of the target tissue between the anvil 1031 and the staple cartridge 1046, the longitudinally movable displacement member 1044 must transmit a sufficient amount of axial closure force to the anvil 1031 to pivot the anvil 1031 to a closed position and retain it in that position throughout the staple forming process. The amount of closure force required to close the anvil and retain it in a closed position can vary during the stapling process due to "tissue creep". For example, as the anvil 1031 compresses the target tissue, fluid within the clamped target tissue can "creep" or migrate within the tissue and even flow to adjacent unclamped tissue. Following the fully-clamped condition, the grasped tissue is allowed time for fluid egress until the closure force is stabilized. Accordingly, the control circuit 1026 can be configured to detect the third closure state based on the closure force.

[0283] The control circuit 1026 may monitor the closure force for a steady state after the second closure state is detected. In certain instances, the control circuit 1026 is configured to detect the third closure state in response to a sensor signal from the one or more force sensors indicative of reaching a steady state after the second closure state is detected, or after reaching a value greater than, or equal to, the predetermined threshold. In certain instances, the steady state can be characterized by a

change in the closure force less than, or equal to, a predetermined threshold over a predetermined time period (t). In other instances, the steady state can be characterized by a change in the closure force within a predetermined range over a predetermined time period (t).

[0284] Further to the above, selectively modulating 1182 a sensor parameter of sensors of the sensor array 1036 may include selectively modulating sensor parameters may include ones associated with data collection, transmission, and/or processing such as, for example, sensor sampling rate, sampling drive current and/or voltage, collection rate, sensor data resolution, sensor-data transmission rate, duration of activation, and/or frequency of activation. In certain instances, the control circuit 1026 can be configured to selectively switch sensors, or subsets of sensors, of the sensor array 1036 to an active mode, an idler mode, or an inactive mode based on the closure states to optimize data collection, transmission, and/or processing, for example. In at least one example, the control circuit 1026 is configured to incrementally adjust the sampling rate of one or more sensors, or groups of sensors, of the sensor array with the detection of each of the closure states.

[0285] In various aspects, one or more closure states of the end effector 1040 can be detected based on situational awareness data. For example, the control circuit 1026 may detect a closure state of the end effector 1040 based on a signal indicative of situational awareness data received from a surgical hub (e.g. surgical hub 1024) and/or a cloud based system for data aggregation and analysis, for example.

[0286] In various aspects, selectively modulating 1182 a sensor parameter, in accordance with the algorithm 1180, comprises assigning different priorities to different sensor data. The assigned priorities can dictate various aspects of the data collection, transmission, and/or processing, for example. The control circuit 1026 can be configured to assign selectively assign priorities to sensor data from different sensors, or groups of sensors, based on the closure states. In one example, cartridge identification data may be assigned a higher priority in the open configuration, and a lower priority at the first, second, and/or third closure states. In another example, sensor data from tissue contact sensors may be assigned a higher priority up to and/or at the first closure state, and a lower priority at the second and/or third closure states. In yet another example, tissue interrogation data may be assigned a higher priority at the first, second, and/or third closure state, and a lower priority after the third closure state. The higher priority and/or lower priority can be implemented by a circuit 1026 by adjusting various aspects of the data collection, transmission, and/or processing, as previously described in greater detail.

[0287] FIG. 32 is a logic flow diagram of an algorithm 1190 depicting a control program or a logic configuration for modulating a sensor parameter of the sensor array 1036, in accordance with at least one aspect of the

present disclosure. In the illustrated example, the algorithm 1190 includes detecting 1191 a tissue contact status of the staple cartridge 1046. The algorithm 1190 further includes selectively modulating 1182 a sensor parameter of one or more sensors of the sensor array 1036 in accordance with the detected tissue contact status. In the illustrated example, the algorithm 1190 is implemented, or at least partially implemented, by the control circuit 1026. In other examples, various aspects of the algorithm 1190 can be implemented by other control circuits such as, for example, the control circuit 1049, or any other suitable control circuit. For brevity the following description will focus on executing various aspects of the algorithm 1190 by the control circuit 1026.

[0288] In various aspects, detecting 1191 the tissue contact status of the staple cartridge 1046 is performed at each of a plurality of closure states. As the closure of the end effector 1040 commences, the size and/or position of the tissue in contact with the sensor array 1036 of the staple cartridge 1046 may change. To optimize sensor data collection, transmission, and/or processing, the control circuit 1026 can be configured to adjust one or more sensor parameters of one or more sensors, or groups of sensors, of the sensor array 1036 based on whether tissue contact is detected at the different closure states.

[0289] In certain exemplifications, as illustrated in FIG. 33, the sensor array 1036 is disposed along a length L of the staple cartridge 1046. However, the tissue grasped by the end effector 1040 may cover a region 1193 extending only along a portion of the length L, for example extending along a length L1. In such instances, sensor data from sensors beyond the region 1193 can be assigned a lower priority than sensor data from sensors within the region 1193. A control circuit 1026 can be configured to determine a priority level of the sensors of the sensor array 1036 based on their location with respect to the region 1193, for example. Furthermore, the control circuit 1026 can be configured to switch sensors of the sensor array 1036 that are within the region 1193 to an active mode 1083 and/or switch sensors of the sensor array 1136 that are outside the region 1193 to an idler mode 1084 (See FIG. 15), for example.

[0290] In various aspects, tissue contact detection can be accomplished by a tissue contact circuit 2830, as described in greater detail elsewhere in the present disclosure. The tissue contact circuit 2830 is in open circuit mode with no tissue located against the sensors 2788a, 2788b. The tissue contact circuit 2830 is transitioned to a closed circuit mode by the tissue 2820. The sensors 2788a, 2788b are powered by voltage source V and a sensors circuit 2790 measures a signal generated by the sensors 2788a, 2788b. In some aspects, the sensors 2788a, 2788b may include a pair of opposing electrode plates to make electrical contact with the tissue 2820.

[0291] Any of the sensors 2788a, 2788b disclosed herein may include, and are not limited to, electrical contacts placed on an inner surface of a jaw which, when

in contact with tissue, close a sensing circuit that is otherwise open. The contact sensors may also include sensitive force transducers that detect when the tissue being clamped first resists compression. Force transducers may include, and are not limited to, piezoelectric elements, piezoresistive elements, metal film or semiconductor strain gauges, inductive pressure sensors, capacitive pressure sensors, and resistive sensors.

[0292] Further to the above, a control circuit 1026, for example, may receive one or more signals from the sensor circuit 2790 and/or sensors 2788a, 2788b indicative of a tissue contact status of one or more regions along the length L of the staple cartridge 1046. In response, the adjust one or more sensor parameters of one or more sensors, or groups of sensors, the control circuit 1026 can be configured to adjust sensor parameters of one or more sensors of the sensor array 1036 in the one or more regions based on the tissue contact status.

[0293] Additional details are disclosed in U.S. Patent No. 10,595,887, titled SYSTEMS FOR ADJUSTING END EFFECTOR PARAMETERS BASED ON PERIOPERATIVE INFORMATION, and issued March 24, 2020, U.S. Patent No. 9,724,094, titled ADJUNCT WITH INTEGRATED SENSORS TO QUANTIFY TISSUE COMPRESSION, and issued August 8, 2017, and U.S. Patent No. 9,808,246, titled METHOD OF OPERATING A POWERED SURGICAL INSTRUMENT, and issued November 7, 2017, the entireties of disclosures of which are hereby incorporated by reference herein.

[0294] In one general aspect, the present disclosure provides methods of monitoring multiple sensors over time to detect moving characteristics of tissue located in the jaws of the end effector. In one aspect, the end effector comprises a cartridge. More than one sensor can be located on a cartridge to sense the motion of the tissue from one sensor towards an adjacent sensor. In a stapling cartridge, multiple sensors may be located on the stapling cartridge to sense movement of tissue by monitoring a property of the tissue. In one aspect, the tissue property could be an electrical property of the tissue such as impedance or capacitance. In another aspect, monitoring the impedance of the tissue from one time point to the next can allow the system to detect the motion of the tissue from one sensor towards the next.

[0295] In one aspect, a method of monitoring multiple sensors over time to detect moving characteristics of the tissue comprises monitoring multiple sensors over time to detect tissue movement relative to at least two sensed locations. The method provides real-time tissue flow sensing through monitoring a sensed tissue property through time.

[0296] Turning now to FIG. 34, which illustrates a diagram of a surgical instrument 2750 comprising an instrument housing 2800 and an end effector 2752 inductively coupled to the instrument housing 2800 via a set of coils 2818 implementing a wireless power and data communication system, in accordance with at least one aspect of the present disclosure. The instrument housing 2800

comprises an energy source 2762 and a control circuit 2760 inductively coupled to the end effector 2752. Power from the energy source 2762 is inductively coupled to the end effector 2752 from a primary coil 2802 tuned for power located in the instrument housing 2800 to a secondary coil 2804 tuned for power located in the end effector 2752. Data is transmitted between the control circuit 2760 and the end effector sensor circuits 2790 between a primary coil 2816 tuned for data located in the instrument housing 2800 and a secondary coil 2814 tuned for data located in the end effector 2752.

[0297] FIG. 34 illustrates one implementation of the transmission system 1045 for wireless transmission of power and data. In the implementation illustrated in FIG. 34, power and data are transmitted separately. In other implementations, as described supra, power and data are transmitted sequentially or simultaneously. For brevity, the following description focuses on the implementation of the transmission system 1045 that is configured to separately transmit power and data. However, it is understood that the other implementations of the transmission system 1045 can be equally utilized.

[0298] In various aspects, the end effector 2752 comprises a cartridge 2768 and an anvil 2766 pivotally coupled to the cartridge 2768. A plurality of sensors 2788 (see FIG. 40 for a detail view) may be disposed in the cartridge 2768, the anvil 2766, or both. As described supra, the end effector 2752 comprises secondary coils 2804, 2814 to receive power from the instrument housing 2800 and communicate between the end effector 2752 circuits and the instrument housing 2800 circuits, respectively. Power from the secondary coil 2804 is rectified by a rectifier circuit 2806 and filter capacitor 2808 and is provided to a plurality of sensors 2788 via an analog multiplexer 2810 or other analog switching circuit. Signals from the sensors 2788 are transmitted through the analog multiplexer 2810, coupled to a near field communication (NFC) tag 2812, and coupled to the control circuit 2760 from the secondary coil 2814 located in the end effector 2752 and the primary coil 2816 located in the instrument housing 2800. The NFC tag 2812 is configured to transmit data from the cartridge 2768. The sensors 2788 may be configured to measure tissue impedance, tissue temperature, tissue capacitance, tissue inductance, elapsed time, among other tissue parameters explained in the following description.

[0299] In other aspects, the cartridge 2768 portion of the end effector 2752 may comprise electrodes to receive electrosurgical energy to assist or enhance the tissue sealing process. In such aspects, some or all of the plurality of sensors 2788 may act as electrodes to deliver the electrosurgical energy through the tissue clamped between the anvil 2766 and the cartridge 2768. In such aspects, the plurality of sensors 2788 may be configured to measure tissue parameters such as impedance, capacitance, among other tissue parameters explained in the following description.

[0300] In other aspects, the end effector 2752 may

comprise a clamp arm assembly and an ultrasonic blade for cutting and sealing tissue clamped between the clamp arm assembly and the ultrasonic blade instead of the anvil 2766 and cartridge 2768 as shown in the example of FIG. 34. In such aspects comprising a clamp arm assembly and ultrasonic blade, the plurality of sensors 2788 may be disposed in the clamp arm assembly and the electrical return path may be provided through the electrically conductive ultrasonic blade. The plurality of sensors 2788 may be configured to measure tissue parameters such as impedance, capacitance, among other tissue parameters explained in the following description.

[0301] In other aspects, the end effector 2752 may comprise a pair of jaws configured with electrodes to deliver electrosurgical energy to seal tissue clamped between the jaws instead of the anvil 2766 and cartridge 2768 as shown in the example of FIG. 34. One of the jaws may be configured with a knife slot for cutting through the tissue after sealing. In such aspects, the plurality of sensors 2788 may be disposed in either jaw or both. The plurality of sensors 2788 may be configured to measure tissue parameters such as impedance, capacitance, among other tissue parameters explained in the following description.

[0302] In other aspects, the end effector 2752 may comprise a clamp arm assembly and an ultrasonic blade instead of the anvil 2766 and cartridge 2768 as shown in the example of FIG. 34. In such aspects, the clamp arm assembly is configured with electrodes for receiving electrosurgical energy for sealing tissue located between the clamp arm assembly and the ultrasonic blade. The electrical return path for the electrosurgical energy is provided through the electrically conductive ultrasonic blade. In such aspects, the ultrasonic blade is utilized to cut the sealed tissue clamped between the clamp arm assembly and the ultrasonic blade. The plurality of sensors 2788 may be configured to measure tissue parameters such as impedance, capacitance, among other tissue parameters explained in the following description.

[0303] In certain instances, as described in greater detail elsewhere in the present disclosure, wireless power and/or data transmission between an instrument housing 2800 and the end effector 2752 encompasses a wireless power and/or data transmission between the surgical instrument 2750 and the staple cartridge 2768. For example, the primary coils 2802, 2816 can be disposed on a cartridge channel of the end effector 2752, and the secondary coils 2804, 2814 can be disposed on the staple cartridge 2768 such that the primary coils 2802, 2816 and the secondary coils 2804, 2814 are aligned for a wireless connection when the staple cartridge 2768 is seated in the cartridge channel. In such instances, the instrument housing 2800 may encompass a proximal housing including the energy source 2762 and the control circuit 2760, a shaft extending distally from the proximal housing, and the cartridge channel.

[0304] FIG. 35 illustrates a block diagram of the surgical instrument 2750 shown in FIG. 34 comprising an

instrument housing 2800 and an end effector 2752 inductively coupled to the instrument housing 2800 via a set of coils 2818 implementing a wireless power and data communication system, in accordance with at least one aspect of the present disclosure. In one aspect, the surgical instrument 2750 is configured or programmed to control the distal translation of a displacement member such as the I-beam 2764. The surgical instrument 2750 comprises an end effector 2752 that may comprise an anvil 2766, an I-beam 2764 (including a sharp cutting edge), and a removable cartridge 2768. The end effector 2752 comprises sensors 2788 and a sensors circuit 2790 coupled to the sensors 2788. Power is inductively coupled to the sensor circuit 2790 and to the sensors 2788 through coils 2802, 2804 via near field communication. Signals (e.g., voltage, current, resistance, impedance, capacitance, inductance, frequency, phase, etc.) from the sensors 2788 are conditioned by the sensors circuit 2790. The signals or data corresponding to the signals are communicated between the sensors circuit 2790 in the end effector 2752 and the control circuit 2760 in the instrument housing 2800 via near field communication inductive coupling between the coils 2814, 2816.

[0305] It will be appreciated that the sensors 2788 may be located in any suitable location in the end effector 2752. In one aspect, the sensors 2788 are arranged in an array in the cartridge 2768. In another aspect, the sensors 2788 are arranged in an array in the anvil 2766. In various aspects, the sensors 2788 are arranged in arrays in the cartridge 2768 and the anvil 2766. The control circuit 2760 may be configured to monitor the sensors 2788 over time to detect moving characteristics of tissue located in the jaws of the end effector 2752. In one aspect, the jaws of the end effector 2752 may be comprised of the anvil 2766 and the cartridge 2768, for example.

[0306] The position, movement, displacement, and/or translation of a linear displacement member, such as the I-beam 2764, can be measured by an absolute positioning system, sensor arrangement, and position sensor 2784. A control circuit 2760 may be configured or programmed to control the translation of the displacement member, such as the I-beam 2764. The control circuit 2760, in some examples, may comprise one or more microcontrollers, microprocessors, or other suitable processors for executing instructions that cause the processor or processors to control the displacement member, e.g., the I-beam 2764. In other aspects, the control circuit 2760 may comprise analog or digital circuits such as, for example, programmable logic devices (PLD), field programmable gate arrays (FPGA), discrete logic, or other hardware circuits, software, and/or firmware, or other machine executable instructions to perform the functions explained in the following description.

[0307] In one aspect, the control circuit 2760 may be configured or programmed to sense multiple longitudinal and lateral locations within the end effector 2752 independently and to use these different sensed locations

with a localized predetermined return path to sense changes in the impedance of tissue grasped between the anvil 2766 and the cartridge 2768 both laterally and longitudinally to be able to detect any specific tissue mid-thickness measure by triangulating at least two interconnected session combinations. For example, the sensors 2788 may comprise an array of impedance sensors distributed laterally and longitudinally along the length of the stapler jaws, i.e., the cartridge 2768 and anvil 2766. As the jaws are closing, the control circuit 2760 may track the local impedance over time during the course of the jaw closure for each sensor, based on readings from the timer/counter 2781, or using software timing techniques. This time history can be used to infer, if present, regions of heterogeneous impedance values - where there are distinct changes or anomalies that mark a particular location. These baseline location(s) are noted and tracked as firing is initiated. Once initiated, the position histories of these locations is tracked and used for feedback control of the firing process. In another example, the control circuit may be configured or programmed to modify functions of the surgical instrument 2750 to alter tissue flow during firing of the I-beam 2764 including changing the firing speed, pauses (complete stops) in firing, closure force, among other parameters.

[0308] In other aspects, the control circuit 2760 may be configured or programmed to predict an amount of tissue flow occurring in the jaws of the end effector 2752 by monitoring the sensors 2788. Knowledge of tissue type from situational awareness and/or other device sensed measures, e.g., rate of change of closure load during closure, rate of change of closure load after closure is complete, etc. can be used by the control circuit 2760 to predict tissue flow. Accordingly, in one aspect, the control circuit 2760 is configured or programmed to determine tissue type or condition by combining tissue flow during jaw closure with force feedback of the anvil 2766 closure system.

[0309] In another example, the predictions can be further refined by using the sensors 2788 to measure tissue impedance, among other parameters, detect rigid or foreign objects in the jaws, measure magnitude of tissue impedance, measure tissue flow during jaw closure, etc. In another example, the control circuit 2760 may execute a jaw closure algorithm to sense tissue movements during closure as an indicator of the potential effect of each change during firing of the I-beam 2764. For example, at a first closure rate, the control circuit 2760 estimates the magnitude / direction of tissue flow, adjusts the closure rate of the jaws, and observes or records the changes in tissue flow within the jaws. In another example, the control circuit 2760 may be configured or programmed to predict post-fire tissue position by utilizing closure flow in combination with closure force feedback prior to firing to provide feedback to surgeon and allowing an opportunity to reposition the end effector 2752 to ensure tissue is fully captured in cut the line of the end effector 2752 (See slots 2822, 2824 in FIG. 40 for an

example of a cut line).

[0310] In other aspects, the control circuit 2760 may be configured or programmed to receive data for various configurations of the sensors 2788 to monitor and interrogate tissue. This may include, monitoring tissue impedance, and tracking the impedance of the tissue across a single electrode or segmented electrode set configured along the length of the cartridge 2788. The control circuit 2760 may be configured or programmed to monitor spectrographic impedance by utilizing sweeps of different frequencies and monitoring the tissue impedance to the power and frequency to determine the physiological composition of the tissue, monitoring capacitance of the tissue, and determining the tissue characteristics and gap relationship of the jaws to determine the amount of tissue present within the jaws. In another aspect, the control circuit 2760 may be configured or programmed to measure light transmissivity, refractivity or Doppler effects to determine tissue characteristics. Local light refractivity analysis may be employed to determine the surface conditions of the tissue to monitor irregularities within the tissue captured between the jaws. The control circuit 2760 may be configured or programmed to monitor local moving particles of tissue using Doppler effect frequency analysis of the light.

[0311] In one aspect, a timer/counter 2781 provides an output signal, such as the elapsed time or a digital count, to the control circuit 2760 to correlate the position of the I-beam 2764 as determined by the position sensor 2784 with the output of the timer/counter 2781 such that the control circuit 2760 can determine the position of the I-beam 2764 at a specific time (t) relative to a starting position. The timer/counter 2781 may be configured to measure elapsed time, count external events, or time external events. In other aspects, the timer/counter 2781 may be employed to measure elapsed time to monitor the sensors 2788 over time to detect moving characteristics of tissue located in the jaws of the end effector 2752.

[0312] The control circuit 2760 may generate a motor set point signal 2772. The motor set point signal 2772 may be provided to a motor controller 2758. The motor controller 2758 may comprise one or more circuits configured to provide a motor drive signal 2774 to the motor 2754 to drive the motor 2754 as described herein. In some examples, the motor 2754 may be a brushed DC electric motor. For example, the velocity of the motor 2754 may be proportional to the motor drive signal 2774. In some examples, the motor 2754 may be a brushless DC electric motor and the motor drive signal 2774 may comprise a PWM signal provided to one or more stator windings of the motor 2754. Also, in some examples, the motor controller 2758 may be omitted, and the control circuit 2760 may generate the motor drive signal 2774 directly.

[0313] The motor 2754 may receive power from an energy source 2762. The energy source 2762 may be or include a battery, a super capacitor, or any other suitable energy source. The motor 2754 may be me-

chanically coupled to the I-beam 2764 via a transmission 2756. The transmission 2756 may include one or more gears or other linkage components to couple the motor 2754 to the I-beam 2764. A position sensor 2784 may sense a position of the I-beam 2764. The position sensor 2784 may be or include any type of sensor that is capable of generating position data that indicate a position of the I-beam 2764. In some examples, the position sensor 2784 may include an encoder configured to provide a series of pulses to the control circuit 2760 as the I-beam 2764 translates distally and proximally. The control circuit 2760 may track the pulses to determine the position of the I-beam 2764. Other suitable position sensors may be used, including, for example, a proximity sensor. Other types of position sensors may provide other signals indicating motion of the I-beam 2764. Also, in some examples, the position sensor 2784 may be omitted. Where the motor 2754 is a stepper motor, the control circuit 2760 may track the position of the I-beam 2764 by aggregating the number and direction of steps that the motor 2754 has been instructed to execute. The position sensor 2784 may be located in the end effector 2752 or at any other portion of the instrument.

[0314] The control circuit 2760 may be in communication with one or more sensors 2788 located in the end effector 2752. The sensors 2788 may be positioned in the end effector 2752 and adapted to operate with the surgical instrument 2750 to measure various derived parameters such as gap distance versus time, tissue compression versus time, anvil strain versus time, tissue movement versus time, tissue impedance, tissue capacitance, spectroscopic impedance, light transmissivity, refractivity or Doppler effects, among other parameters. The sensors 2788 may comprise a magnetic sensor, a magnetic field sensor, a strain gauge, a pressure sensor, a force sensor, an inductive sensor such as an eddy current sensor, a resistive sensor, a capacitive sensor, an optical sensor, and/or any other suitable sensor for measuring one or more parameters of the end effector 2752. The sensors 2788 may include one or more sensors.

[0315] The one or more sensors 2788 may comprise a strain gauge, such as a micro-strain gauge, configured to measure the magnitude of the strain in the anvil 2766 during a clamped condition. The strain gauge provides an electrical signal whose amplitude varies with the magnitude of the strain. The sensors 2788 may comprise a pressure sensor configured to detect a pressure generated by the presence of compressed tissue between the anvil 2766 and the cartridge 2768. The sensors 2788 may be configured to detect impedance of a tissue section located between the anvil 2766 and the cartridge 2768 that is indicative of the thickness and/or fullness of tissue located therebetween.

[0316] The sensors 2788 may be configured to measure forces exerted on the anvil 2766 by a closure drive system. For example, one or more sensors 2788 can be at an interaction point between a closure tube and the

anvil 2766 to detect the closure forces applied by a closure tube to the anvil 2766. The forces exerted on the anvil 2766 can be representative of the tissue compression experienced by the tissue section captured between the anvil 2766 and the cartridge 2768. The one or more sensors 2788 can be positioned at various interaction points along the closure drive system to detect the closure forces applied to the anvil 2766 by the closure drive system. The one or more sensors 2788 may be sampled in real time during a clamping operation by a processor of the control circuit 2760. The control circuit 2760 receives real-time sample measurements to provide and analyze time-based information and assess, in real time, closure forces applied to the anvil 2766.

[0317] A current sensor 2786 can be employed to measure the current drawn by the motor 2754. The force required to advance the I-beam 2764 corresponds to the current drawn by the motor 2754. The force is converted to a digital signal and provided to the control circuit 2760.

[0318] The drive system of the surgical instrument 2750 is configured to drive the displacement member, cutting member, or I-beam 2764, by a brushed DC motor with gearbox and mechanical links to an articulation and/or knife system. Another example is the electric motor 2754 that operates the displacement member and the articulation driver, for example, of an interchangeable shaft assembly. An outside influence is an unmeasured, unpredictable influence of things like tissue, surrounding bodies and friction on the physical system. Such outside influence can be referred to as drag which acts in opposition to the electric motor 2754. The outside influence, such as drag, may cause the operation of the physical system to deviate from a desired operation of the physical system.

[0319] Various example aspects are directed to a surgical instrument 2750 comprising an end effector 2752 with motor-driven surgical stapling and cutting implements. For example, a motor 2754 may drive a displacement member distally and proximally along a longitudinal axis of the end effector 2752. The end effector 2752 may comprise a pivotable anvil 2766 and, when configured for use, a cartridge 2768 positioned opposite the anvil 2766. A clinician may grasp tissue between the anvil 2766 and the cartridge 2768, as described herein. When ready to use the instrument 2750, the clinician may provide a firing signal, for example by depressing a trigger of the instrument 2750. In response to the firing signal, the motor 2754 may drive the displacement member distally along the longitudinal axis of the end effector 2752 from a proximal stroke begin position to a stroke end position distal of the stroke begin position. As the displacement member translates distally, an I-beam 2764 with a cutting element positioned at a distal end, may cut the tissue between the cartridge 2768 and the anvil 2766.

[0320] In various examples, the control circuit 2760 may be configured or programmed to control the distal translation of the displacement member, such as the I-beam 2764, for example, based on one or more tissue

conditions. The control circuit 2760 may be configured or programmed to sense tissue conditions, such as thickness, flow, impedance, capacitance, light transmissivity, either directly or indirectly, as described herein. The control circuit 2760 may be configured or programmed to select a firing control program based on tissue conditions. A firing control program may describe the distal motion of the displacement member. Different firing control programs may be selected to better treat different tissue conditions. For example, when thicker tissue is present, the control circuit 2760 may be configured or programmed to translate the displacement member at a lower velocity and/or with lower power. When thinner tissue is present, the control circuit 2760 may be configured or programmed to translate the displacement member at a higher velocity and/or with higher power.

[0321] FIG. 36 illustrates a perspective view of an end effector 2752 of the surgical instrument 2750 shown in FIGS. 34 and 35, in accordance with at least one aspect of the present disclosure. The end effector 2752 comprises an anvil 2766 and a cartridge 2768 forming a pair of jaws to grasp tissue 2820 therebetween as shown in FIG. 37. The plurality of sensors 2788 may be disposed in the anvil 2766, the cartridge 2768, or both.

[0322] FIG. 37 depicts an example of an end effector 2752 with tissue 2820 compressed in the jaws formed by the anvil 2766 and cartridge 2768, in accordance with at least one aspect of the present disclosure. The anvil 2766 defines a first longitudinal slot 2822 configured to slidably receive an I-beam portion for closing the anvil 2766 in order to grasp tissue 2820. The cartridge 2768 defines a second longitudinal slot 2824 configured to receive a cutting element for severing the tissue 2820 grasped between the anvil 2766 and the cartridge 2768. The longitudinal slots 2822, 2824 define a cut the line of the end effector 2752. (See slots 2822, 2824 in FIG. 40.)

[0323] With reference now to FIGS. 36-37, the sensors 2788 may be positioned in the anvil 2766 and the cartridge 2768 on opposite sides of the tissue 2820 grasped therebetween. As described supra, the plurality of sensors 2788 may be configured to measure various derived parameters such as gap distance versus time, tissue compression versus time, anvil strain versus time, tissue movement versus time, tissue impedance, tissue capacitance, spectroscopic impedance, light transmissivity, refractivity or Doppler effects, among other parameters.

[0324] FIGS. 38A and 38B are schematic illustrations of a tissue contact circuit 2830, in accordance with at least one aspect of the present disclosure. The tissue contact circuit 2830 in FIG. 38A is shown in open circuit mode with no tissue located between sensors 2788a, 2788b prior to clamping between the anvil 2766 and cartridge 2768 (described in FIGS. 34-37), respectively. The tissue contact circuit 2830 shown in FIG. 38B is shown in closed circuit mode showing the completion of the circuit upon the sensors 2788a, 2788b in contact with tissue 2820 after clamping between the anvil 2766 and cartridge 2768. The sensors 2788a, 2788b are pow-

ered by voltage source V and the sensors circuit 2790 measures a signal generated by the sensors 2788a, 2788b. and come in contact with the tissue 2820 in the jaws. In some aspects, the sensors 2788a, 2788b may include a pair of opposing electrode plates to make electrical contact with the tissue 2820.

[0325] Any of the sensors 2788a, 2788b disclosed herein may include, and are not limited to, electrical contacts placed on an inner surface of a jaw which, when in contact with tissue, close a sensing circuit that is otherwise open. The contact sensors may also include sensitive force transducers that detect when the tissue being clamped first resists compression. Force transducers may include, and are not limited to, piezoelectric elements, piezoresistive elements, metal film or semiconductor strain gauges, inductive pressure sensors, capacitive pressure sensors, and resistive sensors.

[0326] In an aspect, any one of the aforementioned surgical instruments may include one or more piezoelectric elements to detect a change in pressure occurring on the jaw members. Piezoelectric elements are bi-directional transducers which convert stress into an electrical potential. Elements may consist of metallized quartz or ceramics. In operation, when stress is applied to the crystals there is a change in the charge distribution of the material resulting in a generation of voltage across the material. Piezoelectric elements may be used to indicate when any one or both of the jaw members (e.g., anvil 2766, cartridge 2768) makes contact with the tissue 2820 and the amount of pressure exerted on the tissue 2820 after contact is established.

[0327] In an aspect, the sensors 2788a, 2788b may comprise one or more metallic strain gauges placed within or upon a portion of the body thereof. Metallic strain gauges operate on the principle that the resistance of the material depends upon length, width and thickness. Accordingly, when the material of the metallic strain gauge undergoes strain the resistance of the material changes. Thus, a resistor made of this material incorporated into a circuit will convert strain to a change in an electrical signal. Desirably, the strain gauge may be placed on the surgical instruments such that pressure applied to the tissue effects the strain gauge.

[0328] Alternatively, in another aspect, the sensors 2788a, 2788b may comprise one or more semiconductor strain gauges may be used in a similar manner as the metallic strain gauge described above, although the mode of transduction differs. In operation, when a crystal lattice structure of the semiconductor strain gauge is deformed, as a result of an applied stress, the resistance of the material changes. This phenomenon is referred to as the piezoresistive effect.

[0329] In yet another aspect, the sensors 2788a, 2788b may comprise one or more inductive pressure sensors to transduce pressure or force into motion of inductive elements relative to each other. This motion of the inductive elements relative to one another alters the overall inductance or inductive coupling. Capacitive

pressure transducers similarly transduce pressure or force into motion of capacitive elements relative to each other altering the overall capacitance.

[0330] In still another aspect, the sensors 2788a, 2788b may comprise one or more capacitive pressure transducers to transduce pressure or force into motion of capacitive elements relative to each other altering an overall capacitance.

[0331] In one aspect, the sensors 2788a, 2788b may comprise one or more mechanical pressure transducers to transduce pressure or force into motion. In use, a motion of a mechanical element is used to deflect a pointer or dial on a gauge. This movement of the pointer or dial may be representative of the pressure or force applied to the tissue 2820. By way of example, mechanical elements may be coupled with other measuring and/or sensing elements, such as a potentiometer pressure transducer. In this example the mechanical element is coupled with a wiper on the variable resistor. In use, pressure or force may be transduced into mechanical motion which deflects the wiper on the potentiometer thus changing the resistance to reflect the applied pressure or force.

[0332] In another aspect, the tissue 2820 impedance Z may be measured by the sensors circuit 2790 by applying a voltage difference V across the sensors 2788a, 2788b, conducting an electrical current I through the tissue 2820, and measuring the voltage and current (V , I) to determine the impedance Z . In another aspect, the capacitance C of the tissue 2820 between the sensors 2788a, 2788b may be measured by the sensors circuit 2790 based on the tissue impedance Z according to the following formula $C = 1/2\pi fZ$, where f is the frequency of the alternating voltage and current and C is the capacitance of the tissue 2820.

[0333] In one aspect, the sensors circuit 2790 may generally be an integrated circuit that measures the capacitance of the conductive plates of the sensors 2788a, 2788b. In some aspects, the sensors circuit 2790 may measure a supply voltage V and current I , measure an external voltage, and / or measure a temperature. The tissue capacitance sensors circuit 2790 system applies an electric field signal to the tissue 2820 to determine a capacitance signal. The sensors circuit 2790 generates one or more electric signals to generate an electric field signal in the tissue 2820 to drive a capacitance node defined by the conductive plate of sensor 2788a to emit an electric field in the tissue 2820. In some examples, the capacitance node includes a single plate capacitor which uses the tissue 2820 as a dielectric. In many examples, the electric field signal may be a modulated electric signal.

[0334] In one aspect, the sensors circuit 2790 can apply an electric field proximate to the tissue 2820, which can include application of an electric field signal without contact of any capacitor plate portion of capacitance node to the tissue 2820. In other examples, any associated capacitor plate portion of capacitance node is

positioned to contact tissue 2820. A contact example is shown in FIG. 38B. An electric field signal may comprise a modulated signal produced by the sensors circuit 2790 and apply by the voltage supply V .

[0335] The sensors circuit 2790 can detect changes in the electric field signal applied to the tissue 2820 to identify a capacitance signal. These changes in electric field signal can be measured and detected by the sensors circuit 2790. The change in capacitance can be monitored as an electric field signal is applied to the tissue 2820 and the capacitance signal can reflect the change in capacitance. In various aspects, the electric field signal may comprise a modulated signal, such as a sine wave signal. Modulation circuitry used to produce electric field signal can include a capacitor portion of the conductive plate of the sensors 2788a forming a capacitance node. Changes in a capacitance value of a capacitor used to apply electric field signal to the tissue 2820 can be detected by the sensors circuit 2790 as a change in modulation frequency or a change in power draw of the capacitor or associated modulation circuitry, among other detection methods. These changes in electric field signal also can be measured by monitoring changes in a noise level, current draw, or other characteristics of electric field signal as detected by the sensors circuit 2790. The sensors circuit 2790 may comprise capacitance-to-digital converter circuitry. The capacitance signal can be monitored concurrent with other physiological parameter monitoring, as explained in the following description.

[0336] FIG. 39 is a schematic illustration of a surgical instrument 2750 described in connection with FIGS. 34 and 35 comprising sensor monitoring and processing circuit 2400, in accordance with at least one aspect of the present disclosure. The sensor monitoring and processing circuit 2400 is contained within the instrument housing 2800 and is wirelessly coupled to the end effector 2752 through near field communication coils 2802 / 2804 for power and coils 2814 / 2816 for data.

[0337] In one aspect, the sensor monitoring and processing circuit 2400 comprises tissue impedance module 2442. In one aspect, the tissue impedance module 2442 may be configured to measure tissue impedance Z and capacitance. The tissue impedance module 2442 also may be employed to monitor other tissue parameters. In one aspect, the tissue impedance module 2442 may comprise an RF oscillator 2446, a voltage sensing circuit 2448, and a current sensing circuit 2450. The voltage and current sensing circuits 2448, 2450 respond to the RF voltage V_{rf} applied to electrodes or sensors 2788 disposed in the end effector 2752 and the RF current I_{rf} conducted through the electrodes of the sensors 2788, the tissue, and other conductive portions of the end effector 2752. The sensed current I_{rf} and the sensed voltage V_{rf} from the current sense circuit 2430 and the voltage sense circuit 2432 are converted to digital form by the analog-to-digital converter 2436 (ADC) via an analog multiplexer 2434. The control circuit 2760 receives the digitized output 2438 of the ADC 2436 and processes the

signals in conjunctions with sensor data coupled through coils 2814 / 2816 to determine various tissue parameters including to measure tissue impedance, tissue temperature, tissue capacitance, tissue inductance, elapsed time, among other tissue parameters explained in the following description. In one aspect, tissue impedance Z and / or tissue capacitance may be calculated by the control circuit 2760 by calculating the ratio of the RF voltage V_{rf} to current I_{rf} measured by the voltage sensing circuit 2448 and the current sense circuit 2450 or by processing the data received from the sensors circuit 2790 independently.

[0338] In one form, the control circuit 2760 may be configured to generate a digital current signal 2420 and a digital frequency signal 2422. These signals 2420, 2422 are applied to a direct digital synthesizer (DDS) circuit 2424 to adjust the amplitude and the frequency (f) of the current output signal 2404 to the sensors 2788 disposed in the end effector 2752. The output of the DDS circuit 2424 is applied to an amplifier 2426 whose output may be applied to a transformer 2428. The output of the transformer 2428 is inductively coupled to a power module 2805 in the end effector 2752 through the coils 2802 / 2804. The power module 2805 may include rectifiers, filters, and other elements to apply power to the sensors 2788 and the sensors circuit 2790.

[0339] In one form, the RF voltage V_{rf} applied to the end effector 2752 electrodes and the RF current I_{rf} conducted through the tissue clamped by the end effector 2752 are suitable for vessel sealing and / or dissecting. Thus, the RF power output of the sensor monitoring and processing circuit 2400 can be selected for therapeutic functions such as sealing and dissecting and non-therapeutic functions such as measuring tissue impedance, capacitance, and other tissue parameters. It will be appreciated, that in the context of the present disclosure, ultrasonic and RF electrosurgical energies can be supplied to the end effector 2752 either individually or simultaneously for therapeutic or non-therapeutic functions.

[0340] In one aspect, inputs 2412 to the sensor monitoring and processing circuit 2400 may comprise any suitable input signals 2414 that can be applied to the control circuit 2760 to control the operation of the sensor monitoring and processing circuit 2400. In various forms, the inputs 2412 may be preprogrammed, uploaded, and / or entered via a user interface such as buttons, switches, thumbwheels, keyboard, keypad, touch screen monitor, pointing device, remote connection to a general purpose or dedicated computer. In other forms, the inputs 2412 may comprise a suitable user interface. Accordingly, by way of example, the inputs 2412 may be set or entered by a user to program the current (I), voltage (V), frequency (f), and/or period (T) for programming the function output of the sensor monitoring and processing circuit 2400. The control circuit 2760 may display the selected inputs 2412.

[0341] In one form, the various executable modules (e.g., algorithms 2410) comprising computer readable instructions can be executed by the control circuit 2760

portion of the sensor monitoring and processing circuit 2400. In various forms, the operations described with respect to the techniques may be implemented as one or more software components, e.g., programs, subroutines, logic; one or more hardware components, e.g., processors, DSPs, PLDs, ASICs, circuits, registers; and/or combinations of software and hardware. In one form, the executable instructions to perform the techniques may be stored in memory. When executed, the instructions cause the control circuit 2760 to determine tissue parameters as described herein. In accordance with such executable instructions, the control circuit 2760 monitors and evaluates voltage, current, and / or frequency signal samples available from the sensor monitoring and processing circuit 2400 and according to the evaluation of such signal samples determines tissue parameters. As further explained in the following description, a change in tissue parameters, state, or condition may be determined based on processing such signals.

[0342] FIG. 40 is a schematic illustration of a portion of the end effector 2752 comprising the anvil 2766 and cartridge 2768 to show arrays of sensors 2788a, 2788b disposed therein, in accordance with at least one aspect of the present disclosure. A first array of sensors 2788a may be disposed in the anvil 2766 longitudinally, along the I-beam slot 2822, and laterally, on either side of the I-beam slot 2822. A second array of sensors 2788b may be disposed in the cartridge 2768 longitudinally, along the knife slot 2824, and laterally, on either side of the knife slot 2824. In various other aspects, the sensors 2788 may be located in the anvil 2766, or in the cartridge 2768, or both the anvil 2766 and the cartridge 2768. Further, in some aspects the array of sensors 2788a disposed in the anvil 2766 may be arranged longitudinally, laterally, or both longitudinally and laterally as shown in FIG. 40. In other aspects the array of sensors 2788b disposed in the anvil 2766 may be arranged longitudinally, laterally, or both longitudinally and laterally as shown in FIG. 40. The sensors 2788 may be arranged in arrays comprising a single row or multiple rows or single sensors. Still further, the sensors 2788 in either array of sensors 2788a, 2788b may be individually addressed, powered, and read by the control circuit 2760. In other aspects, the array of sensors 2788a in the anvil 2766 may be addressed, powered, and read by the control circuit 2760 as a group separately from the array of sensors 2788b in the cartridge 2768. In other aspects, the array of sensors 2788b in the cartridge 2768 may be addressed, powered, and read by the control circuit 2760 as a group separately from the array of sensors 2788a in the anvil 2766. In other aspects, the array of sensors 2788a in the anvil 2766 and the array of sensors 2788b in the cartridge 2768 may be addressed, powered, and read by the control circuit 2760 as a group.

[0343] FIG. 41 is a partial cutaway view of the cartridge 2768 comprising a plurality of independently addressable sensors 2788 ($S_1 - S_n$), in accordance with at least one aspect of the present disclosure. To address and

read each one of the plurality of sensors 2788, individually labeled $S_1 - S_n$, the sensors circuit 2790 comprises a multiplexer 2840 and a logic circuit 2842 to control the selection and reading of the individual sensors 2788. The outputs of the sensor 2788 are routed to the inputs 2844 of the multiplexer 2840. Individual sensors $S_1 - S_n$ can be selected by the logic circuit 2842 by individually addressing a sensor through the multiplexer input select 2846 lines. The output 2848 of a selected sensor $S_1 - S_n$ is provided to the logic circuit 2842 and coupled to the control circuit 2760 through coils 2814, 2816, for example, for further processing to track properties of the tissue and execute algorithms for tracking to motion of the tissue across multiple sensors $S_1 - S_n$. As shown in FIG. 41, in one aspect, the sensors $S_1 - S_n$ are coupled to a common return path. A similar configuration may be provided in the anvil 2766 portion of the end effector 2752 (FIG. 40).

[0344] The positions of the sensors $S_1 - S_n$ are mapped to the cartridge 2768 such that the control circuit 2760 knows the location of each sensor $S_1 - S_n$ on the cartridge 2768. By monitoring the output of each sensor $S_1 - S_n$, the control circuit 2760 can determine if tissue is occupying the location of a sensor $S_1 - S_n$ based on the output of the monitored sensor $S_1 - S_n$. For example, if the monitored property of the tissue 2820 is impedance Z , the control circuit 2760 can map the location of the tissue 2820 based on impedance outputs read from each sensor $S_1 - S_n$, to infer the presence of tissue 2820 based on an impedance reading and infer the absence of tissue based on no impedance reading (e.g., open circuit).

[0345] The description now turns to various methods 2900, 2910, 2930, 2950 as illustrated in the accompanying FIGS. 42-45. Each of the methods 2900, 2910, 2930, 2950 may be implemented as algorithms 2410 stored in program memory of the sensor monitoring and processing circuit 2400 that may be executed by the control circuit 2760 as explained in connection with FIG. 39. In one aspect, the algorithms 2410 (e.g., methods 2900, 2910, 2930, 2950) may be stored as a series of machine executable instructions that the control circuit 2760 is programmed to execute. In other aspects, the algorithms 2410 (e.g., methods 2900, 2910, 2930, 2950) may be executed by the control circuit 2760 implemented in hardware where the control circuit 2760 is configured to execute the algorithms 2410.

[0346] With reference now to FIGS. 34-42, in one general aspect, FIG. 42 illustrates a flow diagram of a method 2900 of monitoring multiple sensors 2788 located in the jaws of end effector 2752 over time to detect characteristics of tissue 2820 grasped in the jaws of the end effector 2752, in accordance with at least one aspect of the present disclosure. In one aspect one aspect, the surgical instrument 2750 comprises an end effector 2752 comprising a pair of jaws for grasping tissue 2820 therebetween. In one aspect the end effector 2752 comprises an anvil 2766 and cartridge 2768. A plurality of sensors 2788 may be located on the cartridge 2768 to sense the motion of tissue 2820 grasped between the anvil 2766

and the cartridge 2768 from one sensor S_1 towards an adjacent sensor S_2 , for example. As explained supra, the control circuit 2760 may be configured to execute the method 2900, implemented as an algorithm 2410 in the sensor monitoring and processing circuit 2400.

[0347] In one aspect, the control circuit 2760 is configured to independently select any one or more of the sensors $S_1 - S_n$ disposed in the end effector 2752. The one or more sensors $S_1 - S_n$ are configured to sense 2902 a property of tissue 2820 disposed in the end effector 2752 of the surgical instrument 2750. The control circuit 2760 is configured to monitor 2904 the sensed property of the tissue 2820 disposed in the end effector 2752 of the surgical instrument 2750 over time. In a stapling cartridge, multiple sensors 2788 are disposed on the stapling cartridge 2768 and can be independently monitored to sense movement of the tissue 2820 relative to each sensor 2788 as described in FIG. 41. In one aspect, the control circuit 2760 sends a command to the logic circuit 2842 to select an individual sensor $S_1 - S_n$ through the multiplexer 2840. Each sensor $S_1 - S_n$ be sequentially addressed and monitored in a continuous loop. By monitoring 2904 the output 2848 of each of the selected sensor $S_1 - S_n$, the control circuit 2760 may be configured to sense 2906 movement of the tissue 2820 from one sensor S_1 relative to an adjacent sensor S_2 based on the monitored property of the tissue 2820. In one aspect, the tissue property monitored by the control circuit 2760 can be an electrical property of the tissue 2820 such as impedance Z or capacitance C . In another aspect, monitoring the impedance Z or capacitance C of the tissue 2820 from one time point to the next can allow the control circuit 2760 to detect the motion of the tissue 2820 from one sensor towards the next. The control circuit 2760 may be configured to select 2908 a function of the surgical instrument 2750 based on the sensed movement of the tissue 2820. The control circuit 2760 can detect the position on the tissue 2820 based on the monitored property of the tissue 2820. In various other aspects, the monitored 2902 property may be rate of change of closure load during closure of the end effector 2752 on the tissue 2820, rate of change of closure load after closure of the end effector 2752 on the tissue 2820 is complete, force applied to the tissue 2820, impedance Z spectrography, light transmissivity, light refractivity, or Doppler effects to determine tissue characteristics, among other properties that may be monitored by the sensors $S_1 - S_n$.

[0348] With reference now to FIGS. 34-41 and 43, in one general aspect, FIG. 43 illustrates a flow diagram of a method 2910 of monitoring multiple sensors 2788 located in the jaws of the end effector 2752 over time to detect characteristics or properties of tissue 2820 grasped in the jaws of the end effector 2752, in accordance with at least one aspect of the present disclosure. In one aspect, the method 2910 comprises monitoring multiple sensors $S_1 - S_n$ over time to detect motion characteristics of the tissue 2820, to detect tissue 2820 move-

ment relative to at least two sensed locations, and to provide real-time tissue flow sensing by monitoring one or more than one sensed tissue property over a period of time. As explained supra, the control circuit 2760 may be configured to execute the method 2910 implemented as an algorithm 2410 in the sensor monitoring and processing circuit 2400.

[0349] In one aspect, the control circuit 2760 is configured to independently sense tissue 2820 properties by monitoring multiple longitudinally and laterally disposed sensor S_1 - S_n locations in the end effector 2752. The control circuit 2760 may be configured to employ sensing techniques with a localized predetermined return path to sense changes in a property of the both laterally and longitudinally. In various aspects, the tissue property may be impedance Z , impedance Z spectrography, capacitance C , force exerted on the end effector 2752, force applied to the tissue 2820, light transmissivity, light refractivity, or Doppler effects to determine tissue characteristics, among other tissue properties that may be monitored by the sensors S_1 - S_n .

[0350] light reflectivity, light refraction, among others. Using these sensing techniques, the control circuit 2760 can detect specific a mid-thickness measure of the tissue 2820 located between at least two interconnected sensor combinations in the array of sensors 2788, for example S_1 - S_2 or S_1 - S_4 , using well-known triangulation algorithm techniques.

[0351] More specifically, according to one aspect of the method 2910, the control circuit 2760 may be configured to monitor 2912 an array of longitudinal and lateral sensors S_1 - S_n independently and measure a property of the tissue 2820. For example, the control circuit 2760 may monitor the impedance Z , capacitance C , force exerted on the end effector 2752, light reflection, light refraction etc., of the tissue 2820 to determine if an individual or group of sensors S_1 - S_2 is in contact with tissue 2820. The control circuit 2760 may be configured to determine 2914 any changes in the monitored property of the tissue 2820 both laterally and longitudinally and these changes may be tracked over a period of time occurring during closure, after closure is complete, during firing, or after firing is complete. The control circuit 2760 may be configured to triangulate 2916 at least two interconnected sensor combinations, for example S_1 - S_2 or S_1 - S_4 , using well-known triangulation algorithm techniques to detect 2918 the mid-thickness measure of tissue 2820 located between two S_1 - S_2 or S_1 - S_4 , for example, and select 2920 a function of the surgical instrument 2750 based on the detected mid-thickness of the tissue 2820.

[0352] There are a variety of well-known triangulation algorithms that may be employed by the control circuit 2760 to detect mid-thickness of the tissue 2820. These algorithms include the Delaunay Triangulation Algorithm, "A New Voronoi-Based Surface Reconstruction Algorithm" (Amenta et al., SIGGRAPH 1998), and "Poisson Surface Reconstruction" (Kazhdan et al, Symposium on Geometry Processing 2006), for example, each of which

is herein incorporated by reference.

[0353] The Delaunay Triangulation Algorithm is able to generate edges between vertices based on spatial geometric relationship among vertices from a set of vertices, thereby constructing a set of triangular faces and thus constructing a target mesh model. The vertices may be determined by sensors S_1 - S_n locations that sense the presence of tissue 2820. Specifically, the Delaunay Triangulation Algorithm speculatively may calculate out the vertices between which there should be a connecting line by attempting to maximize the value of the least of the three interior angles of each triangular face. In most cases, the Delaunay Triangulation Algorithm would avoid generating a triangle that is too narrow and long in shape (e.g., a triangle of which at least one of the interior angles is less than 10 degrees). From experimental results disclosed in a number of literatures it may be known that, in the case of a large number of vertices, the Delaunay Triangulation Algorithm can make a relatively accurate guess on the edges among vertices.

[0354] With reference to FIGS. 34-41 and 44, in one general aspect, FIG. 44 illustrates a method 2930 of monitoring an array of sensors S_1 - S_n distributed laterally and longitudinally along the length of the end effector 2752 jaws (e.g., cartridge 2768 and anvil 2766) to determine the location of heterogeneous tissue impedance regions of tissue 2820 grasped in the jaws of the end effector 2752, in accordance with at least one aspect of the present disclosure. As explained supra, the control circuit 2760 may be configured to execute the method 2930 implemented as an algorithm 2410 in the sensor monitoring and processing circuit 2400.

[0355] In one aspect, the control circuit 2760 is configured to monitor 2932 the jaws of the end effector 2752 closing on tissue 2820 (e.g., the anvil 2766 pivotally rotating toward the cartridge 2768 to grasp tissue therebetween). The control circuit 2760 may be configured to monitor 2934 each sensor S_1 - S_n located on the anvil 2766 and / or cartridge 2768 of the jaw for a tissue property during the jaw closing period. In various aspects, the tissue property may be impedance Z , impedance Z spectrography, capacitance C , force exerted on the end effector 2752, force applied to the tissue 2820, light transmissivity, light refractivity, or Doppler effects to determine tissue characteristics, among other tissue properties that may be monitored by the sensors S_1 - S_n . The control circuit 2760 can track and record the sensed tissue property for each sensor S_1 - S_n during the jaw closure period. This time history of the sensed tissue property during the jaw closure period can be used by the control circuit 2760 to determine 2936, e.g., by inference, if present, heterogeneous regions of the monitored tissue property - where the heterogeneous define distinct changes or anomalies that mark a particular baseline location. The control circuit 2760 may be configured to track 2938 these baseline location(s) as the firing of the knife / I-beam 2764 is initiated. Once firing of the knife / I-beam 2764 is initiated, the control circuit 2760

is configured to track 2940 the position histories of these baseline locations and use them for feedback control of the firing process. The control circuit 2760 is configured to modify 2942 functions of the surgical instrument 2750 to alter tissue flow during the knife / I-beam 2764 firing process. Device functions that can be modified to alter tissue flow during the firing process includes changing the firing speed, pausing (complete stops) the firing process, closure force among, others.

[0356] With reference to FIGS. 34-41 and 45, in one general aspect, FIG. 45 illustrates a method 2950 of monitoring an array of sensors S_1 - S_n distributed laterally and longitudinally in the end effector 2752 (e.g., cartridge 2768 and anvil 2766) to predict tissue 2820 flow in the jaws of the end effector 2752, in accordance with at least one aspect of the present disclosure. As explained supra, the control circuit 2760 may be configured to execute the method 2950 implemented as an algorithm 2410 in the sensor monitoring and processing circuit 2400.

[0357] In order to predict the amount of tissue 2820 flow in the jaws of the end effector 2752, according to the method 2950, the control circuit 2760 may be configured to monitor 2952 an array of longitudinal and lateral sensors S_1 - S_n independently and measure a property of the tissue 2820. In various aspects, the tissue property may be impedance Z , impedance Z spectrography, capacitance C , force exerted on the end effector 2752, force applied to the tissue 2820, light transmissivity, light refractivity, or Doppler effects to determine tissue characteristics, among other tissue properties that may be monitored by the sensors S_1 - S_n . During the monitoring 2952 phase, the control circuit 2760 may be configured to determine 2954 changes in the monitored property of the tissue 2820 both longitudinally and laterally and based on the determined 2954 changes, the control circuit 2760 may be configured to sense 2956 tissue flow during the jaw closure time period. Once the tissue flow is sensed 2956, the control circuit 2760 may be configured to determine 2958 at least one device parameter after jaw closure is complete. The at least one device parameter may include device sensed parameters such as, for example, rate of change of closure load during closure, rate of change of closure load after closure is complete, etc.. The control circuit 2760 may be configured to determine 2960 tissue type or tissue condition based on the tissue flow during jaw closure in combination with the at least one device parameter determined 2958 after the jaw closure is complete. The control circuit 2760 may be further configured to modify 2962 functions of the surgical instrument based on the tissue type.

[0358] In one aspect, sensing 2956 tissue flow can be based on knowledge of tissue type from situational awareness and / or other device sensed measures (e.g., rate of change of closure load during closure, rate of change of closure load after closure is complete, etc.). Tissue type or tissue condition may be determined tissue type by combining tissue flow during jaw closure with force feedback of closure system. Tissue flow may be

further refined by determining tissue impedance. The process may be employed to detect rigid or foreign objects within the jaws of the end effector 2752.

[0359] In another aspect, the control circuit 2760 may be configured to monitor and record the magnitude of tissue impedance Z while measuring tissue flow during jaw closure. A jaw closure algorithm can be used to sense tissue movements during closure as an indicator of the potential effect of each change during firing of the knife / I-beam 2764. For example, at a first closure rate, the magnitude / direction of tissue flow may be estimated, then the closure rate may be adjusted and the changes in tissue flow are tracked and recorded in memory by the control circuit 2760. In one aspect, the control circuit 2760 may be configured to predict post-fire tissue position by utilizing closure tissue flow and closure force feedback prior to firing - to provide feedback to surgeon allowing opportunity to reposition to ensure tissue is fully captured in the cut line 2824 of the end effector 2752.

[0360] In various other aspects, the control circuit 2760 of the sensor monitoring and processing circuit 2400 may be configured or programmed to execute algorithms 2410 to monitor and interrogate tissue based on a variety of sensor configurations in the end effector 2752.

[0361] In one aspect, the control circuit 2760 may be configured or programmed to monitor tissue impedance Z over time and tracking the tissue impedance Z across a single electrode or segmented electrodes of the sensor array S_1 - S_n configured along the length of the cartridge 2768.

[0362] In other aspects, the control circuit 2760 may be configured or programmed to monitor tissue impedance Z spectrography. This may be accomplished by utilizing sweeps of different frequencies and monitoring the tissue impedance Z to the power and frequency to determine the composition of the tissue 2820.

[0363] In other aspects, the control circuit 2760 may be configured or programmed to monitor tissue capacitance C . Tissue characteristics and gap relationship of the jaws may be utilized to determine the amount of tissue 2820 present in the jaws of the end effector 2752.

[0364] In other aspects, the jaws of the end effector 2752 may include optical sensors disposed longitudinally and laterally in the anvil 2766 and / or cartridge 2768. The control circuit 2760 may be configured to monitor light transmissivity, refractivity, or Doppler effects to determine tissue characteristics. The method may include analyzing local light refractivity to determine the surface conditions of the tissue 2820 to monitor irregularities within the tissue captured between the jaws. The method further may include analyzing a Doppler effect frequency of the light to monitor for local moving particles of tissue in the jaws of the end effector 2752.

[0365] In one general aspect, the present disclosure provides a sensor and electronic circuit capable of monitoring at least two internal cartridge component locations to determine status or operation of the cartridge. The disclosure also provides sensors and electronic circuit for

monitoring the internal function or motion of components within the cartridge to determine the status, operation, or current stroke location of the couple firing actuator. In one aspect, the sensors and electronic circuit provides information to the user derived from the sensed parameters. In another aspect, the electronic circuit can alter the functional status of the device (e.g., safety lock-out) based on the sensed status.

[0366] In various aspects, the cartridge sensors and electronic circuit are configured to monitor the operation of the cartridge elements comprises sensors and electronic circuit for detecting staple drivers and the deployment of staples to monitor the status and operation of staple deployment. In another aspect, the cartridge sensors and electronic circuit are configured to monitor and interrogate tissue captured in the jaws of the end effector. Finally, in another aspect, the cartridge sensors and electronic circuit are configured to employ a combination of data aggregation that can be employed to create redundant measures of safety. These aspects are explained in more detail in the following description accompanying the drawings.

[0367] An exploded view of an end effector 4000 of a surgical stapling system is illustrated in FIG. 46. The end effector 4000 comprises a frame 4002, a cartridge jaw 4004, and an anvil 4006. The cartridge jaw 4004 extends fixedly from the frame 4002. The anvil 4006 is movable between an open, or unclamped, position and a closed, or clamped, position relative to the cartridge jaw 4004. In alternative aspects, the cartridge jaw 4004 is movable between an open, or unclamped, position and a closed, or clamped, position relative to the anvil 4006. In at least one such embodiment, the anvil 4006 extends fixedly from the frame 4002.

[0368] The cartridge jaw 4004 includes a channel or carrier 4022 configured to receive a staple cartridge, such as a staple cartridge 4008, for example. Referring to FIG. 58, the staple cartridge 4008 comprises a cartridge body 4010. The cartridge body 4010 comprises a deck 4012 configured to support the tissue of a patient, a longitudinal slot 4014, and six longitudinal rows of staple cavities 4016 defined therein. Each staple cavity 4016 is configured to receive and removably store a staple therein. The staple cartridge 4008 further comprises staple drivers 4028 configured to drive the staples out of the staple cavities 4016. Other staple cartridges with various other arrangements of staple cavities, decks, and/or staples are envisioned for use with the end effector 4000.

[0369] Further to the above, the staple cartridge 4008 further comprises a sled 4018 configured to engage the staple drivers 4028. More specifically, the sled 4018 comprises ramps 4020 configured to engage cams defined on the staple drivers 4028 and lift the staple drivers 4028 and the staples within the staple cavities 4016 as the sled 4018 is moved distally through the staple cartridge 4008. A firing member is configured to motivate the sled 4018 distally from a proximal, unfired, or starting position toward a distal, fired, or end position during a

staple firing stroke.

[0370] The staples are supported by the staple drivers 4028 in the cartridge body 4010. The staple drivers 4028 are movable between a first, or unfired position, and a second, or fired, position to eject the staples from the staple cavities 4016. The staple drivers 4028 are retained in the cartridge body 4010 by a pan or retainer 4030 which extends around the bottom of the cartridge body 4010 and includes resilient members 4031 configured to grip the cartridge body 4010 and hold the retainer 4030 to the cartridge body 4010. The staple drivers 4028 are movable between their unfired positions and their fired positions by the sled 4018. The sled 4018 is movable between a proximal position and a distal position. The sled 4018 comprises a plurality of ramped surfaces 4020 configured to slide under the staple drivers 4028 and lift the staple drivers 4028, and the staples supported thereon, toward the anvil 4006.

[0371] In various examples, the staple cartridge 4008 includes one or more retaining members that are configured to ensure a tight attachment between an unfired staple cartridge 4008 and a cartridge channel or carrier 4022. The retaining members can be moved, or otherwise modified, during the firing of the staple cartridge 4008 to yield a reduced attachment between the fired staple cartridge 4008 and the cartridge channel or carrier 4022. The reduced attachment permits a user to easily remove the fired staple cartridge 4008 from the cartridge channel or carrier 4022.

[0372] In the example illustrated in FIG. 46, the staple cartridge 4008 is removably seated in the cartridge channel or carrier 4022. The staple cartridge 4008 includes two retaining members 4037 on opposite sides of the staple cartridge 4008. The retaining members 4037 are configured to maintain, or to help maintain, a tight attachment between the staple cartridge 4008 and the cartridge channel or carrier 4022. The retaining members 4037 may extend from a base 4019 of the retainer 4030. In various examples, the retaining members 4037 are spaced apart from walls 4039 of the retainer 4030 to permit the retaining members 4037 to flex relative to the walls 4039.

[0373] Each retaining member 4037 is in the form of a resilient member movable between a biased configuration in an unfired staple cartridge 4008, and an unbiased, or less biased, configuration in a fired staple cartridge 4008. In the unfired staple cartridge 4008, the retaining member 4037 is biased into an engagement with the cartridge channel or carrier 4022 to maintain, or to help maintain, a pre-firing cartridge removal load. A load greater than or equal to the pre-firing cartridge removal load is needed to separate an unfired staple cartridge 4008 from the cartridge channel or carrier 4022.

[0374] Each retaining member 4037 includes a first curved portion 4044 that defines a first retention feature or detent receivable in a depression or groove defined in a side wall 4009 of the cartridge channel or carrier 4022. The first curved portion 4044 is retained in groove while

the retaining member 4037 is in the biased configuration. Each retaining member 4037 further includes a second curved portion 4047 that defines a second retention feature detent configured to rest against at least one staple driver 4028 while the retaining member 4037 is in the biased configuration. In various examples, each retaining member 4037 defines a plane transecting the base 4019, wherein the first curved portion 4044 defines a first detent on the first side of the plane, and wherein the second curved portion 4047 defines a second detent on the second side of the plane.

[0375] In one aspect, the pan or retainer 4030 comprises a first plurality of sensors 4050 arranged in a first array disposed longitudinally on both sides of a longitudinal slot 4054 formed in the base 4019 of the retainer 4030. A second plurality of sensors 4052 arranged in a second array are disposed on one side of the longitudinal slot 4054. It will be appreciated, however, that the second sensor array 4052 also may be disposed on both sides of the longitudinal slot 4054. In one general aspect, the first sensor array 4050 are configured to detection motion of the movable staple drivers 4028 and more particularly, the first sensor array 4050 are configured to sense the advancement state of the staple drivers 4028 to drive the staples out of the staple cavities 4016. In one aspect, the second sensor array 4052 are configured to sense the motion of the sled 4018 as it moves along the longitudinal slot 4054 and actuates the staple drivers 4028.

[0376] In one aspect, the sled 4018 and / or the staple drivers 4028 may be formed out of ferromagnetic material or embedded with ferromagnetic particles. The first and second sensor arrays 4050, 4052 may be positioned in the pan or retainer 4030 of the cartridge base 4019. The movement of the sled 4018 and / or the staple drivers 4028 induces a current (signal) in the first and / or second sensor arrays 4050, 4052 below the staple driver 4028 to produce a signal detectable by the electronic circuit 4074, described in FIG. 47. This configuration of the sled 4018 and staple drivers 4028 and the first and second sensor arrays 4050, 4052 enable the electronic circuit 4074 to determine the position and speed of the staple driver 4028 and / or the position and speed of the sled 4018.

[0377] Referring to FIGS. 46 and 47, the staple cartridge 4008 includes a cartridge circuit 4044. The cartridge circuit 4024 includes a storage medium 4026, a cartridge connector-region 4017 comprising a plurality of external electrical contacts 4028, and a cartridge-status circuit portion 4032 that includes a trace element 4034. The storage medium 4026 can be a memory that stores information about the staple cartridge 4008 such as, for example, various characteristics of the staple cartridge 4008 including a firing status, staple-type, staple-size, cartridge batch number, and/or cartridge color.

[0378] FIG. 47 is a schematic illustration of the first and second sensor arrays 4050, 4052 positioned in the pan or retainer 4030 of the cartridge base 4019, the first and second sensor arrays 4050, 4052 shown coupled to an electronic circuit 4074, in accordance with at least one

aspect of the present disclosure. As shown, the first sensor array 4050 is longitudinally disposed on both sides of the slot 4054 defined in the pan or retainer 4030. The second sensor array 4052 is disposed longitudinally along one side of the slot 4054, although in other aspects the second sensor array 4052 may be disposed on both sides of the slot 4054 similar to the first sensor array 4050.

[0379] With reference now to FIGS. 46 and 47, in one aspect, the first sensor array 4050 comprises a plurality of elements configured to detect the movement of the staple drivers 4028 as they move between their unfired positions and their fired positions by the sled 4018. As discussed supra, the staple drivers 4028 may be made of a ferromagnetic material or may be embedded with a ferromagnetic material that is detected by the elements in the first sensor array 4050. In one aspect, the movement of the staple driver 4028 induces a current (signal) in the first array sensor 4050 located below the staple driver 4028. Thus, the first sensor array 4050 can detect the position and speed of the staple driver 4028. In one aspect, the first sensor array 4050 may comprise a plurality of Hall cells constructed from a semiconductor strip. In other aspects, the first sensor array 4050 may comprise a plurality of Hall sensor elements. In other aspects, the first sensor array 4050 may comprises other sensor elements configured to detect magnetic fields generated by moving ferromagnetic elements in the cartridge 4008.

[0380] Still with reference to FIGS. 46 and 47, in one aspect, the second sensor array 4052 comprises a plurality of elements configured to detect the movement of the sled 4018 or the tissue cutting knife and it moved along the slot 4014 of the staple cartridge 4008. As discussed supra, the sled 4018 or the tissue cutting knife may be made of a ferromagnetic material or may be embedded with a ferromagnetic material that is detected by the elements in the second sensor array 4052. In one aspect, the movement of the sled 4018 or cutting knife induces a current (signal) in the second array sensor 4052 as it travels along the slot 4054. Thus, the second sensor array 4052 can detect the position and speed of the sled 4018 or cutting knife. In one aspect, the sensor array 4052 may comprise a plurality of Hall cells constructed from a semiconductor strip. In other aspects, the second sensor array 4052 may comprise a plurality of Hall sensor elements. In other aspects, the second sensor array 4052 may comprises other sensor elements configured to detect magnetic fields generated by moving ferromagnetic elements in the cartridge 4008.

[0381] Still with reference to FIGS. 46 and 47, the first sensor array 4050 is coupled to a control circuit 4062 for processing the signals 4058 generated by the motion of the staple drivers 4028. The signals 4058 generated by the first sensor array 4050 may comprise voltage, current, resistance, impedance, capacitance, inductance, frequency, phase, etc. The individual sensor elements of the first sensor array 4050 are selected by a multiplexer

4056 by the control circuit 4062 and are selected by a logic / analog-to-digital converter (ADC) circuit 4060 via select line 4066. The output signal 4058 of the selected sensor element is routed to the output 4068 of the multiplexer 4056 to an ADC portion of the logic / ADC circuit 4060. The digital output value of the output signal 4058 of the selected sensor element in the first sensor array 4050 is read by the control circuit 4062 through data lines 4064. The value may be stored in the memory 4066 coupled to the control circuit 4062.

[0382] The second sensor array 4052 is coupled to the control circuit 4062 for processing the signals 4070 generated by the motion of the sled 4018 or tissue cutting knife. The signals 4070 generated by the second sensor array 4052 may comprise voltage, current, resistance, impedance, capacitance, inductance, frequency, phase, etc. The individual sensor elements of the second sensor array 4052 are selected by the multiplexer 4056 by the control circuit 4062 and are selected by the logic / ADC circuit 4060 via select line 4066. The output signal 4070 of the selected sensor element is routed to the output 4068 of the multiplexer 4056 to an ADC portion of the logic / ADC circuit 4060. The digital output value of the output signal 4070 of the selected sensor element in the second sensor array 4052 is read by the control circuit 4062 through data lines 4064. The value may be stored in the memory 4066 coupled to the control circuit 4062.

[0383] In various aspects, the control circuit 4062 may comprise one or more microcontrollers, microprocessors, or other suitable processors for executing instructions that cause the processor or processors to process the signals received from the first and second sensor arrays 4050, 4052. In other aspects, the control circuit 4062 may comprise analog or digital circuits such as programmable logic devices (PLD), field programmable gate arrays (FPGA), discrete logic, or other hardware circuits, software, and / or firmware, or other machine executable instructions to perform the functions explained in the following description. The control circuit 4062 is coupled to a memory 4066 for storing data and / or machine executable instructions. In various aspects, the control circuit 4062 and the memory 4066 may be located in the cartridge 4008. In other aspects, the control circuit 4062 and the memory 4066 may be located off the cartridge 4008 and coupled to the other components of the electronic circuit 4074 via wired or wireless communication techniques. In other aspects, the memory 4066 may be located in the cartridge 4008 and the control circuit 4062 may be located off the cartridge 4008 and coupled to the electronic circuit 4074 via wired or wireless connection techniques.

[0384] Still with reference to FIGS. 46 and 47, for configurations where the tissue cutting knife is housed within the cartridge 4008 instead of being integrated to the I-Beam, the knife can serve as the ferromagnetic material. Same principle can be applied to the staple pan or retainer 4030, the I-beam, and anvil 4006. In some aspects, the staples may be made of Titanium or Titanium

alloys. However, if staples are made of a ferromagnetic material, the same principle could also be applied to the staples.

[0385] If the motions of measured components such as staple drivers 4028 and the sled 4018, for example, deviates from what is desired improper device status, poor staple formation, etc. can occur which can lead to complications such as bleeding, leaks, etc. Accordingly, the control circuit 4062 may be programmed or configured to detect the deviation from the proper operation based on the readings obtained from the first and second sensor arrays 4050, 4052 and intervene in the function of the device before the next step in the operation has begun to improve the operation of the device. For example, if a staple driver 4028 does not move the intended distance, staple formation can be compromised. If the sled 4018 does not move the intended distance, the staple line may not be complete. Accordingly, the control circuit 4062 may process the measured signals 4058, 4070 obtained from the first and second sensor arrays 4050, 4052 to authenticate the cartridge 4008 and to ensure it is not a (sub-optimal) copy. In addition, the control circuit 4062 may process the measured signals 4058, 4070 obtained from the first and second sensor arrays 4050, 4052 to determine device status including whether the cartridge 4008 was properly loaded, the staple pan or retainer 4030 has been removed, cartridge 4008 was already fired, etc. Additional circuits explained below in reference to FIGS. 48 and 49 can be employed by the control circuit 4062 to determine if a bad staple formation may occur such as when a staple leg does not contact a staple pocket, which likely increases the potential for leaks in that area. Other conditions that can be monitored by the control circuit 4062 include, for example, determining whether the anvil 4006 is fully closed prior to firing the sled 4018 and tissue cutting knife, for example.

[0386] Turning now primarily to FIGS. 48 and 49 and with reference back to FIGS. 46 and 47, the anvil 4006 comprises staple-forming pockets 4310 including an electrically conductive circuit element 4314, in accordance with one or more aspects of the present disclosure. FIG. 49 illustrates a perspective view of the staple-forming pocket 4310 of FIG. 48 after the electrically conductive circuit element 4314 has been severed by a staple leg during proper formation of the staple leg, in accordance with one or more aspects of the present disclosure.

[0387] As illustrated in FIG. 48, a staple-forming pocket 4310 comprises a concave surface 4324 that intersects the tissue-contacting surface 4308 at outer edges 4326. The electrically conductive circuit element 4314 can be positioned onto the concave surface 4324 in the path of a properly forming staple. Sidewalls 4328 along with the concave surface 4324 define a forming track 3325 for a staple leg. The concave surface 4324 includes a first contact portion 4330, a deep portion 4332, and an end portion 4334. The first contact portion 4330 is configured to make first contact with the tip of the staple leg as the

staple leg enters the staple-forming pocket 4310. The staple leg is then curled as it follows the forming track 4325 passing along the deep portion 4332 and the end portion 4334 of the concave surface 4324. The end portion 4334 guides the staple leg toward the base of the staple.

[0388] As illustrated in FIG. 48, the electrically conductive circuit element 4314 can be positioned across the forming track 4325. Since successful contact with the first contact portion 4330 increases the likelihood of proper formation of a staple leg, placing the electrically conductive circuit element 4314 onto the forming track 4325 at a position beyond the first contact portion 4330 improves the accuracy of detecting proper or improper staple formation.

[0389] In at least one example, the electrically conductive circuit element 4314 is placed on the forming track 4325 between the first contact portion 4330 and the deep portion 4332. In at least one example, the electrically conductive circuit element 4314 is placed on the forming track 4325 between the deep portion 4332 and the end portion 4334. In at least one example, the electrically conductive circuit element 4314 is placed on the forming track 4325 within the deep portion 4332. In at least one example, the electrically conductive circuit element 4314 is placed on the forming track 4325 at the center, or substantially at the center, of the deep portion 4332. In at least one example, the electrically conductive circuit element 4314 is placed on the forming track 4325 at the deepest section of the forming track 4325. In at least one example, the electrically conductive circuit element 4314 is positioned onto the concave surface 4324 closer to the first contact portion 4330 than end portion 4334. In at least one example, the electrically conductive circuit element 4314 is positioned onto the concave surface 4324 closer the end portion 4334 than the first contact portion 4330.

[0390] In certain instances, an electrical circuit can be positioned in the path of a properly forming staple and may be coupled to the electronic circuit 4074 (FIG. 47). The electronic circuit 4074 is configured to detect the continuity of the electrically conductive circuit element 4314 to determine if a staple was properly formed in the staple-forming pocket 4310. In such instances, an interruption in the electrical circuit can be construed by the electronic circuit 4074 as an indication that a staple was properly formed while persistence in the electrical continuity of the electronic circuit can be construed by the electronic circuit 4074 as an indication that a staple was improperly formed. In other instances, an electrical circuit can be positioned in a likely path of an improperly forming staple. In such other instances, an interruption in the electrical continuity of the electrical circuit can be construed as an indication that a staple was improperly formed while persistence in the electrical continuity of the electrical circuit can be construed by the electronic circuit 4074 as an indication that the staple was properly formed.

[0391] Referring to FIG. 48, an electrical circuit can include one or more electrically conductive circuit elements 4314 that cause an interruption in the electrical circuit when severed by a staple leg as the staple leg is formed. An electrically conductive circuit element 4314 of an electrical circuit can be positioned in the path of a properly forming staple leg. A severance of the electrically conductive circuit element 4314, as illustrated in FIG. 49, can be construed as an indication that the staple was properly formed. In other instances, an electrically conductive circuit element 4314 of an electrical circuit can be positioned in a likely path of an improperly forming staple. In such instances, a severance of the electrically conductive circuit element 4314 can be construed by the electronic circuit 4074 as an indication that a staple was improperly formed.

[0392] With reference to FIGS. 46-49, in one aspect the control circuit 4062 may be programmed or configured to monitor and interrogate tissue. In one aspect, the control circuit 4062 may be programmed or configured to monitor magnetic fields by reading the output signals 4058, 4070 of the first and second sensor arrays 4050, 4052 located in the pan or retainer 4030 portion of the staple cartridge 4008 in the end effector 4000. The first and second sensor arrays 4050, 4052 may be disposed in the pan or retainer 4030 portion to monitor magnetic structures located within the boundaries of the cartridge 4008 or to monitor or aero magnetic fields outside the cartridge 4008. The control circuit 4062 may be further programmed or configured to detect the staple legs contacting the staple-forming pocket 4310 as explained in FIGS. 48 and 49 as associated description. The control circuit 4062 may consider the detection of the staple legs contacting the staple-forming pocket 4310 in combination with the signals 4058, 4070 received from the first and second sensor arrays 4050, 4052 to determine the status of the cartridge 4008 such as, for example, determining whether the cartridge 4008 was properly loaded, the staple pan or retainer 4030 has been removed, cartridge 4008 was already fired, staples are properly formed, location and speed of the staple drivers 4028, and / or location and speed of the sled 4018, among others. Additional techniques for detecting staple formation are described in U.S. Patent No. 10,456,137 titled STAPLE FORMATION DETECTION MECHANISMS, which is herein incorporated by reference in its entirety.

[0393] FIG. 50 illustrates a distal sensor plug 4816 comprising an electronic circuit 4074 configured to monitor and process signals 4058, 4070 from the first and second sensor arrays 4050, 4052, in accordance with at least one aspect of the present disclosure. The distal sensor plug 4816 comprises a memory sensor 4810 and an electronic circuit 4074. The distal sensor plug 4816 further comprises a flex board 4814. The sensor 4810 and the electronic circuit 4074 are operatively coupled to the flex board 4814 such that they are capable of communicating. Additional smart cartridge techniques are described in U.S. Patent No. 9,993,248 titled SMART

SENSORS WITH LOCAL SIGNAL PROCESSING, which is herein incorporated by reference in its entirety.

[0394] With reference to FIGS. 46-50, in one aspect, the cartridge 4008 feature sensing of the staple drivers 4028, sled 4018, and other elements, employed to monitor the operation of the cartridge 4008 may be used in combination with other data aggregations to create redundant measures of safety. Accordingly, a combination or hybrid of data transferred to the cartridge 4008 and data sensed locally on the cartridge 4008 may be processed by the control circuit 4062 for safety context resolution.

[0395] In one aspect, the combination of aggregated data may be obtained by the control circuit 4062 from mechanically derived data sources and instrument lockout data sources. The combination of data may be processed by the control circuit 4062 to determine authenticity, safety, and data value of the cartridge 4008 or other end effector 4000 components. For example, the mechanical lockout acts as a safety system for force detection. In one aspect, as explained herein, a force feature may be provided in the cartridge 4008 to identify the presence of an unfired reload and some level of identification of the type of cartridge 4008 loaded in the end effector 4000. The mechanical lockout exists in conjunction to ensure that failure of digital detection still allows safe operation of the device. This could be as part of the same system or as a separate system, for example.

[0396] In another aspect, the combination of aggregated data may be obtained by the control circuit 4062 from multiple radio frequency identification (RFID) tags or 1-wire memories located on different data channels. This combination of data may be processed by the control circuit 4062 to determine authenticity, safety, and data value of the cartridge 4008 or other end effector 4000 components. The authenticity of the cartridge 4008 may be determined by a combination of multiple RFID or 1-wire memory sources for security. Safety may be accomplished by employing multiple data channels in the cartridge 4008 to ensure redundancy in the system. In one aspect, the reading should not be established unless all system faults / challenges are successfully mitigated.

[0397] In yet another aspect, the combination of aggregated data may be obtained by the control circuit 4062 from at least one RFID tag or 1-wire memory in combination with mechanical lockout data. This combination of data may be processed by the control circuit 4062 to determine authenticity, safety, and data value of the cartridge 4008 or other end effector 4000 components. Authenticity may be determined by encryption of the memory device and embedding force features in the cartridge 4008 mechanical lockout as explained supra. Further, the mechanical lockout acts as a safety system for the memory device.

[0398] In yet another aspect, the combination of aggregated data may be obtained by the control circuit 4062 from at least one RFID tag or 1-wire memory in combination with force detection data. This combination of data

may be processed by the control circuit 4062 to determine authenticity, safety, and data value of the cartridge 4008 or other end effector 4000 components. Authenticity may be determined by encryption of the memory device and the presence of a force detection feature. Safety may be accomplished by a force detection confirmation of proper system function. Needs to only function if all system faults / challenges are successfully mitigated.

[0399] In yet another aspect, the combination of aggregated data may be obtained by the control circuit 4062 from multiple RFID tags in combination with mechanical lockout data. This combination of data may be processed by the control circuit 4062 to determine authenticity, safety, and data value of the cartridge 4008 or other end effector 4000 components. Authenticity may be determined by employing multiple memory sources for security device and the presence of a mechanical lockout. The mechanical lockout acts as a safety system for the memory device.

[0400] In yet another aspect, the combination of aggregated data may be obtained by the control circuit 4062 from a memory source and force detection data where memory access is restricted. The memory source data is used to unlock the memory source and force detection. A tuning circuit may be employed to unlock memory access a force detection data. The force detection data may be employed as an input value to authenticate memory reads.

[0401] Each of the above described processing of aggregated data may be based on a hardware based programmable logic risk mitigation strategy comprising digital logic including, for example, FPGAs and ASICs (application specific integrated circuits).

[0402] FIG. 51 is a method 4100 of monitoring internal systems of a staple cartridge 4000 to detect and track motion status of cartridge components, in accordance with at least one aspect of the present disclosure. Having described a sensor system configured to monitor at least two internal cartridge 4008 component locations to determine status or operation of the cartridge 4008 to determine the status, operation, or current stroke location of the coupled firing actuator, provide information to the user derived from the sensed parameters, and alter the functional status of the device (e.g., safety lock-out) based on the sensed status, the description now turns to a method 4100 of monitoring the internal function or motion of components within the cartridge 4008 as shown in FIG. 51. The method 4100 may be implemented by the control circuit 4062 of the electronic circuit 4074 as described with reference to FIGS. 46-50 and more particularly in FIG. 47.

[0403] According to the method, the control circuit 4062 is programmed or configured to receive 4102 the digitized signal 4058 samples from the first sensor array 4050 configured to monitor a first internal function or motion of a component located within the staple cartridge 4008 of a surgical instrument. The first sensor array 4050

is disposed in the cartridge 4008 to sense the location or motion of a first component located in the cartridge 4008. By way of example, as discussed supra, the first sensor array 4050 is disposed on the pan or retainer 4030 of the cartridge 4008 and is configured to sense the location or motion of the staple drivers 4028. In addition to the staple driver 4028 and sled 4018 information, the control circuit 4062 may receive a signal from the electrically conductive circuit element 4314 of the staple-forming pockets 4310 to determine proper formation of the staple leg.

[0404] According to the method 4100, the control circuit 4062 is programmed or configured to receive 4104 the digitized signal 4070 samples from the second sensor array 4052 configured to monitor a second internal function or motion of a component located within the staple cartridge 4008. The second sensor array also is disposed in the cartridge 4008 to sense the location or motion of a second component located in the cartridge 4008. By way of example, the second sensor array 4052 is disposed in the pan or retainer 4030 of the cartridge 4008 and is configured to sense the location or motion of the sled 4018. As discussed throughout this disclosure, the firing actuator is coupled to the sled 4018 and the tissue cutting knife. Accordingly, the position and speed of the sled 4018 as sensed by the second sensor array 4052 may be processed by the control circuit 4062 to determine status, operation, or current stroke location of the firing actuator and / or tissue cutting knife.

[0405] According to the method 4100, the control circuit 4062 is programmed or configured to process 4106 the signal 4058, 4070 samples received 4102, 4104 from the first and second sensor arrays 4050, 4052 to determine a status of the staple cartridge 4008. The control circuit 4062 is programmed or configured to provide 4108 information derived from the processed signal samples to a user of the surgical instrument. According to the method 4100, the control circuit 4062 is programmed or configured to alter 4110 the functional status of the surgical instrument (e.g., safety lock-out) based on the sensed status of the cartridge 4008 based on the processed signal samples.

[0406] Also, by way of example, as discussed supra, the control circuit 4062 may receive data from multiple sources including, without limitation, mechanical lockout features, force measurements, RFID tags, 1-wire or other memory devices to determine authenticity, safety, and data value associated with cartridge 4008.

[0407] The surgical instrument systems described herein have been described in connection with the deployment and deformation of staples; however, the embodiments described herein are not so limited. Various embodiments are envisioned which deploy fasteners other than staples, such as clamps or tacks, for example. Moreover, various embodiments are envisioned which utilize any suitable means for sealing tissue. For instance, an end effector in accordance with various embodiments can comprise electrodes configured to heat and seal the tissue. Also, for instance, an end effector in

accordance with certain embodiments can apply vibrational energy to seal the tissue.

[0408] The entire disclosures of:

- 5 - U.S. Patent No. 5,403,312, entitled ELECTROSURGICAL HEMOSTATIC DEVICE, which issued on April 4, 1995;
- U.S. Patent No. 7,000,818, entitled SURGICAL STAPLING INSTRUMENT HAVING SEPARATE DISTINCT CLOSING AND FIRING SYSTEMS, which issued on February 21, 2006;
- 10 - U.S. Patent No. 7,422,139, entitled MOTOR-DRIVEN SURGICAL CUTTING AND FASTENING INSTRUMENT WITH TACTILE POSITION FEEDBACK, which issued on September 9, 2008;
- U.S. Patent No. 7,464,849, entitled ELECTRO-MECHANICAL SURGICAL INSTRUMENT WITH CLOSURE SYSTEM AND ANVIL ALIGNMENT COMPONENTS, which issued on December 16, 2008;
- 15 - U.S. Patent No. 7,670,334, entitled SURGICAL INSTRUMENT HAVING AN ARTICULATING END EFFECTOR, which issued on March 2, 2010;
- U.S. Patent No. 7,753,245, entitled SURGICAL STAPLING INSTRUMENTS, which issued on July 13, 2010;
- 20 - U.S. Patent No. 8,393,514, entitled SELECTIVELY ORIENTABLE IMPLANTABLE FASTENER CARTRIDGE, which issued on March 12, 2013;
- U.S. Patent Application Serial No. 11/343,803, entitled SURGICAL INSTRUMENT HAVING RECORDING CAPABILITIES, now U.S. Patent No. 7,845,537;
- 25 - U.S. Patent Application Serial No. 12/031,573, entitled SURGICAL CUTTING AND FASTENING INSTRUMENT HAVING RF ELECTRODES, filed February 14, 2008;
- U.S. Patent Application Serial No. 12/031,873, entitled END EFFECTORS FOR A SURGICAL CUTTING AND STAPLING INSTRUMENT, filed February 15, 2008, now U.S. Patent No. 7,980,443;
- 30 - U.S. Patent Application Serial No. 12/235,782, entitled MOTOR-DRIVEN SURGICAL CUTTING INSTRUMENT, now U.S. Patent No. 8,210,411;
- 35 - U.S. Patent Application Serial No. 12/235,972, entitled MOTORIZED SURGICAL INSTRUMENT, now U.S. Patent No. 9,050,083.
- 40 - U.S. Patent Application Serial No. 12/249,117, entitled POWERED SURGICAL CUTTING AND STAPLING APPARATUS WITH MANUALLY RETRACTABLE FIRING SYSTEM, now U.S. Patent No. 8,608,045;
- 45 - U.S. Patent Application Serial No. 12/647,100, entitled MOTOR-DRIVEN SURGICAL CUTTING INSTRUMENT WITH ELECTRIC ACTUATOR DIRECTIONAL CONTROL ASSEMBLY, filed December 24, 2009, now U.S. Patent No. 8,220,688;
- 50 - U.S. Patent Application Serial No. 12/893,461, entitled STAPLE CARTRIDGE, filed September 29,
- 55

- 2012, now U.S. Patent No. 8,733,613;
- U.S. Patent Application Serial No. 13/036,647, entitled SURGICAL STAPLING INSTRUMENT, filed February 28, 2011, now U.S. Patent No. 8,561,870;
 - U.S. Patent Application Serial No. 13/118,241, entitled SURGICAL STAPLING INSTRUMENTS WITH ROTATABLE STAPLE DEPLOYMENT ARRANGEMENTS, now U.S. Patent No. 9,072,535;
 - U.S. Patent Application Serial No. 13/524,049, entitled ARTICULATABLE SURGICAL INSTRUMENT COMPRISING A FIRING DRIVE, filed on June 15, 2012, now U.S. Patent No. 9,101,358;
 - U.S. Patent Application Serial No. 13/800,025, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, filed on March 13, 2013, now U.S. Patent No. 9,345,481;
 - U.S. Patent Application Serial No. 13/800,067, entitled STAPLE CARTRIDGE TISSUE THICKNESS SENSOR SYSTEM, filed on March 13, 2013, now U.S. Patent Application Publication No. 2014/0263552;
 - U.S. Patent Application Publication No. 2007/0175955, entitled SURGICAL CUTTING AND FASTENING INSTRUMENT WITH CLOSURE TRIGGER LOCKING MECHANISM, filed January 31, 2006; and
 - U.S. Patent Application Publication No. 2010/0264194, entitled SURGICAL STAPLING INSTRUMENT WITH AN ARTICULATABLE END EFFECTOR, filed April 22, 2010, now U.S. Patent No. 8,308,040, are hereby incorporated by reference herein.

[0409] Although various devices have been described herein in connection with certain embodiments, modifications and variations to those embodiments may be implemented. Particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. Thus, the particular features, structures, or characteristics illustrated or described in connection with one embodiment may be combined in whole or in part, with the features, structures or characteristics of one or more other embodiments without limitation. Also, where materials are disclosed for certain components, other materials may be used. Furthermore, according to various embodiments, a single component may be replaced by multiple components, and multiple components may be replaced by a single component, to perform a given function or functions. The foregoing description and following claims are intended to cover all such modification and variations.

[0410] The devices disclosed herein can be designed to be disposed of after a single use, or they can be designed to be used multiple times. In either case, however, a device can be reconditioned for reuse after at least one use. Reconditioning can include any combination of the steps including, but not limited to, the disassembly of the device, followed by cleaning or replacement of parti-

cular pieces of the device, and subsequent reassembly of the device. In particular, a reconditioning facility and/or surgical team can disassemble a device and, after cleaning and/or replacing particular parts of the device, the device can be reassembled for subsequent use. Those skilled in the art will appreciate that reconditioning of a device can utilize a variety of techniques for disassembly, cleaning/replacement, and reassembly. Use of such techniques, and the resulting reconditioned device, are all within the scope of the present application.

[0411] The devices disclosed herein may be processed before surgery. First, a new or used instrument may be obtained and, when necessary, cleaned. The instrument may then be sterilized. In one sterilization technique, the instrument is placed in a closed and sealed container, such as a plastic or TYVEK bag. The container and instrument may then be placed in a field of radiation that can penetrate the container, such as gamma radiation, x-rays, and/or high-energy electrons. The radiation may kill bacteria on the instrument and in the container. The sterilized instrument may then be stored in the sterile container. The sealed container may keep the instrument sterile until it is opened in a medical facility. A device may also be sterilized using any other technique known in the art, including but not limited to beta radiation, gamma radiation, ethylene oxide, plasma peroxide, and/or steam.

[0412] While this invention has been described as having exemplary designs, the present invention may be further modified within the spirit and scope of the disclosure. This application is therefore intended to cover any variations, uses, or adaptations of the invention using its general principles.

[0413] The foregoing detailed description has set forth various forms of the devices and/or processes via the use of block diagrams, flowcharts, and/or examples. Insofar as such block diagrams, flowcharts, and/or examples contain one or more functions and/or operations, it will be understood by those within the art that each function and/or operation within such block diagrams, flowcharts, and/or examples can be implemented, individually and/or collectively, by a wide range of hardware, software, firmware, or virtually any combination thereof. Those skilled in the art will recognize that some aspects of the forms disclosed herein, in whole or in part, can be equivalently implemented in integrated circuits, as one or more computer programs running on one or more computers (e.g., as one or more programs running on one or more computer systems), as one or more programs running on one or more processors (e.g., as one or more programs running on one or more microprocessors), as firmware, or as virtually any combination thereof, and that designing the circuitry and/or writing the code for the software and/or firmware would be well within the skill of one of skill in the art in light of this disclosure. In addition, those skilled in the art will appreciate that the mechanisms of the subject matter described herein are capable of being distributed as one or more program

products in a variety of forms, and that an illustrative form of the subject matter described herein applies regardless of the particular type of signal bearing medium used to actually carry out the distribution.

[0414] Instructions used to program logic to perform various disclosed aspects can be stored within a memory in the system, such as dynamic random access memory (DRAM), cache, flash memory, or other storage. Furthermore, the instructions can be distributed via a network or by way of other computer readable media. Thus a machine-readable medium may include any mechanism for storing or transmitting information in a form readable by a machine (e.g., a computer), but is not limited to, floppy diskettes, optical disks, compact disc, read-only memory (CD-ROMs), and magneto-optical disks, read-only memory (ROMs), random access memory (RAM), erasable programmable read-only memory (EPROM), electrically erasable programmable read-only memory (EEPROM), magnetic or optical cards, flash memory, or a tangible, machine-readable storage used in the transmission of information over the Internet via electrical, optical, acoustical or other forms of propagated signals (e.g., carrier waves, infrared signals, digital signals, etc.). Accordingly, the non-transitory computer-readable medium includes any type of tangible machine-readable medium suitable for storing or transmitting electronic instructions or information in a form readable by a machine (e.g., a computer).

[0415] As used in any aspect herein, the term "control circuit" may refer to, for example, hardwired circuitry, programmable circuitry (e.g., a computer processor including one or more individual instruction processing cores, processing unit, processor, microcontroller, microcontroller unit, controller, digital signal processor (DSP), programmable logic device (PLD), programmable logic array (PLA), or field programmable gate array (FPGA)), state machine circuitry, firmware that stores instructions executed by programmable circuitry, and any combination thereof. The control circuit may, collectively or individually, be embodied as circuitry that forms part of a larger system, for example, an integrated circuit (IC), an application-specific integrated circuit (ASIC), a system on-chip (SoC), desktop computers, laptop computers, tablet computers, servers, smart phones, etc. Accordingly, as used herein "control circuit" includes, but is not limited to, electrical circuitry having at least one discrete electrical circuit, electrical circuitry having at least one integrated circuit, electrical circuitry having at least one application specific integrated circuit, electrical circuitry forming a general purpose computing device configured by a computer program (e.g., a general purpose computer configured by a computer program which at least partially carries out processes and/or devices described herein, or a microprocessor configured by a computer program which at least partially carries out processes and/or devices described herein), electrical circuitry forming a memory device (e.g., forms of random access memory), and/or electrical circuitry forming a communi-

cations device (e.g., a modem, communications switch, or optical-electrical equipment). Those having skill in the art will recognize that the subject matter described herein may be implemented in an analog or digital fashion or some combination thereof.

[0416] As used in one or more aspects of the present disclosure, a microcontroller may generally comprise a memory and a microprocessor ("processor") operationally coupled to the memory. The processor may control a motor driver circuit generally utilized to control the position and velocity of a motor, for example. In certain instances, the processor can signal the motor driver to stop and/or disable the motor, for example. In certain instances, the microcontroller may be an LM 4F230H5QR, available from Texas Instruments, for example. In at least one example, the Texas Instruments LM4F230H5QR is an ARM Cortex-M4F Processor Core comprising on-chip memory of 256 KB single-cycle flash memory, or other non-volatile memory, up to 40 MHz, a prefetch buffer to improve performance above 40 MHz, a 32 KB single-cycle serial random access memory (SRAM), internal read-only memory (ROM) loaded with StellarisWare® software, 2 KB electrically erasable programmable read-only memory (EEPROM), one or more pulse width modulation (PWM) modules, one or more quadrature encoder inputs (QE1) analog, one or more 12-bit Analog-to-Digital Converters (ADC) with 12 analog input channels, among other features that are readily available for the product datasheet.

[0417] It should be understood that the term processor as used herein includes any suitable microprocessor, or other basic computing device that incorporates the functions of a computer's central processing unit (CPU) on an integrated circuit or at most a few integrated circuits. The processor is a multipurpose, programmable device that accepts digital data as input, processes it according to instructions stored in its memory, and provides results as output. It is an example of sequential digital logic, as it has internal memory. Processors operate on numbers and symbols represented in the binary numeral system. In at least one instance, the processor may be any single core or multicore processor such as those known under the trade name ARM Cortex by Texas Instruments. Nevertheless, other suitable substitutes for microcontrollers and safety processor may be employed, without limitation.

[0418] As used in any aspect herein, the term "logic" may refer to an app, software, firmware and/or circuitry configured to perform any of the aforementioned operations. Software may be embodied as a software package, code, instructions, instruction sets and/or data recorded on non-transitory computer readable storage medium. Firmware may be embodied as code, instructions or instruction sets and/or data that are hard-coded (e.g., nonvolatile) in memory devices.

[0419] As used in any aspect herein, the terms "component," "system," "module" and the like can refer to a computer-related entity, either hardware, a combination

of hardware and software, software, or software in execution.

[0420] As used in any aspect herein, an "algorithm" refers to a self-consistent sequence of steps leading to a desired result, where a "step" refers to a manipulation of physical quantities and/or logic states which may, though need not necessarily, take the form of electrical or magnetic signals capable of being stored, transferred, combined, compared, and otherwise manipulated. It is common usage to refer to these signals as bits, values, elements, symbols, characters, terms, numbers, or the like. These and similar terms may be associated with the appropriate physical quantities and are merely convenient labels applied to these quantities and/or states.

[0421] A network may include a packet switched network. The communication devices may be capable of communicating with each other using a selected packet switched network communications protocol. One example communications protocol may include an Ethernet communications protocol which may be capable permitting communication using a Transmission Control Protocol/Internet Protocol (TCP/IP). The Ethernet protocol may comply or be compatible with the Ethernet standard published by the Institute of Electrical and Electronics Engineers (IEEE) titled "IEEE 802.3 Standard", published in December, 2008 and/or later versions of this standard. Alternatively or additionally, the communication devices may be capable of communicating with each other using an X.25 communications protocol. The X.25 communications protocol may comply or be compatible with a standard promulgated by the International Telecommunication Union-Telecommunication Standardization Sector (ITU-T). Alternatively or additionally, the communication devices may be capable of communicating with each other using a frame relay communications protocol. The frame relay communications protocol may comply or be compatible with a standard promulgated by Consultative Committee for International Telegraph and Telephone (CCITT) and/or the American National Standards Institute (ANSI). Alternatively or additionally, the transceivers may be capable of communicating with each other using an Asynchronous Transfer Mode (ATM) communications protocol. The ATM communications protocol may comply or be compatible with an ATM standard published by the ATM Forum titled "ATM-MPLS Network Interworking 2.0" published August 2001, and/or later versions of this standard. Of course, different and/or after-developed connection-oriented network communication protocols are equally contemplated herein.

[0422] As used in any aspect herein, a wireless transmission such as, for example, a wireless communication or a wireless transfer of a data signal can be achieved, by a device including one or more transceivers. The transceivers may include, but are not limited to cellular modems, wireless mesh network transceivers, Wi-Fi® transceivers, low power wide area (LPWA) transceivers, and/or near field communications transceivers (NFC). The

device may include or may be configured to communicate with a mobile telephone, a sensor system (e.g., environmental, position, motion, etc.) and/or a sensor network (wired and/or wireless), a computing system (e.g., a server, a workstation computer, a desktop computer, a laptop computer, a tablet computer (e.g., iPad®, GalaxyTab® and the like), an ultraportable computer, an ultramobile computer, a netbook computer and/or a sub-notebook computer; etc. In at least one aspect of the present disclosure, one of the devices may be a coordinator node.

[0423] The transceivers may be configured to receive serial transmit data via respective universal asynchronous receiver-transmitters (UARTs) from a processor to modulate the serial transmit data onto an RF carrier to produce a transmit RF signal and to transmit the transmit RF signal via respective antennas. The transceiver(s) can be further configured to receive a receive RF signal via respective antennas that includes an RF carrier modulated with serial receive data, to demodulate the receive RF signal to extract the serial receive data and to provide the serial receive data to respective UARTs for provision to the processor. Each RF signal has an associated carrier frequency and an associated channel bandwidth. The channel bandwidth is associated with the carrier frequency, the transmit data and/or the receive data. Each RF carrier frequency and channel bandwidth is related to the operating frequency range(s) of the transceiver(s). Each channel bandwidth is further related to the wireless communication standard and/or protocol with which the transceiver(s) may comply. In other words, each transceiver may correspond to an implementation of a selected wireless communication standard and/or protocol, e.g., IEEE 802.11 a/b/g/n for Wi-Fi® and/or IEEE 802.15.4 for wireless mesh networks using Zigbee routing.

[0424] One or more drive systems or drive assemblies, as described herein, employ one or more electric motors. In various forms, the electric motors may be a DC brushed driving motor, for example. In other arrangements, the motor may include a brushless motor, a cordless motor, a synchronous motor, a stepper motor, or any other suitable electric motor. The electric motors may be powered by a power source that in one form may comprise a removable power pack. Batteries may each comprise, for example, a Lithium Ion ("LI") or other suitable battery. The electric motors can include rotatable shafts that operably interface with gear reducer assemblies, for example. In certain instances, a voltage polarity provided by the power source can operate an electric motor in a clockwise direction wherein the voltage polarity applied to the electric motor by the battery can be reversed in order to operate the electric motor in a counter-clockwise direction. In various aspects, a microcontroller controls the electric motor through a motor driver via a pulse width modulated control signal. The motor driver can be configured to adjust the speed of the electric motor either in clockwise or counter-clockwise direction. The motor dri-

ver is also configured to switch between a plurality of operational modes which include an electronic motor braking mode, a constant speed mode, an electronic clutching mode, and a controlled current activation mode. In electronic braking mode, two terminal of the drive motor 200 are shorted and the generated back EMF counteracts the rotation of the electric motor allowing for faster stopping and greater positional precision.

[0425] Unless specifically stated otherwise as apparent from the foregoing disclosure, it is appreciated that, throughout the foregoing disclosure, discussions using terms such as "processing," "computing," "calculating," "determining," "displaying," or the like, refer to the action and processes of a computer system, or similar electronic computing device, that manipulates and transforms data represented as physical (electronic) quantities within the computer system's registers and memories into other data similarly represented as physical quantities within the computer system memories or registers or other such information storage, transmission or display devices.

[0426] One or more components may be referred to herein as "configured to," "configurable to," "operable/-operative to," "adapted/adaptable," "able to," "conformable/conformed to," etc. Those skilled in the art will recognize that "configured to" can generally encompass active-state components and/or inactive-state components and/or standby-state components, unless context requires otherwise.

[0427] Those skilled in the art will recognize that, in general, terms used herein, and especially in the appended claims (e.g., bodies of the appended claims) are generally intended as "open" terms (e.g., the term "including" should be interpreted as "including but not limited to," the term "having" should be interpreted as "having at least," the term "includes" should be interpreted as "includes but is not limited to," etc.). It will be further understood by those within the art that if a specific number of an introduced claim recitation is intended, such an intent will be explicitly recited in the claim, and in the absence of such recitation no such intent is present. For example, as an aid to understanding, the following appended claims may contain usage of the introductory phrases "at least one" and "one or more" to introduce claim recitations. However, the use of such phrases should not be construed to imply that the introduction of a claim recitation by the indefinite articles "a" or "an" limits any particular claim containing such introduced claim recitation to claims containing only one such recitation, even when the same claim includes the introductory phrases "one or more" or "at least one" and indefinite articles such as "a" or "an" (e.g., "a" and/or "an" should typically be interpreted to mean "at least one" or "one or more"); the same holds true for the use of definite articles used to introduce claim recitations.

[0428] In addition, even if a specific number of an introduced claim recitation is explicitly recited, those skilled in the art will recognize that such recitation should typically be interpreted to mean at least the recited num-

ber (e.g., the bare recitation of "two recitations," without other modifiers, typically means at least two recitations, or two or more recitations). Furthermore, in those instances where a convention analogous to "at least one of A, B, and C, etc." is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., "a system having at least one of A, B, and C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). In those instances where a convention analogous to "at least one of A, B, or C, etc." is used, in general such a construction is intended in the sense one having skill in the art would understand the convention (e.g., "a system having at least one of A, B, or C" would include but not be limited to systems that have A alone, B alone, C alone, A and B together, A and C together, B and C together, and/or A, B, and C together, etc.). It will be further understood by those within the art that typically a disjunctive word and/or phrase presenting two or more alternative terms, whether in the description, claims, or drawings, should be understood to contemplate the possibilities of including one of the terms, either of the terms, or both terms unless context dictates otherwise. For example, the phrase "A or B" will be typically understood to include the possibilities of "A" or "B" or "A and B."

[0429] With respect to the appended claims, those skilled in the art will appreciate that recited operations therein may generally be performed in any order. Also, although various operational flow diagrams are presented in a sequence(s), it should be understood that the various operations may be performed in other orders than those which are illustrated, or may be performed concurrently. Examples of such alternate orderings may include overlapping, interleaved, interrupted, reordered, incremental, preparatory, supplemental, simultaneous, reverse, or other variant orderings, unless context dictates otherwise. Furthermore, terms like "responsive to," "related to," or other past-tense adjectives are generally not intended to exclude such variants, unless context dictates otherwise.

[0430] It is worthy to note that any reference to "one aspect," "an aspect," "an exemplification," "one exemplification," and the like means that a particular feature, structure, or characteristic described in connection with the aspect is included in at least one aspect. Thus, appearances of the phrases "in one aspect," "in an aspect," "in an exemplification," and "in one exemplification" in various places throughout the specification are not necessarily all referring to the same aspect. Furthermore, the particular features, structures or characteristics may be combined in any suitable manner in one or more aspects.

[0431] In this specification, unless otherwise indicated, terms "about" or "approximately" as used in the present disclosure, unless otherwise specified, means an acceptable error for a particular value as determined by one of

ordinary skill in the art, which depends in part on how the value is measured or determined. In certain embodiments, the term "about" or "approximately" means within 1, 2, 3, or 4 standard deviations. In certain embodiments, the term "about" or "approximately" means within 50%, 20%, 15%, 10%, 9%, 8%, 7%, 6%, 5%, 4%, 3%, 2%, 1%, 0.5%, or 0.05% of a given value or range.

[0432] In this specification, unless otherwise indicated, all numerical parameters are to be understood as being prefaced and modified in all instances by the term "about," in which the numerical parameters possess the inherent variability characteristic of the underlying measurement techniques used to determine the numerical value of the parameter. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter described herein should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

[0433] Any numerical range recited herein includes all sub-ranges subsumed within the recited range. For example, a range of "1 to 10" includes all sub-ranges between (and including) the recited minimum value of 1 and the recited maximum value of 10, that is, having a minimum value equal to or greater than 1 and a maximum value equal to or less than 10. Also, all ranges recited herein are inclusive of the end points of the recited ranges. For example, a range of "1 to 10" includes the end points 1 and 10. Any maximum numerical limitation recited in this specification is intended to include all lower numerical limitations subsumed therein, and any minimum numerical limitation recited in this specification is intended to include all higher numerical limitations subsumed therein. Accordingly, Applicant reserves the right to amend this specification, including the claims, to expressly recite any sub-range subsumed within the ranges expressly recited. All such ranges are inherently described in this specification.

[0434] Any patent application, patent, non-patent publication, or other disclosure material referred to in this specification and/or listed in any Application Data Sheet is incorporated by reference herein, to the extent that the incorporated materials is not inconsistent herewith. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

[0435] In summary, numerous benefits have been described which result from employing the concepts described herein. The foregoing description of the one or more forms has been presented for purposes of illustration and description. It is not intended to be exhaustive or limiting to the precise form disclosed. Modifications or

variations are possible in light of the above teachings. The one or more forms were chosen and described in order to illustrate principles and practical application to thereby enable one of ordinary skill in the art to utilize the various forms and with various modifications as are suited to the particular use contemplated. It is intended that the claims submitted herewith define the overall scope.

10 EMBODIMENTS:

[0436]

1. A surgical end effector for use with a surgical instrument, the surgical end effector comprising:

a jaw; and
a staple cartridge seatable in the jaw, wherein the staple cartridge comprises:

a sensor array configured to take measurements corresponding to a parameter associated with a function of the surgical instrument;

a processor; and

a memory storing program instructions that, when executed by the processor, cause the processor to:

perform an initial calibration of the sensor array;

determine an initial adjustment to the measurements based on the initial calibration;

perform an in-use calibration of the sensor array; and

modify the initial adjustment based on the in-use calibration.

2. The surgical end effector of Embodiment 1, wherein the program instructions further cause the processor to store the initial adjustment in the memory.

3. The surgical end effector of Embodiment 1, wherein performing the in-use calibration comprises identifying a conversion factor, and wherein modifying the initial adjustment is based on the conversion factor.

4. The surgical end effector of Embodiment 3, wherein the conversion factor is a shelf-life conversion factor.

5. The surgical end effector of Embodiment 1, wherein the parameter is a tissue parameter.

6. The surgical end effector of Embodiment 1, wherein performing at least one of the initial calibration and

the in-use calibration comprises causing the sensor array to take a measurement of a known property of a predetermined medium.

7. A surgical instrument, comprising:

a motor configured to generate a closure motion;
an end effector configured to grasp tissue, the end effector comprising:

a first jaw comprising an anvil comprising a first tissue contacting surface;
a second jaw, wherein the closure motion causes at least one of the first jaw and the second jaw to move relative to the other to transition the end effector toward a closed configuration;
a staple cartridge seatable in the second jaw, wherein the staple cartridge comprises:

a cartridge deck comprising a second tissue contacting surface;
a cartridge body;
staples removably stored in the cartridge body; and
a sensor; and

a control circuit configured to:

measure a physical parameter of the staple cartridge; and
modulate a control parameter of the surgical instrument based on the physical characteristic of the staple cartridge measured by the control circuit.

8. The surgical instrument of Embodiment 7, wherein the physical parameter of the staple cartridge is a tissue gap, and wherein measuring the physical parameter comprises:

detecting the closed configuration based on a current draw of the motor; and
determining a minimum gap between the anvil and the staple cartridge from an output signal of the sensor at the closed configuration.

9. The surgical instrument of Embodiment 8, wherein detecting the closed configuration comprises detecting a value of the current draw greater than or equal to a current-draw threshold.

10. The surgical instrument of Embodiment 7, wherein the control parameter is a parameter of an algorithm executable to perform a function of the surgical instrument.

11. The surgical instrument of Embodiment 7, where-

in the minimum gap is defined by a cartridge feature configured to interfere with closure of the end effector.

12. The surgical instrument of Embodiment 7, wherein the control circuit is further configured to verify a tissue compression creep of a tissue grasped between the first jaw and the second jaw based on the value of the minimum gap and an initial thickness of the tissue.

13. The surgical instrument of Embodiment 7, wherein the control circuit is configured to verify a type of the cartridge based on the physical parameter of the staple cartridge.

14. The surgical instrument of Embodiment 7, wherein the control parameter is a threshold.

15. A surgical instrument, comprising:

a motor configured to generate a closure motion;
an end effector configured to grasp tissue, the end effector comprising:

a first jaw comprising an anvil;
a second jaw, wherein the closure motion causes at least one of the first jaw and the second jaw to move relative to the other to transition the end effector between closure states to grasp the tissue;
a staple cartridge seatable in the second jaw, wherein the staple cartridge comprises:

a cartridge body;
staples removably stored in the cartridge body; and
a sensor array; and

a control circuit configured to:

detect the closure states of the end effector based on an operational parameter of the motor; and
selectively adjust a sensor parameter of sensors of the sensor array in accordance with the closure states.

16. The surgical instrument of Embodiment 15, wherein the closure states comprise a first closure state associated with an initial tissue contact.

17. The surgical instrument of Embodiment 16, wherein the closure states comprise a second closure state associated with a fully-clamped tissue condition.

18. The surgical instrument of Embodiment 17,

wherein the closure states comprise a third closure state associated with a fully-stabilized tissue creep.

19. The surgical instrument of Embodiment 15, wherein selectively adjusting the sensor parameter of the sensors comprises selectively switching the sensors between an active mode and an idler mode.

Claims

1. A surgical instrument, comprising:

a motor configured to generate a closure motion;
an end effector configured to grasp tissue, the end effector comprising:

a first jaw comprising an anvil;
a second jaw, wherein the closure motion causes at least one of the first jaw and the second jaw to move relative to the other to transition the end effector between closure states to grasp the tissue;
a staple cartridge seatable in the second jaw, wherein the staple cartridge comprises:

a cartridge body;
staples removably stored in the cartridge body; and
a sensor array; and

a control circuit configured to:

detect the closure states of the end effector based on an operational parameter of the motor; and
selectively adjust a sensor parameter of sensors of the sensor array in accordance with the closure states.

2. The surgical instrument of Claim 1, wherein the closure states comprise a first closure state associated with an initial tissue contact.

3. The surgical instrument of Claim 2, wherein the closure states comprise a second closure state associated with a fully-clamped tissue condition.

4. The surgical instrument of Claim 3, wherein the closure states comprise a third closure state associated with a fully-stabilized tissue creep.

5. The surgical instrument of Claim 1, wherein selectively adjusting the sensor parameter of the sensors comprises selectively switching the sensors between an active mode and an idler mode.

6. A surgical end effector for use with a surgical instru-

ment, the surgical end effector comprising:

a jaw; and
a staple cartridge seatable in the jaw, wherein the staple cartridge comprises:

a sensor array configured to take measurements corresponding to a parameter associated with a function of the surgical instrument;
a processor; and
a memory storing program instructions that, when executed by the processor, cause the processor to:

perform an initial calibration of the sensor array;
determine an initial adjustment to the measurements based on the initial calibration;
perform an in-use calibration of the sensor array; and
modify the initial adjustment based on the in-use calibration.

7. The surgical end effector of Claim 6, wherein the program instructions further cause the processor to store the initial adjustment in the memory.

8. The surgical end effector of Claim 6, wherein performing the in-use calibration comprises identifying a conversion factor, and wherein modifying the initial adjustment is based on the conversion factor, optionally wherein the conversion factor is a shelf-life conversion factor.

9. The surgical end effector of Claim 6, wherein the parameter is a tissue parameter.

10. The surgical end effector of Claim 6, wherein performing at least one of the initial calibration and the in-use calibration comprises causing the sensor array to take a measurement of a known property of a predetermined medium.

11. A surgical instrument, comprising:

a motor configured to generate a closure motion;
an end effector configured to grasp tissue, the end effector comprising:

a first jaw comprising an anvil comprising a first tissue contacting surface;
a second jaw, wherein the closure motion causes at least one of the first jaw and the second jaw to move relative to the other to transition the end effector toward a closed configuration;

a staple cartridge seatable in the second jaw, wherein the staple cartridge comprises:

a cartridge deck comprising a second tissue contacting surface; 5
 a cartridge body;
 staples removably stored in the cartridge body; and
 a sensor; and 10

a control circuit configured to:

measure a physical parameter of the staple cartridge; and 15
 modulate a control parameter of the surgical instrument based on the physical characteristic of the staple cartridge measured by the control circuit.

12. The surgical instrument of Claim 11, wherein the physical parameter of the staple cartridge is a tissue gap, and wherein measuring the physical parameter comprises: 20

detecting the closed configuration based on a current draw of the motor; and 25
 determining a minimum gap between the anvil and the staple cartridge from an output signal of the sensor at the closed configuration, optionally wherein detecting the closed configuration comprises detecting a value of the current draw greater than or equal to a current-draw threshold. 30

13. The surgical instrument of Claim 11, wherein the control parameter is a parameter of an algorithm executable to perform a function of the surgical instrument, and/or wherein the control parameter is a threshold. 35

40

14. The surgical instrument of Claim 11, wherein the minimum gap is defined by a cartridge feature configured to interfere with closure of the end effector.

15. The surgical instrument of Claim 11, wherein the control circuit is further configured to verify a tissue compression creep of a tissue grasped between the first jaw and the second jaw based on the value of the minimum gap and an initial thickness of the tissue, and/or wherein the control circuit is configured to verify a type of the cartridge based on the physical parameter of the staple cartridge. 45
 50

55




FIG. 1




FIG. 2






FIG. 3








FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6




FIG. 7




FIG. 8





FIG. 8A






FIG. 8C




FIG. 8D




FIG. 9




FIG. 10




FIG. 11




FIG. 11A




FIG. 11B




FIG. 11C




FIG. 11D




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG.16




FIG. 17

1090 

	SamplingRate	BandwidthCapacity	DischargeRate	RemainingCapacity
...	S1	B1	D1	R1
	S2	B2	D2	R2
	...	...	...	...
	Sn	Bn	Dn	Rn

FIG. 18




FIG. 19




FIG. 20




FIG. 21




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26




FIG. 27




FIG. 28




FIG. 29




FIG. 30




FIG. 31




FIG. 32




FIG. 33




FIG. 34




FIG. 35




FIG. 36




FIG. 37




FIG. 38B

FIG. 38A




FIG. 39




FIG. 40




FIG. 41




FIG. 42




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47




FIG. 48




FIG. 49




FIG. 50




FIG. 51

REFERENCES CITED IN THE DESCRIPTION

This list of references cited by the applicant is for the reader's convenience only. It does not form part of the European patent document. Even though great care has been taken in compiling the references, errors or omissions cannot be excluded and the EPO disclaims all liability in this regard.

Patent documents cited in the description

- US 084179 A [0005]
- US 084190 A [0005]
- US 084198 A [0005]
- US 084205 A [0005]
- US 084258 A [0005]
- US 084206 A [0005]
- US 084215 A [0005]
- US 084229 A [0005]
- US 084180 A [0005]
- US 756615 F [0005]
- US 756620 F [0005]
- US 084188 A [0005]
- US 084193 A [0005]
- US 846303 A [0006]
- US 20200345353 [0006]
- US 846304 A [0006]
- US 20200345354 [0006]
- US 846305 A [0006]
- US 20200345446 [0006]
- US 846307 A [0006]
- US 202003453549 [0006]
- US 846308 A [0006]
- US 20200345355 [0006]
- US 846309 A [0006]
- US 20200345356 [0006]
- US 846310 A [0006]
- US 20200345357 [0006]
- US 846311 A [0006]
- US 20200345358 [0006]
- US 846312 A [0006]
- US 20200345359 [0006]
- US 846313 A [0006]
- US 20200345360 [0006]
- US 62840715 A [0007]
- US 28165819 A [0008]
- US 20190298350 [0008]
- US 28167019 A [0008]
- US 20190298340 [0008]
- US 28167519 A [0008]
- US 20190298354 [0008]
- US 28168519 A [0008]
- US 20190298341 [0008]
- US 28169319 A [0008]
- US 20190298342 [0008]
- US 28170419 A [0008]
- US 20190298356 [0008]
- US 28170719 A [0008]
- US 20190298347 [0008]
- US 28174119 A [0008]
- US 20190298357 [0008]
- US 281762 A [0008]
- US 20190298343 [0008]
- US 28166619 A [0008]
- US 20190298352 [0008]
- US 28167219 A [0008]
- US 20190298353 [0008]
- US 28167819 A [0008]
- US 20190298355 [0008]
- US 28168219 A [0008]
- US 20190298346 [0008]
- US 62807310 A [0009]
- US 62807319 A [0009]
- US 62807309 A [0009]
- US 62649302 A [0010] [0034]
- US 62649294 A [0010] [0034]
- US 62649300 A [0010] [0034]
- US 62649309 A [0010] [0034]
- US 62649310 A [0010] [0034]
- US 62649291 A [0010] [0034]
- US 62649296 A [0010] [0034]
- US 62649333 A [0010] [0034]
- US 62649327 A [0010] [0034]
- US 62649315 A [0010] [0034]
- US 62649313 A [0010] [0034]
- US 62649320 A [0010] [0034]
- US 62649307 A [0010] [0034]
- US 62649323 A [0010] [0034]
- US 62650887 A [0011]
- US 20942318 A [0012]
- US 20190200981 A [0013]
- US 10510118 A [0014]
- US 20200054323 [0014]
- US 10518318 A [0014]
- US 10912559 B [0014]
- US 10515018 A [0014]
- US 20200054326 [0014]
- US 10509818 A [0014]
- US 20200054322 [0014]
- US 10514018 A [0014]
- US 10779821 B [0014]
- US 10508118 A [0014]
- US 20200054320 [0014]
- US 10509418 A [0014]
- US PUBLICATIONNO20200054321 A [0014]
- US 10509718 A [0014]
- US 20200054328 [0014]
- US 10510418 A [0014]
- US 10842492 B [0014]

EP 4 521 595 A2

- US 10511918 A [0014]
- US 20200054330 [0014]
- US 10516018 A [0014]
- US 10856870 B [0014]
- US 66025218 [0014]
- US 386185 A [0015]
- US 10639035 B [0015]
- US 386230 A [0015]
- US 20180168649 [0015]
- US 386221 A [0015]
- US 10835247 B [0015]
- US 386209 A [0015]
- US 10588632 B [0015]
- US 386198 A [0015]
- US 10610224 B [0015]
- US 386240 A [0015]
- US 20180168651 [0015]
- US 385939 A [0015]
- US 10835246 B [0015]
- US 385941 A [0015]
- US 10736629 B [0015]
- US 385943 A [0015]
- US 10667811 B [0015]
- US 385950 A [0015]
- US 10588630 B [0015]
- US 385945 A [0015]
- US 10893864 B [0015]
- US 385946 A [0015]
- US 20180168633 [0015]
- US 385951 A [0015]
- US 10568626 B [0015]
- US 385953 A [0015]
- US 10675026 B [0015]
- US 385954 A [0015]
- US 10624635 B [0015]
- US 385955 A [0015]
- US 10813638 B [0015]
- US 385948 [0015]
- US 20180168584 [0015]
- US 385956 A [0015]
- US 10588631 B [0015]
- US 385958 A [0015]
- US 10639034 B [0015]
- US 385947 A [0015]
- US 10568625 B [0015]
- US 385896 [0015]
- US 20180168597 [0015]
- US 385898 A [0015]
- US 10537325 B [0015]
- US 385899 A [0015]
- US 10758229 B [0015]
- US 385901 A [0015]
- US 10667809 B [0015]
- US 385902 A [0015]
- US 10888322 B [0015]
- US 385904 A [0015]
- US 10881401 B [0015]
- US 385905 A [0015]
- US 10695055 B [0015]
- US 385907 A [0015]
- US 20180168608 [0015]
- US 385908 A [0015]
- US 20180168609 [0015]
- US 385909 A [0015]
- US 20180168610 [0015]
- US 385920 A [0015]
- US 10499914 B [0015]
- US 385913 A [0015]
- US 20180168614 [0015]
- US 385914 A [0015]
- US 20180168615 [0015]
- US 385893 A [0015]
- US 10682138 B [0015]
- US 385929 A [0015]
- US 10667810 B [0015]
- US 385911 A [0015]
- US 10448950 B [0015]
- US 385927 A [0015]
- US 20180168625 [0015]
- US 385917 A [0015]
- US 20180168617 [0015]
- US 385900 A [0015]
- US 10898186 B [0015]
- US 385931 A [0015]
- US 20180168627 [0015]
- US 385915 A [0015]
- US 10779823 B [0015]
- US 385897 A [0015]
- US 20180168598 [0015]
- US 385922 A [0015]
- US 10426471 B [0015]
- US 385924 A [0015]
- US 10758230 B [0015]
- US 385910 A [0015]
- US 10485543 B [0015]
- US 385903 A [0015]
- US 10617414 B [0015]
- US 385906 A [0015]
- US 10856868 B [0015]
- US 386188 A [0015]
- US 10537324 B [0015]
- US 386192 A [0015]
- US 10687810 B [0015]
- US 386206 A [0015]
- US 20180168586 [0015]
- US 386226 A [0015]
- US 20180168648 [0015]
- US 386222 A [0015]
- US 20180168647 [0015]
- US 386236 A [0015]
- US 20180168650 [0015]
- US 385887 A [0015]
- US 10835245 B [0015]
- US 385889 [0015]
- US 20180168590 [0015]
- US 385890 A [0015]

EP 4 521 595 A2

- US 10675025 B [0015]
- US 385891 A [0015]
- US 20180168592 [0015]
- US 385892 A [0015]
- US 10918385 B [0015]
- US 385894 A [0015]
- US 10492785 B [0015]
- US 385895 A [0015]
- US 10542982 B [0015]
- US 385916 A [0015]
- US 20180168575 [0015]
- US 385918 A [0015]
- US 20180168618 [0015]
- US 385919 A [0015]
- US 20180168619 [0015]
- US 385921 A [0015]
- US 10687809 B [0015]
- US 385923 A [0015]
- US 20180168623 [0015]
- US 385925 A [0015]
- US 10517595 B [0015]
- US 385926 A [0015]
- US 20180168577 [0015]
- US 385928 A [0015]
- US 20180168578 [0015]
- US 385930 A [0015]
- US 20180168579 [0015]
- US 385932 A [0015]
- US 20180168628 [0015]
- US 385933 [0015]
- US 10603036 B [0015]
- US 385934 A [0015]
- US 10582928 B [0015]
- US 385935 A [0015]
- US 10524789 B [0015]
- US 385936 A [0015]
- US 10517596 B [0015]
- US 318996 [0015]
- US 20150297228 [0015]
- US 319006 A [0015]
- US 10010324 B [0015]
- US 318991 A [0015]
- US 9833241 B [0015]
- US 319004 A [0015]
- US 9844369 B [0015]
- US 319008 A [0015]
- US 10299792 B [0015]
- US 318997 A [0015]
- US 10561422 B [0015]
- US 319002 A [0015]
- US 9877721 B [0015]
- US 319013 A [0015]
- US 20150297233 [0015]
- US 319016 A [0015]
- US 10470768 B [0015]
- US 19177516 A [0016]
- US 20170367695 [0016]
- US 19180716 A [0016]
- US 10702270 B [0016]
- US 19183416 A [0016]
- US 10542979 B [0016]
- US 19178816 A [0016]
- US 10675024 B [0016]
- US 19181816 A [0016]
- US 10893863 B [0016]
- US 56921816 F [0017]
- US D826405 S [0017]
- US 56922716 F [0017]
- US D822206 S [0017]
- US 56925916 F [0017]
- US D847989 S [0017]
- US 56926416 F [0017]
- US D850617 S [0017]
- US 08932516 A [0018]
- US 20170281171 [0018]
- US 08932116 A [0018]
- US 10271851 B [0018]
- US 08932616 A [0018]
- US 10433849 B [0018]
- US 08926316 A [0018]
- US 10307159 B [0018]
- US 08926216 [0018]
- US 10357246 B [0018]
- US 08927716 A [0018]
- US 10531874 B [0018]
- US 08929616 A [0018]
- US 10413293 B [0018]
- US 08925816 A [0018]
- US 10342543 B [0018]
- US 08927816 A [0018]
- US 10420552 B [0018]
- US 08928416 A [0018]
- US PUBLICATIONNO20170281186 A [0018]
- US 08929516 A [0018]
- US 10856867 B [0018]
- US 08930016 A [0018]
- US 10456140 B [0018]
- US 08919616 A [0018]
- US 10568632 B [0018]
- US 08920316 A [0018]
- US 10542991 B [0018]
- US 08921016 A [0018]
- US 10478190 B [0018]
- US 08932416 A [0018]
- US 10314582 B [0018]
- US 08933516 A [0018]
- US 10485542 B [0018]
- US 08933916 A [0018]
- US 20170281173 [0018]
- US 08925316 [0018]
- US 10413297 B [0018]
- US 08930416 A [0018]
- US 10285705 B [0018]
- US 08933116 A [0018]
- US 10376263 B [0018]
- US 08933616 A [0018]

EP 4 521 595 A2

- US 10709446 B [0018]
- US 08931216 A [0018]
- US 20170281189 [0018]
- US 08930916 A [0018]
- US 10675021 B [0018]
- US 08934916 A [0018]
- US 10682136 B [0018]
- US 98448815 A [0019]
- US 10292704 B [0019]
- US 98452515 A [0019]
- US 10368865 B [0019]
- US 98455215 A [0019]
- US 10265068 B [0019]
- US 01922016 A [0020]
- US 10245029 B [0020]
- US 01922816 [0020]
- US 10433837 B [0020]
- US 01919616 A [0020]
- US 10413291 B [0020]
- US 01920616 A [0020]
- US 10653413 B [0020]
- US 01921516 A [0020]
- US 20170224332 [0020]
- US 01922716 A [0020]
- US 20170224334 [0020]
- US 01923516 A [0020]
- US 10245030 B [0020]
- US 01923016 A [0020]
- US 10588625 B [0020]
- US 01924516 A [0020]
- US 10470764 B [0020]
- US 04325416 A [0021]
- US 10258331 B [0021]
- US 04325916 A [0021]
- US 10448948 B [0021]
- US 04327516 A [0021]
- US 20170231627 [0021]
- US 04328916 A [0021]
- US 20170231628 [0021]
- US 74292515 A [0022]
- US 10182818 B [0022]
- US 74294115 [0022]
- US 10052102 B [0022]
- US 74293315 A [0022]
- US 10154841 B [0022]
- US 74291415 A [0022]
- US 10405863 B [0022]
- US 74290015 A [0022]
- US 10335149 B [0022]
- US 74288515 A [0022]
- US 10368861 B [0022]
- US 74287615 A [0022]
- US 10178992 B [0022]
- US 64074615 A [0023]
- US 9808246 B [0023] [0293]
- US 64079515 A [0023]
- US 10441279 B [0023]
- US 64083215 A [0023]
- US 10687806 B [0023]
- US 64093515 A [0023]
- US 10548504 B [0023] [0084]
- US 64083115 A [0023]
- US 9895148 B [0023]
- US 64085915 A [0023]
- US 10052044 B [0023]
- US 64081715 A [0023]
- US 9924961 B [0023]
- US 64084415 A [0023]
- US 10045776 B [0023]
- US 64083715 A [0023]
- US 9993248 B [0023] [0084] [0228] [0393]
- US 64076515 A [0023]
- US 10617412 B [0023]
- US 64079915 A [0023]
- US 9901342 B [0023]
- US 64078015 A [0023]
- US 10245033 B [0023]
- US 63357615 A [0024]
- US 10045779 B [0024]
- US 63354615 A [0024]
- US 10180463 B [0024]
- US 63356015 [0024]
- US 20160249910 [0024]
- US 63356615 A [0024]
- US 10182816 B [0024]
- US 633555 A [0024]
- US 10321907 B [0024]
- US 633542 A [0024]
- US 9931118 B [0024]
- US 633548 A [0024]
- US 10245028 B [0024]
- US 633526 A [0024]
- US 9993258 B [0024]
- US 633541 A [0024]
- US 10226250 B [0024]
- US 633562 A [0024]
- US 10159483 B [0024]
- US 57447814 A [0025]
- US 9844374 B [0025]
- US 57448314 A [0025]
- US 10188385 B [0025]
- US 57513914 A [0025]
- US 9844375 B [0025]
- US 57514814 A [0025]
- US 10085748 B [0025]
- US 57513014 A [0025]
- US 10245027 B [0025]
- US 57514314 A [0025]
- US 10004501 B [0025]
- US 57511714 A [0025]
- US 9943309 B [0025]
- US 57515414 A [0025]
- US 9968355 B [0025]
- US 57449314 A [0025]
- US 9987000 B [0025]
- US 57450014 A [0025]

EP 4 521 595 A2

- US 10117649 B [0025]
- US 78229513 A [0026]
- US 9700309 B [0026]
- US 78232313 A [0026]
- US 9782169 B [0026]
- US 78233813 A [0026]
- US 20140249557 [0026]
- US 78249913 A [0026]
- US 9358003 B [0026]
- US 78246013 A [0026]
- US 9554794 B [0026]
- US 78235813 A [0026]
- US 9326767 B [0026]
- US 78248113 A [0026]
- US 9468438 B [0026]
- US 78251813 A [0026]
- US 20140246475 [0026]
- US 78237513 [0026]
- US 9398911 B [0026]
- US 78253613 A [0026]
- US 9307986 B [0026]
- US 80309713 A [0027]
- US 9687230 B [0027]
- US 80319313 A [0027]
- US 9332987 B [0027]
- US 80305313 A [0027]
- US 9883860 B [0027]
- US 80308613 A [0027]
- US 20140263541 [0027]
- US 80321013 A [0027]
- US 9808244 B [0027]
- US 80314813 A [0027]
- US 10470762 B [0027]
- US 80306613 A [0027]
- US 9629623 B [0027]
- US 80311713 A [0027]
- US 9351726 B [0027]
- US 80313013 A [0027]
- US 9351727 B [0027]
- US 80315913 A [0027]
- US 9888919 B [0027]
- US 20011114 A [0028]
- US 9629629 B [0028] [0051]
- US 22610614 A [0029]
- US 20150272582 [0029]
- US 22609914 A [0029]
- US 9826977 B [0029]
- US 22609414 A [0029]
- US 20150272580 [0029]
- US 22611714 A [0029]
- US 10013049 B [0029]
- US 22607514 A [0029]
- US 9743929 B [0029]
- US 22609314 [0029]
- US 10028761 B [0029]
- US 22611614 A [0029]
- US 20150272571 [0029]
- US 22607114 A [0029]
- US 9690362 B [0029]
- US 22609714 A [0029]
- US 9820738 B [0029]
- US 22612614 A [0029]
- US 10004497 B [0029]
- US 22613314 A [0029]
- US 20150272557 [0029]
- US 22608114 A [0029]
- US 9804618 B [0029]
- US 22607614 A [0029]
- US 9733663 B [0029]
- US 22611114 A [0029]
- US 9750499 B [0029]
- US 22612514 A [0029]
- US 10201364 B [0029]
- US 47910314 [0030]
- US 10111679 B [0030]
- US 47911914 A [0030]
- US 9724094 B [0030] [0293]
- US 47890814 A [0030]
- US 9737301 B [0030]
- US 47889514 A [0030]
- US 9757128 B [0030]
- US 47911014 A [0030]
- US 10016199 B [0030]
- US 47909814 A [0030]
- US 10135242 B [0030] [0084] [0088]
- US 47911514 A [0030]
- US 9788836 B [0030]
- US 47910814 A [0030]
- US 20160066913 [0030]
- US 24859014 A [0031]
- US 9826976 B [0031]
- US 24858114 A [0031]
- US 9649110 B [0031]
- US 24859514 A [0031]
- US 9844368 B [0031]
- US 24858814 A [0031]
- US 10405857 B [0031]
- US 24859114 A [0031]
- US 10149680 B [0031]
- US 24858414 A [0031]
- US 9801626 B [0031]
- US 24858714 A [0031]
- US 9867612 B [0031]
- US 24858614 A [0031]
- US 10136887 B [0031]
- US 24860714 A [0031]
- US 9814460 B [0031]
- US 61812365 A [0032]
- US 61812376 A [0032]
- US 61812382 A [0032]
- US 61812385 A [0032]
- US 61812372 A [0032]
- US 62611341 A [0033]
- US 62611340 A [0033]
- US 62611339 A [0033]
- US 94064118 A [0035]

EP 4 521 595 A2

- US 20190207911 [0035]
- US 94064818 A [0035]
- US 20190206004 [0035]
- US 94065618 [0035]
- US 20190201141 [0035]
- US 94066618 A [0035]
- US 20190206551 [0035]
- US 94067018 A [0035]
- US 20190201116 [0035]
- US 94067718 A [0035]
- US 20190201143 [0035]
- US 94063218 A [0035]
- US 20190205566 [0035]
- US 94064018 A [0035]
- US 20190200863 [0035]
- US 94064518 A [0035]
- US 10892899 B [0035]
- US 94064918 A [0035]
- US 20190205567 [0035]
- US 94065418 A [0035]
- US 20190201140 [0035]
- US 94066318 A [0035]
- US 20190201033 [0035]
- US 94066818 A [0035]
- US 20190201115 [0035]
- US 94067118 A [0035]
- US 20190201104 [0035]
- US 94068618 A [0035]
- US 20190201105 [0035]
- US 94070018 A [0035]
- US 20190205001 [0035]
- US 94062918 A [0035]
- US 20190201112 [0035]
- US 94070418 A [0035]
- US 20190206050 [0035]
- US 94072218 A [0035]
- US 20190200905 [0035]
- US 94074218 A [0035]
- US 20190200906 [0035]
- US 94063618 A [0036]
- US 20190206003 [0036]
- US 94065318 A [0036]
- US 20190201114 [0036]
- US 94066018 A [0036]
- US 20190206555 [0036]
- US 94067918 A [0036]
- US 20190201144 [0036]
- US 94069418 [0036]
- US 20190201119 [0036]
- US 94063418 A [0036]
- US 20190201138 [0036]
- US 94070618 [0036]
- US 20190206561 [0036]
- US 94067518 A [0036]
- US 10849697 B [0036]
- US 94062718 A [0037]
- US 20190201111 [0037]
- US 94063718 A [0037]
- US 20190201139 [0037]
- US 94064218 A [0037]
- US 20190201113 [0037]
- US 94067618 A [0037]
- US 20190201142 [0037]
- US 94068018 A [0037]
- US 20190201135 [0037]
- US 94068318 A [0037]
- US 20190201145 [0037]
- US 94069018 A [0037]
- US 20190201118 [0037]
- US 94071118 A [0037]
- US 20190201120 [0037]
- US 10149683 B [0049]
- US 20180125481 [0049]
- US 8632525 B [0049]
- US 118241 A [0052] [0408]
- US 9072535 B [0052] [0053] [0408]
- WO 2017083125 A [0052]
- WO 2017083126 A [0052]
- WO 2015153642 A [0052]
- US 20170265954 [0052]
- US 10350016 B [0052]
- US 20170265865 [0052]
- US 10631858 B [0052]
- US 20170290586 [0052]
- US 10722233 B [0052]
- US 7524320 B [0053]
- US 5817084 A [0054]
- US 5878193 A [0054]
- US 6132368 A [0055]
- US 20200405301 [0062]
- US 8622274 B [0084]
- US 20160256071 [0084]
- US 20180168625 A [0084]
- US 20180250002 A [0084]
- WO 2018049206 A [0084]
- US 9345481 B [0088] [0274] [0408]
- US 9872722 B [0088]
- US 8991678 B [0137]
- US 10085749 B [0137]
- US 20150324317 [0137]
- US 7143923 B [0150]
- US 7044352 B [0150]
- US 7000818 B [0150] [0408]
- US 6988649 B [0150]
- US 6978921 B [0150]
- US 9171244 B [0172]
- US 20939518 A [0189]
- US 20190201136 [0189]
- US 20140263552 [0274] [0408]
- US 10032719 B [0274]
- US 62817517 A [0274]
- US 10881399 B [0274]
- US 10595887 B [0293]
- US 10456137 B [0392]
- US 5403312 A [0408]
- US 7422139 B [0408]

EP 4 521 595 A2

- US 7464849 B [0408]
- US 7670334 B [0408]
- US 7753245 B [0408]
- US 8393514 B [0408]
- US 343803 A [0408]
- US 7845537 B [0408]
- US 03157308 A [0408]
- US 03187308 A [0408]
- US 7980443 B [0408]
- US 235782 A [0408]
- US 8210411 B [0408]
- US 235972 A [0408]
- US 9050083 B [0408]
- US 249117 A [0408]
- US 8608045 B [0408]
- US 64710009 A [0408]
- US 8220688 B [0408]
- US 89346112 A [0408]
- US 8733613 B [0408]
- US 03664711 A [0408]
- US 8561870 B [0408]
- US 52404912 A [0408]
- US 9101358 B [0408]
- US 80002513 A [0408]
- US 80006713 A [0408]
- US 20070175955 [0408]
- US 20100264194 [0408]
- US 8308040 B [0408]

Non-patent literature cited in the description

- **AMENTA et al.** A New Voronoi-Based Surface Reconstruction Algorithm. *SIGGRAPH*, 1998 [0352]
- **KAZHDAN et al.** Poisson Surface Reconstruction. *Symposium on Geometry Processing*, 2006 [0352]
- IEEE 802.3 Standard. Institute of Electrical and Electronics Engineers (IEEE), December 2008 [0421]
- ATM-MPLS Network Interworking 2.0. ATM Forum, August 2001 [0421]