



(12)

EUROPEAN PATENT APPLICATION

- (43)

Date of publication:
14.05.2025 Bulletin 2025/20
- (51)

International Patent Classification (IPC):
F01D 5/14 (2006.01) F01D 9/04 (2006.01)
- (21)

Application number: 23208306.3
- (52)

Cooperative Patent Classification (CPC):
F01D 5/145; F01D 5/143; F01D 9/041
- (22)

Date of filing: 07.11.2023

<div>(84)</div> <div>Designated Contracting States: AL AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL NO PL PT RO RS SE SI SK SM TR Designated Extension States: BA Designated Validation States: KH MA MD TN</div>	<div>(71)</div> <div>Applicant: PAPIZTURBINE Europe GmbH 35104 Lichtenfels (DE)</div> <div>(72)</div> <div>Inventor: PAPIZ, Juan Manuel 2189 Cruz Alta City, Cordoba Province (AR)</div> <div>(74)</div> <div>Representative: Eisenführ Speiser Patentanwälte Rechtsanwälte PartGmbH Stralauer Platz 34 10243 Berlin (DE)</div>
--	---

(54)

GAS TURBINE AND TURBOPROP ENGINE

- (57)

The invention concerns a turboprop engine (10) comprising a gas turbine assembly (20) with a compressor (22), a combustor (24) and an axial gas turbine (26). The gas turbine (26) comprises a nozzle guide vane (26.1) and a turbine wheel (26.2). The nozzle guide vane (26.1) is arranged between an annular exhaust nozzle (24.3) of a combustion chamber (24.1) of the combustor (24) and the turbine wheel (26.2), the turbine wheel (26.2) being connected to a turbine shaft (28) and the nozzle guide vane (26.1) being arranged to guide hot combustion gases from the combustion chamber (24.1) to turbine blades (26.2.1) of the turbine wheel (26.2). The nozzle guide vane (26.1) comprises guide blades (26.1.3) radially extending between an inner ring (26.1.2) of the
- nozzle guide vane (26.1) and an outer ring (26.1.1) of the nozzle guide vane (26.1), the outer ring (26.1.1) having an inner wall portion (26.1.4) defining a feed gas passage (26.1.5) for feeding the hot combustion gases to the guide blades (26.1.3) of the nozzle guide vane (26.1). A diameter of the feed gas passage (26.1.5) as defined by the inner wall (26.1.4) of the outer ring (26.1.1) initially decreases in the direction of flow of the hot combustion gases causing the feeding gas passage (26.1.5) to narrow in the direction of gas flow resulting an accelerating the gas flow between the inner ring (26.1.2) and the outer ring (26.1.1) of the nozzle guide vane (26.1) due to a Venturi effect.



Fig. 2

Description

[0001] The invention relates to a gas turbine engine and a gas turbine. The invention relates in particular to a nozzle gas vane for a gas turbine of a gas turbine engine, in particular a turboprop engine.

[0002] Gas turbine engines in particular turboprop engines are generally known. A turboprop engine comprises a gas turbine that drives a propeller via a reduction gear. The gas turbine engine comprises a compressor, a combustion chamber and a turbine wheel. The compressor is fed with air from the environment, compresses the air and feeds the compressed air to the combustion chamber. In the combustion chamber, the compressed air is mixed with fuel and the mixture is ignited and combusts. The hot combustion gases then drive a gas turbine that in turn drives the compressor and the propeller.

[0003] A turboprop engine is typically used as an aero engine that creates thrust by means of the propeller. The thrust of the hot combustion gases at the exhaust of the turbine does not significantly contribute to the engine's overall thrust.

[0004] In general, gas turbine engines can comprise an axial compressor or a centrifugal (i.e. radial) compressor. The turbine of the gas turbine engine in most cases is an axial turbine with one or more turbine stages. Turboprop gas turbine engines can have separate turbines for driving the propeller and for driving the compressor. Alternatively, the compressor can be fixed to the same shaft as the turbine for driving the propeller. Then, only one turbine is needed.

[0005] In a gas turbine engine, the compressor feeds high-pressure air to the combustion chamber. The combustion chamber is also known as combustor. In the combustor the compressed air is mixed with fuel and ignited. Thus, the compressed air is heated at constant pressure as the fuel/air mix burns. As it burns the fuel/air mix heats and rapidly expands. The burned mix, i.e. the combustion gases are exhausted from the combustor through the nozzle guide vanes to a turbine wheel.

[0006] The gas turbine can be an axial gas turbine comprising one or more turbine stages with nozzle guide vanes and turbine wheels (also known as turbine vanes). A nozzle guide vane is a stationary component located at the entry of a turbine stage in a gas turbine. The nozzle guide vane's function is to direct and guide the flow of high-velocity hot gases from the combustion chamber onto the turbine blades. The nozzle guide vane also helps to optimize the velocity and pressure of the gases entering the turbine stage, which can improve the efficiency and performance of the engine.

[0007] For larger airplanes, gas turbine engines and turboprop engines are the most secure and efficient aero engines. Gas turbine engines and turboprop engines having a size, weight and power suiting smaller airplanes, however, suffer from a very high consumption and thus are economically not feasible.

[0008] While turboprop engines typically are used for larger airplanes, small airplanes typically are powered by piston engines, for instance air cooled boxer engines providing a power between 100 and 200 kW. While turboprop engines have proven to be very reliable, replacing less reliable piston engines with turboprop engines typically is not feasible, because the efficiency of turboprop engines suffers from downscaling. This results in higher fuel consumption.

[0009] It is therefore an object of the invention to provide a turboprop engine for small airplanes with improved efficiency.

[0010] According to a first aspect, a gas turbine engine, in particular a turboprop engine, with an axial gas turbine is provided, wherein the gas turbine comprises a nozzle guide vane and a turbine wheel. The nozzle guide vane is arranged between an exhaust of a combustion chamber and the turbine wheel. The turbine wheel is connected to a turbine shaft. The nozzle guide vane is arranged to guide hot combustion gases from the combustion chamber to turbine blades of the turbine wheel. According to the invention, the nozzle guide vane comprises nozzle guide blades radially extending between an inner ring of the nozzle guide vane and an outer ring of the nozzle guide vane. The outer ring has an inner diameter that narrows in the direction of gas flow and thus provides a Venturi effect to accelerate the gas flow between the inner ring and the outer ring of the nozzle guide vane.

[0011] Thus, the nozzle guide vane provides a specific geometry of the walls provided by the inner ring and the outer ring and the guide blades extending there between in a radial direction to thus maximize the efficiency of the gas flow towards the turbine blades of the turbine wheel.

[0012] It is noted that the nozzle guide vane is a stator in the hot section of the gas turbine engine and is fundamental for directing the flow of hot combustion gases from the combustion chamber to the turbine wheel.

[0013] In general, the turboprop engine comprises a gas turbine assembly with a compressor, a combustor and an axial turbine wheel. The gas turbine comprises the at least one nozzle guide vane and the at least one turbine wheel. Preferably, the gas turbine comprises a single axial turbine stage with one nozzle guide vane and one turbine wheel.

[0014] The outer ring of the nozzle guide vane has an inner wall portion that defines a feed gas passage for feeding the hot combustion gases to the guide blades of the nozzle guide vane. A diameter of the feed gas passage as defined by the inner wall of the outer ring initially decreases in the direction of flow of the hot combustion gases causing the feeding gas passage to narrow in the direction of gas flow resulting an accelerating the gas flow through the feed gas passage due to a Venturi effect.

[0015] According to a preferred embodiment, the diameter of the inner wall portion of the outer ring increases in a downstream direction - i.e. in the direction of flow of the hot combustion gases - where the guide blades contact the inner wall portion of the outer ring. Accord-

ingly the inner wall of the outer ring has a smallest inner diameter where hot combustion gases are hitting the guide blades during operation of the gas turbine.

[0016] According to a preferred embodiment, an outer diameter of an outer wall portion of the inner ring decreases in a downstream direction where the guide blades contact the outer wall portion of the inner ring. Thus, the distance between the outer wall of the inner ring and the inner wall of the outer ring increases in the direction of gas flow where the guide blades are arranged. This improves the efficiency of the gas turbine because it reduces losses caused by the nozzle guide vane.

[0017] Preferably, the outer ring, the guide blades and the inner ring are an integral part made of metal.

[0018] Preferably, the nozzle guide vane comprises between 16 to 24 guide blades, in particular 20 guide blades. The number of nozzle guide blades preferably is different from the number of turbine blades of the turbine wheel. Preferably, the number of turbine blades is larger than the number of nozzle guide blades. In particular, the number of turbine blades is at least 20%, preferably about 50% larger than the number of nozzle guide blades.

[0019] Preferably, the extension of the nozzle guide blades in the direction of flow of the hot combustion gases is larger than the extension of the turbine blades in the direction of flow of the hot combustion gases. In particular, the extension of the nozzle guide blades in the direction of flow of the hot combustion gases is about 50% to 110% larger than the extension of the turbine blades in the direction of flow of the hot combustion gases. In other words, there are preferably fewer nozzle guide blades than turbine blades but the nozzle guide blades have a longer extension in the direction of flow of the hot combustion gases than the turbine blades.

[0020] According to a preferred embodiment, the inner diameter of the inner wall portion of the outer ring at the entrance of the feed gas passage corresponds to an outer diameter of the annular exhaust nozzle of the combustion chamber of the combustor at the exit of the annular exhaust nozzle.

[0021] According to a further preferred embodiment, a longitudinal extension of the feed gas passage along a longitudinal axis of the gas turbine assembly is about 1.2 to 2.3 times of the extension of the guide blades of the nozzle guide vane along a longitudinal axis of the gas turbine assembly.

[0022] Preferably, the inner diameter of the inner wall portion of the outer ring at the entrance of the feed gas passage is between 140 mm and 170 mm, for instance 155 mm

[0023] According to a second aspect that can be combined with the first aspect, a combustor for a gas turbine assembly is provided. The combustor comprises a plurality of fuel injection nozzles and an annular combustion chamber. The annular combustion chamber comprises an inner space that is enclosed by a combustion chamber wall with an inner wall portion, a front wall portion and an

outer wall portion. The front wall portion closes the combustion chamber at a combustion chamber front end and the inner wall portion and the outer wall portion define an open annular nozzle at the rear side of the combustion chamber. The fuel injection nozzles are circumferentially arranged around the outer wall portion and protrude into the inner space enclosed by the combustion chamber wall.

[0024] According to the invention, the inner wall portion and the outer wall portion are shaped so as to provide that the inner cross-sectional diameter of the annular inner space of the combustion chamber initially decreases (narrows) towards the open end of the combustion chamber nozzle and ultimately widens again, thus causing a Venturi effect where a radial distance between the inner wall portion and the outer wall portion is smallest.

[0025] The Venturi effect created by the annular Venturi nozzle portion of the combustion chamber improves the mass flow exiting from the combustion chamber and is fed to the axial turbine of the gas turbine assembly.

[0026] According to a preferred embodiment of the combustion chamber, the distance of the inner wall portion from a longitudinal axis of the gas turbine assembly initially increases in the direction of a combustion gas flow and then decreases again thus defining an apex that together with the outer wall portion of the combustion chamber wall defines a Venturi nozzle for accelerating the hot combustion exhaust gases and causing a lowered static pressure in the inner space close to the combustion chamber annular nozzle.

[0027] Preferably, the combustion chamber is surrounded by an open space that during operation is filled with compressed air and wherein the outer wall portion narrows towards to an open end of the annular nozzle portion of the combustion chamber. Preferably, holes (orifices) are provided in the narrowing outer wall portion. The holes are placed where during operation a reduced static pressure exists in the inner space, thus allowing air entering from the surrounding open space into the inner space and increasing the mass flow of the hot combustion gases exiting the combustion chamber. This improves the efficiency of the gas turbine assembly.

[0028] According to a preferred embodiment of the combustion chamber, the holes provided in the narrowing outer wall portion have a keyhole shape.

[0029] According to a further preferred embodiment of the combustion chamber, the outer wall portion comprises a generally cylindrical sub-portion in which an annular vortex generating protrusion is arranged, that protrudes inwardly into the inner space enclosed by the combustion chamber wall. The annular vortex generating protrusion improves mixing of fuel and compressed air and provides for an equal and complete combustion, thus improving the efficiency of the gas turbine assembly.

[0030] Preferably, the annular vortex generating protrusion comprises an upstream wall portion facing towards the fuel injection nozzles and a downstream wall portion facing away from the fuel injection nozzles. The

vortex generating holes preferably are arranged in the downstream wall portion. This further improves the efficiency of the gas turbine assembly.

[0031] According to a further preferred embodiment of the combustion chamber, the inner wall portion comprises a frusto-conical shaped wall sub-portion with a diameter that increases towards the annular Venturi nozzles portion of the combustion chamber and provides that the annular free space between the inner wall portion and the outer wall portion becomes narrower, thus causing an acceleration of the hot combustion gases during operation and a decreasing static pressure in the annular free space between the inner wall portion and the outer wall portion.

[0032] Preferably, the frusto-conical shaped wall sub-portion of the inner wall portion is provided with holes allowing compressed air from the surrounding open space entering into the inner space, thus increasing the mass flow of the hot combustion gases exiting the combustion chamber. The increased mass flow further improves the efficiency of the gas turbine assembly.

[0033] According to a preferred embodiment of the combustor, the combustor comprises four fuel injection nozzles that are equally spaced from each other. This arrangement of fuel injection nozzles supports producing a homogeneous stream of hot combustion gases for driving the axial gas turbine of the gas turbine assembly.

[0034] According to a third aspect that can be combined with the first and/or the second aspect, a fuel injection nozzle for a combustion chamber of a gas turbine assembly is provided. The fuel injection nozzle comprises a central fuel duct having a distal end provided with a fuel nozzle. The central fuel duct is configured for feeding fuel from a proximal end of the fuel duct to the fuel nozzle at the distal end of the fuel duct. The fuel injection nozzle further comprises a fuel intake connector and a fuel return connector that both are connected to the proximal end of the fuel duct for feeding pressurized fuel into the fuel duct and allowing the fuel to circulate in an external fuel line. The fuel injection nozzle further comprises a coaxial air duct coaxially surrounding the fuel duct and being configured for providing that fuel exiting at the fuel nozzle at the distal end of the fuel duct is surrounded by an air stream that prevents the fuel from sticking to parts of the fuel injection nozzle. According to the invention, the fuel injection nozzle is provided with a Venturi nozzle formed at the distal end of the air duct surrounding the fuel nozzle of the fuel duct. The Venturi nozzle has an inner diameter that varies over the length of the Venturi nozzle, i.e. in the longitudinal direction of the fuel injection nozzle, and that is larger at the beginning of the Venturi nozzle and at the end of the Venturi nozzle than in the middle of the Venturi nozzle.

[0035] The inventor found that the Venturi nozzle at the end of the air duct and in front of the fuel nozzle at the end of the fuel duct improves vaporization fuel exiting the fuel duct even if the fuel is provided with lower than usual pressure. In prior art fuel injection nozzles, the vaporiza-

tion of fuel is affected if the pressure of the fuel is too low. However, a higher fuel pressure leads to a larger amount of fuel being injected and thus leads a higher fuel consumption.

[0036] According to a preferred embodiment, the fuel injection nozzle comprises a baffle body that is arranged directly in line with the fuel duct in front of the fuel nozzle of the fuel duct. During operation, fuel exiting from the fuel nozzle at the end of the fuel duct hits the baffle body and thus is vaporized even if the pressure in the fuel duct is not high enough to cause vaporizing of the fuel alone. Thus, the baffle body further improves fuel vaporization.

[0037] Preferably, the baffle body has a cone shape with a cone tip facing away from the fuel nozzle and a baffle face facing towards the fuel nozzle. The cone shape of the baffle body supports the Venturi effect of the Venturi nozzle and helps controlling flow separation and forming of a wake downstream of the baffle body.

[0038] Preferably, the baffle body is held by a pin in the middle of the Venturi nozzle at the distal orifice of the air duct. The arrangement of the baffle body in the middle of the Venturi nozzle optimizes the Venturi effect and the acceleration of the injected fuel-air mixture.

[0039] Preferably, the fuel injection nozzle is further configured for adding hydrogen to the fuel-air mixture that is formed by the fuel injection nozzle. In particular, the fuel injection nozzle is configured for enriching the air in the coaxial air duct with 1% to 8% of hydrogen further, thus improving the mixture provided by the fuel injection nozzle.

[0040] The preferably reduced fuel pressure in the fuel duct results in less fuel being injected into the combustion chamber. While this generally improves the efficiency, it also leads to less power provided by the combusted mixture of fuel and air. Adding a small amount of hydrogen to the mixture does not increase the temperature of the combusted fuel mixture but makes the combustion 60% more clean than a prior art combustion.

[0041] The Venturi nozzle with the baffle body in front of the fuel nozzle of the fuel duct improves mixing of the fuel with air even at lower fuel pressures. Additionally adding some amount of hydrogen makes the combustion cleaner and thus reduces air pollution. In combination, a lower fuel consumption and less pollution is achieved by means of the novel fuel injection nozzle.

[0042] Further preferred features and advantages will be apparent from the disclosure of exemplary embodiments. Additional aspects of the present invention will become more readily apparent from the detailed description, particularly when taken together with the drawings.

Figure 1: illustrates an embodiment of a turboprop engine comprising a gas turbine according to the invention;

Figures 2a and 2b: are perspective views of a nozzle guide vane of the gas turbine of

	the turboprop engine according to the invention;		Figure 10d:	is a top view of a fuel injection nozzle;
Figure 3a:	is a front view of the nozzle guide vane according to the invention;	5	Figure 11 a:	is a front view of the fuel injection nozzle of figure 10;
Figure 3b:	is a rear view of the nozzle guide vane according to the invention;		Figure 11b:	is a longitudinal cross-section through the fuel injection nozzle of figure 10 and
Figure 3c:	is a side view of the nozzle guide vane according to the invention;	10	Figure 12:	illustrates the individual parts the fuel injection nozzle of figures 10 and 11 is composed of.
Figure 3d:	is a central cut away view of the nozzle guide vane according to the invention;	15	<p>[0043] As illustrated in figure 1, the main components of a turboprop engine 10 are a gas turbine assembly 20 that can drive a main shaft 30 of a propeller 12 via a reduction gear. The reduction gear comprises a helical reduction gearing 40, a centrifugal clutch 24 and a planetary reduction gear 32.</p>	
Figure 4:	is a perspective view of a combustion chamber;		<p>[0044] The gas turbine engine 20 comprises a compressor 22, for instance a centrifugal compressor. Compressed air provided by the centrifugal compressor 22 is fed into a combustor 24, for instance a combustor with an annular combustion chamber 24.1 with an outlet nozzle 24.3 for the hot exhaust that feeds the hot exhaust to a turbine, for instance an axial turbine 26. The axial turbine 26 drives the centrifugal compressor 22 and - via the planetary reduction gear - the propeller 12.</p>	
Figure 5a:	is a rear view of the combustion chamber of figure 4;	20		
Figure 5b:	is a side view of the combustion chamber of figure 4;	25		
Figure 5c:	is a front view of the combustion chamber of figure 4;	30	<p>[0045] The turboprop engine 10 as shown in figure 1 comprises a gas turbine assembly 20 with a single turbine stage 26. The gas turbine assembly 20 comprises a stationary nozzle guide vane 26.1 and a turbine wheel 26.2 that is connected to a gas turbine shaft 28. The gas turbine shaft 28 is also connected to the centrifugal compressor 22. Accordingly, gas turbine 26 can drive compressor 22 of turboprop engine 10. Turbine shaft 28 is also connected to a reduction gear 32 that in turn is connected to a propeller 12 by means of gas turbine assembly 20.</p>	
Figure 6:	is a longitudinal cross-section through the combustion chamber of figures 4 and 5;	35		
Figure 7:	is a longitudinal cross-section through the turbine shaft, the gas turbine and the combustion chamber of figures 4 and 5;	40	<p>[0046] During operation, the compressor 22 takes air from the environment, compresses the air and pushes the compressed air into the combustion chamber 24.1 wherein the compressed air is mixed with fuel and combusted by a spark. The combustion chamber nozzle 24.3 directs the resulting flow of hot combustion gases to the axial turbine 26. The axial turbine 26 comprises a single turbine stage with the nozzle guide vane 26.1 and the single turbine wheel 26.2. As mentioned above, the turbine wheel 26.2 drives the turbine shaft 28 that is connected to the centrifugal compressor 22 and the planetary reduction gear 32. The rotation speed of the turbine shaft 28 is reduced by the helical reduction gearing 40 and the planetary reduction gear 32 to a fraction in order to provide a rotation speed that is suitable for driving a standard propeller 12.</p>	
Figure 8:	is a longitudinal cross-section similar to figure 7 illustrating the narrowing of the exhaust gas stream at the exit of the combustion chamber and through the axial gas turbine;	45		
Figure 9a and b:	are perspective views of the combustion chamber together with the turbine shaft and the axial gas turbine;	50		
Figure 10a:	is a rear view of a fuel injection nozzle;	55	<p>[0047] A number of improvements contribute to a more efficient turboprop engine providing a power between</p>	
Figure 10b:	is a side view of a fuel injection nozzle;			
Figure 10c:	is a bottom view of a fuel injection nozzle;			

100 kW and 400 kW.

The compressor 22

[0048] The compressor 22 is a centrifugal compressor comprising a centrifugal impeller 22.1, a diffuser 22.2 (not shown) and a collector (not shown). As the air passes through the impeller 22.1, the kinetic and potential energy increase. The diffuser 22.2 converts the air flow's kinetic energy (high velocity) into increased potential energy (static pressure) by gradually slowing (diffusing) the gas velocity. The collector gathers the flow from the diffuser 22.2 discharge annulus and delivers this flow downstream to an open space 23 surrounding the combustor's combustion chamber.

The combustor 24

[0049] Figures 4 to 6 illustrate a first embodiment of a combustor 24, while figures 7 to 9 illustrate a second, alternative embodiment of the combustor 24 with additional holes 24.4.3 in the combustion chamber wall towards the open space 23 surrounding the combustion chamber 24.1.

[0050] The combustor has an annular combustion chamber 24.1. The annular combustion chamber 24.1 is enclosed by a wall 24.2 with an inner wall portion 24.2.1, a front wall portion 24.2.2 and an outer wall portion 24.2.3. The front wall portion 24.2.2 closes the combustion chamber 24.1 at a combustion chamber front end. The inner wall portion 24.2.1 and the outer wall portion 24.2.3 define an open annular nozzle 24.3 at the rear side of the combustion chamber 24.1. Holes 24.4 in the wall 24.2 enclosing the combustion chamber 24.1 allow entering of compressed air from the open space 23 surrounding the combustion chamber into the inner space 24.5 of the combustion chamber. Additional holes 24.4.3 in the combustion chamber wall towards the open space 23 surrounding the combustion chamber 24.1 may improve the efficiency; c.f. figures 7 to 9. The combustion chamber 24.1 is the place where the mixing of the compressed high pressure air and fuel occurs and the mixture is combusted. Since the combustion generates a very high temperature, part of the compressed high pressure air entering the inner space 24.5 of the combustion chamber 24.1 is used to cool down the metal walls 24.2 of the combustion chamber. The purpose of the holes 24.4 is to keep flames of the burning fuel away from the metal walls 24.2 thus keeping the combustion chamber wall temperature under a limit temperature.

[0051] Another purpose of holes in walls of prior art combustion chambers wall is to generate a vortex to make the mixing of compressed air and fuel more efficient. That is why the combustor design is different for each gas turbine engine.

[0052] In the case of the instant turboprop engine 10, the combustion chamber 24.1 must handle a mixture of fuel and air that is fed into the combustion chamber 24.1

by one or more fuel injection nozzles 24.7. With annular combustion chambers, typically multiple fuel injection nozzles 24.7 are provided and arranged around the circumference of the combustion chamber 24.1. Prior art combustion chambers have special holes in the combustion chamber wall around the fuel injection nozzle to make a vortex with the fuel. In the instant turboprop engine the vortex is generated by the fuel injection nozzle itself so the holes of the combustion chamber wall in this area are only to produce an upper vortex that keeps the flame and the heat away from the walls of the combustion chamber.

[0053] Similarly, the other holes 24.4 in the wall of the instant combustion chamber 24.1 are basically provided to allow more air entering the inner space 24.5 of the combustion chamber 24.1 in order to improve the combustion and to keep the heat away from the combustion chamber walls 24.2.

[0054] While the instant turboprop engine 10 can be realized with different kinds of combustion chambers, a combustion chamber 24.1 as disclosed herein is beneficial because it improves the efficiency of the gas turbine assembly 20.

[0055] A beneficial feature of the instant combustor 24 as disclosed herein is the design of the inner wall portion and the outer wall portion in the region of the nozzle at the rear and of the combustion chamber. As is apparent from figures 5 and 6, the inner cross-sectional diameter of the inner space of the combustion chamber - as defined by the radial distance between the inner wall portion and the outer wall portion of the combustion chamber wall - initially decreases (narrows) towards the open end of the combustion chamber nozzle and ultimately widens again, thus causing a Venturi effect where radial distance between the inner wall portion and the outer wall portion is smallest.

[0056] Keyhole shaped orifices (holes) 24.4.1 in the outer wall portion 24.2.3 allow entering of compressed air in the nozzle area of the combustion chamber 24.1. The entering of compressed air as promoted by the Venturi effect caused by the particular shape of the inner wall portion 24.2.1 and the outer wall portion 24.2.3 in the area of the combustion chamber annular nozzle portion 24.3.

[0057] The desired effect is improved by the design of the inner wall portion 24.2.1 of the combustion chamber wall 24.2. As can be seen for instance in figure 4, the distance of the inner wall portion 24.2.1 from the longitudinal axis of the gas turbine assembly 20 initially increases in the direction of a combustion gas flow and then decreases again thus defining an apex 24.6. Thus, together with the shape of the outer wall portion 24.2.3, the Venturi effect is promoted.

[0058] The additional air sucked into the nozzle portion 24.3 of the combustion chamber 24.1 due to the Venturi effect increases the mass flow of air exiting the combustion chamber 24.1 and streaming to the nozzle guide vane 26.1 of the gas turbine stage 26. This is achieved by the shape of the inner wall portion 24.2.1 and the outer

wall portion 24.2.3. The shape provides that the inner cross-sectional diameter of the annular inner space of the combustion chamber 24.1 initially decreases (narrows) towards the open end of the combustion chamber nozzle 24.3 and ultimately widens again, thus causing the aforementioned Venturi effect where the radial distance between the inner wall portion 24.2.1 and the outer wall portion 24.2.3 is smallest.

[0059] The Venturi effect created by the annular Venturi nozzles portion of the combustion chamber improves the mass flow exiting from the combustion chamber and is fed to the axial turbine of the gas turbine assembly, thus improving the efficiency of the gas turbine assembly 20.

[0060] The preferred shape of the combustion chamber's annular nozzle portion 24.3 preferably is achieved by varying the distance of the inner wall portion 24.2.1 from a longitudinal axis of the gas turbine assembly 20 along the longitudinal axis of the gas turbine assembly 20. The distance initially increases in the direction of a combustion gas flow and then decreases again thus defining an apex 24.6 that together with the outer wall portion 24.2.3 of the combustion chamber wall 24.2 defines the Venturi nozzle 24.7.6 for accelerating the hot combustion exhaust gases and for causing a reduced static pressure in inner space 24.5 close to the combustion chamber annular nozzle 24.3.

[0061] The combustion chamber 24.1 is surrounded by the open space 23 that during operation is filled with compressed air. Where the outer wall portion 24.2.3 narrows towards to an open end of the annular nozzle portion 24.3 of the combustion chamber 24.1, orifices or holes 24.4.1 are provided. The holes 24.4.1 are placed where during operation a reduced static pressure exists in the inner space 24.5, thus allowing air entering from the surrounding open space 23 into the inner space 24.5 and increasing the mass flow of the hot combustion gases exiting the combustion chamber 24.1. This improves the efficiency of the gas turbine assembly.

[0062] As mentioned above, the holes 24.4.1 provided in the narrowing outer wall portion 24.2.3 have a keyhole shape.

[0063] Further, the outer wall portion 24.2.3 comprises a generally cylindrical sub-portion 24.2.4 in which an annular vortex generating protrusion 24.2.5 is arranged, that protrudes into the inner space 24.5 enclosed by the combustion chamber wall 24.2. The annular vortex generating protrusion 24.2.5 improves mixing of fuel and compressed air and provides for an equal and complete combustion, thus improving the efficiency of the gas turbine assembly.

[0064] The annular vortex generating protrusion 24.2.5 comprises an upstream wall portion 24.2.6 facing towards the fuel injection nozzles 24.7 and a downstream wall portion 24.2.7 facing away from the fuel injection nozzles 24.7. The vortex generating holes 24.4.2 are arranged in the downstream wall portion 24.2.7. This further improves the efficiency of the gas turbine assembly.

[0065] Further, the inner wall portion 24.2.1 comprises a frusto-conical shaped wall sub-portion 24.2.8 with a diameter that increases towards the annular Venturi nozzles portion 24.3 of the combustion chamber 24.1.

5 The frusto-conical shaped wall sub-portion 24.2.8 provides that the annular free space between the inner wall portion 24.2.1 and the outer wall portion 24.2.3 decreases, thus causing an acceleration of the hot combustion gases during operation and a decreasing static pressure in the annular free space between the inner wall portion 24.2.1 and the outer wall portion 24.2.3. The frusto-conical shaped wall sub-portion 24.2.8 of the inner wall portion 24.2.1 is provided with holes 24.4 allowing compressed air from the surrounding open space 23 entering into the inner space 24.5. This increases the mass flow of the hot combustion gases exiting the combustion chamber 24.1. The increased mass flow further improves the efficiency of the gas turbine assembly. The holes 24.5 in the frusto-conical shaped wall sub-portion 20 24.2.8 of the inner wall portion 24.2.1 are arranged in eight rows along the longitudinal axis of the gas turbine assembly 20. The rows are equally spaced with respect to the circumferential direction of the frusto-conical shaped wall sub-portion 24.2.8. Each row comprises five holes 24.5 of different size and diameter, respectively.

[0066] The combustor comprises four fuel injection nozzles 24.7 that are equally spaced from each other with respect to the circumferential direction of the cylindrical sub-portion 24.2.5. This arrangement of fuel injection nozzles supports producing a homogeneous stream of hot combustion gases for driving the axial gas turbine of the gas turbine assembly. As is apparent from figure 4, the cylindrical sub-portion 24.2.5 of the outer wall portion 24.2.3 is provided with four openings 24.2.9 for mounting the fuel injection nozzles 24.7.

[0067] Further parts of the combustor 24 not shown herein but known to the skilled person in general are an igniter system and spark plugs 24.8. The combustor 24 is provided with four fuel injection nozzles 24.7 equally spaced around the circumference of the front part of the combustion chamber. The combustor 24 is further provided with two spark plugs 24.8 that are arranged downstream of two of the fuel injection nozzles 24.7.

45 The fuel injection nozzle 24.7

[0068] As disclosed above, a combustor 24 of a gas turbine assembly 20 typically is provided with multiple fuel injection nozzles 24.7 as shown in figures 10 to 12. 50 The fuel injection nozzles 24.7 are feeding the fuel, for instance kerosene, into the inner space of the combustion chamber 24.1. The main purpose of each fuel injection nozzle 24.7 is to vaporize the fuel that is injected into the combustion chamber 24.1 with high pressure. Fuel injection nozzles 24.7 may have a central fuel duct 24.7.1 that is surrounded by a coaxial air duct 24.7.2. Fuel is fed into a proximal end of the fuel duct 24.7.1 and can exit the fuel duct at a fuel nozzle 24.7.3 at the distal end of the fuel

duct 24.7.1. Typically, a fuel injection nozzle 24.7 is provided with a fuel intake connector 24.7.4 and a fuel return connector 24.7.5 that both are connected to the proximal end of the fuel duct 24.7.1 for allowing the fuel to circulate and to supply several fuel injection nozzles 24.7 in series.

[0069] The air duct 24.7.2 surrounding the fuel duct 24.7.1 provides that fuel exiting at a fuel nozzle 24.7.3 at the distal end of the fuel duct 24.7.1 is surrounded by an airstream that prevents the fuel from sticking to parts of the fuel injection nozzle 24.7.

[0070] The fuel injection nozzle 24.7 of the instant turboprop engine 10 is provided with a Venturi nozzle 24.7.6 formed at the distal end of the air duct 24.7.2 surrounding the fuel nozzle 24.7.3 of the fuel duct 24.7.1. Directly in line with the fuel duct 24.7.1 in front of the fuel nozzle 24.7.3 of the fuel duct 24.7.1 a baffle body 24.7.7 is arranged. The baffle body 24.7.7 has the shape of an inverted cone and is held by a pin 24.7.8 in the middle of the Venturi nozzle 24.7.6 at the distal orifice of the air duct 24.7.2. The baffle body 24.7.7 has a cone tip 24.7.9 facing away from the fuel nozzle 24.7.3 and a baffle face 24.7.10 facing towards the fuel nozzle 24.7.3.

[0071] The arrangement of a Venturi nozzle 24.7.6 for the fuel injector air stream in front of the fuel nozzle 24.7.3 of the fuel duct 24.7.1 combined with the baffle body 24.7.7 provides for an intense mixing of fuel and air. Even if the fuel is injected with a lower pressure than usual.

[0072] Further, the air in the coaxial air duct 24.7.2 is enriched with 1% to 8% of hydrogen further improving the mixture provided by the fuel injection nozzle 24.7.

[0073] Fuel exiting the fuel nozzle 24.7.3 at the end of the fuel duct 24.7.1 hits the baffle body 24.7.7 and thus is vaporized even if the pressure in the fuel duct 24.7.1 is not high enough to cause vaporization of the fuel alone.

[0074] The baffle body 24.7.7 - shaped as an inverted cone - together with the Venturi shape of the air duct's Venturi nozzle 24.7.6 surrounding the baffle body 24.7.7 in front of the fuel duct nozzle 24.7.3 causes a Venturi effect that accelerates the stream of air mixed with fuel. This further improves vaporization of the fuel.

[0075] The reduced fuel pressure in the fuel duct 24.7.1 results in less fuel being injected into the combustion chamber 24. While this generally improves the efficiency, it also leads to less power provided by the combusted mixture of fuel and air. Adding a small amount of hydrogen to the mixture does not increase the temperature of the combusted fuel mixture but makes the combustion 60% more clean than a prior art combustion.

[0076] The Venturi nozzle 24.7.6 with the baffle body 24.7.7 in front of the fuel nozzle 24.7.3 of the fuel duct 24.7.1 improves mixing of the fuel with air even at lower fuel pressures. Additionally adding some amount of hydrogen makes the combustion cleaner and thus reduces air pollution. In combination, a lower fuel consumption and less pollution is achieved by means of the novel fuel injection nozzle 24.7.

[0077] Preferably, the novel fuel injection nozzle 24.7 is

used in a combustor 24 as disclosed above. As already mentioned, the fuel injection nozzle 24.7 already provides a very good mixing of fuel and air and thus reduces or eliminates the need for causing vortices in the inner space of the combustion chamber 24.1. This in turn improves the efficiency of the combustion chamber 24.1.

[0078] The overall efficiency of the novel combustor 24 with the novel fuel injection nozzle 24.7 is further improved by the design of the combustion chamber nozzle 24.3 that increases the mass stream exiting the combustion chamber 24.1 by drawing air into the combustion chamber nozzle 24.3 as the result of a Venturi effect achieved by the shape of the exhaust nozzle 24.3 of the combustion chamber 24.1.

[0079] It is noted, that both, the particular combustion chamber and the particular fuel injection nozzle can be used separately and implemented independent from each other in different gas turbine engines.

[0080] The instant combustion chamber has a unique design in the general inside shape that uses the inner and external ring to generate a Venturi effect to accelerate the flow to the exit of the combustion chamber making a high-pressure flow of the combustion to be used more efficiently.

[0081] The gas turbine assembly 20 comprises the compressor 22, the combustor 24 and the axial gas turbine 26.

[0082] Gas turbine 26 of gas turbine assembly 20 is a single stage axial gas turbine. Accordingly, gas turbine 26 comprises one static nozzle guide vane assembly 26.1 and one turbine wheel 26.2 that rotates during operation of gas turbine 26. Turbine wheel 26.2 is connected to the turbine shaft 28 that is also connected to the centrifugal impeller 22.1 of compressor 22. Thus, gas turbine 26 can drive the compressor 22. Turbine shaft 28 further is connected to the main shaft 30 to which the propeller 12 is mounted. The drive train from the turbine shaft 28 to the main shaft 30 comprises the helical reduction gearing 40, the centrifugal clutch 34 and the planetary reduction gear 32. The turbine shaft 28 is operatively connected to the centrifugal clutch 34 by the helical reduction gearing 40. The helical reduction gearing 40 comprises a pinion on the turbine shaft 28 and a main gear that is driven by the pinion. An input assembly of the centrifugal clutch 34 is connected to the main gear of the helical reduction gearing 40. The centrifugal clutch 34 provides that turbine shaft 28 only drives the planetary reduction gear 32 and thus propeller 12 if the rotation speed of the gas turbine assembly 20 is high enough.

The axial gas turbine 26

[0083] Regarding the axial gas turbine 26, it is important, that the flow characteristics of the gas turbine 26 are carefully matched with those of the compressor 22 and the combustor 24 to obtain a maximum efficiency and performance of the gas turbine assembly 20 during operation. In case the nozzle guide vane 26.1 would allow to

lower maximum flow, than a back pressure would build up causing the compressor 22 to surge. On the other hand, too high flow through the nozzle guide vane 26.1 might cause the compressor to choke. In either condition a loss of efficiency very rapidly occurs.

[0084] Figures 7 and 8 illustrate how the combustor 24, the guide vane 26.1 and the turbine blades 26.2.1 are arranged with respect to each other (see figure 7) and how the hot exhaust gases are guided by the annular Venturi nozzle's portion of the combustion chamber 24.3, the nozzle guide vane 26.1 and the turbine blades 26.2.1. Since the free space defined by the combustion chamber 24.3, the nozzle guide vane 26.1 and the turbine blades 26.2.1 narrows in the downstream direction, the hot exhaust gases are accelerated.

[0085] Regarding the axial gas turbine 26, it is noted, that the guide blades 26.1.3 of nozzle guide vane 26.1 have a cross section corresponding to an airfoil shape. Passages between adjacent guide blades 26.1.3 form a convergent duct. The guide blades 26.1.3 are arranged between the outer ring 26.1.1 and the inner ring 26.1.2 in a manner that allows for expansion of the hot combustion gases flowing between the guide blades 26.1.3.

[0086] Similarly, the turbine blades 26.2.1 also have cross section with an airfoil shape. The turbine blades 26.2.1 are designed to provide passages between adjacent turbine blades 26.2.1 that give a steady acceleration of the flow of hot combustion gases up to where the area between the turbine blades 26.2.1 is smallest and the velocity of the hot combustion gases is high enough as required at the exit to produce the required degree of reaction.

The nozzle guide vane 26.1 of the axial gas turbine 26

[0087] The axial gas turbine 26 comprises an improved nozzle guide vane 26.1 that directs the stream of hot combustion gases towards turbine blades of turbine wheel 26.2. As pointed out above, in the embodiment disclosed herein, the axial gas turbine 26 has a single turbine stage, i.e. only one turbine wheel.

[0088] The improved nozzle guide vane 26.1 comprises an outer ring 26.1.1, an inner ring 26.1.2 and guide blades 26.1.3 extending between the inner ring 26.1.2 and the outer ring 26.1.1 in a radial direction; see figures 2 and 3. The guide blades 26.1.3 of nozzle guide vane 26.1 redirect the flow of hot combustion gases coming out of the combustion chamber's annular nozzle 24.3 and gives a spin to the stream of hot combustion gases in the direction of the rotation of the turbine blades.

[0089] The outer ring 26.1.1 has an inner wall portion defining a feed gas passage 26.1.5 for feeding the hot combustion gases to the guide blades of the nozzle guide vane 26.1.

[0090] The diameter of the feed gas passage 26.1.5 as defined by the inner wall 26.1.4 of the outer ring 26.1.1 initially decreases in the direction of flow of the hot combustion gases. This has the effect that the stream

of hot combustion gases is accelerated prior to reaching the guide blades 26.3. This implies, that the outer ring 26.1.1 protrudes with respect to the guide blades 26.1.3 against the direction of flow of the hot combustion gases.

5 As can be taken from figure 3c, the longitudinal extension of the outer ring 26.1.1 - i.e. the extension of the outer ring in the direction of air flow or in the longitudinal direction of shaft 28 - is 1,5 to 3 times larger than the extension of the inner ring 26.1.2 and the extension of the guide blades 10 26.1.3 in the longitudinal direction. Accordingly, a longitudinal extension of the feed gas passage along a longitudinal axis of the gas turbine assembly is about 1,2 to 2,3 times of the extension of the guide blades of the nozzle guide vane along a longitudinal axis of the gas turbine assembly.

15 **[0091]** The diameter of the inner wall portion of the outer ring 26.1.1 increases where the guide blades 26.1.3 contact the inner wall portion of the outer ring 26.1.1. Accordingly the inner wall of the outer ring 20 26.1.1 has a smallest inner diameter where hot combustion gases are hitting the guide blades 26.1.3 during operation of the gas turbine 26.

[0092] An outer diameter of an outer wall portion of the inner ring 26.1.2 decreases where the guide blades 25 26.1.3 contact the outer wall portion of the inner ring 26.1.2. Thus, the distance between the outer wall 26.1.6 of the inner ring 26.1.2 and the inner wall 26.1.4 of the outer ring 26.1.1 increases in the direction of gas flow where the guide blades 26.1.3 are arranged. This 30 improves the efficiency of the gas turbine 26 because it reduces losses caused by the nozzle guide vane 26.1.

[0093] The outer ring 26.1.1, the guide blades 26.1.3 and the inner ring 26.1.2 are an integral part made of metal.

35 **[0094]** The nozzle guide vane 26.1 comprises 20 guide blades 26.1.3. The number of nozzle guide blades preferably is different from the number of turbine blades 26.2.1 of the turbine wheel 26.2. Preferably, the number of turbine blades 26.2.1 of the turbine wheel 26.2 is larger 40 than the number of nozzle guide blades 26.1.3. In particular, the number of turbine blades 26.2.1 of the turbine wheel 26.2 is at least 20%, preferably about 50% larger than the number of nozzle guide blades 26.1.3.

[0095] Preferably, the extension of the nozzle guide blades 26.1.3 in the direction of flow of the hot combustion gases is larger than the extension of the turbine blades 26.2.1 of the turbine wheel 26.2 in the direction of flow of the hot combustion gases. In particular, the extension of the nozzle guide blades 26.1.3 in the direction of flow of the hot combustion gases is about 50% to 110% larger than the extension of the turbine blades 26.2.1 of the turbine wheel 26.2 in the direction of flow of the hot combustion gases. In other words, there are preferably less nozzle guide blades 26.1.3 than turbine blades 26.2.1 but the nozzle guide blades 26.1.3 have a longer extension in the direction of flow of the hot combustion gases than the turbine blades 26.2.1. 9. 50

[0096] The inner diameter of the inner wall portion of

the outer ring 26.1.1 at the entrance of the feed gas passage 26.1.5 corresponds to an outer of the annular exhaust nozzle 24.3 of the combustion chamber 24.1 of the combustor 24 at the exit of the annular exhaust nozzle 24.3.

[0097] The inner diameter of the inner wall portion of the outer ring at the entrance of the feed gas passage is between 140 mm and 170 mm, for instance 155 mm.

[0098] The arrangement of the nozzle guide vane 26.1 between the annular Venturi nozzle's portion of the combustion chamber 24 and the turbine blades 26.2.1 is illustrated in figure 7.

[0099] Regarding the combustor 24, an improved fuel injection nozzle 24.7 and an improved combustion chamber 24.1 are provided. For improving the gas turbine assembly 20, an improved nozzle guide vane 26.1 and a self-lubricating turbine main shaft 28 are provided. These improvements may be implemented independently from each other, i.e. the improved fuel injection nozzle or the improved combustion chamber or the improved nozzle guide vane or the self-lubricating turbine main shaft or a combination thereof may be implemented with any known or future gas turbine engine.

Reference numerals

[0100]

10	turboprop engine
12	propeller
14	air intake
20	gas turbine assembly
22	compressor of the gas turbine assembly
22.1	impeller
22.2	diffuser
23	open space surrounding the combustor's combustion chamber
24	combustor
24.1	combustion chamber of gas turbine assembly
24.2	combustion chamber wall
24.2.1	inner wall portion of the combustion chamber wall
24.2.2	front wall portion of the combustion chamber wall
24.2.3	outer wall portion of the combustion chamber wall
24.2.4	cylindrical sub-portion of the outer wall portion
24.2.5	annular vortex generating protrusion
24.2.6	upstream wall portion of the annular vortex generating protrusion
24.2.7	downstream wall portion of the annular vortex generating protrusion
24.2.8	frusto-conical shaped wall sub-portion of the inner wall portion
24.2.9	opening for mounting a fuel injection nozzle
24.3	annular Venturi nozzles portion of the com-

24.4	bustion chamber
24.4.1	holes in the combustion chamber wall
24.4.2	holes in the annular Venturi nozzle portion of the combustion chamber
24.4.3	holes in the vortex generating protrusion
24.5	additional holes in the combustion chamber wall
24.6	inner space of the combustion chamber
24.7	apex of the inner combustion chamber wall
24.7.1	fuel injection nozzle
24.7.2	fuel duct of the fuel injection nozzle
24.7.3	air duct of the fuel injection nozzle
24.7.4	fuel nozzle of the fuel injection nozzle
24.7.5	fuel intake connector
24.7.6	fuel return connector
24.7.7	Venturi nozzle
24.7.8	baffle body
24.7.9	pin for holding the baffle body
24.7.10	cone tip of the baffle body
24.8	baffle face of the baffle body
26	spark plug
26.1	axial gas turbine stage of the gas turbine assembly
26.1.1	nozzle gas vane of the axial gas turbine
26.1.2	outer ring of the nozzle gas vane
26.1.3	inner ring of the nozzle gas vane
26.1.4	guide blades of the nozzle gas vane
26.1.5	inner wall of the outer ring of the nozzle gas vane
26.1.6	feed gas passage
26.2	outer wall of the inner ring of the nozzle gas vane
26.2.1	turbine wheel of the axial gas turbine
28	turbine blade
28.1	gas turbine shaft
30	shaft tunnel for the gas turbine shaft
32	main shaft, propeller shaft
34	planetary reduction gear
36	centrifugal clutch
38	starter/generator
40	starter gearbox
40	helical reduction gearing

Claims

1. Turboprop engine (10) comprising a gas turbine assembly (20) with a compressor (22), a combustor (24) and an axial gas turbine (26),

wherein the gas turbine (26) comprises a nozzle guide vane (26.1) and a turbine wheel (26.2), wherein the nozzle guide vane (26.1) is arranged between an annular exhaust nozzle (24.3) of a combustion chamber (24.1) of the combustor (24) and the turbine wheel (26.2), the turbine wheel (26.2) being connected to a turbine shaft (28) and the nozzle guide vane (26.1) being arranged to guide hot combustion gases

- from the combustion chamber (24.1) to turbine blades (26.2.1) of the turbine wheel (26.2), wherein the nozzle guide vane (26.1) comprises guide blades (26.1.3) radially extending between an inner ring (26.1.2) of the nozzle guide vane (26.1) and an outer ring (26.1.1) of the nozzle guide vane (26.1), the outer ring (26.1.1) having an inner wall portion (26.1.4) defining a feed gas passage (26.1.5) for feeding the hot combustion gases to the guide blades (26.1.3) of the nozzle guide vane (26.1), wherein a diameter of the feed gas passage (26.1.5) as defined by the inner wall (26.1.4) of the outer ring (26.1.1) initially decreases in the direction of flow of the hot combustion gases causing the feeding gas passage (26.1.5) to narrow in the direction of gas flow that causes an acceleration of the gas flow between the inner ring (26.1.2) and the outer ring (26.1.1) of the nozzle guide vane (26.1) due to a Venturi effect.
2. Turboprop engine according to claim 1, wherein the diameter of the inner wall portion (26.1.4) of the outer ring (26.1.1) increases in a downstream direction where the guide blades (26.2.1) contact the inner wall portion (26.1.4) of the outer ring (26.1.1).
 3. Turboprop engine according to claim 1 or 2, wherein an outer diameter of an outer wall portion (26.1.6) of the inner ring (26.1.2) decreases in a downstream direction where the guide blades (26.2.1) contact the outer wall portion (26.1.6) of the inner ring (26.1.2).
 4. Turboprop engine according to at least one of claims 1 to 3, wherein the outer ring (26.1.1), the guide blades (26.1.3) and the inner ring (26.1.2) are an integral part made of metal.
 5. Turboprop engine according to at least one of claims 1 to 4, wherein the nozzle guide vane (26.1) comprises between 16 to 24 guide blades (26.1.3), in particular 20 guide blades (26.1.3).
 6. Turboprop engine according to at least one of claims 1 to 5, wherein the number of turbine blades (26.2.1) of the turbine wheel (26.2) is larger than the number of nozzle guide blades (26.1.3).
 7. Turboprop engine according to claim 6, wherein the number of turbine blades (26.2.1) of the turbine wheel (26.2) is at least 20%, preferably about 50% larger than the number of nozzle guide blades (26.1.3).
 8. Turboprop engine according to at least one of claims 1 to 7, wherein the extension of the nozzle guide blades (26.1.3) in the direction of flow of the hot combustion gases is larger than the extension of the turbine blades (26.2.1) of the turbine wheel (26.2) in the direction of flow of the hot combustion gases.
 9. Turboprop engine according to claim 8, wherein the extension of the nozzle guide blades (26.1.3) in the direction of flow of the hot combustion gases is about 50% to 110% larger than the extension of the turbine blades (26.2.1) of the turbine wheel (26.2) in the direction of flow of the hot combustion gases.
 10. Turboprop engine according to at least one of claims 1 to 9, wherein the inner diameter of the inner wall portion (26.1.4) of the outer ring (26.1.1) at the entrance of the feed gas passage (26.1.5) corresponds to an outer diameter of the annular exhaust nozzle (24.3) of the combustion chamber (24.1) of the combustor (24) at the exit of the annular exhaust nozzle (24.3).
 11. Turboprop engine according to at least one of claims 1 to 10, wherein a longitudinal extension of the feed gas passage (26.1.5) along a longitudinal axis of the gas turbine assembly (20) is about 1,2 to 2,3 times of the extension of the guide blades (26.1.3) of the nozzle guide vane (26.1) along a longitudinal axis of the gas turbine assembly (20).
 12. Turboprop engine according to at least one of claims 1 to 11, wherein inner diameter of the inner wall portion (26.1.4) of the outer ring (26.1.1) at the entrance of the feed gas passage (26.1.5) is between 140 mm and 170 mm, in particular 155 mm.




Fig. 1 26.2

26.1



Fig. 2




Fig. 3




Fig. 4




Fig. 5




Fig. 6




Fig. 7 24.5 24.2.1




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12



EUROPEAN SEARCH REPORT

Application Number

EP 23 20 8306

DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	US 2021/079799 A1 (VITT PAUL HADLEY [US] ET AL) 18 March 2021 (2021-03-18)	1-4, 8-12	INV.
Y	* paragraphs [0027], [0034], [0035], [0045] - [0047], [0056], [0066], [0067]; figures 1, 2, 5 *	5-7	F01D5/14 F01D9/04
X	US 8 393 870 B2 (NASH TIMOTHY CHARLES [US]; O'HEARN JASON L [US] ET AL.) 12 March 2013 (2013-03-12)	1-3, 8-12	
Y	* columns 3-6; figures 2, 6A *	5-7	
Y	EP 3 919 733 A1 (RAYTHEON TECH CORP [US]) 8 December 2021 (2021-12-08)	5-7	
	* paragraphs [0022], [0056], [0057] *		
A	US 2016/290168 A1 (KARAFILLIS APOSTOLOS PAVLOS [US] ET AL) 6 October 2016 (2016-10-06)	1-12	
	* paragraph [0021]; figures 1, 2, 4-7 *		
A	US 2020/378302 A1 (TEETS JOSEPH MICHAEL [US]) 3 December 2020 (2020-12-03)	1	TECHNICAL FIELDS SEARCHED (IPC)
	* paragraphs [0016] - [0023]; figures 1, 6 *		F01D
The present search report has been drawn up for all claims			
Place of search		Date of completion of the search	Examiner
Munich		28 March 2024	Chatziapostolou, A
CATEGORY OF CITED DOCUMENTS		T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document	
X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document			

EPO FORM 1503 03.82 (P04C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 23 20 8306

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

28-03-2024

10

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 2021079799 A1	18-03-2021	CN 112483192 A	12-03-2021
		US 2021079799 A1	18-03-2021

US 8393870 B2	12-03-2013	EP 2428643 A1	14-03-2012
		US 2012057981 A1	08-03-2012

EP 3919733 A1	08-12-2021	EP 3919733 A1	08-12-2021
		US 2021381431 A1	09-12-2021
		US 2023407817 A1	21-12-2023

US 2016290168 A1	06-10-2016	BR 102016006218 A2	25-10-2016
		CA 2924169 A1	01-10-2016
		CN 106050315 A	26-10-2016
		EP 3075967 A1	05-10-2016
		JP 2016194293 A	17-11-2016
		US 2016290168 A1	06-10-2016

US 2020378302 A1	03-12-2020	US 2020378302 A1	03-12-2020
		US 2023392547 A1	07-12-2023

15

20

25

30

35

40

45

50

55

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82