

(19)



(11)

EP 4 682 434 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
21.01.2026 Bulletin 2026/04

(51) International Patent Classification (IPC):
F24F 7/003 ^(2021.01) **F24F 8/108** ^(2021.01)
F24F 11/00 ^(2018.01)

(21) Application number: **25186252.0**

(52) Cooperative Patent Classification (CPC):
F24F 8/108; F24F 7/003; F24F 11/0001;
F24F 8/158; F24F 8/167; F24F 8/22; F24F 2110/10;
F24F 2110/20; F24F 2110/50

(22) Date of filing: **30.06.2025**

(84) Designated Contracting States:
**AL AT BE BG CH CY CZ DE DK EE ES FI FR GB
GR HR HU IE IS IT LI LT LU LV MC ME MK MT NL
NO PL PT RO RS SE SI SK SM TR**

Designated Extension States:

BA

Designated Validation States:

GE KH LA MA MD TN

(30) Priority: **18.07.2024 TW 113126977**

(71) Applicant: **Microjet Technology Co., Ltd.**
Hsinchu (TW)

(72) Inventors:


- **Mou, Hao-Jan**
Hsinchu (TW)
- **Wu, Chin-Chuan**
Hsinchu (TW)
- **Huang, Chi-Feng**
Hsinchu (TW)

(74) Representative: **Uexküll & Stolberg**
Partnerschaft von
Patent- und Rechtsanwälten mbB
Beselerstraße 4
22607 Hamburg (DE)

(54) MOUNTABLE FAN FILTER ASSEMBLY

(57) A mountable fan filter assembly used in an indoor air cleaning network mechanism is provided and includes a detector (1) and a unit main part (2). The unit main part (2) is built-in and suspended in the indoor field (A) and comprises an air guiding fan (21), a filter component (22), a driving controller (23) and a flow guiding pathway (24). The flow guiding pathway (24) is horizontally parallel to and separated from the filter duct (24b), and the air guiding fan (21) and the filter component (22)

are arranged under the filter duct (24b). The gas detector (1) controls the actuation operation of the air guiding fan (21) through the Internet of Things communication. Consequently, air in the indoor field (A) is introduced into the filter duct through the circulating return air port (24a), and air pollution is filtered and purified for multiple cycles to implement circulation filtration and purification treatment in real time and prevent the backflow of the filtered gas.

**FIG. 1A****EP 4 682 434 A1**

Description

FIELD OF THE INVENTION

[0001] The present disclosure relates to a mountable fan filter assembly, and more particularly to a mountable fan filter assembly for implementing air pollution detection and complete purification in an indoor field.

BACKGROUND OF THE INVENTION

[0002] Suspended particles are defined as the solid particles or droplets contained in the air. Due to their extremely fine size, the suspended particles may enter the lungs of human body through the nasal hair in the nasal cavity easily, causing inflammation in the lungs, asthma or cardiovascular disease. If other pollutant compounds are attached to the suspended particles, it will further increase the harm to the respiratory system. In recent years, the issue of air pollution has been increasingly severe, especially with consistently high concentrations of suspended particles (e.g., PM_{2.5}). Therefore, the monitoring to the concentration of the gas suspended particles is taken more and more seriously. However, the gas flows unstably due to the variable wind direction and the air volume, and the general gas-quality monitoring station is located in a fixed place. Under this circumstance, it is impossible for people to check the concentration of suspended particles in current environment.

[0003] Furthermore, in recent years, modern people are placing increasing importance on the quality of the air in their surroundings. For example, carbon monoxide, carbon dioxide, volatile organic compounds (VOC), PM_{2.5}, nitric oxide, sulfur monoxide and even the suspended particles contained in the air are exposed in the environment to affect the human health, and even endanger the life seriously. Therefore, the quality of environmental air has attracted the attention of various countries. At present, how to detect the air quality and avoid the harm is a crucial issue that urgently needs to be solved.

[0004] In order to confirm the quality of the air, it is feasible to use a gas sensor to detect the air surrounding in the environment. If the detection information can be provided in real time to warn the people in the environment, it is helpful of avoiding the harm and facilitates the people to escape the hazard immediately, preventing the hazardous gas exposed in the environment from affecting the human health and causing the harm. Therefore, it is considered a valuable application to use a gas sensor detecting the air in the surrounding environment.

[0005] In addition, it is difficult to have the surveillance and control the indoor air quality. Besides the outdoor air quality, the indoor air-conditioning conditions and the pollution sources are the major factors affecting the indoor air quality. It is necessary to intelligently and quickly detect indoor air pollution sources in various indoor fields, effectively remove the indoor air pollution to form a clean

and safe breathing gas state, and monitor indoor air quality in real time anytime, anywhere. Certainly, if the concentration of the suspended particles in the indoor field is strictly controlled according to the "clean room" standard, it allows avoiding the introduction, generation and retention of suspended particles, and the temperature and humidity in the indoor field can be controlled within the required range, and thus, the indoor field can meet the clean room requirements for safe breathing.

[0006] Therefore, it is a main subject in the present disclosure to develop a mountable fan filter assembly which provides a solution of detecting the indoor air quality and solving the problem of air pollution, so that the indoor field can meet the clean room requirements, and the impact and injury for human health caused by the gas hazards in the environment can be avoided.

SUMMARY OF THE INVENTION

[0007] One object of the present disclosure is to provide a mountable fan filter assembly for implementing air pollution detection and complete purification in the space of an indoor field. The mountable fan filter assembly is equipped with at least one gas detector, at least one air guiding fan, at least one filter component, a driving controller and a flow guiding pathway which is design without piping. Moreover, the flow guiding pathway is fluidly communicated with a circulating return air port and a filter duct, the circulating return air port and filter duct are fluidly communicated with the indoor field, and the at least one air guiding fan and the at least one filter component are arranged under the filter duct. The gas detector is electrically connected to the driving controller and connected to a networked cloud computing service device of the indoor air cleaning network mechanism to form an intelligent linkage system. At this time, the gas detector receives a control instruction from the networked cloud computing service device of the indoor air cleaning network mechanism through an Internet of Things communication, and controls actuation operation of the air guiding fan, so that air in the indoor field is introduced through the circulating return air port and passed the flow guiding pathway into the filter duct. In that, air pollution is filtered and purified through the at least one filter component under the filter duct, and the filtered air is introduced into the indoor field for multiple cycles, so as to implement circulation filtration and purification treatment in real time, prevent the backflow of the filtered gas effectively, and achieve complete clean room treatment. At the same time, the air pollution in the space of the indoor field is detected by intelligently comparing the ambient air quality status, and the air guiding fan is instantly controlled to adjust the air flow volume according to the air quality, thereby effectively adjusting the energy-saving efficiency of the operation of the mountable fan filter assembly. Consequently, the air flow volume noise reaches zero specification value, thereby achieving the ultimate environmental protection of balanced

energy saving and power saving. The present disclosure includes the industrial applicability and the inventive steps.

[0008] In accordance with an aspect of the present disclosure, a mountable fan filter assembly used in an indoor air cleaning network mechanism is provided, and includes at least one gas detector and a unit main part. The at least one gas detector is arranged in an indoor field for detecting air pollution information and temperature and humidity information of gas. The unit main part is built-in and suspended in the indoor field and comprises at least one air guiding fan, at least one filter component, a driving controller and a flow guiding pathway. The flow guiding pathway is fluidly communicated with a circulating return air port and a filter duct, the circulating return air port and filter duct are fluidly communicated with the indoor field. The flow guiding pathway is horizontally parallel to and separated from the filter duct. Wherein, the at least one air guiding fan and the at least one filter component are arranged under the filter duct. Moreover, the at least one gas detector is electrically connected to the driving controller. The at least one gas detector receives a control instruction and transmits it to the driving controller through an Internet of Things communication, so as to control the driving controller to enable an actuation operation of the at least one air guiding fan. Consequently, air in the indoor field is introduced through the circulating return air port and passed the flow guiding pathway into the filter duct. In that, air pollution is filtered and purified through the at least one filter component under the filter duct, and the filtered air is introduced into the indoor field for multiple cycles, so as to implement circulation filtration and purification treatment in real time, prevent the backflow of the filtered gas effectively, and achieve complete clean room treatment.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009]

FIG. 1A is a schematic view illustrating a mountable fan filter assembly according to an embodiment of the present disclosure;

FIG. 1B is a schematic view illustrating the mountable fan filter assembly implemented in an indoor field according to the embodiment of the present disclosure;

FIG. 2 is a schematic cross-sectional view illustrating a filter component of the mountable fan filter assembly according to the embodiment of the present disclosure;

FIG. 3A is a schematic perspective view illustrating a gas detector according to the embodiment of the present disclosure;

FIG. 3B is a schematic perspective view illustrating the gas detector according to the embodiment of the present disclosure and taken from another perspective;

FIG. 3C is a schematic perspective view illustrating the gas detection module installed inside the gas detector according to the embodiment of the present disclosure;

FIG. 4A is a schematic perspective view (1) illustrating a gas detection main part according to the embodiment of the present disclosure;

FIG. 4B is a schematic perspective view (2) illustrating the gas detection main part according to the embodiment of the present disclosure;

FIG. 4C is an exploded view illustrating the gas detection device according to the embodiment of the present disclosure;

FIG. 5A is a schematic perspective view (1) illustrating a base according to the embodiment of the present disclosure;

FIG. 5B is a schematic perspective view (2) illustrating the base according to the embodiment of the present disclosure;

FIG. 6 is a schematic view (3) illustrating the base according to the embodiment of the present disclosure;

FIG. 7A is a schematic exploded view illustrating a combination of a piezoelectric actuator and the base according to the embodiment of the present disclosure;

FIG. 7B is a schematic perspective view illustrating the combination of the piezoelectric actuator and the base according to the embodiment of the present disclosure;

FIG. 8A is a schematic exploded view (1) illustrating the piezoelectric actuator according to the embodiment of the present disclosure;

FIG. 8B is a schematic exploded view (2) illustrating the piezoelectric actuator according to the embodiment of the present disclosure;

FIG. 9A is a schematic cross-sectional view (1) illustrating an action of the piezoelectric actuator according to the embodiment of the present disclosure;

FIG. 9B is a schematic cross-sectional view (2) illustrating an action of the piezoelectric actuator according to the embodiment of the present disclosure;

FIG. 9C is a schematic cross-sectional view (3) illustrating an action of the piezoelectric actuator according to the embodiment of the present disclosure;

FIG. 10A is a schematic cross-sectional view (1) illustrating the gas detection main part according to the embodiment of the present disclosure;

FIG. 10B is a schematic cross-sectional view (2) illustrating the gas detection main part according to the embodiment of the present disclosure;

FIG. 10C is a schematic cross-sectional view (3) illustrating the gas detection main part according to the embodiment of the present disclosure; and FIG. 11 is a schematic diagram illustrating a com-

munication transmission of the gas detector according to the embodiment of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0010] The present disclosure will now be described more specifically with reference to the following embodiments. It is to be noted that the following descriptions of preferred embodiments of this invention are presented herein for purpose of illustration and description only. It is not intended to be exhaustive or to be limited to the precise form disclosed.

[0011] Please refer to FIG. 1A and FIG. 1B. The present disclosure provides a mountable fan filter assembly used in an indoor air cleaning network mechanism. In the embodiment, the mountable fan filter assembly is a fan filter unit (FFU), but not limited to. The mountable fan filter assembly comprising at least one gas detector 1 and a unit main part 2. The at least one gas detector 1 is arranged in an indoor field A for detecting air pollution information and temperature and humidity information of gas. The unit main part 2 is built-in and suspended in the indoor field A. The unit main part 2 comprises at least one air guiding fan 21, at least one filter component 22, a driving controller 23 and a flow guiding pathway 24. In the embodiment, the flow guiding pathway 24 is fluidly communicated with a circulating return air port 24a and a filter duct 24b, and the circulating return air port 24a and filter duct 24b are fluidly communicated with the indoor field A. The at least one air guiding fan 21 and the at least one filter component 22 are arranged under the filter duct 24b. The at least one gas detector 1 is electrically connected to the driving controller 23. Wherein, the at least one gas detector 1 receives a control instruction and transmits it to the driving controller 23 through an Internet of Things communication, so as to control the driving controller 23 to enable an actuation operation of the at least one air guiding fan 21, so that air in the indoor field A is introduced through the circulating return air port 24a and passed the flow guiding pathway 24 into the filter duct 24b. In the embodiment, the flow guiding pathway 24 is horizontally parallel to and separated from the filter duct 24b, and the circulating return air port 24a is longitudinally parallel to and separated from the filter duct 24b. In that, air pollution is filtered and purified through the at least one filter component 22 under the filter duct 24b, and the filtered air is introduced into the indoor field A for multiple cycles, so as to implement circulation filtration and purification treatment in real time, prevent the backflow of the filtered gas effectively, and achieve complete clean room treatment.

[0012] Notably, in the embodiment, the mountable fan filter assembly is used for implementing air pollution detection and complete purification in the indoor field A, which is built-in and suspended in the indoor field A without piping, so as to implement ventilation. In this embodiment, when the mountable fan filter assembly

enable the actuation operation for ventilation, a positive pressure greater than 0 Pa is maintained in the space of the indoor field A to prevent the air pollution of the outdoor field B from entering the indoor field A. Please refer to FIG. 1A, the flow guiding pathway 24 is horizontally parallel to and separated from the filter duct 24b, and the circulating return air port 24a is longitudinally parallel to and separated from the filter duct 24b, so as to reduce the backflow of the filtered gas and achieve complete clean room treatment. In the embodiment, the clean room level of the indoor field A is ZAPClean Room 1~12. In some embodiments, the air pollution information of the indoor field A and the outdoor field is air pollution data of carbon dioxide (CO₂), and ventilation is performed to achieve a zero difference of carbon dioxide (CO₂) between the indoor field A and the outdoor field B. In other embodiments, the mountable fan filter assembly is a fresh air fan, a full heat exchanger, or a heating, ventilation and air conditioning (HVAC), but not limited to.

[0013] Please refer to FIG. 1B. The mountable fan filter assembly is used in an indoor air cleaning network mechanism. The indoor air cleaning network mechanism includes a plurality of gas detectors 1, at least one gas molecule control hardware device and a networked cloud computing service device 3. The plurality of detectors 1 are arranged in the indoor field A and the outdoor field B for detecting air pollution information and temperature and humidity information of gas. In the embodiment, the indoor field A comprises at least one gas introducing opening C1 and at least one gas discharging opening C2. The at least one gas molecule control hardware device includes the at least one mountable fan filter assembly, at least one mountable gas exchange device 4 disposed corresponding to the gas introducing opening C1, at least one purifier 5, at least one exhaust device 6 disposed corresponding to the gas discharging opening C2, at least one extractor hood system 7 disposed corresponding to the gas discharging opening C2, at least one air conditioning device 8, at least one vacuum cleaner 9 and at least one dehumidifier 10 disposed in the indoor field A. In some embodiments, the gas molecule control hardware device includes at least one detector 1, at least one air guiding fan 21, at least one filter component 22 and at least one driving controller 23. The gas detector 1 is electrically connected to the driving controller 23. In the embodiment, the networked cloud computing service device 3 receives the air pollution information and the temperature and humidity information of the indoor field A and the outdoor field B detected by the gas detector 1 through the Internet of Things communication, stores and constructs an air pollution big data database accordingly, and intelligently selects to issue the control instruction to the detector 1, so as to control the driving controller 23 to enable the actuation operation of the air guiding fan 21. Consequently, air in the indoor field A is ventilated, the temperature and the humidity are adjusted, and air pollution is guided through the filter component 22 for multiple cycles of purification and complete

clean room treatment, so as to achieve complete clean room treatment, and the gas detector 1 externally transmits the air pollution information and the temperature and humidity information in the indoor field A.

[0014] In the embodiment, the at least one gas detector 1 is arranged in an indoor field A and an outdoor field B to detect air pollution information. The at least one gas detector 1 also outputs the air pollution information through Internet of Things (IoT) communication. Notably, in the embodiment, the gas detector 1 includes a gas detection module disposed therein. Please refer to FIG. 3A and FIG. 3B. Preferably but not exclusively, the gas detector 1 is formed by a type of structure including an external power terminal, which can be directly inserted into the power interface in the indoor field A to start the operation of detecting air pollution. In an embodiment, as shown in FIG. 3C, a type of the gas detection module without an external power terminal is directly constructed on a gas molecule control hardware device (e.g., the mountable fan filter assembly, the mountable gas exchange device 4, the purifier 5, the exhaust device 6, the extractor hood system 7, the air conditioning device 8, the vacuum cleaner 9 and the dehumidifier 10) and connected to a driving controller 23. A control instruction is received for the driving controller 23 to control the power supply of the gas molecule control hardware device and control actuation operation of the air guiding fan 21.

[0015] In the embodiment, Internet of Things communication refers to a collective network, which connects various devices and technologies and helps the devices communicate with the cloud and with each other. Preferably but not exclusively, the IoT communication is a wired communication, which is connected to the networked cloud computing service device 3 via a wired line. Preferably but not exclusively, the IoT communication is a wireless communication for communicating with the networked cloud computing service device 3 via a wireless connection. The wireless communication transmission includes one selected from the group consisting of a Wi-Fi module, a Bluetooth module, a radio frequency identification module, and a near field communication (NFC) module.

[0016] Notably, in the embodiment, the air pollution is at least one selected from the group consisting of particulate matter, carbon monoxide, carbon dioxide, ozone, sulfur dioxide, nitrogen dioxide, lead, total volatile organic compounds (TVOC), formaldehyde, bacteria, fungi, virus and a combination thereof.

[0017] Certainly, the gas detector 1 monitors the air quality in the space of the indoor field A anytime and anywhere. Moreover, at the same time, the air pollution information in the space of the indoor field A is transmitted to the air pollution big data database of the networked cloud computing service device 3 to intelligently compare the ambient air quality status, and instantly control the air guiding fan 21 arranged in each area to adjust the air volume according to the air quality. The energy-saving

benefits of the operation of the gas molecule control hardware device are effectively controlled.

[0018] In the present disclosure, the specific implementation of the mountable fan filter assembly is understandable, and the structure of the gas detection module of the gas detector 1 of the present disclosure is described in detail below. Please refer to FIG. 3A to FIG. 11. In the embodiment, the gas detection module includes a controlling circuit board 11, a gas detection main part 12, a microprocessor 13 and a communicator 14. The gas detection main part 12, the microprocessor 13 and the communicator 14 are integrally packaged on the controlling circuit board 11 and electrically connected to each other. In the embodiment, the microprocessor 13 and the communicator 14 are mounted on the controlling circuit board 11. The microprocessor 13 controls the driving signal of the gas detection main part 12 for enabling the detection. In this way, the gas detection main part 12 detects the air pollution and outputs the air pollution information, and the microprocessor 13 receives, processes and provides the air pollution information to the communicator 14 for a communication transmission externally, and transmitting to the cloud computing server device 3 through IoT (Internet of Things) communication.

[0019] Please refer to FIG. 4A to FIG. 9A. In the embodiment, the gas detection main part 12 includes a base 121, a piezoelectric actuator 122, a driving circuit board 123, a laser component 124, a particulate sensor 125, and an outer cover 126. In the embodiment, the base 121 includes a first surface 1211, a second surface 1212, a laser loading region 1213, a gas-inlet groove 1214, a gas-guiding-component loading region 1215 and a gas-outlet groove 1216. The first surface 1211 and the second surface 1212 are two surfaces opposite to each other. In the embodiment, the laser loading region 1213 is hollowed out from the first surface 1211 toward the second surface 1212. The outer cover 126 covers the base 121 and includes a side plate 1261. The side plate 1261 has an inlet opening 1261a and an outlet opening 1261b. The gas-inlet groove 1214 is concavely formed from the second surface 1212 and disposed adjacent to the laser loading region 1213. The gas-inlet groove 1214 includes a gas-inlet 1214a and two lateral walls. The gas-inlet 1214a is in communication with an environment outside the base 121, and is spatially corresponding in position to an inlet opening 1261a of the outer cover 126. Two transparent windows 1214b are opened on the two lateral walls of the gas-inlet groove 1214 and are in communication with the laser loading region 1213. Therefore, the first surface 1211 of the base 121 is covered and attached by the outer cover 126, and the second surface 1212 is covered and attached by the driving circuit board 123, so that an inlet path is defined by the gas-inlet groove 1214. In the embodiment, the gas-guiding-component loading region 1215 mentioned above is concavely formed from the second surface 1212 and in communication with the gas-inlet groove 1214. A ventilation hole 1215a penetrates a bottom surface of the gas-guiding-

component loading region 1215. The gas-guiding-component loading region 1215 includes four positioning protrusions 1215b disposed at four corners of the gas-guiding-component loading region 1215, respectively. In the embodiment, the gas-outlet groove 1216 includes a gas-outlet 1216a, and the gas-outlet 1216a is spatially corresponding to the outlet opening 1261b of the outer cover 126. The gas-outlet groove 1216 includes a first section 1216b and a second section 1216c. The first section 1216b is concavely formed out from the first surface 1211 in a region spatially corresponding to a vertical projection area of the gas-guiding-component loading region 1215. The second section 1216c is hollowed out from the first surface 1211 to the second surface 1212 in a region where the first surface 1211 is extended from the vertical projection area of the gas-guiding-component loading region 1215. The first section 1216b and the second section 1216c are connected to form a stepped structure. Moreover, the first section 1216b of the gas-outlet groove 1216 is in communication with the ventilation hole 1215a of the gas-guiding-component loading region 1215, and the second section 1216c of the gas-outlet groove 1216 is in communication with the gas-outlet 1216a. In that, when first surface 1211 of the base 121 is attached and covered by the outer cover 126 and the second surface 1212 of the base 121 is attached and covered by the driving circuit board 123, the gas-outlet groove 1216 and the driving circuit board 123 collaboratively define an outlet path.

[0020] In the embodiment, the laser component 124 and the particulate sensor 125 are disposed on and electrically connected to the driving circuit board 123 and located within the base 121. In order to clearly describe and illustrate the positions of the laser component 124 and the particulate sensor 125 in the base 121, the driving circuit board 123 is intentionally omitted. The laser component 124 is accommodated in the laser loading region 1213 of the base 121, and the particulate sensor 125 is accommodated in the gas-inlet groove 1214 of the base 121 and is aligned to the laser component 124. In addition, the laser component 124 is spatially corresponding to the transparent window 1214b, therefore, a light beam emitted by the laser component 124 passes through the transparent window 1214b and is irradiated into the gas-inlet groove 1214. A light beam path emitted from the laser component 124 passes through the transparent window 1214b and extends in an orthogonal direction perpendicular to the gas-inlet groove 1214. In the embodiment, a projecting light beam emitted from the laser component 124 passes through the transparent window 1214b and enters the gas-inlet groove 1214 to irradiate the suspended particles contained in the gas passing through the gas-inlet groove 1214. When the suspended particles contained in the gas are irradiated and generate scattered light spots, the scattered light spots are received and calculated by the particulate sensor 125 to obtain the gas detection information.

[0021] In the embodiment, the piezoelectric actuator

122 is accommodated in the square-shaped gas-guiding-component loading region 1215 of the base 121. In addition, the gas-guiding-component loading region 1215 of the base 121 is in fluid communication with the gas-inlet groove 1214. When the piezoelectric actuator 122 is enabled, the gas in the gas-inlet groove 1214 is inhaled by the piezoelectric actuator 122, so that the gas flows into the piezoelectric actuator 122, and is transported into the gas-outlet groove 1216 through the ventilation hole 1215a of the gas-guiding-component loading region 1215. Moreover, the driving circuit board 123 covers the second surface 1212 of the base 121, and the laser component 124 is disposed on the driving circuit board 123, and is electrically connected to the driving circuit board 123. The particulate sensor 125 is also disposed on the driving circuit board 123 and electrically connected to the driving circuit board 123. In that, when the outer cover 126 covers the base 121, the inlet opening 1261a is spatially corresponding to the gas-inlet 1214a of the base 121, and the outlet opening 1261b is spatially corresponding to the gas-outlet 1216a of the base 121.

[0022] In the embodiment, the piezoelectric actuator 122 includes a gas-injection plate 1221, a chamber frame 1222, an actuator element 1223, an insulation frame 1224 and a conductive frame 1225. In the embodiment, the gas-injection plate 1221 is made by a flexible material and includes a suspension plate 1221a and a hollow aperture 1221b. The suspension plate 1221a is a sheet structure and is permitted to undergo a bending deformation. Preferably but not exclusively, the shape and the size of the suspension plate 1221a are accommodated in the inner edge of the gas-guiding-component loading region 1215, but not limited thereto. The hollow aperture 1221b passes through a center of the suspension plate 1221a, so as to allow the gas to flow therethrough. Preferably but not exclusively, in the embodiment, the shape of the suspension plate 1221a is selected from the group consisting of a square, a circle, an ellipse, a triangle and a polygon, but not limited thereto.

[0023] In the embodiment, the chamber frame 1222 is carried and stacked on the gas-injection plate 1221. In addition, the shape of the chamber frame 1222 is corresponding to the gas-injection plate 1221. The actuator element 1223 is carried and stacked on the chamber frame 1222. A resonance chamber 1226 is collaboratively defined by the actuator element 1223, the chamber frame 1222 and the suspension plate 1221a and is formed between the actuator element 1223, the chamber frame 1222 and the suspension plate 1221a. The insulation frame 1224 is carried and stacked on the actuator element 1223 and the appearance of the insulation frame 1224 is similar to that of the chamber frame 1222. The conductive frame 1225 is carried and stacked on the insulation frame 1224, and the appearance of the conductive frame 1225 is similar to that of the insulation frame 1224. In addition, the conductive frame 1225 includes a conducting pin 1225a and a conducting elec-

trode 1225b. The conducting pin 1225a is extended outwardly from an outer edge of the conductive frame 1225, and the conducting electrode 1225b is extended inwardly from an inner edge of the conductive frame 1225. Moreover, the actuator element 1223 further includes a piezoelectric carrying plate 1223a, an adjusting resonance plate 1223b and a piezoelectric plate 1223c. The piezoelectric carrying plate 1223a is carried and stacked on the chamber frame 1222. The adjusting resonance plate 1223b is carried and stacked on the piezoelectric carrying plate 1223a. The piezoelectric plate 1223c is carried and stacked on the adjusting resonance plate 1223b. The adjusting resonance plate 1223b and the piezoelectric plate 1223c are accommodated in the insulation frame 1224. The conducting electrode 1225b of the conductive frame 1225 is electrically connected to the piezoelectric plate 1223c. In the embodiment, the piezoelectric carrying plate 1223a and the adjusting resonance plate 1223b are made by a conductive material. The piezoelectric carrying plate 1223a includes a piezoelectric pin 1223d. The piezoelectric pin 1223d and the conducting pin 1225a are electrically connected to a driving circuit (not shown) of the driving circuit board 123, so as to receive a driving signal, such as a driving frequency and a driving voltage. Through this structure, a circuit is formed by the piezoelectric pin 1223d, the piezoelectric carrying plate 1223a, the adjusting resonance plate 1223b, the piezoelectric plate 1223c, the conducting electrode 1225b, the conductive frame 1225 and the conducting pin 1225a for transmitting the driving signal. Moreover, the insulation frame 1224 is insulated between the conductive frame 1225 and the actuator element 1223, so as to avoid the occurrence of a short circuit. Thereby, the driving signal is transmitted to the piezoelectric plate 1223c. After receiving the driving signal such as the driving frequency and the driving voltage, the piezoelectric plate 1223c deforms due to the piezoelectric effect, and the piezoelectric carrying plate 1223a and the adjusting resonance plate 1223b are further driven to generate the bending deformation in the reciprocating manner.

[0024] Furthermore, in the embodiment, the adjusting resonance plate 1223b is located between the piezoelectric plate 1223c and the piezoelectric carrying plate 1223a and served as a cushion between the piezoelectric plate 1223c and the piezoelectric carrying plate 1223a. Thereby, the vibration frequency of the piezoelectric carrying plate 1223a is adjustable. Basically, the thickness of the adjusting resonance plate 1223b is greater than the thickness of the piezoelectric carrying plate 1223a, and the vibration frequency of the actuator element 1223 can be adjusted by adjusting the thickness of the adjusting resonance plate 1223b.

[0025] Please further refer to FIG. 7A, FIG. 7B, FIG. 8A, FIG. 8B and FIG. 9A. In the embodiment, the gas-injection plate 1221, the chamber frame 1222, the actuator element 1223, the insulation frame 1224 and the conductive frame 1225 are stacked and positioned in the

gas-guiding-component loading region 1215 sequentially, so that the piezoelectric actuator 122 is supported and positioned in the gas-guiding-component loading region 1215. A plurality of clearances 1221c are defined between the suspension plate 1221a of the gas-injection plate 1221 and an inner edge of the gas-guiding-component loading region 1215 for gas flowing therethrough. In the embodiment, a flowing chamber 1227 is formed between the gas-injection plate 1221 and the bottom surface of the gas-guiding-component loading region 1215. The flowing chamber 1227 is in communication with the resonance chamber 1226 between the actuator element 1223, the chamber frame 1222 and the suspension plate 1221a through the hollow aperture 1221b of the gas-injection plate 1221. By controlling the vibration frequency of the gas in the resonance chamber 1226 to be close to the vibration frequency of the suspension plate 1221a, the Helmholtz resonance effect is generated between the resonance chamber 1226 and the suspension plate 1221a, so as to improve the efficiency of gas transportation. When the piezoelectric plate 1223c is moved away from the bottom surface of the gas-guiding-component loading region 1215, the suspension plate 1221a of the gas-injection plate 1221 is driven to move away from the bottom surface of the gas-guiding-component loading region 1215 by the piezoelectric plate 1223c. In that, the volume of the flowing chamber 1227 is expanded rapidly, the internal pressure of the flowing chamber 1227 is decreased to form a negative pressure, and the gas outside the piezoelectric actuator 122 is inhaled through the clearances 1221c and enters the resonance chamber 1226 through the hollow aperture 1221b. Consequently, the pressure in the resonance chamber 1226 is increased to generate a pressure gradient. When the suspension plate 1221a of the gas-injection plate 1221 is driven by the piezoelectric plate 1223c to move toward the bottom surface of the gas-guiding-component loading region 1215, the gas in the resonance chamber 1226 is discharged out rapidly through the hollow aperture 1221b, and the gas in the flowing chamber 1227 is compressed, thereby the converged gas is quickly and massively ejected out of the flowing chamber 1227 under the condition close to an ideal gas state of the Benulli's law, and transported to the ventilation hole 1215a of the gas-guiding-component loading region 1215.

[0026] By repeating the above operation steps shown in FIG. 9B and FIG. 9C, the piezoelectric plate 1223c is driven to generate the bending deformation in a reciprocating manner. According to the principle of inertia, since the gas pressure inside the resonance chamber 1226 is lower than the equilibrium gas pressure after the converged gas is ejected out, the gas is introduced into the resonance chamber 1226 again. Moreover, the vibration frequency of the gas in the resonance chamber 1226 is controlled to be close to the vibration frequency of the piezoelectric plate 1223c, so as to generate the Helmholtz resonance effect to achieve the gas transportation

at high speed and in large quantities. The gas is inhaled through the gas-inlet 1214a on the outer cover 126, flows into the gas-inlet groove 1214 of the base 121 through the gas-inlet 1214a, and is transported to the position of the particulate sensor 125. The piezoelectric actuator 122 is enabled continuously to inhale the gas into the inlet path, and facilitate the gas outside the gas detection module to be introduced rapidly, flow stably, and transported above the particulate sensor 125. At this time, a projecting light beam emitted from the laser component 124 passes through the transparent window 1214b to irritate the suspended particles contained in the gas flowing above the particulate sensor 125 in the gas-inlet groove 1214. When the suspended particles contained in the gas are irradiated and generate scattered light spots, the scattered light spots are received and calculated by the particulate sensor 125 for obtaining related information about the sizes and the concentration of the suspended particles contained in the gas. Moreover, the gas above the particulate sensor 125 is continuously driven and transported by the piezoelectric actuator 122, flows into the ventilation hole 1215a of the gas-guiding-component loading region 1215, and is transported to the gas-outlet groove 1216. At last, after the gas flows into the gas outlet groove 1216, the gas is continuously transported into the gas-outlet groove 1216 by the piezoelectric actuator 122, and thus the gas in the gas-outlet groove 1216 is pushed to discharge through the gas-outlet 1216a and the outlet opening 1261b.

[0027] The gas detector 1 of the present disclosure not only can detect the particulate matters in the gas, but also can detect the gas characteristics of the introduced gas, for example, to determine whether the gas is formaldehyde, ammonia, carbon monoxide, carbon dioxide, oxygen, ozone, or the like. Therefore, in one or some embodiments, the gas detector 1 of the present disclosure further includes a gas sensor 127 positioned and disposed on the driving circuit board 123, electrically connected to the driving circuit board 123, and accommodated in the gas-outlet groove 1216, so as to detect the air pollution introduced into the gas-outlet groove 1216. Preferably but not exclusively, in an embodiment, the gas sensor 127 includes a volatile-organic-compound sensor for detecting the information of carbon dioxide (CO₂) or volatile organic compounds (TVOC). Preferably but not exclusively, in an embodiment, the gas sensor 127 includes a formaldehyde sensor for detecting the information of formaldehyde (HCHO) gas. Preferably but not exclusively, in an embodiment, the gas sensor 127 includes a bacteria sensor for detecting the information of bacteria or fungi. Preferably but not exclusively, in an embodiment, the gas sensor 127 includes a virus sensor for detecting the information of virus in the gas. Preferably but not exclusively, the gas sensor 127 is a temperature and humidity sensor for detecting the temperature and humidity information of the gas.

[0028] Please refer to FIG. 2. In the embodiment, the air guiding fan 21 of the mountable fan filter assembly is

controlled to start and guide the air pollution to pass through the filter component 22 for filtration. Preferably but not exclusively, the filter component 22 is a filter with a grade of minimum filtration efficiency value (MREV) 8 or above, or a filter with high-efficiency particulate air (HEPA) grade, which is configured to absorb the chemical smoke, the bacteria, the dust particles and the pollen contained in the air pollution, so that the air pollution introduced into the filter component 22 is filtered and purified to achieve the effect of filtering and purification. Notably, in the present disclosure, the filter with the high efficiency particulate air (HEPA) grade is of 10 or above, and has a dust holding capacity greater than 12,000 mg. In an embodiment, the filter component 22 of the present disclosure is further combined with physical or chemical materials to provide a sterilization effect on the air pollution, and the airflow of the air guiding fan 21 flows in the path indicated by the arrow. In an embodiment, the filter component 22 includes a decomposition layer coated thereon to sterilize in chemical means. Preferably but not exclusively, the decomposition layer includes an activated carbon 22a configured to remove organic and inorganic substances in air pollution, and remove colored and odorous substances. Preferably but not exclusively, the activated carbon has a formaldehyde absorption capacity greater than 1,500 mg. In an embodiment, the decomposition layer includes a cleansing factor containing chlorine dioxide layer 22b configured to inhibit viruses, bacteria, fungi, influenza A, influenza B, enterovirus and norovirus in the air pollution, and the inhibition ratio can reach 99% and more, thereby reducing the cross-infection of viruses. In an embodiment, the decomposition layer includes an herbal protective layer 22c extracted from ginkgo and Japanese Rhus chinensis configured to resist allergy effectively and destroy a surface protein of influenza virus (such as H1N1 influenza virus) passing therethrough. In an embodiment, the decomposition layer includes a silver ion 22d configured to inhibit viruses, bacteria and fungi contained in the air pollution. In an embodiment, the decomposition layer includes a zeolite 22e configured to remove ammonia nitrogen, heavy metals, organic pollutants, Escherichia coli, phenol, chloroform and anionic surfactants. Furthermore, in some embodiments, the filter component 22 is combined with a light irradiation element to sterilize in chemical means. Preferably but not exclusively, the light irradiation element is a photo-catalyst unit including a photo catalyst 22f and an ultraviolet lamp 22g. When the photo catalyst 22f is irradiated by the ultraviolet lamp 22g, the light energy is converted into the chemical energy, thereby decomposes harmful gases and disinfects bacteria contained in the air pollution, so as to achieve the effects of filtering and purifying. Notably, the power of the ultraviolet lamp 22g in the present disclosure is more than 120 mw. In an embodiment, the light irradiation element is a photo-plasma unit including a nanometer irradiation tube 22h. When the introduced air pollution is irradiated by the nanometer irradiation tube 22h, the oxygen mo-

lecules and water molecules contained in the air pollution are decomposed into high oxidizing photo-plasma, and an ion flow capable of destroying organic molecules is generated. In that, volatile formaldehyde, volatile toluene and volatile organic compounds (VOC) contained in the air pollution are decomposed into water and carbon dioxide, so as to achieve the effects of filtering and purifying. Moreover, in some embodiments, the filter component 22 is combined with a decomposition unit to sterilize in chemical means. Preferably but not exclusively, the decomposition unit is a negative ion unit 22i with a dust collecting plate. It makes the suspended particles in the air pollution to carry with positive charge and adhered to the dust collecting plate carry with negative charges, so as to achieve the effects of filtering and purifying. Preferably but not exclusively, the decomposition unit is a plasma ion unit 22j. The oxygen molecules and water molecules contained in the air pollution are decomposed into positive hydrogen ions (H^+) and negative oxygen ions (O^{2-}) by the plasma ion. The substances attached with water around the ions are adhered on the surface of viruses and bacteria and converted into OH radicals with extremely strong oxidizing power, thereby removing hydrogen (H) from the protein on the surface of viruses and bacteria, and thus decomposing (oxidizing) the protein, so as to filter the introduced air pollution and achieve the effects of filtering and purifying.

[0029] In summary, the present disclosure provides a mountable fan filter assembly for implementing air pollution detection and complete purification in the space of an indoor field. The mountable fan filter assembly is equipped with at least one gas detector, at least one air guiding fan, at least one filter component, a driving controller and a flow guiding pathway which is design without piping. Moreover, the flow guiding pathway is fluidly communicated with a circulating return air port and a filter duct, the circulating return air port and filter duct are fluidly communicated with the indoor field, and the at least one air guiding fan and the at least one filter component are arranged under the filter duct. The gas detector is electrically connected to the driving controller and connected to a networked cloud computing service device of the indoor air cleaning network mechanism to form an intelligent linkage system. At this time, the gas detector receives a control instruction from the networked cloud computing service device of the indoor air cleaning network mechanism through an Internet of Things communication, and controls actuation operation of the air guiding fan, so that air in the indoor field is introduced through the circulating return air port and passed the flow guiding pathway into the filter duct. In that, air pollution is filtered and purified through the at least one filter component under the filter duct, and the filtered air is introduced into the indoor field for multiple cycles, so as to implement circulation filtration and purification treatment in real time, prevent the backflow of the filtered gas effectively, and achieve complete clean room treatment. At the same time, the air pollution in the space

of the indoor field is detected by intelligently comparing the ambient air quality status, and the air guiding fan is instantly controlled to adjust the air flow volume according to the air quality, thereby effectively adjusting the energy-saving efficiency of the operation of the mountable fan filter assembly. Consequently, the air flow volume noise reaches zero specification value, thereby achieving the ultimate environmental protection of balanced energy saving and power saving. The present disclosure includes the industrial applicability and the inventive steps.

Claims

1. A mountable fan filter assembly used in an indoor air cleaning network mechanism, the mountable fan filter assembly **characterized by** comprising:

at least one gas detector (1) arranged in an indoor field (A) for detecting air pollution information and temperature and humidity information of gas; and
a unit main part (2) built-in and suspended in the indoor field (A), and comprising at least one air guiding fan (21), at least one filter component (22), a driving controller (23) and a flow guiding pathway (24), wherein the flow guiding pathway (24) is fluidly communicated with a circulating return air port (24a) and a filter duct (24b), the circulating return air port (24a) and filter duct (24b) are fluidly communicated with the indoor field (A), the flow guiding pathway (24) is horizontally parallel to and separated from the filter duct (24b), wherein the at least one air guiding fan (21) and the at least one filter component (22) are arranged under the filter duct (24b), and the at least one gas detector (1) is electrically connected to the driving controller (23);
wherein the at least one gas detector (1) receives a control instruction and transmits it to the driving controller (23) through an Internet of Things communication, so as to control the driving controller (23) to enable an actuation operation of the at least one air guiding fan (21), so that air in the indoor field (A) is introduced through the circulating return air port (24a) and passed the flow guiding pathway (24) into the filter duct (24b), wherein air pollution is filtered and purified through the at least one filter component (22) under the filter duct (24b), and the filtered air is introduced into the indoor field (A) for multiple cycles, so as to implement circulation filtration and purification treatment in real time, prevent the backflow of the filtered gas effectively, and achieve complete clean room treatment.

2. The mountable fan filter assembly according to claim

- 1, wherein the at least one gas detector (1) transmits the air pollution information and the temperature and humidity information to a networked cloud computing service device (3) of the indoor air cleaning network mechanism through the Internet of Things communication, wherein the networked cloud computing service device (3) receives the air pollution information and the temperature and humidity information of the indoor field and the outdoor field, stores and constructs an air pollution big data database accordingly, intelligently computes and compares according to the air pollution big data database, and intelligently selects to issue the control instruction to the at least one gas detector (1), so as to control the driving controller (23) to enable the actuation operation of the at least one air guiding fan (21).
3. The mountable fan filter assembly according to claim 1, wherein the at least one filter component (22) is a filter with a minimum efficiency reporting value (MREV) of 8 or above.
4. The mountable fan filter assembly according to claim 1, wherein the at least one filter component (22) is a filter with a high efficiency particulate air (HEPA) grade, and the high efficiency particulate air (HEPA) grade is of 10 or above, and has a dust holding capacity greater than 12,000 mg.
5. The mountable fan filter assembly according to claim 1, wherein the at least one filter component (22) is combined with a decomposition layer coated thereon, and the decomposition layer uses chemical means to sterilize the air pollution.
6. The mountable fan filter assembly according to claim 5, wherein the decomposition layer is composed of an activated carbon or a cleansing factor containing chlorine dioxide layer, and the activated carbon has a formaldehyde absorption capacity greater than 1,500 mg.
7. The mountable fan filter assembly according to claim 5, wherein the decomposition layer is composed of an herbal protective layer extracted from ginkgo and Japanese rhus chinensis, a silver ion, or a zeolite.
8. The mountable fan filter assembly according to claim 1, wherein the at least one filter component (22) is combined with a light irradiation element to sterilize in chemical means.
9. The mountable fan filter assembly according to claim 8, wherein the light irradiation element is a photocatalyst unit including a photo catalyst and an ultraviolet lamp, and the power of the ultraviolet lamp is more than 120 mw.
10. The mountable fan filter assembly according to claim 8, wherein the light irradiation element is a photo-plasma unit including a nanometer irradiation tube.
11. The mountable fan filter assembly according to claim 1, wherein the at least one filter component (22) is combined with a decomposition unit to sterilize in chemical means.
12. The mountable fan filter assembly according to claim 11, wherein the decomposition unit is a negative ion unit, or a plasma ion unit.
13. The mountable fan filter assembly according to claim 1, wherein the clean room level of the indoor field is ZAPClean Room 1~12.




FIG. 1A




FIG. 1B




FIG. 2

1



FIG. 3A

1




FIG. 3B




FIG. 3C

12




FIG. 4A

12




FIG. 4B

12




FIG. 4C




FIG. 5A




FIG. 5B




FIG. 6




FIG. 7A




FIG. 7B

122




FIG. 8A


122

FIG. 8B




FIG. 9A




FIG. 9B




FIG. 9C




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 11



EUROPEAN SEARCH REPORT

Application Number

EP 25 18 6252

DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (IPC)
X	CN 105 737 262 B (SHENZHEN THY ENV PROT INC) 26 February 2019 (2019-02-26) * Description of fig. 1; claim 1; figure 1 *	1-12	INV. F24F7/003 F24F8/108 F24F11/00
X	----- CN 117 366 744 A (MICROJET TECHNOLOGY CO LTD) 9 January 2024 (2024-01-09) * paragraphs [0012] - [0015], [0020], [0022]; figure 1A *	1-12	
A	----- CN 116 792 842 A (MICROJET TECHNOLOGY CO LTD) 22 September 2023 (2023-09-22) * paragraphs [0011], [0014], [0018], [0027] - [0035], [0038], [0039]; figure 1B *	1-12	

The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (IPC)
			F24F
Place of search			Examiner
Munich			Degen, Marcello
Date of completion of the search			
19 November 2025			
CATEGORY OF CITED DOCUMENTS			
X : particularly relevant if taken alone			
Y : particularly relevant if combined with another document of the same category			
A : technological background			
O : non-written disclosure			
P : intermediate document			
T : theory or principle underlying the invention			
E : earlier patent document, but published on, or after the filing date			
D : document cited in the application			
L : document cited for other reasons			
& : member of the same patent family, corresponding document			

EPO FORM 1503 03.82 (P34C01)

ANNEX TO THE EUROPEAN SEARCH REPORT ON EUROPEAN PATENT APPLICATION NO.

EP 25 18 6252

5

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-11-2025

10

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
CN 105737262 B	26-02-2019	NONE	

CN 117366744 A	09-01-2024	CN 117366744 A	09-01-2024
		EP 4299996 A1	03-01-2024
		JP 2024006844 A	17-01-2024
		TW 202403243 A	16-01-2024
		US 2024001278 A1	04-01-2024

CN 116792842 A	22-09-2023	CN 116792842 A	22-09-2023
		TW 202338267 A	01-10-2023
		US 2023304684 A1	28-09-2023

25

30

35

40

45

50

55

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82